




Circular convolution

$$x1(n) = \{0, 1, 2, 3\} \quad x2(n) = \{4, 5, 6, 7\}$$

4, 7, 6, 5




Activate Windows
Go to Settings to activate Windows



Contd...

$$x_2(1-n) = x_2(-n+1)$$

i.e. shift $x_2(-n)$ by 1 sample anticlockwise




Activate Windows
Go to Settings to activate Windows.





You






Activate Windows
Go to Settings to activate Windows.



You




Contd...




You



Contd...



Activate Windows
Go to Settings to activate Windows.



Circular convolution using Matrix method

N-point DFT :

$$X(k) = \sum_{n=0}^{N-1} x(n) e^{-j2\pi \frac{nk}{N}} \quad \text{For } k=0,1,2,\dots,N-1$$

Twiddle factor:

$$W_N = e^{-\frac{j2\pi}{N}}$$

$$X(k) = \sum_{n=0}^{N-1} x(n) W_N^{kn} \quad \text{For } k=0,1,2,\dots,N-1$$

$$W_2^{kn} = \begin{bmatrix} W_2^0 & W_2^0 \\ W_2^0 & W_2^1 \end{bmatrix}$$

$$W_N = e^{-\frac{j2\pi}{N}}$$

$$W_2 = e^{-\frac{j2\pi}{2}}$$


$$W_2 = e^{-j\pi}$$

$$e^{-j\theta} = \cos(\theta) - j\sin(\theta) \dots \dots \dots \text{Euler's Identity}$$

$$W_2^{kn} = \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}$$

$$V_N^{kn} = \begin{matrix} & \begin{matrix} n=0 & n=1 & n=2 & \dots & n=N-1 \end{matrix} \\ \begin{matrix} k=0 \\ k=1 \\ k=2 \\ \vdots \\ k=N-1 \end{matrix} & \begin{bmatrix} W_N^{kn} & W_N^{kn} & W_N^{kn} & \dots & W_N^{kn} \\ W_N^{kn} & W_N^{kn} & W_N^{kn} & \dots & W_N^{kn} \\ W_N^{kn} & W_N^{kn} & W_N^{kn} & \dots & W_N^{kn} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ W_N^{kn} & W_N^{kn} & W_N^{kn} & \dots & W_N^{kn} \end{bmatrix} \end{matrix}$$

Activate Windows
Go to Settings to activate Windows.



Contd...

$$W_4^{in} = \begin{bmatrix} W_4^0 & W_4^0 & W_4^0 & W_4^0 \\ W_4^0 & W_4^1 & W_4^2 & W_4^3 \\ W_4^0 & W_4^2 & W_4^4 & W_4^6 \\ W_4^0 & W_4^3 & W_4^6 & W_4^9 \end{bmatrix}$$

$$W_4^{br} = \begin{bmatrix} 1 & 1 & 1 & 1 \\ 1 & -j & -1 & +j \\ 1 & -1 & 1 & -1 \\ 1 & j & -1 & -j \end{bmatrix}$$

$$X_N = [W_N]x_N$$

$$X_4 = \begin{bmatrix} 1 & 1 & 1 & 1 \\ 1 & -j & -1 & +j \\ 1 & -1 & 1 & -1 \\ 1 & j & -1 & -j \end{bmatrix} \begin{bmatrix} 1 \\ 2 \\ 0 \\ 1 \end{bmatrix}$$

DFT : $X_N = [W_N]x_N$

- Where

$$X_N = \begin{bmatrix} X(0) \\ X(1) \\ X(2) \\ \vdots \\ X(N-1) \end{bmatrix}$$

$$\{4, 1-j, -2, 1+j\}$$

Activate Windows
Go to Settings to activate Windows.



You



$$\begin{bmatrix} X(0) \\ X(1) \\ X(2) \\ X(3) \end{bmatrix} = \begin{bmatrix} 1 & 1 & 1 & 1 \\ 1 & -j & -1 & j \\ 1 & -1 & 1 & -1 \\ 1 & +j & -1 & -j \end{bmatrix} \begin{bmatrix} 1 \\ 2 \\ 2 \\ 3 \end{bmatrix}$$

$n = 1/2$

$K = 1/2$

$$Y(k) = X(k) \cdot H(k)$$

$$Y(k) = (48, -2j, 0, 2j)$$

$$D(n) = \frac{1}{4} \begin{bmatrix} 1 & 1 & 1 & 1 \\ 1 & +j & -1 & -j \\ 1 & -1 & 1 & -1 \\ 1 & -j & -1 & +j \end{bmatrix}$$

Activate Windows
Go to Settings to activate Windows.



You



Computation of DFT(Computational Complexity)

The DFT pair was given as

$$X[k] = \sum_{n=0}^{N-1} x[n] e^{-j[2\pi/N]kn} \quad x[n] = \frac{1}{N} \sum_{k=0}^{N-1} X[k] e^{j[2\pi/N]kn}$$

Baseline for computational complexity:

Each DFT coefficient requires

N complex **multiplications**;

N-1 complex **additions**

All N DFT coefficients require

N² complex **multiplications**;

N(N-1) complex **additions**

Activ



You



$$X(k) = \sum_{n=0}^{N-1} x(n) W_N^{kn} = x(0) W_N^0 + x(1) W_N^0 + x(2) W_N^0 + x(3) W_N^0$$

$$C_1 = 4 - \text{complex m } C_2$$

$$(a+jb) + c + jb \quad 3 \quad (a+jb) (c+jd)$$

$$(a+ic) + j(y) \quad 4) - N^2$$

$$a_1 + j a d + j b c - b d$$

$$4(3) - N(N-1)$$

$$4 \text{ real multi}$$

$$2 \text{ real add}$$

$$4N^2 - \text{Real}$$

$$2N - \text{Real}$$

$$N^2 - N \text{ add}$$

$$(2N - 2N) + 2$$


Activate Windows
Go to Settings to activate Windows.



You



FFT Algorithms



Activate Windows
Go to Settings to activate Windows.

