

Q Algo :-

- 1) For $(n-1)$ iterations repeat these steps (2-4)
- 2) Make $\text{newArr} = \{ \}$.
- 3) For $i = 0$ to $i = n-2$,
add to ~~set~~ newArr , $\text{value} = (\text{arr}[i] + \text{arr}[i+1]) \% 10$;
- 4) Set $\text{arr} = \text{newArr}$
- 5) Return ~~new~~ $\text{arr}[0]$

Code :-

```
int func (vector<int> & arr) {  
    int N = arr.size();  
    for (int s = 0; s < N-1; s++) {  
        set vector<int> newArr;  
        int n = arr.size();  
        for (int i = 0; i < n-1; i++) {  
            newArr.push_back((arr[i] + arr[i+1]) % 10);  
        }  
        arr = newArr;  
    }  
    return arr[0];  
}
```


Name : Sudhaneshu

UID : 23BCS12388

Class : KRG-1-A

Expt-1

classmate

Date _____

Page _____

Algo :-

- 1) For $(n-1)$ iterations repeat these steps (2-4)
- 2) Make $\text{newArr} = \{ \}$.
- 3) For $i = 0$ to $i = n-2$,
add to ~~set~~ newArr , $\text{value} = (\text{arr}[i] + \text{arr}[i+1]) \% 10$;
- 4) Set $\text{arr} = \text{newArr}$
- 5) Return ~~new~~ $\text{arr}[0]$

Code :-

```
int func (vector<int> & arr) {  
    int N = arr.size();  
    for (int s = 0; s < N-1; s++) {  
        vector<int> newArr;  
        int n = arr.size();  
        for (int i = 0; i < n-1; i++) {  
            newArr.push_back((arr[i] + arr[i+1]) % 10);  
        }  
        arr = newArr;  
    }  
    return arr[0];  
}
```