On-Device Indic Voice Cloning and Text-to-Speech Synthesis for Edge Architectures

Mid-Semester Project Report

Submitted in partial fulfillment of the requirements of
CS F377 Design Project

By

Sudhanva B H
ID No. 2024A7PS0085H

Under the supervision of:

Dr. Jabez Christopher

Reshma A.S.



BIRLA INSTITUTE OF TECHNOLOGY AND SCIENCE PILANI, HYDERABAD CAMPUS
October 2026

BIRLA INSTITUTE OF TECHNOLOGY AND SCIENCE PILANI, HYDERABAD CAMPUS

Abstract

B.E. Computer Science

On-Device Indic Voice Cloning and Text-to-Speech Synthesis for Edge Architectures

by Sudhanva B H

On-device zero-shot neural voice cloning enables the localized replication of an unseen human speaker's acoustic timbre and prosody from a brief reference recording (three to five seconds) without model fine-tuning or server communication. This report investigates this capability specifically to empower government school children and visually impaired (blind) students with accessible audio learning in their own classroom teacher's voice. In rural and semi-urban government schools, foundational learners demonstrate significantly higher cognitive engagement, retention, and comfort when educational content is articulated in the familiar, trusted voice of their local teacher rather than an unfamiliar or accent-mismatched synthetic voice. For visually impaired students, who rely entirely on auditory channels for textbook study and concept explanations, hearing lessons in their teacher's voice provides vital pedagogical continuity and confidence.

Despite its societal importance, this educational domain remains largely untapped by commercial speech synthesis, which prioritizes cloud entertainment and Western languages. Deploying voice cloning in government school settings introduces severe operational constraints: classrooms frequently operate in low-connectivity rural zones with zero internet access, rely on low-cost government-procured tablets such as the Lenovo Tab K10 (MediaTek Helio P22T with 4 GB RAM), and have zero budget for cloud API fees. Furthermore, the system must enforce absolute biometric privacy for teachers and children while operating within strict physical memory limits before the Linux kernel's *LowMemoryKiller* terminates user processes.

This report develops an offline, multilingual zero-shot voice cloning pipeline designed for commodity Android hardware. We implement a dual-engine architecture consisting of: (i) an optimized English baseline using a non-autoregressive Zipformer backbone (ZipVoice-Distill, 123M parameters, INT8 quantized to 104 MB) with a 24 kHz Vocos vocoder executed via Sherpa-ONNX; and (ii) an Indic voice cloning engine based on a 22-layer Diffusion Transformer (IndicF5, 335M parameters) adapted from AI4Bharat's 1,417-hour multilingual foundation model. To satisfy edge memory budgets, we apply static INT8 quantization and pre-allocated memory arenas, reducing the IndicF5 DiT from 1.35 GB down to 349 MB and the Vocos vocoder to 22 MB, bounding peak resident memory to 801 MB. We formulate a calibrated on-device syllabic duration model (6.5 mel frames per character) that eliminates grapheme-to-phoneme rule dictionaries, and engineer a native C++ runtime engine for mobile execution. Physical hardware profiling across four ARM device tiers validates process stability without out-of-memory terminations. Finally, we formulate a concrete production roadmap targeting Google LiteRT and hardware neural processing units (Qualcomm QNN HTP and MediaTek NeuroPilot), establishing that high-fidelity multilingual voice cloning can be achieved entirely at the edge to support accessible education.

Acknowledgements

I am grateful to Prof Dr. Jabez Christopher for providing me the opportunity to work under him as a part of the Study Project. I appreciate his invaluable guidance and support throughout the course of the project. His expertise in AI domain and insightful feedback has led to the success of this work. I am filled with gratitude to receive his mentorship which has been essential for my personal and professional development. I would also like to extent my gratitude to Reshma A.S. for her valuable guidance and planning throughout the project.

Contents

Abstract i

Acknowledgements iii

Contents iv

List of Tables vii

List of Figures ix

1 Introduction and Problem Formulation 1
- 1.1 Teacher-Voice Learning in Government Schools and Accessibility for Blind Students 1
  - 1.1.1 Voice Identity, Pedagogical Trust, and Biometric Privacy 2
  - 1.1.2 Evolution of Speech Synthesis Paradigms 2
- 1.2 The Zero-Shot In-Context Voice Cloning Paradigm 3
- 1.3 Rationale for On-Device Edge Execution 4
- 1.4 The Tri-Factor Challenge in Educational Edge Deployment 4
- 1.5 Embedded Hardware Constraints and Operating System Resource Envelopes . . 5
  - 1.5.1 The Linux Kernel LowMemoryKiller (LMK) Paradigm 6
- 1.6 Evaluation Framework for Edge Speech Generative Systems 6
  - 1.6.1 Physical Memory Confinement and Peak RSS 7
  - 1.6.2 Storage Footprint and Package Compressibility 7
  - 1.6.3 Acoustic and Speaker Identity Transfer Fidelity 7
  - 1.6.4 Computational Throughput and RTF 7
  - 1.6.5 The Fixed Overhead Anomaly in Short Utterances 8
- 1.7 Scope and Structural Organization of the Report 8

2 Theoretical Foundations and Comprehensive Literature Survey 10
- 2.1 Taxonomy of Deep Generative Speech Architectures 10
  - 2.1.1 Autoregressive Acoustic Models 10
  - 2.1.2 Variational Autoencoders and Normalizing Flows 11
  - 2.1.3 Score-Based Diffusion Generative Models 11
  - 2.1.4 Continuous Flow Matching Principles 12
- 2.2 Continuous Normalizing Flows and Optimal Transport Flow Matching 12
  - 2.2.1 Conditional Flow Matching (CFM) 12
  - 2.2.2 Optimal Transport (OT) Displacement Interpolant 13
- 2.3 Diffusion Transformers (DiT) and Non-Autoregressive Sequence Modeling 13

2.3.1 Backbone Microarchitecture . . . 13
2.3.2 Rotary Position Embeddings (RoPE) . . . 14
2.3.3 ConvNeXt-V2 Text Representation . . . 14
2.4 In-Context Speech Inpainting and Acoustic Timbre Transfer . . . 14
2.5 Neural Vocoding Paradigms: Transposed Convolutions vs. Fourier Synthesis . . . 15
2.5.1 The HiFi-GAN Paradigm and Edge Bottlenecks . . . 15
2.5.2 Vocos: Fourier Magnitude and Phase Synthesis . . . 15
2.6 Numerical Solvers and Trajectory Dynamics . . . 16
2.6.1 Euler Numerical Integration . . . 16
2.6.2 Sway Sampling Parameterization . . . 16
2.7 Trajectory Straightening and Step Distillation for Edge Efficiency . . . 17
2.7.1 Rectified Flow and Reflow (Liu et al., 2022) . . . 17
2.7.2 FlashSpeech and Consistency Distillation (Zhang et al., 2024) . . . 17
2.8 Indic Linguistic Phonetics and Acoustic Corpora . . . 18
2.8.1 The Akshara Syllabic Structure . . . 18
2.8.2 Acoustic Duration Properties (IndicVoices) . . . 18
2.8.3 IndicF5 and Multilingual Adaptation (AI4Bharat, 2025) . . . 19
2.9 Edge Machine Learning Runtimes: Runtime Comparative Analysis . . . 19
2.9.1 Sherpa-ONNX . . . 20
2.9.2 ONNX Runtime Mobile (C++ / Dart FFI) . . . 20
2.9.3 Google LiteRT (Formerly TensorFlow Lite) . . . 20

3 System Architecture and Algorithmic Formulation 21
3.1 Heterogeneous Dual-Engine Pipeline Architecture . . . 21
3.2 Signal Preprocessing and Acoustic Feature Extraction . . . 22
3.2.1 Standardized Audio Ingestion and Format Transcoding . . . 22
3.2.2 Root-Mean-Square (RMS) Energy Normalization . . . 22
3.2.3 Log-Mel Filterbank Transformation . . . 23
3.3 Indic Akshara Dynamics and Syllabic Duration Modeling . . . 23
3.3.1 The Linguistic Duration Mismatch Problem . . . 23
3.3.2 Mathematical Derivation of the Calibrated Syllabic Model . . . 24
3.4 Conditioning Representation and Sequence Concatenation . . . 24
3.4.1 Multilingual Character Tokenization . . . 25
3.4.2 The Spatial Alignment Constraint (Reference Duration Law) . . . 25
3.5 Continuous Flow Matching Sampling Formulation . . . 26
3.6 Vocos Neural Spectral Decoding via Inverse STFT . . . 26
3.7 Formal Algorithmic Specifications . . . 27
3.8 Comparative Model Architectural Matrix . . . 28

4 Implementation Methodology and Step-by-Step Engineering Iterations 29
4.1 Iterative Engineering Methodology . . . 29
4.2 Iteration 1: English Baseline Implementation via Sherpa-ONNX . . . 29
4.2.1 Objective and Setup . . . 29
4.2.2 Implementation Details . . . 30
4.2.3 Findings and Milestones . . . 30
4.3 Iteration 2: Flutter Mobile Prototype (`voice_clone_proto`) . . . 30
4.3.1 Objective and UI Architecture . . . 30

4.3.2 System Implementation . . . 30
4.3.3 Concurrency and Background Isolate Decoupling . . . 31
4.4 Iteration 3: Empirical Multi-Device Benchmarking and In-Kernel RSS Profiling . 31
4.4.1 Benchmarking Methodology . . . 31
4.4.2 Empirical Hardware Measurements . . . 32
4.4.3 Analysis of Baseline Benchmarks . . . 32
4.5 Iteration 4: IndicF5 Model Adaptation and Desktop PyTorch Verification . . . 33
4.5.1 Objective . . . 33
4.5.2 Model Setup and Adaptation . . . 33
4.5.3 Validation Across Indian Languages . . . 33
4.6 Iteration 5: Syllabic Duration Calibration (Resolving Audio Truncation and Trailing Silence) . . . 33
4.6.1 The Duration Mismatch Issue . . . 33
4.6.2 Root Cause Investigation . . . 34
4.6.3 Resolution: Calibrated 6.5 Mel Frames per Character . . . 34
4.7 Iteration 6: Sequence Alignment and Reference Audio Duration Constraints . . . 34
4.7.1 The Long-Reference Degradation Issue . . . 34
4.7.2 Root Cause Investigation . . . 34
4.7.3 Resolution: Operational Reference Boundary Law . . . 35
4.8 Iteration 7: In-Memory Warm Model Batch Synthesis and Dataset Curation . . . 35
4.8.1 Motivation and Batch Engine . . . 35
4.8.2 System Architecture . . . 35
4.8.3 The Multilingual Dataset (`prompts.json`) . . . 36
4.9 Iteration 8: Unified Voice Studio Suite and Dynamic Catalog Management . . . 36
4.9.1 System Architecture . . . 36
4.9.2 Dynamic Catalog Management (`samples/voices.json`) . . . 36
4.10 Iteration 9: Graph Optimization and INT8 Quantization . . . 37
4.10.1 Objective: Decoupling from the PyTorch Runtime . . . 37
4.10.2 Exported Model Artifacts . . . 37
4.11 Iteration 10: Custom Native C++ Engine and Dart FFI Shared Library . . . 38
4.11.1 Motivation . . . 38
4.11.2 C++ Engine Architecture (`indicf5_engine.cpp`) . . . 38
4.12 Hardware Memory Budget Analysis on 4 GB RAM Platforms . . . 38

5 Strategic Future Architecture: Google LiteRT Implementation and Edge Acceleration Roadmap 40
5.1 Motivation and Architectural Rationale for Transitioning to Google LiteRT . . . 40
5.2 Direct PyTorch Conversion via LiteRT Torch (`litert-torch`) . . . 41
5.2.1 StableHLO Dialect and Operator Fusion . . . 42
5.3 Hardware Acceleration via the CompiledModel API . . . 42
5.3.1 Declarative Accelerator Prioritization . . . 42
5.3.2 Qualcomm AI Engine Direct (QNN) Integration . . . 43
5.3.3 MediaTek NeuroPilot Integration . . . 43
5.4 Zero-Copy Pipelines via Android Hardware Buffers . . . 43
5.5 Trajectory Distillation: 2-Step and 4-Step Sampling . . . 44
5.5.1 Rectified Flow Trajectory Straightening (4-Step Reflow) . . . 44
5.5.2 Consistency Distillation via FlashSpeech (2-Step Synthesis) . . . 44

5.6 Physical Testing and Verification Protocol 44

6 Conclusion and Research Summary **46**
6.1 Summary of Research Accomplishments and Milestones 46
6.2 Key Scientific, Systems, and Societal Contributions 47
6.2.1 Theoretical and Linguistic Contributions 47
6.2.2 Systems and Edge Deployment Contributions 47
6.2.3 Pedagogical and Accessibility Impact in Untapped Domains 47
6.3 Concluding Remarks and Immediate Priorities 48

A Mathematical Derivations and Numerical Proofs **50**
A.1 Derivation of the Optimal Transport Flow Matching Objective 50
A.1.1 Probability Paths and the Continuity Equation 50
A.1.2 Gradient Equivalence of the Loss Objective 51
A.2 Analytical Formulation of the Inverse STFT with Window Overlap-Add 52

B Multilingual Phonetic Evaluation Prompts Dataset **54**
B.1 Dataset Architecture and Stratification Methodology 54
B.2 Telugu Dataset Inventory 54
B.3 Tamil Dataset Inventory 55
B.4 Hindi Dataset Inventory 55

Bibliography **58**

List of Tables

3.1 Comprehensive Architectural Comparison of Speech Synthesis Models 28

4.1 Empirical On-Device Baseline Benchmarks across Physical Android Devices . . . 32
4.2 Physical RAM Budget Comparison on 4 GB Android Edge Hardware 39

5.1 System Architecture Comparison: Custom ONNX Runtime vs. Google LiteRT . 41

B.1 Curated Telugu Evaluation Prompts across Standardized Tiers 55
B.2 Curated Tamil Evaluation Prompts across Standardized Tiers 56
B.3 Curated Hindi Evaluation Prompts across Standardized Tiers 57

List of Figures

Chapter 1

Introduction and Problem Formulation

1.1 Teacher-Voice Learning in Government Schools and Accessibility for Blind Students

In primary and upper-primary government schools across India, millions of children undertake foundational education in regional languages such as Telugu, Tamil, and Hindi. Educational psychology indicates that young learners exhibit significantly higher cognitive engagement, listening comprehension, and emotional comfort when instructional materials are spoken in the familiar, trusted voice of their classroom teacher rather than an unfamiliar or synthetic persona.

For visually impaired (blind) students, the importance of voice is even more profound. Auditory learning serves as their primary sensory medium for textbooks, practice exercises, and conceptual explanations. Hearing lessons delivered in their own teacher's voice provides pedagogical continuity, comfort, and cognitive trust, helping bridge the gap between classroom instruction and independent study.

Despite the clear educational benefits, this domain remains almost completely untapped by contemporary voice cloning technologies:

1. **Commercial Neglect of Public Education**: Commercial voice synthesis platforms primarily focus on Western languages, media dubbing, and commercial entertainment, leaving vernacular public school education and special-needs accessibility largely unaddressed.
2. **Offline Classroom Realities**: Many government schools operate in rural and semi-urban areas with intermittent or nonexistent internet access, making cloud-dependent speech synthesis completely unusable in everyday classrooms.
3. **Hardware Budgets**: State educational programs distribute budget Android tablets (such as the Lenovo Tab K10 with 4 GB RAM) with zero recurring budget for cloud API subscription fees.

4. **Biometric Privacy**: Public schools have a duty of care to ensure that the voiceprints of teachers and children are never transmitted to external third-party servers.

To serve this untapped domain, there is a clear need for an on-device, zero-shot multilingual voice cloning pipeline. A schoolteacher records a single three-to-five second reference clip once onto a classroom tablet; the system can then synthesize textbook chapters, interactive lessons, and audio aids for visually impaired learners in that teacher's authentic voice, completely offline, at zero recurring cost.

1.1.1 Voice Identity, Pedagogical Trust, and Biometric Privacy

A human speech signal jointly conveys linguistic content, speaker identity, prosody, and acoustic environment characteristics within a few seconds of audio. In zero-shot voice cloning, the goal is to synthesize arbitrary new text in the voice of an unseen speaker using only a brief reference recording (three to five seconds), without modifying model parameters or running gradient updates during inference.

While frontier generative speech models achieve high perceptual naturalness, existing deployments operate almost exclusively on cloud servers equipped with high-end GPUs. This status quo presents three major obstacles for government school education:

(i) **Biometric Privacy Exposure**: Transmitting unencrypted speech samples to external servers exposes teachers' voiceprints to data retention, misuse, and spoofing risks.

(ii) **Lack of Regional Language Coverage**: Over one billion people speak Dravidian and Indo-Aryan languages, which are the primary instructional media in state schools. Most commercial edge voice models support only English or Mandarin.

(iii) **Network Dependency**: In rural government classrooms and special education facilities, internet connectivity is often absent, rendering cloud-dependent educational assistants unusable.

1.1.2 Evolution of Speech Synthesis Paradigms

Automated text-to-speech (Text-to-Speech (TTS)) architectures have developed across three major generations:

1. *Formant synthesis* modeled the human vocal tract through systems of acoustic resonators. Although computationally lightweight, the generated audio sounded unnatural and metallic.

2. *Concatenative synthesis* assembled waveforms from multi-hour databases of pre-recorded speech fragments. This approach yielded high segmental naturalness, but required hundreds of megabytes of storage per voice, could not modify prosody dynamically, and required recording an entire dataset to support a new speaker.

3. *Statistical parametric speech synthesis* (SPSS) modeled acoustic features using Hidden Markov Models. While SPSS reduced storage requirements and permitted parametric voice transformations, over-smoothing often produced muffled output.

The introduction of deep neural networks led to end-to-end architectures such as Tacotron 2, FastSpeech, and Variational Inference with adversarial learning for End-to-end Text-to-Speech (VITS) [1], alongside neural vocoders such as WaveNet and High-Fidelity Generative Adversarial Network (HiFi-GAN) [2], which achieved human-like Mean Opinion Scores (Mean Opinion Score (MOS)). Nevertheless, traditional neural pipelines remain ill-suited for mobile deployment: they require minutes of clean audio for speaker adaptation, and their multi-stage architectures generally demand high-power GPUs.

Modern zero-shot in-context voice cloning models address this limitation by conditioning generation directly on short reference clips without gradient updates. This investigation adapts and optimizes that paradigm for on-device deployment across Indian languages.

1.2 The Zero-Shot In-Context Voice Cloning Paradigm

Formally, zero-shot voice cloning denotes the capacity of an acoustic model to synthesize arbitrary target text in the vocal identity, pitch range, and cadence of an unseen speaker, conditioned solely on a brief reference audio prompt (three to five seconds), without parameter fine-tuning.

Let $\mathbf{x}_{\text{ref}} \in \mathbb{R}^{C \times T_{\text{ref}}}$ denote the intermediate acoustic representation (such as a 100-channel log-mel spectrogram) extracted from a reference recording of duration T_{ref}, and let $\mathbf{w}_{\text{ref}} = (w_1^{\text{ref}}, w_2^{\text{ref}}, \ldots, w_N^{\text{ref}})$ denote its linguistic transcript. Given a novel target text sequence $\mathbf{w}_{\text{tgt}} = (w_1^{\text{tgt}}, w_2^{\text{tgt}}, \ldots, w_{N_{\text{tgt}}}^{\text{tgt}})$, zero-shot speech synthesis models the conditional distribution:

$$p(\mathbf{x}_{\text{tgt}} \mid \mathbf{w}_{\text{tgt}}, \mathbf{x}_{\text{ref}}, \mathbf{w}_{\text{ref}}; \theta) \tag{1.1}$$

such that the synthesized target mel-spectrogram $\mathbf{x}_{\text{tgt}} \in \mathbb{R}^{C \times T_{\text{tgt}}}$ matches the text sequence $\mathbf{w}_{\text{tgt}}$ while replicating the acoustic identity of $\mathbf{x}_{\text{ref}}$.

Early zero-shot systems relied on speaker encoder networks trained with contrastive objectives (such as the generalized end-to-end loss). These encoders projected variable-length audio into fixed-dimensional speaker embeddings (d-vectors or x-vectors) $\mathbf{e}_{\text{spk}} \in \mathbb{R}^D$, typically with $D \in [256, 512]$. The acoustic model was conditioned on $\mathbf{e}_{\text{spk}}$ via feature concatenation or adaptive instance normalization (AdaIN) layers.

However, global embedding vectors introduce an information bottleneck: a single static vector struggles to preserve fine-grained temporal cues, including prosodic variations, co-articulation patterns, and room reverberation characteristics.

To address this limitation, recent models such as Voicebox [3], Embarrassingly Easy Non-Autoregressive Text-to-Speech (E2 TTS) [4], and F5-TTS [5] frame zero-shot speech synthesis as an audio inpainting problem. Instead of compressing the reference signal into a single vector,

continuous acoustic frames $\mathbf{x}_{\text{ref}}$ are concatenated directly with the target generation trajectory along the time axis. The model uses self-attention and cross-attention mechanisms to learn dependencies between the reference acoustics and the target phonetic sequence, harmonizing speaker timbre across the transition boundary.

1.3 Rationale for On-Device Edge Execution: Privacy, Connectivity, and Operational Costs in Public Education

Although cloud-based voice cloning systems achieve strong fidelity on server GPUs, relying on remote infrastructure introduces three critical obstacles for public education:

1. **Biometric Data Privacy and Teacher Protection**: A human voice recording is an immutable biometric identifier. In public schools, uploading raw audio samples of teachers and students to external commercial servers creates severe privacy and liability risks, including corporate data retention, unauthorized voice harvesting, and unconsented cloning. Performing inference entirely on the classroom edge device guarantees that biometric voice samples never leave local device memory.
2. **Reliable Offline Operation in Vernacular Classrooms**: In many regions of the Indian subcontinent, internet access in government primary and secondary schools remains intermittent or completely absent. In rural classrooms and special education facilities for visually impaired students, continuous network access cannot be assumed. Edge execution ensures deterministic, uninterrupted learning and audio study aid generation in complete airplane mode.
3. **Elimination of Cloud Infrastructure and Per-Character Costs**: Commercial speech synthesis APIs incur recurring per-minute and per-character fees driven by GPU server maintenance. Public schools and state education departments operate under strict budgetary boundaries with zero recurring budget for cloud subscriptions. Running models directly on subsidized student tablets eliminates external infrastructure costs entirely, enabling unlimited personalized educational audio generation at zero marginal cost.

1.4 The Tri-Factor Challenge in Educational Edge Deployment

Deploying continuous flow-matching models on budget mobile hardware in government classrooms exposes a multi-constraint optimization problem, which we designate as the Tri-Factor Challenge:

1. **Native Indic and Dravidian Phonological Support for State Curricula**: Over 1.4 billion people speak Dravidian and Indo-Aryan languages, which form the primary instructional medium in state board curricula (such as Telugu, Tamil, and Hindi). These

languages feature distinct phonetic inventories, agglutinative morphology, syllabic akshara scripts, consonant conjuncts (*samyuktaksharas*), and dependent vowel signs (*matras*). Western and Chinese zero-shot models (e.g., Kokoro-82M, standard F5-TTS, or ZipVoice-Distill) lack Indic character vocabularies and phonetic coverage, making them incapable of synthesizing Indian school textbooks.

2. **Zero-Shot In-Context Generalization from Brief Classroom Samples**: The system must adapt to an unseen teacher from a single, three-to-five second recording captured in an ordinary classroom environment, without gradient updates or fine-tuning. Autoregressive models (e.g., XTTS-v2 at 467M parameters [6]) suffer from $O(T)$ sequential latency, quadratic attention memory, and hallucination loops. Non-autoregressive flow-matching models generate frames in parallel, but require low-step numerical solvers to remain feasible on mobile hardware.

3. **Strict Physical Edge Memory and Compute Budgets on Subsidized Tablets**: The pipeline must run entirely on-device without cloud connectivity. Commodity edge devices distributed in state education programs have limited RAM, bounded memory bandwidth, thermal constraints, and heterogeneous CPU clusters without dedicated NPUs.

Existing open-source and commercial models typically address at most two of these requirements: models that run on-device are limited to English and Chinese; models that support Indian languages rely on remote server clusters; and lightweight on-device engines are restricted to single-speaker statistical synthesis. This investigation targets the intersection of all three criteria to empower public education and accessibility.

1.5 Embedded Hardware Constraints and Operating System Resource Envelopes

To design an edge architecture capable of practical mass deployment across public schools, our engineering target is anchored against budget commodity hardware rather than flagship silicon. In this project, our primary reference hardware is the **Lenovo Tab K10**, a tablet widely procured and distributed in government school digitization programs across India, with the following specifications:

- **System-on-Chip (System-on-Chip (SoC))**: MediaTek Helio P22T (MT8768T), built on a 12 nm FinFET process.
- **Processor Microarchitecture**: An octa-core ARM Cortex-A53 cluster in a big.LITTLE configuration (4 cores up to 2.3 GHz and 4 efficiency cores up to 1.8 GHz). The Cortex-A53 implements an in-order execution pipeline with dual-issue capabilities, lacking modern out-of-order execution optimizations.

- **Vector Acceleration**: Standard ARMv8-A ARM NEON Advanced SIMD (NEON) 128-bit Single Instruction Multiple Data (Single Instruction Multiple Data (SIMD)) execution units.
- **Neural Processing Hardware**: Zero dedicated NPU or AI accelerator. All deep learning inference operations (matrix multiplications, convolutional projections, and Fourier transformations) execute on the CPU cluster.
- **Physical System Memory**: 3 GB or 4 GB LPDDR4X Random Access Memory (RAM) over a 32-bit dual-channel memory bus with a theoretical peak bandwidth capped at approximately 14.9 GB/s.

1.5.1 The Linux Kernel LowMemoryKiller (LMK) Paradigm

Memory management in Android is governed by the Linux kernel out-of-memory (Low Memory Killer (LMK)) driver. Unlike desktop operating systems (Linux, Windows, macOS) that use disk paging space to absorb memory spikes, Android disables swap-to-flash storage to protect mobile eMMC and UFS storage chips from write-endurance degradation.

Android instead assigns `oom_adj_score` values to processes. Foreground applications receive low scores but must remain within an absolute physical memory ceiling. On a device with 4 GB of physical RAM, the operating system kernel, system services (SurfaceFlinger, SystemUI), background daemons, and radio baseband stacks consume between 2.2 GB and 2.5 GB of resident RAM. Consequently, the user-space foreground process has an available physical Resident Set Size (RSS) budget strictly capped at:

$$\text{RSS}_{\max} \approx 1,500\,\text{MB} \quad \text{to} \quad 1,800\,\text{MB} \tag{1.2}$$

If an executing model allocates tensor activation buffers, dynamic memory arenas, or uncompressed weights that exceed this ceiling, the Linux kernel issues an immediate, uncatchable `SIGKILL` signal.

Standard FP32 models illustrate this risk: the unquantized IndicF5 PyTorch model requires 1.35 GB for model weights alone, and its dynamic activation buffers require an additional 1.2 GB during generation. This pushes process memory beyond 2.5 GB, triggering an immediate SIGKILL termination on a 4 GB Android device. Consequently, integer quantization, graph optimization, and pre-allocated memory arenas are structural requirements for on-device deployment.

1.6 Evaluation Framework for Edge Speech Generative Systems

To evaluate on-device speech synthesis, we define an evaluation framework balancing physical hardware constraints, vocal cloning fidelity, and inference throughput:

1.6.1 Physical Memory Confinement and Peak Resident Set Size (RSS)

The core operational criterion for on-device viability is physical memory confinement. Memory consumption is quantified not by virtual address reservations (`VmSize`), which reflect mapped address space, but by Peak Resident Set Size (`VmRSS`), which measures physical RAM allocated to the process by the kernel memory subsystem. Peak RSS is monitored by polling `/proc/self/status` at the peak of the diffusion integration loop. For edge stability on 4 GB platforms, peak resident memory must remain strictly below 1,000 MB, leaving sufficient headroom for the host application and Android framework services.

1.6.2 Storage Footprint and Package Compressibility

On consumer mobile hardware, application package size directly affects user adoption. Large desktop checkpoints requiring gigabytes of disk space are impractical for distribution. We evaluate models based on their quantized on-disk footprint, targeting ≤ 400 MB for the combined acoustic model and neural vocoder.

1.6.3 Acoustic and Speaker Identity Transfer Fidelity

Voice cloning fidelity is evaluated along two complementary dimensions:

- **Speaker Similarity and Naturalness**: Measured through Mean Opinion Scores (MOS) on a 5-point Likert scale, assessing how faithfully the synthesized audio replicates the timbre, pitch contour, and perceived identity of the reference speaker.
- **Acoustic Spectral Distortion**: Measured via Mel-Cepstral Distortion (Mel-Cepstral Distortion (MCD)) between ground-truth and synthesized acoustic trajectories:

$$\text{MCD} = \frac{10\sqrt{2}}{\ln 10} \frac{1}{T} \sum_{t=1}^{T} \sqrt{\sum_{d=1}^{D} (c_t[d] - \hat{c}_t[d])^2} \tag{1.3}$$

  where $c_t[d]$ and $\hat{c}_t[d]$ denote the d-th mel-frequency cepstral coefficients of target and synthesized frames.

1.6.4 Computational Throughput and Real-Time Factor (Real-Time Factor (RTF))

Operational throughput is quantified via the RTF, defined as the ratio between the total wall-clock computational latency required to synthesize the audio and the physical duration of the resulting synthesized speech waveform:

$$\text{RTF} = \frac{T_{\text{synthesis}}}{T_{\text{audio}}} = \frac{\Delta t_{\text{proc}}}{\frac{N_{\text{samples}}}{f_s}} \tag{1.4}$$

where Δt_{proc} represents execution time in seconds, N_{samples} denotes synthesized audio samples, and f_s represents the acoustic sampling frequency (24,000 Hz).

In edge environments lacking discrete GPUs, the immediate goal is to establish stable, deterministic execution latencies on mobile ARM CPUs, providing an empirical baseline for future NPU acceleration.

1.6.5 The Fixed Overhead Anomaly in Short Utterances

In iterative flow-matching systems, empirical latency characterization reveals an effect we term the Fixed Overhead Anomaly. In traditional autoregressive systems, computational latency scales linearly with output sequence length ($O(T)$). However, in non-autoregressive continuous flow matching on edge hardware, total synthesis latency decomposes into fixed initialization overhead and length-dependent numerical solving:

$$T_{\text{synthesis}} = T_{\text{init}} + N_{\text{steps}} \cdot T_{\text{forward}}(T_{\text{audio}}) + T_{\text{vocoder}}(T_{\text{audio}}) \tag{1.5}$$

Here, T_{init} encompasses tokenization, vocabulary lookup, text embedding projections, runtime memory arena configuration, and vocoder setup. On mobile ARM hardware, T_{init} represents an invariant baseline cost of approximately 1.0 to 1.5 seconds.

Consequently, when synthesizing a short sentence (e.g., a five-word utterance yielding $T_{\text{audio}} \approx 1.2\,\text{seconds}$), the invariant overhead T_{init} dominates the numerator of Equation 1.4, producing an elevated RTF (e.g., RTF $\in [3.8, 9.3]$). As target audio duration increases to medium ($T_{\text{audio}} \approx 5.5\,\text{s}$) and long ($T_{\text{audio}} \approx 15.0\,\text{s}$) sequences, T_{init} amortizes over the larger denominator, allowing the measured RTF to decrease toward the model's steady-state forward-pass throughput on physical ARM cores.

1.7 Scope and Structural Organization of the Report

This mid-semester technical report documents the theoretical foundations, iterative engineering milestones, hardware profiling results, and production roadmaps developed for on-device voice cloning. The remainder of this document is organized as follows:

- **Chapter 2 (Theoretical Foundations and Comprehensive Literature Survey)** provides a mathematical review of Continuous Normalizing Flows (Continuous Normalizing Flow (CNF)), Optimal Transport Flow Matching (Continuous Flow Matching (CFM)), Diffusion Transformers (Diffusion Transformer (DiT)), neural vocoders (comparing HiFi-GAN and Vocos), trajectory straightening via Rectified Flow, step distillation via FlashSpeech, Dravidian/Indic phonology, and edge machine learning runtimes.

- **Chapter 3 (System Architecture and Algorithmic Formulation)** details the design of the dual-engine edge voice cloning framework, the signal conditioning pipeline, the calibration of our syllabic akshara duration model, the Euler Ordinary Differential Equation (ODE) numerical solver, and formal algorithmic specifications.
- **Chapter 4 (Implementation Methodology and Step-by-Step Engineering Iterations)** chronicles the ten engineering iterations executed during the project, detailing the empirical baselines, the resolution of duration truncation and spatial alignment anomalies, integer quantization pipelines, and native C++ execution on mobile hardware.
- **Chapter 5 (Strategic Future Architecture: Google LiteRT Implementation and Edge Acceleration Roadmap)** establishes the technical blueprint for migrating the IndicF5 pipeline to Google LiteRT, outlining the `litert-torch` conversion flow, hardware accelerator targeting via the `CompiledModel` API (Qualcomm QNN HTP and MediaTek NeuroPilot), zero-copy buffer sharing, and 2-step distillation for mobile efficiency.
- **Chapter 6 (Conclusion and Research Summary)** summarizes the engineering accomplishments and outlines immediate next steps.
- **Appendices** provide formal mathematical derivations and an inventory of the curated multilingual conversational dataset.

Chapter 2

Theoretical Foundations and Comprehensive Literature Survey

2.1 Taxonomy of Deep Generative Speech Architectures

Neural generative speech synthesis models the probability distribution of acoustic representations conditioned on linguistic text and speaker descriptors. Modern deep generative paradigms partition into four foundational mathematical families:

2.1.1 Autoregressive Acoustic Models

Autoregressive (Autoregressive (AR)) architectures formulate speech generation as a sequential next-token prediction task. Representing the acoustic feature sequence as $\mathbf{X} = (\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_T)$, the joint probability is factored via the chain rule of probability:

$$p(\mathbf{X} \mid \mathbf{W}) = \prod_{t=1}^{T} p(\mathbf{x}_t \mid \mathbf{x}_{<t}, \mathbf{W}; \theta) \tag{2.1}$$

where $\mathbf{x}_{<t} = (\mathbf{x}_1, \ldots, \mathbf{x}_{t-1})$ represents the historical acoustic context and $\mathbf{W}$ denotes the conditioning text sequence. Architectures such as Tacotron, AudioLM, and XTTS-v2 [6] leverage causal multi-head self-attention mechanisms [7] to parameterize each conditional step.

While autoregressive models capture expressive prosody effectively, they present practical computational bottlenecks for edge devices:

(a) **Inference Complexity** $O(T)$: Generating T acoustic frames strictly requires T sequential forward passes through the network. On a mobile CPU, where each forward pass consumes 15–30 ms, generating a 10-second utterance ($T \approx 937$ frames) demands over 15 to 25 seconds of compute (RTF > 2.0).

(b) **Exposure Bias and Compounding Errors**: Because the model is trained with teacher-forcing but tested with its own predictions, small deviations at step t compound recursively over time, sometimes resulting in phoneme deletions, unnatural pitch inflections, or repetition loops.

(c) **KV-Cache Memory Overhead**: Retaining historical key-value tensors across deep transformer stacks inflates RAM usage linearly with sequence length, increasing LMK termination risks on 4 GB Android devices.

2.1.2 Variational Autoencoders and Normalizing Flows

Conditional Variational Autoencoders (Variational Autoencoders (VAEs)) and finite normalizing flows (such as VITS [1]) model speech by maximizing the variational evidence lower bound (Evidence Lower Bound (ELBO)). By employing continuous normalizing flows parameterized by affine coupling layers, VITS establishes invertible bijective mappings between a standard Gaussian prior and the target mel distribution. While VITS achieves non-autoregressive parallel synthesis ($O(1)$ forward passes) with fast execution speeds, its mathematical structure relies on Monotonic Alignment Search (MAS) and dynamic programming alignment paths. These aligners degrade in zero-shot cross-lingual transfer, as the internal phonetic duration predictors cannot accommodate unseen multilingual scripts without dedicated acoustic phoneme dictionaries.

2.1.3 Score-Based Diffusion Generative Models

Denoising Diffusion Probabilistic Models (Denoising Diffusion Probabilistic Models (DDPM)) [8] and continuous score-based generative models [9] synthesize data by reversing a progressive forward noising process. Formally, a forward Stochastic Differential Equation (SDE) corrupts the data distribution $p_{\text{data}}(\mathbf{x})$ into an isotropic Gaussian distribution $\mathcal{N}(\mathbf{0}, \mathbf{I})$ via an Itô stochastic differential equation:

$$d\mathbf{x} = \mathbf{f}(\mathbf{x}, t)dt + g(t)d\mathbf{w} \tag{2.2}$$

where $\mathbf{w}$ is standard Brownian motion. Generation is achieved by solving the reverse-time SDE:

$$d\mathbf{x} = \left[\mathbf{f}(\mathbf{x}, t) - g(t)^2 \nabla_{\mathbf{x}} \log p_t(\mathbf{x})\right] dt + g(t)d\bar{\mathbf{w}} \tag{2.3}$$

where $\nabla_{\mathbf{x}} \log p_t(\mathbf{x})$ is the score function, approximated by a deep neural network $\mathbf{s}_\theta(\mathbf{x}, t)$.

Although diffusion models generate high-quality audio, their stochastic trajectories are inherently curved. Simulating stochastic differential equations requires numerical solvers across 50 to 1,000 sampling steps. Even accelerated diffusion solvers (such as DPM-Solver) require at least 15 to 30 forward evaluations, incurring unviable latency on mobile ARM processors.

2.1.4 Continuous Flow Matching Principles

To avoid the curved trajectories and stochastic overhead of diffusion SDEs, Lipman et al. [10] formulated *Continuous Flow Matching* (CFM). CFM synthesizes data along deterministic probability trajectories governed by ordinary differential equations. By constructing optimal transport displacement interpolants, CFM ensures that trajectories between noise and clean speech follow straight paths, establishing the mathematical foundation for low-step execution on resource-constrained edge architectures.

2.2 Continuous Normalizing Flows and Optimal Transport Flow Matching

Let $\mathbb{R}^d$ denote the data space representing flattened mel-spectrogram tensors. A CNF defines a time-dependent push-forward transformation $\psi_t : \mathbb{R}^d \to \mathbb{R}^d$ for $t \in [0, 1]$, driven by a time-dependent vector field $\mathbf{v}_t : \mathbb{R}^d \to \mathbb{R}^d$ via the initial value problem (ODE):

$$\frac{d}{dt}\psi_t(\mathbf{x}) = \mathbf{v}_t(\psi_t(\mathbf{x})), \quad \psi_0(\mathbf{x}) = \mathbf{x} \tag{2.4}$$

The vector field induces a continuous probability density path $p_t(\mathbf{x})$ satisfying the continuity equation:

$$\frac{\partial p_t(\mathbf{x})}{\partial t} + \nabla \cdot (p_t(\mathbf{x})\mathbf{v}_t(\mathbf{x})) = 0 \tag{2.5}$$

where $p_0(\mathbf{x}) = \mathcal{N}(\mathbf{x}; \mathbf{0}, \mathbf{I})$ represents the tractable standard Gaussian prior, and $p_1(\mathbf{x}) = p_{\text{data}}(\mathbf{x})$ denotes the empirical target speech distribution.

2.2.1 Conditional Flow Matching (CFM)

Directly regressing the marginal vector field $\mathbf{v}_t(\mathbf{x})$ is computationally intractable because the marginal density $p_t(\mathbf{x}) = \int p_t(\mathbf{x} \mid \mathbf{x}_1)q(\mathbf{x}_1)d\mathbf{x}_1$ involves an integral over the entire data manifold. Lipman et al. [10] proved that regressing conditional vector fields $\mathbf{v}_t(\mathbf{x} \mid \mathbf{x}_1)$ conditioned on individual data samples $\mathbf{x}_1$ yields identical parameter gradients:

Theorem 2.1 (Equivalence of CFM and Marginal Objectives [10])**.** *Let $p_t(\mathbf{x} \mid \mathbf{x}_1)$ be a conditional probability path generated by conditional vector field $\mathbf{v}_t(\mathbf{x} \mid \mathbf{x}_1)$. Define the marginal vector field $\mathbf{v}_t(\mathbf{x}) = \int \mathbf{v}_t(\mathbf{x} \mid \mathbf{x}_1)\frac{p_t(\mathbf{x}|\mathbf{x}_1)q(\mathbf{x}_1)}{p_t(\mathbf{x})}d\mathbf{x}_1$. Then the objective:*

$$\mathcal{L}_{CFM}(\theta) = \mathbb{E}_{t\sim U[0,1],\mathbf{x}_1\sim q(\mathbf{x}_1),\mathbf{x}\sim p_t(\mathbf{x}|\mathbf{x}_1)} \left\|\mathbf{v}_\theta(\mathbf{x}, t) - \mathbf{v}_t(\mathbf{x} \mid \mathbf{x}_1)\right\|^2 \tag{2.6}$$

satisfies $\nabla_\theta \mathcal{L}_{CFM}(\theta) = \nabla_\theta \mathcal{L}_{Marginal}(\theta)$.

2.2.2 Optimal Transport (OT) Displacement Interpolant

Among the family of conditional probability paths connecting p_0 to p_1, the *Optimal Transport* path minimizes kinetic energy $\int_0^1 \|\mathbf{v}_t\|^2 dt$. By pairing prior noise samples $\mathbf{x}_0 \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ directly with target mel-spectrograms $\mathbf{x}_1 \sim q(\mathbf{x}_1)$, the optimal transport displacement interpolant is defined as:

$$\psi_t(\mathbf{x}_0) = (1 - (1 - \sigma_{\min})t)\mathbf{x}_0 + t\mathbf{x}_1 \tag{2.7}$$

where $\sigma_{\min} \approx 10^{-5}$ is an infinitesimal stability regularizer. Setting $\sigma_{\min} \to 0$ yields the canonical linear trajectory:

$$\mathbf{x}_t = (1 - t)\mathbf{x}_0 + t\mathbf{x}_1 \tag{2.8}$$

Differentiating Equation 2.8 with respect to time t gives the target conditional velocity:

$$\mathbf{u}_t(\mathbf{x}_t \mid \mathbf{x}_0, \mathbf{x}_1) = \frac{d\mathbf{x}_t}{dt} = \mathbf{x}_1 - \mathbf{x}_0 \tag{2.9}$$

Notably, the target velocity vector is constant with respect to time t. The neural network $v_\theta(\mathbf{x}_t, t, \mathbf{c})$ is trained to predict the displacement vector $(\mathbf{x}_1 - \mathbf{x}_0)$ given the intermediate noisy state $\mathbf{x}_t$, time step t, and conditioning context $\mathbf{c}$:

$$\mathcal{L}_{\text{OT-CFM}}(\theta) = \mathbb{E}_{t,\mathbf{x}_0,\mathbf{x}_1} \|\mathbf{v}_\theta(\mathbf{x}_t, t, \mathbf{c}) - (\mathbf{x}_1 - \mathbf{x}_0)\|_2^2 \tag{2.10}$$

Because the ground-truth trajectory is a straight line, numerical integration during generation does not suffer from stochastic drift, enabling first-order Euler solvers to converge in few steps.

2.3 Diffusion Transformers (DiT) and Non-Autoregressive Sequence Modeling

To parameterize the velocity network $\mathbf{v}_\theta(\mathbf{x}_t, t, \mathbf{c})$, recent architectures have adopted *Diffusion Transformers* (DiT) [5, 11] in place of traditional U-Net convolutional backbones.

2.3.1 Backbone Microarchitecture

In IndicF5, the velocity field estimator is structured as a 22-layer Diffusion Transformer with the following specifications:

- **Transformer Depth**: $L = 22$ identical transformer blocks.
- **Model Hidden Dimension**: $D = 1024$.
- **Attention Multi-Head Configuration**: $H = 16$ attention heads, yielding a per-head dimension of $d_h = \frac{D}{H} = 64$.
- **Feed-Forward Multiplier**: $\text{mult}_{\text{FFN}} = 2$, establishing an intermediate MLP expansion dimension of $D_{\text{FFN}} = 2048$.

- **Total Parameter Footprint**: Approximately 335 million parameters.

2.3.2 Rotary Position Embeddings (RoPE)

Unlike sinusoidal positional encodings that inject absolute coordinates into the input layer, IndicF5 employs *Rotary Position Embeddings* (Rotary Position Embedding (RoPE)) at every self-attention layer. Given a query vector $\mathbf{q}_m$ and key vector $\mathbf{k}_n$ at sequence positions m and n, RoPE applies an orthogonal rotation matrix $\mathbf{R}^d_{\Theta,m}$:

$$\tilde{\mathbf{q}}_m = \mathbf{R}^d_{\Theta,m}\mathbf{q}_m, \quad \tilde{\mathbf{k}}_n = \mathbf{R}^d_{\Theta,n}\mathbf{k}_n \tag{2.11}$$

such that their inner product encodes relative positional displacement:

$$\langle \tilde{\mathbf{q}}_m, \tilde{\mathbf{k}}_n \rangle = \mathbf{q}_m^T \mathbf{R}^d_{\Theta,n-m}\mathbf{k}_n = g(\mathbf{q}_m, \mathbf{k}_n, m-n) \tag{2.12}$$

This property enables the DiT to generalize to variable-length audio sequences during inference without positional coordinate degradation.

2.3.3 ConvNeXt-V2 Text Representation

Text tokens are mapped to a 512-dimensional embedding space. Rather than passing raw embeddings directly to cross-attention layers, IndicF5 processes the character token sequence through four ConvNeXt-V2 convolutional blocks incorporating depthwise convolutions, layer normalization, inverted bottlenecks, and Global Response Normalization (GRN). This extracts hierarchical local phonological representations prior to concatenation with the acoustic mel frames.

2.4 In-Context Speech Inpainting and Acoustic Timbre Transfer

Modern zero-shot voice cloning architectures frame speaker identity transfer as an in-context audio inpainting problem [3, 4].

Let $\mathbf{x}_{\text{ref}} \in \mathbb{R}^{C \times T_{\text{ref}}}$ denote the mel-spectrogram extracted from a reference audio clip, and let $\mathbf{w}_{\text{ref}}$ represent its transcript. The model constructs a composite conditioning tensor along the temporal dimension:

$$\mathbf{x}_{\text{cond}} = \left[\mathbf{x}_{\text{ref}} \,\middle\|\, \mathbf{0}_{C \times T_{\text{tgt}}} \right] \in \mathbb{R}^{C \times (T_{\text{ref}} + T_{\text{tgt}})} \tag{2.13}$$

where $\|$ denotes concatenation along the time axis, and $\mathbf{0}_{C \times T_{\text{tgt}}}$ represents zero-padding across the target generation window.

During training, random spans of audio are masked. The model learns to reconstruct the masked acoustic frames conditioned on the unmasked frames and the complete text sequence $[\mathbf{w}_{\text{ref}} \| \mathbf{w}_{\text{tgt}}]$.

During inference, the reference audio $\mathbf{x}_{\text{ref}}$ is placed in the unmasked prefix region, while the target region is initialized with Gaussian noise $\mathbf{x}_0 \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$. Throughout the numerical ODE integration, the velocity network v_θ reads the acoustic context in the prefix frames via bidirectional self-attention. The model extracts formant structure, glottal excitation timbre, speaking rate, and room acoustics from $\mathbf{x}_{\text{ref}}$, propagating these characteristics into the synthesized target frames $\mathbf{x}_{\text{tgt}}$ without requiring explicit speaker classification losses or static d-vector bottlenecks.

2.5 Neural Vocoding Paradigms: Transposed Convolutions vs. Fourier Synthesis

Once the mel-spectrogram tensor $\mathbf{x}_{\text{tgt}} \in \mathbb{R}^{C \times T_{\text{tgt}}}$ is synthesized by the flow-matching backbone, a neural vocoder reconstructs the continuous time-domain speech waveform $y(t) \in \mathbb{R}^{N_{\text{samples}}}$.

2.5.1 The HiFi-GAN Paradigm and Edge Bottlenecks

HiFi-GAN [2] has served as a widely adopted neural vocoder. It operates entirely in the time domain, employing a multi-receptive field fusion (MRF) module driven by a cascade of transposed convolutions to upsample 100-channel mel frames (hop size 256) to 24 kHz raw audio.

While HiFi-GAN produces high-quality audio, its design presents substantial computational overhead on mobile ARM processors:

1. **Memory Bandwidth Overhead**: Upsampling audio by factors of $8 \times 8 \times 2 \times 2 = 256$ requires repeatedly allocating and writing large intermediate feature buffers, exceeding mobile L1/L2 caches.
2. **Strided Access Patterns**: Multi-branch dilated convolutions induce strided memory access patterns, hindering continuous SIMD vectorization on ARM NEON units.

2.5.2 Vocos: Fourier Magnitude and Phase Synthesis

To avoid the physical bottlenecks of transposed convolutions, Siuzdak [12] developed Vocos. Rather than predicting raw time-domain samples through iterative upsampling, Vocos frames audio generation as complex spectral coefficient prediction.

The Vocos backbone consists of ConvNeXt blocks that operate directly at the mel frame rate without temporal upsampling. The network outputs two spectral heads:

1. **Magnitude Head**: Predicts real-valued magnitude spectra $|\mathbf{X}(f,t)| \in \mathbb{R}^{(N_{\text{fft}}/2+1) \times T}$.
2. **Phase Spectrogram Head**: Predicts unit complex numbers representing spectral phase angles $\phi(f,t) \in [-\pi, \pi]$ via two output channels $(\cos\phi, \sin\phi)$, normalized such that $\cos^2\phi + \sin^2\phi = 1$.

The complex Short-Time Fourier Transform (Short-Time Fourier Transform (STFT)) representation is assembled via:

$$\mathbf{X}(f,t) = |\mathbf{X}(f,t)| \odot (\cos\phi(f,t) + j\sin\phi(f,t)) \tag{2.14}$$

The time-domain audio waveform $y(t)$ is reconstructed analytically via the Inverse Short-Time Fourier Transform (Inverse Short-Time Fourier Transform (iSTFT)):

$$y(n) = \text{iSTFT}(\mathbf{X}(f,t)) = \frac{\sum_m \mathbf{x}_m(n-mH)w(n-mH)}{\sum_m w^2(n-mH)} \tag{2.15}$$

where $H = 256$ is the hop size and $w(n)$ is a Hanning synthesis window.

Because the Fourier inversion (Equation 2.15) is computed using optimized Fast Fourier Transform (SIMD) routines (such as ARM NEON FFT or vDSP), Vocos eliminates transposed convolutions entirely. On mobile ARM CPUs, Vocos runs approximately 10× faster than HiFi-GAN while occupying an INT8 model footprint of 22 MB (13.5M parameters).

2.6 Numerical Solvers and Trajectory Dynamics

During inference, sampling from the velocity field $\mathbf{v}_\theta(\mathbf{x}_t, t, \mathbf{c})$ requires solving the initial value problem:

$$\frac{d\mathbf{x}_t}{dt} = \mathbf{v}_\theta(\mathbf{x}_t, t, \mathbf{c}), \quad \mathbf{x}_0 \sim \mathcal{N}(\mathbf{0}, \mathbf{I}), \quad t \in [0,1] \tag{2.16}$$

2.6.1 Euler Numerical Integration

Discretizing the time domain into N uniform intervals with step size $\Delta t = \frac{1}{N}$, the first-order Euler update step is:

$$\mathbf{x}_{t+\Delta t} = \mathbf{x}_t + \Delta t \cdot \tilde{\mathbf{v}}_\theta(\mathbf{x}_t, t, \mathbf{c}) \tag{2.17}$$

where $\tilde{\mathbf{v}}_\theta$ incorporates Classifier-Free Guidance (Classifier-Free Guidance (CFG)) [13] with guidance weight $\gamma = 2.0$:

$$\tilde{\mathbf{v}}_\theta(\mathbf{x}_t, t, \mathbf{c}) = (1+\gamma)\mathbf{v}_\theta(\mathbf{x}_t, t, \mathbf{c}) - \gamma\mathbf{v}_\theta(\mathbf{x}_t, t, \emptyset) \tag{2.18}$$

Evaluating Equation 2.18 requires two forward passes per ODE step (or batching the conditioned and unconditioned inputs together into a single $[2, C, T]$ forward pass).

2.6.2 Sway Sampling Parameterization

While uniform time steps $t_k = \frac{k}{N}$ are standard, the curvature of the learned vector field is non-uniform across the interval $[0,1]$. Empirical studies indicate that vector field trajectories exhibit

the greatest non-linearity near $t = 0$ (where noise is initially structured into coarse acoustic formants) and near $t = 1$ (where high-frequency harmonic overtones are synthesized).

To optimize solver step distribution, IndicF5 implements Sway Sampling [5] parameterized by coefficient $\rho \in [-1, 1]$:

$$t(s) = s + \rho \cdot s(1 - s)(1 - 2s), \quad s \in [0, 1] \tag{2.19}$$

Setting $\rho = -1.0$ clusters integration steps closer to the boundaries $t = 0$ and $t = 1$. This adjustment allows an 8-step Euler solver to match the acoustic quality of a 16-step or 32-step uniform solver, reducing computational latency by half.

2.7 Trajectory Straightening and Step Distillation for Edge Efficiency

To minimize iterative numerical evaluations, prevent battery depletion, and mitigate processor thermal throttling during edge execution on mobile SoCs, two acceleration methodologies have been proposed in the literature:

2.7.1 Rectified Flow and Reflow (Liu et al., 2022)

While optimal transport continuous flow matching produces straight trajectories in expectation, individual sample trajectories can cross in high-dimensional space, forcing the neural network to learn an average velocity that introduces curvature. Liu et al. [14] proved that this curvature can be systematically eliminated through recursive Reflow:

Definition 2.2 (The Reflow Operation [14])**.** Given a 1-rectified flow model v_{θ_1} trained on empirical pairs $(\mathbf{x}_0, \mathbf{x}_1)$, generate synthetic pairs $(\mathbf{x}_0, \mathbf{z}_1)$ by numerically integrating $\mathbf{x}_0 \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ to $t = 1$ using v_{θ_1}. The 2-rectified flow model v_{θ_2} is trained on these synthetic straight-line pairs:

$$\mathcal{L}_{\text{Reflow}}(\theta_2) = \mathbb{E}_{\mathbf{x}_0, \mathbf{z}_1, t} \left\| \mathbf{v}_{\theta_2}((1 - t)\mathbf{x}_0 + t\mathbf{z}_1, t) - (\mathbf{z}_1 - \mathbf{x}_0) \right\|^2 \tag{2.20}$$

By training on coupled pairs generated by the flow itself, trajectory intersections are untangled. The resulting vector field trajectories become straight lines, permitting numerical integration in as few as 4 Euler steps without perceptual degradation.

2.7.2 FlashSpeech and Consistency Distillation (Zhang et al., 2024)

FlashSpeech [15] applies adversarial consistency distillation to speech flow matching. Rather than stepping through an ODE, a student network is trained to learn a direct mapping $f_\theta(\mathbf{x}_t, t) = \mathbf{x}_1$ enforcing self-consistency:

$$f_\theta(\mathbf{x}_{t_1}, t_1) = f_\theta(\mathbf{x}_{t_2}, t_2) \quad \forall\, t_1, t_2 \in [0, 1] \tag{2.21}$$

This property collapses the multi-step numerical solving loop into one or two forward passes, enabling sub-100 ms voice cloning on embedded hardware.

2.8 Indic Linguistic Phonetics and Acoustic Corpora

Indian languages belong predominantly to two distinct linguistic families: the Dravidian family (Tamil, Telugu, Kannada, Malayalam) and the Indo-Aryan family (Hindi, Marathi, Gujarati, Bengali, Punjabi, Odia, Assamese). Unlike English, which employs a Latin alphabet requiring non-deterministic grapheme-to-phoneme conversion (e.g., the pronunciation difference of "ough" in *through*, *rough*, and *thought*), Indic scripts are strictly phonetic and syllabic.

2.8.1 The Akshara Syllabic Structure

In Indic orthography, the core phonetic unit is the *akshara*. An akshara is an orthographic syllable structured as:

$$\text{Akshara} = C_0^k V \tag{2.22}$$

representing zero or more consonants (C) followed by an inherent vowel (V, typically /a/). Consonants are modified by dependent vowel diacritics (*matras*), vowel suppressors (*viramas* or *halant*), and nasalization marks (*anusvaras*). When multiple consonants combine without intervening vowels, they form composite consonant conjuncts (*samyuktaksharas*).

2.8.2 Acoustic Duration Properties (IndicVoices)

The IndicVoices speech corpus [16] comprises 1,417 hours of verified spontaneous and read speech recorded across 22 Indian languages. Acoustic analysis of this corpus demonstrates that an average Indic akshara possesses an acoustic duration spanning:

$$\Delta t_{\text{akshara}} \approx 150\,\text{ms} \quad \text{to} \quad 220\,\text{ms} \tag{2.23}$$

In digital mel-spectrogram representations utilizing a 24 kHz sampling rate and a hop size of 256 samples, each mel frame spans:

$$\Delta t_{\text{frame}} = \frac{256}{24000} \approx 10.667\,\text{ms} \tag{2.24}$$

Dividing the akshara duration (Equation 2.23) by the frame duration (Equation 2.24) reveals that an Indic character glyph corresponds to an average density of 5.5 to 7.0 mel frames per Unicode character code point. This relationship provides the theoretical basis for our duration model calibrated in Chapter 3.

2.8.3 IndicF5 and Multilingual Adaptation (AI4Bharat, 2025)

IndicF5, formulated by Praveen et al. [17] at AI4Bharat (IIT Madras) in their work *"Phir Hera Fairy: An English Fairytaler is a Strong Faker of Fluent Speech in Low-Resource Indian Languages"*, adapts non-autoregressive continuous flow matching to the multilingual domain of the Indian subcontinent.

The authors evaluated whether an English-pretrained flow-matching checkpoint (F5-TTS [5]) could generalize to phonologically distinct Indian languages, testing three optimization strategies:

1. **Training from Scratch**: Initializing the 22-layer DiT backbone with randomized weights on Indian corpora. This yielded slow phonological convergence and unstable mel trajectories due to data scarcity in low-resource languages.
2. **Joint Multilingual Pre-training**: Fine-tuning simultaneously on paired English and Indic datasets. While stable, this experienced language competition and reduced prosodic expression in regional dialects.
3. **Exclusive Indic Fine-Tuning of the English Prior**: Fine-tuning the pre-trained English F5-TTS checkpoint exclusively on Indic speech data. This strategy achieved the highest naturalness (MOS) and speaker similarity, demonstrating that flow-matching vector fields learned from dense English acoustic priors provide effective inductive biases that transfer across phonetic boundaries without catastrophic forgetting.

Trained on 1,417 hours of multi-speaker speech sourced from IndicVoices-R [16], Rasa, IndicTTS, and LIMMITS across eleven official languages (Assamese, Bengali, Gujarati, Hindi, Kannada, Malayalam, Marathi, Odia, Punjabi, Tamil, and Telugu), IndicF5 demonstrates cross-lingual zero-shot cloning. A reference prompt in one language (such as Kannada or Odia) can guide synthesis in another language (such as Hindi or Tamil) while maintaining vocal timbre, pitch trajectory, and cadence. Furthermore, by defining a unified character tokenizer spanning 187 Unicode glyphs across Indic scripts and Latin characters, the model eliminates external G2P rule tables by learning character-to-acoustic alignments end-to-end.

2.9 Edge Machine Learning Runtimes: Runtime Comparative Analysis

Deploying deep flow-matching models on mobile devices requires an execution engine capable of parsing ONNX or FlatBuffer graphs, executing quantized integer operators, and offloading tensor operations to hardware accelerators. Three primary frameworks exist in the modern mobile ML ecosystem:

2.9.1 Sherpa-ONNX

Developed by the Next-gen Kaldi team [18], `sherpa-onnx` is an embedded C++ speech recognition and synthesis engine with Flutter/Dart bindings. Sherpa-ONNX provides specialized C++ loaders for Zipformer, VITS, and Matcha-TTS architectures. However, Sherpa-ONNX currently lacks native C++ loaders for Diffusion Transformers (DiT) and F5-TTS, preventing direct execution of IndicF5.

2.9.2 ONNX Runtime Mobile (C++ / Dart FFI)

Microsoft's ONNX Runtime Mobile [19] provides a generic C++ execution engine supporting standard ONNX graphs. It includes the XNNPACK execution provider for multi-threaded ARM NEON CPU acceleration and optional NNAPI/QNN delegates. However, executing custom multi-step ODE flow-matching loops requires developing custom C++ wrappers, shared libraries (`.so`), and manual Dart FFI bindings.

2.9.3 Google LiteRT (Formerly TensorFlow Lite)

Google LiteRT [20] is designed for mobile ML deployments, offering:

- Direct PyTorch conversion via `litert-torch` [21], avoiding intermediate ONNX operator translation issues.
- A unified `CompiledModel` API supporting automatic accelerator selection:
  - Qualcomm Hexagon HTP via Qualcomm QNN [22].
  - MediaTek APU via NeuroPilot [23].
  - Multi-core ARM NEON fallback via XNNPACK.
- Zero-copy hardware buffer management (`AHardwareBuffer`), minimizing memory transfers.

The architectural trade-offs across these runtimes are detailed in Chapter 3 and form the core of our future roadmap in Chapter 5.

Chapter 3

System Architecture and Algorithmic Formulation

3.1 Heterogeneous Dual-Engine Pipeline Architecture

To satisfy the requirements of high-throughput English speech synthesis and native Indian zero-shot voice cloning, we formulate a **heterogeneous dual-engine pipeline architecture**. Rather than relying on a single compromise model to handle disparate phonetic systems, the architecture separates execution into two specialized, complementary generative engines coordinated by a language router:

1. **Engine 1: English Baseline Engine (ZipVoice-Distill)**:
    - *Backbone Architecture*: A non-autoregressive Zipformer acoustic backbone comprising approximately 123 million parameters, pre-trained on the multi-speaker Emilia English-Chinese dataset.
    - *Numerical Solver*: A 4-step distilled continuous flow-matching decoder.
    - *Neural Vocoder*: A 24 kHz Vocos vocoder (INT8 quantized to 54 MB).
    - *Execution Runtime*: Executed natively via `sherpa-onnx` C++ binaries wrapped in a background Flutter Dart Isolate.
    - *Memory Footprint*: Approximately 104 MB for the quantized INT8 acoustic graph.
2. **Engine 2: Indic Multilingual Engine (IndicF5)**:
    - *Backbone Architecture*: A 22-layer Diffusion Transformer (DiT) comprising 335 million parameters, pre-trained on 1,417 hours of multi-speaker speech across eleven major Indian languages.
    - *Generative Formulation*: Continuous Flow Matching (CFM) solved via an 8-step Euler ODE solver with Classifier-Free Guidance and sway scheduling ($\rho = -1.0$).

- *Neural Vocoder*: An INT8-quantized 24 kHz Vocos vocoder (22 MB, 13.5M parameters) computing analytical iSTFT acoustic waveforms.
- *Execution Runtime*: Python environment (PyTorch safetensors baseline), static/dynamic INT8 ONNX graphs, and a custom native C++ engine with a migration path toward Google LiteRT.

3.2 Signal Preprocessing and Acoustic Feature Extraction

Audio ingested from smartphone microphones or uploaded media containers exhibits variances in sampling rates, bit depths, channel configurations, and recording levels. To ensure numerical stability across the generative pipeline, every audio signal undergoes a standardized three-stage preprocessing pipeline:

3.2.1 Standardized Audio Ingestion and Format Transcoding

User-provided audio files (in `.mp3`, `.ogg`, `.m4a`, `.flac`, or `.wav` formats) are decoded and transcoded using FFmpeg into standardized 16-bit signed uncompressed Pulse Code Modulation (Pulse Code Modulation (PCM)) mono WAV files at a sampling frequency of:

$$f_s = 24,000\,\text{Hz} \tag{3.1}$$

3.2.2 Root-Mean-Square (RMS) Energy Normalization

Reference recordings exhibit noticeable dynamic range disparities, ranging from low-gain speech to saturated signals. In continuous flow matching, acoustic amplitude directly modulates the magnitude of the conditioning mel frames $\mathbf{x}_{\text{ref}}$. If the reference audio energy is too low, the model predicts weak, muffled speech; conversely, excessive input gain introduces harmonic distortion and phase clipping.

To standardize acoustic energy, all reference audio signals $\mathbf{y} \in \mathbb{R}^N$ undergo Root-Mean-Square (Root Mean Square (RMS)) normalization. The root-mean-square amplitude of the signal is defined as:

$$\text{RMS}(\mathbf{y}) = \sqrt{\frac{1}{N}\sum_{n=1}^{N} y(n)^2} \tag{3.2}$$

The audio waveform is scaled linearly to match a target reference energy level $\text{RMS}_{\text{target}} = 0.10$:

$$\mathbf{y}_{\text{norm}} = \mathbf{y} \cdot \left(\frac{\text{RMS}_{\text{target}}}{\text{RMS}(\mathbf{y}) + \epsilon}\right) \tag{3.3}$$

where $\epsilon = 10^{-7}$ prevents division by zero during silence. Following scaling, peak amplitude values are clamped to the dynamic range $[-1.0, 1.0]$ to prevent clipping:

$$\tilde{y}(n) = \max\left(-1.0, \min\left(1.0, y_{\text{norm}}(n)\right)\right) \tag{3.4}$$

3.2.3 Log-Mel Filterbank Transformation

Continuous acoustic features are extracted by computing 100-channel log-mel spectrograms. Let $N_{\text{fft}} = 1024$ represent the Fast Fourier Transform analysis window size, and let $H = 256$ represent the hop size. The Short-Time Fourier Transform (STFT) is computed using a periodic Hanning window:

$$X(k, m) = \sum_{n=0}^{N_{\text{fft}}-1} \tilde{y}(n + mH)w(n)e^{-j\frac{2\pi}{N_{\text{fft}}}kn} \tag{3.5}$$

where $k \in [0, \frac{N_{\text{fft}}}{2}]$ represents discrete frequency bins, and $m \in [0, M-1]$ denotes discrete time frames.

The physical power spectrum $|X(k, m)|^2$ is warped onto the perceptual mel scale via a bank of $C = 100$ triangular bandpass filters $H_c(k)$ spanning the frequency range $[0, \frac{f_s}{2}]$:

$$S_{\text{mel}}(c, m) = \sum_{k=0}^{N_{\text{fft}}/2} |X(k, m)|^2 H_c(k), \quad c \in [1, 100] \tag{3.6}$$

The log-mel spectrogram tensor $\mathbf{x}_{\text{mel}} \in \mathbb{R}^{100\times M}$ is obtained via logarithmic compression:

$$\mathbf{x}_{\text{mel}}(c, m) = \log\left(\max\left(S_{\text{mel}}(c, m), 10^{-5}\right)\right) \tag{3.7}$$

3.3 Indic Akshara Dynamics and Syllabic Duration Modeling

A key challenge in non-autoregressive speech generation is determining the sequence length of the target audio prior to synthesis. Autoregressive models terminate generation organically upon emitting an end-of-sequence token. Non-autoregressive flow-matching models, by contrast, must pre-allocate a fixed-dimensional noise canvas of shape $[1, 100, T_{\text{total}}]$.

3.3.1 The Linguistic Duration Mismatch Problem

In English text-to-speech, character counts correlate loosely with duration due to irregular orthography, but phoneme counts provide reasonable estimates ($\approx$ 80–120 ms per phoneme). In Indian languages, written text consists of base consonants combined with dependent diacritics (*matras*, *viramas*, *anusvaras*).

Early IndicF5 implementations utilized an uncalibrated heuristic derived from English phoneme models:

$$T_{\text{gen}}^{\text{naive}} = \lfloor \text{len}(\mathbf{w}_{\text{tgt}}) \times 15.0 \rfloor \quad \text{frames} \tag{3.8}$$

This formula resulted in severe duration over-allocation. In Tamil, for example, an utterance containing 80 Unicode code points was allocated:

$$T_{\text{gen}} = 80 \times 15 = 1,200\,\text{frames} \implies \frac{1200 \times 256}{24000} = 12.8\,\text{seconds} \tag{3.9}$$

However, a native speaker articulates that same sentence in approximately 5.2 seconds (487 frames). Because the Diffusion Transformer was forced to integrate across a 1,200-frame canvas, the model articulated the speech correctly in the initial 5 seconds, but spent the remaining 7.6 seconds producing acoustic artifacts: audible breathing, murmuring sounds, repeated syllables, and background noise. Conversely, under-allocating duration resulted in truncated words, clipping the final words of sentences.

3.3.2 Mathematical Derivation of the Calibrated Syllabic Model

To resolve this issue, we derived a calibrated syllabic duration model grounded in the phonetic distributions of the IndicVoices corpus [16].

Let $N_{\text{chars}} = \text{len}(\mathbf{w}_{\text{tgt}})$ denote the Unicode string length of the target Indic text. In Dravidian and Indo-Aryan scripts, a complete syllabic akshara decomposes into an average of 1.6 to 2.2 Unicode code points (such as base consonant plus matra). Accounting for pauses, phrase-final lengthening, and punctuation cadence, the empirical acoustic duration per character glyph evaluates to:

$$\tau_{\text{char}} \approx 54.0\,\text{ms} \quad \text{to} \quad 60.0\,\text{ms per Unicode character} \tag{3.10}$$

Converting this temporal density into discrete mel frames at a 256-sample hop size yields:

$$k_{\text{mel}} = \frac{\tau_{\text{char}}}{\Delta t_{\text{frame}}} = \frac{0.055\,\text{s}}{\frac{256}{24000}\,\text{s}} \approx 6.445\,\text{mel frames / character} \tag{3.11}$$

Incorporating an adjustable user speaking rate modifier $\alpha_{\text{speed}} \in [0.5, 2.0]$ and an explicit post-utterance acoustic padding buffer $\tau_{\text{pad}} = 0.30\,\text{seconds}$, the exact target frame duration is formulated as:

$$T_{\text{gen}} = \left\lfloor \text{len}(\mathbf{w}_{\text{tgt}}) \times \frac{6.5}{\max(\alpha_{\text{speed}}, 0.1)} \right\rfloor \tag{3.12}$$

$$T_{\text{pad}} = \left\lfloor \frac{\tau_{\text{pad}} \cdot f_s}{H} \right\rfloor = \left\lfloor \frac{0.30 \times 24000}{256} \right\rfloor = 28\,\text{frames} \tag{3.13}$$

$$T_{\text{total}} = T_{\text{ref}} + T_{\text{gen}} + T_{\text{pad}} \tag{3.14}$$

where $T_{\text{ref}} = \lfloor \frac{N_{\text{ref_samples}}}{H} \rfloor$ represents the exact mel frame length of the reference audio clip. This calibrated formulation (Equation 3.14) eliminates both tail hallucinations and phoneme truncation across test utterances.

3.4 Conditioning Representation and Sequence Concatenation

In the F5-TTS and IndicF5 paradigm, zero-shot voice cloning operates without an explicit phoneme duration aligner or CTC loss. The architecture achieves monotonic alignment implicitly by concatenating text representations and acoustic frames along the sequence dimensions:

3.4.1 Multilingual Character Tokenization

Text sequences are parsed using a shared multilingual character vocabulary (`vocab.txt`) comprising 187 discrete tokens. The vocabulary encompasses:

- Latin alphabet characters (a–z, A–Z) for English baseline compatibility.
- Devanagari Unicode blocks (U+0900 to U+097F) for Hindi and Marathi.
- Tamil Unicode blocks (U+0B80 to U+0BFF) for Tamil.
- Telugu Unicode blocks (U+0C00 to U+0C7F) for Telugu.
- Kannada Unicode blocks (U+0C80 to U+0CFF) for Kannada.
- Standard punctuation markers (periods, commas, question marks, exclamation marks, and the Devanagari danda).

3.4.2 The Spatial Alignment Constraint (Reference Duration Law)

Let $\mathbf{w}_{\text{full}} = \mathbf{w}_{\text{ref}} \oplus \text{“ ”} \oplus \mathbf{w}_{\text{tgt}}$ represent the concatenated string. The text is passed through the ConvNeXt-V2 text encoder, producing a sequence of continuous text embeddings $\mathbf{E}_{\text{text}} \in \mathbb{R}^{512 \times N_{\text{tokens}}}$.

The model constructs an acoustic conditioning canvas $\mathbf{C} \in \mathbb{R}^{100 \times T_{\text{total}}}$:

$$\mathbf{C}[:, t] = \begin{cases} \mathbf{x}_{\text{ref}}[:, t], & \text{for } 0 \leq t < T_{\text{ref}} \\ \mathbf{0}, & \text{for } T_{\text{ref}} \leq t < T_{\text{total}} \end{cases} \tag{3.15}$$

Remark 3.1 (The Reference Duration Boundary Law). In the F5-TTS ConvNeXt architecture, the text encoder places text tokens contiguously at indices $0 \ldots N_{\text{tokens}}$ at the start of the sequence. If the reference audio duration T_{ref} is excessively long (for example, $T_{\text{ref}} > 7.0\,\text{seconds}$), the text representations corresponding to the target utterance are positioned far behind the reference audio boundary. The self-attention layers suffer from positional degradation, attempting to synthesize speech across a temporal span where text conditioning is completely zero-padded, resulting in garbled output.

Conversely, if $T_{\text{ref}} < 3.0\,\text{seconds}$, the reference signal provides insufficient acoustic context to extract stable speaker pitch contours and room reverberation profiles. Hence, we establish the operational guideline:

$$3.5\,\text{seconds} \leq \Delta t_{\text{ref}} \leq 5.0\,\text{seconds} \tag{3.16}$$

accompanied by a verbatim transcript matching the spoken reference audio exactly.

3.5 Continuous Flow Matching Sampling Formulation

The generation trajectory is initialized at $t = 0$ by drawing Gaussian noise:

$$\mathbf{x}_0 \sim \mathcal{N}(\mathbf{0}, \mathbf{I}_{100 \times T_{\text{total}}}) \tag{3.17}$$

Numerical integration proceeds from $s = 0$ to $s = 1$ across N discrete steps using the sway-warped schedule:

$$s_i = \frac{i}{N}, \quad t_i = s_i + \rho \cdot s_i(1 - s_i)(1 - 2s_i), \quad i \in \{0, 1, \ldots, N\} \tag{3.18}$$

with step size $\Delta t_i = t_{i+1} - t_i$ and sway parameter $\rho = -1.0$.

At each step i, the velocity vector field is evaluated twice to apply Classifier-Free Guidance (CFG):

$$\mathbf{v}_{\text{cond}} = \mathbf{v}_\theta(\mathbf{x}_{t_i}, t_i, \mathbf{C}, \mathbf{E}_{\text{text}}) \tag{3.19}$$

$$\mathbf{v}_{\text{uncond}} = \mathbf{v}_\theta(\mathbf{x}_{t_i}, t_i, \mathbf{0}, \mathbf{0}) \tag{3.20}$$

$$\tilde{\mathbf{v}}_i = (1 + \gamma)\mathbf{v}_{\text{cond}} - \gamma \mathbf{v}_{\text{uncond}} \tag{3.21}$$

where $\gamma = 2.0$ amplifies linguistic and speaker conditioning while suppressing unconditional background noise.

The state is updated via first-order Euler integration:

$$\mathbf{x}_{t_{i+1}} = \mathbf{x}_{t_i} + \Delta t_i \cdot \tilde{\mathbf{v}}_i \tag{3.22}$$

Upon reaching $t = 1$, the integrated trajectory $\mathbf{x}_1 \in \mathbb{R}^{100 \times T_{\text{total}}}$ represents clean mel-spectrogram features. The target speech frames are extracted by slicing off the prefix reference window:

$$\mathbf{x}_{\text{tgt}} = \mathbf{x}_1[:, T_{\text{ref}} : T_{\text{total}}] \in \mathbb{R}^{100 \times (T_{\text{gen}} + T_{\text{pad}})} \tag{3.23}$$

3.6 Vocos Neural Spectral Decoding via Inverse STFT

The extracted mel-spectrogram $\mathbf{x}_{\text{tgt}}$ is passed directly to the INT8 Vocos neural vocoder. The Vocos ConvNeXt backbone processes the 100 mel channels and emits:

1. **Magnitude Matrix**: $|\mathbf{X}| \in \mathbb{R}^{513 \times T_{\text{out}}}$ representing Fourier frequency amplitudes.
2. **Phase Vectors**: $(\mathbf{P}_{\cos}, \mathbf{P}_{\sin}) \in \mathbb{R}^{513 \times T_{\text{out}}}$, normalized to unit length:

$$\hat{\mathbf{P}}_{\cos} = \frac{\mathbf{P}_{\cos}}{\sqrt{\mathbf{P}_{\cos}^2 + \mathbf{P}_{\sin}^2 + \epsilon}}, \quad \hat{\mathbf{P}}_{\sin} = \frac{\mathbf{P}_{\sin}}{\sqrt{\mathbf{P}_{\cos}^2 + \mathbf{P}_{\sin}^2 + \epsilon}} \tag{3.24}$$

The complex spectral matrix $\mathbf{Z} \in \mathbb{C}^{513 \times T_{\text{out}}}$ is assembled via Cartesian coordinates:

$$\mathbf{Z}(f,t) = |\mathbf{X}(f,t)| \cdot \left(\hat{\mathbf{P}}_{\cos}(f,t) + j\hat{\mathbf{P}}_{\sin}(f,t) \right) \tag{3.25}$$

The continuous time-domain speech waveform $\mathbf{y} \in \mathbb{R}^{N_{\text{samples}}}$ is computed via the Inverse Short-Time Fourier Transform:

$$y(n) = \frac{\sum_{m=-\infty}^{\infty} w(n - mH) \left[\frac{1}{N_{\text{fft}}} \sum_{k=0}^{N_{\text{fft}}-1} \mathbf{Z}(k,m) e^{j\frac{2\pi}{N_{\text{fft}}}kn} \right]}{\sum_{m=-\infty}^{\infty} w^2(n - mH)} \tag{3.26}$$

where $w(n)$ is a periodic Hanning analysis window of length $N_{\text{fft}} = 1024$ and frame hop $H = 256$.

3.7 Formal Algorithmic Specifications

The end-to-end mathematical procedures for Continuous Flow Matching Voice Cloning and Vocos Neural Spectral Inversion are formalized in Algorithm 1 and Algorithm 2.

Algorithm 1 Continuous Flow Matching Zero-Shot Voice Synthesis

Require: Reference audio $\mathbf{y}_{\text{ref}} \in \mathbb{R}^N$, Reference text $\mathbf{w}_{\text{ref}}$, Target text $\mathbf{w}_{\text{tgt}}$, Model v_θ, Vocoder V_ϕ, Sampling steps N, Guidance weight γ, Speaking speed α, Padding τ_{pad}.
Ensure: Cloned time-domain speech waveform $\mathbf{y}_{\text{tgt}} \in \mathbb{R}^M$.

$\mathbf{y}_{\text{norm}} \leftarrow \text{NormalizeRMS}(\mathbf{y}_{\text{ref}}, \text{target_rms} = 0.10)$
$\mathbf{x}_{\text{ref}} \leftarrow \text{MelFilterbank}(\mathbf{y}_{\text{norm}}, f_s = 24000, H = 256, N_{\text{fft}} = 1024)$
$T_{\text{ref}} \leftarrow \text{Cols}(\mathbf{x}_{\text{ref}})$
$T_{\text{gen}} \leftarrow \lfloor \text{len}(\mathbf{w}_{\text{tgt}}) \times (6.5/\alpha) \rfloor$
$T_{\text{pad}} \leftarrow \lfloor (\tau_{\text{pad}} \times 24000)/256 \rfloor$
$T_{\text{total}} \leftarrow T_{\text{ref}} + T_{\text{gen}} + T_{\text{pad}}$
$\mathbf{C} \leftarrow \text{Zeros}(100, T_{\text{total}})$
$\mathbf{C}[:, 0 : T_{\text{ref}}] \leftarrow \mathbf{x}_{\text{ref}}$ ▷ Set unmasked prefix acoustic prompt
$\mathbf{w}_{\text{full}} \leftarrow \mathbf{w}_{\text{ref}} \oplus \text{“ ”} \oplus \mathbf{w}_{\text{tgt}}$
$\mathbf{E}_{\text{text}} \leftarrow \text{ConvNeXtEncoder}(\text{Tokenize}(\mathbf{w}_{\text{full}}))$
$\mathbf{x}_0 \sim \mathcal{N}(\mathbf{0}, \mathbf{I}_{100 \times T_{\text{total}}})$ ▷ Initialize prior Gaussian noise
for $i = 0$ **to** $N - 1$ **do**
  $s_i \leftarrow i/N; \quad s_{i+1} \leftarrow (i+1)/N$
  $t_i \leftarrow s_i - s_i(1 - s_i)(1 - 2s_i)$ ▷ Sway schedule with $\rho = -1.0$
  $t_{i+1} \leftarrow s_{i+1} - s_{i+1}(1 - s_{i+1})(1 - 2s_{i+1})$
  $\Delta t_i \leftarrow t_{i+1} - t_i$
  $\mathbf{v}_{\text{cond}} \leftarrow \mathbf{v}_\theta(\mathbf{x}_{t_i}, t_i, \mathbf{C}, \mathbf{E}_{\text{text}})$
  $\mathbf{v}_{\text{uncond}} \leftarrow \mathbf{v}_\theta(\mathbf{x}_{t_i}, t_i, \mathbf{0}, \mathbf{0})$
  $\tilde{\mathbf{v}}_i \leftarrow (1 + \gamma)\mathbf{v}_{\text{cond}} - \gamma\mathbf{v}_{\text{uncond}}$ ▷ Classifier-Free Guidance
  $\mathbf{x}_{t_{i+1}} \leftarrow \mathbf{x}_{t_i} + \Delta t_i \cdot \tilde{\mathbf{v}}_i$ ▷ Euler ODE numerical update
$\mathbf{x}_{\text{tgt}} \leftarrow \mathbf{x}_1[:, T_{\text{ref}} : T_{\text{total}}]$ ▷ Slice generated target mel frames
$\mathbf{y}_{\text{tgt}} \leftarrow \text{VocosDecode}(V_\phi, \mathbf{x}_{\text{tgt}})$
return $\mathbf{y}_{\text{tgt}}$

Algorithm 2 Vocos Neural Fourier Audio Synthesis

Require: Quantized Vocos Model V_ϕ, Synthesized Mel-Spectrogram $\mathbf{x}_{\text{tgt}} \in \mathbb{R}^{100 \times T}$.
Ensure: Reconstructed PCM Audio Samples $\mathbf{y} \in \mathbb{R}^N$.

$\mathbf{H}_{\text{features}} \leftarrow \text{ConvNeXtBackbone}_\phi(\mathbf{x}_{\text{tgt}})$
$|\mathbf{X}| \leftarrow \exp\left(\text{LinearMagHead}_\phi(\mathbf{H}_{\text{features}})\right)$ ▷ Predict magnitude spectra
$\mathbf{P}_{\cos}, \mathbf{P}_{\sin} \leftarrow \text{LinearPhaseHead}_\phi(\mathbf{H}_{\text{features}})$
$\mathbf{P}_{\text{norm}} \leftarrow \sqrt{\mathbf{P}_{\cos}^2 + \mathbf{P}_{\sin}^2 + 10^{-8}}$
$\hat{\mathbf{P}}_{\cos} \leftarrow \mathbf{P}_{\cos} / \mathbf{P}_{\text{norm}}; \quad \hat{\mathbf{P}}_{\sin} \leftarrow \mathbf{P}_{\sin} / \mathbf{P}_{\text{norm}}$
$\mathbf{Z}_{\text{real}} \leftarrow |\mathbf{X}| \odot \hat{\mathbf{P}}_{\cos}; \quad \mathbf{Z}_{\text{imag}} \leftarrow |\mathbf{X}| \odot \hat{\mathbf{P}}_{\sin}$
$\mathbf{Z} \leftarrow \mathbf{Z}_{\text{real}} + j\mathbf{Z}_{\text{imag}} \in \mathbb{C}^{513 \times T}$
$\mathbf{y} \leftarrow \text{iSTFT}(\mathbf{Z}, N_{\text{fft}} = 1024, H = 256, \text{window} = \text{Hanning})$
return $\mathbf{y}$

3.8 Comparative Model Architectural Matrix

To validate the selection of IndicF5 as our primary Indic backbone and ZipVoice-Distill as our English baseline, Table 3.1 summarizes the architectural specifications, parameter counts, memory footprints, and edge feasibility of candidate models surveyed in the literature.

TABLE 3.1: Comprehensive Architectural Comparison of Speech Synthesis Models

Model	Params	Paradigm	Quantized	Zero-Shot	Indic Support	Edge Verdict
IndicF5	**335M**	**OT-CFM (DiT)**	**349 MB (INT8)**	**Yes**	**Native (11 Lang)**	**Primary Indic**
ZipVoice	123M	OT-CFM (Zipf.)	104 MB (INT8)	Yes	None (En/Zh only)	English Baseline
GPT-SoVITS	77M	Hybrid AR+VITS	85 MB (FP16)	Yes (5s)	Unofficial/Weak	Tier-B Spike
Chatterbox	110M	AR + 1-Step	Not Quantized	Yes	None (English)	Excluded
XTTS-v2	467M	AR Transformer	>1.8 GB	Yes	Adaptable (Heavy)	Excluded (OOM)
Kokoro-82M	82M	StyleTTS2	80 MB	No	None (English)	Excluded
VITS (Base)	35M	VAE + Flow	45 MB	No (Fixed)	Per-Voice Training	Excluded

As shown in Table 3.1, IndicF5 combines zero-shot voice cloning with native multilingual support for Indian languages, while remaining compressible into a sub-400 MB INT8 mobile footprint.

Chapter 4

Implementation Methodology and Step-by-Step Engineering Iterations

4.1 Iterative Engineering Methodology

Deploying zero-shot deep generative speech architectures to resource-constrained embedded systems requires addressing disparities between high-level machine learning frameworks (PyTorch, TorchScript) and physical edge execution environments (ARM NEON, Android NDK, Flutter runtime). These differences emerge across numerical precision, memory allocation, and linguistic tokenization boundaries.

To document the development of this project with academic rigor and experimental reproducibility, this chapter details the ten engineering iterations completed during this phase. Each iteration outlines:

(i) The operational objective and architectural hypotheses;

(ii) The technical implementation and system modifications;

(iii) The defects, runtime anomalies, or hardware bottlenecks encountered; and

(iv) The algorithmic and systems-level resolutions applied.

4.2 Iteration 1: English Baseline Implementation via Sherpa-ONNX

4.2.1 Objective and Setup

The initial milestone verified whether non-autoregressive flow-matching models could execute zero-shot speaker adaptation directly on client hardware without cloud server dependencies. This established an empirical performance baseline prior to addressing Indian languages.

4.2.2 Implementation Details

We developed the standalone evaluation script `english_tts.py` (and legacy `zipvoice-tts.py`) utilizing the Python C++ bindings of `sherpa-onnx` [18]. The model architecture incorporated:

- An INT8-quantized ZipVoice encoder (`encoder.int8.onnx`, 5.5 MB);
- An INT8-quantized Zipformer flow-matching decoder (`decoder.int8.onnx`, 124 MB);
- An espeak-ng Grapheme-to-Phoneme lexicon mapping English orthography to phonetic tokens; and
- A 24 kHz Vocos vocoder graph (`vocos_24khz.onnx`, 54 MB).

4.2.3 Findings and Milestones

Executing on a multi-core desktop CPU, the 4-step flow-matching engine cloned reference voices in approximately 1.8 to 2.4 seconds, achieving RTF ≈ 0.35 for a 6-second utterance. This confirmed that 4-step distilled continuous flow matching eliminates the multi-minute latency bottlenecks associated with classical score-based diffusion models.

4.3 Iteration 2: Flutter Mobile Prototype (`voice_clone_proto`)

4.3.1 Objective and UI Architecture

Following Python validation, Iteration 2 migrated the generative pipeline into a cross-platform Android application named `voice_clone_proto`. The application was purposefully engineered as a teacher-facing classroom audio generator and an assistive learning tool for visually impaired students.

4.3.2 System Implementation

The application was built in Flutter using Material 3 design tokens, incorporating high-contrast layouts and Android TalkBack accessibility semantics to assist visually impaired learners. The user interface was structured into a guided 4-step workflow designed for rapid classroom lesson preparation:

1. **Step 1: Reference Script Selection**: The teacher selects a phonetically balanced prompt phrase (such as *"The quick brown fox jumps over the lazy dog"* or regional language equivalents) or enters custom text.

2. **Step 2: Reference Audio Acquisition**: The teacher's voice is captured via live microphone recording (3 to 5 seconds) using the `record` package or imported from local storage via `file_picker`.

3. **Step 3: Target Text Entry**: The teacher enters textbook passages, conceptual explanations, or student quiz items categorized by duration presets (Short, Medium, Long).

4. **Step 4: Generation and Waveform Playback**: Synthesizes the educational audio in the teacher's cloned voice and renders an interactive waveform visualization widget with tactile playback controls.

4.3.3 Concurrency and Background Isolate Decoupling

Executing neural network inference on the main UI thread causes frame drops and triggers Android Application Not Responding (ANR) warnings. To maintain interface responsiveness, the Sherpa-ONNX C++ runtime was decoupled into a background **Dart Isolate** via `Isolate.run()`.

To handle arbitrary classroom recordings (such as AAC `.m4a` files captured on mobile handsets), we integrated an audio transcoding library based on FFmpeg to convert recordings into 16-bit 24 kHz mono PCM WAV prior to inference.

4.4 Iteration 3: Empirical Multi-Device Benchmarking and In-Kernel RSS Profiling

4.4.1 Benchmarking Methodology

To evaluate hardware performance across silicon tiers, we deployed `voice_clone_proto` across physical Android devices representing different performance brackets:

1. **Flagship Tier**: Samsung Galaxy S23 (Qualcomm Snapdragon 8 Gen 2, 8 GB RAM, dedicated NPU).

2. **Upper Mid-Range Tier**: Samsung Galaxy Tab S9 FE+ (Samsung Exynos 1380, 8 GB RAM, dedicated NPU).

3. **Mid-Range Tier**: Samsung Galaxy M53 5G (MediaTek Dimensity 900, 8 GB RAM, dedicated NPU).

4. **Target Budget Baseline (Government School Hardware)**: Lenovo Tab K10 (MediaTek Helio P22T, 4 GB RAM, CPU-only execution). This device serves as our primary engineering target because it represents the benchmark specification of subsidized tablets procured and distributed in bulk by Indian state education departments for rural classrooms and special education facilities.

To measure exact physical memory consumption, the Flutter background isolate was instrumented to poll `/proc/self/status` directly from the Linux kernel virtual filesystem upon completion of each utterance:

```
int rssMB = 0;
final file = File('/proc/self/status');
if (file.existsSync()) {
  for (final line in file.readAsLinesSync()) {
    if (line.startsWith('VmRSS:')) {
      final parts = line.split(RegExp(r'\s+'));
      if (parts.length >= 2) {
        rssMB = (int.tryParse(parts[1]) ?? 0) ~/ 1024;
        break;
      }
    }
  }
}
```

Listing 4.1: Dart In-Kernel Memory Profiling Hook via /proc/self/status

4.4.2 Empirical Hardware Measurements

The measured Real-Time Factors (RTF), Peak Resident Set Sizes (RSS), and cold-initialization latencies across standardized utterance lengths are tabulated in Table 4.1.

Table 4.1: Empirical On-Device Baseline Benchmarks across Physical Android Devices

Device Model	**Processor (SoC)**	**RAM**	**Tier**	**RTF (Median)**	**Peak RSS**	**Status**
Samsung Galaxy S23	Snapdragon 8 Gen 2	8 GB	Short (5w)	3.826	1,033 MB	PASS
Samsung Galaxy S23	Snapdragon 8 Gen 2	8 GB	Med (25w)	1.520	1,287 MB	PASS
Samsung Galaxy S23	Snapdragon 8 Gen 2	8 GB	Long (65w)	**1.288**	**1,562 MB**	PASS
Galaxy Tab S9 FE+	Exynos 1380	8 GB	Short (5w)	9.279	1,021 MB	PASS
Galaxy Tab S9 FE+	Exynos 1380	8 GB	Med (25w)	2.918	1,491 MB	PASS
Galaxy Tab S9 FE+	Exynos 1380	8 GB	Long (65w)	**2.508**	**1,772 MB**	MARGINAL
Samsung Galaxy M53	Dimensity 900	8 GB	Short (5w)	8.415	1,021 MB	PASS
Samsung Galaxy M53	Dimensity 900	8 GB	Med (25w)	2.782	1,219 MB	PASS
Samsung Galaxy M53	Dimensity 900	8 GB	Long (65w)	**2.531**	**1,539 MB**	PASS
Lenovo Tab K10	Helio P22T (No NPU)	4 GB	All Tiers	*> 5.0 (Est.)*	*> Budget*	CRITICAL

4.4.3 Analysis of Baseline Benchmarks

1. **Fixed Overhead Dominance**: Across all devices, short utterances exhibited elevated RTFs (3.8× to 9.3×). Model initialization, lexicon loading, and vocoder startup represent an invariant baseline cost of ≈ 1.2 seconds.

2. **Peak Memory Escalation on Long Utterances**: On long sentences, physical memory reached 1,772 MB on the Exynos 1380 and 1,562 MB on the Snapdragon 8 Gen 2. On an 8 GB device, this remains within acceptable operating boundaries. However, on budget 4 GB devices (such as the Lenovo Tab K10), foreground processes exceeding 1,500 MB risk termination by the Android LowMemoryKiller. This demonstrated that uncompressed

FP32 models cannot be deployed without integer quantization and pre-allocated static memory arenas.

4.5 Iteration 4: IndicF5 Model Adaptation and Desktop PyTorch Verification

4.5.1 Objective

Having established the English baseline and its edge resource constraints, Iteration 4 addressed the core linguistic problem: zero-shot voice cloning for Indian languages.

4.5.2 Model Setup and Adaptation

We adapted AI4Bharat's IndicF5 repository under `scratch/indicf5_repo/`. Developed in PyTorch using safetensors serialization, the base model (`model.safetensors`) occupied 1.35 GB in memory. We engineered the standalone command-line verification script `clone.py` (and `test_indicf5_clone.py`) implementing the continuous flow-matching pipeline with the 22-layer DiT backbone and 24 kHz Vocos vocoder.

4.5.3 Validation Across Indian Languages

We validated synthesis across four major Indian languages:

- **Tamil**: Synthesizing conversational phrases (e.g., வணக்கம், நீங்கள் எப்படி இருக்கிறீர்கள்?);
- **Telugu**: Synthesizing conversational phrases (e.g., నమస్కారం, మీరు ఎలా ఉన్నారు?);
- **Kannada**: Testing Kannada phonetic prompts (e.g., *"Namaskara, neevu hegiddira?"*); and
- **Hindi**: Testing Devanagari prompts (e.g., नमस्ते, आप कैसे हैं?).

The model produced intelligible pronunciation without external G2P dictionaries, validating the unified character tokenization approach.

4.6 Iteration 5: Syllabic Duration Calibration (Resolving Audio Truncation and Trailing Silence)

4.6.1 The Duration Mismatch Issue

During early testing with IndicF5, synthesized audio clips suffered from a noticeable duration mismatch:

> *When synthesizing an Indic sentence, the model articulated target speech with natural prosody during the initial 4 to 5 seconds. However, the generated audio file extended for an additional 6 to 8 seconds, during which the model generated trailing silence, audible breathing, whispered murmurs, repeated syllables, or background noise.*

4.6.2 Root Cause Investigation

Investigation revealed that the duration allocator utilized an uncalibrated linear heuristic ($T_{\text{gen}} = \text{len}(\mathbf{w}_{\text{tgt}}) \times 15.0$ frames). Because written Indic text contains numerous combining diacritics (*matras*, *viramas*), character string length is inflated relative to spoken syllable counts. Allocating 15 mel frames per Unicode character resulted in a 12.8-second mel canvas for an utterance that naturally completes in 5.2 seconds.

Because continuous flow matching integrates trajectories across the entire allocated canvas, the model was forced to solve the ODE into a temporal region where text conditioning had terminated. The self-attention layers consequently synthesized low-probability acoustic artifacts (breathing, murmurs, and repeated phonemes).

4.6.3 Resolution: Calibrated 6.5 Mel Frames per Character

As derived in Chapter 3.3, we re-calibrated the temporal density constant to:

$$k_{\text{mel}} = 6.5 \quad \text{mel frames per character code point} \tag{4.1}$$

Setting $k_{\text{mel}} = 6.5$ (at $H = 256, f_s = 24000$) matches the natural speaking cadence of $\approx 55\,\text{ms}$ per character glyph. Post-utterance padding was constrained to an explicit 0.30-second acoustic buffer ($\tau_{\text{pad}} = 28$ frames). This adjustment eliminated trailing artifacts and yielded clean sentence endings across Tamil, Telugu, and Hindi.

4.7 Iteration 6: Sequence Alignment and Reference Audio Duration Constraints

4.7.1 The Long-Reference Degradation Issue

In subsequent testing, we observed that when users supplied long reference audio clips (such as a 10.8-second recording, `sudhanva_voic_clone.wav`), the synthesized output degraded into unintelligible static, even when the prompt text was brief.

4.7.2 Root Cause Investigation

We traced this issue to the spatial alignment design of the F5-TTS ConvNeXt text encoder:

1. In F5-TTS, text tokens for the concatenated string $[\mathbf{w}_{\text{ref}} \oplus \mathbf{w}_{\text{tgt}}]$ are embedded contiguously at the start of the sequence $(0 \dots N_{\text{tokens}})$.
2. When a 10.8-second reference audio clip is ingested, $T_{\text{ref}} = 1016$ mel frames. The reference audio finishes at frame 1016, but text representations for both reference and target text terminate at sequence index 228 (corresponding to $t \approx 1.6\,\text{s}$ in normalized sequence coordinates).
3. Consequently, target audio synthesis occurred in a temporal region ($t \in [1016, 1500]$ frames) where the text conditioning channel was completely zero-padded. The Diffusion Transformer lacked local cross-attention alignment to target text tokens, generating unconditioned noise.

4.7.3 Resolution: Operational Reference Boundary Law

We established the operational rule that reference audio clips must be bounded strictly between 3.5 seconds and 5.0 seconds in duration ($T_{\text{ref}} \in [328, 468]$ frames). We recorded and verified clean, phonetically balanced 3.8-second reference clips (`samples/sudhanva_short_ref.wav` and `samples/tamil_voices/tamil_classic_pangram.mp3`). When paired with verbatim reference transcripts, spatial text-mel alignment was maintained, restoring clear phonetic articulation.

4.8 Iteration 7: In-Memory Warm Model Batch Synthesis and Dataset Curation

4.8.1 Motivation and Batch Engine

Iterative model validation required evaluating multiple sentences across diverse speakers, languages, and duration tiers. Loading the 1.35 GB PyTorch model weights from disk on every invocation incurred a 12-second cold-start penalty per sentence.

4.8.2 System Architecture

We engineered the dedicated batch synthesis engine `batch.py` within the backend architecture:

- **In-Memory Model Caching**: The 1.35 GB model weights, vocabularies, and Vocos vocoder are loaded into RAM once during initialization. Subsequent synthesis requests reuse the warm pipeline, eliminating cold-load latency.
- **Auto-Incrementing Batch Storage**: Each execution automatically creates the next incremental output directory (`generated/batches/batch-1/`, `batch-2/`, etc.).
- **Multi-Processing Concurrency**: Implemented an optional multi-worker process pool (`--parallel --workers N`) utilizing inter-process queues for parallel benchmark throughput.

4.8.3 The Multilingual Dataset (`prompts.json`)

To standardize evaluation, we authored the curated dataset `prompts.json`, comprising 120 authentic conversational phrases across Tamil, Telugu, and Hindi. To evaluate latency and duration scaling systematically, the dataset is stratified into four standardized tiers:

1. **Short Tier** (10 phrases/language, 4–7 words): Everyday conversational greetings and inquiries.
2. **Medium Tier** (10 phrases/language, 12–18 words): Moderate-length social dialogues.
3. **Midlong Tier** (10 phrases/language, 20–25 words): Compound sentences describing activities and settings.
4. **Long Tier** (10 phrases/language, 28–35 words): Complex narrative sentences with multiple dependent clauses.

4.9 Iteration 8: Unified Voice Studio Suite and Dynamic Catalog Management

4.9.1 System Architecture

To establish a modular codebase, the backend was refactored into the Python package `src/voice_studio/`, organized as follows:

- `config.py`: Centralized path resolutions, hardware constants, and UTF-8 stream configurations.
- `audio/io.py`: Format decoding, FFmpeg transcoding, and RMS normalization.
- `catalog/manager.py`: Voice catalog CRUD operations, automatic metadata extraction, and audio validation.
- `dataset/prompts.py`: Tier-based phrase parsing and range selection.
- `engines/`: Unified engine interfaces for IndicF5, ZipVoice, and batch runner execution.
- `cli/`: Unified entry point via `main.py`, supporting an interactive Terminal User Interface (TUI) and direct subcommands (`list`, `info`, `add`, `prompts`, `clone`, `batch`).

4.9.2 Dynamic Catalog Management (`samples/voices.json`)

The catalog tracks registered speaker reference clips, storing voice keys, spoken transcripts, descriptions, audio durations, and creation timestamps. In an educational setting, this catalog enables teachers across different academic subjects (such as Mathematics, Science, and Regional

Literature) to register distinct instructor profiles. When a teacher registers a new voice via `python main.py add`, the system validates audio integrity, measures duration, normalizes RMS energy, and stores the file into `samples/added/`. This structure allows students, particularly visually impaired learners who rely entirely on audio lessons, to select and listen to content voiced by their specific subject teacher.

4.10 Iteration 9: Graph Optimization, FP32 Export, and Static/Dynamic INT8 Quantization

4.10.1 Objective: Decoupling from the PyTorch Runtime

Deploying IndicF5 onto Android devices requires decoupling the model from the heavy Python runtime, Librosa, and PyTorch (which exceed 2.5 GB on disk). Iteration 9 developed the complete graph optimization and integer quantization export pipeline under `models/indicf5/`.

4.10.2 Exported Model Artifacts

We successfully exported and verified five model graphs:

1. **`model.safetensors`**: Baseline PyTorch weights (1.35 GB, 335M parameters).
2. **`indicf5_dit_fp32_static.onnx`**: Static-shape unquantized FP32 graph (1.36 GB, fixed at 128 mel frames).
3. **`indicf5_dit_dynamic_fp32.onnx`**: Dynamic sequence dimension FP32 graph (1.36 GB, supporting variable audio lengths).
4. **`indicf5_dit_int8_static.onnx`**: Static INT8 quantized DiT graph (349 MB, 74% size reduction).
5. **`indicf5_vocos_int8.onnx`**: INT8 quantized Vocos neural vocoder (22 MB, down from 54 MB).
6. **`vocab.txt`**: Standalone multilingual character tokenization mapping (11.3 KB, 187 tokens).

4.11 Iteration 10: Custom Native C++ Engine and Dart FFI Shared Library

4.11.1 Motivation

Because `sherpa-onnx` lacks built-in C++ loaders for Diffusion Transformers and F5-TTS, we engineered a dedicated native shared library (`libindicf5_engine.so`) linking directly to the ONNX Runtime Mobile C++ API.

4.11.2 C++ Engine Architecture (`indicf5_engine.cpp`)

The native engine implements:

- Direct session management via `Ort::Session` for `indicf5_dit_int8_static.onnx` and `indicf5_vocos_int8.onnx`.
- Pre-allocated static tensor arenas, eliminating dynamic heap allocations across the 8 Euler ODE integration steps.
- Native implementation of the Classifier-Free Guidance Euler update step:

$$x_{t+\Delta t}[k] = x_t[k] + \Delta t \cdot ((1+\gamma)v_{\text{cond}}[k] - \gamma v_{\text{uncond}}[k]) \tag{4.2}$$

  accelerated via multi-threaded ARM NEON execution kernels.
- A C ABI interface (`indicf5_c_api.h`) exposing core lifecycle and synthesis routines (`indicf5_create`, `indicf5_synthesize`, `indicf5_destroy`).
- A Dart FFI bridge service (`indicf5_service.dart`) enabling the Flutter application to invoke native C++ inference in background Dart Isolates without bridging overhead.

4.12 Hardware Memory Budget Analysis on 4 GB RAM Platforms

To verify that the quantized system avoids Android LowMemoryKiller crashes on budget devices like the Lenovo Tab K10, Table 4.2 details the comparative physical memory budget.

By compressing the operational footprint to 801 MB, the quantized architecture operates safely within the memory constraints of budget mobile edge devices, providing a 699 MB safety margin on 4 GB hardware.

TABLE 4.2: Physical RAM Budget Comparison on 4 GB Android Edge Hardware

Memory Subsystem Component	**Unquantized Baseline (FP32)**	**Quantized System (Ours)**
Diffusion Transformer (DiT) Weights	1,350 MB	349 MB (Static INT8)
Vocos Neural Vocoder Weights	54 MB	22 MB (INT8)
Inference Working Arenas	850 MB (Dynamic Heap)	280 MB (Pre-allocated Static)
Flutter Runtime, Dart VM & UI Buffers	150 MB	150 MB
Total Peak Resident Set Size (RSS)	**2,404 MB**	**801 MB**
Android LowMemoryKiller Ceiling	$\approx 1,500$–$1,800$ MB	$\approx 1,500$–$1,800$ MB
Safety Margin / Operational Verdict	**EXCEEDED (Crash / SIGKILL)**	**+699 MB SAFE HEADROOM**

Chapter 5

Strategic Future Architecture: Google LiteRT Implementation and Edge Acceleration Roadmap

5.1 Motivation and Architectural Rationale for Transitioning to Google LiteRT

While the custom native C++ engine (`libindicf5_engine.so`) developed in Iteration 10 executes INT8 ONNX graphs on mobile ARM CPUs, long-term deployment across commercial Android ecosystems requires addressing three systemic limitations of custom ONNX Runtime pipelines:

1. **Intermediate ONNX Operator Overhead**: Exporting PyTorch Diffusion Transformers to ONNX decomposes native PyTorch multi-head attention blocks and rotary embeddings into hundreds of individual primitive nodes (`Transpose`, `Reshape`, `Concat`, `MatMul`). Intermediate tensor permutations introduce memory layout overhead, degrading L1/L2 data cache locality on mobile processors.

2. **Heterogeneous Accelerator Fragmentation**: In standard ONNX Runtime Mobile, offloading tensor operations to dedicated on-device silicon (Neural Processing Units or Neural Processing Units (NPUs)) requires vendor-specific Execution Providers (such as the Qualcomm QNN Execution Provider). Configuring and cross-compiling QNN EP shared libraries within the Android NDK introduces build fragility, large binary sizes (>80 MB for runtime libraries alone), and lacks support for competing chipsets such as MediaTek Dimensity or Google Tensor.

3. **Memory Copy Penalties**: Standard ONNX C++ wrappers copy tensors between Java/Kotlin, native C++ heap buffers, and hardware memory arenas, producing multiple memory copies per forward pass.

To address these limitations, the central post-midsem engineering roadmap transitions the Indic speech generative pipeline to **Google LiteRT** [20] (formerly TensorFlow Lite and AI Edge Torch). Table 5.1 presents an architectural comparison between custom ONNX Runtime Mobile and Google LiteRT.

TABLE 5.1: System Architecture Comparison: Custom ONNX Runtime vs. Google LiteRT

Architectural Dimension	**Custom ONNX Runtime (C++)**	**Google LiteRT (LiteRT Torch)**
Model Ingestion Path	PyTorch → ONNX → ORT	Direct PyTorch → `.tflite` FlatBuffer
Graph Operator Dialect	Generic ONNX standard	Optimized TFLite / StableHLO dialect
Transpose-Op Overhead	High (Frequent Transpose nodes)	Low (Fused native tensor layouts)
Snapdragon NPU Acceleration	Manual QNN Execution Provider	Native Qualcomm AI Engine Direct
MediaTek APU Acceleration	Unstable Android NNAPI fallback	Native MediaTek NeuroPilot integration
Buffer Allocation	Custom heap memory arenas	Zero-copy Android Hardware Buffers
Runtime Binary Footprint	Heavy (>75 MB `.so` dependencies)	Lightweight (8–12 MB runtime)
Ecosystem Integration	Manual NDK CMake & Dart FFI	Google Play On-Device AI (PODAI)

5.2 Direct PyTorch Conversion via LiteRT Torch (`litert-torch`)

Historically, converting PyTorch generative models to TensorFlow Lite required exporting to ONNX, followed by conversion via `onnx2tf` or `tf2onnx`, an error-prone multi-stage process that frequently failed on dynamic shapes or custom attention kernels.

The modern LiteRT toolchain introduces **LiteRT Torch** (`litert-torch`) [21], enabling direct compilation from native PyTorch code into optimized `.tflite` FlatBuffers:

```
import torch
import litert_torch

# 1. Instantiate the pre-trained IndicF5 DiT PyTorch backbone
model = load_indicf5_dit_backbone().eval()

# 2. Define sample dynamic inputs (noisy mel, time step, text tokens, ref mel)
sample_inputs = (
    torch.randn(1, 100, 512, dtype=torch.float32),   # x_t
    torch.tensor([0.5], dtype=torch.float32),         # time step t
    torch.randint(0, 187, (1, 64), dtype=torch.int32),# text tokens
    torch.randn(1, 100, 350, dtype=torch.float32),   # ref mel conditioning
)

# 3. Export model graph using PyTorch 2.x export infrastructure
exported_program = torch.export.export(model, sample_inputs)

# 4. Directly compile to LiteRT FlatBuffer with INT8 quantization
litert_model = litert_torch.convert(
    exported_program,
    sample_inputs,
    quantization_config=litert_torch.QuantizationConfig.int8_ptq()
)

# 5. Serialize FlatBuffer to disk
litert_model.save("models/indicf5/indicf5_dit_int8.tflite")
```

LISTING 5.1: Conceptual PyTorch-to-LiteRT Conversion Pipeline via litert-torch

5.2.1 StableHLO Dialect and Operator Fusion

LiteRT Torch translates PyTorch operators into *StableHLO* (Stable High-Level Optimizer) intermediate representations. Within the StableHLO dialect:

- Multi-head self-attention projections ($\mathbf{Q}, \mathbf{K}, \mathbf{V}$ linear layers) are fused into batched matrix contractions.
- Rotary Position Embedding rotations (Equation 2.11) are fused with attention dot-product kernels, eliminating redundant intermediate tensor allocations.
- Layer normalization and ConvNeXt depthwise convolutions are transformed into optimized SIMD primitives.

5.3 Hardware Acceleration via the CompiledModel API

A key capability of Google LiteRT is the **`CompiledModel` API**, which abstracts low-level vendor delegates behind a unified declarative interface.

5.3.1 Declarative Accelerator Prioritization

In Android edge applications, the developer specifies a hardware execution hierarchy. The runtime automatically probes the underlying silicon, binds to available vendor drivers, and falls back gracefully if hardware acceleration is unavailable:

```
import com.google.ai.edge.litert.CompiledModel
import com.google.ai.edge.litert.Accelerator

val options = CompiledModel.Options().apply {
    // Set hierarchical accelerator priority: NPU -> GPU -> CPU
    setAcceleratorPriority(listOf(
        Accelerator.NPU,
        Accelerator.GPU,
        Accelerator.CPU
    ))
    setNumThreads(4) // 4 threads for XNNPACK CPU fallback
}

// Compile model ahead-of-time or on-device
val compiledModel = CompiledModel.create(
    context.assets.openFd("indicf5_dit_int8.tflite"),
    options
)
```

Listing 5.2: Kotlin/Android CompiledModel Initialization with Accelerator Priority

5.3.2 Qualcomm AI Engine Direct (QNN) Integration

When running on devices powered by Qualcomm Snapdragon platforms (such as the Samsung Galaxy S23 featuring the Snapdragon 8 Gen 2):

- LiteRT binds directly to Qualcomm AI Engine Direct (QNN) [22].
- Matrix multiplications in the DiT layers are offloaded to the Hexagon Tensor Processor (HTP), executing 8-bit integer dot products at up to 35 Tera Operations Per Second (TOPS).
- This hardware offloading reduces forward-pass latency from $\approx 85\,\text{ms}$ on the CPU down to ≈ 15–$20\,\text{ms}$ on the HTP, projecting an overall synthesis Real-Time Factor below $0.4\times$.

5.3.3 MediaTek NeuroPilot Integration

When running on devices powered by MediaTek Dimensity or Helio SoCs (such as the Samsung Galaxy M53 or commercial tablets):

- LiteRT offloads operations to the MediaTek APU via the MediaTek NeuroPilot [23] driver stack.
- On lower-tier devices lacking dedicated APUs (such as the Helio P22T in the Lenovo Tab K10), LiteRT automatically triggers graceful fallback to XNNPACK, executing 4-thread ARMv8 NEON assembly routines.

5.4 Zero-Copy Pipelines via Android Hardware Buffers

In traditional deep learning runtimes, passing generated mel-spectrogram tensors from the acoustic model to the neural vocoder and subsequently to the audio output track incurs memory copying overhead:

$$\text{Model Heap} \xrightarrow{\text{memcpy}} \text{Vocoder Input Buffer} \xrightarrow{\text{memcpy}} \text{PCM Audio Track} \tag{5.1}$$

On memory-bandwidth-constrained edge SoCs, these copies generate memory bus stalls and inflate physical RSS.

LiteRT addresses this via native support for **Android Hardware Buffers** (`AHardwareBuffer`):

1. The output tensor of the DiT model and the input tensor of the Vocos vocoder are allocated in a shared, memory-mapped `AHardwareBuffer`.
2. The Fourier Inverse STFT synthesis is performed in-place within this memory-mapped hardware buffer.

3. Synthesized PCM audio samples are streamed directly to the Android low-latency audio subsystem (AAudio / OpenSL ES) without intermediate user-space buffer duplication.

5.5 Trajectory Distillation: 2-Step and 4-Step Sampling

While hardware acceleration reduces per-step evaluation latency, algorithmic acceleration reduces the total number of steps required to solve the continuous flow-matching ODE. As established in Chapter 2, our post-midsem roadmap incorporates two distinct trajectory distillation techniques:

5.5.1 Rectified Flow Trajectory Straightening (4-Step Reflow)

By retraining the IndicF5 DiT model on synthetic coupled pairs $(\mathbf{x}_0, \mathbf{z}_1)$ generated by the base 1-rectified model (Equation 2.20), trajectory crossing is eliminated. In 2-rectified flow, the vector field paths become straight lines, allowing a 4-step Euler solver to achieve Mean Opinion Scores equivalent to the current 8-step baseline, cutting overall computational requirements in half.

5.5.2 Consistency Distillation via FlashSpeech (2-Step Synthesis)

Applying consistency distillation principles [15] trains a student network enforcing $f_\theta(\mathbf{x}_{t_1}, t_1) = f_\theta(\mathbf{x}_{t_2}, t_2)$. This collapses the initial value problem into a 2-step sampling process:

- **Step 1** ($t = 0.0 \rightarrow 0.5$): Establishes global harmonic structure, speaker formant resonance, and vocal tract identity.
- **Step 2** ($t = 0.5 \rightarrow 1.0$): Synthesizes high-frequency fricatives, aspiration noise, and fine phonetic articulation.

Executing 2 steps on an NPU-accelerated mobile runtime reduces mobile SoC active duty cycles and power consumption, enabling responsive on-device voice cloning.

5.6 Physical Testing and Verification Protocol

The post-midsem implementation will be validated against a standardized physical testing protocol across our four target device tiers:

1. **Phase A: Graph Compilation and Validation**:
    - Validate numerical parity between PyTorch FP32 outputs and LiteRT INT8 `.tflite` outputs (ensuring Spectral Mel-Cepstral Distortion MCD < 3.5 dB).

- Verify that INT8 quantization introduces zero audible quantization hiss or phase distortion across Vocos iSTFT reconstructions.

2. **Phase B: Ahead-of-Time NPU Compilation and Delegate Profiling**:
   - Measure per-operator execution times on Qualcomm QNN HTP (Galaxy S23) and MediaTek NeuroPilot (Galaxy M53).
   - Validate that 100% of DiT layers and Vocos ConvNeXt blocks offload to the NPU without falling back to CPU execution.
3. **Phase C: Real-World Battery, Thermal, and Memory Benchmarking**:
   - Continuously synthesize 100 consecutive sentences from `prompts.json` to monitor thermal throttling curves and battery consumption.
   - Continuously profile `/proc/self/status` (`VmRSS`) on the Lenovo Tab K10 to guarantee that peak resident memory remains strictly below 850 MB, avoiding LMK termination.

Chapter 6

Conclusion and Research Summary

6.1 Summary of Research Accomplishments and Milestones

This mid-semester investigation developed, evaluated, and optimized an on-device, zero-shot multilingual neural voice cloning pipeline capable of operating entirely offline on resource-constrained Android mobile hardware. Addressing the lack of Indian language support in edge speech processing, where existing zero-shot engines exclusively target English and Chinese, this project brings native Indian language voice synthesis to commodity mobile platforms.

The primary engineering milestones accomplished during this reporting period include:

1. **Deployment of the English Edge Baseline**: Integrated and benchmarked the ZipVoice-Distill 123M flow-matching model and 24 kHz Vocos vocoder within a Flutter application (`voice_clone_proto`), demonstrating physical memory stability and throughput scaling across Android devices.
2. **Verification of Native Indic Voice Cloning**: Ported and adapted AI4Bharat's 335M Diffusion Transformer (IndicF5) across Tamil, Telugu, Kannada, and Hindi, verifying acoustic speaker adaptation without requiring external grapheme-to-phoneme rule dictionaries.
3. **Formulation of the Syllabic Akshara Duration Model**: Identified and resolved the duration mismatch defect that caused trailing silence and repeated syllables, establishing a calibrated formulation of **6.5 mel frames per Unicode character** ($\approx$ 55 ms per character).
4. **Identification of the Reference Duration Boundary**: Characterized the sequence alignment constraints governing ConvNeXt text representations, demonstrating that reference audio clips must be bounded strictly between **3.5 and 5.0 seconds** to avoid positional attention collapse.

5. **In-Memory Batch Benchmarking Engine and Dataset**: Engineered `batch.py` with warm RAM model caching and curated `prompts.json`, comprising **120 authentic conversational sentences** across Tamil, Telugu, and Hindi stratified across four duration tiers.

6. **Full Model Integer Quantization**: Exported and verified the static INT8 ONNX pipeline, achieving a **74% reduction in model size** (from 1.35 GB FP32 down to 349 MB) for the DiT backbone and quantizing the Vocos vocoder down to 22 MB.

7. **Memory Budget Safety on Edge Devices**: Confirmed that the quantized system bounds operational physical memory to **801 MB**, safely operating below the 1.5 GB *LowMemoryKiller* threshold on 4 GB edge devices like the Lenovo Tab K10.

8. **Formulation of the Google LiteRT Roadmap**: Established the post-midsem roadmap toward Google LiteRT, leveraging the compiled model API to offload matrix operations to Qualcomm Hexagon and MediaTek NPUs.

6.2 Key Scientific, Systems, and Societal Contributions

The technical and humanitarian contributions of this project span three primary dimensions:

6.2.1 Theoretical and Linguistic Contributions

By connecting continuous flow matching with the syllabic structure of Dravidian and Indo-Aryan scripts, this research provides an empirical characterization of akshara frame density for flow-matching TTS. We demonstrated that in-context audio inpainting bridges linguistic families, allowing an English reference voice clip to guide the pitch contour and timbre of native Tamil or Telugu speech without external phonetic dictionaries.

6.2.2 Systems and Edge Deployment Contributions

Through in-kernel physical memory profiling (`/proc/self/status`) across physical silicon tiers, this research demonstrated the empirical reality of the Fixed Overhead Anomaly and established rigorous memory budgets for edge generative AI. We showed that by pairing static INT8 tensor graphs with Fourier-based Inverse STFT neural vocoders (Vocos), deep diffusion models can execute deterministically within the strict memory and compute boundaries of budget edge platforms, safely bounded within 801 MB.

6.2.3 Pedagogical and Accessibility Impact in Untapped Domains

Commercial speech synthesis platforms have predominantly focused on entertainment, commercial assistants, and Western languages, leaving foundational education in vernacular public

schools and special education for visually impaired learners almost completely untapped. This investigation demonstrates how on-device voice cloning addresses these critical societal needs:

1. **Familiar-Voice Learning for Government School Children**: Primary school children in rural and semi-urban government schools exhibit higher listening comprehension and emotional comfort when instruction is delivered in the familiar voice of their local teacher.
2. **Accessible Auditory Learning for Blind Students**: For visually impaired students who rely entirely on auditory channels for academic study, hearing textbook lessons, practice questions, and conceptual explanations articulated in their teacher's voice provides essential pedagogical continuity and cognitive trust.
3. **Economic and Operational Feasibility**: Operating entirely offline on state-subsidized tablets (such as the Lenovo Tab K10) with zero recurring cloud API fees ensures that schools can generate unlimited audio educational aids without fiscal constraints, while protecting the biometric voice privacy of educators and children.

6.3 Concluding Remarks and Immediate Priorities

The work completed during this phase demonstrates that zero-shot multilingual voice cloning can execute fully offline on budget commodity hardware, without transmitting user biometric voice data to remote servers. By tailoring this capability to the untapped domains of vernacular government schools and accessible education for visually impaired students, this project provides a practical pathway for personalized, familiar-voice audio learning at zero marginal infrastructure cost. The technical feasibility of this approach has been substantiated through mathematical formulation, ten consecutive engineering iterations, and physical hardware profiling across four distinct silicon tiers.

The immediate priorities for the post-midsem phase are ordered as follows:

1. **Google LiteRT Migration**: Execute the `litert-torch` PyTorch-to-FlatBuffer conversion and validate numerical parity (MCD $< 3.5\,\text{dB}$) against the PyTorch FP32 baseline.
2. **NPU Hardware Delegation**: Profile and verify 100% DiT operator offloading to Qualcomm QNN HTP (Galaxy S23) and MediaTek NeuroPilot (Galaxy M53).
3. **2-Step Consistency Distillation**: Apply FlashSpeech consistency distillation to reduce the ODE solver from 8 steps to 2 steps, targeting sub-2$\times$ RTF on budget CPU hardware.
4. **Lenovo Tab K10 Benchmarking**: Conduct on-device memory profiling under sustained classroom lesson generation to guarantee RSS $< 850\,\text{MB}$ and zero LMK terminations.
5. **Classroom Accessibility and Dual-Engine UI Integration**: Wire the native IndicF5 Dart FFI service into the Flutter application, integrating large-target controls and

TalkBack accessibility features for pilot evaluations with educators and visually impaired students.

Appendix A

Mathematical Derivations and Numerical Proofs

A.1 Derivation of the Optimal Transport Flow Matching Objective

In this section, we present the complete mathematical derivation demonstrating that regressing the intractable marginal vector field $\mathbf{v}_t(\mathbf{x})$ is equivalent to minimizing the conditional flow matching loss over individual data points, following the formulation established by Lipman et al. [10].

A.1.1 Probability Paths and the Continuity Equation

Let $p_t(\mathbf{x})$ denote a time-dependent probability density function on $\mathbb{R}^d$ for $t \in [0, 1]$. The evolution of $p_t(\mathbf{x})$ driven by a vector field $\mathbf{v}_t(\mathbf{x})$ satisfies the continuity equation:

$$\frac{\partial p_t(\mathbf{x})}{\partial t} = -\nabla \cdot (p_t(\mathbf{x})\mathbf{v}_t(\mathbf{x})) \tag{A.1}$$

Given a target empirical distribution $q(\mathbf{x}_1)$, let $p_t(\mathbf{x} \mid \mathbf{x}_1)$ represent a conditional probability path such that $p_0(\mathbf{x} \mid \mathbf{x}_1) = p_0(\mathbf{x}) = \mathcal{N}(\mathbf{x}; \mathbf{0}, \mathbf{I})$ and $p_1(\mathbf{x} \mid \mathbf{x}_1) \approx \delta(\mathbf{x} - \mathbf{x}_1)$. The marginal probability path is defined by:

$$p_t(\mathbf{x}) = \int_{\mathbb{R}^d} p_t(\mathbf{x} \mid \mathbf{x}_1) q(\mathbf{x}_1) d\mathbf{x}_1 \tag{A.2}$$

Differentiating Equation A.2 with respect to time t:

$$\begin{aligned}\frac{\partial p_t(\mathbf{x})}{\partial t} &= \int_{\mathbb{R}^d} \frac{\partial p_t(\mathbf{x} \mid \mathbf{x}_1)}{\partial t} q(\mathbf{x}_1) d\mathbf{x}_1 \\ &= -\int_{\mathbb{R}^d} \nabla \cdot \left(p_t(\mathbf{x} \mid \mathbf{x}_1)\mathbf{v}_t(\mathbf{x} \mid \mathbf{x}_1)\right) q(\mathbf{x}_1) d\mathbf{x}_1 \\ &= -\nabla \cdot \left(\int_{\mathbb{R}^d} p_t(\mathbf{x} \mid \mathbf{x}_1)\mathbf{v}_t(\mathbf{x} \mid \mathbf{x}_1) q(\mathbf{x}_1) d\mathbf{x}_1\right) \end{aligned} \tag{A.3}$$

Comparing Equation A.3 with the marginal continuity equation Equation A.1, the vector field $\mathbf{v}_t(\mathbf{x})$ is uniquely determined by:

$$p_t(\mathbf{x})\mathbf{v}_t(\mathbf{x}) = \int_{\mathbb{R}^d} p_t(\mathbf{x} \mid \mathbf{x}_1)\mathbf{v}_t(\mathbf{x} \mid \mathbf{x}_1) q(\mathbf{x}_1) d\mathbf{x}_1 \tag{A.4}$$

Dividing both sides by $p_t(\mathbf{x})$ yields:

$$\mathbf{v}_t(\mathbf{x}) = \int_{\mathbb{R}^d} \mathbf{v}_t(\mathbf{x} \mid \mathbf{x}_1) \frac{p_t(\mathbf{x} \mid \mathbf{x}_1) q(\mathbf{x}_1)}{p_t(\mathbf{x})} d\mathbf{x}_1 = \mathbb{E}_{\mathbf{x}_1 \sim q(\mathbf{x}_1 \mid \mathbf{x})} \left[\mathbf{v}_t(\mathbf{x} \mid \mathbf{x}_1)\right] \tag{A.5}$$

A.1.2 Gradient Equivalence of the Loss Objective

The ideal marginal regression loss is given by:

$$\mathcal{L}_{\text{Marginal}}(\theta) = \mathbb{E}_{t \sim U[0,1], \mathbf{x} \sim p_t(\mathbf{x})} \left\|\mathbf{v}_\theta(\mathbf{x}, t) - \mathbf{v}_t(\mathbf{x})\right\|^2 \tag{A.6}$$

Expanding the squared L_2 norm:

$$\left\|\mathbf{v}_\theta(\mathbf{x}, t) - \mathbf{v}_t(\mathbf{x})\right\|^2 = \left\|\mathbf{v}_\theta(\mathbf{x}, t)\right\|^2 - 2\langle \mathbf{v}_\theta(\mathbf{x}, t), \mathbf{v}_t(\mathbf{x})\rangle + \left\|\mathbf{v}_t(\mathbf{x})\right\|^2 \tag{A.7}$$

Now consider the Conditional Flow Matching (CFM) objective:

$$\mathcal{L}_{\text{CFM}}(\theta) = \mathbb{E}_{t, \mathbf{x}_1 \sim q(\mathbf{x}_1), \mathbf{x} \sim p_t(\mathbf{x} \mid \mathbf{x}_1)} \left\|\mathbf{v}_\theta(\mathbf{x}, t) - \mathbf{v}_t(\mathbf{x} \mid \mathbf{x}_1)\right\|^2 \tag{A.8}$$

Expanding the expectation:

$$\begin{aligned}\mathcal{L}_{\text{CFM}}(\theta) = &\int_0^1 \int\int \left\|\mathbf{v}_\theta(\mathbf{x}, t)\right\|^2 p_t(\mathbf{x} \mid \mathbf{x}_1) q(\mathbf{x}_1) d\mathbf{x} d\mathbf{x}_1 dt \\ &- 2\int_0^1 \int\int \langle \mathbf{v}_\theta(\mathbf{x}, t), \mathbf{v}_t(\mathbf{x} \mid \mathbf{x}_1)\rangle p_t(\mathbf{x} \mid \mathbf{x}_1) q(\mathbf{x}_1) d\mathbf{x} d\mathbf{x}_1 dt \\ &+ C_1 \end{aligned} \tag{A.9}$$

where $C_1 = \mathbb{E}[\|\mathbf{v}_t(\mathbf{x} \mid \mathbf{x}_1)\|^2]$ is independent of the model parameters θ.

Applying Equation A.4 to the second term:

$$\begin{aligned}\int\int\langle\mathbf{v}_\theta(\mathbf{x},t),\mathbf{v}_t(\mathbf{x}\mid\mathbf{x}_1)\rangle p_t(\mathbf{x}\mid\mathbf{x}_1)q(\mathbf{x}_1)d\mathbf{x}_1d\mathbf{x} &= \int\langle\mathbf{v}_\theta(\mathbf{x},t),\int\mathbf{v}_t(\mathbf{x}\mid\mathbf{x}_1)p_t(\mathbf{x}\mid\mathbf{x}_1)q(\mathbf{x}_1)d\mathbf{x}_1\rangle d\mathbf{x}\\ &= \int\langle\mathbf{v}_\theta(\mathbf{x},t),p_t(\mathbf{x})\mathbf{v}_t(\mathbf{x})\rangle d\mathbf{x}\\ &= \mathbb{E}_{\mathbf{x}\sim p_t(\mathbf{x})}\left[\langle\mathbf{v}_\theta(\mathbf{x},t),\mathbf{v}_t(\mathbf{x})\rangle\right] \end{aligned} \tag{A.10}$$

Similarly, the first term evaluates to:

$$\int\int\|\mathbf{v}_\theta(\mathbf{x},t)\|^2 p_t(\mathbf{x}\mid\mathbf{x}_1)q(\mathbf{x}_1)d\mathbf{x}_1d\mathbf{x} = \mathbb{E}_{\mathbf{x}\sim p_t(\mathbf{x})}\left[\|\mathbf{v}_\theta(\mathbf{x},t)\|^2\right] \tag{A.11}$$

Therefore:

$$\mathcal{L}_{\text{CFM}}(\theta) = \mathcal{L}_{\text{Marginal}}(\theta) + C(\mathbf{x}_1) \tag{A.12}$$

Consequently, their gradients with respect to network parameters θ are identically equal:

$$\nabla_\theta\mathcal{L}_{\text{CFM}}(\theta) \equiv \nabla_\theta\mathcal{L}_{\text{Marginal}}(\theta) \tag{A.13}$$

This confirms that optimizing the conditional objective over individual training samples yields parameter gradients identical to those of the marginal generative flow.

A.2 Analytical Formulation of the Inverse STFT with Window Overlap-Add

Let $\mathbf{Z}(k,m) \in \mathbb{C}$ denote the synthesized discrete complex Fourier matrix at frequency bin $k \in [0, N_{\text{fft}}-1]$ and time frame $m \in \mathbb{Z}$. The one-dimensional Inverse Discrete Fourier Transform (IDFT) of each individual column frame is:

$$z_m(n) = \frac{1}{N_{\text{fft}}}\sum_{k=0}^{N_{\text{fft}}-1}\mathbf{Z}(k,m)e^{j\frac{2\pi}{N_{\text{fft}}}kn}, \quad n \in [0, N_{\text{fft}}-1] \tag{A.14}$$

Each frame is weighted by a periodic synthesis Hanning window $w(n)$:

$$w(n) = 0.5\left(1-\cos\left(\frac{2\pi n}{N_{\text{fft}}}\right)\right), \quad n \in [0, N_{\text{fft}}-1] \tag{A.15}$$

The time-domain output $y(n)$ is reconstructed via the Weighted Overlap-Add (WOLA) method with frame hop $H = 256$:

$$y(n) = \frac{\sum_{m=-\infty}^{\infty} z_m(n-mH)w(n-mH)}{\sum_{m=-\infty}^{\infty} w^2(n-mH)} \tag{A.16}$$

When the synthesis window satisfies the Principle of Perfect Reconstruction:

$$\sum_{m=-\infty}^{\infty} w^2(n - mH) = C_{\text{norm}} \quad \forall\, n \tag{A.17}$$

the denominator in Equation A.16 evaluates to a constant scalar, allowing the reconstruction to be computed in linear time $O(M \cdot N_{\text{fft}} \log N_{\text{fft}})$ using ARM NEON vector instructions.

Appendix B

Multilingual Phonetic Evaluation Prompts Dataset

B.1 Dataset Architecture and Stratification Methodology

To evaluate voice cloning fidelity, articulation clarity, and edge execution throughput under controlled experimental conditions, we curated the standardized dataset `prompts.json`. The corpus comprises 120 phonetically balanced conversational sentences distributed across Tamil, Telugu, and Hindi (40 phrases per language).

To quantify temporal scaling dynamics and verify our syllabic duration formula across diverse utterance lengths, the corpus is stratified into four standardized duration tiers:

1. **Short Tier** ($\sim$ 4–7 words): Everyday inquiries, greetings, and brief conversational exchanges.
2. **Medium Tier** ($\sim$ 12–18 words): Single-clause sentences conveying social activities and observations.
3. **Midlong Tier** ($\sim$ 20–25 words): Compound descriptive sentences containing coordinate clauses.
4. **Long Tier** ($\sim$ 28–35 words): Complex narrative sentences designed to stress-test attention mechanisms and RAM allocations.

B.2 Telugu Dataset Inventory

Table B.1 documents representative Telugu evaluation prompts across standardized duration tiers, displaying the native Telugu script along with English semantic translations.

Table B.1: Curated Telugu Evaluation Prompts across Standardized Tiers

Tier	Target Utterance (Telugu Script)	English Semantic Translation
Short 1	నువ్వు భోజనం చేశావా?	Have you had your meal?
Short 2	ఈరోజు వాతావరణం చాలా బాగుంది.	The weather is very pleasant today.
Short 3	రేపు సాయంత్రం కలుద్దామా?	Shall we meet tomorrow evening?
Short 4	నాకు కాసిన్ని నీళ్లు కావాలి.	I need some water, please.
Short 5	ఇంటికి వెళ్లే సైం అయ్యింది.	It is time to head back home.
Short 6	ఈ పుస్తకం చదవడం నాకు నచ్చింది.	I enjoyed reading this book.
Short 7	అందరూ బాగున్నారా?	Is everyone doing well?
Medium 1	చాలా రోజుల తర్వాత నిన్ను చూడటం చాలా సంతోషంగా ఉంది.	I am glad to see you after such a long time.
Medium 2	ఈరోజు ఉదయం నుండి చల్లగా ఉంది, వర్షం వచ్చేలా ఉంది.	It has been cool since morning; it looks like rain.
Medium 3	మా ఊర్లో పండగ సైంలో అందరూ చాలా ఉత్సాహంగా ఉంటారు.	Everyone in our village is energetic during festival time.
Medium 4	పిల్లలు తోటలో పువ్వులు చూస్తూ సంతోషంగా ఆడుకుంటున్నారు.	Children are happily playing in the garden admiring flowers.
Midlong 1	ప్రతిరోజూ ఉదయం లేచి కొంచెం సేపు నడిస్తే రోజంతా చురుగ్గా, ఆరోగ్యంగా ఉంటుంది.	Walking every morning keeps one active and healthy throughout the day.
Midlong 2	మా ఊరి చెరువు దగ్గర పచ్చని పొలాలు, తాటి చెట్లు, పక్షుల అరుపులు చూస్తుంటే మనసుకి చాలా బాగుంటుంది.	The green fields, palm trees, and birds by our village pond are delightful.
Long 1	మన కుటుంబంలో అందరం కలిసి పండగలు చేసుకోవడం వల్ల మన మధ్య అనుబంధం ఇంకా బలంగా అవుతుంది.	Celebrating festivals together strengthens our family bonds.
Long 2	రైతులు ఎండైనా వానైనా లెక్క చేయకుండా పొలంలో కష్టపడి పని చేస్తారు కాబట్టే మనందరికీ తినడానికి తిండి దొరుకుతుంది.	Because farmers work tirelessly through sun and rain, we have food to eat.

B.3 Tamil Dataset Inventory

Table B.2 documents representative Tamil evaluation prompts across standardized duration tiers, displaying the native Tamil script along with English semantic translations.

B.4 Hindi Dataset Inventory

Table B.3 documents representative Hindi evaluation prompts across standardized duration tiers, displaying the native Devanagari script along with English semantic translations.

Table B.2: Curated Tamil Evaluation Prompts across Standardized Tiers

Tier	**Target Utterance (Tamil Script)**	**English Semantic Translation**
Short 1	நீ நலமா இருக்கியா?	Are you doing well?
Short 2	இன்று மாலை கடற்கரைக்குப் போவோமா?	Shall we go to the beach this evening?
Short 3	எனக்கு கொஞ்சம் தண்ணி வேணும்.	I need some drinking water.
Short 4	இந்த புத்தகம் ரொம்ப நல்லா இருக்கு.	This book is very good.
Short 5	நேரத்த வீணடிக்க கூடாது.	We should not waste our time.
Short 6	வீட்டுக்குப் போக நேரமாச்சு.	It is time to head back home.
Short 7	உன்னைப் பார்த்ததுல ரொம்ப சந்தோஷம்.	I am very glad to see you.
Medium 1	நீண்ட நாளுக்கு அப்புறம் உன் குரலக் கேட்டது ரொம்ப சந்தோஷமா இருக்கு.	Hearing your voice after a long time brings great joy.
Medium 2	இன்று காலையிலிருந்து குளிர் காத்து வீசுது, மழை வரலாம் போல.	A cool breeze has been blowing since morning; it looks like rain.
Medium 3	தோட்டத்துல பூக்கள் மலர்ந்து இருக்கு, வீடு முழுக்க வாசனை.	Flowers have bloomed in the garden, filling the house with fragrance.
Medium 4	குழந்தைங்க மாலையில ஒண்ணா சேர்ந்து விளையாடுறது பார்க்க நல்லா இருக்கு.	Watching children play together in the evening is lovely.
Midlong 1	தினமும் காலையில எழுந்து கொஞ்ச நேரம் நடந்தா, நாள் முழுக்க உடம்பு லேசா இருக்கும்.	Walking a bit every morning keeps the body feeling refreshed throughout the day.
Midlong 2	எங்க ஊரு வயல் வெளி, பனை மரங்கள், பறவைகளோட சத்தம் எல்லாம் ரொம்ப அழகா இருக்கும்.	The open fields, palm trees, and birds in our village are scenic.
Long 1	நம்ம குடும்பத்துல எல்லாரும் சேர்ந்து பண்டிகை கொண்டாடுறது நம்ம பந்தத்த இன்னும் பலமா ஆக்கும்.	Celebrating festivals together strengthens our family ties.
Long 2	விவசாயிகள் வெயில், மழை பாக்காம இரவு பகலா உழைக்கிறதால தான் நமக்கு சாப்பாடு கிடைக்குது, அவங்கள மதிக்கணும்.	Because farmers labor day and night regardless of heat or rain, we have food to eat.

Table B.3: Curated Hindi Evaluation Prompts across Standardized Tiers

Tier	**Target Utterance (Devanagari Script)**	**English Semantic Translation**
Short 1	तुम कैसे हो?	How are you doing?
Short 2	आज शाम घूमने चलें?	Shall we go out for a walk this evening?
Short 3	मुझे थोड़ा पानी चाहिए।	I would like some water.
Short 4	यह किताब बहुत अच्छी है।	This book is very good.
Short 5	समय बर्बाद नहीं करना चाहिए।	We should not waste time.
Short 6	घर जाने का समय हो गया।	It is time to head back home.
Short 7	तुमसे मिलकर अच्छा लगा।	It was pleasant meeting you.
Medium 1	इतने दिनों बाद तुमसे बात करके बहुत अच्छा लग रहा है।	It feels wonderful speaking with you after so many days.
Medium 2	आज सुबह से ठंडी हवा चल रही है, लगता है बारिश आएगी।	Cool breeze has been blowing since morning; it seems rain is coming.
Medium 3	बगीचे में फूल खिले हैं, पूरा घर महक रहा है।	Flowers are blooming in the garden, and the whole house smells fresh.
Medium 4	शाम को बच्चों को साथ खेलते देखना अच्छा लगता है।	Watching children play together in the evening is heartwarming.
Midlong 1	रोज सुबह उठकर थोड़ी देर टहलने से पूरे दिन शरीर हल्का और तरोताज़ा रहता है।	Walking a little every morning keeps the body active and fresh all day.
Midlong 2	गाँव के खेत, पेड़ और पक्षियों की आवाज़ें मन को बहुत सुकून देती हैं।	The village fields, trees, and chirping birds bring peace of mind.
Long 1	हमारे घर में सब मिलकर त्योहार मनाते हैं, इससे हमारा आपसी रिश्ता और मजबूत होता है।	Celebrating festivals together as a family deepens our mutual relationships.
Long 2	किसान धूप और बारिश की परवाह किए बिना दिन-रात मेहनत करते हैं, इसी वजह से हमें खाना मिलता है, इसलिए उनका सम्मान करना चाहिए।	Because farmers work tirelessly day and night regardless of sun or rain, we have food.

Bibliography

[1] Jaehyeon Kim, Jungil Kong, and Juhee Son. Conditional variational autoencoder with adversarial learning for end-to-end text-to-speech. In *International Conference on Machine Learning (ICML)*, pages 5530–5540, 2021.

[2] Jungil Kong, Jaehyeon Kim, and Jaekyoung Bae. HiFi-GAN: Generative adversarial networks for efficient and high fidelity speech synthesis. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, pages 17022–17033, 2020.

[3] Matthew Le, Apoorv Vyas, Bowen Shi, Brian Karrer, Leda Sari, Rasmus Moritz, Mary Williamson, Vimal Manohar, Yossi Adi, Jay Mahadeokar, and Wei-Ning Hu. Voicebox: Text-guided multilingual universal speech generation at scale. *arXiv preprint arXiv:2306.15687*, 2023.

[4] E2 TTS Authors. E2 TTS: Fully non-autoregressive zero-shot text-to-speech. *arXiv preprint arXiv:2406.18009*, 2024.

[5] Yushen Chen, Zhikang Niu, Ziyang Ma, Keqi Liu, Guanrou Zhao, Kai Shen, Chenpeng Lin, Zhijun Wang, Xie Chen, and Heng Lu. F5-TTS: A fairytaler that fakes fluent and faithful speech with flow matching. *arXiv preprint arXiv:2410.06885*, 2024.

[6] Edress Casanova, Kelly Weber, Christopher Shulby, et al. XTTS: Massively multilingual voice cloning with latent diffusion and autoregressive priors. *arXiv preprint arXiv:2406.04904*, 2024.

[7] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30, 2017.

[8] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems (NeurIPS)*, 33:6840–6851, 2020.

[9] Yang Song, Jascha Sohl-Dickstein, Diederik P. Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International Conference on Learning Representations (ICLR)*, 2021.

[10] Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nicklas, and Matt Le. Flow matching for generative modeling. *arXiv preprint arXiv:2210.02747*, 2022.

[11] William Peebles and Saining Xie. Scalable diffusion models with transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 4195–4205, 2023.

[12] Hubert Siuzdak. Vocos: Closing the gap between neural vocoders and fourier-based audio synthesis. *arXiv preprint arXiv:2306.00814*, 2023.

[13] Jonathan Ho and Tim Salimans. Classifier-free diffusion guidance. *arXiv preprint arXiv:2207.12598*, 2022.

[14] Xingchao Liu, Chengyue Gong, and Qiang Liu. Flow straight and fast: Learning to generate and transfer data with rectified flow. *arXiv preprint arXiv:2209.03003*, 2022.

[15] Zhen Zhang et al. Flashspeech: Efficient zero-shot speech synthesis. *arXiv preprint arXiv:2404.14700*, 2024.

[16] Tahir Javed, Sumanth Doddapaneni, Abhigyan Raman, Kaushal Seshadri, Pratyush Kumar, and Mitesh M. Khapra. Indicvoices: Towards building an inclusive multilingual speech dataset for indian languages. *arXiv preprint arXiv:2403.07639*, 2024.

[17] S. V. Praveen, Srija Anand, Soma Siddhartha, and Mitesh M. Khapra. Phir hera fairy: An english fairytaler is a strong faker of fluent speech in low-resource indian languages. *arXiv preprint arXiv:2505.20693*, 2025.

[18] Next-gen Kaldi Team. Sherpa-onnx: Next-gen kaldi on-device speech recognition and synthesis. `https://github.com/k2-fsa/sherpa-onnx`, 2023.

[19] Microsoft Corporation. ONNX Runtime: Cross-platform, high performance scoring engine for ML models. *GitHub Repository*, 2021.

[20] Google AI Edge Team. Litert: Unified on-device machine learning framework. `https://ai.google.dev/edge/litert`, 2024.

[21] Google AI Edge Team. Litert torch: High performance pytorch on-device deployment. `https://github.com/google-ai-edge/litert-torch`, 2024.

[22] Qualcomm Technologies, Inc. Qualcomm AI engine direct (QNN) software development kit. `https://developer.qualcomm.com/software/qualcomm-ai-engine-direct-sdk`, 2024.

[23] MediaTek Inc. Mediatek NeuroPilot edge AI platform architecture and software toolkit. `https://neuropilot.mediatek.com/`, 2024.