

CODE

```
%{
#include <stdio.h>
#include <string.h>
int keywords=0, identifiers=0;
}%

%%
"int"|"float"|"char"|"while"|"if"|"else"    { keywords++;
printf("Keyword : %s\n", yytext); }

[a-zA-Z_][a-zA-Z0-9_]*                        { identifiers++;
printf("Identifier : %s\n", yytext); }

[ \t\n]+                                     ; /* ignore
spaces/newlines */

.                                             ; /* ignore anything
else */

%%

int yywrap() { return 1; }

int main() {
    printf("Enter C code:\n");
    yylex();
    printf("\nTotal Keywords = %d\n", keywords);
    printf("Total Identifiers = %d\n", identifiers);
    return 0;
}
```

```
C:\Windows\System32\cmd.e  X  +  v
Command Prompt: C:\Windows\System32\cmd.exe
ctrl+alt+1
C:\Compiler>set path=C:\Program Files (x86)\GnuWin32\bin

C:\Compiler>flex EXP_29.l

C:\Compiler>set path=C:\Program Files\CodeBlocks\MinGW\bin

C:\Compiler>gcc lex.yy.c

C:\Compiler>a.exe
Enter C code:
int x;
Keyword : int
Identifier : x
int x;
Keyword : int
Identifier : x
float marks;
Keyword : float
Identifier : marks
while(x < 10) x++;
Keyword : while
Identifier : x
Identifier : x
^Z

Total Keywords = 4
Total Identifiers = 5

C:\Compiler>
```