



PlaySBC

Product and Administration Guide

Features, architecture, deployment, operations, regression, and evidence

Version 2.6.0

Public v2.6.0 and private commercial build tracks

Contributor

Sudheer Kumar Vatrappu

Contents

Contents	2
Document Control	2
Common Local Preparation	3
Public v2.6.0 Release Upgrade	4
Public Source Build And Upgrade	5
Private Commercial Build And Upgrade	6
Private Commercial RFC 5359 Regression	7
Evidence, Prometheus, And Grafana	8
Troubleshooting	9
Detailed Runbooks	10

Document Control

Track	Repository	Artifact identity
Public release	PlaySBC	Published 2.6.0 images and chart
Public source	PlaySBC	Local commit SHA
Private commercial	PlaySBC-Commercial	playsbc-commercial-dev:<commit>

This curated guide does not embed the standalone Markdown runbooks. They remain maintained independently under docs/. The browser edition provides COPY buttons; PDF viewers keep command text selectable but cannot access the system clipboard.

Common Local Preparation

COMMAND

SELECT + COPY

```
set -euo pipefail
export KUBE_CONTEXT=kind-playsbc
export KIND_CLUSTER=playsbc
open -a Docker
until docker info >/dev/null 2>&1; do echo "Waiting for Docker Desktop..."; sleep 5; done
if ! kind get clusters | grep -qx "$KIND_CLUSTER"; then
  kind create cluster --name "$KIND_CLUSTER" --wait 180s
fi
kubectl --context "$KUBE_CONTEXT" get --raw=/readyz
kubectl --context "$KUBE_CONTEXT" create namespace playsbc --dry-run=client -o yaml \
| kubectl --context "$KUBE_CONTEXT" apply -f -
```

Public v2.6.0 Release Upgrade

COMMAND

SELECT + COPY

```
cd /Users/sudheerkumar/Documents/Codex/2026-05-18/Mini-Call-Server
export PLAYSBC_VERSION=2.6.0
export KUBE_CONTEXT=kind-playsbc
helm upgrade --install playsbc \
  "https://github.com/sudheerkumarvatrapu/PlaySBC/releases/download/v${PLAYSBC_VERSION}/playsbc-${PLAYSBC_VERSION}.tgz" \
  --kube-context "$KUBE_CONTEXT" --namespace playsbc --create-namespace \
  --atomic --wait --timeout 10m \
  -f configs/kubernetes/active-active-values.yaml \
  --set image.repository=ghcr.io/sudheerkumarvatrapu/playsbc \
  --set-string image.tag="$PLAYSBC_VERSION" --set image.pullPolicy=Always \
  --set rtpengine.enabled=true \
  --set rtpengine.image.repository=ghcr.io/sudheerkumarvatrapu/playsbc-rtpengine \
  --set-string rtpengine.image.tag="$PLAYSBC_VERSION" \
  --set rtpengine.image.pullPolicy=Always --set observability.enabled=true
kubectl --context "$KUBE_CONTEXT" -n playsbc get pods -o wide
```

Public Source Build And Upgrade

COMMAND	SELECT + COPY
<pre>cd /Users/sudheerkumar/Documents/Codex/2026-05-18/Mini-Call-Server git switch main && git pull --ff-only origin main export SOURCE_TAG=\$(git rev-parse --short=12 HEAD) export PLAYSBC_REPOSITORY=playsbc-public-dev export PLAYSBC_IMAGE="\${PLAYSBC_REPOSITORY}:\${SOURCE_TAG}" docker build -f docker/playsbc.Dockerfile -t "\$PLAYSBC_IMAGE" . kind load docker-image "\$PLAYSBC_IMAGE" --name playsbc helm upgrade --install playsbc charts/playsbc --kube-context kind-playsbc \ --namespace playsbc --create-namespace --reuse-values --atomic --wait --timeout 10m \ --set image.repository="\$PLAYSBC_REPOSITORY" --set-string image.tag="\$SOURCE_TAG" \ --set image.pullPolicy=IfNotPresent</pre>	

Run the full public source catalog:

COMMAND	SELECT + COPY
<pre>PYTHONPYCACHEPREFIX=/private/tmp/playsbc-public-pycache \ python3 tools/run_k8s_regression_job.py --all-profiles \ --build-playsbc-image --build-runner-image --build-sipp-image \ --build-rtpengine-image --kind-load-images --set-playsbc-image \ --set-rtpengine-image --kind-cluster playsbc</pre>	

Private Commercial Build And Upgrade

This track creates local development artifacts only; it does not publish a commercial release.

COMMAND	SELECT + COPY
<pre>cd /Users/sudheerkumar/Documents/Codex/2026-05-18/PlaySBC-Commercial git switch main && git pull --ff-only origin main test -z "\$(git status --porcelain)" export SOURCE_TAG=\$(git rev-parse --short=12 HEAD) export PLAYSBC_REPOSITORY=playsbc-commercial-dev export PLAYSBC_IMAGE="\${PLAYSBC_REPOSITORY}:\${SOURCE_TAG}" docker build -f docker/playsbc.Dockerfile -t "\$PLAYSBC_IMAGE" . kind load docker-image "\$PLAYSBC_IMAGE" --name playsbc export PACKAGE_DIR=\$(mktemp -d /private/tmp/playsbc-commercial-package.XXXXXX) export CHART_VERSION=\$(awk '/^version:/ {print \$2; exit}' charts/playsbc/Chart.yaml) export PLAYSBC_CHART="\${PACKAGE_DIR}/playsbc-\${CHART_VERSION}.tgz" helm lint charts/playsbc helm package charts/playsbc --destination "\$PACKAGE_DIR" helm upgrade --install playsbc "\$PLAYSBC_CHART" --kube-context kind-playsbc \ --namespace playsbc --create-namespace --reuse-values --atomic --wait --timeout 10m \ --set image.repository="\$PLAYSBC_REPOSITORY" --set-string image.tag="\$SOURCE_TAG" \ --set image.pullPolicy=IfNotPresent kubectl --context kind-playsbc -n playsbc rollout status \ statefulset/playsbc-playsbc --timeout=240s</pre>	

Private Commercial RFC 5359 Regression

COMMAND

SELECT + COPY

```
PYTHONPYCACHEPREFIX=/private/tmp/playsbc-commercial-pycache \  
python3 tools/run_commercial_foundation_regression.py  
  
PYTHONPYCACHEPREFIX=/private/tmp/playsbc-commercial-pycache \  
python3 tools/run_k8s_regression_job.py \  
--profile rfc5359-call-hold-resume \  
--profile rfc5359-call-hold-resume-rtpengine \  
--profile rfc5359-call-hold-resume-tcp \  
--profile rfc5359-call-hold-resume-tls \  
--profile rfc5359-unattended-transfer \  
--profile rfc5359-unconditional-forwarding \  
--profile rfc5359-forwarding-on-busy \  
--profile rfc5359-forwarding-on-no-answer \  
--profile rfc5359-unattended-transfer-rtpengine \  
--profile rfc5359-unconditional-forwarding-rtpengine \  
--profile rfc5359-forwarding-on-busy-rtpengine \  
--profile rfc5359-forwarding-on-no-answer-rtpengine \  
--playsbc-image "$PLAYSBC_IMAGE" --set-playsbc-image --no-load-playsbc-image \  
--build-runner-image --build-sipp-image --kind-load-images --kind-cluster playsbc
```

Evidence, Prometheus, And Grafana

COMMAND

SELECT + COPY

```
LATEST_REPORT=$(find logs/k8s-job -path '*/k8s-reports/latest.html' -type f | sort | tail -1)
: "${LATEST_REPORT:?No report found}"
open "$LATEST_REPORT"
```

Keep `latest.html` with its `evidence/` directory. If local links are blocked:

COMMAND

SELECT + COPY

```
python3 tools/serve_regression_report.py "$LATEST_REPORT"
```

COMMAND

SELECT + COPY

```
kubectl --context kind-playsbc -n playsbc port-forward \
  svc/playsbc-playsbc-prometheus 9090:9090
```

COMMAND

SELECT + COPY

```
kubectl --context kind-playsbc -n playsbc port-forward \
  svc/playsbc-playsbc-grafana 3000:3000
```

Open Prometheus at `http://127.0.0.1:9090`. Open Grafana at `http://127.0.0.1:3000` with admin / playsbc-lab.

Troubleshooting

- Root Dockerfile missing: always use `-f docker/playsbc.Dockerfile`.
- `--rollback-on-failure` unknown: use `--atomic` with the installed Helm.
- kind API refused: start Docker and `docker start playsbc-control-plane`.
- `ImagePullBackOff`: reload the exact image and retain `IfNotPresent`.
- Helm failure: inspect status, history, pod logs, and timestamp-sorted events.
- Broken report links: preserve the entire report directory or use its server.

COMMAND	SELECT + COPY
<pre>helm --kube-context kind-playsbc -n playsbc status playsbc helm --kube-context kind-playsbc -n playsbc history playsbc kubectl --context kind-playsbc -n playsbc get events --sort-by=.lastTimestamp kubectl --context kind-playsbc -n playsbc get pods -o wide</pre>	

Detailed Runbooks

These remain standalone and are not embedded in either generated guide: AZURE_AKS.md, KUBERNETES_HELM_RUNBOOK.md, KUBERNETES_LOCAL.md, REAL_DEVICE_LAB.md, RTPENGINE_LOCAL.md, OBSERVABILITY.md, AI_VOICE_GATEWAY.md, BUSINESS_CALLING_SERVICES.md, and EVOLUTION_PLAN.md.