



PeopleSoft Project Insights — XYZ_TRACE_UTILITY

Technical Developer Reference • App Designer XML Parser

Generated: 6/13/2026, 11:53:42 PM | 28 of 28 objects | All objects (no filter)

#	OBJECT TYPE	NAME / KEY 1	KEY 2	KEY 3/4	SRC STATUS	TGT STATUS	ACTION	TAKE?	DONE?
1	Record	XYZ_TRC_UTL_DVW			Custom Changed	Absent	Copy	Yes	Yes
Updated By: QI8AUpdated At: 2021-01-15-19.29.11.820238Source: Record View SQLType: Dynamic ViewFields: 5Descr: Trace Utility (XYZ) * Do not Migrate * This is Custom Trace Utility, should not be migrated to Any other environment without consulting the AppTech support team.									
◆ SQL — Record View SQL: XYZ_TRC_UTL_DVW									
SELECT ' ' , ' ' , ' ' , ' ' , ' ' , ' ' FROM %Table (INSTALLATION)									
2	Record	XYZ_TRC_UTL_WRK			Custom Changed	Absent	Copy	Yes	Yes
Updated By: QI8AUpdated At: 2021-11-03-15.48.06.323894Type: DerivedFields: 13Descr: Trace Utility (XYZ) * Do not Migrate * This is Custom Trace Utility, should not be migrated to Any other environment without consulting the AppTech support team.									
3	Record	WEBLIB_TRC_XYZ			Custom Changed	Absent	Copy	Yes	Yes
Updated By: QI8AUpdated At: 2021-01-15-19.29.12.820491Type: DerivedFields: 1									
4	Field	ENV_NAME_XYZ			Custom Changed	Absent	Copy	Yes	Yes
Updated By: QI8AUpdated At: 2021-01-15-19.29.13.819977Type: 0 = CharacterLength: 4Long Name: Environment * Do not Migrate * This is Custom Trace Utility, should not be migrated to Any other environment without consulting the AppTech support team.									
5	Translate	ENV_NAME_XYZ	DBG1	2021-10-04	Custom Changed	Absent	Copy	Yes	Yes
Label: FSTLSDBG1Status: Active									
6	Translate	ENV_NAME_XYZ	DBG2	2021-10-04	Custom Changed	Absent	Copy	Yes	Yes
Label: FSTLSDBG2Status: Active									
7	Translate	ENV_NAME_XYZ	DBG3	2021-10-04	Custom Changed	Absent	Copy	Yes	Yes
Label: FSTLSDBG3Status: Active									
8	Translate	ENV_NAME_XYZ	DBH	2017-01-01	Custom Changed	Absent	Copy	Yes	Yes

#	OBJECT TYPE	NAME / KEY 1	KEY 2	KEY 3/4	SRC STATUS	TGT STATUS	ACTION	TAKE?	DONE?
Label: FSDBH Status: Active									
9	Translate	ENV_NAME_XYZ	DBI	2019-08-28	Absent	Absent	None	No	No
10	Translate	ENV_NAME_XYZ	DBK	2021-01-28	Custom Changed	Absent	Copy	Yes	Yes
Label: FSDBK Status: Active									
11	Translate	ENV_NAME_XYZ	DBT	2017-01-01	Absent	Absent	None	No	No
12	Translate	ENV_NAME_XYZ	DBV	2021-02-22	Custom Changed	Absent	Copy	Yes	Yes
Label: FSDBV Status: Active									
13	Translate	ENV_NAME_XYZ	GCC	2019-09-03	Custom Changed	Absent	Copy	Yes	Yes
Label: FSGCC Status: Active									
14	Translate	ENV_NAME_XYZ	TLS	2020-04-14	Custom Changed	Absent	Copy	Yes	Yes
Label: FSTLS Status: Active									
15	Page	TRC_UTIL_XYZ			Custom Changed	Absent	Copy	Yes	Yes
Updated By: QI8A Updated At: 2021-10-04-18.27.15.700352 Type: Standard Page Fields: 10									
* Do not Migrate * This is Custom Trace Utility, should not be migrated to Any other environment without consulting the AppTech support team.									
16	Menu	MENU_TRC_DEV_XYZ			Custom Changed	Absent	Copy	Yes	Yes
* Do not Migrate. Only for Config environment* This is Custom Trace Utility, should not be migrated to Any other environment without consulting the AppTech support team.									
17	Component	TRC_UTIL_XYZ	GBL		Custom Changed	Absent	Copy	Yes	Yes
Updated By: QI8A Actions: Update/Display Pages: 1 Market: GBL									
* Do not Migrate * This is Custom Trace Utility, should not be migrated to Any other environment without consulting the AppTech support team.									
18	Record PeopleCode	XYZ_TRC_UTL_DVW	DELETE_PB	FieldChange	Custom Changed	Absent	Copy	Yes	Yes
Updated By: QI8A Updated At: 2021-01-15-19.29.15.820482 Source: PeopleCode Event: FieldChange									

#	OBJECT TYPE	NAME / KEY 1	KEY 2	KEY 3/4	SRC STATUS	TGT STATUS	ACTION	TAKE?	DONE?
---	-------------	--------------	-------	---------	------------	------------	--------	-------	-------

 PeopleCode — XYZ_TRC_UTL_DVW > VIEW_PB > FieldChange

```
If %UserId = "QI8A" Or
    %UserId = "QI8A" Then

    Local string &rncntrl;
    Local ProcessRequest &procRqst;
    Local Record &recRun, &recParm;
    Local string &strBindValue;

    /* delete the old file in /tmp before copying the new file in */
    &fileTrace = GetFile("/tmp/" | XYZ_TRC_UTL_DVW.DESCR125.Value, "r", %FilePath_Absolute);
    If &fileTrace <> Null Then
        &fileTrace.Delete();
    End-If;

    /* copy the trace file to /tmp */
    &ExitCode = Exec("cp " | XYZ_TRC_UTL_DVW.DESCR254.Value | " /tmp", %Exec_Synchronous + %FilePath_Absolute);
    rem WinMessage("&ExitCode=" | &ExitCode);

    &rncntrl = "TRC_DUMP_XYZ";
    &strBindValue = XYZ_TRC_UTL_DVW.DESCR125.Value;

    &recRun = CreateRecord(Record.AEREQUESTBL);

    /*Create run control */
    &recRun.OPRID.Value = %OperatorId;
    &recRun.RUN_CNTL_ID.Value = &rncntrl;
    &recRun.AE_APPLID.Value = "TRC_DUMP_XYZ";

    If &recRun.SelectByKey() Then
        &recRun.Update();
    Else
        &recRun.OPRID.Value = %OperatorId;
        &recRun.RUN_CNTL_ID.Value = &rncntrl;
        &recRun.AE_APPLID.Value = "TRC_DUMP_XYZ";
        &recRun.Insert();
    End-If;

    &recParm = CreateRecord(Record.AEREQUESTPARM);

    /*Create run control parameters for equity id*/
    &recParm.OPRID.Value = %OperatorId;
    &recParm.RUN_CNTL_ID.Value = &rncntrl;
    &recParm.AE_APPLID.Value = "TRC_DUMP_XYZ";
    &recParm.AE_STATE_RECNAME.Value = "XYZ_TRC_DMP_AET";
    &recParm.AE_BIND_VAR.Value = "DESCR125";

    If &recParm.SelectByKey() Then
        &recParm.AE_BIND_VALUE.Value = &strBindValue;
        &recParm.Update();
    Else
        &recParm.OPRID.Value = %OperatorId;
        &recParm.RUN_CNTL_ID.Value = &rncntrl;
        &recParm.AE_APPLID.Value = "TRC_DUMP_XYZ";
        &recParm.AE_STATE_RECNAME.Value = "XYZ_TRC_DMP_AET";
        &recParm.AE_BIND_VAR.Value = "DESCR125";
        &recParm.AE_BIND_VALUE.Value = &strBindValue;
        &recParm.Insert();
    End-If;

    &procRqst = CreateProcessRequest();
    &procRqst.ProcessType = "Application Engine";
    &procRqst.ProcessName = "TRC_DUMP_XYZ";
    &procRqst.RunControlID = &recParm.RUN_CNTL_ID.Value;
    &procRqst.RunLocation = "PSUNX"; /* server name */
    &procRqst.Schedule();

    If &procRqst.Status <> 0 Then
        MessageBox(0, "", 9999, 999, "ERROR!!! TRC_DUMP_XYZ Failed");
        Exit (1);
    Else
        MessageBox(0, "", 9999, 999, "TRC_DUMP_XYZ has been invoked, check the process status from Process Monitor %1.", &procRqst.ProcessInstanc
e);
    End-If;
```

#	OBJECT TYPE	NAME / KEY 1	KEY 2	KEY 3/4	SRC STATUS	TGT STATUS	ACTION	TAKE?	DONE?
<pre><*- REM Delete existing runcntlid; SQLExec("Delete from psprcsruncntl where oprid = :1 and runcntlid = :2", %OperatorId, &rncntrl); REM Insert runcntlid; SQLExec("Insert into psprcsruncntl (VERSION, OPRID, RUNCNTLID, RUNLOCATION, SERVERNAME, OUTDESTTYPE, OUTDESTFORMAT, SVRDESTFILE, SVRDESTP RINTER, CLNTDESTFILE, CLNTDESTPRINTER, LASTUPDOPRID) VALUES (0, :1, :2, ' ', 'PSUNX', ' ', ' ', ' ', ' ', ' ', ' ', ' ', ' ')", %OperatorId, &rncntr l); REM Delete existing AE Request; &sqlStmt = CreateSQL("DELETE FROM PS_AEREQUESTTBL WHERE OPRID = :1 AND RUN_CNTL_ID = :2"); &sqlStmt.Execute(%OperatorId, &rncntrl); &sqlStmt = CreateSQL("DELETE FROM PS_AEREQUESTPARM WHERE OPRID = :1 AND RUN_CNTL_ID = :2"); &sqlStmt.Execute(%OperatorId, &rncntrl); REM Create SQL to insert PS_AEREQUESTTBL; &sqlStmt = CreateSQL("INSERT INTO PS_AEREQUESTTBL (OPRID, RUN_CNTL_ID, AE_APPLID, CURTEMPINSTANCE, PROCESS_FREQUENCY, AE_PROCESS_STATUS, PRO CESS_INSTANCE, PROCESS_ORIG, MARKET) VALUES (:1, :2, 'TRC_DUMP_XYZ', 1, 'A','N',0,' ','GBL')"); &sqlStmt.Execute(%OperatorId, &rncntrl); REM Create SQL to insert PS_AEREQUESTPARM; &sqlStmt = CreateSQL("INSERT INTO PS_AEREQUESTPARM (OPRID, RUN_CNTL_ID, AE_APPLID, AE_STATE_RECNAME, AE_BIND_VAR, AE_BIND_VALUE) VALUES (:1, :2, 'TRC_DUMP_XYZ', :3, :4, :5)"); &sqlStmt.Execute(%OperatorId, &rncntrl, "XYZ_TRC_DMP_AET", "DESCR254", "TRC"); REM Delete existing row from PS_TRC_DUMP_XYZ_RQST; &sqlStmt = CreateSQL("DELETE FROM PS_TRC_DUMP_XYZ_RQST WHERE OPRID =:1 AND RUN_CNTL_ID = :2"); &sqlStmt.Execute(%OperatorId, &rncntrl); REM Create SQL to insert PS_TRC_DUMP_XYZ_RQST; &sqlStmt = CreateSQL("INSERT INTO PS_TRC_DUMP_XYZ_RQST(OPRID, RUN_CNTL_ID, REQUEST_ID, PROCESS_FREQUENCY, PROCESS_STATUS, PROCESS_INSTANCE, PROCESS_ORIG, DTTM_STAMP_SEC, PARALLEL_SW, PROCESSING_SEQ, INTFC_ID, TO_INTFC_ID, SYSTEM_SOURCE, BUSINESS_UNIT, AMI_RUN_BB, WA_CAP_LIM_SW, MULT I_SEL_OPTN) VALUES(:1, :2, '1', 'A', 'N', 0, 'P', %DateTimeNull, 'N', 0, :3, :4, 'TRC', ' ', 'N', 'N', 'N')"); &sqlStmt.Execute(%OperatorId, &rncntrl); REM Close cursors; &sqlStmt.Close(); &procRqst = CreateProcessRequest(); &procRqst.ProcessType = "Application Engine"; &procRqst.ProcessName = "TRC_DUMP_XYZ"; &procRqst.RunControlID = &rncntrl; &procRqst.RunLocation = "PSUNX"; &procRqst.Schedule(); If &procRqst.Status <> 0 Then MessageBox(0, "", 8010, 394, "ERROR!!! TRC_DUMP_XYZ Failed"); Else MessageBox(0, "", 8010, 393, "TRC_DUMP_XYZ has been invoked, check the process status from Process Monitor.", &procRqst.ProcessInstance); End-If; *> End-If;</pre>									

20	Record PeopleCode	XYZ_TRC_UTL_DVW	VIEW_PB	Rowlnit	Custom Changed	Absent	Copy	Yes	Yes
----	----------------------	-----------------	---------	---------	-------------------	--------	------	-----	-----

Updated By: QI8A	Updated At: 2021-01-15-19.29.16.820051	Source: PeopleCode	Event: Rowlnit
------------------	--	--------------------	----------------

PeopleCode — XYZ_TRC_UTL_DVW > VIEW_PB > Rowlnit

```
If %UserId = "QI8A" Or
    %UserId = "QI8A" Then
    XYZ_TRC_UTL_DVW.VIEW_PB.Visible = True;
    XYZ_TRC_UTL_DVW.VIEW_PB.Visible = True;
Else
    XYZ_TRC_UTL_DVW.VIEW_PB.Visible = False;
End-If;
```

21	Record PeopleCode	XYZ_TRC_UTL_WRK	DELETE_ALL_PB	FieldChange	Custom Changed	Absent	Copy	Yes	Yes
----	----------------------	-----------------	---------------	-------------	-------------------	--------	------	-----	-----

#	OBJECT TYPE	NAME / KEY 1	KEY 2	KEY 3/4	SRC STATUS	TGT STATUS	ACTION	TAKE?	DONE?
---	-------------	--------------	-------	---------	------------	------------	--------	-------	-------

PeopleCode — XYZ_DELETE_TRACE > DeleteTraceFile

```

class DeleteTraceFile
    method DeleteTraceFile();
    method HandleEvent(&intRow As integer, &inField As Field, &inEventName As string);
private
    method initialize();
    method Refresh();
    method DeleteAll();
    method Delete(&intRow As integer);
    method InitEvent(&intRow As integer, &inField As Field);
    method ChangeAppServer();

    instance Rowset &ROWSET_LEVEL0, &ROWSET_LEVEL1;
    instance string &TRACE_DIR, &TRACE_DIR_DB, &HTTP_URL, &HTTP_URL_DB, &INSTANCE, &DIR_FILES;
    instance array of string &FNAMES;
end-class;

method DeleteTraceFile
    %This.initialize();
end-method;

method initialize

    &TRACE_DIR = GetEnv("XYZ_TRACE") | "/";
    %This.Refresh();

end-method;

method Refresh

    Local integer &rownum;
    Local string &Filename, &ShortFilename;
    Local string &strURI;
    Local integer &find;

    &ROWSET_LEVEL0 = GetLevel0();
    &ROWSET_LEVEL1 = &ROWSET_LEVEL0.GetRow(1).GetRowset(Scroll.XYZ_TRC_UTL_DVW);
    &ROWSET_LEVEL1.Flush();

    &TRACE_DIR_DB = &TRACE_DIR | XYZ_TRC_UTL_WRK.ENV_NAME_XYZ.LongTranslateValue | "/";
    &strURI = %Session.GetLocalNode().PortalURI;
    &find = Find(":", &strURI, 7);
    XYZ_TRC_UTL_WRK.URL_1.Value = Substring(&strURI, 1, &find) | "30091/TRACE/FS" | XYZ_TRC_UTL_WRK.ENV_NAME_XYZ.Value | "/";

    /* Populate the grid with login ID trace */
    REM &DIR_FILES = &TRACE_DIR_DB | "*.tracesql";
    &DIR_FILES = &TRACE_DIR_DB | %UserId | "*.tracesql";
    &FNAMES = FindFiles(&DIR_FILES, %FilePath_Absolute);

    &rownum = 1;

    While &FNAMES.Len > 0
        &Filename = &FNAMES.Shift();
        If Substring(&Filename, Len(&TRACE_DIR_DB) + 1, 5) <> "PSAPP" Then
            /* List the files */
            If &rownum = 1 Then /* this just prevents a blank line */
                &rownum = 0;
            Else
                &ROWSET_LEVEL1.InsertRow(0);
            End-If;
            &ROWSET_LEVEL1.GetRow(1).GetRecord(Record.XYZ_TRC_UTL_DVW).DESCR254.Value = &Filename;
            &ShortFilename = Substring(&Filename, Len(&TRACE_DIR_DB) + 1, Len(&Filename) - Len(&TRACE_DIR_DB));
            &ROWSET_LEVEL1.GetRow(1).GetRecord(Record.XYZ_TRC_UTL_DVW).DESCR125.Value = &ShortFilename;
        End-If;
    End-While;

    /* Populate the grid with O Ids */
    REM &DIR_FILES = &TRACE_DIR_DB | "*.tracesql";
    &DIR_FILES = &TRACE_DIR_DB | "O*.tracesql";
    If %UserId = "QI8A" Or
        %UserId = "QI8A" Then
        &DIR_FILES = &TRACE_DIR_DB | "*.tracesql";
    End-If;

```


#	OBJECT TYPE	NAME / KEY 1	KEY 2	KEY 3/4	SRC STATUS	TGT STATUS	ACTION	TAKE?	DONE?
		<pre>&FNAMES = FindFiles(&DIR_FILES, %FilePath_Absolute); While &FNAMES.Len > 0 &Filename = &FNAMES.Shift(); If Substring(&Filename, Len(&TRACE_DIR_DB) + 1, 5) <> "PSAPP" Or Substring(&Filename, Len(&TRACE_DIR_DB) + 1, 14) = "PSAPP_PSSUBHND" Or Find("JavaClient", &Filename) > 0 Then /* List the files */ If &rownum = 1 Then /* this just prevents a blank line */ &rownum = 0; Else &ROWSET_LEVEL1.InsertRow(0); End-If; &ROWSET_LEVEL1.GetRow(1).GetRecord(Record.XYZ_TRC_UTL_DVW).DESCR254.Value = &Filename; &ROWSET_LEVEL1.GetRow(1).GetRecord(Record.XYZ_TRC_UTL_DVW).DESCR125.Value = Substring(&Filename, Len(&TRACE_DIR_DB) + 1, Len(&Filename) - Len(&TRACE_DIR_DB)); End-If; End-While; /* Populate the grid with O Ids */ REM &DIR_FILES = &TRACE_DIR_DB "*.tracesql"; &DIR_FILES = &TRACE_DIR_DB "o*.tracesql"; &FNAMES = FindFiles(&DIR_FILES, %FilePath_Absolute); While &FNAMES.Len > 0 &Filename = &FNAMES.Shift(); If Substring(&Filename, Len(&TRACE_DIR_DB) + 1, 5) <> "PSAPP" Then /* List the files */ If &rownum = 1 Then /* this just prevents a blank line */ &rownum = 0; Else &ROWSET_LEVEL1.InsertRow(0); End-If; &ROWSET_LEVEL1.GetRow(1).GetRecord(Record.XYZ_TRC_UTL_DVW).DESCR254.Value = &Filename; &ROWSET_LEVEL1.GetRow(1).GetRecord(Record.XYZ_TRC_UTL_DVW).DESCR125.Value = Substring(&Filename, Len(&TRACE_DIR_DB) + 1, Len(&Filename) - Len(&TRACE_DIR_DB)); End-If; End-While; &ROWSET_LEVEL1.Sort(XYZ_TRC_UTL_DVW.DESCR125, "A"); end-method; method Delete /* &intRow as Integer */ Local File &MyFile; Local string &str; /* Delete only trace files */ &ROWSET_LEVEL0 = GetLevel0(); &ROWSET_LEVEL1 = &ROWSET_LEVEL0.GetRow(1).GetRowset(Scroll.XYZ_TRC_UTL_DVW); If All(&ROWSET_LEVEL1(&intRow).XYZ_TRC_UTL_DVW.DESCR254.Value) Then &MyFile = GetFile(XYZ_TRC_UTL_DVW.DESCR254.Value, "R", %FilePath_Absolute); &MyFile.Delete(); &str = String(%Datetime); &ROWSET_LEVEL1(&intRow).XYZ_TRC_UTL_DVW.DESCR15.Value = Substring(&str, 6, Len(&str) - 7); Else WinMessage("No file to delete."); End-If; end-method; method DeleteAll Local File &MyFile; Local string &Filename; Local integer &i; /* Delete only trace files */</pre>							

#	OBJECT TYPE	NAME / KEY 1	KEY 2	KEY 3/4	SRC STATUS	TGT STATUS	ACTION	TAKE?	DONE?
		<pre>&ROWSET_LEVEL0 = GetLevel0(); &ROWSET_LEVEL1 = &ROWSET_LEVEL0.GetRow(1).GetRowset(Scroll.XYZ_TRC_UTL_DVW); For &i = 1 To &ROWSET_LEVEL1.ActiveRowCount &Filename = &ROWSET_LEVEL1(&i).XYZ_TRC_UTL_DVW.DESCR254.Value; rem WinMessage(&Filename); If All(&Filename) And Substring(&Filename, Len(&TRACE_DIR_DB) + 1, 5) <> "PSAPP" Then &MyFile = GetFile(&Filename, "R", %FilePath_Absolute); &MyFile.Delete(); End-If; End-For; %This.Refresh(); end-method; method ChangeAppServer /* refresh the grid */ %This.Refresh(); end-method; method HandleEvent /* &intRow as Integer, +/ /* &inField as Field, +/ /* &inEventName as String +/ Local integer &i; &i = &intRow; %This.InitEvent(&i, &inField As Field); Evaluate &inEventName When = "FieldChange" Evaluate &inField.Name When = Field.REFRESH_BTN %This.Refresh(); Break; When = Field.DELETE_PB %This.Delete(&intRow); Break; When = Field.DELETE_ALL_PB %This.DeleteAll(); Break; When = Field.ENV_NAME_XYZ %This.ChangeAppServer(); Break; When-Other End-Evaluate; Break; When-Other End-Evaluate; end-method; method InitEvent /* &intRow as Integer, +/ /* &inField as Field +/ /* Add code here if there are some initial steps to be done before the event */ end-method;</pre>							