Edge Computing Lab

Class: TY-AIEC

School of Computing, MIT Art Design Technology University

Academic Year: 2024-25
Experiment No. 4

Title

Setting Up MQTT Broker on Raspberry Pi and Reading DHT11 Sensor Data and MQ9 Sensor

Objective

This lab aims to teach participants how to set up a Mosquitto MQTT broker on a Raspberry Pi, interface with a DHT11 temperature and humidity sensor, and publish the sensor data to an MQTT topic. Participants will also learn to subscribe to this topic using an MQTT client on an Android device.

Equipment and Materials

- Raspberry Pi (with Raspbian OS installed and internet connection)
- DHT11 Temperature and Humidity Sensor
- Jumper Wires
- Breadboard (optional)
- Android Device with MOTT Client App installed (e.g., MOTT Dash, MOTT Client)

Pre-lab Setup

Ensure the Raspberry Pi is set up with Raspbian OS, connected to the internet, and accessible via SSH or a monitor and keyboard. Install an MQTT client app on the Android device.

Lab Sections

Section 1: Setting Up the MQTT Broker

- 1. Update and Upgrade Raspberry Pi:
 - Open the terminal and execute 'sudo apt-get update' and 'sudo apt-get upgrade'.
- 2. Install Mosquitto MQTT Broker:
 - Run 'sudo apt-get install -y mosquitto mosquitto-clients'.
- 3. Enable Mosquitto Service:
 - Use 'sudo systemctl enable mosquitto.service'.
- 4. Start Mosquitto Service:
 - Execute 'sudo systemctl start mosquitto.service'.
- 5. Test Installation:

- Subscribe to a test topic in one terminal using `mosquitto_sub -h localhost -t test/topic`.
- Publish a message from another terminal with `mosquitto_pub -h localhost -t test/topic -m "Hello MQTT"`.
- Confirm "Hello MQTT" message appears in the subscriber terminal.

Section 2: Interfacing with DHT11 Sensor

- 1. Connect DHT11 to Raspberry Pi:
- Connect VCC to 5V, Data to GPIO4, and GND to Ground.
- 2. Install Python Libraries:
 - Install Adafruit_DHT and paho-mqtt using `sudo pip3 install Adafruit_DHT paho-mqtt`.

Section 3: Publishing Sensor Data to MQTT

- 1. Write Python Script:
- Create `dht11_mqtt_publisher.py` to read sensor data and publish it to `home/sensor/dht11` topic.
- 2. Run the Script:
- Execute the script with `python3 dht11_mqtt_publisher.py`.

Section 4: Subscribing with an Android MQTT Client

- 1. Configure MQTT Client App:
- Set the Raspberry Pi's IP as the MOTT server and subscribe to `home/sensor/dht11`.
- 2. Receive Data:
- Observe the temperature and humidity data published from the Raspberry Pi on the Android device.

Section 5: Enhancements and Troubleshooting

- Discuss JSON formatting, security with TLS/SSL, error handling, and MQTT client configuration.
- Troubleshoot common issues related to sensor readings, MQTT connections, and data reception.

Lab Tasks

- Complete the setup and confirm successful data publication and subscription.
- Experiment with different topics and QoS levels.
- (Optional) Implement ISON formatting for sensor data.

Lab Questions

- 1. How does MQTT protocol ensure message delivery with different QoS levels?
- 2. What are the benefits of using ISON formatting for sensor data in MQTT messages?
- 3. How can TLS/SSL encryption enhance the security of MQTT communication?

Further Exploration

- Explore bridging Mosquitto to an external MQTT broker.
- Integrate sensor data into IoT platforms or home automation systems.

Submission Requirements

- Provide screenshots of the terminal showing successful Mosquitto installation, Python script execution, and MQTT messages on the Android client.
- Submit a short report discussing the setup process, encountered challenges, and how they were overcome.

References

- Mosquitto Documentation: https://mosquitto.org/documentation/
- Adafruit DHT Sensor Library: https://github.com/adafruit/Adafruit_Python_DHT
- Paho MQTT Client: https://www.eclipse.org/paho/clients/python/
 - https://www.youtube.com/watch?v=BFyPzC6No8k&t=1s
 - 1. sudo apt update
 - 2. sudo apt upgrade
 - 3. sudo apt-get install mosquitto mosquitto-clients
 - 4. sudo systemctl enable mosquitto.service
 - 5. mosquitto_sub -d -t "binary/updates"
 - 6. mosquitto_pub -d -t "binary/updates" -m "Hello MITADT" // On 2nd terminal
 - 7. sudo nano /etc/mosquitto/mosquitto.conf
 - a. add line over here as listener 1883 allow_anonymous true
 - 8. sudo boot
 - 9. Open Terminal on Desktop PC as "MQTT Explorer"
 - 1. sudo git clone https://github.com/binaryupdates/mqttclient.git
 - 2. sudo pip3 install paho-mqtt

MIT SCHOOL OF COMPUTING Rajbaug, Loni-Kalbhor, Pune Nome: Such Sortish Konde Class: TY (AIEC) Roll No: 2223118 Sub & Ecl Assignment No 4. What is most of why is it commonly used in Tot application. MOTT is a lightweight resserge protocol designed for low bandwickly, high latercy or unreliable networks, making it ideal for Tot application like strans horses, industrial automation fremate parisoting. Explain the sole of MOTT broker, publisher & subscriber in on Jot system. water companent: · Broker: Central server that isomorpe messe de transmission · Publisher: Sends data to ortopic (e.g. a sensor publishing temperature) · Subscriber: Reciales massages from a Hopic. How can you install of set up the mosquitto

MIT SCHOOL OF COMPUTING Rajbaug, Loni-Kalbhor, Pune Installing mosquitto on Rosp Pi sudo opt update such aptimated - y mosquitto mosquitto-dient suclo system (+1 start mosquitto. White apython script to publish temp date trom or DHTII sensor to a MOTT -topic? iroport palso raft dient as regth Sensor: Acka Fauit_DHT. DHT! pin : 4 Client: routh client () Client. connect ("broker-hivery.com", 1883,60) while True burnichty, temperature : AchiPauit_DHT, read - retry (sensor, pin of temporature: