


Legal Disclaimer: This video is copy-right protected by the Professorship ,Digital Signal Processing and Circuit Technology‘ of the Chemnitz University of Technology. Usage is only allowed for students of the faculty ,Electrical Engineering and Information Technology‘ of the Chemnitz University of Technology. Any copy, publication or further distribution is not allowed.



Chapter 3: Histogram and Point Operations

Histogram calculation


- Each pixel represents a quantized measurement of the intensity
- The Histogram is a vector, which contains one element of each quantization level
 - N-bit resolution $\rightarrow 2^N$ quantization levels $\rightarrow K=2^N$ histogram elements
 - E.g. 8-bit $\rightarrow K=2^8=256$ entries
- Each element contains the number of pixels whose value corresponds to the index of the element
- Example: calculation of a histogram in MATLAB:

```
% read image
I = imread('image.bmp');
[rows cols] = size(I);

% initialize histogram with zeros
h = zeros(256,1);

% iterate over all pixels
for n = 1:rows
    for m = 1:cols
        % increment histogram value at index I(n,m)
        h(I(n,m)+1) = h(I(n,m)+1) + 1;
    end
end

% show histogram
bar(h);
```



Histogram distribution of Lena

Mean value (expectation value)

- Provides information about the brightness of the image

Calculation from the histogram:
$$\mu = \sum_{i_{\min}}^{i_{\max}} i \cdot h_n(i)$$

Calculation from the image:
$$\mu = \frac{1}{M \cdot N} \sum_{m=0}^{M-1} \sum_{n=0}^{N-1} I(n, m)$$

Variance

- Provides information about the dispersion of the values


Calculation from the histogram:
$$\sigma^2 = \sum_{i_{\min}}^{i_{\max}} (i - \mu)^2 \cdot h_n(i)$$

Calculation from the image:
$$\sigma^2 = \frac{1}{M \cdot N} \sum_{m=0}^{M-1} \sum_{n=0}^{N-1} I^2(n, m) - \mu^2$$

Examples:







$$\mu = 127$$
$$\sigma^2 = 0$$







$$\mu = 127,5$$
$$\sigma^2 = 127,5^2 = 16256,25$$

Examples: Brightness



Examples: Contrast



Examples: Quantization noise




Original: 8-bit



Quantized: 4-bit



Quantized: 3-bit





Brightness Adjustment



$$f(m, n) = I(m, n) + a \quad a \in [-255, 255]$$

$$J(m, n) = \begin{cases} f(m, n), & \text{if } 0 \leq f(m, n) \leq 255 \\ 0, & \text{if } f(m, n) < 0 \\ 255, & \text{if } f(m, n) > 255 \end{cases}$$

$a > 0$:



$a < 0$:





Contrast Adjustment

$$f(m,n) = a(I(m,n) - s) + s \quad a, s \in [0,255]$$

$$J(m,n) = \begin{cases} f(m,n), & \text{if } 0 \leq f(m,n) \leq 255 \\ 0, & \text{if } f(m,n) < 0 \\ 255, & \text{if } f(m,n) > 255 \end{cases}$$



s is the center of the
contrast function,
e.g. $s = 127$

$0 \leq a < 1$:







$s = 127$

$a > 1$:



Inversion

$$J(m,n) = 255 - I(m,n)$$



Binning (quantization)

- Images with a high bit depth would generate huge histograms
 - Example: 14-bit $\rightarrow K=2^{14}=16384$ histogram entries
- To reduce the size of the histogram, binning can be done
- The intensity values are counted in B intervals (bins) $[i_j, i_{j+1})$
- For equally sized bins, the interval size is $k_B=K/B$
- The bin index can be calculated with $j = \left\lfloor I(m,n) \frac{B}{K} \right\rfloor$

Example: 14-bit image, histogram with 256 bins

$$\begin{array}{llll} h(0) & \leftarrow & 0 & \leq I(n,m) < 64 \\ h(1) & \leftarrow & 64 & \leq I(n,m) < 128 \\ \vdots & \leftarrow & \vdots & \leq I(n,m) < \vdots \\ h(j) & \leftarrow & i_j & \leq I(n,m) < i_{j+1} \\ \vdots & \leftarrow & \vdots & \leq I(n,m) < \vdots \\ h(255) & \leftarrow & 16320 & \leq I(n,m) < 16384 \end{array}$$

Third exercise

- Implement histogram calculation and some point operations

Expected Output (3 of 6)

Adjusted Brightness



Quantized



Inverted

