

BUDGE BUDGE INSTITUTE OF TECHNOLOGY



Name: Sudip Basu

Department : Computer Science and Technology

Year :2nd

Roll: 16

Semester: 4th

COMPUTER NETWORK ASSIGNMENT

File Transfer Protocol (FTP) Configuration in Cisco Packet Tracer


The **File Transfer Protocol (FTP)** is a standard network protocol used for the transfer of computer files between a client and server on a computer network.

FTP employs a **client-server** architecture whereby the client machine has an **FTP client** installed and establishes a connection to an **FTP server** running on a remote machine. After the connection has been established and the user is successfully authenticated, the data transfer phase can begin.

Worth noting: Although FTP does support **user authentication**, all data is sent in clear text, including usernames and passwords. For **secure** transmission that protects the username and password, and encrypts the content, FTP is often secured with SSL/TLS (FTPS) or replaced with SSH File Transfer Protocol (SFTP).

Let's now do FTP configuration in Packet Tracer:

1. Build the network topology.



2. Configure static IP addresses on the Laptop and the server.

Laptop: IP address: 192.168.1.1 Subnet Mask: 255.255.255.0

Server: IP address: 192.168.1.2 Subnet Mask: 255.255.255.0

3. Now try using an **FTP client** built in the Laptop to send files to an **FTP server** configured in the Server.

From the Laptop's command prompt, FTP the server using the server IP address by typing:

```
ftp 192.168.1.2
```

Provide the **username(cisco)** and **password(cisco)** [which are the defaults] for ftp login.

```
C:\>
C:\>ftp 192.168.1.2
Trying to connect...192.168.1.2
Connected to 192.168.1.2
220- Welcome to PT Ftp server
Username:cisco
331- Username ok, need password
Password:
230- Logged in
(passive mode On)
ftp>
```

You are now in the **FTP prompt** .

PC0 has an **FTP client** which can be used to **read**, **write**, **delete** and **rename** files present in the FTP server.

The **FTP server** can be used to **read** and **write** configuration files as well as IOS images. Additionally, the FTP server also supports file operations such **rename**, **delete** and **listing** directory.

With that in mind, we can do something extra. So let's do this:

4. **Create** a file in the Laptop then **upload** it to the server using **FTP**.

To do this, open the **Text Editor** in the Laptop, create a file and give it your name of choice.

Type any text in the editor then **save** your file. e.g. **myFile.txt**.


5. Now upload the file from the Laptop to the server using FTP. (An FTP connection has to be started first. But this is what we've done in step 3)

So to do an FTP upload, we'll type:

```
put MyFile.txt
```

```
ftp>
ftp>put MyFile.txt
Writing file MyFile.txt to 192.168.1.2:
File transfer in progress...
[Transfer complete - 47 bytes]
47 bytes copied in 0.023 secs (2043 bytes/sec)
ftp>
```

6. Once file upload is successful, go to the Server **FTP directory** to verify if the file sent has been received. To do this, go to **Server->Services->FTP**. Here look for **MyFile.txt** sent from the laptop.



Addendum: To check **other FTP commands** supported by the FTP client running on the Laptop(or PC), you can use a question mark (?) on the Laptop's command prompt as shown below:

```
ftp> ?
?
cd
delete
dir
get
help
passive
put
pwd
quit
rename
```

You can see the put command that we used to upload our file to the FTP server. Other commands listed include:

get—used to get(download) a file from the server.

For example: **get MyFile.txt**

delete— to delete a file in the FTP directory with the server

For example: **delete MyFile.txt**

Rename— used to Rename a file

cd – used to change directory.

For example, we can open an **HTTP directory** in the server by typing: **cd /http**. This will change the current directory from FTP directory to HTTP directory

Once the http directory is open, you can upload a file to the HTTP server. You're now uploading a file to an HTTP folder(directory) using FTP.

For example: **put MyFile.txt**


To see this working, let's **open an HTTP directory** and upload(**put**) a file to it using FTP:

```
ftp>cd /http
ftp>
Working directory changed to /http successfully
ftp>put MyFile.txt

Writing file MyFile.txt to 192.168.1.2:
File transfer in progress...

[Transfer complete - 47 bytes]
47 bytes copied in 0.01 secs (4700 bytes/sec)
```

You can now check up in the **HTTP directory** in the server and verify that the file uploaded from the Laptop(**MyFile.txt**) is well received:



Notice that we are uploading files to an HTTP Server directory using File Transfer Protocol.(FTP). This is what actually happens when you use an **FTP client** such as [FileZilla client](#) to upload files to a website. In our case here, we are using an FTP client **built-in** the Laptop.

This may interest you: The first FTP client applications were [command-line programs](#) developed before operating systems had graphical user interfaces, and are still shipped with most Windows and Linux operating systems. (Actually this is what we have been using this far). Many FTP clients (e.g. FileZilla) and automation utilities have since been developed for desktops, servers, mobile devices, and hardware. FTP has also been incorporated into productivity applications, such as HTML *editors*.


Well done for reading this topic up to this point! You now have more than a foundation regarding working with FTP to upload, download, delete, rename...files.

If you're okay so far, then let's do something even more interesting...


We'll **create** an html file in our Laptop, **upload** it to HTTP server directory using FTP, then try to **access** the file from the Laptop's browser.

So psych up and let's move on!

On the Laptop, open the **text editor**, then type some markup(html) and save the file with the extension **.html**. See all this below:



Save your file as an html file like this:



Now upload the file(**File2.html**) to the HTTP server using FTP. This is easy. We've already done it previously!

If you're already in the **HTTP directory**, you just need to type: **put File2.html**. If no, first ftp the server(**ftp 192.168.1.2**), provide the login username(**cisco**) and password(**cisco**); change the current directory to HTTP(**cd /http**) , and finally upload the html file onto the HTTP directory(**put File2.html**)

```
C:\>ftp 192.168.1.2
Trying to connect...192.168.1.2
Connected to 192.168.1.2
220- Welcome to PT Ftp server
Username:cisco
331- Username ok, need password
Password:
230- Logged in
(passive mode On)
ftp>cd /http
ftp>
Working directory changed to /http successfully
ftp>put File2.html

Writing file File2.html to 192.168.1.2:
File transfer in progress...


[Transfer complete - 136 bytes]

136 bytes copied in 0.041 secs (3317 bytes/sec)
ftp>
```


Moving on...

Check whether the html file uploaded has been received in the **HTTP directory**:

Go to **Server->Services-> HTTP**. Then look up for the file in the File Manager.




Now edit **index.html** file in the **HTTP** directory so as to include a link to **File2** that we've just uploaded. This will make **File2** accessible from the Laptop's browser. To do this, locate **index.html** then click **edit**. Proceed to edit it as shown below. Then **save** and accept overwrite.



Finally, try to access the newly uploaded file from the Laptop's browser.

So go to the Laptop's browser and access the server using the server's IP address. By doing this, the browser is making an http request to the server. The server will respond to the Laptop with the **index.html** file containing a **link** to **File2** which we've uploaded from the Laptop using FTP.



Click **File2** link to view the contents of the file in the browser.