

Lab Report 1

Sudipto Ghosh
MCSC101 – M. Sc. Semester I
Department of Computer Science
University of Delhi

December 15, 2022

1 Insertion Sort

Algorithm 1: Insertion Sort

```
Data: Array  $A[1..n]$ , Array Size  $n$ 
for  $i = 2..n$  do
     $Insert(A[1..i-1], i)$  /* this function searches for an appropriate location
         $j$  to insert  $A[i]$  in  $A[1..i-1]$  so that  $A[1..i]$  is sorted, and inserts
         $A[i]$  in the  $j^{th}$  location */
end
```

Algorithm 2: Insert

```
Data: Array  $A[1..i]$ , Index  $i$ 
 $j \leftarrow i - 1$ ;
 $key \leftarrow A[i]$ ;
while  $j \geq 1$  do
    /* compare  $A[j]$  and  $key$  */
    if  $A[j] > key$  then
         $A[j+1] \leftarrow A[j]$ ;
         $j \leftarrow j - 1$ ;
    else
        break;
    end
end
/* insert  $A[i]$  in the  $j^{th}$  location */
 $A[j+1] \leftarrow key$ ;
```

2 Solutions

2.1 Problem 1

The possible locations that $A[i]$ may take in the i^{th} iteration are $1..i$ where $1 \leq i \leq n$.

2.2 Problem 2

The number of comparisons performed by Insertion Sort to insert $A[i]$ in location j is given by $i - j + 1$ or $i - j$, which is supported by comparing the observed values and the value of the expression for all values of i and j as shown in [this table](#).

2.3 Problem 3

On running Insertion Sort for all possible permutations of 1, 2, 3, 4, we observe the following behaviour.

For $i = 1$, all $A[i]$ get placed at location $j = 1$, with probability 1.

For $i = 2$, we have

Permutation	j=1	j=2
1 2 3 4		1
1 2 4 3		1
1 3 2 4		1
1 3 4 2		1
1 4 2 3		1
1 4 3 2		1
2 1 3 4	1	
2 1 4 3	1	
2 3 1 4		1
2 3 4 1		1
2 4 1 3		1
2 4 3 1		1
3 1 2 4	1	
3 1 4 2	1	
3 2 1 4	1	
3 2 4 1	1	
3 4 1 2		1
3 4 2 1		1
4 1 2 3	1	
4 1 3 2	1	
4 2 1 3	1	
4 2 3 1	1	
4 3 1 2	1	
4 3 2 1	1	
Occurences	12	12

We observe that the probabilities of $A[i]$ to get placed in $j = 1$ and $j = 2$ are equal and given by $1/2$.

For $i = 3$, we have

Permutation	j=1	j=2	j=3
1 2 3 4			1
1 2 4 3			1
1 3 2 4		1	
1 3 4 2			1
1 4 2 3		1	
1 4 3 2		1	
2 1 3 4			1
2 1 4 3			1
2 3 1 4	1		
2 3 4 1			1
2 4 1 3	1		
2 4 3 1		1	
3 1 2 4		1	
3 1 4 2			1
3 2 1 4	1		
3 2 4 1			1
3 4 1 2	1		
3 4 2 1	1		
4 1 2 3		1	

Permutation	j=1	j=2	j=3
4 1 3 2		1	
4 2 1 3	1		
4 2 3 1		1	
4 3 1 2	1		
4 3 2 1	1		
Occurrences	8	8	8

We observe that the probabilities of $A[i]$ to get placed in $j = 1$, $j = 2$ and $j = 3$ are equal and given by $1/3$.

For $i = 4$, we have

Permutation	j=1	j=2	j=3	j=4
1 2 3 4				1
1 2 4 3			1	
1 3 2 4				1
1 3 4 2		1		
1 4 2 3			1	
1 4 3 2		1		
2 1 3 4				1
2 1 4 3			1	
2 3 1 4				1
2 3 4 1	1			
2 4 1 3			1	
2 4 3 1	1			
3 1 2 4				1
3 1 4 2		1		
3 2 1 4				1
3 2 4 1	1			
3 4 1 2		1		
3 4 2 1	1			
4 1 2 3			1	
4 1 3 2		1		
4 2 1 3			1	
4 2 3 1	1			
4 3 1 2		1		
4 3 2 1	1			
Occurrences	6	6	6	6

We observe that the probabilities of $A[i]$ to get placed in $j = 1$, $j = 2$, $j = 3$ and $j = 4$ are equal and given by $1/4$.

We can thus say that the probability that $A[i]$ will be inserted at the j^{th} location is $1/i$. ■

2.3.1 Part (a)

For every $i = 2..4$, we report the total number of comparisons done to insert $A[i]$ to the j^{th} location and compute the average number of comparisons over all possible permutations. The observations are recorded in the table below.

Permutation	i=2	i=3	i=4	Total Comparisons
1 2 3 4	1	1	1	3
1 2 4 3	1	1	2	4
1 3 2 4	1	2	1	4
1 3 4 2	1	1	3	5
1 4 2 3	1	2	2	5
1 4 3 2	1	2	3	6
2 1 3 4	1	1	1	3
2 1 4 3	1	1	2	4

Permutation	i=2	i=3	i=4	Total Comparisons
2 3 1 4	1	2	1	4
2 3 4 1	1	1	3	5
2 4 1 3	1	2	2	5
2 4 3 1	1	2	3	6
3 1 2 4	1	2	1	4
3 1 4 2	1	1	3	5
3 2 1 4	1	2	1	4
3 2 4 1	1	1	3	5
3 4 1 2	1	2	3	6
3 4 2 1	1	2	3	6
4 1 2 3	1	2	2	5
4 1 3 2	1	2	3	6
4 2 1 3	1	2	2	5
4 2 3 1	1	2	3	6
4 3 1 2	1	2	3	6
4 3 2 1	1	2	3	6
Sum	24	40	54	118
Average	1	1.666666666666667	2.25	4.916666666666667

2.3.2 Part (b)

We construct a 2D-table with i in rows and j in columns where each $P[i, j]$ represents the probability that $A[i]$ will be inserted in location j in the i^{th} iteration.

	1	2	3	4
1	24/24	0	0	0
2	12/24	12/24	0	0
3	8/24	8/24	8/24	0
4	6/24	6/24	6/24	6/24

2.3.3 Part (c)

TODO.

2.4 Problem 4

We observe the placement of the elements of a randomly generated input sequence of size 3.

For $i = 1$, all $A[i]$ get placed at location $j = 1$ with probability 1.

For $i = 2$, we have

Permutation	j=1	j=2
2 3 5		1
2 5 3		1
3 2 5	1	
3 5 2		1
5 2 3	1	
5 3 2	1	
Occurrences	3	3

We observe that the probabilities of $A[i]$ to get placed in $j = 1$, and $j = 2$ are equal and given by $1/2$.

For $i = 3$, we have

Permutation	j=1	j=2	j=3
2 3 5			1
2 5 3		1	

Permutation	j=1	j=2	j=3
3 2 5			1
3 5 2	1		
5 2 3		1	
5 3 2	1		
Occurences	2	2	2

We observe that the probabilities of $A[i]$ to get placed in $j = 1$, $j = 2$ and $j = 3$ are equal and given by $1/3$.

We can thus say that the probability that $A[i]$ will be inserted at the j^{th} location is $1/i$. ■

3 Raw Data

permutation	i	j	comparisons
1 2 3 4	2	2	1
1 2 3 4	3	3	1
1 2 3 4	4	4	1
1 2 4 3	2	2	1
1 2 4 3	3	3	1
1 2 4 3	4	3	2
1 3 2 4	2	2	1
1 3 2 4	3	2	2
1 3 2 4	4	4	1
1 3 4 2	2	2	1
1 3 4 2	3	3	1
1 3 4 2	4	2	3
1 4 2 3	2	2	1
1 4 2 3	3	2	2
1 4 2 3	4	3	2
1 4 3 2	2	2	1
1 4 3 2	3	2	2
1 4 3 2	4	2	3
2 1 3 4	2	1	1
2 1 3 4	3	3	1
2 1 3 4	4	4	1
2 1 4 3	2	1	1
2 1 4 3	3	3	1
2 1 4 3	4	3	2
2 3 1 4	2	2	1
2 3 1 4	3	1	2
2 3 1 4	4	4	1
2 3 4 1	2	2	1
2 3 4 1	3	3	1
2 3 4 1	4	1	3
2 4 1 3	2	2	1
2 4 1 3	3	1	2
2 4 1 3	4	3	2
2 4 3 1	2	2	1
2 4 3 1	3	2	2
2 4 3 1	4	1	3
3 1 2 4	2	1	1
3 1 2 4	3	2	2
3 1 2 4	4	4	1
3 1 4 2	2	1	1
3 1 4 2	3	3	1
3 1 4 2	4	2	3
3 2 1 4	2	1	1
3 2 1 4	3	1	2

permutation	i	j	comparisons
3 2 1 4	4	4	1
3 2 4 1	2	1	1
3 2 4 1	3	3	1
3 2 4 1	4	1	3
3 4 1 2	2	2	1
3 4 1 2	3	1	2
3 4 1 2	4	2	3
3 4 2 1	2	2	1
3 4 2 1	3	1	2
3 4 2 1	4	1	3
4 1 2 3	2	1	1
4 1 2 3	3	2	2
4 1 2 3	4	3	2
4 1 3 2	2	1	1
4 1 3 2	3	2	2
4 1 3 2	4	2	3
4 2 1 3	2	1	1
4 2 1 3	3	1	2
4 2 1 3	4	3	2
4 2 3 1	2	1	1
4 2 3 1	3	2	2
4 2 3 1	4	1	3
4 3 1 2	2	1	1
4 3 1 2	3	1	2
4 3 1 2	4	2	3
4 3 2 1	2	1	1
4 3 2 1	3	1	2
4 3 2 1	4	1	3