


Small Signal Schottky Diodes



LINKS TO ADDITIONAL RESOURCES



3D Models

SPICE

Models



Marking



Parametric Search



Order Samples

MECHANICAL DATA

Case: SOD-123

Weight: approx. 10.6 mg

Packaging codes/options:

18/10K per 13" reel (8 mm tape), 10K/box

08/3K per 7" reel (8 mm tape), 15K/box

FEATRUES

- For general purpose applications
- The low forward voltage drop and fast switching make it ideal for protection of MOS devices, steering, biasing and coupling diodes for fast switching and low logic level applications
- The SD101 series is a metal-on-silicon Schottky barrier device which is protected by a PN junction guarding
- AEC-Q101 qualified available (part number on request)
- Molding compound meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level (MSL) 1
- Base P/N-G3 - green, commercial grade
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


RoHS
COMPLIANT
HALOGEN
FREE
GREEN
(5-2008)

PARTS TABLE

| PART | ORDERING CODE | AEC-Q101 QUALIFIED | TYPE MARKING | CIRCUIT CONFIGURATION | TAPED UNITS PER REEL | MINIMUM ORDER QUANTITY |
|-----------|---------------|--------------------|--------------|-----------------------|-------------------------------|------------------------|
| SD101AW-G | SD101AW-G3-08 | no | SK | Single | 3 000 (8 mm tape on 7" reel) | 15 000 |
| | SD101AW-G3-18 | no | | | 10 000 (8 mm tape on 7" reel) | 10 000 |
| SD101BW-G | SD101BW-G3-08 | no | SL | Single | 3 000 (8 mm tape on 7" reel) | 15 000 |
| | SD101BW-G3-18 | no | | | 10 000 (8 mm tape on 7" reel) | 10 000 |
| SD101CW-G | SD101CW-G3-08 | no | SM | Single | 3 000 (8 mm tape on 7" reel) | 15 000 |
| | SD101CW-G3-18 | no | | | 10 000 (8 mm tape on 7" reel) | 10 000 |

ABSOLUTE MAXIMUM RATINGS (T_{amb} = 25 °C, unless otherwise specified)

| PARAMETER | TEST CONDITION | PART | SYMBOL | VALUE | UNIT |
|---|--|-----------|------------------|-------|------|
| Repetitive peak reverse voltage | | SD101AW-G | V _{RRM} | 60 | V |
| | | SD101BW-G | V _{RRM} | 50 | V |
| | | SD101CW-G | V _{RRM} | 40 | V |
| Power dissipation | on FR-4 board with recommended soldering footprint | | P _{tot} | 230 | mW |
| | Infinite heatsink | | | 330 | mW |
| Forward continuous current ⁽¹⁾ | | | I _F | 100 | mA |
| Maximum single cycle surge | 10 μs square wave | | I _{FSM} | 2 | A |

Note

⁽¹⁾ Infinite heatsink

**THERMAL CHARACTERISTICS** ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
|--|---|------------|-------------|--------------------|
| Thermal resistance junction to ambient air | according to JEDEC® 51-3 on FR-4 board with recommended soldering footprint | R_{thJA} | 420 | K/W |
| Thermal resistance junction lead | Infinite heatsink | R_{thJL} | 300 | K/W |
| Maximum junction temperature | | T_j | 125 | $^{\circ}\text{C}$ |
| Storage temperature range | | T_{stg} | -65 to +150 | $^{\circ}\text{C}$ |
| Operating temperature range | | T_{op} | -55 to +150 | $^{\circ}\text{C}$ |

ELECTRICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

| PARAMETER | TEST CONDITION | PART | SYMBOL | MIN. | TYP. | MAX. | UNIT |
|---------------------------|---|-----------|------------|------|------|------|------|
| Reverse breakdown voltage | $I_R = 10\text{ }\mu\text{A}$ | SD101AW-G | $V_{(BR)}$ | 60 | | | V |
| | | SD101BW-G | $V_{(BR)}$ | 50 | | | V |
| | | SD101CW-G | $V_{(BR)}$ | 40 | | | V |
| Leakage current | $V_R = 50\text{ V}$ | SD101AW-G | I_R | | | 200 | nA |
| | $V_R = 40\text{ V}$ | SD101BW-G | I_R | | | 200 | nA |
| | $V_R = 30\text{ V}$ | SD101CW-G | I_R | | | 200 | nA |
| Forward voltage drop | $I_F = 1\text{ mA}$ | SD101AW-G | V_F | | | 410 | mV |
| | | SD101BW-G | V_F | | | 400 | mV |
| | | SD101CW-G | V_F | | | 390 | mV |
| | $I_F = 15\text{ mA}$ | SD101AW-G | V_F | | | 1000 | mV |
| | | SD101BW-G | V_F | | | 950 | mV |
| | | SD101CW-G | V_F | | | 900 | mV |
| Diode capacitance | $V_R = 0\text{ V}$, $f = 1\text{ MHz}$ | SD101AW-G | C_D | | | 2 | pF |
| | | SD101BW-G | C_D | | | 2.1 | pF |
| | | SD101CW-G | C_D | | | 2.2 | pF |
| Reverse recovery time | $I_F = I_R = 5\text{ mA}$, recover to $0.1\text{ }I_R$ | | t_{rr} | | | 1 | ns |



TYPICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)




Fig. 1 - Typical Forward Current vs. Forward Voltage




Fig. 3 - Typical Capacitance vs. Reverse Voltage




Fig. 2 - Admissible Power Dissipation vs. Ambient Temperature






Fig. 4 - Typical Reverse Leakage vs. Reverse Voltage



PACKAGE DIMENSIONS in millimeters (inches): SOD-123



Foot print recommendation




Rev. 01 - Date: 18. Jan. 2022

Document no.: S8-V-3910.01-003 (4)

23223



CARRIER TAPE SOD-123



Rev. 02 - Date: 21. Jan. 2014
Document no.: S8-V-3717.10-002 (4)

23224

ORIENTATION IN CARRIER TAPE SOD-123



Rev. 02 - Date: 07. Nov. 2022
Document no.: S8-V-3717.10-003 (4)

23225



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.