USB-OTG BUS-Port ESD Protection for V_{BUS} = 28 V

FEATURES

- Ultra compact LLP75-7L package
- Low package height < 0.6 mm
- 3-line USB ESD protection with max. working range = 5.5 V
- V_{BUS}-protection with 28 V working range
- Low leakage current
- Low load capacitance C_D = 0.7 pF
- ESD immunity to IEC 61000-4-2
  ± 15 kV contact discharge
  ± 15 kV air discharge
- Surge current acc. IEC 61000-4-5 I_{PP} > 3 A
- e4 - precious metal (e.g. Ag, Au, NiPd, NiPdAu) (no Sn)
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

Pb-free

e4

RoHS
COMPLIANT

HALOGEN
FREE

GREEN
(5-2008)

21102

20517

1

MARKING (example only)

XX
■YY   21001

Dot = pin 1 marking
XX = date code
YY = type code (see table below)

DESIGN SUPPORT TOOLS

click logo to get started

3D
Models
Available

ORDERING INFORMATION

DEVICE NAME	ORDERING CODE	TAPED UNITS PER REEL (8 mm TAPE on 7" REEL)	MINIMUM ORDER QUANTITY
VBUS053CZ-HAF	VBUS053CZ-HAF-G-08	3000	15 000

PACKAGE DATA

DEVICE NAME	PACKAGE NAME	TYPE CODE	WEIGHT	MOLDING COMPOUND FLAMMABILITY RATING	MOISTURE SENSITIVITY LEVEL	SOLDERING CONDITIONS
VBUS053CZ-HAF	LLP75-7L	UA	4.2 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	Peak temperature max. 260 °C

ABSOLUTE MAXIMUM RATINGS VBUS053CZ-HAF

PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Data line D+, D-, ID: Pin 1, 2 and 3 to ground (pin 7)				
Peak pulse current	acc. IEC 61000-4-5; t_P = 8/20 μs; single shot	I_{PPM}	3	A
Peak pulse power	acc. IEC 61000-4-5; t_P = 8/20 μs; single shot	P_{PP}	54	W
ESD immunity	Contact discharge acc. IEC 61000-4-2; 10 pulses	V_{ESD}	± 15	kV
	Air discharge acc. IEC 61000-4-2; 10 pulses		± 15	kV
V_{BUS}: Pin 6 to ground (pin 7)				
Peak pulse current	acc. IEC 61000-4-5; t_P = 8/20 μs; single shot	I_{PPM}	3	A
Peak pulse power	acc. IEC 61000-4-5; t_P = 8/20 μs; single shot	P_{PP}	156	W
ESD immunity	Contact discharge acc. IEC 61000-4-2; 10 pulses	V_{ESD}	± 30	kV
	Air discharge acc. IEC 61000-4-2; 10 pulses		± 30	kV
Operating temperature	Junction temperature	T_J	-40 to +125	°C
Storage temperature		T_{STG}	-55 to +150	°C

ELECTRICAL CHARACTERISTICS VBUS053CZ-HAF All inputs (pin 1, 2, and 3) to ground (pin 7)

PARAMETER	TEST CONDITIONS/REMARKS	SYMBOL	MIN.	TYP.	MAX.	UNIT
Protection paths	Number of line which can be protected	$N_{channel}$	-	-	3	lines
Reverse working voltage	Reverse stand-off voltage	V_{RWM}	-	-	5.5	V
Reverse voltage	at I_R = 0.1 µA	V_R	5.5	-	-	V
Reverse current	at V_R = 3.3 V	I_R	-	-	0.02	µA
	at V_R = 3.3 V; T = 65 °C	I_R	-	-	0.085	µA
	at V_R = V_{RWM} = 5.5 V	I_R	-	-	0.1	µA
Forward voltage	at I_F = 15 mA	V_F	0.7	-	1.2	V
Reverse breakdown voltage	at I_R = 1 mA	V_{BR}	6.5	-	10	V
Reverse clamping voltage	at I_{PP} = 1 A; acc. IEC 61000-4-5	V_C	-	10	12	V
	at I_{PP} = 3 A; acc. IEC 61000-4-5	V_C	-	15	18	V
Forward clamping voltage	at I_F = 3 A; acc. IEC 61000-4-5	V_F	-	3.4	4.1	V
Line capacitance	Test pin at V_R = 0 V; any other I/O pin at V_R = 3.3 V; f = 1 MHz	C_D	-	0.7	1	pF
Line to line capacitance	Among pins 1, 2 and 3 at V_R = 0 V; f = 1 MHz	C_D	-	0.35	0.5	pF
Line symmetry	Difference of the line capacitance	dC_D	-	-	0.1	pF

Note
- Ratings at 25 °C ambient temperature, unless otherwise specified

ELECTRICAL CHARACTERISTICS V_{BUS} (pin 6) to ground (pin 7)

| PARAMETER	TEST CONDITIONS/REMARKS	SYMBOL	MIN.	TYP.	MAX.	UNIT
Protection paths	Number of line which can be protected	$N_{channel}$	-	-	1	lines
Reverse working voltage	Reverse stand-off voltage	V_{RWM}	-	-	28	V
Reverse voltage	at I_R = 0.1 µA	V_R	28	-	-	V
Reverse current	at V_R = V_{RWM} = 28 V	I_R	-	-	100	nA
Forward voltage	at I_F = 10 mA	V_F	0.6	0.75	0.9	V
Reverse breakdown voltage	at I_R = 1 mA	V_{BR}	32	-	40	V
Reverse clamping voltage	at I_{PP} = 1 A; acc. IEC 61000-4-5; T = 25 °C	V_C	-	37	45	V
	at I_{PP} = 3 A; acc. IEC 61000-4-5; T = 25 °C	V_C	-	42	52	V
Forward clamping voltage	at I_F = 3 A; acc. IEC 61000-4-5	V_F	-	-	2.2	V
Line capacitance	at V_R = 0 V; f = 1 MHz	C_D	-	31	40	pF

Note
- Ratings at 25 °C ambient temperature, unless otherwise specified

APPLICATION NOTE

The VBUS053CZ-HAF is intended as an ESD protection and transient voltage suppressor for one USB-OTG port.

The LLP75-7L package contains two separate dies which are mounted on a common ground plane (pin 7).

The high-speed data lines D-, D+ and ID, are connected to any of the pins no. 1 to 3. As long as the signal voltage on the data lines is between the ground- and the 5 V working range, the low capacitance PN-diodes offer a very high isolation to ground and to the other data lines. But as soon as any transient signal like an ESD signal, exceeds this working range of 5 V in either the positive or negative direction, one of the PN-diodes gets into the forward mode and clamps the transient either to ground or to the avalanche break through level. An extra avalanche diode (separate die) clamps the supply line voltage (V_{BUS} at pin 6) above the 28 V working range to ground (pin 7). Due to the "two die construction" the V_{BUS} line has a very high isolation to the data lines. In case of a destructive transient signal, i.e. coming from a charger, the data lines will not be influenced.

Remark:
The input pins no. 1, 2 and 3 are symmetrical. Each of the data signals D-, D+ and ID can be connected to pin 1, 2 or 3

For technical questions, contact: ESDprotection@vishay.com

**TYPICAL CHARACTERISTICS** (T_{amb} = 25 °C, unless otherwise specified)

Fig. 1 - ESD Discharge Current Wave Form
acc. IEC 61000-4-2 (330 Ω/150 pF)

Fig. 4 - Typical Capacitance C_D vs. Reverse Voltage V_R

Fig. 2 - 8/20 µs Peak Pulse Current Wave Form
acc. IEC 61000-4-5

Fig. 5 - Typical Forward Current I_F vs. Forward Voltage V_F

Fig. 3 - Typical Capacitance C_D vs. Reverse Voltage V_R

Fig. 6 - Typical Reverse Voltage V_R vs. Reverse Current I_R

For technical questions, contact: ESDprotection@vishay.com

Fig. 7 - Typical Peak Clamping Voltage V_C vs. Peak Pulse Current I_{PP}

Fig. 10 - Typical Clamping Performance at - 8 kV Contact Discharge (acc. IEC 61000-4-2)


Fig. 8 - Typical Peak Clamping Voltage V_C vs. Peak Pulse Current I_{PP}

Fig. 11 - Typical Clamping Performance at + 8 kV Contact Discharge (acc. IEC 61000-4-2)


Fig. 9 - Typical Clamping Performance at + 8 kV Contact Discharge (acc. IEC 61000-4-2)


Fig. 12 - Typical Clamping Performance at - 8 kV Contact Discharge (acc. IEC 61000-4-2)

Fig. 13 - Typical Clamping Voltage at after 30 ns of ESD Contact Discharge (acc. IEC 61000-4-2)

Fig. 14 - Typical Clamping Voltage at after 30 ns of ESD Contact Discharge (acc. IEC 61000-4-2)

PACKAGE DIMENSIONS in millimeters (inches): **LLP75-7L**

Document no.:S8-V-3906.02-014 (4)
Created - Date: 04. April 2006
20500

LLP75-7x

Pad layout - view from top / seen at bottom side

S8-V-3906.02-008a (4)
10.12.2009

Pin 1 - location

S9
F5

For technical questions, contact: ESDprotection@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT
ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Revision: 01-Jan-2024   **1**   Document Number: 91000

For technical questions, contact:

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000