
RoHS

COMPLIANT



128 x 64 Graphic LCD



MECHANICAL DATA					
ITEM	STANDARD VALUE	UNIT			
Module dimension	93.0 x 70.0				
Viewing area	72.0 x 40.0				
Dot size	0.48 x 0.48	mm			
Dot pitch	0.52 x 0.52	mm			
Mounting hole	88.0 x 65.0				
Character size	n/a				

FEATURES

• Type: graphic

• Display format: 128 x 64 dots

• Built-in controller: NT7107, NT7108

Duty cycle: 1/64+5 V power supply

• N.V. built-in

LCD-128H064AB: N.V. option for +3.3 V
LCD-128H064A1: double row interface

Material categorization: for definitions of compliance

please see www.vishay.com/doc?99912

ABSOLUTE MAXIMUM RATINGS						
ITEM	SYMBOL	STAN	UNIT			
		MIN.	TYP.	MAX.	UNII	
Power supply	V_{DD} to V_{SS}	4.75	5.0	5.25	V	
Input voltage	Vı	- 0.3	_	V _{DD}	V	

Note

• $V_{SS} = 0 \text{ V}, V_{DD} = 5.0 \text{ V}$

ELECTRICAL CHARACTERISTICS							
ITEM	SYMBOL	CONDITION	STANDARD VALUE			UNIT	
		CONDITION	MIN.	TYP.	MAX.	ONIT	
Input voltage	V_{DD}	L level	0.7 V _{DD}	ı	V_{DD}	V	
	V _{IO}	H level	0	-	0.3 V _{DD}		
Supply current	I _{DD}	$V_{DD} = +5 \text{ V}$	-	2.5	7.5	mA	
	V _{DD} to V ₀	-20 °C	9.9	10.4	10.9		
		0 °C	9.7	10.2	10.7	V	
Recommended LC driving voltage for normal temperature version module		25 °C	8.9	9.4	9.9		
		50 °C	8.6	9.1	9.6	1	
		70 °C	8.4	8.9	9.4	İ	
LED forward voltage	V _F	25 °C	-	4.2	4.6	V	
LED forward current - array	1	25 °C	-	330	660	mA	
LED forward current - edge	· I _F	25 0	-	120	240	IIIA	
EL power supply current	I _{EL}	V _{EL} = 110 V _{AC} , 400 Hz	-	-	5.0	mA	


OPTIONS									
PROCESS COLOR							BACK	LIGHT	
TN	STN GRAY	STN YELLOW	STN BLUE	FSTN B&W	STN COLOR	NONE	LED	EL	CCFL
-	х	х	х	х	-	х	х	х	-

For detailed information, please see the "Product Numbering System" document.



www.vishay.com

INTERFACE PIN FUNCTION						
PIN NO.	SYMBOL	FUNCTION				
1	V _{SS}	Ground				
2	V _{DD}	Power supply (+5 V)				
3	V ₀	Contrast adjustment				
4	D/I	Data / instruction				
5	R/W	Data read / write				
6	E	$H \rightarrow L$ enable signal				
7	DB0	Data bus line				
8	DB1	Data bus line				
9	DB2	Data bus line				
10	DB3	Data bus line				
11	DB4	Data bus line				
12	DB5	Data bus line				
13	DB6	Data bus line				
14	DB7	Data bus line				
15	CS1	Chip select for IC1				
16	CS2	Chip select for IC1				
17	RST	Reset				
18	V _{EE}	Negative voltage output				
19	A	Power supply for LED (+4.2 V), $R_A = 0 \Omega$				
20	К	Power supply for LED (0 V)				





Legal Disclaimer Notice

Vishay

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.