P-Channel 20 V (D-S) MOSFET

MICRO FOOT® 0.8 x 0.8



Backside View



Bump Side View

FEATURES

- TrenchFET® Gen III p-channel power MOSFET
- Compact 0.8 mm x 0.8 mm outline area
- Low 0.4 mm max. profile
- $R_{DS(on)}$ rating at V_{GS} = -1.5 V
- Typical ESD protection: 1900 V HBM
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

Pb-free

RoHS COMPLIANT

HALOGEN FREE

APPLICATIONS

- Load switch
- Power management in battery-operated, mobile, and wearable devices



PRODUCT SUMMARY	
V_{DS} (V)	-20
$R_{DS(on)}$ max. (Ω) at V_{GS} = -4.5 V	0.095
$R_{DS(on)}$ max. (Ω) at V_{GS} = -2.5 V	0.120
$R_{DS(on)}$ max. (Ω) at V_{GS} = -1.8 V	0.200
$R_{DS(on)}$ max. (Ω) at V_{GS} = -1.5 V	0.335
Q_g typ. (nC)	6.6
I_D (A)	-2.7 [a]
Configuration	Single

ORDERING INFORMATION	
Package	MICRO FOOT
Lead (Pb)-free and halogen-free	Si8823EDB-T2-E1

ABSOLUTE MAXIMUM RATINGS (T_A = 25 °C, unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNIT
Drain-source voltage		V_{DS}	-20	V
Gate-source voltage		V_{GS}	± 8	
Continuous drain current (T_J = 150 °C)	T_A = 25 °C	I_D	-2.7 [a]	A
	T_A = 70 °C		-2.1 [a]	
	T_A = 25 °C		-1.9 [b]	
	T_A = 70 °C		-1.5 [b]	
Pulsed drain current (t = 100 µs)		I_{DM}	-15	
Continuous source-drain diode current	T_A = 25 °C	I_S	-0.7 [a]	
	T_A = 70 °C		-0.4 [b]	
Maximum power dissipation	T_A = 25 °C	P_D	0.9 [a]	W
	T_A = 70 °C		0.6 [a]	
	T_A = 25 °C		0.5 [b]	
	T_A = 70 °C		0.3 [b]	
Operating junction and storage temperature range		T_J, T_{stg}	-55 to +150	°C
Package reflow conditions [c]		VPR	260	
		IR / convection		

THERMAL RESISTANCE RATINGS

PARAMETER		SYMBOL	TYPICAL	MAXIMUM	UNIT
Maximum junction-to-ambient [a, f]	t = 5 s	R_{thJA}	105	135	°C/W
Maximum junction-to-ambient [b, g]			200	260	

Notes

a. Surface mounted on 1" x 1" FR4 board with full copper, t = 5 s.
b. Surface mounted on 1" x 1" FR4 board with minimum copper, t = 5 s.
c. Refer to IPC / JEDEC® (J-STD-020), no manual or hand soldering.
d. In this document, any reference to case represents the body of the MICRO FOOT device and foot is the bump.
e. Based on T_A = 25 °C.
f. Maximum under steady state conditions is 185 °C/W.
g. Maximum under steady state conditions is 330 °C/W.

SPECIFICATIONS (T_J = 25 °C, unless otherwise noted)						
PARAMETER	**SYMBOL**	**TEST CONDITIONS**	**MIN.**	**TYP.**	**MAX.**	**UNIT**
Static						
Drain-source breakdown voltage	V_{DS}	V_{GS} = 0 V, I_D = -250 µA	-20	-	-	V
V_{DS} temperature coefficient	$\Delta V_{DS}/T_J$	I_D = -250 µA	-	-12.5	-	mV/°C
$V_{GS(th)}$ temperature coefficient	$\Delta V_{GS(th)}/T_J$		-	2.3	-	
Gate-source threshold voltage	$V_{GS(th)}$	V_{DS} = V_{GS} , I_D = -250 µA	-0.4	-	-0.8	V
Gate-source leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = ± 4.5 V	-	-	± 0.5	µA
		V_{DS} = 0 V, V_{GS} = ± 8 V	-	-	± 5	
Zero gate voltage drain current	I_{DSS}	V_{DS} = -20 V, V_{GS} = 0 V	-	-	-1	
		V_{DS} = -20 V, V_{GS} = 0 V, T_J = 55 °C	-	-	-10	
On-state drain current [a]	$I_{D(on)}$	$V_{DS} \geq$ -5 V, V_{GS} = -4.5 V	-5	-	-	A
Drain-source on-state resistance [a]	$R_{DS(on)}$	V_{GS} = -4.5 V, I_D = -1 A	-	0.077	0.095	Ω
		V_{GS} = -2.5 V, I_D = -1 A	-	0.100	0.120	
		V_{GS} = -1.8 V, I_D = -0.5 A	-	0.137	0.185	
		V_{GS} = -1.5 V, I_D = -0.5 A	-	0.200	0.335	
Forward transconductance [a]	g_{fs}	V_{DS} = -5 V, I_D = -1 A	-	6	-	S
Dynamic [b]						
Input capacitance	C_{iss}	V_{DS} = -10 V, V_{GS} = 0 V, f = 1 MHz	-	580	-	pF
Output capacitance	C_{oss}		-	165	-	
Reverse transfer capacitance	C_{rss}		-	75	-	
Total gate charge	Q_g	V_{DS} = -10 V, V_{GS} = -8 V, I_D = -1 A	-	11	17	nC
		V_{DS} = -10 V, V_{GS} = -4.5 V, I_D = -1 A	-	6.6	10	
Gate-source charge	Q_{gs}	V_{DS} = -10 V, V_{GS} = -4.5 V, I_D = -1 A	-	1	-	
Gate-drain charge	Q_{gd}		-	1.5	-	
Gate resistance	R_g	f = 1 MHz	-	20	-	Ω
Turn-on delay time	$t_{d(on)}$	V_{DD} = -10 V, R_L = 10 Ω, $I_D \cong$ -1 A, V_{GEN} = -4.5 V, R_g = 1 Ω	-	16	30	ns
Rise time	t_r		-	30	60	
Turn-off delay time	$t_{d(off)}$		-	60	120	
Fall time	t_f		-	40	80	
Turn-on delay time	$t_{d(on)}$	V_{DD} = -10 V, R_L = 10 Ω, $I_D \cong$ -1 A, V_{GEN} = -8 V, R_g = 1 Ω	-	7	15	
Rise time	t_r		-	20	40	
Turn-off delay time	$t_{d(off)}$		-	75	150	
Fall time	t_f		-	35	70	
Drain-Source Body Diode Characteristics						
Continuous source-drain diode current	I_S	T_A = 25 °C	-	-	-0.7	A
Pulse diode forward current	I_{SM}		-	-	-15	
Body diode voltage	V_{SD}	I_S = -1 A, V_{GS} = 0 V	-	-0.8	-1.2	V
Body diode reverse recovery time	t_{rr}	I_F = -1 A, dI/dt = 100 A/µs, T_J = 25 °C	-	20	40	ns
Body diode reverse recovery charge	Q_{rr}		-	7	15	nC
Reverse recovery fall time	t_a		-	12.5	-	ns
Reverse recovery rise time	t_b		-	7.5	-	

Notes

a. Pulse test; pulse width ≤ 300 µs, duty cycle ≤ 2 %.

b. Guaranteed by design, not subject to production testing.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



Gate-Current vs. Gate-Source Voltage



Gate-Current vs. Gate-Source Voltage



Output Characteristics



Transfer Characteristics



On-Resistance vs. Drain Current and Gate Voltage



Capacitance

TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



Gate Charge



On-Resistance vs. Junction Temperature



Source-Drain Diode Forward Voltage



On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage



Single Pulse Power, Junction-to-Ambient

TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



Current Derating [a]



Power, Junction-to-Ambient



Safe Operating Area, Junction-to-Ambient

Note

a. The power dissipation P_D is based on T_J max. = 25 °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



Normalized Thermal Transient Impedance, Junction-to-Ambient (on 1" x 1" FR4 board with maximum copper)



Normalized Thermal Transient Impedance, Junction-to-Ambient (on 1" x 1" FR4 board with minimum copper)

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?76852.

MICRO FOOT®: 4-Bump (0.8 mm x 0.8 mm, 0.4 mm Pitch)



Mark on Backside of die





Note 4



Notes

(1) Laser mark on the backside surface of die
(2) Bumps are 95.5 % Sn,3.8 % Ag,0.7 % Cu
(3) "i" is the location of pin 1
(4) "b1" is the diameter of the solderable substrate surface, defined by an opening in the solder resist layer solder mask defined.
(5) Non-solder mask defined copper landing pad.

DIM.	MILLIMETERS [a]			INCHES		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	0.328	0.365	0.402	0.0129	0.0144	0.0158
A1	0.136	0.160	0.184	0.0053	0.0062	0.0072
A2	0.192	0.205	0.218	0.0076	0.0081	0.0086
b	0.200	0.220	0.240	0.0078	0.0086	0.0094
b1		0.175			0.0068	
e		0.400			0.0157	
S	0.160	0.180	0.200	0.0062	0.0070	0.0078
D	0.720	0.760	0.800	0.0283	0.0299	0.0314
K	0.040	0.070	0.100	0.0015	0.0027	0.0039

Note

a. Use millimeters as the primary measurement.

ECN: T15-0053-Rev. A, 16-Feb-15
DWG: 6033

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.