


High Frequency, Surface Mount Inductors


RoHS
COMPLIANT

FEATURES

- High self-resonant frequency values
- High Q values at higher frequencies
- Wirewound construction
- Compatible with vapor phase and infrared reflow soldering
- Tape and reel packaging for automatic handling, 2000/reel
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

ELECTRICAL SPECIFICATIONS

Inductance Range: 3.3 nH to 47 000 nH

Inductance and Tolerance: 0.3 nH for 3.3 nH
± 5 % for 6.8 nH to 47 000 nH

Operating Temperature: -40 °C to +125 °C


Core Material: Ceramic from 3.3 nH to 1000 nH
Ferrite from 1200 nH to 47 000 nH

TEST EQUIPMENT

- Inductance and Q measured on HP4286A
- SRF measured on HP8753D

STANDARD ELECTRICAL SPECIFICATIONS						
IND. (nH)	TOL.	TEST FREQ. (MHz)		Q MIN.	SRF MIN. (MHz)	DCR MAX. (Ω)
		L	Q			
3.3	0.3 nH	100	1000	50	6000	0.06
6.8	5 %	100	1000	50	5500	0.06
8.2	5 %	100	1000	50	5500	0.06
10	5 %	100	1000	50	4300	0.08
12	5 %	100	500	60	3600	0.08
15	5 %	100	500	60	2700	0.08
18	5 %	100	350	60	2700	0.10
22	5 %	100	350	60	2500	0.10
27	5 %	100	350	60	1800	0.10
33	5 %	100	350	60	1700	0.10
39	5 %	100	350	60	1500	0.10
47	5 %	100	350	60	1500	0.10
56	5 %	100	350	60	1350	0.12
68	5 %	100	350	60	1300	0.15
82	5 %	100	350	60	1100	0.18
100	5 %	100	350	60	1100	0.18
120	5 %	25	100	45	950	0.20
150	5 %	25	100	45	880	0.22
180	5 %	25	100	45	800	0.33
220	5 %	25	100	45	730	0.45
270	5 %	25	100	45	650	0.75
330	5 %	25	100	45	570	0.90
390	5 %	25	100	45	530	1.06
470	5 %	25	100	45	480	1.17
560	5 %	25	100	45	430	1.50
680	5 %	25	100	45	380	2.06
750	5 %	25	100	45	360	2.20
820	5 %	25	100	45	350	2.30
910	5 %	25	100	45	330	3.18
1000	5 %	25	50	35	310	3.30
1200	5 %	7.96	7.96	20	280	1.30
1500	5 %	7.96	7.96	20	250	1.65
1800	5 %	7.96	7.96	20	200	2.20
2200	5 %	7.96	7.96	20	160	2.35
2700	5 %	7.96	7.96	20	130	2.60
3300	5 %	7.96	7.96	20	80	2.85
3900	5 %	7.96	7.96	20	50	4.00
4700	5 %	7.96	7.96	20	45	4.30
5600	5 %	7.96	7.96	20	42	2.60
6800	5 %	7.96	7.96	20	39	2.80
8200	5 %	7.96	7.96	20	36	3.05
10 000	5 %	2.52	2.52	15	33	3.50
12 000	5 %	2.52	2.52	15	30	3.60
15 000	5 %	2.52	2.52	15	26	4.00
18 000	5 %	2.52	2.52	15	24	4.50
22 000	5 %	2.52	2.52	15	22	5.00
27 000	5 %	2.52	2.52	15	21	6.00
33 000	5 %	2.52	2.52	15	20	6.50
39 000	5 %	2.52	2.52	15	18	8.50
47 000	5 %	2.52	2.52	15	17	14.00

DIMENSIONS in inches [millimeters]



DESCRIPTION






IMC-1008	10 nH	± 5 %	ER	e4 (1)
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC® LEAD (Pb)-FREE STANDARD

Note

- (1) For parts within 3.3 nH to 910 nH please use e4 for JEDEC lead (Pb)-free standard. For parts within 1000 nH to 47 000 nH please use e3 for JEDEC lead (Pb)-free standard.

GLOBAL PART NUMBER

I	M	C	1	0	0	8	E	R	1	0	N	J
PRODUCT FAMILY			SIZE				PACKAGE CODE		INDUCTANCE VALUE			TOL.

PERFORMANCE GRAPHS IMC-1008

TAPE AND REEL SPECIFICATIONS in inches [millimeters]
REEL DIMENSIONS

TAPE DIMENSIONS

RECOMMENDED PATTERN


MODEL	UNITS PER REEL	MODEL	A	B	T	MODEL	A	B	C
IMC-1008	2000	IMC-1008	0.087 [2.20]	0.110 [2.80]	0.071 [1.80]	IMC-1008	0.047 [1.20]	0.150 [3.80]	0.100 [2.54]



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.