Automotive N-and P-Channel 30 V (D-S) 175 °C MOSFET



Marking Code: Q4532A

FEATURES

- TrenchFET® power MOSFET
- AEC-Q101 qualified [c]
- 100 % R_g and UIS tested
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

AUTOMOTIVE GRADE

Pb-free

RoHS COMPLIANT

HALOGEN FREE



PRODUCT SUMMARY		
	N-CHANNEL	P-CHANNEL
V_{DS} (V)	30	-30
$R_{DS(on)}$ (Ω) at V_{GS} = ± 10 V	0.031	0.070
$R_{DS(on)}$ (Ω) at V_{GS} = ± 4.5 V	0.042	0.190
I_D (A)	7.3	-5.3
Configuration	N- and p-pair	

ORDERING INFORMATION	
Package	SO-8
Lead (Pb)-free and halogen-free	SQ4532AEY (for detailed order number please see www.vishay.com/doc?79771)

ABSOLUTE MAXIMUM RATINGS (T_C = 25 °C, unless otherwise noted)					
PARAMETER		SYMBOL	N-CHANNEL	P-CHANNEL	UNIT
Drain-source voltage		V_{DS}	30	-30	V
Gate-source voltage		V_{GS}	± 20		
Continuous drain current	T_C = 25 °C	I_D	7.3	-5.3	A
	T_C = 125 °C		4.2	-3	
Continuous source current (diode conduction)		I_S	4.2	-3	
Pulsed drain current [a]		I_{DM}	29	-21	
Single pulse avalanche current	L = 0.1 mH	I_{AS}	10	-9	
Single pulse avalanche energy		E_{AS}	5	4	mJ
Maximum power dissipation [a]	T_C = 25 °C	P_D	3.3	3.3	W
	T_C = 125 °C		1.1	1.1	
Operating junction and storage temperature range		T_J, T_{stg}	-55 to +175		°C

THERMAL RESISTANCE RATINGS					
PARAMETER		SYMBOL	N-CHANNEL	P-CHANNEL	UNIT
Junction-to-ambient	PCB mount [b]	R_{thJA}	110	105	°C/W
Junction-to-foot (drain)		R_{thJF}	45	45	

Notes

a. Pulse test; pulse width ≤ 300 µs, duty cycle ≤ 2 %
b. When mounted on 1" square PCB (FR4 material)
c. Parametric verification ongoing

SPECIFICATIONS (T_C = 25 °C, unless otherwise noted)								
PARAMETER	**SYMBOL**	**TEST CONDITIONS**			**MIN.**	**TYP.**	**MAX.**	**UNIT**
Static								
Drain-source breakdown voltage	V_{DS}	V_{GS} = 0, I_D = 250 µA		N-Ch	30	-	-	V
		V_{GS} = 0, I_D = -250 µA		P-Ch	-30	-	-	
Gate-source threshold voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 250 µA		N-Ch	1.5	2	2.5	
		V_{DS} = V_{GS}, I_D = -250 µA		P-Ch	-1.5	-2	-2.5	
Gate-source leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = ± 20 V		N-Ch	-	-	± 100	nA
				P-Ch	-	-	± 100	
Zero gate voltage drain current	I_{DSS}	V_{GS} = 0 V	V_{DS} = 30 V	N-Ch	-	-	1	µA
		V_{GS} = 0 V	V_{DS} = -30 V	P-Ch	-	-	-1	
		V_{GS} = 0 V	V_{DS} = 30 V, T_J = 125 °C	N-Ch	-	-	50	
		V_{GS} = 0 V	V_{DS} = -30 V, T_J = 125 °C	P-Ch	-	-	-50	
		V_{GS} = 0 V	V_{DS} = 30 V, T_J = 175 °C	N-Ch	-	-	150	
		V_{GS} = 0 V	V_{DS} = -30 V, T_J = 175 °C	P-Ch	-	-	-150	
On-state drain current [a]	$I_{D(on)}$	V_{GS} = 10 V	V_{DS} = 5 V	N-Ch	15	-	-	A
		V_{GS} = -10 V	V_{DS} = -5 V	P-Ch	-15	-	-	
Drain-source on-state resistance [a]	$R_{DS(on)}$	V_{GS} = 10 V	I_D = 4.9 A	N-Ch	-	0.021	0.031	Ω
		V_{GS} = -10 V	I_D = -3.5 A	P-Ch	-	0.056	0.070	
		V_{GS} = 10 V	I_D = 4.9 A, T_J = 125 °C	N-Ch	-	-	0.064	
		V_{GS} = -10 V	I_D = -3.5 A, T_J = 125 °C	P-Ch	-	-	0.100	
		V_{GS} = 10 V	I_D = 4.9 A, T_J = 175 °C	N-Ch	-	-	0.082	
		V_{GS} = -10 V	I_D = -3.5 A, T_J = 175 °C	P-Ch	-	-	0.117	
		V_{GS} = 4.5 V	I_D = 4.1 A	N-Ch	-	0.033	0.042	
		V_{GS} = -4.5 V	I_D = -2.5 A	P-Ch	-	0.157	0.190	
Forward transconductance [b]	g_{fs}	V_{DS} = 15 V, I_D = 4.9 A		N-Ch	-	22	-	S
		V_{DS} = -15 V, I_D = -3.5 A		P-Ch	-	5.5	-	
Dynamic [b]								
Input capacitance	C_{iss}	V_{GS} = 0 V	V_{DS} = 15 V, f = 1 MHz	N-Ch	-	357	535	pF
		V_{GS} = 0 V	V_{DS} = -15 V, f = 1 MHz	P-Ch	-	352	528	
Output capacitance	C_{oss}	V_{GS} = 0 V	V_{DS} = 15 V, f = 1 MHz	N-Ch	-	82	123	
		V_{GS} = 0 V	V_{DS} = -15 V, f = 1 MHz	P-Ch	-	95	142	
Reverse transfer capacitance	C_{rss}	V_{GS} = 0 V	V_{DS} = 15 V, f = 1 MHz	N-Ch	-	36	53	
		V_{GS} = 0 V	V_{DS} = -15 V, f = 1 MHz	P-Ch	-	59	88	
Total gate charge	Q_g	V_{GS} = 10 V	V_{DS} = 15 V, I_D = 3.9 A	N-Ch	-	5.9	7.8	nC
		V_{GS} = -10 V	V_{DS} = -15 V, I_D = -2.5 A	P-Ch	-	7.9	10.2	
Gate-source charge	Q_{gs}	V_{GS} = 10 V	V_{DS} = 15 V, I_D = 3.9 A	N-Ch	-	1	-	
		V_{GS} = -10 V	V_{DS} = -15 V, I_D = -2.5 A	P-Ch	-	1.1	-	
Gate-drain charge [c]	Q_{gd}	V_{GS} = 10 V	V_{DS} = 15 V, I_D = 3.9 A	N-Ch	-	1.9	-	
		V_{GS} = -10 V	V_{DS} = -15 V, I_D = -2.5 A	P-Ch	-	2.7	-	
Gate resistance	R_g	f = 1 MHz		N-Ch	1.7	3.4	5.1	Ω
				P-Ch	2.8	5.8	8.6	

SPECIFICATIONS (T_C = 25 °C, unless otherwise noted)							
PARAMETER	**SYMBOL**	**TEST CONDITIONS**		**MIN.**	**TYP.**	**MAX.**	**UNIT**
Turn-on delay time	$t_{d(on)}$	V_{DD} = 15 V, R_L = 15 Ω $I_D \cong$ 1 A, V_{GEN} = 10 V, R_g = 1 Ω	N-Ch	-	7	10	ns
		V_{DD} = -15 V, R_L = 15 Ω $I_D \cong$ -1 A, V_{GEN} = -10 V, R_g = 1 Ω	P-Ch	-	6	9	
Rise time	t_r	V_{DD} = 15 V, R_L = 15 Ω $I_D \cong$ 1 A, V_{GEN} = 10 V, R_g = 1 Ω	N-Ch	-	17	21	
		V_{DD} = -15 V, R_L = 15 Ω $I_D \cong$ -1 A, V_{GEN} = -10 V, R_g = 1 Ω	P-Ch	-	17	21	
Turn-off delay time	$t_{d(off)}$	V_{DD} = 15 V, R_L = 15 Ω $I_D \cong$ 1 A, V_{GEN} = 10 V, R_g = 1 Ω	N-Ch	-	10	14	
		V_{DD} = -15 V, R_L = 15 Ω $I_D \cong$ -1 A, V_{GEN} = -10 V, R_g = 1 Ω	P-Ch	-	19	24	
Fall time	t_f	V_{DD} = 15 V, R_L = 15 Ω $I_D \cong$ 1 A, V_{GEN} = 10 V, R_g = 1 Ω	N-Ch	-	19	24	
		V_{DD} = -15 V, R_L = 15 Ω $I_D \cong$ -1 A, V_{GEN} = -10 V, R_g = 1 Ω	P-Ch	-	16	20	
Source-Drain Diode Ratings and Characteristics [b]							
Pulsed current [a]	I_{SM}		N-Ch	-	-	29	A
			P-Ch	-	-	-21	
Forward voltage	V_{SD}	I_S = 2 A	N-Ch	-	0.8	1.2	V
		I_S = -1.5 A	P-Ch	-	-0.8	-1.2	

Notes

a. Pulse test; pulse width ≤ 300 µs, duty cycle ≤ 2 %

b. Guaranteed by design, not subject to production testing

c. Independent of operating temperature

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

N-CHANNEL TYPICAL CHARACTERISTICS (T_A = 25 °C, unless otherwise noted)



Output Characteristics



Transfer Characteristics



On-Resistance vs. Drain Current



Capacitance



Gate Charge



On-Resistance vs. Junction Temperature

N-CHANNEL TYPICAL CHARACTERISTICS (T_A = 25 °C, unless otherwise noted)



Transfer Characteristics



Threshold Voltage



Source Drain Diode Forward Voltage



On-Resistance vs. Gate-to-Source Voltage



Transconductance



Drain Source Breakdown vs. Junction Temperature

N-CHANNEL THERMAL RATINGS (T_A = 25 °C, unless otherwise noted)



Safe Operating Area

Note

a. V_{GS} > minimum V_{GS} at which $R_{DS(on)}$ is specified

N-CHANNEL THERMAL RATINGS (T_A = 25 °C, unless otherwise noted)



Normalized Thermal Transient Impedance, Junction-to-Ambient



Normalized Thermal Transient Impedance, Junction-to-Foot

Note

- The characteristics shown in the two graphs
  - Normalized Transient Thermal Impedance Junction-to-Ambient (25 °C)
  - Normalized Transient Thermal Impedance Junction-to-Case (25 °C)

  are given for general guidelines only to enable the user to get a “ball park” indication of part capabilities. The data are extracted from single pulse transient thermal impedance characteristics which are developed from empirical measurements. The latter is valid for the part mounted on printed circuit board - FR4, size 1" x 1" x 0.062", double sided with 2 oz. copper, 100 % on both sides. The part capabilities can widely vary depending on actual application parameters and operating conditions.

P-CHANNEL TYPICAL CHARACTERISTICS (T_A = 25 °C, unless otherwise noted)



Output Characteristics



Transfer Characteristics



On-Resistance vs. Drain Current



Capacitance



Gate Charge



On-Resistance vs. Junction Temperature

P-CHANNEL TYPICAL CHARACTERISTICS (T_A = 25 °C, unless otherwise noted)



Transfer Characteristics



Threshold Voltage



Source Drain Diode Forward Voltage



On-Resistance vs. Gate-to-Source Voltage



Transconductance



Drain Source Breakdown vs. Junction Temperature

P-CHANNEL THERMAL RATINGS (T_A = 25 °C, unless otherwise noted)



Safe Operating Area

Note

a. V_{GS} > minimum V_{GS} at which $R_{DS(on)}$ is specified

P-CHANNEL THERMAL RATINGS (T_A = 25 °C, unless otherwise noted)



Normalized Thermal Transient Impedance, Junction-to-Ambient



Normalized Thermal Transient Impedance, Junction-to-Foot

Note

- The characteristics shown in the two graphs
  - Normalized Transient Thermal Impedance Junction-to-Ambient (25 °C)
  - Normalized Transient Thermal Impedance Junction-to-Case (25 °C)

  are given for general guidelines only to enable the user to get a “ball park” indication of part capabilities. The data are extracted from single pulse transient thermal impedance characteristics which are developed from empirical measurements. The latter is valid for the part mounted on printed circuit board - FR4, size 1" x 1" x 0.062", double sided with 2 oz. copper, 100 % on both sides. The part capabilities can widely vary depending on actual application parameters and operating conditions.

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?62981.

SOIC (NARROW): 8-LEAD
JEDEC Part Number: MS-012



DIM	MILLIMETERS		INCHES	
	Min	Max	Min	Max
A	1.35	1.75	0.053	0.069
A_1	0.10	0.20	0.004	0.008
B	0.35	0.51	0.014	0.020
C	0.19	0.25	0.0075	0.010
D	4.80	5.00	0.189	0.196
E	3.80	4.00	0.150	0.157
e	1.27 BSC		0.050 BSC	
H	5.80	6.20	0.228	0.244
h	0.25	0.50	0.010	0.020
L	0.50	0.93	0.020	0.037
q	0°	8°	0°	8°
S	0.44	0.64	0.018	0.026
ECN: C-06527-Rev. I, 11-Sep-06 DWG: 5498				

RECOMMENDED MINIMUM PADS FOR SO-8



Recommended Minimum Pads
Dimensions in Inches/(mm)

Return to Index

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.