

# Juan Claimed

Six figures covering request flow, the eligibility engine's decision logic, eGovPH API integration points, the data model, and the deploy pipeline — the citizen-facing benefits matcher built for a hackathon centered on eGovPH platform integration.


**Rev.** 2026-09-09    **Stack** React · Express · PostgreSQL    **Repository** [github.com/sudowares/juan-claimed](https://github.com/sudowares/juan-claimed)

---

## Figure 1. System Overview

---

One request path from browser to database, plus the eGovPH platform the backend is actually, live, wired into.




*Frontend → Backend → PostgreSQL, eGovPH, and Vercel Blob*

The **eGovPH Platform** box on the right isn't aspirational — `egovApi.service.ts` makes real HTTP calls out to it for SSO, eMessage, and AI Core, exercised by actual routes in the product (sign-in, benefit-publish SMS, translate-while-authoring); Figure 4 breaks down exactly which endpoints. The frontend never talks to Postgres, eGovPH, or Blob directly — every read or write is mediated by the backend's service layer. The dashed line to **Vercel Blob** is deliberately drawn apart from the solid "fetch" flows: the file's actual bytes go straight from the browser to Blob on a separate upload path (client-direct, using a short-lived token the backend issues), and only the resulting URL and metadata round-trip back through the backend to be saved — the full upload sequence is documented in the project's GitHub repository.

## Figure 2. eGovPH Sign-in Sequence

A real, working eGovPH SSO login — one exchange code becomes this backend's own JWT, and seeds the citizen's first answers along the way.




*Citizen → Frontend → Backend → eGov SSO → Database, nine steps end to end*

Every step here is a real network call against eGovPH's own SSO API ( `hackathon-sso.e.gov.ph` ), not a mocked login screen — steps 3 and 5 are live requests to eGov's servers with our partner credentials, and step 6's profile payload is genuine eGov identity data. The token the frontend ends up with (step 9) is **this backend's own JWT**, signed with `JWT_SECRET` — eGov's `access_token` from step 4 is single-use and never leaves the backend. Steps 7–8 are what make eGovPH sign-in more than authentication: known profile fields (date of birth, residence, name) are written straight into the citizen's answers on first login, so the eligibility quiz never re-asks something eGov already told us.

### Figure 3. Eligibility Engine — Leaf Evaluation

A missing answer is never an automatic fail — it's a fail only if another condition has already ruled it out.




Decision flow for evaluating a single eligibility condition

An unanswered field only becomes a hard **NOT\_ELIGIBLE** when it's **hidden by its parent field** — a follow-up field whose own visibility condition has already resolved against the applicant, so asking it can no longer change anything. Otherwise a missing answer is **PENDING**: it keeps resurfacing in "Answer More" because it could still tip the outcome either way. Once a field does have an answer, it's compared straight against the condition's operator to resolve **MATCHED** or **NOT\_ELIGIBLE**. Applies identically to a signed-in citizen and to a guest's in-browser answers. This diagram is **one condition** — a benefit's full eligibility rule is a tree of these, and the same evaluation repeats for every condition in it. One unmatched condition anywhere in the tree is enough to make the whole benefit **NOT\_ELIGIBLE**; only once every condition comes back **MATCHED** (and none are still **PENDING**) does the benefit itself resolve to **MATCHED** — how **ALL/ANY** groups combine these per-condition results is covered in the project's GitHub repository.

## Figure 4. eGov API Integration Points


Three eGovPH products, actually called by live routes in the product — not credentials sitting unused.



This is the actual eGovPH integration surface of the product, end to end: a citizen signing in with **SSO**, an agent publishing a benefit and the platform pushing **eMessage** SMS to every citizen who now qualifies, and an admin drafting a field or benefit in English and getting a Tagalog translation from **AI Core** with one click. Each is exercised by a real feature a user can click through today, not a health-check ping — try any of the three in the live app and it round-trips through eGovPH's own sandbox APIs. All three calls fail closed and silently — a failed API request is logged, never something the user sees break.

Figure 5. Data Model


Two parallel condition trees over the same reusable fields: one decides benefit eligibility, the other decides field visibility.



Two structurally identical condition-tree systems, kept deliberately separate: a **Benefit Rule Group** tree (over `Benefit Field Condition`) decides whether a benefit matches, while a **Dynamic Rule Group** tree (over `Dynamic Field Condition`) decides whether a single **FOLLOW-UP**-classified field is even shown — that's the actual mechanism behind an anchored field only appearing once its parent is answered a specific way, not a simple parent pointer. Both trees bottom out in the same reusable `Field` table, which is also where `Field Options` (select choices) and `Hierarchy / Hierarchy Levels / Hierarchy Nodes` (PSGC location, business-sector taxonomies, ...) attach. A citizen's `User Field Answers` reference that same `Field` table, so one answer can satisfy conditions in both trees at once.

## Figure 6. Deployment Pipeline

A push builds once and lands on the VPS as a pull, never a rebuild on the server.



*Dev push → GitHub Actions → registry → staging/prod VPS → Nginx*

The two VPS compose files only ever `pull` — no `build:`, no bind mount, no git checkout on the server. Each push tags images two ways: a floating `latest / staging` tag plus an immutable `<branch>-<timestamp>-<sha>` tag, so rolling back is re-pointing the compose file at an older tag, not rebuilding. Postgres and Prisma Studio have no public port in either stack — only Nginx is reachable from outside.

