

RADIONUCLIDE SAFETY DATA SHEET																																									
RADIONUCLIDE: Mn-52			FORMS: Soluble																																						
PHYSICAL CHARACTERISTICS HALF-LIFE: 5.6 days DECAY EMISSIONS																																									
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">Gammas / X-rays</th> <th colspan="2">Betas / Positrons (+) / Electrons*</th> <th colspan="2">Alphas</th> </tr> <tr> <th>E (keV)</th> <th>%</th> <th>E (keV, Ave)</th> <th>%</th> <th>E (keV)</th> <th>%</th> </tr> </thead> <tbody> <tr> <td>1434</td> <td>100</td> <td>242(+)</td> <td>30</td> <td></td> <td></td> </tr> <tr> <td>936</td> <td>95</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>744</td> <td>90</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>511</td> <td>59</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>		Gammas / X-rays		Betas / Positrons (+) / Electrons*		Alphas		E (keV)	%	E (keV, Ave)	%	E (keV)	%	1434	100	242(+)	30			936	95					744	90					511	59								
Gammas / X-rays		Betas / Positrons (+) / Electrons*		Alphas																																					
E (keV)	%	E (keV, Ave)	%	E (keV)	%																																				
1434	100	242(+)	30																																						
936	95																																								
744	90																																								
511	59																																								
- Only 4 most probable emissions per decay type included. Emissions below 10 keV or 1% excluded.																																									
STANFORD HAZARD CATEGORY C – level (low hazard): ≤ 20 mCi B – level (moderate hazard): > 20 mCi ≤ 1 Ci A – level (high hazard): > 1 Ci																																									
EXTERNAL RADIATION HAZARDS Gamma dose rate, point source at 1 ft, 1 mCi: 17.5 mrem/h Beta dose rate to skin, point source at 1 ft, 1 mCi: 129 mrem/h Contamination skin dose, uniform deposit of 1 µCi per cm²: 2800 mrem/h			INTERNAL RADIATION HAZARDS Annual Limit on Intake: 700 µCi (Ingestion) 900 µCi (Inhalation) The values above indicate the activity taken into the body that would result in either 5 rem to the whole body (CEDE) or 50 rem to an organ or tissue (CDE).																																						
SHIELDING Gammas/X-rays: 3.9 cm of lead will reduce the gamma dose rate by 90%. Betas/electrons: 1.5 mm of plastic will absorb all emissions. Bremsstrahlung may be created and require additional shielding.			DOSIMETRY AND BIOASSAY REQS Whole-body and finger-ring dosimeters are required for handling 5 mCi or more, or 1 mCi amounts weekly . Urine assays may be required after large spills or contaminations.																																						
SPECIAL PROBLEMS AND PRECAUTIONS: 1. Recommended survey probe: PGM or NaI 2. Always wear protective gloves, a lab coat, and safety eyewear to protect the skin and eyes from contamination. Change gloves often. 3. Survey work areas before, during, and after work. Work areas may require shielding to keep dose ALARA. Instrument and smear surveys are required. 4. Segregate waste to those with half-lives of between 1 and 8 days. Survey the waste disposal area to ensure exposure rates are less than 2 mR/hr at 1 foot. 5. Limit soluble waste to the sewer to less than 100 µCi/day per lab.																																									

References:

- Delacroix, D., Guerre, J.P., Leblanc, P., Hickman, C. (2002). Radionuclide and Radiation Protection Data Handbook (2nd ed.). Ashford, Kent: Nuclear Technology Publishing.
- Johnson, T.E., Birky, B.K. (2012). Health Physics and Radiological Health (4th ed.). Baltimore, MD: Lippincott Williams & Wilkins.
- ICRP, 2008. Nuclear Decay Data for Dosimetric Calculations. ICRP Publication 107. Ann. ICRP 38 (3).
- Peplow, D. (2020) Specific Gamma-Ray Dose Constants with Current Emission Data. *Health Physics*, 118(4):402-416; 2020.
- Smith, D., Stabin, M. (2012) Exposure Rate Constants and Lead Shielding Values for Over 1,100 Radionuclides. *Health Physics*, 102(3): 271-291.
- 10.CFR.20 – Standards for Protection Against Radiation (2019). Retrieved from <https://www.nrc.gov/reading-rm/doc-collections/cfr/part020/>