

OPERATING SYSTEMS EXERCISE 3

Aufgabenstellung – lastmsg

Man implementiere ein Programm, das den Inhalt eines Shared-Memory-Segments als String ausliest und eventuell durch einen neuen String ersetzt.

SYNOPSIS

```
lastmsg [-i id] [-c|-d] ["Message"]
```

Die `id` (`-i`) steht für die ID des Shared-Memory-Segments (per default: die eigene Matrikelnummer). Die ID des Semaphores ist die um eins erhöhte (default: Matrikelnummer + 1).

Mit `-c` wird ein neues Shared-Memory-Segment und eine Semaphore angelegt. Mit `-d` werden diese wieder gelöscht.

Das optionale Argument `"Message"` ist der in das Shared Memory zu schreibende String.

Anleitung

Wird die Option `-c` übergeben, so soll ein neues Shared-Memory-Segment angelegt werden – entweder mit der voreingestellten `id` (Matrikelnummer), oder mit einer über die Option `-i` übergebenen `id`. Außerdem soll eine Semaphore mit der um eins erhöhten `id` des Shared-Memory-Segments angelegt werden.

Die Option `-d` löscht Shared Memory und Semaphore wieder (auch hier ist die mit `-i` übergebene `id` zu beachten).

Das Programm soll den im Shared Memory befindlichen String auf die Konsole ausgeben (außer `-c` wurde angegeben).

Wird eine `"Message"` übergeben, so soll das Programm diese in den Shared Memory schreiben (außer `-d` wurde angegeben).

Hinweise

Die Optionen `-c` und `-d` schließen sich wechselseitig aus. Außerdem darf keine `"Message"` angegeben werden, wenn die Option `-d` gesetzt ist. Wird die Option `-c` ohne `"Message"` angegeben, soll das neu angelegte Shared Memory mit einem leeren String befüllt werden.

Testen

Mit folgendem Shell-Skript lässt sich testen, ob sich das Programm korrekt verhält:

```
#!/bin/sh
./lastmsg -c 1234

(
    for i in $(seq 1000)
    do
        ./lastmsg foo &
        ./lastmsg bar &
        ./lastmsg blah &
    done
    wait
    ./lastmsg -d
) > foo.tmp

grep -c foo foo.tmp
grep -c bar foo.tmp
grep -c blah foo.tmp
rm -f foo.tmp
```

Als Ergebnis soll drei mal „1000“ ausgegeben werden. Weichen diese Werte ab, so liegt vermutlich ein Synchronisierungsproblem vor.

Coding Rules and Guidelines

Your score depends upon the compliance of your submission to the presented guidelines and rules. Violations result in deductions of points. Hence, before submitting your solution, go through the following list and check if your program complies.

Rules

Compliance with these rules is essential to get any points for your submission. A violation of any of the following rules results in 0 points for your submission.

1. All source files of your program(s) must compile via

```
$ gcc -std=c99 -pedantic -Wall -D_DEFAULT_SOURCE -D_BSD_SOURCE -D_SVID_SOURCE  
-D_POSIX_C_SOURCE=200809L -g -c filename.c
```

without *errors* and your program(s) must link without *errors*. The compilation flags must be used in the Makefile. The feature test macros must not be bypassed (i.e., by undefining these macros or adding some in the C source code).

2. The functionality of the program(s) must conform to the assignment. The program(s) shall operate according to the specification/assignment given the test cases in the respective assignment.

General Guidelines

Violation of following guidelines leads to a deduction of points.

1. All source files of your program(s) must compile with

```
$ gcc -std=c99 -pedantic -Wall -D_DEFAULT_SOURCE -D_BSD_SOURCE -D_SVID_SOURCE  
-D_POSIX_C_SOURCE=200809L -g -c filename.c
```

without *warnings and info messages* and your program(s) must link without warnings.

2. There must be a Makefile implementing the targets: **all** to build the program(s) (i.e. generate executables) from the sources (this must be the first target in the Makefile); **clean** to delete all files that can be built from your sources with the Makefile.
3. The program shall operate according to the specification/assignment without major issues (e.g., segmentation fault, memory corruption).
4. Arguments have to be parsed according to UNIX conventions (we strongly encourage the use of **getopt(3)**). The program has to conform to the given synopsis/usage in the assignment. If the synopsis is violated (e.g., unspecified options or too many arguments), the program has to terminate with the usage message containing the program name and the correct calling syntax. Argument handling should also be implemented for programs without arguments.
5. Correct (=normal) termination, including a cleanup of resources.
6. Upon success the program has to terminate with exit code 0, in case of errors with an exit code greater than 0. We recommend to use the macros **EXIT_SUCCESS** and **EXIT_FAILURE** (defined in **stdlib.h**) to enable portability of the program.
7. If a function indicates an error with its return value, it *should* be checked in general. If the subsequent code depends on the successful execution of a function (e.g. resource allocation), then the return value *must* be checked.

8. Functions that do not take any parameters have to be declared with **void** in the signature, e.g., `int get_random_int(void);`.
9. Procedures (i.e., functions that do not return a value) have to be declared as **void**.
10. Error messages shall be written to **stderr** and should contain the program name **argv[0]**.
11. It is forbidden to use the functions: **gets**, **scanf**, **fscanf**, **atoi** and **atol** to avoid crashes due to invalid inputs.

| FORBIDDEN | USE INSTEAD |
|---------------------|--|
| <code>gets</code> | <code>fgets</code> |
| <code>scanf</code> | <code>fgets</code> , <code>sscanf</code> |
| <code>fscanf</code> | <code>fgets</code> , <code>sscanf</code> |
| <code>atoi</code> | <code>strtol</code> |
| <code>atol</code> | <code>strtol</code> |

12. Documentation is mandatory. Format the documentation in Doxygen style (see Wiki and Doxygen's intro).
13. Write meaningful comments. For example, meaningful comments describe the algorithm, or why a particular solution has been chosen, if there seems to be an easier solution at a first glance. Avoid comments that just repeat the code itself (e.g., `i = i + 1; /* i is incremented by one */`).
14. The documentation of a module must include: name of the module, name and student id of the author (**@author** tag), purpose of the module (**@brief**, **@details** tags) and creation date of the module (**@date** tag).
Also the Makefile has to include a header, with author and program name at least.
15. Each function shall be documented either before the declaration or the implementation. It should include purpose (**@brief**, **@details** tags), description of parameters and return value (**@param**, **@return** tags) and description of global variables the function uses (**@details** tag).
You should also document **static** functions (see **EXTRACT_STATIC** in the file **Doxyfile**). Document visible/exported functions in the header file and local (**static**) functions in the C file. Document variables, constants and types (especially **structs**) too.
16. Documentation, names of variables and constants shall be in English.
17. Internal functions shall be marked with the **static** qualifier and are not allowed to be exported (e.g., in a header file). Only functions that are used by other modules shall be declared in the header file.
18. All exercises shall be solved with functions of the C standard library. If a required function is not available in the standard library, you can use other (external) functions too. Avoid reinventing the wheel (e.g., re-implementation of **strcmp**).
19. Name of constants shall be written in upper case, names of variables in lower case (maybe with first letter capital).
20. Use meaningful variable and constant names (e.g., also semaphores and shared memories).
21. Avoid using global variables as far as possible.
22. All boundaries shall be defined as constants (macros). Avoid arbitrary boundaries. If boundaries are necessary, treat its crossing.
23. Avoid side effects with **&&** and **||**, e.g., write `if (b != 0) c = a/b;` instead of `if (b != 0 && c = a/b).`

24. Each **switch** block must contain a **default** case. If the case is not reachable, write **assert(0)** to this case (defensive programming).
25. Logical values shall be treated with logical operators, numerical values with arithmetic operators (e.g., test 2 strings for equality by `strcmp(...) == 0` instead of `!strcmp(...)`).
26. Indent your source code consistently (there are tools for that purpose, e.g., **indent**).
27. Avoid tricky arithmetic statements. Programs are written once, but read more times. Your program is not better if it is shorter!
28. For all I/O operations (read/write from/to **stdin**, **stdout**, files, sockets, pipes, etc.) use *either* standard I/O functions (**fdopen(3)**, **fopen(3)**, **fgets(3)**, etc.) *or* POSIX functions (**open(2)**, **read(2)**, **write(2)**, etc.). Remember, standard I/O functions are buffered. Mixing standard I/O functions and POSIX functions to access a common file descriptor can lead to undefined behaviour and is therefore forbidden.
29. If asked in the assignment, you must implement signal handling (**SIGINT**, **SIGTERM**). You must only use *async-signal-safe* functions in your signal handlers.
30. Close files, free dynamically allocated memory, and remove resources after usage.
31. Don't waste resources due to inconvenient programming. Header files shall not include implementation parts (exception: macros).

Exercise 3 Guidelines

Violation of following guidelines leads to a deduction of points in exercise 3.

1. It is forbidden to use the deprecated functions **gethostbyname**, **gethostbyaddr**, **gethostbyname2**, **gethostbyname_r**, **gethostbyname2_r** or any other function of that family documented on the man page **gethostbyname(3)**. Use **getaddrinfo(3)** instead.