

# The `vutinfth` class\*

Thomas Auzinger  
`thomas@auzinger.name`

June 2, 2024

## **Abstract**

This class provides a L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> template for theses at TU Wien Informatics. In the current version, bachelor and master theses as well as dissertations are supported in both English and German.

---

\*This document corresponds to `vutinfth` v1.13, dated 2024/05/29.

# Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
<b>2</b>	<b>Known Issues</b>	<b>3</b>
<b>3</b>	<b>Usage for Document Authors</b>	<b>3</b>
3.1	Data . . . . .	3
3.1.1	Textual Data . . . . .	3
3.1.2	Persons . . . . .	4
3.1.3	Dates . . . . .	4
3.1.4	List Data . . . . .	5
3.1.5	Polylingual Data . . . . .	6
3.2	Layout . . . . .	6
<b>4</b>	<b>Usage for Class Writers</b>	<b>7</b>
4.1	Data . . . . .	7
4.2	Layout . . . . .	8
<b>5</b>	<b>Implementation</b>	<b>9</b>
5.1	Initialization . . . . .	9
5.1.1	Class Options . . . . .	9
5.1.2	Loaded Class and Packages . . . . .	9
5.1.3	Low-Level Functionality . . . . .	10
5.1.4	Fonts . . . . .	10
5.2	Data . . . . .	11
5.2.1	Dates . . . . .	11
5.2.2	Textual Data . . . . .	11
5.2.3	Persons . . . . .	11
5.2.4	Polylingual Text . . . . .	13
5.2.5	Thesis Types . . . . .	16
5.2.6	Declarations . . . . .	19
5.3	Layout . . . . .	23
5.3.1	Setup . . . . .	23
5.3.2	Title Page . . . . .	23
5.3.3	Front Matter Material . . . . .	29
5.3.4	Page Style . . . . .	32
<b>6</b>	<b>Change History</b>	<b>33</b>
	<b>Index</b>	<b>34</b>

# 1 Introduction

This class provides a L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> template for all theses at TU Wien Informatics. Further information on the document class and accompanying support can be found at <https://gitlab.com/ThomasAUZINGER/vutinfth>. Further guidelines may apply to both the format and structure of certain theses. These can be found at <https://informatics.tuwien.ac.at/study-services>. Thesis authors are advised to consult Section 3 for a documentation of all relevant commands. Information for class developers is provided in Section 4.

# 2 Known Issues

This class is incompatible with the `minitoc` package as of version 60, due to the incompatibility of the underlying `memoir` class. Use the `titletoc` package as a replacement.

# 3 Usage for Document Authors

This section contains relevant information for authors of theses that are based on the `vutinfth` document class.

## 3.1 Data

To allow the generation of the title pages, signature fields, statements, etc., several pieces of information have to be set by the author using the commands in the subsequent sections. We discern several categories of data: *(i)* textual data, which is given by a simple text string, *(ii)* persons, which are defined by their names, optional titles, and their gender, as well as, *(iii)* dates and *(iv)* list data, which allow the selection of one argument from a list of permissible arguments. Several commands have polylingual capabilities and support different languages (see Section 3.1.5). A superscript P, i.e., `\commandP`, indicates such a command.

### 3.1.1 Textual Data

`\setregnumber` All commands in this section are called with one mandatory argument, e.g., as  
`\settitle` `\command{<text>}`, where `<text>` defines the content of the commands. For polylin-  
`\setsubtitle` gual commands, given by `\commandP`, one `<text>` argument has to be supplied for each  
`\setcurriculum` language (see Section 3.1.5). The following textual data can be set:  
`\setfirstreviewerdata`  
`\setsecondreviewerdata`

Command	Role	Type	Optional
<code>\setregnumber</code>	Registration number of the author	All	No
<code>\settitle<sup>P</sup></code>	Title of the thesis	All	No
<code>\setsubtitle<sup>P</sup></code>	Subtitle of the thesis	All	Yes
<code>\setcurriculum<sup>P</sup></code>	Name of the curriculum	B, M	No
Types: Bachelor (B), Master (M), Doctoral (D), All (All)			

Command	Role	Type	Optional
<code>\setfirstreviewerdata</code>	Affiliation and country of first reviewer	D	No
<code>\setsecondreviewerdata</code>	Affiliation and country of second reviewer	D	No
Types: Bachelor (B), Master (M), Doctoral (D), All (All)			

### 3.1.2 Persons

`\setauthor` All commands in this section are called with four mandatory arguments, e.g., as  
`\setadvisor` `\command{<prettitle>}{<name>}{<posttitle>}{<gender>}`, where `<name>` defines both  
`\setsecondadvisor` the first name(s) and family name(s) of the person. A title that is placed before  
`\setfirstassistant` the name is assigned with `<prettitle>`, while a trailing title is given with `<posttitle>`.  
`\setsecondassistant` Both `<prettitle>` and `<posttitle>` can be left empty, to indicate an absence of such  
`\setthirdassistant` a title; the insertion of appropriate glue between titles and names is handled by  
`\setfirstreviewer` the `vutinfth` class. The declaration of the persons gender via `<gender>` allows  
`\setsecondreviewer` the use of gender-specific terms in languages that support them, e.g., German.  
The possible options for `<gender>` are `male` and `female` (see Section 3.1.4). The following persons can be set:

Command	Role	Type	Optional
<code>\setauthor</code>	Author of the thesis	All	No
<code>\setadvisor</code>	Main advisor of the thesis	All	No
<code>\setsecondadvisor</code>	Second advisor of the thesis	D	Yes
<code>\setfirstassistant</code>	First advising assistant	B, M	Yes
<code>\setsecondassistant</code>	Second advising assistant	B, M	Yes
<code>\setthirdassistant</code>	Third advising assistant	B, M	Yes
<code>\setfirstreviewer</code>	First thesis reviewer	D	No
<code>\setsecondreviewer</code>	Second thesis reviewer	D	No
Types: Bachelor (B), Master (M), Doctoral (D), All (All)			

### 3.1.3 Dates

`\setdate` All commands in this section are called with three mandatory arguments, e.g., as  
`\command{<day>}{<month>}{<year>}`. These commands derive from the `\DTMsave date`  
command of the `datetime2` package. The following dates can be set:

Command	Role	Type	Optional
<code>\setdate</code>	Signing date	All	No
Types: Bachelor (B), Master (M), Doctoral (D), All (All)			

### 3.1.4 List Data

All commands in this section are called with at least one mandatory argument called  $\langle list \rangle$ , e.g., as `\command...{\langle list \rangle}...`, where  $\langle list \rangle$  is given one element from a set of possible arguments.

`\setauthor` When setting a person, the person's gender is specified with a list argument (see `\setadvisor` Section 3.1.2):

Command	Options	Description
<code>\command{\langle . \rangle}{\langle . \rangle}{\langle . \rangle}{\langle list \rangle}</code>	<b>male</b>	Specifies a male person.
	<b>female</b>	Specifies a female person.

No pronouns are generated based on the gender choice and it should be chosen in a way to reflect the preferred use of nouns (e.g., Autor or Autorin in German).

`\setthesis` The thesis type is selected from one of the fundamental types:

Command	Options	Description
<code>\setthesis{\langle list \rangle}</code>	<b>bachelor</b>	Specifies a bachelor's thesis.
	<b>master</b>	Specifies a master's thesis.
	<b>doctor</b>	Specifies a dissertation.

`\setmasterdegree` With a master's curriculum, different degrees can be achieved and the appropriate type has to be chosen based on the curriculum that the author is enrolled in:

Command	Options	Description
<code>\setmasterdegree{\langle list \rangle}</code>	<b>dipl.</b>	Specifies the degree 'Diplom-Ingenieur(in)'.
	<b>master</b>	Specifies the degree 'Master of Science'.
	<b>rer.nat.</b>	Specifies the degree 'Magist(er/ra) der Naturwissenschaften'.
	<b>rer.soc.oec.</b>	Specifies the degree 'Magist(er/ra) der Sozial- und Wirtschaftswissenschaften'.

`\setdoctordegree` With a doctorate study, different degrees can be achieved and the appropriate type has to be chosen based on the program that the author is enrolled in:

Command	Options	Description
<code>\setdoctordegree{⟨list⟩}</code>	<code>techn.</code>	Specifies the degree ‘Doktor(in) der Technischen Wissenschaften’.
	<code>rer.nat.</code>	Specifies the degree ‘Doktor(in) der Naturwissenschaften’.
	<code>rer.soc.oec.</code>	Specifies the degree ‘Doktor(in) der Sozial- und Wirtschaftswissenschaften’.

### 3.1.5 Polylingual Data

`\setcurriculum` Used as `\setcurriculum{⟨english⟩}{⟨german⟩}`, it sets the name of the curriculum that the student is enrolled in. The name can be given in English, with `⟨english⟩`, and in German, with `⟨german⟩`. Note that the curriculum name does not need to be supplied for all thesis types, since, e.g., doctoral studies do not have a curriculum per se. If a title page of one of the languages is not used, the corresponding argument can be left empty.

`\settitle` Used as `\settitle{⟨english⟩}{⟨german⟩}`, it sets the title of the thesis. The title can be given both in an English version, with `⟨english⟩`, and in a German version, with `⟨german⟩`. For title pages in a given language, the corresponding title will be used. Unused languages can be supplied as empty brackets and it is possible to use the English or German title for both language versions.

`\setsubtitle` Used as `\setsubtitle{⟨english⟩}{⟨german⟩}`, it sets the subtitle of the thesis. The same specifications as for `\settitle` apply.

`\addtitlepage` The titlepage can be generated in the following languages (see Section 3.2):

Command	Options	Description
<code>\addtitlepage{⟨list⟩}</code>	<code>english</code>	Generates an English title page.
	<code>naustrian</code>	Generates a German title page.

## 3.2 Layout

Most of the data that is supplied with the commands of the previous sections is used to generate the front matter of the thesis. It consists of obligatory items such as the title page(s) and the statement of originality as well as optional items such as the acknowledgements or the abstract in different languages. In the remainder of this section, the available items of the front matter are given.

`\addtitlepage` Used as `\addtitlepage{⟨lang⟩}`, where `⟨lang⟩` is the name of a language as given in the `babel` package (see Section 3.1.4). The necessary pieces of information have to be set beforehand (as described in Section 3.1). This command is usually used directly after `\begin{document}\frontmatter`.

`\addstatementpage` Used as `\addstatementpage`, it generates a page with the statement of originality.

`acknowledgements` (*env.*) Used as `\begin{acknowledgements}<text>\end{acknowledgements}`, this environment generates a chapter with the English acknowledgements. Use the starred version, i.e., `acknowledgements*`, to remove the table of content entry of this environment.

`danksagung` (*env.*) Used as `\begin{danksagung}<text>\end{danksagung}`, this environment generates a chapter with the German acknowledgements. Use the starred version, i.e., `danksagung*`, to remove the table of content entry of this environment.

`abstract` (*env.*) Used as `\begin{abstract}<text>\end{abstract}`, this environment generates a chapter with the English abstract. Use the starred version, i.e., `abstract*`, to remove the table of content entry of this environment.

`kurzfassung` (*env.*) Used as `\begin{kurzfassung}<text>\end{kurzfassung}`, this environment generates a chapter with the German abstract. Use the starred version, i.e., `kurzfassung*`, to remove the table of content entry of this environment.

## 4 Usage for Class Writers

To accomodate shifting requirements, the `vutinfth` class provides various convenience functions that allow the modification and extension of its functionality.

### 4.1 Data

To compose several parts of the thesis layout, input from the thesis author is required. For the `vutinfth` class, this is realized by the commands provided in Section 3.1. Additional data can be defined with the the commands in the remainder of this section.

`\CreateData` Used as `\CreateData{<name>}`, it generates a command `\set{<name>}`. Used as `\set{<name>}{<string>}`, the newly created command assigns the value `<string>` to the internal variable `\vutinfth@data@<name>`. The variable is initialized with an error value to alert the user of the fact that `<string>` was not supplied via the `\set{<name>}` command. Furthermore, a command `\vutinfth@data@<name>@def` is created, to increase source code readability when verifying the existence of a specific data item. See Section 5.2.6 for examples.

`\CreatePerson` Used as `\CreatePerson{<name>}`, it generates a command `\set{<name>}`. Used as `\set{<name>}{<pretile>}{<personname>}{<posttitle>}{<gender>}`, the newly created command assigns the supplied values to the corresponding internal variables `\vutinfth@person@<name>@...` as given in the table below.

Argument	Internal Variable
	<code>\vutinfth@person@⟨name⟩@def</code>
<code>⟨prettitle⟩</code>	<code>\vutinfth@person@⟨name⟩@prettitle</code>
<code>⟨personname⟩</code>	<code>\vutinfth@person@⟨name⟩@name</code>
<code>⟨posttitle⟩</code>	<code>\vutinfth@person@⟨name⟩@posttitle</code>
<code>⟨gender⟩</code>	<code>\vutinfth@person@⟨name⟩@gender</code>

The command `\vutinfth@person@⟨name⟩@def` is created to increase source code readability when verifying the existence of a specific person. Furthermore, the command `\vutinfth@person@⟨name⟩@fullname` returns the person's name together with existing titles and correct whitespace in between. The person's gender is either `\vutinfth@person@male` or `\vutinfth@person@female`, depending on the input. See Section 5.2.6 for examples.

`\AddLanguage` Used as `\AddLanguage{⟨lang⟩}`, it enables the language `⟨lang⟩` to be used by polylingual expressions. `⟨lang⟩` has to be chosen from the languages of the `babel` package that is used by this class. Currently, `vutinfth` uses two languages, i.e., `english` for English expressions and `naustrian` for German expressions.

`\CreatePolylingual` Used as `\CreatePolylingual[⟨expressions⟩]{⟨name⟩}`, it generates a command `\vutinfth@polylingual@⟨name⟩` that selects the appropriate expression based on the current language at the time of use. The argument `⟨expressions⟩` is a list of elements of the form `⟨expri⟩`, where each element defines the expression for a valid language, e.g., `⟨langi⟩=⟨texti⟩`. `⟨langi⟩` has to be chosen from the languages that were defined via `\AddLanguage`. As a convention, text that needs to start with an uppercase letter is assigned to a name that starts with an uppercase letter. The same holds for uppercase words, e.g.,  
`\CreatePolylingual[english=advisor,naustrian=Betreuer]{advisor}`  
`\CreatePolylingual[english=Advisor,naustrian=Betreuer]{Advisor}`  
`\CreatePolylingual[english=ADVISOR,naustrian=BETREUER]{ADVISOR}`.  
See Section 5.2.6 for examples.

## 4.2 Layout

Several key elements in the layout of the frontmatter are encapsulated to allow a convenient extension of this functionality.

`\SignatureFields` Used as `\SignatureFields[⟨mode⟩]{⟨center⟩}{⟨right⟩}`, it creates a place and date description and/or one or two signature fields. `⟨mode⟩` can be set to `y`, which adds an entry with date and place to the left, to `h`, which adds the corresponding whitespace, or to `n`, which adds nothing. If text is supplied to `⟨center⟩`, it is added below a rule, right to the possible date and place entry. If text is supplied to `⟨right⟩`, it is added below a rule, right to the possible signature field created by `⟨center⟩`. This command ensures a uniform width and positioning of the signature fields on both the title pages and the statement of originality.

`\SignatureBlock` Used as `\SignatureBlock`, it generates the signature fields for both author and



advisor.

- `\ReviewerBlock` Used as `\ReviewerBlock`, it generates the signature fields for both reviewers.
- `\AdvisorBlock` Used as `\AdvisorBlock`, it generates the name fields for both the advisor and the potential assistants.
- `\AddTitlePage` Used as `\AddTitlePage`, it generates a title page in the current language. This command contains the placement of the header graphics, the footer, the appropriate blocks, etc.
- `\AddStatementPage` Used as `\AddStatementPage`, it generates a chapter with the statement of originality together with the author's signature field.
- `SFFont` (*env.*) Alters the sans serif font inside the environment. Called with one mandatory argument as `\begin{SFFont}{\family}`, which determines the sans serif font family that should be used, e.g., `phv` for Helvetica.

## 5 Implementation

### 5.1 Initialization

#### 5.1.1 Class Options

Pass the options to the underlying memoir class.

```
1 \DeclareOption*{%
2   \PassOptionsToClass{\CurrentOption}{memoir}%
3 }%
4 \ProcessOptions\relax
```

#### 5.1.2 Loaded Class and Packages

The `vutinfth` class is based on the `memoir` class.

```
5 \LoadClass[a4paper,11pt]{memoir}%
6 \chapterstyle{veelo}%
```

The following packages are required for the functionality and style of the document class.

```
7 \RequirePackage[scaled]{helvet}%
8 \RequirePackage{lmodern}%
9 \RequirePackage{courier}%
10 \RequirePackage[T1]{fontenc}%
11 \RequirePackage[english,naustrian]{babel}%
12 \RequirePackage[userregional]{datetime2}%
13 \RequirePackage{geometry}%
14 \RequirePackage{calc}%
15 \RequirePackage{etoolbox}%
```

```

16 \RequirePackage{graphicx}%
17 \graphicspath{{graphics/}}%

```

### 5.1.3 Low-Level Functionality

This section provides low-level functionality for macro definitions and macro expansions.

`\@namexdef` Globally defines a control sequence with an expanded argument.

```

18 \newcommand{\@namexdef}[1]{\expandafter\xdef\csname#1\endcsname}%

```

`\ifstrequal` A variant of `\ifstrequal` that fully expands the first two arguments.

```

19 \newcommand{\ifstrequal}[4]{%
20   \begingroup
21   \edef\vutinfth@tempa{{#1}}%
22   \edef\vutinfth@tempb{{#2}}%
23   \expandafter\expandafter\expandafter\ifstrequal
24   \expandafter\vutinfth@tempa\vutinfth@tempb{#3}{#4}%
25   \endgroup
26 }%

```

### 5.1.4 Fonts

`\vutinfth@HUGE` Initializes the font sizes.

```

\vutinfth@huge
\vutinfth@LARGE
\vutinfth@Large
\vutinfth@large
\vutinfth@normalsize
27 \newcommand{\vutinfth@HUGE}{\fontsize{30}{34}\selectfont}%
28 \newcommand{\vutinfth@huge}{\fontsize{20}{23}\selectfont}%
29 \newcommand{\vutinfth@LARGE}{\fontsize{17}{22}\selectfont}%
30 \newcommand{\vutinfth@Large}{\fontsize{14}{18}\selectfont}%
31 \newcommand{\vutinfth@large}{\fontsize{12}{14.5}\selectfont}%
32 \newcommand{\vutinfth@normalsize}{\fontsize{11}{13.6}\selectfont}%

```

`SFFont` (*env.*) Selects the given font family as sans serif font.

```

33 \newenvironment{SFFont}[1]{%

```

Stores the current sans serif font in `\vutinfth@f@family@tmp` and changes to the given sans serif font.

```

34   \begingroup
35   \sffamily
36   \global\let\vutinfth@f@family@tmp=\f@family
37   \endgroup
38   \renewcommand{\sfdefault}{#1}%

```

In case the outer scope is already sans serif, the new font has to be activated.

```

39   \ifdefstrequal{\f@family}{\vutinfth@f@family@tmp}{\sffamily}{}%
40 }%

```

The scope of the font change is the environment itself. Thus, no cleanup code is required in case the outer scope was already sans serif.

```
41 \renewcommand{\sfdefault}{\vutinfth@f@family@tmp}%
42 }%
```

## 5.2 Data

### 5.2.1 Dates

`\setdate` Creates the internal storage for the signing date.

```
43 \newcommand{\setdate}[3]{%
44 \DTMsavedate{\vutinfth@date@signing}{#3-#2-#1}%
45 }%
```

### 5.2.2 Textual Data

`\vutinfth@def@data` Creates the internal storage for simple data entries.

```
46 \newcommand{\vutinfth@def@data}[2]{%
47 \@namedef{\vutinfth@data@#1@def}{}%
48 \@namedef{\vutinfth@data@#1}{#2}%
49 }%
```

`\vutinfth@def@data@invalid` Initializes the internal storage with error messages.

```
50 \newcommand{\vutinfth@def@data@invalid}[2]{%
51 \@namedef{\vutinfth@data@#1@error}{%
52 \ClassError{\vutinfth}{No #2 issued}{Set #1 with #2.}%
53 }%
54 \@namedef{\vutinfth@data@#1}{\@nameuse{\vutinfth@data@#1@error}}%
55 }%
```

`\CreateData` Issues the construction of a setter function for a data entry given by `\setdate`.

```
56 \newcommand{\CreateData}[1]{%
57 \@namedef{set#1}##1{%
58 \vutinfth@def@data{#1}{##1}%
59 }%
60 \vutinfth@def@data@invalid{#1}{\string\set#1}%
61 }%
```

### 5.2.3 Persons

`\vutinfth@person@male` Two genders are differentiated for each person: male and female.  
`\vutinfth@person@female`

```
62 \newcommand{\vutinfth@person@male}{male}%
63 \newcommand{\vutinfth@person@female}{female}%
```

`\ifmale` Convenience macros to determine the gender of a person.

`\iffemale`

```

64 \newcommand{\ifmale}[2]{%
65   \ifcsstring{vutinfth@person@#1@gender}{\vutinfth@person@male}{#2}{}%
66 }%
67 \newcommand{\iffemale}[2]{%
68   \ifcsstring{vutinfth@person@#1@gender}{\vutinfth@person@female}{#2}{}%
69 }%
```

`\vutinfth@def@person` Creates the internal storage for a person's name, titles and gender.

```

70 \newcommand{\vutinfth@def@person}[5]{%
71   \@namedef{vutinfth@person@#1@def}{}%
72   \@namedef{vutinfth@person@#1@prettitle}{#2}%
73   \@namedef{vutinfth@person@#1@name}{#3}%
74   \@namedef{vutinfth@person@#1@posttitle}{#4}%
75   \ifdefstring{\vutinfth@person@male}{#5}{%
76     \@namedef{vutinfth@person@#1@gender}{\vutinfth@person@male}%
77   }{%
78     \ifdefstring{\vutinfth@person@female}{#5}{%
79       \@namedef{vutinfth@person@#1@gender}{\vutinfth@person@female}%
80     }{%

```

For the full name, additional spaces have to be inserted depending on the presence of pre- or posttitles.

```

81   \ifstrempy{#3}{%
82     \ifstrempy{#2}{%
83       \@namedef{vutinfth@person@#1@fullname}{#4}%
84     }{%
85       \ifstrempy{#4}{%
86         \@namedef{vutinfth@person@#1@fullname}{#2}%
87       }{%
88         \@namedef{vutinfth@person@#1@fullname}{#2 #4}%
89       }%
90     }%
91   }{%
92     \ifstrempy{#2}{%
93       \ifstrempy{#4}{%
94         \@namedef{vutinfth@person@#1@fullname}{#3}%
95       }{%
96         \@namedef{vutinfth@person@#1@fullname}{#3, #4}%
97       }%
98     }{%
99       \ifstrempy{#4}{%
100         \@namedef{vutinfth@person@#1@fullname}{#2 #3}%
101       }{%
102         \@namedef{vutinfth@person@#1@fullname}{#2 #3, #4}%
103       }%
104     }%

```

```

105 }%
106 }%

```

`\vutinfth@def@person@invalid` Initializes the internal storage with error messages.

```

107 \newcommand{\vutinfth@def@person@invalid}[2]{%
108   \@namedef{\vutinfth@person@#1@error}{%
109     \ClassError{\vutinfth}{No #2 issued}{Set #1 with #2.}%
110   }%
111   \@namedef{\vutinfth@person@#1@name}{%
112     \@nameuse{\vutinfth@person@#1@error}}%
113   \@namedef{\vutinfth@person@#1@pretitle}{%
114     \@nameuse{\vutinfth@person@#1@error}}%
115   \@namedef{\vutinfth@person@#1@posttitle}{%
116     \@nameuse{\vutinfth@person@#1@error}}%
117   \@namedef{\vutinfth@person@#1@gender}{%
118     \@nameuse{\vutinfth@person@#1@error}}%
119   \@namedef{\vutinfth@person@#1@fullname}{%
120     \@nameuse{\vutinfth@person@#1@error}}%
121 }%

```

`\CreatePerson` Issues the construction of a setter function for a person given by `\setperson`.

```

122 \newcommand{\CreatePerson}[1]{%
123   \@namedef{set#1}##1##2##3##4{%
124     \vutinfth@def@person{#1}{##1}{##2}{##3}{##4}%
125   }%
126   \vutinfth@def@person@invalid{#1}{\string\set#1}%
127 }%

```

### 5.2.4 Polylingual Text

This class supports bi- and polylingual text via a key-value mechanism. See the `\CreatePolylingual` command further down for the actual definition of polylingual expressions.

`\AddLanguage` Constructs the temporary variables and the permanent storage for polylingual text in the given language.

```

128 \newcommand{\AddLanguage}[1]{%

```

First, the key for the current language, given by its name in the `babel` package, is created. Keys of the `keyval` package are internally stored as `KV@family@keyname`, where we use `vutinfth` as family name and the argument as key name. The value that is given to this key as part of a function argument is assigned to a temporary storage.

```

129   \@namedef{KV@vutinfth@#1}##1{%
130     \@namedef{\vutinfth@current@#1}{##1}%
131   }%

```

The key value is initialized as empty.

```
132 \@nameuse{KV@vutinfth@#1}{}%
```

The transfer from temporary to permanent storage is achieved by adding code to the already existing transfer routine. This causes each new language to issue the transfer for the previously defined language.

```
133 \ifundef{\vutinfth@allocate@polylingual}{%
```

Define the transfer function, if it has not been defined so far.

```
134 \newcommand{\vutinfth@allocate@polylingual}[1]{\@empty}%
135 }{}%
```

Store the current transfer function via `\let` to allow recursion.

```
136 \@namelet{\vutinfth@allocate@polylingual@#1}%
137 \vutinfth@allocate@polylingual
```

Define the transfer function to permanent storage.

```
138 \renewcommand{\vutinfth@allocate@polylingual}[1]{%
```

Call the transfer routine of the previously defined language.

```
139 \@nameuse{\vutinfth@allocate@polylingual@#1}{##1}%
```

To define the permanent storage, `\@namexdef` is used the definition's scope has to be global.

```
140 \@namexdef{\vutinfth###1@#1}{%
141 \ifcempty{\vutinfth@current@#1}{%
```

In draft mode we mark unassigned languages, i.e., polylingual expression that were not defined for a language that is in use when the polylingual expression is called.

```
142 \ifdraftdoc{%
143 [Draft: No '#1' text for polylingual '##1'.]%
144 }%
145 \relax
146 }\fi
147 }{%
```

The use of `\@namexdef` expands the content of the temporary storage before assigning it to the permanent one.

```
148 \@nameuse{\vutinfth@current@#1}%
149 }%
150 }%
151 }%
```

At time of usage, the language, which is given as an argument, is checked against the currently active language.

```
152 \ifundef{\vutinfth@selectlanguage@polylingual}{%
```

Define the language selection function, if it has not been defined so far.

```
153 \newcommand{\vutinfth@selectlanguage@polylingual}[1]{\@empty}%
154 }{}%
```

Store the current selection function via `\let` to allow recursion.

```
155 \@namelet{\vutinfth@selectlanguage@polylingual@#1}%
156 \vutinfth@selectlanguage@polylingual
```

Define the selection function.

```
157 \renewcommand{\vutinfth@selectlanguage@polylingual}[1]{%
```

Call the selection routine of the previously defined language.

```
158 \@nameuse{\vutinfth@selectlanguage@polylingual@#1}{##1}%
```

The currently active language is given by `\language`. If it matches the language, which was supplied as the argument, the content of the current permanent storage is returned.

```
159 \ifdefstring{\language}{#1}{\@nameuse{\vutinfth@##1@#1}}{}%
160 }%
161 }%
```

`\CreatePolylingual` Creates the actual polylingual expressions.

```
162 \newcommand{\CreatePolylingual}[2][]{%
163 \begingroup
```

The key-value pairs of the optional argument define the text that is returned for the respective languages. We use `vutinfth` as the family name for the keys.

```
164 \setkeys{vutinfth}{#1}%
```

Each key was already assigned a temporary storage, whose content has to be transferred to permanent storage.

```
165 \vutinfth@allocate@polylingual{#2}%
166 \endgroup
```

The mandatory argument `{⟨arg⟩}` is used to define the macro that returns the appropriate text for the currently active language.

```
167 \@namedef{\vutinfth@polylingual@#2}{%
168 \vutinfth@selectlanguage@polylingual{#2}}%
169 }%
```

### 5.2.5 Thesis Types

Two thesis categories are differentiated: undergraduate and graduate.

```

\thesis@basetype@undergraduate
\thesis@basetype@graduate
170 \newcommand{\vutinfth@thesis@basetype@undergraduate}{%
171   \vutinfth@undergraduate}%
172 \newcommand{\vutinfth@thesis@basetype@graduate}{%
173   \vutinfth@graduate}%

\ifundergraduate
\ifgraduate
174 \newcommand{\ifundergraduate}[1]{%
175   \ifstrequal{\vutinfth@thesis@basetype}{%
176     \vutinfth@thesis@basetype@undergraduate
177   }{#1}{}%
178 }%
179 \newcommand{\ifgraduate}[1]{%
180   \ifstrequal{\vutinfth@thesis@basetype}{%
181     \vutinfth@thesis@basetype@graduate
182   }{#1}{}%
183 }%

\vutinfth@thesis@basetype
\vutinfth@thesis@thesisname
\vutinfth@thesis@degreename
184 \newcommand{\vutinfth@thesis@basetype}{%
185   \ClassError{\vutinfth}{No \string\setthesis \space issued}{%
186     Set thesis type with \string\setthesis.}%
187 }%
188 \newcommand{\vutinfth@polylingual@degreename}{%
189   \ClassError{\vutinfth}{No \string\setthesis \space issued}{%
190     Set thesis type with \string\setthesis.}%
191 }%
192 \newcommand{\vutinfth@polylingual@thesisname}{%
193   \ClassError{\vutinfth}{No \string\setthesis \space issued}{%
194     Set thesis type with \string\setthesis.}%
195 }%

\vutinfth@thesis@bachelor
\vutinfth@thesis@master
\vutinfth@thesis@doctor
196 \newcommand{\vutinfth@thesis@bachelor}{bachelor}%
197 \newcommand{\vutinfth@thesis@master}{master}%
198 \newcommand{\vutinfth@thesis@doctor}{doctor}%

\@setthesisname
\@setdegreename
\@setgendereddegreename
199 \newcommand{\@setthesisname}[1]{%
200   \renewcommand{\vutinfth@polylingual@thesisname}{#1}}%
201 \newcommand{\@setdegreename}[1]{%
202   \renewcommand{\vutinfth@polylingual@degreename}{#1}}%
203 \newcommand{\@setgendereddegreename}[2]{%

```

Convenience macros to determine the category of the selected thesis type.

Initialize the thesis category, the type and the specific degree with error messages.

Three main thesis types are differentiated: bachelor, master, and doctor.

Internal convenience macros.



```

204 \iffemale{author}{\@setdegreegreename{#1}}%
205 \iffemale{author}{\@setdegreegreename{#2}}%
206 }%

```

`\setthesis` Sets the thesis type.

```

207 \newcommand{\setthesis}[1]{%
208 \ifdefstring{\vutinfth@thesis@bachelor}{#1}{%

```

Initializes bachelor thesis type.

```

209 \renewcommand{\vutinfth@thesis@basetype}{%
210 \vutinfth@thesis@basetype@undergraduate}%
211 \@setthesisname{\vutinfth@polylingual@BACHELORTHESIS}%
212 \@setdegreegreename{\vutinfth@polylingual@Bdeg}%
213 }{}%
214 \ifdefstring{\vutinfth@thesis@master}{#1}{%

```

Initializes master thesis type.

```

215 \renewcommand{\vutinfth@thesis@basetype}{%
216 \vutinfth@thesis@basetype@undergraduate}%
217 \@setthesisname{%
218 \ClassError{\vutinfth}{No \string\setmasterdegree \space issued}{%
219 Set masterdegree with \string\setmasterdegree.}%
220 }%
221 \@setdegreegreename{%
222 \ClassError{\vutinfth}{No \string\setmasterdegree \space issued}{%
223 Set master degree with \string\setmasterdegree.}%
224 }%
225 }{}%
226 \ifdefstring{\vutinfth@thesis@doctor}{#1}{%

```

Initializes doctor thesis type.

```

227 \renewcommand{\vutinfth@thesis@basetype}{%
228 \vutinfth@thesis@basetype@graduate}%
229 \@setthesisname{\vutinfth@polylingual@DOCTORTHESIS}%
230 \@setdegreegreename{%
231 \ClassError{\vutinfth}{No \string\setdoctordegree \space issued}{%
232 Set doctor degree with \string\setdoctordegree.}%
233 }%
234 }{}%
235 }%

```

```

\vutinfth@thesis@mdeg@dipl Four master degrees can be selected: dipl., master, rer.nat., and
\vutinfth@thesis@mdeg@master rer.soc.oec..
\vutinfth@thesis@mdeg@rernat
\vutinfth@thesis@mdeg@rersocoec 236 \newcommand{\vutinfth@thesis@mdeg@dipl}{dipl.}%
237 \newcommand{\vutinfth@thesis@mdeg@master}{master}%

```

```

238 \newcommand{\vutinfth@thesis@mdeg@rernat}{rer.nat.}%
239 \newcommand{\vutinfth@thesis@mdeg@rersocoec}{rer.soc.oec.}%

```

`\setmasterdegree` Sets the specific master degree.

```

240 \newcommand{\setmasterdegree}[1]{%
241   \ifdefstring{\vutinfth@thesis@mdeg@dipl}{#1}{%
242     \@setthesisname{\vutinfth@polylingual@DIPLOMATHESES}%
243     \@setgendereddegreename{%
244       \vutinfth@polylingual@mdegDiplMale
245     }{%
246       \vutinfth@polylingual@mdegDiplFemale
247     }%
248   }{}%
249   \ifdefstring{\vutinfth@thesis@mdeg@master}{#1}{%
250     \@setthesisname{\vutinfth@polylingual@MASTERTHESIS}%
251     \@setdegreename{\vutinfth@polylingual@mdegMaster}%
252   }{}%
253   \ifdefstring{\vutinfth@thesis@mdeg@rernat}{#1}{%
254     \@setthesisname{\vutinfth@polylingual@MASTERTHESIS}%
255     \@setgendereddegreename{%
256       \vutinfth@polylingual@mdegRerNatMale
257     }{%
258       \vutinfth@polylingual@mdegRerNatFemale
259     }%
260   }{}%
261   \ifdefstring{\vutinfth@thesis@mdeg@rersocoec}{#1}{%
262     \@setthesisname{\vutinfth@polylingual@MASTERTHESIS}%
263     \@setgendereddegreename{%
264       \vutinfth@polylingual@mdegRerSocOecMale
265     }{%
266       \vutinfth@polylingual@mdegRerSocOecFemale
267     }%
268   }{}%
269 }%

```

`\vutinfth@thesis@ddeg@rernat` Three doctor degrees can be selected: `rer.nat.`, `techn.`, and `rer.soc.oec.`.

`\vutinfth@thesis@ddeg@techn`

`\vutinfth@thesis@ddeg@rersocoec`

```

270 \newcommand{\vutinfth@thesis@ddeg@rernat}{rer.nat.}%
271 \newcommand{\vutinfth@thesis@ddeg@techn}{techn.}%
272 \newcommand{\vutinfth@thesis@ddeg@rersocoec}{rer.soc.oec.}%

```

`\setdoctordegree` Sets the specific doctor degree.

```

273 \newcommand{\setdoctordegree}[1]{%
274   \ifdefstring{\vutinfth@thesis@ddeg@rernat}{#1}{%
275     \@setgendereddegreename{%
276       \vutinfth@polylingual@ddegRerNatMale
277     }{%
278       \vutinfth@polylingual@ddegRerNatFemale

```

```

279 }%
280 }{}%
281 \ifdefstring{\vutinfth@thesis@ddeg@techn}{#1}{%
282   \@setgendereddegreename{%
283     \vutinfth@polylingual@ddegTechnMale
284   }{%
285     \vutinfth@polylingual@ddegTechnFemale
286   }%
287 }{}%
288 \ifdefstring{\vutinfth@thesis@ddeg@rersocoec}{#1}{%
289   \@setgendereddegreename{%
290     \vutinfth@polylingual@ddegRerSocOecMale
291   }{%
292     \vutinfth@polylingual@ddegRerSocOecFemale
293   }%
294 }{}%
295 }%

```

### 5.2.6 Declarations

**Textual Data** Creates the required textual data entries.

```

296 % ^^A\CreateData{address}%
297 \CreateData{regnumber}%
298 \CreateData{firstreviewerdata}%
299 \CreateData{secondreviewerdata}%

```

**Persons** Creates the required person entries.

```

300 \CreatePerson{author}%
301 \CreatePerson{advisor}%
302 \CreatePerson{secondadvisor}%
303 \CreatePerson{firstassistant}%
304 \CreatePerson{secondassistant}%
305 \CreatePerson{thirdassistant}%
306 \CreatePerson{firstreviewer}%
307 \CreatePerson{secondreviewer}%

```

**Languages** Adds the desired languages to the polylingual expressions. All added languages have to be given as arguments to the `babel` package.

```

308 \AddLanguage{english}%
309 \AddLanguage{naustrian}%

```

**PolyLinguals** Creates the polylingual expressions.

```

310 \CreatePolylingual[
311   english=Advisor,
312   naustrian=Betreuung]{Advisor}%
313 \CreatePolylingual[

```

```

314 english=Second advisor,
315 naustrian=Zweitbetreuung]{Secondadvisor}%
316 \CreatePolylingual[
317 english=submitted in partial fulfillment of the requirements
318 for the degree of,
319 naustrian=zur Erlangung des akademischen Grades]{submission}%
320 \CreatePolylingual[
321 english=in,
322 naustrian=im Rahmen des Studiums]{in}%
323 \CreatePolylingual[
324 english=by,
325 naustrian=eingereicht von]{by}%
326 \CreatePolylingual[
327 english=Registration Number,
328 naustrian=Matrikelnummer]{Registrationnumber}%
329 \CreatePolylingual[
330 english=to the Faculty of Informatics,
331 naustrian=an der Fakult\"at f\"ur Informatik]{faculty}%
332 \CreatePolylingual[
333 english=at the TU Wien,
334 naustrian=der Technischen Universit\"at Wien]{university}%
335 \CreatePolylingual[
336 english=Assistance,
337 naustrian=Mitwirkung]{Assistance}%
338 \CreatePolylingual[
339 english=The dissertation has been reviewed by:,
340 naustrian=Diese Dissertation haben begutachtet:]{Reviewed}%
341 \CreatePolylingual[
342 english=External reviewers:]{Reviewers}%
343 \CreatePolylingual[
344 english=Vienna,
345 naustrian=Wien]{Place}%
346 \CreatePolylingual[
347 english=Declaration of Authorship,
348 naustrian=Erkl\"arung zur Verfassung der Arbeit]{StatementChapter}%
349 \CreatePolylingual[
350 english={I hereby declare that I have written this Doctoral Thesis
351 independently, that I have completely specified the utilized
352 sources and resources and that I have definitely marked all parts
353 of the work - including tables, maps and figures - which belong
354 to other works or to the internet, literally or extracted, by
355 referencing the source as borrowed.},
356 naustrian={Hiermit erkl\"are ich, dass ich diese Arbeit
357 selbst\"andig verfasst habe, dass ich die verwendeten Quellen
358 und Hilfsmittel vollst\"andig angegeben habe und dass ich die
359 Stellen der Arbeit -- einschlie{\ss}lich Tabellen, Karten und
360 Abbildungen --, die anderen Werken oder dem Internet im Wortlaut
361 oder dem Sinn nach entnommen sind, auf jeden Fall unter Angabe
362 der Quelle als Entlehnung kenntlich gemacht habe.}]{Statement}%
363 \CreatePolylingual[

```

```

364 english={I further declare that I have used generative AI tools only as an aid,
365 and that my own intellectual and creative efforts predominate in this
366 work. In the appendix ‘‘Overview of Generative AI Tools Used’’ I have
367 listed all generative AI tools that were used in the creation of this
368 work, and indicated where in the work they were used. If whole passages
369 of text were used without substantial changes, I have indicated the
370 input (prompts) I formulated and the IT application used with its
371 product name and version number/date.},
372 naustrian={Ich erkl\are weiters, dass ich mich generativer KI-Tools lediglich als
373 Hilfsmittel bedient habe und in der vorliegenden Arbeit mein
374 gestalterischer Einfluss \uberwiegt. Im Anhang \glqq\''Übersicht verwendeter
375 Hilfsmittel\grqq\ habe ich alle generativen KI-Tools gelistet, die verwendet
376 wurden, und angegeben, wo und wie sie verwendet wurden. F\'ur
377 Textpassagen, die ohne substantielle \''Anderungen \''ubernommen wurden, haben
378 ich jeweils die von mir formulierten Eingaben (Prompts) und die
379 verwendete IT- Anwendung mit ihrem Produktnamen und Versionsnummer/Datum
380 angegeben.}}{AIStatement}%
381 \CreatePolylingual[
382 english=Overview of Generative AI Tools Used,
383 naustrian=Übersicht verwendeter Hilfsmittel]{AIToolsChapter}%

```

Degree titles.

```

384 \CreatePolylingual[
385 english=Bachelor of Science,
386 naustrian=Bachelor of Science]{Bdeg}%
387 \CreatePolylingual[
388 english=Master of Science,
389 naustrian=Master of Science]{MdegMaster}%
390 \CreatePolylingual[
391 english=Diplom-Ingenieur,
392 naustrian=Diplom-Ingenieur]{MdegDiplMale}%
393 \CreatePolylingual[
394 english=Diplom-Ingenieurin,
395 naustrian=Diplom-Ingenieurin]{MdegDiplFemale}%
396 \CreatePolylingual[
397 english=Magister der Naturwissenschaften,
398 naustrian=Magister der Naturwissenschaften]{MdegRerNatMale}%
399 \CreatePolylingual[
400 english=Magistra der Naturwissenschaften,
401 naustrian=Magistra der Naturwissenschaften]{MdegRerNatFemale}%
402 \CreatePolylingual[
403 english=Magister der Sozial- und Wirtschaftswissenschaften,
404 naustrian=Magister der Sozial- und Wirtschaftswissenschaften]{%
405 MdegRerSocOecMale}%
406 \CreatePolylingual[
407 english=Magistra der Sozial- und Wirtschaftswissenschaften,
408 naustrian=Magistra der Sozial- und Wirtschaftswissenschaften]{%
409 MdegRerSocOecFemale}%
410 \CreatePolylingual[

```

```

411 english=Doktor der Naturwissenschaften,
412 naustrian=Doktor der Naturwissenschaften]{DdegRerNatMale}%
413 \CreatePolylingual[
414 english=Doktorin der Naturwissenschaften,
415 naustrian=Doktorin der Naturwissenschaften]{DdegRerNatFemale}%
416 \CreatePolylingual[
417 english=Doktor der Technischen Wissenschaften,
418 naustrian=Doktor der Technischen Wissenschaften]{DdegTechnMale}%
419 \CreatePolylingual[
420 english=Doktorin der Technischen Wissenschaften,
421 naustrian=Doktorin der Technischen Wissenschaften]{DdegTechnFemale}%
422 \CreatePolylingual[
423 english=Doktor der Sozial- und Wirtschaftswissenschaften,
424 naustrian=Doktor der Sozial- und Wirtschaftswissenschaften]{%
425 DdegRerSocOecMale}%
426 \CreatePolylingual[
427 english=Doktorin der Sozial- und Wirtschaftswissenschaften,
428 naustrian=Doktorin der Sozial- und Wirtschaftswissenschaften]{%
429 DdegRerSocOecFemale}%

```

Thesis types.

```

430 \CreatePolylingual[
431 english=BACHELOR'S THESIS,
432 naustrian=BACHELORARBEIT]{BACHELORTHESIS}%
433 \CreatePolylingual[
434 english=MASTER'S THESIS,
435 naustrian=MASTERARBEIT]{MASTERTHESIS}%
436 \CreatePolylingual[
437 english=DIPLOMA THESIS,
438 naustrian=DIPLOMARBEIT]{DIPLOMATHESIS}%
439 \CreatePolylingual[
440 english=DISSERTATION,
441 naustrian=DISSERTATION]{DOCTORTHESIS}%

```

`\settitle` Sets the title of the thesis.

```

442 \newcommand{\settitle}[2]{%
443 \CreatePolylingual[english=#1,naustrian=#2]{Title}%
444 }%

```

`\setsubtitle` Sets the subtitle of the thesis.

```

445 \newcommand{\setsubtitle}[2]{%
446 \CreatePolylingual[english=#1,naustrian=#2]{Subtitle}%
447 }%

```

`\setcurriculum` Sets the curriculum name.

```

448 \newcommand{\setcurriculum}[2]{%

```

```

449 \CreatePolylingual[english=#1,naustrian=#2]{Curriculum}%
450 }%

```

## 5.3 Layout

### 5.3.1 Setup

`\vutinfth@squarebullet` Set internal convenience macros.

```

451 \newcommand{\newsetlength}[2]{%
452   \newlength{#1}%
453   \setlength{#1}{#2}%
454 }%
455 \newcommand{\vutinfth@squarebullet}{\rule[0.47ex]{0.4ex}{0.4ex}}%

```

`\vutinfth@tmp@parindent` Temporary storage for page layout lengths.

```

\vutinfth@tmp@baselineskip
\vutinfth@tmp@parskip
456 \newlength{\vutinfth@tmp@parindent}%
457 \newlength{\vutinfth@tmp@baselineskip}%
458 \newlength{\vutinfth@tmp@parskip}%

```

`\vutinfth@savelayout` Saves and restores relevant page layout lengths.

```

\vutinfth@restorelayout
459 \newcommand{\vutinfth@savelayout}{%
460   \setlength{\vutinfth@tmp@parindent}{\parindent}%
461   \setlength{\vutinfth@tmp@baselineskip}{\baselineskip}%
462   \setlength{\vutinfth@tmp@parskip}{\parskip}%
463 }%
464 \newcommand{\vutinfth@restorelayout}{%
465   \setlength{\parindent}{\vutinfth@tmp@parindent}%
466   \setlength{\baselineskip}{\vutinfth@tmp@baselineskip}%
467   \setlength{\parskip}{\vutinfth@tmp@parskip}%
468 }%

```

### 5.3.2 Title Page

Initialize the header graphics. The vertical placement of the header graphics on the title pages are given by `\vutinfth@header@placement`, while the composition of the graphical elements are determined by the subsequent lengths, which constitute direct measurements of the graphics. If the header graphics are changed, these values have to be adapted.

```

469 \newsetlength{\vutinfth@logo@offset@x}{10.6mm}%
470 \newsetlength{\vutinfth@logo@offset@y}{22mm}%
471 \newsetlength{\vutinfth@logo@width@safe}{74mm}%
472 \newsetlength{\vutinfth@logo@height}{11mm}%
473 \newsetlength{\vutinfth@header@width}{\paperwidth - \vutinfth@logo@offset@x - \vutinfth@logo@o
474 \newsetlength{\vutinfth@header@height}{\vutinfth@logo@height}%
475 \newsetlength{\vutinfth@header@separator}{-12mm}%

```

`\vutinfth@header@titlepage` Initialize header.

```
476 \newcommand{\vutinfth@header@titlepage}{%
477   \setlength{\unitlength}{1mm}%
478   \begin{picture}(74, 11)%
479     {\includegraphics[height=\vutinfth@logo@height]{Logo-schwarz.pdf}}
480   \end{picture}\hfill
481 }%
```

`\vutinfth@footer@titlepage` Initialize footer.

```
482 \newcommand{\vutinfth@footer@titlepage}{%
483   \centering
484   \begin{minipage}{\textwidth}%
485     \centering\vutinfth@normalsize\sffamily
486     Technische Universit\{"a\}t Wien\\
487     A-1040 Wien \vutinfth@squarebullet\space
488     Karlsplatz 13 \vutinfth@squarebullet\space
489     Tel. +43-1-58801-0 \vutinfth@squarebullet\space
490     www.tuwien.at%
491   \end{minipage}%
492 }%
```

`vutinfth@pagestyle@titlepage` Generate the title page style.

```
493 \makepagestyle{\vutinfth@pagestyle@titlepage}%
494 \makerunningwidth{\vutinfth@pagestyle@titlepage}{\textwidth}{%
495   \vutinfth@header@width}%
496 \makeheadposition{\vutinfth@pagestyle@titlepage}{%
497   center}{center}{center}{center}%
498 \makeevenhead{\vutinfth@pagestyle@titlepage}{}{%
499   \vutinfth@header@titlepage}{}%
500 \makeoddhead{\vutinfth@pagestyle@titlepage}{}{%
501   \vutinfth@header@titlepage}{}%
502 \makefootrule{\vutinfth@pagestyle@titlepage}{%
503   \vutinfth@pagestyle@titlepagefootrunwidth}{0.5pt}{\footruleskip}%
504 \makeevenfoot{\vutinfth@pagestyle@titlepage}{}{%
505   \vutinfth@footer@titlepage}{}%
506 \makeoddfoot{\vutinfth@pagestyle@titlepage}{}{%
507   \vutinfth@footer@titlepage}{}%

```

Set style element specifications.

```
508 \newsetlength{\vutinfth@bigskipamount}{6mm}%

```

Helper functions.

```
509 \newcommand{\vutinfth@bigskip}{\vspace{\vutinfth@bigskipamount}}%

```



`\AdvisorBlock` Generates a block with the advisor's name (and potential assistances' names). An error is thrown, if the advisors are not defined consecutively, starting with the first.

```

510 \newcommand{\AdvisorBlock}{%
511   \ifundergraduate{%
512     \begin{minipage}[t][2.5cm][t]{\textwidth}%
513       \vutinfth@normalsize
514       \begin{tabular}{@{}l@{ }l}%
515         \vutinfth@polylingual@Advisor: &
516         \vutinfth@person@advisor@fullname\\
517         \ifdef{\vutinfth@person@firstassistant@def}{%
518           \vutinfth@polylingual@Assistance: &
519           \vutinfth@person@firstassistant@fullname\\
520         }{}%
521         \ifdef{\vutinfth@person@secondassistant@def}{%
522           \ifundef{\vutinfth@person@firstassistant@def}{%
523             \vutinfth@person@firstassistant@error
524           }{%
525             & \vutinfth@person@secondassistant@fullname\\
526           }%
527         }{}%
528         \ifdef{\vutinfth@person@thirdassistant@def}{%
529           \ifundef{\vutinfth@person@firstassistant@def}{%
530             \vutinfth@person@firstassistant@error
531           }{%
532             \ifundef{\vutinfth@person@secondassistant@def}{%
533               \vutinfth@person@secondassistant@error
534             }{%
535               & \vutinfth@person@thirdassistant@fullname\\
536             }%
537           }%
538         }{}%
539       \end{tabular}%
540     \end{minipage}%
541   }%
542   \ifgraduate{%
543     \begin{minipage}[t][1.6cm][t]{\textwidth}%
544       \vutinfth@normalsize
545       \vutinfth@polylingual@Advisor:
546       \vutinfth@person@advisor@fullname
547       \ifdef{\vutinfth@person@secondadvisor@def}{%
548         \\
549         \vutinfth@polylingual@Secondadvisor:
550         \vutinfth@person@secondadvisor@fullname
551       }{}%
552     \end{minipage}\par%
553   }%
554 }%

```

`\vutinfth@signature@height` Set lengths of the signature blocks.

```

\vutinfth@signature@width
\vutinfth@placedate@width
555 \newsetlength{\vutinfth@signature@height}{25mm}%
556 \newsetlength{\vutinfth@signature@width}{51mm}%
557 \newsetlength{\vutinfth@placedate@width}{50mm}%

```

`\SignatureFields` Generates a block with signatures and an optional place-date entry. The first argument is optional and adds an entry with date and place [y], or adds corresponding whitespace [h] or adds nothing [n], which is also the default value. The second arguments adds a rule and the given text below it, if a text is given, or the corresponding whitespace, if not. The third argument adds a rule and the given text below it, if a text is given.

```

558 \newcommand{\SignatureFields}[3][n]{%
559   {\vutinfth@normalsize
560     \ifstrequal{#1}{y}{%
561       \begin{minipage}[b][\vutinfth@signature@height]{%
562         \vutinfth@placedate@width
563       }%
564       \vutinfth@polylingual@Place,
565       \DTMusedate{\vutinfth@date@signing}\vspace*{\baselineskip}%
566     \end{minipage}%
567     \hfill
568   }{}%
569   \ifstrequal{#1}{n}{}{}%
570   \ifstrequal{#1}{h}{%
571     \hspace*{\vutinfth@placedate@width}%
572     \hfill
573   }{}%
574   \ifstreempty{#2}{%
575     \hspace*{\vutinfth@signature@width}%
576     \hfill
577   }{%
578     \begin{minipage}[b][\vutinfth@signature@height]{%
579       \vutinfth@signature@width
580     }%
581     \centering
582     \rule{\vutinfth@signature@width}{0.5pt}\\
583     #2%
584   \end{minipage}%
585   \hfill
586 }%
587 \ifstreempty{#3}{}{}%
588   \begin{minipage}[b][\vutinfth@signature@height]{%
589     \vutinfth@signature@width
590   }%
591   \centering
592   \rule{\vutinfth@signature@width}{0.5pt}\\
593   #3%
594   \end{minipage}%

```

```

595 }%
596 }%
597 }%

```

`\ReviewerBlock` Generates a block with the relevant signatures.

```

598 \newcommand{\ReviewerBlock}{%
599   \ifgraduate{%
600     {\vutinfth@normalsize
601       \vutinfth@polylingual@Reviewed\\
602       \SignatureFields[h]{%
603         \vutinfth@person@firstreviewer@name
604       }{%
605         \vutinfth@person@secondreviewer@name
606       }%
607     }%
608   }%
609 }%

```

`\SignatureBlock` Generates a block with the relevant signatures.

```

610 \newcommand{\SignatureBlock}{%
611   \ifundergraduate{%
612     {\vutinfth@normalsize
613       \SignatureFields[y]{%
614         \vutinfth@person@author@name
615       }{%
616         \vutinfth@person@advisor@name
617       }%
618     }%
619   }%
620   \ifgraduate{%
621     {\vutinfth@normalsize
622       \SignatureFields[y]{%
623         \vutinfth@person@author@name
624       }%
625     }%
626   }%
627 }%

```

`\AddTitlePage` Generates the language-dependant title page. Multiline title and subtitle are supported.

```

628 \newcommand{\AddTitlePage}{
629   \thispagestyle{vutinfth@pagestyle@titlepage}%

```

Set a new page geometry where the header separation length (`headsep`) places the header. The actual header height (`head`) has to be large enough to contain the header content otherwise the underlying `memoir` class issues a warning.

```

630 \newgeometry{%
631     left=2.4cm,right=2.4cm,bottom=2.5cm,top=2cm,
632     headsep=\vutinfth@header@separator,
633     head=\vutinfth@header@height
634 }%

```

Save the current page layout lengths for later restoration.

```

635 \vutinfth@savelayout
636 \setlength{\parindent}{0pt}%
637 \setlength{\baselineskip}{13.6pt}%
638 \setlength{\parskip}{0pt plus 1pt}%

```

Set title page text to helvetica.

```

639 \begin{SFFont}{phv}%
640     \sffamily
641     {\centering
642         \vspace*{1.2cm}}\par

```

Title and subtitle are bottom aligned and grow upwards.

```

643     \begin{minipage}[t][5cm][b]{\textwidth}%
644         \centering
645         \vutinfth@HUGE{\bfseries\vutinfth@polylingual@Title}\\
646         \bigskip
647         \vutinfth@huge{\bfseries
648             \ifdef{\vutinfth@polylingual@Subtitle}{%
649                 \vutinfth@polylingual@Subtitle}{%
650             }}%
651         }%
652     \end{minipage}\par
653     \vutinfth@bigskip\vutinfth@bigskip
654     {\vutinfth@LARGE\vutinfth@polylingual@thesisname}\par
655     \vutinfth@bigskip
656     {\vutinfth@large\vutinfth@polylingual@submission}\par
657     \vutinfth@bigskip
658     \ifundergraduate{%
659         {\vutinfth@LARGE{\bfseries\vutinfth@polylingual@degreename}}\par
660         \vutinfth@bigskip
661         {\vutinfth@large\vutinfth@polylingual@in}\par
662         \vutinfth@bigskip
663         {\vutinfth@Large{\bfseries\vutinfth@polylingual@Curriculum}}\par
664     }%
665     \ifgraduate{%
666         {\vutinfth@LARGE{\bfseries\vutinfth@polylingual@degreename}}\par
667     }%
668     \vutinfth@bigskip
669     {\vutinfth@large\vutinfth@polylingual@by}\par
670     \vutinfth@bigskip
671     {\vutinfth@Large{\bfseries\vutinfth@person@author@fullname}}\par

```

```

672     \smallskip
673     {\vutinfth@large\vutinfth@polylingual@Registrationnumber\
674     \vutinfth@data@regnumber}\par
675 }%
676 \vutinfth@bigskip\vutinfth@bigskip
677 \begin{minipage}[b][1.6cm][c]{\textwidth}%
678     \vutinfth@normalsize%
679     \vutinfth@polylingual@faculty\par
680     \vutinfth@polylingual@university
681 \end{minipage}\par
682 \AdvisorBlock\par

```

Add stretchable glue between the advisor block and the signatures. This ensures that the signature part is always at the bottom of the page.

```

683     \vfill
684     \ReviewerBlock\par
685     \SignatureBlock\par
686     \vspace*{1cm}%
687 \end{SFFont}%
688 \pagestyle{empty}%
689 \cleardoublepage
690 \vutinfth@restorelayout
691 \restoregeometry
692 }%

```

### 5.3.3 Front Matter Material

`\AddStatementPage` Generates the statement page.

```

693 \newcommand{\AddStatementPage}{

```

Set the same page geometry as for the titlepages.

```

694 %^^A \newgeometry{%
695 %^^A     left=2.4cm,right=2.4cm,bottom=2.5cm,top=2cm,
696 %^^A     headsep=\vutinfth@header@separator,
697 %^^A     head=\vutinfth@header@height
698 %^^A }%

```

Save the current page layout lengths for later restoration.

```

699 \vutinfth@savelayout
700 \setlength{\parindent}{0pt}%
701 \setlength{\baselineskip}{13.6pt}%
702 \setlength{\parskip}{0pt plus 1pt}%
703 \begin{SFFont}{phv}%
704     \sffamily
705     \chapter*{\vutinfth@polylingual@StatementChapter}%
706     \vutinfth@person@author@fullname\par
707 % ^^A     \vutinfth@data@address\par

```

```

708     \vspace{1.2cm}%
709     {\normalfont\vutinfth@polylingual@Statement}\par
710     {\normalfont\vutinfth@polylingual@AIStatement}\par
711     \vspace{1.2cm}%
712     \SignatureFields[y]{\vutinfth@person@author@name}{}%
713 \end{SFFont}%
714 \cleardoublepage
715 \vutinfth@restorelayout
716 %^^A \restoregeometry
717 }%

```

`\addtitlepage` Generates the titlepage in given language.

```

718 \newcommand{\addtitlepage}[1]{%
719   \selectlanguage{#1}%
720   \AddTitlePage
721 }%

```

`\addstatementpage` Generates the statement page.

```

722 \newcommand{\addstatementpage}{%
723   \selectlanguage{naustrian}%
724   \AddStatementPage
725 }%

```

`acknowledgements (env.)` Generates the English acknowledgement section.

```

726 \newenvironment{acknowledgements}{%
727   \selectlanguage{english}%
728   \chapter{Acknowledgements}%
729 }{%
730   \cleardoublepage
731 }%

```

`acknowledgements* (env.)` Generates the English acknowledgement section without an entry in the table of contents.

```

732 \newenvironment{acknowledgements*}{%
733   \selectlanguage{english}%
734   \chapter*{Acknowledgements}%
735 }{%
736   \cleardoublepage
737 }%

```

`danksagung (env.)` Generates the German acknowledgement section.

```

738 \newenvironment{danksagung}{%
739   \selectlanguage{naustrian}%
740   \chapter{Danksagung}%

```

```

741 }{%
742   \cleardoublepage
743 }%

```

**danksagung\*** (*env.*) Generates the German acknowledgement section without an entry in the table of contents.

```

744 \newenvironment{danksagung*}{%
745   \selectlanguage{naustrian}%
746   \chapter*{Danksagung}%
747 }{%
748   \cleardoublepage
749 }%

```

**abstract** (*env.*) Generates the English abstract.

```

750 \renewenvironment{abstract}{%
751   \selectlanguage{english}%
752   \chapter{Abstract}%
753 }{%
754   \cleardoublepage
755 }%

```

**abstract\*** (*env.*) Generates the English abstract without an entry in the table of contents.

```

756 \newenvironment{abstract*}{%
757   \selectlanguage{english}%
758   \chapter*{Abstract}%
759 }{%
760   \cleardoublepage
761 }%

```

**kurzfassung** (*env.*) Generates the German abstract.

```

762 \newenvironment{kurzfassung}{%
763   \selectlanguage{naustrian}%
764   \chapter{Kurzfassung}%
765 }{%
766   \cleardoublepage
767 }%

```

**kurzfassung\*** (*env.*) Generates the German abstract without an entry in the table of contents.

```

768 \newenvironment{kurzfassung*}{%
769   \selectlanguage{naustrian}%
770   \chapter*{Kurzfassung}%
771 }{%
772   \cleardoublepage
773 }%

```

**aitools** (*env.*) Generates the English AI statement.

```
774 \newenvironment{aitools}{%  
775   \selectlanguage{english}%  
776   \chapter[\vutinfth@AIToolsChapter@english]{\vutinfth@polylingual@AIToolsChapter}%  
777 }{%  
778   \cleardoublepage  
779 }%
```

**aitools\*** (*env.*) Generates the English AI statement without an entry in the table of contents.

```
780 \newenvironment{aitools*}{%  
781   \selectlanguage{english}%  
782   \chapter*{\vutinfth@polylingual@AIToolsChapter}%  
783 }{%  
784   \cleardoublepage  
785 }%
```

**kitools** (*env.*) Generates the German AI statement.

```
786 \newenvironment{kitools}{%  
787   \selectlanguage{naustrian}%  
788   \chapter[\vutinfth@AIToolsChapter@naustrian]{\vutinfth@polylingual@AIToolsChapter}%  
789 }{%  
790   \cleardoublepage  
791 }%
```

**kitools\*** (*env.*) Generates the German AI statement without an entry in the table of contents.

```
792 \newenvironment{kitools*}{%  
793   \selectlanguage{naustrian}%  
794   \chapter*{\vutinfth@polylingual@AIToolsChapter}%  
795 }{%  
796   \cleardoublepage  
797 }%
```

### 5.3.4 Page Style

**vutinfth@pagestyle@default** Define the default page style of the thesis.

```
798 \makepagestyle{\vutinfth@pagestyle@default}%  
799 \makeevenfoot{\vutinfth@pagestyle@default}{\thepage}{\thepage}%  
800 \makeoddfoot{\vutinfth@pagestyle@default}{\thepage}{\thepage}%
```

**\frontmatter** Apply the default page style to the thesis.

```
\mainmatter  
\backmatter 801 \aliaspagestyle{chapter}{\vutinfth@pagestyle@default}%  
802 \aliaspagestyle{part}{\vutinfth@pagestyle@default}%  
803 \addto\frontmatter{\pagestyle{\vutinfth@pagestyle@default}}%  
804 \addto\mainmatter{\pagestyle{Ruled}}%  
805 \addto\backmatter{\pagestyle{\vutinfth@pagestyle@default}}%
```



## 6 Change History

v0.9	General: Pre-release version . . . . .	1	v1.4	General: Added comma to separate posttitle and changed mainmatter pagestyle to 'Ruled'. . . . .	1
v1.0	General: Initial release version . . .	1		\mainmatter: Added 'Ruled' pagestyle. . . . .	32
v1.1	General: Added references to the GitLab environment . . . . .	1		\vutinfth@def@person: Added comma to separate posttitle. .	12
v1.3	General: Added support for a dissertation at the Vienna Phd School of Informatics. Issue #4 . . .	1	v1.5	General: Updated name of university to 'TU Wien'. . . . .	1
	\AddStatementPage: Updated to support multiple languages. Issue #4 . . . . .	29		PolyLinguals: Updated name of university to 'TU Wien'. . . . .	19
	\addstatementpage: Updated to support English version. Issue #4 . . . . .	30	v1.6	General: Enabled second advisor for dissertations. . . . .	1
	\AddTitlePage: Added check for subtitle existence before usage. Issue #1 . . . . .	27		\AdvisorBlock: Enabled second advisor for dissertations. . . . .	25
	Updated to support PhD School mentioning and fixed the associated vertical overflow. Issue #4 . . . . .	27		PolyLinguals: Provided German term for second advisor. . . . .	19
	\AdvisorBlock: Updated to support second advisor. Issue #4 . . . . .	25	v1.8	General: Removed address information. . . . .	1
	Persons: Updated to support second advisor. Issue Issue #4 . . .	19		\AddStatementPage: Removed address information. . . . .	29
	TextualData: Updated to support external reviewer data. Issue #4 . . . . .	19		TextualData: Removed address information. . . . .	19
	PolyLinguals: Added to support multiple dissertation types. Issue #4 . . . . .	19	v1.9	General: Changed header graphics and unversity URL. . . . .	1
	\ReviewerBlock: Updated to support external reviewers. Issue #4 . . . . .	27		\AddStatementPage: Changed header graphics. . . . .	29
	\setthesis: Altered to support multiple dissertation types. Issue #4 . . . . .	17		\AddTitlePage: Changed header graphics. . . . .	27
	\SignatureBlock: Updated to support multiple dissertation types. Issue #4 . . . . .	27		vutinfth@pagestyle@titlepage: Changed header graphics. . . .	24
	\vutinfth@thesis@doctor: Added to support multiple dissertation types. Issue #4 . . .	16		\vutinfth@footer@titlepage: Changed university URL. . . .	24
				\vutinfth@header@titlepage: Changed header graphics. . . .	24
			v1.11	General: Updated name of faculty to 'TU Wien Informatics'. . . .	1
				\setdate: Updated to datetime2 package. . . . .	11

\SignatureFields: Updated to datetime2 package. . . . .	26	\setthesis: Removed support for multiple dissertation types. Issue #8 . . . . .	17
v1.12		\SignatureBlock: Removed support for multiple dissertation types. Issue #8 . .	27
General: Removed obsolete support for a dissertation at the Vienna PhD School of Informations. Issue #8 . . . . .	1	\vutinfth@thesis@doctor: Removed support for multiple dissertation types. Issue #8 . .	16
\addstatementpage: Removed support for English version. Issue #8 . . . . .	30	v1.13	
\AddTitlePage: Removed obsolete support for a dissertation at the Vienna PhD School of Informations. Issue #8 . . . . .	27	General: Added AI statement. . . .	1
PolyLinguals: Removed support of multiple dissertation types. Issue #8 . . . . .	19	\AddStatementPage: Added AI statement. . . . .	29
\ReviewerBlock: Removed support for external reviewers. Issue #8 . . . . .	27	aitools: Added AI statement. . .	32
		aitools*: Added AI statement. .	32
		kitools: Added AI statement. . .	32
		kitools*: Added AI statement. .	32
		PolyLinguals: Added AI statement. . . . .	19

## Index

### Symbols

\"	331, 334, 348, 356, 357, 358, 372, 374, 376, 377, 486
\@empty	134, 153
\@namedef	47, 48, 51, 54, 57, 71, 72, 73, 74, 76, 79, 83, 86, 88, 94, 96, 100, 102, 108, 111, 113, 115, 117, 119, 123, 129, 130, 167
\@namelet	136, 155
\@nameuse	54, 112, 114, 116, 118, 120, 132, 139, 148, 158, 159
\@namexdef	18, 140
\@setdegreename	199, 212, 221, 230, 251
\@setgendereddegreename	199, 243, 255, 263, 275, 282, 289
\@setthesisname	199, 211, 217, 229, 242, 250, 254, 262
\\	486, 516, 519, 525, 535, 548, 582, 592, 601, 645
\sq	375, 673

### A

abstract (env.) . . . . .	7, 750
abstract* (env.) . . . . .	7, 756
acknowledgements (env.) . . . . .	7, 726
acknowledgements* (env.) . . . . .	7, 732
\AddLanguage . . . . .	8, 128, 308, 309
\AddStatementPage . . . . .	9, 693, 724
\addstatementpage . . . . .	7, 722
\AddTitlePage . . . . .	9, 628, 720
\addtitlepage . . . . .	6, 6, 718

\addto	803, 804, 805
\AdvisorBlock	9, 510, 682
aitools (env.)	774
aitools* (env.)	780
\aliaspagestyle	801, 802

## B

\backmatter	801
\baselineskip	461, 466, 565, 637, 701
\begin	478, 484, 512, 514, 543, 561, 578, 588, 639, 643, 677, 703
\begingroup	20, 34, 163
\bfseries	645, 647, 659, 663, 666, 671
\bigskip	646

## C

\centering	483, 485, 581, 591, 641, 644
\chapter	705, 728, 734, 740, 746, 752, 758, 764, 770, 776, 782, 788, 794
\chapterstyle	6
\ClassError	52, 109, 185, 189, 193, 218, 222, 231
\cleardoublepage	689, 714, 730, 736, 742, 748, 754, 760, 766, 772, 778, 784, 790, 796
\CreateData	7, 56, 296, 297, 298, 299
\CreatePerson	7, 122, 300, 301, 302, 303, 304, 305, 306, 307
\CreatePolylingual	8, 162, 310, 313, 316, 320, 323, 326, 329, 332, 335, 338, 341, 343, 346, 349, 363, 381, 384, 387, 390, 393, 396, 399, 402, 406, 410, 413, 416, 419, 422, 426, 430, 433, 436, 439, 443, 446, 449
\csname	18
\CurrentOption	2

## D

danksagung (env.)	7, 738
danksagung* (env.)	7, 744
\DeclareOption	1
\DTMsavedate	44
\DTMusedate	565

## E

\edef	21, 22
\else	144
\end	480, 491, 539, 540, 552, 566, 584, 594, 652, 681, 687, 713
\endcsname	18
\endgroup	25, 37, 166
environments:	
abstract	7, 750
abstract*	7, 756
acknowledgements	7, 726

acknowledgements*	7, <a href="#">732</a>
aitools	<a href="#">774</a>
aitools*	<a href="#">780</a>
danksagung	7, <a href="#">738</a>
danksagung*	7, <a href="#">744</a>
kitools	<a href="#">786</a>
kitools*	<a href="#">792</a>
kurzfassung	7, <a href="#">762</a>
kurzfassung*	7, <a href="#">768</a>
SFFont	9, <a href="#">33</a>
\expandafter	18, 23, 24

## F

\f@family	36, 39
\fi	146
\fontsize	27, 28, 29, 30, 31, 32
\footruleskip	503
\frontmatter	<a href="#">801</a>

## G

\global	36
\glqq	374
\graphicspath	17
\grqq	375

## H

\hfill	480, 567, 572, 576, 585
\hspace	571, 575

## I

\ifcempty	141
\ifcsstring	65, 68
\ifdef	517, 521, 528, 547, 648
\ifdefstrequal	39
\ifdefstring	75, 78, 159, 208, 214, 226, 241, 249, 253, 261, 274, 281, 288
\ifdraftdoc	142
\ifestrequal	19, 175, 180
\iffemale	64, 205
\ifgraduate	174, 542, 599, 620, 665
\ifmale	64, 204
\ifstrempty	81, 82, 85, 92, 93, 99, 574, 587
\ifstrequal	23, 560, 569, 570
\ifundef	133, 152, 522, 529, 532
\ifundergraduate	174, 511, 611, 658
\includegraphics	479

## K

kitools (env.)	786
kitools* (env.)	792
kurzfassung (env.)	7, 762
kurzfassung* (env.)	7, 768

## L

\language	159
\Languages	308
\let	36
\LoadClass	5

## M

\mainmatter	801
\makeevenfoot	504, 799
\makeevenhead	498
\makefootrule	502
\makeheadposition	496
\makeoddfoot	506, 800
\makeoddhead	500
\makepagestyle	493, 798
\makerunningwidth	494

## N

\newcommand	18, 19, 27, 28, 29, 30, 31, 32, 43, 46, 50, 56, 62, 63, 64, 67, 70, 107, 122, 128, 134, 153, 162, 170, 172, 174, 179, 184, 188, 192, 196, 197, 198, 199, 201, 203, 207, 236, 237, 238, 239, 240, 270, 271, 272, 273, 442, 445, 448, 451, 455, 459, 464, 476, 482, 509, 510, 558, 598, 610, 628, 693, 718, 722
\newenvironment	33, 726, 732, 738, 744, 756, 762, 768, 774, 780, 786, 792
\newgeometry	630, 694
\newlength	452, 456, 457, 458
\newsetlength	451, 469, 470, 471, 472, 473, 474, 475, 508, 555, 556, 557
\normalfont	709, 710

## P

\pagestyle	688, 803, 804, 805
\paperwidth	473
\par	552, 642, 652, 654, 656, 659, 661, 663, 666, 669, 671, 674, 679, 681, 682, 684, 685, 706, 707, 709, 710
\parindent	460, 465, 636, 700
\parskip	462, 467, 638, 702
\PassOptionsToClass	2
\Persons	300
\PolyLinguals	310
\ProcessOptions	4

## R

<code>\relax</code> .....	4, 145
<code>\renewcommand</code> .....	38, 41, 138, 157, 200, 202, 209, 215, 227
<code>\renewenvironment</code> .....	750
<code>\RequirePackage</code> .....	7, 8, 9, 10, 11, 12, 13, 14, 15, 16
<code>\restoregeometry</code> .....	691, 716
<code>\ReviewerBlock</code> .....	9, 598, 684
<code>\rule</code> .....	455, 582, 592

## S

<code>\selectfont</code> .....	27, 28, 29, 30, 31, 32
<code>\selectlanguage</code> .....	719, 723, 727, 733, 739, 745, 751, 757, 763, 769, 775, 781, 787, 793
<code>\set</code> .....	60, 126
<code>\setadvisor</code> .....	4, 5
<code>\setauthor</code> .....	4, 5
<code>\setcurriculum</code> .....	3, 6, 448
<code>\setdate</code> .....	4, 43
<code>\setdoctordegree</code> .....	5, 231, 232, 273
<code>\setfirstassistant</code> .....	4
<code>\setfirstreviewer</code> .....	4
<code>\setfirstreviewerdata</code> .....	3
<code>\setkeys</code> .....	164
<code>\setlength</code> .....	453, 460, 461, 462, 465, 466, 467, 477, 636, 637, 638, 700, 701, 702
<code>\setmasterdegree</code> .....	5, 218, 219, 222, 223, 240
<code>\setregnumber</code> .....	3
<code>\setsecondadvisor</code> .....	4
<code>\setsecondassistant</code> .....	4
<code>\setsecondreviewer</code> .....	4
<code>\setsecondreviewerdata</code> .....	3
<code>\setsubtitle</code> .....	3, 6, 445
<code>\setthesis</code> .....	5, 185, 186, 189, 190, 193, 194, 207
<code>\setthirdassistant</code> .....	4
<code>\settitle</code> .....	3, 6, 442
<code>\sfdefault</code> .....	38, 41
<code>\sffamily</code> .....	35, 39, 485, 640, 704
<code>SFFont (env.)</code> .....	9, 33
<code>\SignatureBlock</code> .....	8, 610, 685
<code>\SignatureFields</code> .....	8, 558, 602, 613, 622, 712
<code>\smallskip</code> .....	672
<code>\space</code> .....	185, 189, 193, 218, 222, 231, 487, 488, 489
<code>\ss</code> .....	359
<code>\string</code> ....	60, 126, 185, 186, 189, 190, 193, 194, 218, 219, 222, 223, 231, 232

## T

<code>\Textual□Data</code> .....	296
----------------------------------	-----

\textwidth	484, 494, 512, 543, 643, 677
\thepage	799, 800
\thispagestyle	629

## U

\unitlength	477
-------------	-----

## V

\vfill	683
\vspace	509, 565, 642, 686, 708, 711
\vutinfth@AIToolsChapter@english	776
\vutinfth@AIToolsChapter@naustrian	788
\vutinfth@allocate@polylingual	133, 134, 137, 138, 165
\vutinfth@bigskip	509, 653, 655, 657, 660, 662, 668, 670, 676
\vutinfth@bigskipamount	508, 509
\vutinfth@data@address	707
\vutinfth@data@regnumber	674
\vutinfth@def@data	46, 58
\vutinfth@def@data@invalid	50, 60
\vutinfth@def@person	70, 124
\vutinfth@def@person@invalid	107, 126
\vutinfth@f@family@tmp	36, 39, 41
\vutinfth@footer@titlepage	482, 505, 507
\vutinfth@header@height	474, 633, 697
\vutinfth@header@separator	475, 632, 696
\vutinfth@header@titlepage	476, 499, 501
\vutinfth@header@width	473, 495
\vutinfth@HUGE	27, 645
\vutinfth@huge	27, 647
\vutinfth@LARGE	27, 654, 659, 666
\vutinfth@Large	27, 663, 671
\vutinfth@large	27, 656, 661, 669, 673
\vutinfth@logo@height	472, 474, 479
\vutinfth@logo@offset@x	469, 473
\vutinfth@logo@offset@y	470
\vutinfth@logo@width@safe	471
\vutinfth@normalsize	27, 485, 513, 544, 559, 600, 612, 621, 678
\vutinfth@pagestyle@default	798
\vutinfth@pagestyle@titlepage	493
\vutinfth@pagestyle@titlepagefootrunwidth	503
\vutinfth@person@advisor@fullname	516, 546
\vutinfth@person@advisor@name	616
\vutinfth@person@author@fullname	671, 706
\vutinfth@person@author@name	614, 623, 712
\vutinfth@person@female	62, 68, 78, 79
\vutinfth@person@firstassistant@def	517, 522, 529

\vutinfth@person@firstassistant@error	523, 530
\vutinfth@person@firstassistant@fullname	519
\vutinfth@person@firstreviewer@name	603
\vutinfth@person@male	62, 65, 75, 76
\vutinfth@person@secondadvisor@def	547
\vutinfth@person@secondadvisor@fullname	550
\vutinfth@person@secondassistant@def	521, 532
\vutinfth@person@secondassistant@error	533
\vutinfth@person@secondassistant@fullname	525
\vutinfth@person@secondreviewer@name	605
\vutinfth@person@thirdassistant@def	528
\vutinfth@person@thirdassistant@fullname	535
\vutinfth@placedate@width	555, 562, 571
\vutinfth@polylingual@Advisor	515, 545
\vutinfth@polylingual@AIStatement	710
\vutinfth@polylingual@AIToolsChapter	776, 782, 788, 794
\vutinfth@polylingual@Assistance	518
\vutinfth@polylingual@BACHELORTHESIS	211
\vutinfth@polylingual@Bdeg	212
\vutinfth@polylingual@by	669
\vutinfth@polylingual@Curriculum	663
\vutinfth@polylingual@DdegRerNatFemale	278
\vutinfth@polylingual@DdegRerNatMale	276
\vutinfth@polylingual@DdegRerSocOecFemale	292
\vutinfth@polylingual@DdegRerSocOecMale	290
\vutinfth@polylingual@DdegTechnFemale	285
\vutinfth@polylingual@DdegTechnMale	283
\vutinfth@polylingual@degreename	188, 202, 659, 666
\vutinfth@polylingual@DIPLOMATHESES	242
\vutinfth@polylingual@DOCTORTHESIS	229
\vutinfth@polylingual@faculty	679
\vutinfth@polylingual@in	661
\vutinfth@polylingual@MASTERTHESIS	250, 254, 262
\vutinfth@polylingual@MdegDiplFemale	246
\vutinfth@polylingual@MdegDiplMale	244
\vutinfth@polylingual@MdegMaster	251
\vutinfth@polylingual@MdegRerNatFemale	258
\vutinfth@polylingual@MdegRerNatMale	256
\vutinfth@polylingual@MdegRerSocOecFemale	266
\vutinfth@polylingual@MdegRerSocOecMale	264
\vutinfth@polylingual@Place	564
\vutinfth@polylingual@Registrationnumber	673
\vutinfth@polylingual@Reviewed	601
\vutinfth@polylingual@Secondadvisor	549
\vutinfth@polylingual@Statement	709
\vutinfth@polylingual@StatementChapter	705



\vutinfth@polylingual@submission	656
\vutinfth@polylingual@Subtitle	648, 649
\vutinfth@polylingual@thesisname	192, 200, 654
\vutinfth@polylingual@Title	645
\vutinfth@polylingual@university	680
\vutinfth@restorelayout	459, 690, 715
\vutinfth@savelayout	459, 635, 699
\vutinfth@selectlanguage@polylingual	152, 153, 156, 157, 168
\vutinfth@signature@height	555, 561, 578, 588
\vutinfth@signature@width	555, 575, 579, 582, 589, 592
\vutinfth@squarebullet	451, 487, 488, 489
\vutinfth@tempa	21, 24
\vutinfth@tempb	22, 24
\vutinfth@thesis@bachelor	196, 208
\vutinfth@thesis@basetype	175, 180, 184, 209, 215, 227
\vutinfth@thesis@basetype@graduate	170, 181, 228
\vutinfth@thesis@basetype@undergraduate	170, 176, 210, 216
\vutinfth@thesis@ddeg@rernat	270, 274
\vutinfth@thesis@ddeg@rersocoec	270, 288
\vutinfth@thesis@ddeg@techn	270, 281
\vutinfth@thesis@degreename	184
\vutinfth@thesis@doctor	196, 226
\vutinfth@thesis@master	196, 214
\vutinfth@thesis@mdeg@dipl	236, 241
\vutinfth@thesis@mdeg@master	236, 249
\vutinfth@thesis@mdeg@rernat	236, 253
\vutinfth@thesis@mdeg@rersocoec	236, 261
\vutinfth@thesis@thesisname	184
\vutinfth@tmp@baselineskip	456, 461, 466
\vutinfth@tmp@parindent	456, 460, 465
\vutinfth@tmp@parskip	456, 462, 467

## X

\xdef	18
-------	----