

2 - Symbols - Abbreviations - References

To allow quick and easy consultation, this manual uses graphic symbols to highlight situations in which maximum care is required, as well as practical advice or information. Pay attention to the meaning of the symbols since they serve to avoid repeating technical concepts or safety warnings throughout the text. The symbols should therefore be seen as an aid to memory. Please refer to this page whenever in doubt as to their meaning.

The terms RIGHT-HAND and LEFT-HAND refer to the motorcycle viewed from the riding position.



Warning

Failure to comply with these instructions may put you at risk, and could lead to severe injury or even death.



Important

Failure to follow the instructions in text marked with this symbol can lead to serious damage to the motorcycle and its components.



Note

This symbol indicates additional useful information for the current operation.

Text references

(X)

References in bold type indicate a part that is not illustrated in the figures next to the text, but which can be found in the exploded views at the beginning of each chapter.

(X)

References in non-bold type indicate a part that is illustrated in the figures alongside the text.

Product specifications

Symbols in the diagram show the type of thread locker, sealant or lubricant to be used at the points indicated. The table below shows the symbols used and the specifications of the various products.

Symbol	Specifications	Recommended product
	Engine oil (for characteristics see Sect. C 2, Fuel, lubricants and other fluids)	SHELL Advance Ultra 4
	DOT 4 special hydraulic brake fluid.	SHELL Advance Brake DOT 4
	SAE 80-90 gear oil or special products for chains with O-rings.	SHELL Advance Chain or Advance Teflon Chain
	Anti-freeze (nitride, amine and phosphate free) 30 to 40% solution in water.	SHELL Advance coolant or Glycoshell
	GREASE A Multipurpose, medium fibre, lithium grease.	SHELL Alvania R3
	GREASE B Molybdenum disulphide grease, high mechanical stress and high temperature resistant.	SHELL Retinax HDX2

	GREASE C	Bearing/joint grease for parts subject to prolonged mechanical stress. Temperature range: -10 to 110 °C.	SHELL Retinax LX2
	GREASE D	Protective grease, with anti-corrosive and waterproofing properties.	SHELL Retinax HD2
	GREASE E	PANKL grease - PLB 05.	
	GREASE F	OPTIMOL grease - PASTE WHITE T.	
	LOCK 1	Low-strength thread locker.	Loctite 222
	LOCK 2	Medium-strength threadlocker, compatible with oil.	Loctite 243
	LOCK 3	High-strength thread locker for threaded parts.	Loctite 270
	LOCK 4	Flange sealant resistant to high mechanical stress and solvents. Resists high temperatures (up to 200 °C) and pressures up to 350 bar; fills gaps up to 0.4 mm.	Loctite 510
	LOCK 5	Permanent adhesive for smooth or threaded cylindrical fasteners on mechanical parts. High resistance to mechanical stress and solvents. Temperature range: -55 to 175 °C.	Loctite 128455
	LOCK 6	Pipe sealant for pipes and medium to large fasteners. For water and gases (except oxygen). Maximum filling capacity: diameter clearances up to 0.40 mm.	Loctite 577
	LOCK 7	Speed bonder for rubber and plastics with elastomer charged ethylic base.	Loctite 480
	LOCK 8	High-strength retaining compound for threaded parts, bearings, bushes, splines and keys. Temperature range: -55 to 150 °C.	Loctite 601
	LOCK 9	Medium-strength threadlocker.	Loctite 406
	LOCK 10	Product for metal parts to seal and lock cylindrical freely sliding or threaded couplings. Resistant to high mechanical stress and high temperature, excellent resistance to solvents and chemical attack.	Loctite 128443
	LOCK 11	Medium-strength threadlocker.	Loctite 401
	LOCK 12	Instant adhesive gel offering tensile/shear strength.	Loctite 454 gel



DUCATI liquid gasket.

942470014



Exhaust pipe paste. Self-sealing paste, hardens when heated; resists temperatures exceeding 1000 °C.

Holts Firegum



Spray used to protect electric systems. Eliminates moisture and condensation and provides excellent corrosion resistance. Water repellent.

SHELL
Advance Contact Cleaner



Dry lubricant, polymerising on contact with air.

Molykote D321R



Emulsion for lubrication of rubber.

P 80