


Single Phase Hybrid Inverter

SUN-7.6/8K-SG02LP1-EU-AM2-P

SUN-10/12K-SG02LP1-EU-AM3-P



Colorful touch LCD, IP65 protection degree



AC couple to retrofit existing solar system



Max. 16 pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel



Max. charging/discharging current of 250A



6 time periods for battery charging/discharging



Support storing energy from diesel generator

Deye

Stock Code: 605117.SH

Model	SUN-7.6K-SG02 LP1-EU-AM2-P	SUN-8K-SG02 LP1-EU-AM2-P	SUN-10K-SG02 LP1-EU-AM3-P	SUN-12K-SG02 LP1-EU-AM3-P
Battery Input Data				
Battery Type		Lead-acid or Lithium-ion		
Battery Voltage Range (V)		40-60		
Max. Charging Current (A)	190	190	220	250
Max. Discharging Current (A)	190	190	220	250
Charging Strategy for Li-ion Battery		Self-adaption to BMS		
Number of Battery Input		1		
PV String Input Data				
Max. PV Access Power (W)	15200	16000	20000	24000
Max. PV Input Power (W)	12160	12800	16000	19200
Max. PV Input Voltage (V)		500		
Start-up Voltage (V)		125		
MPPT Voltage Range (V)		150-425		
Rated PV Input Voltage (V)		370		
Max. Operating PV Input Current (A)	32+32			32+32+32
Max. Input Short-Circuit Current (A)	60+60			60+60+60
No. of MPP Trackers/ No. of Strings MPP Tracker	2/2+2			3/2+2+2
AC Input/Output Data				
Rated AC Input/Output Active Power (W)	7600	8000	10000	12000
Max. AC Input/Output Apparent Power (VA)	8360	8800	11000	13200
Rated AC Input/Output Current (A)	34.6/33.1	36.4/34.8	45.5/43.5	54.6/52.2
Max. AC Input/Output Current (A)	38/36.4	40/38.3	50/47.9	60/57.4
Max. Continuous AC Passthrough (grid to load) (A)	50		60	
Peak Power (off-grid) (W)		2 times of rated power, 10s		
Power Factor Adjustment Range		0.8 leading to 0.8 lagging		
Rated Input/Output Voltage/Range (V)		220/230 0.85Un-1.1Un		
Rated Input/Output Grid Frequency/Range(Hz)		50/45-55 60/55-65		
Grid Connection Form		L+N+PE		
Total Current Harmonic Distortion THDi		<3% (of nominal power)		
DC Injection Current		<0.5% In		
Efficiency				
Max. Efficiency		97.6%		
Euro Efficiency		96.5%		
MPPT Efficiency		>99%		
Equipment Protection				
Integrated	DC Reverse Polarity Protection, AC Output Overcurrent Protection, Thermal Protection, AC Output Overvoltage Protection, AC Output Short Circuit Protection, DC Component Monitoring, Arc Fault Circuit Interrupter (optional), Anti-islanding Protection, DC Switch, Insulation Impedance Detection, Residual Current Detection			
Surge Protection Level		TYPE II(DC), TYPE II(AC)		
Interface				
Communication Interface		RS485/RS232/CAN		
Monitor Mode		GPRS/WIFI/Bluetooth/4G/LAN(optional)		
General Data				
Operating Temperature Range (°C)		-40 to +60°C, +45°C Derating		
Permissible Ambient Humidity		0-100%		
Permissible Altitude		2000m		
Noise (dB)		<45		
Ingress Protection(IP) Rating		IP65		
Inverter Topology		Non-Isolated		
Over Voltage Category		OVC II(DC) OVC III(AC)		
Cabinet Size (WxHxD mm)		420×670×233 (Excluding Connectors and Brackets)		
Weight (kg)		35.6		
Type of Cooling		Intelligent Air Cooling		
Warranty	the Warranty Period Depends the Final Installation Site of Inverter, More Info Please Refer to Warranty Policy			
Grid Regulation	VDE4105, IEC61727/62116, VDE0126, AS4777.2, CEI 0 21, EN50549-1, G98, G99, C10-11, UNE217002, NBR16149/NBR16150			
Safety / EMC Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2			