

Product Highlights

Long Cycle Life

Cycle life up to 6000+ cycles to maximise return on investment.

Self-heating

Built-in heating film to support battery charging in extremely cold environment.

Lightweight

Lithium iron batteries are 60% lighter than lead-acid batteries, allowing for simple installation and transportation.

Multiple Protection

Support OC/OV/OT/UV/UT/SC protection function. The battery management system provides comprehensive protection and manages.

Active Backup Protection

Extra relay can cut off the input/output to ensure safety when battery failure.



Electrical Parameters

Nominal Voltage	12.8V
Nominal Capacity	314Ah
Maximum Series and Parallel Capability	4S or 8P
Cycle Life	6000
Maximum Sustained Discharge Current	160A
Peak Discharge Current	320A/10s
Maximum Sustained Charge Current	160A
Recommended Charge Current	≤50A
Recommended Charge Voltage	14-14.4V

Environmental Parameters

Recommended Storage Temperature	10-35°C
Working Temperature	-20-50°C
Altitude	< 4000m
Relative Humidity	5%-95% (No Condensation)

Other

Switch	Yes
Certifications	CE, UN38.3
Heating Film	Yes

Mechanical Parameters

Dimension (L*W*H)	340*280*235
Weight	≈31.5kg
Terminal Type	M8*1.25*14mm
Terminal Torque	8±1Nm
Case Material	Metal
Production Rating	IP55
Battery Type	LiFePO4