

75-125K

SOLARATOR SERIES

Experience Uninterrupted Power with Solis Energy Storage Inverters

S6-EH3P(75-125)K10-NV-YD-H

Three Phase | High Voltage



12 Unique Advantages

- ★ Supports up to 2x rated PV input, maximizing solar energy utilization
- ★ Supports a maximum string input current of 21A, ensuring compatibility with high-power PV modules
- ★ Compatible with 100-314Ah battery modules, reducing overall system costs
- ★ Supports fast battery charging with a maximum charging current of 200A
- ★ Two independent battery ports for flexible configurations and easy capacity expansion
- ★ Delivers 160% overload for 200ms in off-grid mode, ensuring stable startup of heavy loads
- ★ Offers flexible control for weak grid and genset-hybrid scenarios, reducing investment costs
- ★ SolisCloud: Smart remote control, AI optimisation, and instant troubleshooting - all in one platform
- ★ Integrates PV and storage for demand management and anti-reverse flow functions
- ★ Provides dynamic reactive power compensation to improve grid power factor and reduce reactive power charges
- ★ Utility bypass function allows direct grid supply to backup loads
- ★ Patented cooling technology ensures reliable operation even under high-temperature conditions

6 Leading Advantages

- Supports both DC and AC coupling, for flexible retrofits and system expansions
- Ensures reliable backup power across diverse scenarios through battery reserve management
- Extends supply time for critical loads with intelligent load prioritization
- Offers a versatile three-in-one interface for seamless integration of on-grid PV, wind power, and diesel generators
- Achieves on- and off-grid transitions in less than 10ms, ensuring an uninterrupted power supply
- Supports multi-unit parallel operation up to 1.25MW (Solis STS cabinet recommended for systems over 6 units)

GINLONG TECHNOLOGIES CO., LTD.

t: +86 574 6580 2188 e: sales@ginlong.com
w: solisinverters.com service@ginlong.com



DATASHEET

Models	75K	80K	99.9K	100K	125K
Input DC (PV side)					
Recommended max. PV array size	150 kW	160 kW	200 kW	200 kW	250 kW
Max. usable PV input power	150 kW	160 kW	200 kW	200 kW	250 kW
Max. input voltage			1000 V		
Rated voltage			600 V		
Start-up voltage			180 V		
MPPT voltage range			150 - 950 V		
Max. input current			10 × 42 A		
Max. short circuit current			10 × 60 A		
MPPT number / Max. input strings number			10 / 20		
Battery					
Battery type			Li-ion		
Battery voltage range			300 - 950 V		
Max. charge / discharge current			100 A × 2 / 100 A × 2		
Number of battery ports			2		
Max. charge / discharge current of each port			100 A		
Communication			CAN / RS485		
Output AC (Back-up)					
Rated output power	75 kW	80 kW	99.9 kW	100 kW	125 kW
Max. apparent output power		75-100K: 1.6 times of rated power, 10 s; 2 times of rated power, 200 ms; 125K: 1.4 times of rated power, 10 s; 1.6 times of rated power, 200 ms			
Back-up switch time			< 10 ms		
Rated output voltage		3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V			
Rated frequency			50 Hz / 60 Hz		
THDv (@linear load)			< 3%		
Input AC (Grid side)					
Max. input current			250 A		
Input AC (Generator)					
Max. input power	75 kW	80 kW	99.9 kW	100 kW	125 kW
Rated input current	114.0 A / 108.3 A	121.6 A / 115.5 A	151.8 A / 144.2 A	151.9 A / 144.3 A	189.9 A / 180.4 A
Rated input voltage		3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V			
Rated input frequency			50 Hz / 60 Hz		
Output AC (Grid side)					
Rated output power	75 kW	80 kW	99.9 kW	100 kW	125 kW
Max. apparent output power	75 kVA	80 kVA	99.9 kVA	100 kVA	125 kVA
Rated grid voltage		3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V			
Rated grid frequency			50 Hz / 60 Hz		
Rated grid output current	114 A / 108.3 A	121.6 A / 115.5 A	151.8 A / 144.2 A	151.9 A / 144.3 A	189.9 A / 180.4 A
Power factor		> 0.99 (0.8 leading - 0.8 lagging)			
THDi			< 3%		
Efficiency					
Max. efficiency			97.5%		
EU efficiency	96.9%	96.9%	97.1%	97.1%	97.2%
BAT charged / discharged to AC max. efficiency			97.0%		
Protection					
Anti-islanding protection			Yes		
Output over current protection			Yes		
Short circuit protection			Yes		
Integrated DC switch			Yes		
DC reverse-polarity protection			Yes		
Protection class / Over voltage category			I/ DC II, AC III		
Surge protection			DC Type II / AC Type II		
Integrated AFCI 2.0			Optional (Brazil: Yes)		
General Data					
Max. power per phase (grid & back-up)	25 kW	26.66 kW	33.3 kW	33.33 kW	41.66 kW
Dimensions (W × H × D)			1174 × 814 × 400 mm		
Weight			170 kg		
Topology			Transformerless		
Operating ambient temperature range			-25 ~ +60°C		
Relative humidity			0 - 100%		
Ingress protection			IP66		
Cooling concept			Intelligent redundant fan-cooling		
Max. operation altitude			3000 m		
Grid connection standard ①	G99, VDE-AR-N 4105/VDE V 0124, EN 50549-1&2/EN 50549-10, VDE 0126/UTE C 15/VFR:2019, NTS 631/RF 1699/RD 244/				
	UNE 206006/UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683,				
	EN 50530, MEA, PEA, PORTARIA N° 140, DE 21 DE MARÇO DE 2022;				
Safety / EMC standard ①	Brazil (75K: ORDINANCE (PORTARIA) NO.140, ORDINANCE NO. 515; 100K/125K: NBR 16149, NBR 16150, IEC 62116)				
	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4, EN 55011				
Features					
PV connection	MC4 Quick connection plug				
Battery connection	Terminal connector				
AC connection	Terminal block				
Display	7.0" LCD display & Bluetooth + APP				
Communication interface	Standard: WIFI+LAN+Bluetooth, CAN-BMS × 2, CAN-Parallel × 2, LAN, RS485-Meter, RS485, DRM, DI × 5				
	DO × 4; Optional: 4G				

① This column only shows the planned certification standards. Please confirm the specific time of obtaining the standards with the local team.