

5-8K

SOLARATOR SERIES

Experience Uninterrupted Power with Solis Energy Storage Inverters

S6-EH2P(5-8)K02-SV-YD-L

Split Phase | Low Voltage

- Supports PV input up to 160% of the inverter's rated DC power, maximising solar utilisation
- Supports up to 21A PV input current, compatible with future higher-power PV modules
- 200% overload for 10s in off-grid mode, ensuring stable startup of motors, water pumps and air conditioners
- Seamless on/off-grid switching in under 10ms, guaranteeing an uninterrupted power supply
- Support split-phase unbalanced output, each phase supports output max. 50% rated inverter power
- More battery options, compatible with any battery (between 40V-60V)
- Supports existing PV grid-tied power connection for export control and off-grid use
- Multiple methods of generator connection and auto control, enabling flexible local deployment
- Support max 6 units in parallel, for expanding system capacity
- Smart Load management, extending backup time for critical loads
- Customizable battery backup level for uninterrupted power
- PV only off grid mode, to reduce the initial investment cost
- 7-inch industrial-grade touchscreen, providing a larger, user-friendly interface for local operation
- Ingress protection IP66, adapting to harsh ambient conditions

CINLONG TECHNOLOGIES CO., LTD.

t: +86 574 6580 2188 e: sales@ginlong.com
w: solisinverters.com service@ginlong.com



DATASHEET

Models	5K	6K	7.5K	8K
Input DC (PV side)				
Recommended max. PV array size	10 kW	12 kW	16 kW	16 kW
Max. usable PV input power	8 kW	9.6 kW	12.8 kW	12.8 kW
Max. input voltage		500 V		
Rated voltage		330 V		
Start-up voltage		90 V		
MPPT voltage range		90 - 435 V		
Max. input current	21 A / 21 A	21 A / 42 A		42 A / 42 A
Max. short circuit current	24 A / 24 A	24 A / 48 A		48 A / 48 A
MPPT number / Max. input strings number	2 / 2	2 / 3		2 / 4
Battery				
Battery type		Li-ion / Lead-acid		
Battery voltage range		40 - 60 V		
Max. charge / discharge power	5 kW	6 kW	7.5 kW	8 kW
Max. charge / discharge current	112 A	135 A	190 A	190 A
Communication		RS485 / CAN		
Output AC (Grid side)				
Rated output power	5 kW	6 kW	7.5 kW	8 kW
Rated grid voltage		L+N+PE/2L+PE, 220 V; L1/L2/N(PE), 120(L-N)/240(L1-L2)VAC		
Rated grid frequency		50 Hz / 60 Hz		
Rated grid output current	20.8 A / 22.7 A	25 A / 27.3 A	31.3 A / 34.1 A	33.3 A / 36.4 A
Max. output current	22.9 A / 25 A	27.5 A / 30 A	31.3 A / 34.1 A	36.7 A / 40 A
Power factor		> 0.99 (0.8 leading - 0.8 lagging)		
THDi		< 3%		
Input AC (Grid side)				
Input voltage range		L+N+PE/2L+PE, 220 V; L1/L2/N(PE), 120(L-N)/240(L1-L2)VAC		
Max. input current	35 A	40 A	50 A	50 A
Frequency range		45 - 55 Hz / 55 - 65 Hz		
Input Generator				
Max. input power	5 kW	6 kW	7.5 kW	8 kW
Max. input current	20.8 A / 22.7 A	25 A / 27.3 A	31.3 A / 34.1 A	33.3 A / 36.4 A
Rated input frequency		50 Hz / 60 Hz		
Output AC (Back-up)				
Rated output power	5 kW	6 kW	7.5 kW	8 kW
Max. apparent output power		2 times of rated power, 10 s		
Back-up switch time		< 10 ms		
Rated output voltage		L1/L2/N(PE), 127 V / 220 V; L1/L2/N(PE), 120(L-N)/240(L1-L2)VAC		
Rated frequency		50 Hz / 60 Hz		
Rated output current	20.8 A / 22.7 A	25 A / 27.3 A	31.3 A / 34.1 A	33.3 A / 36.4 A
Max. AC passthrough current	35 A	40 A	50 A	50 A
THDv (@linear load)		< 3%		
Efficiency				
Max. efficiency		96.0%		
EU efficiency		94.5%		
BAT charged by PV / AC max. efficiency		95.0%		
BAT discharged to AC max. efficiency		93.7%		
Protection				
Surge protection		Yes		
Ground fault monitoring		Yes		
Integrated AFCI 2.0		Yes		
DC reverse-polarity protection		Yes		
Protection class / Over voltage category		I / II (PV and BAT), III (MAINS and BACKUP and GEN)		
Dados gerais				
Max. allowable phase imbalance (grid & back-up)		50%		
Dimensions (W × H × D)		390 × 620 × 237 mm		
Weight		28.3 kg		
Topology		Transformerless		
Self-consumption (night)		< 20 W		
Operating ambient temperature range		-25 ~ +60°C		
Relative humidity		0 - 100%		
Ingress protection		IP66 (TYPE 4X)		
Noise emission (typical)		< 55 dB(A)		
Cooling concept		Intelligent fan-cooling		
Max. operation altitude		4000 m		
Grid connection standard		Inmetro140, IEEE 1547		
Safety / EMC standard		IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1	IEC/EN 62109-2, UL 1741, UL 1699B, FCC	
Features				
DC connection		MC4 plug (PV port) / Terminal Block (BAT port)		
AC connection		OT terminal		
Display		7.0" LCD display & Bluetooth + APP		
Communication interface	Standard: Wi-Fi+LAN+Bluetooth	CAN-BMS, CAN-Parallelx2, RS485-Meter, RS485, DRM, DI, DOx2, Optional: 2G/3G/4G		