Exp. No. 8

Write a C program to find FOLLOW( ) - predictive parser for the given grammar

main.c

Run ▶

```c
#include<stdio.h>
#include<ctype.h>
#include<string.h>
int limit, x = 0;
char production[10][10], array[10];
void find_first(char ch);
void find_follow(char ch);
void Array_Manipulation(char ch);
int main()
{
int count;
char option, ch;
printf("\nEnter Total Number of Productions:\t");
scanf("%d", &limit);
for(count = 0; count < limit; count++)
{
printf("\nValue of Production Number [%d]:\t", count + 1);
scanf("%s", production[count]);
}
do
{
x = 0;
printf("\nEnter production Value to Find Follow:\t");
scanf(" %c", &ch);
find_follow(ch);
printf("\nFollow Value of %c:\t{ ", ch);
for(count = 0; count < x; count++)
{
printf("%c ", array[count]);

}
printf("}\n");
printf("To Continue, Press Y:\t");
scanf(" %c", &option);
}while(option == 'y' || option == 'Y');
return 0;
}
void find_follow(char ch)
{
int i, j;
int length = strlen(production[i]);
{
find_follow(production[i][0]);
}
else if(islower(production[k][2]))
{
Array_Manipulation(production[k][2]);
}
else
{
find_first(production[k][2]);
}
}
}
}
void Array_Manipulation(char ch)
{
int count;
for(count = 0; count <= x; count++)
{
if(array[count] == ch)
{
return;
}
}
array[x++] = ch;
}
```

Output

```
Enter Total Number of Productions:  4

Value of Production Number [1]: S=AaAb

Value of Production Number [2]: S=BbBa

Value of Production Number [3]: A=$

Value of Production Number [4]: B=$

Enter production Value to Find Follow:  s
Segmentation fault
```