

Exp. No. 3

Design a lexical Analyzer for given language should ignore the redundant spaces, tabs and new lines and ignore comments using C

main.c

Run ▶

Output

```
1  #include <stdio.h>
2  #include <string.h>
3  int main()
4  {
5      char ch, next;
6      printf("Enter the source code (press Ctrl+D to end):\n");
7      while ((ch = getchar()) != EOF)
8      {
9          if (ch == ' ' || ch == '\t' || ch == '\n')
10         {
11             continue;
12         }
13         if (ch == '/')
14         {
15             next = getchar();
16             if (next == '/')
17             {
18                 while ((ch = getchar()) != '\n' && ch != EOF)
19                     ;
20
21                 continue;
22             }
23
24             /* Multi-line comment */
25             else if (next == '*')
26             {
27                 while ((ch = getchar()) != EOF)
28                 {
29                     if (ch == '*')
30                     {
31                         next = getchar();
32
33                         if (next == '/')
34                             break;
35                     }
36                 }
37                 continue;
38             }
39             else
40             {
41                 putchar(ch);
42                 if (next != EOF)
43                     ungetc(next, stdin);
44             }
45         }
46         else
47         {
48             putchar(ch);
49         }
50     }
51     return 0;
52 }
```

Enter the source code (press Ctrl+D to end):
inta=10;
a=a+5;

inta=10;a=a+5;inta=10;
a=a+5;
\
inta=10;a=a+5;\