

## 切换npm 镜像源

npm config set registry <https://registry.npm.taobao.org>

```
zhaishuangMacBook-Pro:wpf_fly zhaishuang$ npm config set registry https://registry.npm.taobao.org
zhaishuangMacBook-Pro:wpf_fly zhaishuang$ npm i -g nrm
npm ERR! path ../lib/node_modules/nrm/cli.js
npm ERR! code EACCES
npm ERR! errno -13
npm ERR! syscall symlink
npm ERR! Error: EACCES: permission denied, symlink '../lib/node_modules/nrm/cli.js' -> '/usr/local/bin/nrm'
npm ERR! { Error: EACCES: permission denied, symlink '../lib/node_modules/nrm/cli.js' -> '/usr/local/bin/nrm'
  cause:
    { Error: EACCES: permission denied, symlink '../lib/node_modules/nrm/cli.js' -> '/usr/local/bin/nrm'
      errno: -13,
      code: 'EACCES',
      syscall: 'symlink',
      path: '../lib/node_modules/nrm/cli.js',
      dest: '/usr/local/bin/nrm' },
    stack: 'Error: EACCES: permission denied, symlink \'../lib/node_modules/nrm/cli.js\' -> \'
/usr/local/bin/nrm\'',
```

sudo npm i -g nrm //全局安装时必须带字段sudo

nrm ls查看镜像源，切换使用镜像源

```
-bash: nrm: command not found
zhaishuangMacBook-Pro:wpf_fly zhaishuang$ sudo npm i -g nrm
Password:
/usr/local/bin/nrm -> /usr/local/lib/node_modules/nrm/cli.js
+ nrm@1.0.2
added 328 packages in 11.869s
zhaishuangMacBook-Pro:wpf_fly zhaishuang$ nrm ls

npm ---- https://registry.npmjs.org/
cnpm --- http://r.cnpmjs.org/
* taobao - https://registry.npm.taobao.org/
nj ----- https://registry.nodejitsu.com/
rednpm - http://registry.mirror.cqupt.edu.cn/
npmMirror https://skimdb.npmjs.com/registry/
edunpm - http://registry.enpmjs.org/

zhaishuangMacBook-Pro:wpf_fly zhaishuang$ nrm use cnpm

Registry has been set to: http://r.cnpmjs.org/
zhaishuangMacBook-Pro:wpf_fly zhaishuang$ nrm -h

Usage: nrm [options] [command]
```

一般情况下taobao镜像源比较强大，建议使用

```

zhaishuangMacBook-Pro:wpf_fly zhaishuang$ nrm -h

Usage: nrm [options] [command]

Options:
  -V, --version  output the version number
  -h, --help     output usage information

Commands:
  ls              List all the registries
  current         Show current registry name
  use <registry> Change registry to registry
  add <registry> <url> [home] Add one custom registry
  del <registry>  Delete one custom registry
  home <registry> [browser]  Open the homepage of registry with optional browser
  test [registry] Show response time for specific or all registries
  help           Print this help
zhaishuangMacBook-Pro:wpf_fly zhaishuang$ sudo npm install wepy-cli -g
^C(  ) : rollbackFailedOptional: verb npm-session 2ac287a415438c
zhaishuangMacBook-Pro:wpf_fly zhaishuang$ nrm use taobao

```

## 增加本公司（安装源）镜像

```

zhaishuangMacBook-Pro:react-xplatform-boilerplate zhaishuang$ nrm ls

npm ---- https://registry.npmjs.org/
cnpm --- http://r.cnpmjs.org/
* taobao - https://registry.npm.taobao.org/
nj ----- https://registry.nodejitsu.com/
rednpm - http://registry.mirror.cqupt.edu.cn/
npmMirror https://skimdb.npmjs.com/registry/
edunpm - http://registry.enpmjs.org/

zhaishuangMacBook-Pro:react-xplatform-boilerplate zhaishuang$ nrm add zhongan http://npm.zhonganonline.com/

add registry zhongan success

zhaishuangMacBook-Pro:react-xplatform-boilerplate zhaishuang$ nrm use zhongan

Registry has been set to: http://npm.zhonganonline.com/

zhaishuangMacBook-Pro:react-xplatform-boilerplate zhaishuang$

```

## 使用nvm管理本地node版本

### 执行brew install nvm

```

zhaishuangMacBook-Pro:~ zhaishuang$ brew install nvm

```

## 配置文件修改

For other users, you have [some alternatives](#).

Start by :

```
brew update
brew install nvm
mkdir ~/.nvm
nano ~/.bash_profile
```

In your `~/.bash_profile` file (you may be using another file, according to your shell), add the following :

```
export NVM_DIR=~/.nvm
source $(brew --prefix nvm)/nvm.sh
```

vi ~/.bash\_profile 进入bash\_profile文件

i 进入编辑模式

esc退出编辑模式

:(冒号)进入最后行模式

wq保存并退出vi

最后重启nvm ls查看本地node版本

如想使用nvm use v8.9.0

nvm install v8.9.0

就可使用8.9.0版本的Node.js

## nginx切换映射地址步骤

```
Last login: Sun Mar  4 11:35:04 on console
-bash: rt: command not found
zhaishuangMacBook-Pro:~ zhaishuang$ nginx -v
-bash: nginx: command not found
zhaishuangMacBook-Pro:~ zhaishuang$ nginx
nginx: [emerg] bind() to 0.0.0.0:80 failed (13: Permission denied)
zhaishuangMacBook-Pro:~ zhaishuang$ sudo nginx
Password:
Sorry, try again.
Password:
zhaishuangMacBook-Pro:~ zhaishuang$ vi /etc/hosts
```

```
##
# Host Database
#
# localhost is used to configure the loopback interface
# when the system is booting. Do not change this entry.
##
127.0.0.1      dev.zhongan.com
127.0.0.1      localhost
255.255.255.255 broadcasthost
::1           localhost

127.0.0.1      activate.adobe.com
127.0.0.1      practivate.adobe.com
127.0.0.1      ereg.adobe.com
127.0.0.1      wip3.adobe.com
127.0.0.1      activate.wip3.adobe.com
127.0.0.1      3dns-3.adobe.com
127.0.0.1      3dns-2.adobe.com
127.0.0.1      adobe-dns.adobe.com
127.0.0.1      adobe-dns-2.adobe.com
127.0.0.1      adobe-dns-3.adobe.com
127.0.0.1      ereg.wip3.adobe.com
127.0.0.1      activate-sea.adobe.com
```

### nginx修改本地映射操作

```
Last login: Thu Mar  8 16:28:08 on ttys001
-bash: rt: command not found
[zhaishuangMacBook-Pro:~ zhaishuang$ sudo vi /etc/hosts
Password:
[zhaishuangMacBook-Pro:~ zhaishuang$ cat /etc/hosts
##
# Host Database
#
# localhost is used to configure the loopback interface
# when the system is booting. Do not change this entry.
##
127.0.0.1      dev.zhongan.com
127.0.0.1      localhost
255.255.255.255 broadcasthost
::1           localhost

127.0.0.1      tac-gw-api.zhongan.com
127.0.0.1      activate.adobe.com
127.0.0.1      practivate.adobe.com
127.0.0.1      ereg.adobe.com
127.0.0.1      wip3.adobe.com
127.0.0.1      activate.wip3.adobe.com
127.0.0.1      3dns-3.adobe.com
127.0.0.1      3dns-2.adobe.com
```

查看本地之后，直接添加本地映射地址，i 编辑模式

```

##
# Host Database
#
# localhost is used to configure the loopback interface
# when the system is booting. Do not change this entry.
##
127.0.0.1    dev.zhongan.com
127.0.0.1    localhost
255.255.255.255 broadcasthost
::1         localhost
127.0.0.1    tac-gw
127.0.0.1    tac-gw-api.zhongan.com
127.0.0.1    activate.adobe.com
127.0.0.1    practivate.adobe.com
127.0.0.1    ereg.adobe.com
127.0.0.1    wip3.adobe.com
127.0.0.1    activate.wip3.adobe.com
127.0.0.1    3dns-3.adobe.com
127.0.0.1    3dns-2.adobe.com
127.0.0.1    adobe-dns.adobe.com
127.0.0.1    adobe-dns-2.adobe.com
127.0.0.1    adobe-dns-3.adobe.com
127.0.0.1    ereg.wip3.adobe.com
-- INSERT --

```

Control +c wq 退出查看

```

zhaishuangMacBook-Pro:~ zhaishuang$ sudo vi /etc/hosts
Password:
zhaishuangMacBook-Pro:~ zhaishuang$ cat /etc/hosts
##
# Host Database
#
# localhost is used to configure the loopback interface
# when the system is booting. Do not change this entry.
##
127.0.0.1    dev.zhongan.com
127.0.0.1    localhost
255.255.255.255 broadcasthost
::1         localhost

127.0.0.1    tac-gw-api.zhongan.com
127.0.0.1    activate.adobe.com
127.0.0.1    practivate.adobe.com
127.0.0.1    ereg.adobe.com
127.0.0.1    wip3.adobe.com
127.0.0.1    activate.wip3.adobe.com
127.0.0.1    3dns-3.adobe.com
127.0.0.1    3dns-2.adobe.com

```

acttacdev.zhongan.com