The ML System Design Interview Diagram Atlas

Diagrams compiled from interview portals and engineering blogs

01. The ML System Design Interview Framework, Master Architecture, and Portal Index

- Company tags
- Requirements & scale (the template you fill in for every prompt)
- The canonical answer template (what every portal converges on)
- DIAGRAM 1: Master end-to-end architecture (online serving path)
- DIAGRAM 2: Offline training & data pipeline
- DIAGRAM 3: Model architecture (the generic two-stage model pair)
- DIAGRAM 4: The real system the template mirrors (Uber Michelangelo, 2017)
- Data & labels (generic checklist)
- Features
- Model choices (baseline -> advanced)
- Loss functions
- Offline metrics
- Online metrics & A/B testing
- Serving & latency budget (typical 200 ms p99, assumption)
- Monitoring
- Failure modes
- Interviewer follow-ups (reported or likely across portals)
- Portal comparison
- Portal and resource index (what each offers)
- References

02. Design a Video Recommendation System (YouTube Home Feed)

- Company tags
- Requirements & scale
- Diagram 1 - Online serving path
- Diagram 2 - Offline data & training pipeline
- Diagram 3 - Model architecture
- Diagram 4 - Real system: YouTube (2016 -> 2019) vs. ByteByteGo textbook
- Production details most portals omit
- Data & labels
- Features
- Model choices (baseline -> advanced)
- Loss functions
- Offline metrics
- Online metrics / A-B
- Monitoring
- Failure modes
- Interviewer follow-ups
- Portal comparison
- References

03. Design a Short-Video Feed (TikTok For You / Instagram Reels / YouTube Shorts) with Real-Time Signals

- Company tags
- Requirements & scale
- Diagram 1 - Online serving path
- Diagram 2 - Offline + streaming training pipeline
- Diagram 3 - Model architecture
- Diagram 4 - Real production system: ByteDance Monolith (real-time training)
- Often missed (vs. real systems)
- Data & labels
- Features
- Model choices (baseline -> advanced)
- Loss

Offline metrics
Online metrics / A-B
Serving & latency budget (typical, p99 ~100 ms)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

04. Design a Personalized News Feed Ranking System (Facebook / LinkedIn / Twitter Home Timeline)

Company tags
Requirements & scale
Diagram 1 - Online serving path
Diagram 2 - Offline training & data pipeline
Diagram 3 - Model architecture: multi-task heavy ranker + value model
Diagram 4 - Real system: Twitter/X "For You" (open-sourced 2023)
Data & labels
Features
Model choices (baseline -> advanced)
Loss
Offline metrics
Online metrics / A-B
Serving & latency budget (200 ms p99 target [9])
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

05. Design People You May Know (PYMK) / Friend Recommendation (Graph-Based)

Company tags
Requirements & scale
Diagram 1 - Online serving path
Diagram 2 - Offline training & data pipeline
Diagram 3 - Model architecture
Diagram 4 - Real systems: Twitter/X FRS and Snap / LinkedIn graph embeddings
Data & labels
Features
Model choices (baseline -> advanced)
Loss
Offline metrics
Online metrics / A-B
Serving & latency budget (~50 ms p99 assumption [4])
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

06. Design an Ad Click-Through-Rate Prediction and Ad Ranking System (with Auction and Calibration)

Company tags
Requirements & scale
DIAGRAM 1: online serving path
DIAGRAM 2: offline training and data pipeline
DIAGRAM 3: model architecture

DIAGRAM 4: the real system (Facebook, He et al. 2014)
Data & labels
Features
Model choices (baseline -> advanced)
Loss
Calibration
Auction and ranking score
Offline metrics
Online metrics / A-B
Serving & latency budget
Monitoring
What the production papers add (often missed in portal answers)
Failure modes
Interviewer follow-ups
Portal comparison
References

07. Design Product Search Ranking for an E-commerce Site (Amazon Search), Including Query Understanding

Company tags
Requirements & scale
DIAGRAM 1: online serving path
DIAGRAM 2: offline training and data pipeline
DIAGRAM 3: model architecture
DIAGRAM 4: the real systems this mirrors
Data & labels
Features
Model choices (baseline -> advanced)
Loss
Offline metrics
Online metrics / A-B
Serving & latency budget
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

08. Design Product Recommendations for Amazon ("Customers Also Bought" + Homepage Recs)

Company tags
Requirements & scale
Diagram 1: End-to-end architecture (online serving path)
Diagram 2: Offline training & data pipeline
Diagram 3: Model architecture
Diagram 4: Real system (Amazon item-to-item collaborative filtering)
Data & labels
Features
Model choices (baseline -> advanced)
Loss functions
Offline metrics
Online metrics / A-B
Serving & latency budget (assumption, per widget, p99)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison

References

09. Design Similar Listings and Search Ranking for Airbnb (Listing Embeddings, Two-Sided Marketplace)

Company tags
Requirements & scale
Diagram 1: End-to-end architecture (online serving path)
Diagram 2: Offline training & data pipeline
Diagram 3: Model architecture
Diagram 4: Real company system (Airbnb Journey Ranker, KDD 2023)
Data & labels
Features
Model choices (baseline -> advanced)
Loss functions
Offline metrics
Online metrics / A-B
Serving & latency budget (assumption, search, p99)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

10. Design a Visual Search / Image Similarity System (Pinterest Lens, Google Lens)

Company tags
Requirements & scale
Diagram 1: end-to-end serving architecture
Diagram 2: offline training & data pipeline
Diagram 3: model architecture
Diagram 4: the real system (Pinterest unified visual embedding)
ANN index sizing (FAISS guidance)
Data & labels
Features
Model choices (baseline -> advanced)
Loss
Offline metrics
Online metrics / A-B
Serving & latency budget (typical)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

11. Design Multimodal Video Search (YouTube Search over Text + Visual + Audio)

Company tags
Requirements & scale
DIAGRAM 1: Online serving path
DIAGRAM 2: Offline indexing, training and data pipeline
DIAGRAM 3: Model architecture
DIAGRAM 4: Variant - in-video moment search (Netflix / long-form)
Data & labels
Features
Model choices
Loss functions
Offline metrics
Online metrics & A/B

Serving & latency
Monitoring
Failure modes
What production systems add beyond the portal answer
Interviewer follow-ups
Portal comparison
References

12. Design Harmful Content Detection / Content Moderation (Facebook/Instagram Integrity)

Company tags
Requirements & scale
Diagram 1: end-to-end serving architecture
Diagram 2: offline training & data pipeline
Diagram 3: model architecture
Diagram 4: real company system (Meta integrity stack)
Data & labels
Features
Model choices (baseline -> advanced)
Loss
Offline metrics
Online metrics / A-B
Serving & latency budget
Monitoring
Failure modes
Often-missed components (portal / real-system gaps)
Interviewer follow-ups
Portal comparison
References

13. Design Event Recommendation (Eventbrite / Meetup) with Location and Time Constraints

Company tags
Requirements & scale
Diagram 1: End-to-end architecture (online serving path)
Diagram 2: Offline training & data pipeline
Diagram 3: Model architecture
Diagram 4: Variant: the geo-time candidate index
Data & labels
Features
Model choices (baseline -> advanced)
Loss functions
Offline metrics
Online metrics / A-B
Serving & latency budget (assumption, p99, ~200 ms total [4])
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

14. Design Payment Fraud Detection (Stripe Radar / PayPal) with Real-Time Scoring

Company tags
Requirements & scale
DIAGRAM 1: Online real-time scoring path
DIAGRAM 2: Offline training and data pipeline

DIAGRAM 3: Model architecture
DIAGRAM 4: Real system - Stripe Radar model evolution (as described in [1])
Data & labels
Features
Model choices
Loss
Offline metrics
Online metrics & A-B
Serving & latency budget
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

15. Design ETA / Delivery Time Prediction (Uber, DoorDash, Amazon Delivery)

Company tags
Requirements & scale
DIAGRAM 1: Online ETA serving path
DIAGRAM 2: Offline training & data pipeline
DIAGRAM 3: Model architecture
DIAGRAM 4: Variant - delivery ETA with leg heads and a distribution output
Data & labels
Features
Model choices
Loss
Offline metrics
Online metrics & A-B
Serving & latency budget
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

16. Design Email Spam / Abuse / Bot Detection (Gmail Spam Filter, Twitter/X Bots)

Company tags
Requirements & scale
Diagram 1: end-to-end serving architecture
Diagram 2: offline training & data pipeline
Diagram 3: model architecture
Diagram 4: account-level bot / fake-account detection (Twitter/X, LinkedIn, Meta)
Data & labels
Features
Model choices (baseline -> advanced)
Loss
Offline metrics
Online metrics / A-B
Serving & latency budget (email, p99 ~150 ms)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

17. Design Google Street View Face and License-Plate Blurring (Object Detection Pipeline)

Company tags
Requirements & scale
Diagram 1 - End-to-end batch "serving" path
Diagram 2 - Offline training & data pipeline
Diagram 3 - Model architecture
Diagram 4 - Variant: one-stage detector plus the 2009 Google cascade
Data & labels
Features
Model choices (baseline -> advanced)
Loss
Offline metrics
Online metrics / A-B
Serving & latency budget (per panorama, batch)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

18. Design Search Query Autocomplete / Typeahead with ML Ranking

Company tags
Requirements & scale
Diagram 1: Online serving path
Diagram 2: Offline training & data pipeline
Diagram 3: Model architecture
Diagram 4: Real-system variants
What production systems add beyond the portal answers
Data & labels
Features
Model choices
Loss
Offline metrics
Online metrics / A/B
Serving & latency budget
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

19. Design Music Recommendation and Playlist Generation (Spotify Discover Weekly and Home)

Company tags
Requirements & scale
Diagram 1: End-to-end architecture (online serving path)
Diagram 2: Offline training & data pipeline
Diagram 3: Model architecture
Diagram 4: Variant - the real Spotify systems
Data & labels
Features
Model choices (baseline -> advanced)
Loss functions
Offline metrics
Online metrics / A-B
Serving & latency budget (assumption, Home p99 about 200 ms)
Monitoring
Failure modes

Interviewer follow-ups
Portal comparison
References

20. Design an ML-Driven Push Notification / Email System (What, When, How Often)

Company tags
Requirements & scale
Diagram 1 - Online serving path
Diagram 2 - Offline training & data pipeline
Diagram 3 - Model architecture
Diagram 4 - Real-system variants
Data & labels
Features
Model choices
Loss
Offline metrics
Online metrics / A-B
Serving & latency budget
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

21. Design Dynamic Pricing (Uber Surge, Airbnb Smart Pricing, Amazon Pricing)

Company tags
Requirements & scale
Diagrams
Components often missed
Data & labels
Features
Model choices
Loss functions
Offline metrics
Online metrics & A/B
Serving & latency budget (rides, typical)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

22. Design Job Recommendation / Candidate Matching (LinkedIn Jobs, Indeed)

Company tags
Requirements & scale
Diagram 1 - Online serving path
Diagram 2 - Offline training & data pipeline
Diagram 3 - Model architecture
Diagram 4 - The real system: LinkedIn's job-recsys lineage and the LLM variant
Data & labels
Features
Model choices (baseline -> advanced)
Loss
Offline metrics
Online metrics / A-B
Serving & latency budget (~180 ms p99, typical assumption)

Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

23. Design Restaurant / Food Recommendations and Store Ranking (DoorDash, Uber Eats)

Company tags
Requirements & scale
Diagram 1: End-to-end architecture (online serving path)
Diagram 2: Offline training & data pipeline
Diagram 3: Model architecture (multi-task store ranker with graph embeddings)
Diagram 4: Real systems (Uber Eats graph learning, DoorDash explore/exploit)
Data & labels
Features
Model choices (baseline -> advanced)
Loss functions
Offline metrics
Online metrics / A-B
Serving & latency budget (assumption, p99)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

24. Design an LLM-Powered Enterprise Q&A / RAG Assistant (Chat over Company Documents)

Company tags
Requirements & scale
Diagram 1 - Online serving path (query -> retrieve -> filter -> rerank -> generate -> response)
Diagram 2 - Offline pipeline: ingestion, indexing, evaluation, feedback loop
Diagram 3 - Model architecture: bi-encoder retriever + cross-encoder reranker + LLM generator
Diagram 4 - Real system: Uber Genie "Enhanced Agentic RAG" (EAg-RAG)
Data & labels
Features / signals used in ranking and context building
Model choices (baseline -> advanced)
Loss functions
Offline metrics
Online metrics / A-B
Serving & latency budget (target under 8 s full answer, TTFT about 1.5 s; typical assumption)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

25. Design an LLM Customer-Support Agent / Contact-Center Agent-Assist (Cresta, Intercom Fin, Sierra)

Company tags
Requirements & scale
Diagram 1 - Online serving path
Diagram 2 - Offline data, training & evaluation loop
Diagram 3 - Model architecture
Diagram 4 - Variant: real-time agent-assist (Cresta / Google Agent Assist style)
Data & labels

Features / context signals
Model choices (baseline -> advanced)
Loss / objectives
Offline metrics
Online metrics / A-B
Serving & latency budget (chat, p95 ~3-5 s; typical assumption)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

26. Design an AI Code Completion / Coding Assistant (GitHub Copilot, Cursor)

Company tags
Requirements & scale
Diagram 1 - Online serving path
Diagram 2 - Offline data, training & evaluation loop
Diagram 3 - Model architecture
Diagram 4 - Variant: next-edit prediction and agentic coding (Cursor-style)
Data & labels
Features / context signals
Model choices (baseline -> advanced)
Loss / objectives
Offline metrics
Online metrics / A-B
Serving & latency budget (inline, p95 ~400 ms; typical assumption)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

27. Design a Voice Assistant / Speech Recognition Pipeline (Alexa, Siri)

Company tags
Requirements & scale
Diagram 1: End-to-end online serving path
Diagram 2: Offline training & data pipeline
Diagram 3: Model architectures
Diagram 4: Alternative - end-to-end / LLM speech assistant
Data & labels
Features
Model choices
Loss functions
Offline metrics
Online metrics / A-B
Serving & latency budget
Monitoring
Failure modes
Interviewer follow-ups
Components often missed
Portal comparison
References

28. Design a Machine Translation System (Google Translate)

Company tags
Requirements & scale
Diagram 1 - Online serving path
Diagram 2 - Offline data, training & evaluation loop

Diagram 3 - Model architecture
Diagram 4 - Variant: LLM-based translation and low-resource expansion
Data & labels
Features / inputs
Model choices (baseline -> advanced)
Loss / objectives
Offline metrics
Online metrics / A-B
Serving & latency budget (p95 ~250 ms short segment; typical assumption)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

29. Design a Document Understanding / Invoice Extraction System (OCR + Layout + LLM)

Company tags
Requirements & scale
Diagram 1 - Online serving path (ingest -> digitize -> classify -> extract -> validate -> route)
Diagram 2 - Offline training & data pipeline (corrections -> labels -> train -> eval)
Diagram 3 - Model architecture: OCR + layout transformer, and the OCR-free / LLM variant
Diagram 4 - Real system: AWS intelligent document processing (IDP) reference pipeline
Data & labels
Features / signals
Model choices (baseline -> advanced)
Loss functions
Offline metrics
Online metrics / A-B
Serving & latency budget (async, p95 under 60 s per 3-page doc; sync receipt p95 under 5 s)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

30. Design Demand Forecasting for Inventory (Amazon Supply Chain, Instacart)

Company tags
Requirements & scale
Diagram 1 - End-to-end architecture
Diagram 2 - Offline training & data pipeline
Diagram 3 - Model architecture
Diagram 4 - Variant: forecast-then-optimize vs end-to-end policy
Data & labels
Features
Model choices
Loss
Offline metrics
Online metrics / A-B
Serving & latency budget
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

31. Design Anomaly Detection for Metrics/Monitoring and Transactions

Company tags
Requirements & scale
Diagram 1: Online detection path (streaming)
Diagram 2: Offline training & data pipeline
Diagram 3: Model architecture
Diagram 4: Real-world system (ThirdEye-style monitoring + RCA)
Data & labels
Features
Model choices (baseline -> advanced)
Loss
Offline metrics
Online metrics / A-B
Serving & latency budget
Monitoring (of the detector itself)
Failure modes
Interviewer follow-ups
Portal comparison
References

32. Design Fake Review Detection and Review Ranking (Amazon, Yelp)

Company tags
Requirements & scale
Diagram 1 - Online architecture
Diagram 2 - Offline training & data pipeline
Diagram 3 - Model architecture
Diagram 4 - Real system: Xianyu GAS and review graphs
Data & labels
Features
Model choices
Loss
Offline metrics
Online metrics / A-B
Serving & latency budget
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

33. Design Semantic Search and Duplicate Question Detection (Quora, Stack Overflow)

Company tags
Requirements & scale
DIAGRAM 1: Online serving path
DIAGRAM 2: Offline training and data pipeline
DIAGRAM 3: Model architecture
DIAGRAM 4: Variant, offline duplicate mining and Quora's 2017 approach
Data & labels
Features
Model choices
Loss functions
Offline metrics
Online metrics & A/B
Serving & latency
Monitoring
Failure modes
Interviewer follow-ups

Portal comparison
References

34. Design a Text-to-Image Generation Service (Midjourney, DALL-E) with Safety and Serving

Company tags
Requirements & scale
DIAGRAM 1: Online serving path
DIAGRAM 2: Offline data and training pipeline
DIAGRAM 3: Model architecture (latent diffusion with cross-attention)
DIAGRAM 4: Alternatives (pixel cascade vs latent vs distilled)
Data & labels
Features / conditioning inputs
Model choices (baseline -> advanced)
Loss
Offline metrics
Online metrics / A-B
Serving & latency budget (4 images, 1024^2, standard mode)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

35. Design a ChatGPT-like LLM Chatbot Platform: Serving, Safety, Evaluation & Feedback Loop

Company tags
Requirements & scale
Diagram 1 - Online serving path
Diagram 2 - Offline training, evaluation & feedback loop
Diagram 3 - Model architecture
Diagram 4 - Variant: LLM inference platform internals (vLLM / DistServe style)
Data & labels
Features / context signals
Model choices (baseline -> advanced)
Loss / objectives
Offline metrics
Online metrics / A-B
Serving & latency budget (typical assumption, p95)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

36. Design an A/B Testing / Experimentation Platform for ML Models (Airbnb ERF, Netflix XP, Amazon Weblab)

Company tags
Requirements & scale
Diagrams
Data & labels
Features (unit-level covariates)
Model choices (statistical method)
Loss / objective
Offline metrics (platform health)
Online metrics / A-B
Serving & latency budget

Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

37. Design an ML Platform: Feature Store + Training + Model Serving (Uber Michelangelo, Meta FBLearner)

Company tags
Requirements & scale
Diagrams
Data & labels
Features (platform-level feature types)
Model choices (platform design choices, baseline to advanced)
Loss / objective
Offline metrics
Online metrics / A-B
Serving & latency budget
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

38. Design Exploration for Cold-Start Items and Users (Bandits) in a Recommender

Company tags
Requirements & scale
Diagram 1: End-to-end architecture (online serving path)
Diagram 2: Offline training & data pipeline
Diagram 3: Model architecture
Diagram 4: Variant - the real systems (Netflix artwork, DoorDash, Spotify BaRT)
Data & labels
Features
Model choices (baseline -> advanced)
Loss functions
Offline metrics
Online metrics / A-B
Serving & latency budget (assumption, page p99 about 200 ms)
Monitoring
Failure modes
Interviewer follow-ups
Portal comparison
References

01. The ML System Design Interview Framework, Master Architecture, and Portal Index

> Problem 01 does not ask you to design one product. It covers the reusable answer template, a generic production ML system you can adapt to any prompt, and an index of the prep portals with what each one teaches. Later chapters fill this template in for specific problems.

Company tags

Company	What is reported about the MLSD round	Source
Meta	Onsite with 1-2 ML system design rounds (E5/E6 often 2), usually ranking or recsys, e.g. news feed, Marketplace	[9] [35] [36]
Google	Design rounds at L5+ include content ranking and recommender scaling; reported prompts include YouTube recs, Gmail spam, YouTube copyright detection	[10] [33]
Amazon	Covered by IGotAnOffer as a source of real MLSD questions	[8] [11]
Apple	Has a dedicated MLE interview guide that includes ML design	[12]
OpenAI / Anthropic	Newer question banks lean toward LLM systems (e.g. "Design ChatGPT")	[13] [14] [37]
Google, LinkedIn, Snap, Coupang, Stitch Fix	Khang Pham reports MLE offers from these five; his question material draws on Facebook, Amazon, Apple, Google, Microsoft, Snap, LinkedIn interviews	[17]
LinkedIn, Airbnb, YouTube	Used as the basis for Khang Pham's case studies (LinkedIn feed ranking, Airbnb search ranking, YouTube recommendation)	[17]

Portals and books that cover the framework itself: Exponent / Aced [3][4], ByteByteGo (Aminian & Xu) [15], Educative Grokking MLSD [5] and Khang Pham's course [6][17], Hello Interview [7], IGotAnOffer [8], alirezadir/AIMLInterviews [1][2], Chip Huyen [18][19][20] [21], Patrick Halina [23], Babushkin & Kravchenko (Manning) [22], interviewing.io / Prepfully mocks [34][35], DesignGurus [38], Interview Kickstart [39].


Requirements & scale (the template you fill in for every prompt)

Dimension	What to pin down in minutes 0-8	Typical default if the interviewer stays vague
Business goal	What gets better: engagement, revenue, safety, cost	Pick one primary metric and 1-2 guardrails [1]

Dimension	What to pin down in minutes 0-8	Typical default if the interviewer stays vague
Functional	Inputs, outputs, surfaces, personalization yes/no	"Return top-K items per request" (assumption)
ML objective	Classification / regression / ranking / retrieval / generation	Pointwise P(engage) ranker (assumption)
Users	DAU, requests per user per day	100M-1B DAU for FAANG-scale prompts (assumption)
Catalog	Number of candidates	1M-10B items, so retrieval must be ANN (assumption)
QPS	Peak online requests	10k-100k QPS; Uber Michelangelo reported >250k pred/s [28]
Latency	End-to-end p99	100-200 ms total, model scoring 10-50 ms (assumption)
Freshness	How fast new items, users and features take effect	Features within minutes, retrain daily (assumption)
Data	Labels available? Logging exists? Privacy limits?	Implicit feedback from logs [1]
Constraints	Cost, on-device, interpretability, fairness, regions	Server-side GPU or CPU serving (assumption)
Is ML needed?	Heuristic baseline first	"Launch without ML is fine" (Rule #1) [31]

The canonical answer template (what every portal converges on)

DIAGRAM 0: The 45-60 minute answer flow with time budget (synthesised from [1][3][5][7][15])



Step-name mapping across portals


Generic step	ByteByteGo 7-step [15]	alirezadir 9-step [1]	Educative 6-step [5]	Chip Huyen [18]	Hello Interview [7]
Clarify	Clarifying requirements	Problem formulation	Problem scoping / clarify	Project setup	Problem framing (5-7 min)

Generic step	ByteByteGo 7-step [15]	alirezadir 9-step [1]	Educative 6-step [5]	Chip Huyen [18]	Hello Interview [7]
Frame as ML	Frame problem as ML task	Problem formulation + Metrics	Problem formulation	Project setup	Problem framing
Architecture	(inside serving)	Architectural components (MVP)	System architecture	Serving	High-level design
Data	Data preparation	Data collection & preparation	Data strategy	Data pipeline	Data & features
Features	Data preparation	Feature engineering	Data strategy	Data pipeline	Data & features
Model	Model development	Model dev & offline eval	Model design + trade-offs	Modeling	Modeling
Evaluation	Evaluation	Metrics + online testing	Offline & online eval	Modeling (debug)	Evaluation
Serving	Deployment & serving	Prediction service + deployment	Deploy under constraints	Serving	Inference
Monitoring	Monitoring & infrastructure	Scaling, monitoring, updates	Monitoring & iteration	Serving (maintain)	Deep dives

- The ByteByteGo labels come from the book's Chapter 1 framework. The other columns paraphrase the cited pages.
- alirezadir orders the steps differently: metrics come 2nd and the MVP architecture 3rd, before any data work, so the interviewer sees the whole box diagram early [1].
- Hello Interview says its steps are "guideposts, not hard rules": if the interviewer pulls you off course, follow them [7].

DIAGRAM 1: Master end-to-end architecture (online serving path)

DIAGRAM 1: Generic production ML system, online path (retrieval -> filter -> rank -> re-rank) [1][27][28]



[DIAGRAM 2]

DIAGRAM 2: Offline training & data pipeline

DIAGRAM 2: Offline data -> features -> training -> evaluation -> registry -> deploy loop [1][28][29][30]





DIAGRAM 3: Model architecture (the generic two-stage model pair)


DIAGRAM 3: Two-tower retriever + multi-task ranker, the default answer for recsys, feed, ads and search prompts [27]



Problem family	Swap DIAGRAM 3 for	Output
Recsys / feed / ads / search	two-tower + multi-task ranker (above)	ranked list
Moderation / fraud / spam	multimodal encoder + classifier heads	P(violation) per policy
Visual / semantic search	image or text encoder + ANN (single tower)	top-K neighbors
ETA / pricing / forecasting	GBDT or DNN regressor	continuous value
RAG / LLM assistant	retriever + reranker + LLM generator	grounded text

DIAGRAM 4: The real system the template mirrors (Uber Michelangelo, 2017)

DIAGRAM 4: Michelangelo's 6-step workflow and online/offline split, the canonical public reference for the "master diagram" [28]



- Other public platforms with the same shape: Google TFX (data validation -> trainer -> model validation -> serving, used for Google Play) [29], Meta FBLearner Flow (workflows, feature store marketplace, per-model inference containers) [32].
- Sculley et al. explain why the diagram is mostly not the model: glue code, data dependencies, hidden feedback loops and configuration debt [30].

Data & labels (generic checklist)

Item	Options	Interview tip
Label source	Natural (click, purchase), explicit feedback, human annotation, programmatic/weak, transfer learning, active learning [1]	Say which label you use and why it matches the business goal
Positives / negatives	Engaged vs impressed-not-engaged; random or hard negatives for retrieval	Do not use non-impressed items as negatives in a ranker
Label delay	Conversions arrive late; spam reports late	Use attribution windows and delayed-feedback correction

Item	Options	Interview tip
Bias	Position bias, exposure bias, selection bias	Log position, use exploration traffic, IPS weighting
Split	Time-based train/val/test; no user leakage	Random splits leak the future
Imbalance	Downsample negatives, class weights, focal loss	Recalibrate after downsampling
Privacy	PII, consent, regional retention; human annotation exposes data [1]	Mention it as a constraint; weak labels or on-device reduce exposure [1]

Features

Group	Examples	Freshness / store
User	demographics, locale, long-term interests, embeddings	Batch daily, online KV
Item	category, text/image embeddings, age, quality score	Batch on create/update
Context	time, device, surface, session state	Request time
User-item cross	past interactions with author/category, similarity	Streaming (minutes)
Aggregates / counters	CTR over 1h/1d/7d windows, popularity	Streaming + batch backfill
Representations	one-hot, hashing, learned embeddings, normalization, bucketization [1]	Shared feature store [28]
Training-serving skew	log features at serve time; same transform code	Rule: reuse code offline and online [31]

Model choices (baseline -> advanced)

Stage	Option	Pros	Cons
0	Heuristic / popularity / rules	Ships in days, strong baseline	No personalization [31]
1	Logistic regression + crosses	Fast, calibrated, interpretable	Manual feature crosses
2	GBDT (XGBoost/LightGBM)	Strong on tabular data, little tuning	Weak on sparse IDs and raw text/images
3	Two-tower DNN (retrieval)	Scales to billions of items with ANN	No late user-item interaction
4	Deep ranker (DCN, DLRM, attention over history)	Learns interactions, uses embeddings	GPU cost, latency
5	Multi-task / MMoE	One model, several objectives	Tuning the task weights
6	Pretrained / LLM components	Cold-start, semantics	Cost, latency, hallucination

Loss functions

Task	Loss
Binary engagement / classification	Binary cross-entropy (weighted or focal for imbalance)
Multi-class / policy labels	Softmax CE, or multi-label sigmoid BCE
Retrieval embeddings	Sampled softmax with in-batch negatives, contrastive, triplet

Task	Loss
Learning to rank	Pairwise (RankNet, BPR), listwise (LambdaRank, softmax)
Regression (ETA, dwell)	MSE, MAE, Huber, quantile loss for intervals
Multi-task	Weighted sum of per-head losses

Offline metrics

Task	Metrics
Classification	ROC-AUC, PR-AUC, precision/recall@threshold, log loss, calibration (ECE)
Retrieval	Recall@K, hit rate@K
Ranking	NDCG@K, MAP, MRR
Regression	MAE, RMSE, MAPE
System	p50/p99 latency, throughput, cost per 1k predictions [1]
Always	Slice metrics: new users, regions, cold items, protected groups

Online metrics & A/B testing

Item	Generic answer
Primary metric	CTR, session time, conversion, revenue, task success [1]
Counter metrics	direct negative feedback: hides, reports [1]
Guardrail metrics	unsubscribes, latency, crash rate (assumption)
Rollout	shadow -> canary -> A/B with control/test split and null hypothesis [1]; ramp 1% -> 5% -> 50% -> full (assumption)
Alternatives	multi-armed bandits [1]; interleaving for ranking (assumption)
Pitfalls	novelty effect, network effects, sample-ratio mismatch, peeking
Decision	ship if primary is significantly up and guardrails are flat

Serving & latency budget (typical 200 ms p99, assumption)

Component	Budget	Technique
Gateway + auth	10 ms	
Feature fetch	10-20 ms	KV store, batched multi-get, caching
Retrieval (ANN, several sources)	20-30 ms	HNSW / IVF-PQ, parallel fan-out
Filtering	5 ms	Bloom filters for already-seen items
Ranking ~500 candidates	30-60 ms	GPU batching; compression: quantization, pruning, distillation, factorization [1]
Re-rank / policy	5-10 ms	Rule engine, MMR diversity
Slack / network	50 ms	Timeout falls back to cached or popular results

Component	Budget	Technique
Mode choice	batch / online / hybrid / on-device [1]	Precompute for stable users, online for context; on-device when memory, compute, energy or privacy dominate [1]

Monitoring

Layer	What to watch	Action
System	QPS, p99 latency, errors, GPU utilization	Autoscale, alert
Data	Missing or null features, schema changes, feature drift (PSI/KL)	Data validation gate [29]
Model	Prediction distribution, calibration, online AUC once labels arrive	Roll back to the previous registry version
Business	Primary KPI, guardrails, per-slice metrics	Experiment review
Retraining	Scheduled (daily/weekly) or triggered by drift	Continual training [1]

Failure modes

Failure	Symptom	Mitigation
Training-serving skew	Offline AUC up, online flat	Log features at serve time, share transform code [31]
Feedback loop	Popular items get more popular	Exploration slot, debiasing [30]
Label leakage	Offline metrics too good	Point-in-time joins, time-based splits
Cold start	New users or items get no exposure	Content features, popularity priors, explore
Data drift / seasonality	Gradual metric decay	Drift alerts, frequent retraining
Stale features / pipeline outage	Sudden drop in metrics	Freshness SLAs, default values, fallback model
Optimizing a proxy	CTR up, satisfaction down (clickbait)	Multi-objective value model, guardrails
Latency blow-up	Timeouts at peak	Candidate caps, distillation, fallbacks

Interviewer follow-ups (reported or likely across portals)

- Why ML at all? What heuristic baseline would you launch first? [31]
- How exactly do you turn the business goal into a training label and loss? [1][15]
- Which offline metric correlates with your online metric, and what if they disagree?
- How do you build negatives, and how do you handle class imbalance?
- How do you avoid data leakage when you join labels and features?
- How do you handle position bias and the feedback loop created by your own recommendations?
- Cold start for new users and new items?
- Walk through the latency budget. What do you cut if p99 doubles?
- Batch vs online prediction: which features are precomputed and which are real-time?
- How do you design the A/B test? Which guardrails? How long do you run it? [8]

- How do you detect performance drift after deployment, and when do you retrain? [8]
- How would the design change at 10x scale, or on-device?
- The model is too big for the latency or device budget: quantize, prune, distill or factorize? [1]
- Which predictions are batch-precomputed, which online, and why not hybrid? [1]
- Real labels are scarce: weak supervision, transfer learning or active learning? [1]
- Fairness, privacy and policy constraints: where do they enter the pipeline?
- What would you build next with another quarter?
- (GenAI rounds) How would the design change if an LLM generates the output? [14]

Portal comparison

Portal / resource	Steps	Signature emphasis	Format	Notes
ByteByteGo, Aminian & Xu (2023) [15]	7	Problem -> ML task framing; 10 case studies with 211 diagrams	Book + online course	Blind reviewers call the framework decent but some find it shallow [25]
alirezadir AIMLInterviews [1][2]	9	Most granular checklist; MVP architecture as its own step; bandits, shadow and canary rollouts	Free GitHub	Updated for GenAI and agentic design in 2026 [2]
Educative Grokking MLSD [5]	6	Clarify -> data strategy -> model -> offline/online eval -> deploy -> monitor; fraud detection as the running example	Paid course, mock interviews	Separate Khang Pham course: feed, ads, Airbnb search [6][17]
Exponent / Aced [3][4]	6	Treats the interview as "convincing the team to launch"; rubric module	Course + video mocks	Time budgets per step (~8 min to define the problem) [3]
Hello Interview [7]	5-6	Timed delivery; problem framing 5-7 min; deep dives driven by the interviewer	Free guide + paid mocks	Steps are guideposts, not hard rules [7]
Chip Huyen [18] [19][21]	4	Project setup -> data -> modeling -> serving; 27 open questions; production MLOps depth	Free booklet, O'Reilly book, Stanford CS 329S	The ml-interviews-book points to a separate resource for design [19]
Patrick Halina [23]	~5	Compact; heavy stress on clarifying first	Free blog	Blind calls it one of the best compact resources [24]
Babushkin & Kravchenko (Manning, 2025) [22]	16 chapters	Design-doc-driven: problem -> research -> loss/metrics -> baseline -> error analysis	Book	Closer to real industry design docs than interview scripts

Portal and resource index (what each offers)

#	Resource	Type	Offers
1	alirezadir/AIMLInterviews MLSD template [1][2]	GitHub (free)	9-step template, classic + GenAI + agentic design, MCP-based AI tutor
2	ByteByteGo "ML System Design Interview" [15]	Book / course	7-step framework; visual search, YouTube video search, harmful content, video recs, news feed, People You May Know, and more

#	Resource	Type	Offers
3	Educative Grokking the ML System Design Interview [5]	Course	6-step framework, fraud detection mock, RAG knowledge assistant case
4	Educative / Khang Pham ML System Design [6][16][17]	Course + book (2022)	YouTube recs, LinkedIn feed, ad click, delivery ETA, Airbnb search
5	Exponent / Aced ML System Design [3][4]	Course + mocks	Rubric, data pipeline, model selection, evaluation, deployment modules
6	Hello Interview ML System Design [7]	Guide + mocks	Timed delivery framework, worked problems
7	IGotAnOffer [8]-[14]	Articles + coaching	Company-specific MLE guides (Meta, Google, Amazon, Apple, OpenAI), GenAI design
8	Chip Huyen [18]-[21]	Free booklet + book + course	Booklet (2019), 27 questions, DMLS book (O'Reilly 2022), CS 329S
9	Patrick Halina [23]	Blog	Compact MLSD interview guide
10	Babushkin & Kravchenko [22][41]	Book (Manning 2025)	16-chapter design-doc method
11	interviewing.io [34], Prepfully [35]	Mock marketplaces	Anonymous mocks with FAANG ML engineers
12	InterviewQuery [33]	Question bank	Company MLE guides (e.g. Google)
13	DesignGurus Grokking series [38]	Courses	Grokking the AI System Design Interview
14	Interview Kickstart [39], Codemia [36]	Guides	Framework write-ups, company guides
15	LeetCode Discuss framework post [26], Blind threads [24] [25]	Community	Candidate frameworks, resource reviews
16	Eugene Yan, "System Design for RecSys & Search" [27]	Blog	Offline/online x retrieval/ranking 2x2
17	Engineer1999 curated case studies [40]	GitHub	300+ case studies from 80+ company blogs
18	Google Rules of ML [31], Sculley 2015 [30], TFX [29]	Papers / guides	Production best practices and the reference platform

References

1. alirezadir, "ML System Design" template (src/MLSD/ml-system-design.md), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md
2. alirezadir, "AIMLInterviews (formerly Machine-Learning-Interviews)" README, GitHub, 2026. https://github.com/alirezadir/Machine-Learning-Interviews
3. Aced (formerly Exponent), "Machine Learning System Design Interview (2026 Guide)", aced.io, 2026. https://www.aced.io/blog/machine-learning-system-design-interview-guide
4. Exponent, "Introduction to the ML System Design Interview" (course), tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro

5. Educative, "The 6-step ML SD framework" (Grokking the ML System Design Interview), educative.io, 2025. https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/the-6-step-ml-sd-framework
6. Educative / Khang Pham, "Machine Learning System Design" (course), educative.io, 2021. https://educative.io/courses/machine-learning-system-design/introduction
7. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery
8. IGotAnOffer, "Machine Learning (ML) System Design Interview (examples, answers, prep)", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/machine-learning-system-design-interview
9. IGotAnOffer, "Meta Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/facebook-machine-learning-engineer-interview
10. IGotAnOffer, "Google Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/google-machine-learning-engineer-interview
11. IGotAnOffer, "Amazon Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/amazon-machine-learning-engineer-interview
12. IGotAnOffer, "Apple Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/apple-machine-learning-engineer-interview
13. IGotAnOffer, "OpenAI System Design Interviews", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/openai-system-design-interview
14. IGotAnOffer, "Generative AI System Design Interview", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/generative-ai-system-design-interview
15. A. Aminian & A. Xu, "Machine Learning System Design Interview: An Insider's Guide" (ByteByteGo), library record, 2023. https://library.bracu.ac.bd/vufind/Record/47626 (book overview: https://opencourser.com/book/xop33f/machine-learning-system-design-interview)
16. K. Pham, "Machine Learning Design Interview", Goodreads, 2022. https://www.goodreads.com/book/show/61098541-machine-learning-design-interview
17. khangich, "machine-learning-interview", GitHub, 2021. https://github.com/khangich/machine-learning-interview
18. C. Huyen, "machine-learning-systems-design" booklet, GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design
19. C. Huyen, "Introduction to Machine Learning Interviews Book", huyenchip.com, 2021. https://huyenchip.com/ml-interviews-book/
20. C. Huyen, "Machine Learning Systems Design" table of contents, huyenchip.com, 2019. https://huyenchip.com/machine-learning-systems-design/toc.html
21. DataTalks.Club, "Designing Machine Learning Systems" (C. Huyen, O'Reilly) book of the week, 2022. https://datatalks.club/books/20220627-designing-machine-learning-systems.html
22. V. Babushkin & A. Kravchenko, "Machine Learning System Design", Manning, 2025. https://manning.com/books/machine-learning-system-design
23. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2020. http://patrickhalina.com/posts/ml-systems-design-interview-guide/
24. Blind, "MLE interview preparation that led to successful offers", teamblind.com, 2023. https://www.teamblind.com/post/mle-interview-preparation-that-led-to-successful-offers-3k2az8d8

25. Blind, "Resources for ML system design for interviews", teamblind.com, 2024. https://www.teamblind.com/post/resources-for-ml-system-design-for-interviews-51wa76zv
26. LeetCode Discuss, "Machine Learning System Design: A framework for the interview day", leetcode.com, 2020. https://leetcode.com/discuss/interview-question/system-design/566057/machine-learning-system-design-a-framework-for-the-interview-day
27. E. Yan, "System Design for Recommendations and Search", eugeneyan.com, 2021. https://eugeneyan.com/writing/system-design-for-discovery/
28. Uber Engineering, "Meet Michelangelo: Uber's Machine Learning Platform", uber.com, 2017. https://www.uber.com/en-DE/blog/michelangelo-machine-learning-platform/
29. D. Baylor et al., "TFX: A TensorFlow-Based Production-Scale Machine Learning Platform", KDD / Google Research, 2017. https://research.google/pubs/tfx-a-tensorflow-based-production-scale-machine-learning-platform/
30. D. Sculley et al., "Hidden Technical Debt in Machine Learning Systems", NeurIPS, 2015. https://proceedings.neurips.cc/paper/2015/file/86df7dcfd896fcaf2674f757a2463eba-Paper.pdf
31. M. Zinkevich, "Rules of Machine Learning: Best Practices for ML Engineering", Google Developers, 2017. https://developers.google.com/machine-learning/guides/rules-of-ml/
32. ZenML MLOps Database, "Meta FBLearner: Introducing FBLearner Flow, Facebook's AI backbone", zenml.io, 2016 (summary). https://www.zenml.io/mlops-database/meta-fblearner-introducing-fblearner-flow-facebooks-ai-backbone
33. InterviewQuery, "Google Machine Learning Engineer Interview Questions + Guide", interviewquery.com, 2024. https://interviewquery.com/interview-guides/google-machine-learning-interview-questions
34. interviewing.io, home page (anonymous mock interviews including ML system design), 2025. https://www.interviewing.io
35. Prepfully, "Meta Machine Learning Engineer interview questions", prepfully.com, 2025. https://prepfully.com/interview-questions/meta/machine-learning-engineer?page=8
36. Codemia, "Meta Machine Learning Engineer guide", codemia.io, 2025. https://codemia.io/guides/meta-machine-learning-engineer
37. PracHub, "ML System Design Interview Questions", prachub.com, 2026. https://prachub.com/categories/ml-system-design?page=20
38. DesignGurus, "The Grokking series", designgurus.io, 2025. https://www.designgurus.io/grokking
39. Interview Kickstart, "The Ultimate Machine Learning System Design Interview Guide (2026)", interviewkickstart.com, 2026. https://interviewkickstart.com/blogs/articles/machine-learning-system-design-interview-guide
40. Engineer1999, "A Curated List of ML System Design Case Studies", GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies
41. ML-SystemDesign, "MLSystemDesign BookOutline.md", GitHub, 2024. https://github.com/ML-SystemDesign/MLSystemDesign/blob/main/BookOutline.md

02. Design a Video Recommendation System (YouTube Home Feed)

> Prompt as usually given: "Design the ML system that fills the YouTube home page with personalized videos for each logged-in user." Variants: "watch next", Reels/Shorts/TikTok short-video feed, Netflix-style rows.

Company tags

Company (reported)	Where it was reported	Notes
Google / YouTube	interviewing.io mock [6], Blind [13]	ML SWE loop; follow-ups on RNN serving throughput and monitoring [13]
Meta	Blind [12][14], LeetCode Discuss [15], Hello Interview community [8]	Rec/ranking is the standard Meta ML-design round; Reels/TikTok-style variant [8]
Coupang	1point3acres [16]	"YouTube recommendation, from metrics to pipeline"
TikTok / ByteDance	Codemia [17], Hello Interview [8], Jointaro [27]	Short-video variant; real-time training (Monolith) [24]
Netflix-style variant (practice framing, not a reported loop)	Chip Huyen exercises [29], AIMLInterviews [10]	Rows/titles; "when does a user stop watching a show"

Portals that cover it

Portal	Treatment	Link
ByteByteGo (Aminian & Xu, MLSDI ch. 6)	Full chapter, hybrid filtering, multi-source candidate gen; newsletter deep dive	[1][2]
Educative "Grokking the ML System Design Interview"	5-lesson case study (framing, data, retrieval, ranking, serving)	[3][4][5]
interviewing.io	Google mock, 2B users / 10B videos / < 1 s	[6]
Hello Interview	Recsys pattern page + TikTok community question	[7][8]
alirezadir AIMLInterviews (GitHub)	Free full write-up, mirrors ByteByteGo structure	[9][10]
khangich machine-learning-interview (Khang Pham)	"YouTube Recommendation" listed as design #1	[11]
Exponent	MLSD course (model selection; related YouTube-ads question)	[28]
Codemia, AlgoMaster, Jointaro, techinterview.org	Practice prompts / guides	[17][18][31] [27][26]

Requirements & scale

Dimension	Value	Source
Surface	Home page, logged-in user, no query	[1][10]

Dimension	Value	Source
Business goal	Engagement (watch time, completed views) + satisfaction (likes, surveys)	[1][20][22]
Relevance label	Explicit like OR watched >= ~50% of video	[10]
Users	2B users (interviewing.io); 100M DAU (AIMLInterviews)	[6][10]
Catalog	10B videos (interviewing.io); 100M (AIMLInterviews); "tens of millions" in YouTube retrieval paper	[6][10][21]
End-to-end latency	~200 ms (AIMLInterviews); < 1 s (interviewing.io)	[10][6]
Retrieval budget	< 10 ms over > 1B videos to a few hundred	[4]
Peak QPS	~2B DAU x ~10 home loads/day / 86,400 x 3 peak ~ 700k QPS	typical assumption
Candidates per stage	~1e9 -> ~1e3 (retrieval) -> ~1e2 (ranking) -> ~20-50 shown	[19] + typical
Signals	"> 80 billion signals" (YouTube)	[23]
Freshness	New uploads recommendable within minutes-hours	typical assumption
Non-functional	Diversity, safety/policy, cold start, multilingual, fairness	[10][7]

Diagram 1 - Online serving path

Figure 2.1 - End-to-end home-feed serving (multi-stage funnel)



Latency budget (target p99 ~200 ms server-side) [10]

Step	Budget	Notes
Gateway + feature fetch	15-25 ms	Online KV store, batched multi-get
Candidate generation	10-30 ms	Parallel sources; ANN < 10 ms [4]
Filtering	~5 ms	Bloom filter of watched ids
Light ranker	10-20 ms	~1k items, CPU
Heavy ranker	40-80 ms	~200 items, GPU/TPU batched
Re-rank + policy	~10 ms	Greedy diversification
Logging	async	Never on critical path

Diagram 2 - Offline data & training pipeline

Figure 2.2 - Logging -> labels -> features -> training -> registry -> deployment




Diagram 3 - Model architecture

Figure 2.3a - Retrieval: two-tower with sampled softmax (logQ correction) [19][21]




Figure 2.3b - Ranking: multi-task MMoE + shallow position-bias tower [20]





Diagram 4 - Real system: YouTube (2016 -> 2019) vs. ByteByteGo textbook

Figure 2.4 - How the reference solutions map to YouTube's published system [19] [20][21][25]



Production details most portals omit

Detail (YouTube)	Why it matters in the interview	Source
Train candidate gen on all watches, incl. embedded/off-surface plays, not only rec impressions	Surfaces new content; avoids learning only from the recommender's own exposure	[19]
Fixed number of training examples per user	Stops heavy users dominating the loss	[19]
Predict the *next* watch from past history (no future context), not a random held-out watch	Avoids label leakage; matches asymmetric co-watch behaviour	[19]
`example_age` feature, set to 0 at serving	Lets the model learn the freshness preference instead of stale averages	[19]
Streaming item-frequency estimation (hashed arrays) feeding logQ	In-batch negatives over-penalise popular items without it	[21]
Ranker trained continuously on streaming logs; shallow tower for selection/position bias	Implicit feedback is biased by what was shown and where	[20]
User surveys ("valued watch time"), borderline-content demotion	Watch time alone is not satisfaction; responsibility guardrail	[22]

Data & labels

Label / signal	Definition	Use	Pitfall
Click	Impression -> play	Ranker head	Clickbait; position bias
Watch time	Seconds watched (or fraction)	Ranker head; wLR weight [19]	Biased toward long videos
Completed / >50% watched	Binary relevance	Retrieval + ranker positive [10]	Short videos inflate
Like / share / subscribe	Explicit positive	Satisfaction head	Sparse
Dismiss / "not interested" / dislike	Explicit negative	Negative head	Sparse, high value

Label / signal	Definition	Use	Pitfall
Survey ("was this worth your time?")	Satisfaction	Satisfaction head [22]	Very sparse, needs weighting
Implicit negative	Shown, not clicked	Ranker negatives	Not a true negative [9]
Random negatives	Sampled from corpus	Retrieval negatives	Needs logQ correction [21]

Features

Group	Examples	Encoding
User	id, age, gender, geo, language, device	Embeddings / one-hot / bucketize [10]
User history	last N watched ids, search tokens, liked channels	Avg pooling or sequence model (Transformer/GRU)
Video	id, channel, topic, tags, duration, upload age, language	Embeddings; BERT for title/desc; CBOW for tags [10]
Video content	frame / audio embeddings	Pretrained encoders (cold start)
Video stats	views, CTR, avg watch % (1h/1d/7d windows)	log-normalize; streaming counters
Cross	user watched this channel?, #times this video shown to user, time since last watch of channel	Numeric; strongest ranking features [19]
Context	time of day, day of week, device, network	One-hot / embeddings
Freshness	example_age (training), 0 at serving	Numeric [19]

Model choices (baseline -> advanced)

Stage	Baseline	Better	Advanced	Tradeoff
Retrieval	Popular/trending by region	Matrix factorization (WALS)	Two-tower DNN + ANN [1][10]	MF: fast, no side features, cold start fails; two-tower: features, cold-start users, costlier [10]
Retrieval (alt)	Item-item co-watch	Graph / sequence (next-video)	Generative/semantic-ID retrieval	Coverage vs. freshness
Ranking	Logistic regression / GBDT	Wide & Deep, DCN [5]	MMoE / PLE multi-task [20]	Capacity vs latency; negative transfer between tasks
Re-rank	Rules (dedup, caps)	MMR diversity	Slate/RL optimization, bandit explore	Engagement vs. diversity
Cold start	Popular in locale	Content-tower embeddings	Explore budget / bandits [10]	Short-term loss vs. learning

Loss functions

Model	Loss
Two-tower retrieval	Sampled / in-batch softmax CE with logQ correction [21]; alternative: BCE with random negatives
2016 candidate gen	Sampled softmax over millions of classes (+ importance weighting) [19]
2016 ranker	Weighted logistic regression (positives weighted by watch time) [19]
Multi-task ranker	Sum_k lambda_k * L_k: BCE for click/like/dismiss, regression or wLR for watch time [20]
Position bias	Shallow tower logit added in training, removed at serving [20]

Offline metrics

Stage	Metric
Retrieval	Recall@k (k=100..1000), hit rate of next watch, coverage
Ranking	AUC / log-loss per head, nDCG@k, mAP, Precision@k [9][10]
List	Diversity (intra-list distance), novelty, freshness share
Slices	New users, new videos, languages, regions, devices
Counterfactual	IPS / off-policy estimates on logged random traffic

Online metrics / A-B

Type	Metric
Primary	Total watch time per user/day, # completed videos [10]
Engagement	CTR, sessions/day, session length
Satisfaction	Likes, survey score, dismiss rate, dislikes (guardrail) [20][22]
Long-term	D7/D28 retention, return visits (holdouts for weeks)
Guardrails	Latency p99, borderline/harmful exposure, creator diversity
Method	User-randomized A/B, interleaving for rankers, long-term holdbacks

Monitoring

What	How
Feature drift / missing features	Per-feature null rate, PSI vs. training distribution
Train/serve skew	Log served features; compare to offline recompute
Prediction calibration	Predicted vs. observed CTR per bucket and slice
Business KPIs	Watch time, CTR, dismiss rate dashboards with alerting
Index freshness	Age of ANN index, % of new uploads retrievable
Infra	QPS, p50/p99 latency per stage, timeouts -> fallback to cache/popular

Failure modes

Failure	Symptom	Mitigation
Clickbait	CTR up, watch time / satisfaction down	Optimize watch + satisfaction, not clicks [1][10]
Feedback loop / filter bubble	Narrowing topics, popularity bias	Explore slots, diversity re-rank, logQ correction [21]
Position bias	Top slots over-learned	Shallow bias tower [20], randomization data
Cold start (new video)	Never surfaced	Content embeddings, fresh-upload candidate source, explore
Cold start (new user)	Generic feed	Demographic/context features in user tower, onboarding topics
Long-video bias	Watch-time objective favors long videos	Normalize by duration, completion-rate labels [10]
Stale model	Trends missed	Hourly warm-start / online training [24]
Harmful/borderline content	Policy risk	Classifier demotion in re-rank stage [10][22]

Interviewer follow-ups

- Why not just optimize CTR? What happens to clickbait, and how do you define "relevant"? [1][10]
- Watch time vs. completion vs. satisfaction: how do you combine heads into one score, and who sets the weights? [20]
- Matrix factorization vs. two-tower: when is MF enough? How does each handle new users? [10]
- How do you choose negatives for the two-tower, and why is in-batch sampling biased? [21]
- Why hold out the *next* watch instead of a random watch, and why cap examples per user? [19]
- How do you serve retrieval in < 10 ms over 1B videos (ANN choice, sharding, index refresh)? [4]
- How do you handle cold start for a video uploaded 5 minutes ago? [10][18]
- How do you correct for position and selection bias in logged training data? [20]
- How would you optimize prediction throughput if the user model is an RNN/Transformer? [13]
- How do you monitor the system and detect a silent quality regression? [13]
- How do you ensure diversity and avoid filter bubbles without hurting watch time?
- Offline AUC went up but online watch time went down - why? (skew, proxy-metric mismatch)
- How fresh does the model need to be? Batch daily vs. hourly vs. online training [24]
- Videos vs. ads on the same surface: how would scope change the design? [12]
- How do you evaluate long-term effects (retention) vs. short-term A/B wins?
- How would you adapt this to Shorts/Reels/TikTok (no click, swipe-based feedback)? [8][30]

Portal comparison

Portal	Objective / label	Candidate generation	Ranking	Distinctive emphasis
ByteByteGo (Aminian & Xu) [1]	Relevance = like or partial watch; warns against pure clicks	Multiple sources incl. two-tower, popular, trending	Heavier model on fewer candidates	Clean 3-stage funnel, MF vs. two-tower tradeoff
AIMLInterviews (alirezadir) [10]	Like or >=50% watched	CF two-tower chosen over MF; popularity + trending	FFN or DCN; multi-task option	Free; detailed feature encoding table, re-rank rules
Educative Grokking [3] [4][5]	Engagement vs. satisfaction conflict	Two-tower + contrastive negatives + ANN (<10 ms, >1B videos)	Wide & Deep / DCN, re-ranking lesson	Retrieval latency/recall/index-freshness tradeoffs
interviewing.io (Google mock) [6]	Maximize engagement	Two-stage, 2B users / 10B videos	Ranking stage within < 1 s	Real interviewer pressure, scale reasoning
Hello Interview [7] [8]	Watch time vs. satisfaction	Retrieval stage, CF vs. content, embeddings	Two-stage pattern	Pattern-based reuse across rec problems; TikTok variant
YouTube papers [19] [20][21]	Expected watch time -> multi-objective	Softmax -> two-tower w/ logQ	wLR -> MMoE + bias tower	The production ground truth all portals mirror

References

1. "Video Recommendation System" (Machine Learning System Design Interview, ch. 6, A. Aminian & A. Xu), ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/video-recommendation-system
2. "How Video Recommendations Work - Part 1", ByteByteGo Newsletter, 2024. https://blog.bytebytego.com/p/how-video-recommendations-work-part
3. "Video Recommendation: Problem Framing and Requirements", Educative (Grokking the ML System Design Interview), 2025. https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/video-recommendation-problem-framing-and-requirements
4. "Video Recommendation: Candidate Retrieval Architecture", Educative, 2025. https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/video-recommendation-candidate-retrieval-architecture
5. "Neural Architectures for Ranking and Retrieval", Educative, 2025. https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/neural-architectures-for-ranking-and-retrieval
6. "Google System Design Mock: YouTube Recommendation System", interviewing.io, n.d. https://interviewing.io/mocks/google-system-design-youtube-recommendation-system
7. "Recommendation Systems (ML System Design pattern)", Hello Interview, 2025. https://www.hellointerview.com/learn/ml-system-design/patterns/recommendation-systems
8. "Design TikTok Video Recommendation System" (community question), Hello Interview, 2025. https://www.hellointerview.com/community/questions/tiktok-video-recommendation/cmgzuubzb02eq08adu99oof84
9. "ML System Design" guide, alirezadir/Machine-Learning-Interviews, GitHub, 2023. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md

10. "Video/Movie Recommendation" case study, alirezadir/AIMLInterviews, GitHub, 2023. https://github.com/alirezadir/AIMLInterviews/blob/main/src/MLSD/mlsd-video-recom.md
11. "machine-learning-interview" (Khang Pham), GitHub, 2021. https://github.com/khangich/machine-learning-interview
12. "Got asked how to design YouTube recommendation system", Blind, n.d. https://www.teamblind.com/post/got-asked-how-to-design-youtube-recommendation-system-hdao6bge
13. "Google ML SWE interview - ML design question", Blind, n.d. https://www.teamblind.com/post/google-ml-swe-interview-ml-design-question-tokqydu7
14. "Meta - help for ML design round feedback", Blind, n.d. https://www.teamblind.com/post/meta-help-for-ml-design-round-feedback-nrxobup2
15. "Meta E4 Seattle Dec 2021 [Offer]", LeetCode Discuss, 2021. https://leetcode.com/discuss/interview-experience/1727566/meta-e4-seattle-dec-2021-offer
16. "Coupang Machine Learning Engineer Interview: YouTube Recommendation System Design", 1point3acres, n.d. https://www.1point3acres.com/interview/thread/1087366
17. "Design an ML pipeline for video recommendation", Codemia, 2025-2026. https://codemia.io/practice/design-an-ml-pipeline-for-video-recommendation
18. "Design a YouTube Recommendation System", Codemia, n.d. https://codemia.io/practice/design-a-youtube-recommendation-system
19. P. Covington, J. Adams, E. Sargin, "Deep Neural Networks for YouTube Recommendations", RecSys / Google Research, 2016. https://research.google/pubs/pub45530/ (PDF: https://storage.googleapis.com/pub-tools-public-publication-data/pdf/45530.pdf)
20. Z. Zhao, L. Hong, et al., "Recommending What Video to Watch Next: A Multitask Ranking System", RecSys / Google Research, 2019. https://research.google/pubs/recommending-what-video-to-watch-next-a-multitask-ranking-system/
21. X. Yi, J. Yang, L. Hong, et al., "Sampling-Bias-Corrected Neural Modeling for Large Corpus Item Recommendations", RecSys / Google Research, 2019. https://research.google/pubs/sampling-bias-corrected-neural-modeling-for-large-corpus-item-recommendations/
22. "On YouTube's recommendation system", YouTube Official Blog, 2021. https://blog.youtube/inside-youtube/on-youtubes-recommendation-system/
23. "How YouTube recommendations work", YouTube Help, n.d. https://support.google.com/youtube/answer/16089387?hl=en
24. Z. Liu et al., "Monolith: Real Time Recommendation System With Collisionless Embedding Table" (ByteDance), arXiv, 2022. https://arxiv.org/abs/2209.07663
25. A. Colyer, "Deep neural networks for YouTube recommendations", The Morning Paper, 2016. https://blog.acolyer.org/2016/09/19/deep-neural-networks-for-youtube-recommendations/
26. "How to design a recommendation system in an ML interview", techinterview.org, 2026. https://www.techinterview.org/post/3233476954/how-to-design-a-recommendation-system-ml-interview/
27. "System Design Example: TikTok Recommendation System", Jointaro, n.d. https://www.jointaro.com/course/master-the-machine-learning-interview-as-a-software-engineer/system-design-example-tiktok-recommendation-system/
28. "ML System Design: Model Selection", Exponent, n.d. https://www.tryexponent.com/courses/ml-system-design/mlsd-model-selection

29. C. Huyen, "Machine Learning Systems Design - Exercises", GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md
30. "ML Design Interview | Design a short-video platform Part 2", RecSys ML Substack, n.d. https://recsysml.substack.com/p/ml-design-interview-design-a-short
31. "Design Video Recommendation System", AlgoMaster, n.d. https://algomaster.io/learn/ml-system-design/design-video-recommendation-system

03. Design a Short-Video Feed (TikTok For You / Instagram Reels / YouTube Shorts) with Real-Time Signals

Company tags

Company	Evidence	Ref
Meta (Instagram / Facebook Reels)	interviewing.io mock "Meta ML system design: Instagram Reels"; Hello Interview community report (TikTok-style recommender, goal = maximize comments; senior variant on Reels with CLIP, multi-task training, nDCG); Exponent-reported Meta loop ending in a TikTok-style rec round	[13] [14] [15]
TikTok / ByteDance	Codemia TikTok MLE guide ("design the end-to-end ML pipeline for the For You Page"); techinterview.org ByteDance guide (ranking, candidate generation, real-time serving); LeetCode TikTok MLE phone screen (recommender for videos in a user's followed circle, scale to ~1B users, drift)	[16] [19] [20]
YouTube / Google (Shorts)	*Indicative only*: YouTube video rec is the canonical prompt in prep repos, and the reference designs are Google papers; no first-hand Shorts interview report found	[6] [7] [21] [22]

Portals that cover it

Portal	Page	Ref
interviewing.io	Meta ML system design mock: Instagram Reels	[13]
Hello Interview	Community question: Design TikTok Video Recommendation System	[14]
Exponent	TikTok MLE interview guide; "Design TikTok" question	[15]
Codemia	Design TikTok's For You Page Recommendation Feed	[16]
ByteByteGo (Aminian & Xu)	*ML System Design Interview*, ch. "Video Recommendation System"	[30]
Educative	Grokking MLSD: video recommendation candidate-retrieval lesson; TikTok SD blog	[23]
recsysml / BuildML (Substack)	"Design a short-video platform" series; short-video recommender case study	[17] [18]
GitHub	alirezadir/Machine-Learning-Interviews (video recsys); khangich/machine-learning-interview	[21] [22]
Jointaro, DesignGurus, techinterview.org, dataford	TikTok rec walkthroughs; Reels question	[19] [24] [25] [26]

Requirements & scale

Category	Requirement	Source / note
Functional	Infinite vertical feed, one full-screen video at a time, autoplay; next video personalised instantly from in-session actions	[13] [17]
Functional	Signals: watch time / completion, replay, like, share, comment, follow, skip, "not interested"	[3] [4]
Functional	Diversity: no two consecutive videos with same sound or creator; integrity filtering	[3] [4]
Functional	Cold start: new users (onboarding, device/locale priors) and new videos (small-audience exploration pools)	[16] [19]
Non-functional	p99 serving latency < 50-100 ms for ranking	[17] [16] (typical)
Non-functional	Freshness: model reacts to new interactions in minutes (online training)	[1]
Scale	~1B DAU; feed requests ~millions/s; ~1T views/day	[16] [19] (prep-site assumptions)
Scale	Corpus: 100M to billions of videos; tens of millions eligible for retrieval	[8] [21] (typical)
Funnel sizes	Retrieval ~1e4 -> light rank ~1e3 -> heavy rank ~100-500 -> serve ~10 per page	[4] [6] (typical)
Out of scope	Upload/transcoding/CDN (classic SD), ads auction, monetization	[17]

Diagram 1 - Online serving path

Figure 3.1 - End-to-end online serving: request -> retrieval -> filtering -> ranking -> re-ranking -> response, with real-time feature updates.




Diagram 2 - Offline + streaming training pipeline

Figure 3.2 - Data, labels, training, evaluation and deployment, with the real-time (online-training) loop that defines this problem.




Diagram 3 - Model architecture

Figure 3.3 - Two-tower retrieval (left) and multi-task heavy ranker with long-sequence user modelling (right).





Diagram 4 - Real production system: ByteDance Monolith (real-time training)

Figure 3.4 - Monolith: collisionless embedding table + online training loop that lets TikTok-style feeds learn from feedback in minutes [1] [2].



Other real systems to name-drop: Instagram Explore/Reels 4-stage funnel (retrieval -> first-stage ranking -> second-stage MTML ranking -> final re-ranking) with two-tower + caching [4]; Facebook Reels UTIS survey-alignment model feeding both retrieval and late ranking [5]; Kuaishou TWIN lifelong-sequence ranker [9], D2Q duration-debiased watch time [10], on-device re-ranking [12]; Meta HSTU generative recommender [11].

Often missed (vs. real systems)

Item	Why it matters	Ref
Upload-time content understanding (multimodal emb, near-dup / re-upload detection, safety classifiers)	Makes a new video rankable before it has interactions; blocks harmful items pre-ranking	[3] [27]
New-video traffic pool (staged exposure, promote on early engagement)	Item cold start and creator fairness; gated by early finish/like rates	[3] [16]
On-device re-ranking of the prefetched page	Reacts to a skip within the same page without a server round trip	[12]
Survey / satisfaction model as an extra objective	Counters watch-time-only optimisation; used in retrieval and late ranking	[5]
Lifelong user sequence (GSU/ESU, TWIN)	Long-term interests beyond last 50-100 items within latency	[9]
Value-model weight tuning by online experiments	Head weights are product decisions, not learned end-to-end	[4] [7]
Fault tolerance of online training (PS snapshots, rollback)	Monolith reports daily PS snapshots suffice despite real-time updates	[1]

Data & labels

Label	Definition	Notes
Watch time	ms watched (capped, incl. replays)	Biased toward long videos -> duration-quantile (D2Q) or watch_ratio [10]
Completion / "effective view"	watched >= X% or >= N s	recsysml: count of videos watched > ~10 s ~ watch time for short videos [17]
Skip	swiped away < 1-3 s	Strong, dense negative; short-video equivalent of non-click
Like / share / comment / follow	binary per impression	Sparse; shares weighted heavily (Reels) [4]
Negative feedback	"not interested", report, hide	Counter-metric and hard-negative label [21]
Survey	"how well does this match your interests" 1-5	Debiased; aligns to true interest [5]
Retrieval positives	engaged (finish or like) items; negatives = in-batch + random	log-Q correction for popularity [8]

Features

Group	Examples	Freshness
User static	id emb, locale, language, device, age bucket	daily

Group	Examples	Freshness
User sequence	last 50-100 watched ids + watch ratio; lifelong (1e4-1e6) via GSU/ESU search [9]	real-time / daily
Session (real-time)	videos this session, skips in last 5, current topic streak, dwell	seconds
Video content	multimodal emb (frames, audio, ASR, caption, hashtags, sound id)	at upload
Video stats	CTR/finish rate 1h/24h/7d, age since upload, duration	minutes (stream)
Creator	creator emb, follower count, user-creator affinity	hourly
Context	hour, weekday, network type, position in session	request time
Cross	user-topic affinity, user-sound affinity, two-tower score	request time

Model choices (baseline -> advanced)

Stage	Baseline	Advanced	Tradeoff
Retrieval	Popularity + item-item CF	Two-tower ANN (log-Q), multi-source; transformer seq retriever	Recall vs. freshness of item index
Light ranking	Logistic regression on counters	Distilled small DNN / two-tower dot	Latency on ~5k items
Heavy ranking	GBDT on hand features	MMoE/PLE multi-task DNN + DCN + target attention over long seq [7] [9]	Accuracy vs. GPU cost
Watch-time head	Weighted logistic (YouTube 2016) [6]	D2Q quantile / tree-based progressive regression [10] [28]	Duration bias handling
Freshness	Daily batch retrain	Online training, minute-level sparse sync [1]	Stability vs. reactivity
Next-gen	Separate stages	Generative recommender (HSTU) over action sequence [11]	Compute; infra maturity

Loss

Component	Loss
Retrieval	Sampled softmax / in-batch softmax with log-Q correction [8]
Binary heads (finish, like, share, follow, skip)	BCE per head, sum_i lambda_i * L_i (task weights tuned / uncertainty-weighted)
Watch time	Weighted logistic (watch-time-weighted positives) [6] or regression on duration-conditioned quantile [10]
Position / autoplay bias	Shallow bias tower added during training only [7]
Survey alignment	Calibrated regression on debiased survey score [5]

Offline metrics

Stage	Metric
Retrieval	Recall@K, hit rate@K on next-watched videos
Ranking heads	AUC / GAUC (per-user), normalized entropy, calibration (pred/actual)
Watch time	MAE / XAUC on watch time, per-duration-bucket

Stage	Metric
List	nDCG@K, diversity (unique creators/topics per 10), coverage of new videos
Slices	new users, new videos, low-activity regions, long vs short videos

Online metrics / A-B

Type	Metrics
North star	Total watch time / DAU, retention (D1/D7), sessions per user
Engagement	Effective views, finish rate, likes/shares/comments per view, follows
Session	Session length, session success rate [17]
Guardrails	Skip rate, "not interested"/reports, integrity violations, creator diversity, new-creator exposure, latency/QPS
Long-term	Holdouts (weeks) for retention; survey-based satisfaction [5]
Method	User-level randomisation; watch for network effects on creators; interleaving for ranking sensitivity

Serving & latency budget (typical, p99 ~100 ms)

Step	Budget	Technique
Feature fetch (user + session)	10 ms	online KV (Redis-like), co-located cache
Retrieval (parallel sources)	15 ms	HNSW/ScaNN ANN, precomputed item emb
Filtering	5 ms	Bloom filter of seen ids, policy flags
Light ranking ~5k	10 ms	CPU small DNN, precomputed item side
Heavy ranking ~500	35 ms	GPU batch inference, item-feature cache, fp16/int8
Re-rank + response	10 ms	rules + diversity (MMR/DPP)
Prefetch	n/a	return 8-10 videos; client prefetches next page while user watches

Monitoring

What	Signal
Data	Event lag in Kafka, joiner drop rate, feature null rate, train/serve feature skew
Model	Per-head calibration, AUC drift on fresh traffic, embedding norm explosions in online training
Business	Watch time, skip rate, report rate by region, creator concentration (Gini)
System	p50/p99 latency per stage, PS sync delay, ANN index age, GPU utilisation

Failure modes

Failure	Mitigation
Filter bubble / feedback loop	Explore slots, diversity re-rank, creator/sound dedup [3], survey alignment [5]
Clickbait / long-video bias in watch time	Multi-objective value model, D2Q debiasing [10]

Failure	Mitigation
Item cold start (new uploads)	Content emb in item tower, fresh-upload pool with traffic boosting, bandits
User cold start	Onboarding interests, locale/device priors, popular-in-region
Online training instability (bad batch, bot traffic)	Anomaly filters, rollback to last good checkpoint, dense sync slower than sparse [1]
Embedding table blow-up	Frequency filtering + expiring embeddings [1]
Train/serve skew	Log features at serving time and join (Fig 3.2)
Viral spike / hot item	Item-feature cache, real-time counters, rate-limit boosting
Harmful content amplification	Integrity filter before ranking + post-rank policy layer [4]

Interviewer follow-ups

- How do you define "engagement" for a feed with no clicks (autoplay)? Watch time vs. completion vs. effective views? [17]
- How do you remove duration bias from watch-time labels? [10]
- How would the next video change based on a skip that happened 2 seconds ago (session features vs. online training vs. on-device re-rank)? [1] [12]
- How do you combine 5+ predicted objectives into one score, and how do you tune the weights? [4] [7]
- Walk through two-tower training: negatives, popularity bias, log-Q correction, index refresh cadence. [8] [23]
- How do you handle cold start for new users and for a creator's first video? [16] [19]
- How do you avoid filter bubbles and ensure creator diversity? [3]
- How would you model a user's lifelong history (10^5+ items) within latency? [9]
- What happens if the online trainer ingests bot traffic or a corrupted batch? [1]
- How do you detect and fix training/serving skew?
- Offline metrics improved but online watch time dropped: what do you check?
- How would you measure long-term satisfaction rather than short-term engagement? [5]
- How do you scale to ~1B users / millions of QPS; what is cached? [16] [20]
- Concept/data drift: how do you monitor and when do you retrain? [20]
- (Meta variant) Optimise for comments instead of watch time: what changes? [14]
- How do you treat re-uploads / near-duplicates and creator originality in ranking? [3]
- Would you re-rank on the device, and what model and features fit there? [12]
- How do you give a new video its first few hundred impressions, and when do you stop? [3] [16]

Portal comparison

Portal	Framing	Retrieval	Ranking	Real-time angle	Distinctive point
ByteByteGo / Aminian & Xu [30]	Generic YouTube-style video rec	Multiple candidate generators incl. two-tower	Ranking model on relevance labels	Light	Clean 7-step framework; MF vs two-tower tradeoffs

Portal	Framing	Retrieval	Ranking	Real-time angle	Distinctive point
alirezadir GitHub [21]	Homepage video rec, 100M DAU, 200 ms	CF (MF / two-tower) + popularity + trending	Content-based ranker	None	Sequential hybrid; precision@k, mAP, diversity
Educative Grokking MLSD [23]	Video rec retrieval deep-dive	Two-tower + negative sampling + ANN	Separate lessons	Medium	ANN indexing tradeoffs
recsysml Substack [17]	Short video explicitly	MVP then personalisation	Session success rate as CTR analogue	p99 < 50 ms MVP	Watch time ~ count of >10 s views for short clips
Codemia / techinterview.org [16] [19]	TikTok FYP, 1B+ DAU	Two-tower + follow graph + trending	ML ranker	Real-time feature store, Kafka	Heavy on infra and cold start
interviewing.io / Hello Interview [13] [14]	Meta Reels mock / reports	Candidate generation	Heavier multi-task ranker, CLIP content emb	Varies	Real interviewer feedback; problem-solving scored hardest

References

1. Liu et al., "Monolith: Real Time Recommendation System With Collisionless Embedding Table", ByteDance, arXiv / ORSUM@RecSys workshop, 2022. https://arxiv.org/abs/2209.07663
2. ByteDance, "monolith" open-source repository (collisionless embeddings, real-time training), GitHub, 2022. https://github.com/bytedance/monolith
3. TikTok, "How TikTok recommends videos #ForYou", TikTok Newsroom, 2020. https://newsroom.tiktok.com/en-us/how-tiktok-recommends-videos-for-you/
4. Meta Engineering, "Scaling the Instagram Explore recommendations system", engineering.fb.com, 2023. https://engineering.fb.com/2023/08/09/ml-applications/scaling-instagram-explore-recommendations-system/
5. Meta Engineering, "Adapting the Facebook Reels RecSys AI model based on user feedback", engineering.fb.com, 2026. https://engineering.fb.com/2026/01/14/ml-applications/adapting-the-facebook-reels-recsys-ai-model-based-on-user-feedback/
6. Covington, Adams, Sargin, "Deep Neural Networks for YouTube Recommendations", Google Research / RecSys, 2016. https://research.google/pubs/pub45530
7. Zhao et al., "Recommending What Video to Watch Next: A Multitask Ranking System", Google Research / RecSys, 2019. https://research.google/pubs/recommending-what-video-to-watch-next-a-multitask-ranking-system/
8. Yi et al., "Sampling-Bias-Corrected Neural Modeling for Large Corpus Item Recommendations", Google Research / RecSys, 2019. https://research.google/pubs/sampling-bias-corrected-neural-modeling-for-large-corpus-item-recommendations/
9. Chang et al., "TWIN: TWo-stage Interest Network for Lifelong User Behavior Modeling in CTR Prediction at Kuaishou", KDD, 2023. https://arxiv.org/abs/2302.02352
10. Zhan et al., "Deconfounding Duration Bias in Watch-time Prediction for Video Recommendation" (D2Q), Kuaishou, KDD, 2022. https://arxiv.org/abs/2206.06003
11. Zhai et al., "Actions Speak Louder than Words: Trillion-Parameter Sequential Transducers for Generative Recommendations" (HSTU), Meta, ICML, 2024. https://ar

xiv.org/abs/2402.17152
12. Gong et al., "Real-time Short Video Recommendation on Mobile Devices", Kuaishou, CIKM, 2022. https://arxiv.org/abs/2208.09577
13. interviewing.io, "Meta ML system design mock: Instagram Reels", interviewing.io, 2024. https://interviewing.io/mocks/meta-system-design-ml-instagram-reels
14. Hello Interview, "Design TikTok Video Recommendation System" (community question), hellointerview.com, 2026. https://www.hellointerview.com/community/questions/tiktok-video-recommendation/cmgzuubzb02eq08adu99oof84
15. Exponent, "TikTok Machine Learning Engineer Interview Guide" and "Design TikTok" question, tryexponent.com, 2023-2025. https://tryexponent.com/guides/tiktok-machine-learning-engineer-interview , https://www.tryexponent.com/questions/1372/design-tiktok
16. Codemia, "Design TikTok's For You Page Recommendation Feed" and "TikTok Machine Learning Engineer guide", codemia.io, 2025. https://codemia.io/practice/design-tiktok-s-for-you-page-recommendation-feed , https://codemia.io/guides/tiktok-machine-learning-engineer
17. recsysml, "ML Design Interview | Design a short-video platform Part 2", Substack, 2021. https://recsysml.substack.com/p/ml-design-interview-design-a-short
18. BuildML, "Data Science Case Study: Design a Short-Video Recommender System", Substack, 2024. https://buildml.substack.com/p/data-science-case-study-design-a
19. techinterview.org, "System Design: TikTok / Short-Form Video Platform" and "ByteDance / TikTok Interview Guide", techinterview.org, 2025. https://www.techinterview.org/post/3233460374/system-design-tiktok-short-form-video-platform/ , https://www.techinterview.org/companies/bytedance-tiktok-interview-guide/
20. LeetCode Discuss, "Machine Learning Engineer | Tiktok | Phone Screen", leetcode.com, 2022. https://leetcode.com/discuss/interview-experience/2073085/
21. A. Dirafzoon, "Design a video recommendation system", alirezadir/Machine-Learning-Interviews, GitHub, 2023. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/mlsd-video-recom.md
22. K. Pham, "machine-learning-interview" (YouTube recommendation case, TikTok reading list), GitHub, 2022. https://github.com/khangich/machine-learning-interview
23. Educative, "Video recommendation: candidate retrieval architecture" (Grokking the ML System Design Interview) and "TikTok System Design Interview Questions", educative.io, 2025. https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/video-recommendation-candidate-retrieval-architecture , https://www.educative.io/blog/tiktok-system-design-interview-questions
24. DesignGurus, "What is TikTok system design interview like?", designgurus.io, 2024. https://www.designgurus.io/answers/detail/what-is-tiktok-system-design-interview-like
25. Taro, "System Design Example: TikTok Recommendation System", jointaro.com, 2024. https://www.jointaro.com/course/master-the-machine-learning-interview-as-a-software-engineer/system-design-example-tiktok-recommendation-system/
26. Dataford, "Design Instagram Reels Recommendations", dataford.io, 2025. https://dataford.io/interview-guides/questions/design-instagram-reels-recommendations
27. Meta Transparency Center, "Instagram Explore AI system", transparency.meta.com, 2024. https://transparency.meta.com/features/explaining-ranking/ig-explore/
28. Lin et al., "Tree based Progressive Regression Model for Watch-Time Prediction in Short-video Recommendation", Kuaishou, KDD, 2023. https://arxiv.org/abs/2306.03392

29. Meta AI, "Powered by AI: Instagram's Explore recommender system", ai.facebook.com, 2019. https://ai.facebook.com/blog/powered-by-ai-instagrams-explore-recommender-system
30. A. Aminian & A. Xu, *Machine Learning System Design Interview* (ch. "Video Recommendation System"), ByteByteGo, 2023. https://bytebytego.com

Research note: portal pages were read via search-result excerpts. During review, live fetches were blocked by the build environment, so URLs were checked against known publication identifiers (arXiv ids, venues) rather than fetched. Company tags from anonymous reports are indicative, not confirmed.

04. Design a Personalized News Feed Ranking System (Facebook / LinkedIn / Twitter Home Timeline)

> Prompt as usually given: "When a user opens the app, rank the unseen posts from friends, follows, groups and recommended sources so the feed maximizes meaningful engagement." Variants: Twitter/X "For You" timeline, LinkedIn homepage feed, Instagram feed, comment ranking under a post, "compare ranking objectives for a feed".

Company tags

Company (reported)	Where it was reported	Notes
Meta	IGotAnOffer Meta MLE guide [25], Prepfully Meta MLE bank [26], PracHub "comment ranking for a news feed" [14], Blind [28]	Feed / ranking is the standard Meta ML-design round; comment-ranking variant balances engagement, spam/toxicity and freshness [14]
LinkedIn	PracHub "personalized feed + compare ranking objectives" [13]	Follow-up: pointwise vs. pairwise vs. listwise LTR [13]; Khang Pham uses "LinkedIn Feed Ranking" as a case study [7][6]
Twitter / X (case study, not a verified interview tag)	Educative "Feed Based System" uses the Twitter feed as its worked example [3]; Khang Pham repo lists "Twitter timeline ranking" as reading under Adtech, linking [21] [7]	Use as the real-system reference (Figure 4.4), not as evidence that X asks this question
Generic FAANG / big tech	Exponent question bank [2], AlgoMaster [10], techinterview.org [11], Analytics Vidhya 2026 [12]	Exponent page is a question listing; company tag details were not retrievable in this run

Portals that cover it

Portal	Treatment	Link
ByteByteGo (Aminian & Xu, MLSDI ch. 10 "Personalized News Feed")	Full chapter; ads between posts, engagement goal; click/like/comment/hide/block actions	[1]
Educative "Grokking the ML Interview" (Feed Based System, Twitter)	9 lessons: metrics, architecture, tweet selection, features, training data, ranking, diversity, online experiments	[3]
Educative "Grokking the ML System Design Interview" (Social feed ranking)	Framing, guardrails, interleaving, creator equity	[4][5]
Educative / Khang Pham "Machine Learning System Design"	Feed Ranking System Design lesson (LinkedIn-style)	[6][7]
alirezadir AIMLInterviews (GitHub)	Free full write-up: 2B DAU, 200 ms, multi-task NN, dwell + skip heads	[8][9]
Exponent	"Design personalized news ranking system" question	[2]


Portal	Treatment	Link
AlgoMaster, techinterview.org, Analytics Vidhya, PracHub	Guides and reported prompts	[10][11] [12][13] [14]
Hello Interview	Recsys pattern page (applies directly)	[27]

Requirements & scale

Dimension	Value	Source
Surface	Home feed on app open / refresh; no query; user_id + context in	[1][9]
Timelines served	X home-mixer serves For You (ranked) plus Following and Lists (reverse-chron)	[18]
Business goal	Maximize engagement (ads are interleaved, so engagement -> revenue)	[1][9]
Output	Ranked list of unseen posts from friends/follows + recommended sources	[9][3]
Users	5B total, 2B DAU, ~2 refreshes/user/day (AIMLInterviews); Meta "more than 2B" users	[9][15]
Avg / peak QPS	2B x 2 / 86,400 ~ 46k avg; x3 peak ~ 140k QPS	typical assumption from [9]
Candidate inventory	Hundreds of millions of posts; LinkedIn retrieves ~2,000 from hundreds of millions	[22]
Candidates per stage	~1e8 pool -> ~1-2k retrieved -> ~500 light-ranked -> ~50 shown per page	[22][33] + typical
End-to-end latency	200 ms (AIMLInterviews); 100-200 ms (PracHub); < 200 ms (techinterview.org)	[9][14][11]
Features	~6,000 features hydrated per candidate in Twitter home-mixer	[18]
Freshness	New posts visible within seconds-minutes; engagement counters streamed	[9] + typical
Non-functional	Integrity/safety filters, diversity, creator fairness, privacy, cold start	[9][11][5]

Diagram 1 - Online serving path


Figure 4.1 - Home-feed request through the multi-stage ranking funnel



Sources: funnel and stages [1][9][15]; filters/heuristics/mixing [18]; value model [15][19].

Diagram 2 - Offline training & data pipeline


Figure 4.2 - Logging -> labels -> features -> training -> registry -> deploy



Sources: labels, downsampling, continual fine-tune "deploy only if metrics improve" [9]; offline learning systems at Meta [15]; Twitter weights retuned over time [19].

Diagram 3 - Model architecture: multi-task heavy ranker + value model


Figure 4.3 - Shared-bottom multi-task ranker with per-action heads



Sources: multi-task heads incl. dwell + skip, BERT/CLIP encoders, summed loss [9]; multitask NN + embeddings at Meta [15]; MaskNet ranker [19][29]; DCNv2 -> transformer at LinkedIn [22].

Diagram 4 - Real system: Twitter/X "For You" (open-sourced 2023)

Figure 4.4 - Twitter home-mixer pipeline vs. the textbook funnel



Sources: components [17][18]; heads and weights (Apr 5, 2023 config) [19]; features [20].

Table 4.1 - X Heavy Ranker heads and value-model weights (Apr 5, 2023) [19]

Head (predicted P)	Weight	Head (predicted P)	Weight
reply_engaged_by_author	+75.0	retweet	+1.0
reply	+13.5	fav (like)	+0.5
good_profile_click	+12.0	video_playback50	+0.005
good_click	+11.0	negative_feedback_v2	-74.0
good_click_v2	+10.0	report	-369.0

In-network candidates (~50% of the feed) come from the Earlybird search index with its own light ranker [17]; TwHIN supplies three 200-d embeddings and aggregates use 50-day and short-term windows [20].

Data & labels

Signal	Type	Label use	Note
Click / expand	Implicit, abundant	P(click) head	Noisy; clickbait risk [1]
Like / react	Explicit	P(like)	Weight: share > comment > like > click [9]
Comment / reply	Explicit, sparse	P(comment)	Strong "meaningful interaction" signal [15][19]
Share / retweet	Explicit, sparse	P(share)	Virality
Dwell time	Implicit	Regression head	Covers passive users [9]
Skip (dwell < t)	Implicit negative	P(skip)	Passive-user negative [9]

Signal	Type	Label use	Note
Hide / block / report	Explicit negative	Negative-weight heads	Twitter report weight -369 [19]
Non-engaged impression	Negative	All heads = 0	Downsample; imbalance [9]
Surveys ("worth your time?")	Explicit	Eval / auxiliary	Satisfaction metric [9]

Features

Group	Examples	Freshness
User	id embedding, demographics, locale, history aggregates (CTR, likes)	daily batch
Post content	text embedding (BERT), image/video embedding (CLIP/SimCLR), hashtags, age, media type	at post time
Post engagement	like/comment/share counts and velocity (30 min, 1 day)	streaming
Author	follower count, author health/quality, posting rate	daily
User-author affinity	connection type, past reactions, real-graph P(interact), 2-hop	batch + stream
Graph / embeddings	SimClusters, TwHIN, two-tower embeddings	daily
Context	device, time of day, day of week, network, position	request time

Sources: [9][20][15].

Model choices (baseline -> advanced)

Stage	Baseline	Advanced	Tradeoff
Retrieval	Reverse-chron in-network + rules	Two-tower ANN, graph walks, LLM dual encoder (LinkedIn LLaMA-3 retrieval, ~2k from 100s of M) [22]	Recall vs. infra cost
Light ranker	Logistic regression	Small DNN / GBDT	Cheap pre-filter of ~1k
Heavy ranker	Independent per-action LR / GBDT	Shared-bottom multi-task DNN; DCNv2, MaskNet, transformer (LinkedIn Feed-SR) [19][22]	Accuracy vs. GPU cost
Objective	Single P(click)	Multi-task + value model weights	Avoids clickbait; weights become a product lever
LTR	Pointwise	Pairwise / listwise (LinkedIn follow-up) [13][8]	Pointwise simplest; listwise better ordering
Re-rank	Hard rules	Diversity-aware (MMR/DPP), integrity demotion	Engagement vs. diversity

Loss

Head	Loss	Note
Binary actions	Binary cross-entropy	Sum over tasks, optional task weights [9]
Dwell time	MAE / MSE / Huber	Huber robust to long tails [9]

Head	Loss	Note
Calibration	Post-hoc isotonic / Platt	Needed because value model sums probabilities
Imbalance	Negative downsampling + log-odds correction	Recalibrate after sampling

Offline metrics

Metric	What it checks	Source
ROC-AUC per task	Discrimination per head	[9]
Normalized cross-entropy / log loss	Calibrated probability quality	typical
nDCG@10, mAP, MRR	Ranking quality of value-model order	[8][11]
Calibration (pred / actual)	Value-model correctness	typical
Slice metrics	New users, new creators, regions	[5]

Online metrics / A-B

Type	Metrics	Source
Primary	Time spent, sessions/DAU, meaningful interactions (comments, shares)	[9][22]
Secondary	CTR, like/comment/share rates	[8][9]
Counter / guardrail	Hide, report, unfollow rates; ad revenue; latency	[8][5]
Satisfaction	In-app surveys	[9]
Fast comparison	Interleaving of rankers	[5]
Reported wins	LinkedIn Feed-SR +2.10% time spent; LiRank +0.5% member sessions	[22]

Serving & latency budget (200 ms p99 target [9])

Step	Budget	Notes
API, auth, A/B, seen cache	10 ms	
Candidate generation (parallel sources)	30 ms	ANN + index lookups fan out
Filtering + integrity lookups	10 ms	precomputed classifier scores
Feature hydration	30 ms	batched KV reads, ~6k features [18]
Light ranker (~1k)	15 ms	CPU
Heavy ranker (~500)	50 ms	GPU batch inference
Value model + re-rank + ads mix	15 ms	
Network / slack	40 ms	
Precompute option	-	Batch-precompute scores for inactive users; online for active ones (batch vs. online prediction tradeoff [8])
Fallback	-	Reverse-chron in-network feed if the scored pipeline fails (X Conversation Service fallback [18])

Monitoring

What	Signal	Action
Feature drift	PSI/KL on top features, null rates	Alert, fallback defaults
Prediction drift	Mean predicted vs. observed per head	Recalibrate / retrain
Online KPIs	CTR, time spent, hide rate by slice	Auto-rollback
Freshness	Streaming counter lag	Page on-call
Integrity	Prevalence of violating content in feed	Tighten filters
Latency / errors	p50/p99 per stage, timeouts	Degrade to light ranker

Failure modes

Failure	Symptom	Mitigation
Clickbait / engagement bait	High CTR, low dwell, more hides	Multi-task + negative-weight heads [19]
Popular / prolific posters dominate	Close friends crowded out	Affinity features, author diversity [15][18]
Celebrity / viral posts	Fan-out hot spots, repeats	Cache, dedup, fatigue rules [9][18]
Cold start (user or post)	Generic feed; new posts never shown	Onboarding topics, exploration slots [9]
Position bias	Top slots over-labelled positive	Position feature, set to a fixed value at serving (typical; [9] lists positional bias as a topic only)
Feedback loop / filter bubble	Narrowing topics	Exploration traffic, out-of-network quota
Data leakage	Offline AUC up, online flat	Point-in-time feature joins [9]
Catastrophic forgetting	Drift after incremental training	Replay buffer, periodic full retrain [9]
Integrity misses	Harmful content ranks high	Filter + demotion before and after ranking; X visibility-filters use hard filters, visible treatments and coarse down-ranking [17]
Ranker timeout / outage	Empty or stale feed	Serve reverse-chron in-network fallback; degrade to light ranker [18]

Interviewer follow-ups

- Why multi-task instead of N separate models? How do you set the value-model weights? [9][19]
- How would you handle passive users who never like or comment? [9]
- Pointwise vs. pairwise vs. listwise ranking: which and why? [13][8]
- How do you keep close friends' posts from being drowned by pages and frequent posters? [15]
- How do you rank a celebrity post with millions of followers (fan-out, caching)? [9]
- How do you correct for position bias in training labels?
- How do you calibrate probabilities after negative downsampling?
- Design the comment ranking under a post (spam, toxicity, freshness). [14]

- How do you add out-of-network / recommended content to a follow-based feed? [17] [22]
- What guardrail metrics stop you from shipping an engagement-bait winner? [5]
- How fresh must features be, and what goes in batch vs. streaming? [9]
- How do you fit ~500 candidates through a heavy ranker inside 200 ms? [9][18]
- Cold start for new users and new posts? [9]
- How would you measure long-term satisfaction rather than short-term clicks? [23]
- Where do integrity classifiers run, and how do they interact with ranking? [17]
- What does the feed show if the heavy ranker times out? [18]
- Why would a reply the author engages with be weighted 150x a like? [19]

Portal comparison

Portal	Objective	Candidate gen	Ranker	Distinctive emphasis
ByteByteGo [1]	Engagement (ads interleaved)	Retrieval of unseen posts	Multi-task DNN over reactions	Clarifying-questions dialogue; hide/block as negatives
AIMLInterviews [9]	Weighted sum of reactions	Rule-based unseen posts	Multi-task NN + dwell + skip heads	Passive users; BERT/CLIP features; 2B DAU / 200 ms
Educative Grokking ML Interview [3]	P(engage) on Twitter feed	Tweet selection stage	Ranking + diversity	Training data generation, online experimentation
Educative Grokking MLSD [4][5]	Social feed ranking	Funnel	Multi-stage	Guardrails, interleaving, creator equity
Khang Pham [6][7]	LinkedIn-style long-term engagement	Multi-source	Ranking model	Real-company case study framing
techinterview.org / AlgoMaster [11][10]	NDCG@10 offline, A/B online	Followed, topics, trending, embeddings	Multi-task weighted score	< 200 ms, fairness to minority creators

References

1. A. Aminian & A. Xu, "Personalized News Feed" (Machine Learning System Design Interview, ch. 10), ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/personalized-news-feed
2. Exponent, "Design personalized news ranking system" (question), tryexponent.com, n.d. https://www.tryexponent.com/questions/3093/design-personalized-news-ranking-system
3. Educative, "Grokking the Machine Learning Interview" (Feed Based System module), educative.io, n.d. https://www.educative.io/courses/grokking-the-machine-learning-interview
4. Educative, "Social feed ranking: problem framing and requirements" (Grokking the ML System Design Interview), educative.io, 2025. https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/social-feed-ranking-problem-framing-and-requirements

5. Educative, "Social feed ranking: evaluation and experimentation" (Grokking the ML System Design Interview), educative.io, 2025. https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/social-feed-ranking-evaluation-and-experimentation
6. Educative / K. Pham, "Feed Ranking System Design" (Machine Learning System Design course), educative.io, n.d. https://www.educative.io/courses/machine-learning-system-design/lta/feed-ranking-system-design
7. K. Pham, "machine-learning-interview" (LinkedIn Feed Ranking listed), GitHub, 2021. https://github.com/khangich/machine-learning-interview
8. alirezadir, "ML System Design" template (ranking, LTR, metrics), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md
9. alirezadir, "News Feed System" (mlsd-newsfeed.md), GitHub, 2025. https://github.com/alirezadir/AIMLInterviews/blob/main/src/MLSD/mlsd-newsfeed.md
10. AlgoMaster, "Design Personalized News Feed" (ML system design), algomaster.io, n.d. https://algomaster.io/learn/ml-system-design/design-personalized-news-feed
11. techinterview.org, "Machine Learning System Design Interview: Feed Ranking, Recommendations, and Search", techinterview.org, n.d. https://www.techinterview.org/post/3233460469/machine-learning-system-design-interview/
12. Analytics Vidhya, "System Design for ML Interviews: 10 Real Problems Walked Through", analyticsvidhya.com, 2026. https://www.analyticsvidhya.com/blog/2026/06/system-design-for-ml-interviews-real-problems-solved/
13. PracHub, "Design a Personalized Feed and Compare Ranking Objectives" (LinkedIn), prachub.com, n.d. https://prachub.com/interview-questions/design-a-personalized-feed-and-compare-ranking-objectives
14. PracHub, "Design comment ranking for a news feed" (Meta), prachub.com, n.d. https://prachub.com/interview-questions/design-comment-ranking-for-a-news-feed
15. Meta Engineering, "How machine learning powers Facebook's News Feed ranking algorithm", engineering.fb.com, 2021. https://engineering.fb.com/2021/01/26/ml-applications/news-feed-ranking/
16. Facebook, "Adaptive ranking of news feed in social networking systems" (US patent 8768863), Justia Patents, 2014. https://patents.justia.com/patent/8768863
17. Twitter, "the-algorithm" (For You timeline source), GitHub, 2023. https://github.com/twitter/the-algorithm
18. Twitter, "home-mixer README", GitHub, 2023. https://github.com/twitter/the-algorithm/blob/main/home-mixer/README.md
19. Twitter, "the-algorithm-ml: Heavy Ranker (projects/home/recap)", GitHub, 2023. https://github.com/twitter/the-algorithm-ml/tree/main/projects/home/recap
20. Twitter, "Heavy Ranker FEATURES.md", GitHub, 2023. https://github.com/twitter/the-algorithm-ml/blob/main/projects/home/recap/FEATURES.md
21. Twitter Engineering, "Using deep learning at scale in Twitter's timelines", blog.twitter.com, 2017. https://blog.twitter.com/engineering/en_us/topics/insights/2017/using-deep-learning-at-scale-in-twitters-timelines.html
22. F. Borisyuk et al., "LiRank: Industrial Large Scale Ranking Models at LinkedIn", arXiv, 2024. https://arxiv.org/abs/2402.06859
23. KDnuggets, "How LinkedIn Uses Machine Learning To Rank Your Feed", kdnuggets.com, 2022. https://www.kdnuggets.com/2022/11/linkedin-uses-machine-learning-rank-feed.html

24. Shaped, "Feed ranking systems", shaped.ai, n.d. https://shaped.ai/blog/feed-ranking-systems
25. IGotAnOffer, "Meta Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/facebook-machine-learning-engineer-interview
26. Prepfully, "Meta Machine Learning Engineer interview questions", prepfully.com, 2025. https://prepfully.com/interview-questions/meta/machine-learning-engineer?page=8
27. Hello Interview, "Recommendation Systems (ML System Design pattern)", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/patterns/recommendation-systems
28. Blind, "Meta - help for ML design round feedback", teamblind.com, n.d. https://www.teamblind.com/post/meta-help-for-ml-design-round-feedback-nrxobup2
29. Z. Wang, Q. She, J. Zhang, "MaskNet: Introducing Feature-Wise Multiplication to CTR Ranking Models", arXiv, 2021. https://arxiv.org/abs/2102.07619
30. MLconf, "Generating a Billion Personal News Feeds", mlconf.com, n.d. https://mlconf.com/sessions/generating-a-billion-personal-news-feeds-with-exp/
31. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2020. http://patrickhalina.com/posts/ml-systems-design-interview-guide/
32. C. Huyen, "Introduction to Machine Learning Interviews Book", huyenchip.com, 2021. https://huyenchip.com/ml-interviews-book/
33. Twitter Engineering, "Twitter's Recommendation Algorithm", blog.twitter.com, 2023. https://blog.twitter.com/engineering/en_us/topics/open-source/2023/twitter-recommendation-algorithm

> Research note: in the review pass, [7], [8], [9], [17], [18], [19] and [20] were fetched and checked against the claims above; non-GitHub hosts were unreachable from the sandbox (DNS/proxy refusal) and the shared web-search budget was exhausted, so [1]-[6], [10]-[16], [21]-[33] rest on earlier search-result summaries and are unverified here. Company tags for Meta and LinkedIn depend on those unverified portal pages. Values marked "typical" are assumptions.

05. Design People You May Know (PYMK) / Friend Recommendation (Graph-Based)

> Prompt as usually given: "Design the People You May Know feature. Given a user, return a ranked list of other users they are likely to connect with." Variants: Facebook PYMK, LinkedIn PYMK (connection invites), Twitter/X "Who to Follow" (asymmetric follow), Snapchat "Quick Add", Instagram "Suggested for you".

Company tags

Company (reported)	Where it was reported	Notes
Meta / Facebook	alirezadir AIMLInterviews question list: "Friends / follower recommendation: Facebook, Twitter, LinkedIn" [2]	Symmetric friendship; maximize connections formed [1]
LinkedIn	Same list [2]; Kao's write-up frames it "similar to LinkedIn" [6]	Production PYMK uses LiGNN embeddings [10]; equity-aware PYMK [13]
Twitter / X	Same list [2]	Asymmetric "Who to Follow"; open-sourced FRS [7][8], WTF paper [9]
Snap (production, not a reported ask)	Snap Research papers on friend-recommendation EBR [11][12]	Useful "real system" to cite in the interview

Note: company tags for this problem come mainly from the AIMLInterviews list [2]. Blind, LeetCode and Prepfully pages could not be reached in this run.

Portals that cover it


Portal	Treatment	Link
ByteByteGo (Aminian & Xu, MLSDI ch. 11 "People You May Know")	Full chapter. Graph edge prediction with a GNN, FoF candidates, batch vs. online prediction	[3]
alirezadir AIMLInterviews (GitHub, free)	Outline: 1B users, pointwise vs. edge-prediction framing, GNN, FoF, batch precompute	[1] [2]
shafaypro CrackingMachineLearningInterview (GitHub, free)	Deepest free write-up: 5-stage funnel, P(send) x P(accept), leakage, interference, safety	[4]
jsheng0901 MLSD notes (GitHub, free)	GCN -> GraphSAGE -> GAT progression, negative resampling, weekly batch refresh	[5]
M. C. J. Kao "MLSD Interview Extension: PYMK" (Medium, mirrored on GitHub)	Serving flowchart, Airflow offline pipeline, ego-cluster A/B testing	[6] [16]
Khang Pham (Educative / repo), Chip Huyen booklet	Checked: no PYMK chapter (LinkedIn feed and generic recsys only)	[17] [18]

Requirements & scale

Dimension	Value	Source
Input / output	user_id (+ surface context) -> ranked list of candidate users	[1][6]
Business goal	Maximize connections formed (accepted, not just sent)	[1][4]
Edge type	Symmetric friendship (FB/LinkedIn) vs. asymmetric follow (X)	[1][4]
Users	~1B total users	[1][4]
Degree	~10K connections/user (alirezadir) vs. "few hundred median, long tail of hubs" (shafaypro)	[1][4]
DAU	300M DAU (exercise assumption)	[4]
Candidate space	1B -> ~1M FoF (1K x 1K) -> ~1-5K after scoring/quotas	[1][4]
Serving latency	~50 ms p99 (exercise assumption); rules out request-time graph traversal	[4]
Peak QPS	300M DAU x ~3 PYMK views/day / 86,400 ~ 10K avg, ~30K peak	typical assumption
Freshness	Minutes for new users / big graph events; daily for everyone else	[4]
Batch refresh	Precompute for active users (last 30 days); refresh daily to weekly	[5][6]
Non-functional	Privacy (contacts, minors), blocks applied instantly, fallback = hide module	[1][4]

Diagram 1 - Online serving path

Figure 5.1 - PYMK request: precomputed list + read-time filters + light re-score



- Graph events (accept, signup, contact upload, block) trigger incremental refresh of the affected users' lists via a stream processor [4].
- If the store is unavailable, hide the module; never show unfiltered candidates [4].

Diagram 2 - Offline training & data pipeline


Figure 5.2 - Snapshot-at-t / label-at-t+1 pipeline with batch precompute



- Retrain on a schedule (weekly/monthly) or on graph-drift alarms [5].
- Accepts arrive days late: use a fixed collection window or treat recent rows as censored [4][5].

Diagram 3 - Model architecture


Figure 5.3 - GNN node encoder + pair scorer with multi-task heads



- (A) alone is the ByteByteGo / AIMLInterviews answer (GNN edge prediction) [1][3].
- (B) adds the reciprocity objective (ESMM-style, like CTR x CVR in ads) [4].


Diagram 4 - Real systems: Twitter/X FRS and Snap / LinkedIn graph embeddings

Figure 5.4 - Twitter/X Follow Recommendations Service (open-sourced 2023) [7][8] [9]



- Each display location (post-signup NUX, home WTF, FutureGraph tweets) selects its own flow of sources, rankers and filters; candidate-source names above are the folders in the repo [7][20].

Figure 5.5 - Embedding retrieval added beside FoF (Snap EBR [11][12]; LinkedIn LiGNN [10])



- Snap: EBR improved friendships made in both sparse and dense markets [11]; ANN query expansion gave ~11% relative gain in reciprocated communication, 800M+ MAU [12].

Data & labels

Item	Choice	Notes / source
Positive (edge model)	Edge formed in (t, t+1] that was absent at snapshot t	[1][5][6]
Positive (ranker)	send on impression; accept given send; edge used within 28 days	[4]
Negatives	Seen-but-not-sent impressions; hard negatives (FoF not connected)	Random pairs teach "rank by degree" [4][5]

Item	Choice	Notes / source
Explicit negatives	Dismiss, "I don't know this person", ignored/declined, report	Separate heavily-weighted head [4]
Resampling	Re-sample negatives each epoch, keep class balance	[5]
Label window	Fixed 14-day accept window, or censor recent sends	[4][5]
Split	Temporal: train before cutoff, evaluate after	Random edge splits overstate quality [4]

Features

Group	Examples	Source
Neighbourhood overlap	Common neighbours (time-discounted), Adamic-Adar, Jaccard, resource allocation	[1][4]
Paths / walks	Shortest path (cap 3-4), 2/3-hop path counts, PPR both directions	[4][9] [14]
Degree	Degrees, degree ratio, incoming request volume, clustering coefficient	[4][5]
Shared context	Same school + years overlap, employer, industry, city, groups, contact match	[1][5]
Interaction (no edge)	Profile views, co-tags, comments on same posts (feature only, never shown)	[4]
Embeddings	GNN / node2vec cosine, pair score	[4][10]
User	Account age, activity, accept rate of received requests, device, time	[1][5]
Source	Which generator produced the candidate + rank within it	[4]

Model choices (baseline -> advanced)

Stage	Option	Pros	Cons
Heuristic	Rank FoF by mutual-friend count / Adamic-Adar	Cheap, explainable ("12 mutual")	Hubs dominate; no cold start
Walk baseline	Personalized PageRank / SALSA random walk with restart	Reaches 3+ hops, down-weights hubs	Hard to add side features [9]
Learned walk	Supervised random walks (edge weights learned from features)	Combines structure + attributes	Older, costly per-user [14]
Pointwise	GBDT / LR on pair features	Strong light ranker, fast batch	Ignores graph beyond hand features [1]
GNN	GCN -> GraphSAGE (inductive, sampled) -> GAT (attention edge weights)	Uses structure + features; new users	Training scale, leakage risk [5][15][19]
MTL ranker	Shared tower, send / accept / report heads	Models reciprocity, safety	More labels, calibration needed [4]
EBR	GNN embeddings in ANN as extra source	Beyond-2-hop recall, cold start	"Similar stranger" risk [4][11]

Loss

Component	Loss	Notes
GNN edge prediction	BCE on sigmoid(h_u . h_v) with sampled negatives	[1][5]

Component	Loss	Notes
EBR retrieval	Sampled softmax over in-batch / sampled users	Snap friend EBR pattern [11]
MTL ranker	sum_k w_k BCE_k (send, accept	send, report)
Regularization	Dropout, BN, residuals, early stopping	[5]

Offline metrics

Metric	Measures	Source
Recall@k on future edges	Candidate source coverage	[4]
ROC-AUC, log loss per head	Edge / head discrimination	[1][4][5]
mAP, NDCG@k, precision@k	Ranked list quality	[1][4]
Calibration per head	Heads are multiplied, so must be calibrated	[4]
Sliced metrics	New users, low-degree, minors, with/without contacts	[4]

Online metrics / A-B

Type	Metric	Source
Primary	Accepted connections per viewer; requests sent and accepted per window	[1][4] [5]
Long term	Connections with interaction within 28 days; new-user retention; WAU	[4][10]
Funnel	Impressions -> send rate -> acceptance rate	[4]
Guardrails	"Don't know"/remove rate, reports, pending backlog, requests to minors	[4]
Design	Interference (treated users invite control users): ego-cluster or graph-cluster randomization; long-term holdouts	[4][6] [16]

Serving & latency budget (~50 ms p99 assumption [4])

Step	Budget	Notes
Fetch precomputed list (KV)	~5 ms	100-500 candidates per user [4]
Read-time hard filters	~5 ms	KV sets for blocks, pending, friends
Online feature fetch	~10 ms	Mutual counts, recent activity
Light re-score (optional)	~15 ms	GBDT or small MLP on ~500
Re-rank + social proof	~5 ms	Diversity, caps, explanations
Network / slack	~10 ms	Typical assumption
Cache miss / new user	Async	Online FoF + EBR with lightweight ranker, then write back [5][6]

Monitoring

Signal	What to watch
Data	Feature distribution drift, degree-distribution change, graph-structure alarms [5]

Signal	What to watch
Model	AUC/calibration per head on fresh data, score distributions
System	p99 latency, KV hit rate, batch job freshness/SLA, training cost [5]
Ecosystem	Incoming-request concentration (rich-get-richer), cross-cluster edge share [4][13]
Safety	Reports, "don't know", adult-to-minor suggestion rate (should be 0) [4]

Failure modes

Failure	Mitigation
Hub explosion in FoF (one friend with 100K edges)	Sample/cap hubs, Adamic-Adar 1/log(deg) weighting [4]
Target / future-edge leakage	Point-in-time joins, drop target edge, temporal split [4][6]
Optimizing sends only -> spam to popular users	P(accept
Rich-get-richer, homophily	Exposure caps, degree discounts, exploration, equity-aware objective [4][13]
Cold start (no edges)	Contacts (consented), onboarding profile via inductive GNN, inviter's friends [4][11]
Creepy / privacy-leaking suggestions	No sensitive sources, explanations only from visible signals [4]
Self-confirming evaluation	Exploration traffic, long-term holdouts [4]
A/B contamination via network	Ego-cluster / graph-cluster randomization [6][16]

Interviewer follow-ups

- Symmetric friendship or asymmetric follow? How does the objective change? [1][4]
- How do you generate candidates on a 1B-user graph without request-time traversal? [1][4]
- Why is Adamic-Adar often better than common-neighbour counts? [4]
- Train on send, accept, or edge usage? How do you handle accept selection bias? [4]
- How can link-prediction features leak, and how do you split train/test? [4][6]
- Pointwise classifier vs. GNN edge prediction: what does each miss? [1][5]
- GCN vs. GraphSAGE vs. GAT; how do you train a GNN on billions of nodes? [5][15]
- Batch precompute vs. online prediction; how fresh must new users' lists be? [3][4][5]
- Brand-new user with zero friends: what do you show? [4][11]
- A/B test shows +5% connections; what could be wrong (network interference)? [4][6]
- How do you avoid rich-get-richer and suggesting the same celebrities? [4][13]
- What makes a suggestion "creepy", and how do you stop it? Minors? [4]
- How do accepts arriving days later affect labels and metrics? [1][5]
- How would you add embedding-based retrieval beside FoF? [10][11]
- Which filters run before ranking and which after? (cheap pre-rank, heavy post-rank) [7]
- Should onboarding (NUX) and the home module share one flow? (per-surface flows) [7]
- How do you rank users who are not active enough to have a precomputed list? [5][6]

Portal comparison

Portal	Framing	Candidates	Model	Serving	Distinctive
ByteByte Go [3]	Graph edge prediction	FoF	GNN	Batch vs. online prediction trade-off	Polished diagrams; canonical book answer
alirezadir [1]	Edge prediction over pointwise LTR	FoF (1K x 1K = 1M)	GNN embeddings + similarity	Batch precompute to DB	Notes delayed feedback, PRW baseline
shafaypro [4]	Two-sided funnel value score	FoF, PPR, EBR, contacts, co-membership	GBDT light + MTL heavy	Batch + stream refresh + read-time filters	Leakage, interference, safety, minors
jsheng0901 [5]	Edge prediction	FoF	GCN -> SAGE -> GAT, dot + sigmoid	Weekly batch + online fallback	Negative resampling, Cluster-GCN scaling
Kao (Medium) [6]	GNN pair score	FoF, same company/school	GNN	Precomputed DB, scoring on miss	Ego-cluster A/B testing, Airflow DAG
Real systems [7]-[12]	Follow / friend rec	Walks, address book, embeddings	p(follow) + p(engage	follow)	Multi-source union

References

1. alirezadir, "People You May Know (PYMK)" (mlsd-pymk.md), AIMLInterviews, GitHub, 2025. https://github.com/alirezadir/AIMLInterviews/blob/main/src/MLSD/mlsd-pymk.md
2. alirezadir, "ML System Design" question list (ml-system-design.md), AIMLInterviews, GitHub, 2026. https://github.com/alirezadir/AIMLInterviews/blob/main/src/MLSD/ml-system-design.md
3. A. Aminian & A. Xu, "People You May Know" (Machine Learning System Design Interview, ch. 11), ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/people-you-may-know
4. shafaypro, "People You May Know" (system_design/people_you_may_know.md), CrackingMachineLearningInterview, GitHub, n.d. https://github.com/shafaypro/CrackingMachineLearningInterview/blob/master/system_design/people_you_may_know.md
5. jsheng0901, "Friends/Follower Recommendation (PYMK)" (mlsd_pymk.md), Machine-Learning-Implementation, GitHub, n.d. https://github.com/jsheng0901/Machine-Learning-Implementation/blob/main/machine_learning_system_design/mlsd_pymk.md
6. M. C. J. Kao, "Machine Learning System Design Interview Extension: People You May Know", Medium (clipped in alexsnow348/learning-notes), GitHub, 2024. https://github.com/alexsnow348/learning-notes/blob/main/learning-notes/machine-learning-and-ai-notes/ml-interview/People%20You%20May%20Know.md
7. Twitter/X, "Follow Recommendations Service" README, the-algorithm, GitHub, 2023. https://github.com/twitter/the-algorithm/blob/main/follow-recommendations-service/README.md

8. Twitter/X, "the-algorithm" repository, GitHub, 2023. https://github.com/twitter/the-algorithm
9. P. Gupta, A. Goel, J. Lin, A. Sharma, D. Wang, R. Zadeh, "WTF: The Who to Follow Service at Twitter", WWW, 2013. https://web.stanford.edu/~rezab/papers/wtf_overview.pdf
10. F. Borisyuk et al., "LiGNN: Graph Neural Networks at LinkedIn", KDD / arXiv, 2024. https://arxiv.org/abs/2402.11139
11. Snap Research, "Embedding Based Retrieval in Friend Recommendation", SIGIR, 2023. https://research.snap.com/publications/embedding-based-retrieval-in-friend-recommendation.html
12. Snap Research, "Improving Embedding-Based Retrieval in Friend Recommendation with ANN Query Expansion", research.snap.com, n.d. https://research.snap.com/publications/improving-embedding-based-retrieval-in-friend-recommendation-with-ann-query-expansion.html
13. LinkedIn Engineering, "Optimizing PYMK for equity in network creation", LinkedIn Engineering Blog, 2021. https://engineering.linkedin.com/blog/2021/optimizing-pymk-for-equity-in-network-creation
14. L. Backstrom & J. Leskovec, "Supervised Random Walks: Predicting and Recommending Links in Social Networks" (Facebook data), WSDM / arXiv, 2011. https://arxiv.org/abs/1011.4071
15. W. L. Hamilton, R. Ying, J. Leskovec, "Inductive Representation Learning on Large Graphs" (GraphSAGE), NeurIPS / arXiv, 2017. https://arxiv.org/abs/1706.02216
16. G. Saint-Jacques et al. (LinkedIn), "Using Ego-Clusters to Measure Network Effects at LinkedIn", arXiv, 2019. https://arxiv.org/abs/1903.08755
17. K. Pham, "machine-learning-interview" (checked: no PYMK chapter), GitHub, 2021. https://github.com/khangich/machine-learning-interview
18. C. Huyen, "machine-learning-systems-design" booklet (checked: no PYMK question), GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design
19. A. Lerer et al., "PyTorch-BigGraph: A Large-scale Graph Embedding System", Facebook AI / SysML, 2019. https://github.com/facebookresearch/PyTorch-BigGraph
20. Twitter/X, FRS candidate_sources directory, the-algorithm, GitHub, 2023. https://github.com/twitter/the-algorithm/tree/main/follow-recommendations-service/common/src/main/scala/com/twitter/follow_recommendations/common/candidate_sources

> Research note (review pass): web search was exhausted and non-GitHub hosts were unreachable. [1], [2], [4]-[7], [20] were re-read by cloning the repositories (alirezadir: "1 B total users, on avg. 10000 connection per user"; Kao: active users "in the last, say, 30 days"; FRS candidate-source folders and p(follow)/p(engage) score). [9]-[16], [19] are cross-checked against verified chapters of this repository (recsys-system-design ch. 2, 7, 23). [3] could not be fetched; its URL follows ByteByteGo's chapter-URL pattern. QPS and latency splits are assumptions.

06. Design an Ad Click-Through-Rate Prediction and Ad Ranking System (with Auction and Calibration)

> Prompt variants: "Ad click prediction on social platforms" (ByteByteGo), "Ad prediction system" (Educative), "Ads click prediction / ads ranking" (alirezadir), "Ad Click Prediction" (Khang Pham), "Design the ads ranking system for a feed" (Meta-style phrasing).

Company tags

Company	Evidence	Source
Meta (Facebook / Instagram)	The textbook production system for this prompt (GBDT+LR, NE metric, calibration). Ads/feed ranking is a commonly reported Meta MLE design theme	[7] [8] [21] [22]
Google	Search ads CTR at scale (FTRL-Proximal LR, isotonic calibration layer, Ad Rank); DCN-V2 paper reports production use in Google rankers	[9] [23] [27]
Snap	Engineering write-up on Snapchat ad ranking (listed in [24])	[12] [24]
LinkedIn	Deep-learning ads CTR model; ads allocation in feed via constrained optimisation	[13] [24] [25]
Twitter / X	Ads engagement with delayed feedback, and prediction of ad-request value	[4] [11] [14] [24]
Pinterest, Etsy, Wayfair	Lookalike ad targeting, real-time ads personalisation, ads bidding (all listed in [24])	[15] [16] [17] [24]

Portals that cover it


- ByteByteGo / Aminian & Xu, *ML System Design Interview*, chapter "Ad Click Prediction on Social Platforms" [1]
- Educative, *Grokking the Machine Learning Interview*, "Ad Prediction System" module [2]
- Educative / Khang Pham, *Machine Learning System Design*, plus the khangich GitHub "Ad Click Prediction" case and Adtech reading list [3] [4]
- alirezadir/Machine-Learning-Interviews (AIMLInterviews), `mlsd-ads-ranking.md` "Ads click prediction" [5] [6]
- Hello Interview (recsys pattern), Exponent / Aced, IGotAnOffer, Prepfully: generic ranking frameworks used for this prompt [18] [19] [20] [21]

Requirements & scale

Dimension	Value	Source / status
Business goal	Maximise long-term revenue = advertiser value + user experience (not raw CTR)	[1] [5] [22]
Functional	For each ad slot in a feed or search page, pick and price ads; predict P(click), optionally P(conv)	[5]
ML task	Pointwise LTR: binary classification on (user, ad, context)	[5]
Label	Click within t seconds of impression = 1, else 0; "hide/report ad" = negative signal	[5]
Users / ads	1B+ DAU; 10M+ active ads, millions of advertisers	typical assumption
QPS	100k-1M ad requests/s at peak (Khang Pham's worked case assumes 4k/s); ranker scores 100s-1000s ads per request	typical assumption; [4]
Latency	Ads pipeline p99 ~100-150 ms total, ranker ~10-30 ms	typical assumption; 150 ms in [4]
Base rate	CTR is low (often ~1-2% or less), so classes are very imbalanced	[4] [7]
Freshness	New ads and campaigns arrive constantly; stale models lose accuracy daily	[7] [9]
Hard constraints	Calibrated probabilities (they feed the auction and billing); budget pacing; privacy; ad policy	[7] [9] [22]

DIAGRAM 1: online serving path

Diagram 1. Ad request to response: targeting retrieval, filtering, pCTR/pCVR ranking, auction and pricing, with feature store, model store and logging (synthesised from [1] [5] [7] [12] [22])



Funnel numbers (typical assumption)

Stage	In -> out	Model	Budget
Targeting + retrieval	10M -> 10k	Inverted index + ANN embeddings	10-20 ms
Filtering	10k -> 2k	Rules (budget, frequency cap, policy)	2-5 ms
Light ranking	2k -> 200	Two-tower / small GBDT/DNN	5-10 ms
Heavy ranking + calibration	200 -> 200 scored	DCN-V2 / DeepFM / MTL DNN	10-30 ms
Auction + re-rank	200 -> 1-5 slots	eCPM, GSP/VCG, business rules	1-5 ms

DIAGRAM 2: offline training and data pipeline

Diagram 2. Logging, online joining with delayed feedback, negative downsampling, training, calibration fit, evaluation and deployment (synthesised from [5] [7] [9] [11])




DIAGRAM 3: model architecture

Diagram 3. Multi-task CTR/CVR ranker: embeddings, explicit cross network plus deep tower, shared bottom, task heads, calibration and eCPM (DCN-V2 / DeepFM / ESMM style; [1] [5] [26] [27] [30])





DIAGRAM 4: the real system (Facebook, He et al. 2014)

Diagram 4. Facebook's hybrid GBDT + logistic regression CTR model with online joiner and online learning [7] [8]



Data & labels

Item	Choice	Notes / source
Positive	Click within t s of impression	[5] [7]
Negative	Impression with no click by end of window; hide/report as strong negative	[5]
Conversion label	Purchase/install after click, arrives hours-days later	delayed feedback [11]
Window t	Trade-off: short = fresher but more false negatives; long = accurate but stale	[7] [11]
Imbalance	Downsample negatives at rate w; recalibrate q = p / (p + (1-p)/w)	[7]
Position bias	Log position; use as training feature and fix it at serve time, or use a shallow position tower	typical practice
Leakage	Point-in-time feature joins; split train/test by time, not randomly	[5]

Features

Group	Examples	Encoding
Ad	ad id, advertiser id, campaign, category, creative image/text/video	Embeddings; pretrained encoders (e.g. SimCLR-style) [5]
Ad engagement	impressions, clicks, CTR at ad/advertiser/campaign level, 1h/1d/7d	Dense, log-scaled, smoothed for new ads
User	demographics, location, device, language	Embeddings / one-hot
User history	historical CTR, last N clicked ads/categories	Sequence + attention
User-ad cross	user x ad-category CTR, previous impressions of this ad (fatigue)	Crosses or learned by DCN/FM
Context	slot/position, time of day, surface (feed/stories/search), query	One-hot / embeddings

Group	Examples	Encoding
Bid / objective	bid type and objective (not usually a CTR feature; used in auction)	Kept out of pCTR to avoid bias

Model choices (baseline -> advanced)

Model	Strengths	Weaknesses	Source
Logistic regression (+ hashing)	Fast, calibrated-ish, easy online learning (FTRL)	No interactions without manual crosses	[5] [9]
LR + manual feature crosses	Captures key pairwise interactions	Manual, combinatorial, sparse	[1] [5]
GBDT	Strong on dense features, interpretable	Poor with huge sparse IDs; no continual training	[5]
GBDT + LR	Trees as feature transform; LR learns online	Two systems to maintain	[7]
Factorization Machine (FM/FFM)	Learned pairwise interactions via embeddings	Only 2nd-order	[1] [5]
Wide & Deep / DeepFM	Memorisation + generalisation, no manual crosses	Bigger, harder to calibrate	[26] [28]
DCN / DCN-V2	Explicit bounded-degree crosses + deep tower; production use at Google	Tuning cross depth	[27]
DLRM / DIN / MMoE multi-task	Huge embedding tables, user-sequence attention, joint pCTR/pCVR	Infra cost, GPU serving	[29] [30]

Loss

Loss	Use
Binary cross-entropy (log loss)	Default for pCTR; directly optimises calibrated probability [1] [5]
Weighted BCE / importance weights	Correct for negative downsampling [7]
Multi-task sum: L = BCE(click, pCTR) + BCE(click & conv, pCTR x pCVR) over all impressions	ESMM: pCVR learned implicitly, avoiding sample-selection bias and click sparsity [30]
Pairwise / listwise (optional)	Improves ordering but breaks calibration; usually avoided as the only loss because the auction needs absolute probabilities
L1/L2 + FTRL regularisation	Sparsity for huge hashed feature spaces [9]

Calibration

Topic	Detail	Source
Why	eCPM = bid x pCTR: a 10% overestimate means overcharging/mis-ranking advertisers	[7] [9] [22]
Calibration ratio	sum(predicted pCTR) / sum(actual clicks); target 1.0 overall and per slice	[7]
Downsampling fix	q = p / (p + (1-p)/w), w = negative sampling rate	[7]

Topic	Detail	Source
Post-hoc methods	Google: fit tau(p) = gamma x p^kappa by Poisson regression, or piecewise-linear isotonic map per data slice; Platt / temperature scaling for DNNs	[9] [31]
Monitoring	Calibration plots by bucket, per advertiser; alert when ratio drifts beyond about +-5%	typical assumption
Training-time subsampling	Google keeps all clicked queries and a fraction r of others, weighting kept negatives by 1/r so the loss stays unbiased	[9]

Auction and ranking score

Concept	Formula / rule	Source
Expected value (CPC bid)	eCPM = 1000 x bid_CPC x pCTR	standard practice
Optimised CPM / CPA	value = bid_CPA x pCTR x pCVR	[12]
Meta "total value"	advertiser bid x estimated action rate + ad quality	[22]
Google "Ad Rank"	bid, ad quality (expected CTR, relevance, landing page), thresholds, context	[23]
Pricing	GSP: pay the minimum needed to keep the slot; VCG: pay the externality imposed; plus reserve prices	standard practice
Re-rank / policy	Ad load limits, advertiser diversity, frequency caps, pacing multiplier on bid	[1] [5]
Ads allocation in feed	Choose ad slots in an organic feed by maximising revenue subject to user-engagement constraints (LinkedIn)	[25]
Autobidding / pacing	Platform adjusts bids per auction to hit advertiser budget and CPA/ROAS goals	[17]

Offline metrics

Metric	Why	Source
Normalised entropy (NE) / normalised cross-entropy	Log loss divided by the entropy of the background CTR; lower is better	[1] [7]
Log loss	Measures probability quality (needed by the auction)	[5]
ROC-AUC / PR-AUC	Ranking quality; insensitive to calibration, so do not use alone	[7]
Calibration ratio, reliability diagram	Absolute probability correctness	[7]
Sliced metrics	New ads, new users, country, surface, advertiser size	typical practice

Online metrics / A-B

Metric	Type
Revenue per mille (RPM) / revenue lift	Primary business metric [5]
CTR, conversion rate	Engagement [5]

Metric	Type
Advertiser ROI / cost per action, advertiser retention	Advertiser health
Hide/report rate, organic engagement, session time	User-experience guardrails [5]
Calibration in production, auction-price changes	Safety
A/B design	Randomise users; watch budget-split interference between arms (advertiser budgets are shared), so use budget-split or advertiser-side experiments

Serving & latency budget

Component	Budget (p99)	Technique
Feature fetch	5-10 ms	In-memory KV store, batched multi-get, cached ad features
Retrieval	10-20 ms	Inverted targeting index + ANN
Light ranker	5-10 ms	Two-tower dot product, ad embeddings precomputed
Heavy ranker	10-30 ms	GPU/CPU batch inference, quantised embeddings, model distillation
Auction + logging	<5 ms	In-process; async log write
Total	~100 ms	Timeouts with fallback to a cached or simpler model

Monitoring

What	Signal
Prediction drift	Mean pCTR vs observed CTR per hour/slice (calibration ratio)
Feature drift / missing	Null rate, distribution shift (PSI) per feature; online/offline skew check
Data pipeline	Joiner lag, label delay, event loss
Business	Revenue, spend pacing, advertiser complaints, auction clearing price
Model freshness	Hours since last successful update; NE on latest hour

What the production papers add (often missed in portal answers)

Item	Detail	Source
Online joiner click coverage	Too short a wait window loses clicks and biases empirical CTR low; too long delays data and costs memory	[7]
Probabilistic feature inclusion	Add a new sparse feature only after it is seen n times (counting Bloom filter) or with probability p (Poisson) to save RAM	[9]
Progressive validation	Score each example before training on it in online learning; no separate holdout needed	[9]
Confidence estimates	Per-prediction uncertainty to drive exploration and guard bids on rare ads	[9]
Automated feature management	Feature metadata, owners and automatic alerts on signal changes across many models	[9]

Item	Detail	Source
Model size vs trees	Fewer boosted trees keep latency and memory down at small NE cost	[7]

Failure modes

Failure	Mitigation
Mis-calibration after downsampling or a model swap	Recalibration step; calibration gate in deployment [7]
Cold-start ads (no history)	Content embeddings, advertiser priors, exploration budget (bandits / boosted bids)
Delayed conversions labelled as negative	Delayed-feedback model, longer windows, label correction [11]
Training-serving skew	Log features at serve time; reuse those logs for training [7]
Feedback loop / selection bias (only shown ads get labels)	Exploration traffic, inverse propensity weighting
Ad fatigue	Frequency caps; impression-count features [5]
Click fraud / bots	Invalid-traffic filters before labelling
Catastrophic forgetting with continual training	Replay buffer, periodic full retrain [5]
Privacy changes (lost cross-app signals)	On-platform signals, aggregated conversion APIs, modelled conversions

Interviewer follow-ups

- Why must pCTR be calibrated, and how would you measure and fix miscalibration? [7]
- You downsampled negatives to 1%. How do you correct the predicted probabilities? [7]
- Why is AUC not enough as an offline metric for ads? What is normalised entropy? [7]
- How do you pick the click attribution window t, and how do you handle delayed conversions? [11]
- How does the auction combine bid, pCTR, pCVR and quality? GSP vs VCG? [22] [23]
- How do you rank ads for a CPA (conversion) advertiser vs a CPC advertiser?
- Walk through LR -> FM -> DeepFM -> DCN. Why do plain MLPs struggle with sparse crosses? [1] [5]
- How fresh must the model be? Online learning vs daily retrain trade-offs? [7] [9]
- How do you handle a new ad or new advertiser with no history (cold start)?
- How do you deal with position bias in click logs?
- How do you A/B test when the treatment and control arms share advertiser budgets?
- How would you keep the heavy ranker within 30 ms for 1,000 candidates?
- How do you trade off ad revenue against user experience (ad load, hides)?
- What happens to the system when third-party tracking signals disappear?
- How do you prevent the model from learning from fraudulent clicks?
- How long should the online joiner wait before labelling a no-click, and what does that do to click coverage? [7]
- How would you add millions of new sparse features without blowing up model RAM? [9]

- Where should ads go in an organic feed, and how many? [25]

Portal comparison

Portal	Framing	Model path	Distinctive emphasis
ByteByteGo (Aminian & Xu) [1]	"Ad click prediction on social platforms", pointwise LTR	LR -> feature crossing -> GBDT -> GBDT+LR -> NN -> DCN / FM / DeepFM	NCE metric, continual learning, targeting-based candidate generation
alirezadir AIMLInterviews [5]	Follows [1] closely, in outline form	LR baseline, then DCN and DeepFM	Fatigue period, hide-rate metric, catastrophic forgetting, leakage; no auction section
Educative Grokking ML Interview [2]	"Ad prediction system": ad selection funnel + engagement prediction	LR / GBDT -> NN, online learning	Funnel stages and incremental training (from course outline)
Khang Pham (Educative + GitHub) [3] [4]	"Ad Click Prediction" case study	Paper-driven: Facebook GBDT+LR, Google FTRL	Adtech reading list: delayed feedback, entity embeddings
Hello Interview / Exponent / IGotAnOffer [18] [19] [20]	Generic ranking or recsys template applied to ads	Two-stage retrieve + rank	Delivery framework and time-boxing rather than ads detail
Company papers [7] [9] [12]	Production reality	GBDT+LR, FTRL-LR, DCN, MMoE	Calibration, NE, freshness, auction value

References

1. A. Aminian & A. Xu, "Ad Click Prediction on Social Platforms" (Machine Learning System Design Interview, ByteByteGo), bytebytego.com, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/ad-click-prediction-on-social-platforms
2. Educative, "Grokking the Machine Learning Interview" (Ad Prediction System module), educative.io, n.d. https://www.educative.io/courses/grokking-the-machine-learning-interview
3. Educative / K. Pham, "Machine Learning System Design" (course), educative.io, 2021. https://educative.io/courses/machine-learning-system-design/introduction
4. K. Pham, "machine-learning-interview" (Ad Click Prediction case; Adtech list), GitHub, 2021. https://github.com/khangich/machine-learning-interview
5. A. Dirafzoon, "Ads click prediction" (mlsd-ads-ranking.md), alirezadir/AIMLInterviews, GitHub, 2023. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/mlsd-ads-ranking.md
6. alirezadir, "ML System Design" template (lists ads click prediction and ads serving cases), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md
7. X. He et al., "Practical Lessons from Predicting Clicks on Ads at Facebook", ADKDD, 2014. https://quinonero.net/Publications/predicting-clicks-facebook.pdf
8. Facebook Research, same paper (PDF mirror), research.fb.com, 2014. https://research.fb.com/wp-content/uploads/2016/11/practical-lessons-from-predicting-clicks-on-ads-at-facebook.pdf

9. H. B. McMahan et al., "Ad Click Prediction: a View from the Trenches", KDD / Google, 2013. https://storage.googleapis.com/pub-tools-public-publication-data/pdf/41159.pdf
10. alirezadir, "ML at Companies" (ads and auction resources), GitHub, 2025. https://github.com/alirezadir/AIMLInterviews/blob/main/src/MLSD/ml-companies.md
11. Twitter Engineering, "Improving engagement on digital ads with delayed feedback", blog.twitter.com, 2019. https://blog.twitter.com/engineering/en_us/topics/insights/2019/improving-engagement-on-digital-ads-with-delayed-feedback.html
12. Snap Engineering, "Machine Learning for Snapchat Ad Ranking", eng.snap.com, 2022. https://eng.snap.com/machine-learning-snap-ad-ranking
13. LinkedIn Engineering, "Challenges and practical lessons from building a deep-learning-based ads CTR prediction model", engineering.linkedin.com, 2022. https://engineering.linkedin.com/blog/2022/challenges-and-practical-lessons-from-building-a-deep-learning-b
14. Twitter Engineering, "Using machine learning to predict the value of ad requests", blog.twitter.com, 2020. https://blog.twitter.com/engineering/en_us/topics/insights/2020/using-machine-learning-to-predict-the-value-of-ad-requests
15. Pinterest Engineering, "The machine learning behind delivering relevant ads", Medium, 2021. https://medium.com/pinterest-engineering/the-machine-learning-behind-delivering-relevant-ads-8987fc5ba1c0
16. Etsy, "Leveraging Real-Time User Actions to Personalize Etsy Ads", arXiv, 2023. https://arxiv.org/pdf/2302.01255.pdf
17. Wayfair Tech, "Evolution of Ads Bidding at Wayfair", aboutwayfair.com, 2021. https://www.aboutwayfair.com/careers/tech-blog/evolution-of-ads-bidding-at-wayfair
18. Hello Interview, "Recommendation Systems (ML System Design pattern)", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/patterns/recommendation-systems
19. Aced (formerly Exponent), "Machine Learning System Design Interview (2026 Guide)", aced.io, 2026. https://www.aced.io/blog/machine-learning-system-design-interview-guide
20. IGotAnOffer, "Machine Learning (ML) System Design Interview (examples, answers, prep)", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/machine-learning-system-design-interview
21. Prepfully, "Meta Machine Learning Engineer interview questions", prepfully.com, 2025. https://prepfully.com/interview-questions/meta/machine-learning-engineer?page=8
22. Meta Business Help Center, "About ad auctions", facebook.com, n.d. https://www.facebook.com/business/help/430291176997542
23. Google Ads Help, "About Ad Rank", support.google.com, n.d. https://support.google.com/google-ads/answer/1722122
24. Engineer1999, "A Curated List of ML System Design Case Studies" (ads section), GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies
25. J. Yan et al., "Ads Allocation in Feed via Constrained Optimization" (LinkedIn), KDD, 2020. https://dl.acm.org/doi/abs/10.1145/3394486.3403391
26. H. Guo et al., "DeepFM: A Factorization-Machine based Neural Network for CTR Prediction", arXiv, 2017. https://arxiv.org/abs/1703.04247
27. R. Wang et al., "DCN V2: Improved Deep & Cross Network and Practical Lessons for Web-scale Learning to Rank Systems", arXiv, 2020. https://arxiv.org/abs/2008.13535

28. H.-T. Cheng et al., "Wide & Deep Learning for Recommender Systems", arXiv, 2016. https://arxiv.org/abs/1606.07792
29. M. Naumov et al., "Deep Learning Recommendation Model for Personalization and Recommendation Systems" (DLRM), arXiv, 2019. https://arxiv.org/abs/1906.00091
30. X. Ma et al., "Entire Space Multi-Task Model: An Effective Approach for Estimating Post-Click Conversion Rate" (ESMM), arXiv, 2018. https://arxiv.org/abs/1804.07931
31. C. Guo et al., "On Calibration of Modern Neural Networks", arXiv, 2017. https://arxiv.org/abs/1706.04599

> Research note: in this review, non-GitHub hosts were blocked by the network proxy and the web-search budget was exhausted. [4] [5] [6] [10] [24] were re-read from GitHub; the texts of [7] and [9] were checked from PDF mirrors, confirming NE, calibration ratio, online joiner, downsampling recalibration, Poisson/isotonic calibration and subsampling weights. URLs for [7]-[9], [11]-[17] and [31] are confirmed as links in [4] [10] [24]; their pages were not loaded. [1]-[3], [18]-[23] and [26]-[30] are cited from prior knowledge. An unsupported TikTok/Amazon/Reddit/Uber tag row was removed. Scale numbers marked "typical assumption" are not sourced.

07. Design Product Search Ranking for an E-commerce Site (Amazon Search), Including Query Understanding

> Prompt as usually given: "A user types a query into the Amazon (or Walmart, Etsy, Flipkart) search box. Design the ML system that returns the most relevant products, ranked to maximise purchases." Variants: "design a search ranking system", "improve product search recall", "design Airbnb search ranking", "design typeahead / query autocomplete" (a sub-problem).

Company tags

Company (reported)	Where it was reported	Notes
Amazon	Community-compiled Amazon MLE interview process [22]	Sample ML system design prompt: "Design a search retrieval and ranking pipeline, including online experiments and position-bias correction" [22]; Stores "search and personalization" team owns product search ranking [22]
Airbnb	Khang Pham case list [5]; Chip Huyen exercise 9 [7]	"Display top 10 results when a user searches for rental listings in a certain location" [7]
Google (adjacent, not confirmed)	Chip Huyen exercises 5-6 use Google-style "related searches" and Google Images text-to-image search [7]	Web/image-search framing of the same retrieve-then-rank funnel
Walmart, Etsy, eBay	Not confirmed as interview prompts; they publish the production systems this question mirrors [14] [15] [19]	Use their papers as "real system" talking points

Portals and sources that cover it

Portal	What it covers	Link
alirezadir / AIMLInterviews	Full e-commerce text-search case: QU, retrieval, 2-stage LTR, blender, filter [1] [2]	[1]
Educative, Grokking the ML Interview	"Search Ranking" chapter: layered funnel, document selection, LambdaMART, NDCG [3] [4]	[3]
Khang Pham (Educative / mlengineer.io)	"Airbnb Search ranking" case study plus Amazon/Airbnb reading list [5] [6]	[5]
Chip Huyen, ML Systems Design	Exercises: Airbnb search ranking, related searches, image search, autocomplete [7]	[7]
ByteByteGo (Aminian & Xu)	No e-commerce chapter; closest are "Visual Search" and "YouTube Video Search" (text + visual retrieval and fusion) [29]	[29]

Portal	What it covers	Link
Hello Interview / Exponent	Generic retrieval-then-rank pattern and framework applied to search (not re-verified in this pass) [26] [27]	[26]


Research note: in the review pass only github.com pages were reachable (arxiv.org, amazon.science, hellointerview.com, igotanoffer.com did not resolve). Verified against the live page: [1] [4] [5] [6] [7] [20] [22] [31] and the ESCI data repo [10]. Paper URLs were cross-checked against the applied-ml index [20]. Company tags from community lists are indicative, not confirmed; three unsupported tag sources were removed.

Requirements & scale

Dimension	Value	Source
Functional	Text query in, ranked list of products out (SERP); filters/facets; ad auction out of scope (sponsored slots only blended in)	[1]
Business goal	Higher CTR and conversion (purchases per search)	[1]
Personalization	Optional in v1 ("not required" in [1]); add in v2 via user features / personalized EBR [14]	[1] [14]
Users	50M DAU (alirezadir assumption); Amazon-scale 300M+ users (typical assumption)	[1]
Catalog	[1] writes "from 100 B to 100k" (likely a typo); 100M-1B products is a typical assumption	[1]
Query volume	5M queries/day in [1]; Amazon-scale ~10k-50k QPS peak (typical assumption)	[1]
Latency	End-to-end p99 < 200 ms; ranker < 50 ms; feature fetch < 10 ms [4]	[4] + assumption
Funnel sizes	Catalog -> ~100k (retrieval) -> stage-1 -> ~500 (stage-2 output) [1]; [4] uses 500 as the stage-1 window; top 10-50 shown	[1] [4]
Freshness	New products searchable in minutes (index); price/stock real time; models retrained daily-weekly	Typical assumption
Languages / locales	Multi-locale (ESCI covers US, ES, JP)	[10]

DIAGRAM 1: online serving path

Diagram 1. Query to SERP: query understanding, hybrid retrieval, filtering, two-stage learning-to-rank, blending and business rules, with feature store, model store and logging (synthesised from [1] [3] [8] [13])



Funnel and latency (typical assumption, numbers from [1] [4] where cited)

Stage	In -> out	Model	p99 budget
Query understanding	1 query -> rewritten query + attrs + embedding	Spell model, NER, classifier, query tower (cached for head queries)	10-15 ms
Retrieval	100M-100B -> ~100k [1]	BM25 + ANN + category	20-30 ms
Filtering	~100k -> ~20k	Rules + lookups	5 ms
Stage-1 rank	~20k -> ~500 (500 per [4])	LR / small MART, pointwise, AUC [1]	10 ms
Stage-2 rank	~500 -> 50	LambdaMART / LambdaRank NN [1]	30-40 ms
Re-rank + blend	50 -> 48 slots	Rules + diversity	5 ms

DIAGRAM 2: offline training and data pipeline

Diagram 2. Search logs to labels (graded engagement + human ESCI judgements), feature joins with point-in-time correctness, LTR training, offline NDCG gate, registry and interleaving/A-B rollout (synthesised from [1] [3] [9] [10] [11])



DIAGRAM 3: model architecture

Diagram 3a. Retrieval: Amazon "Semantic Product Search" style two-tower model [8] (shared token embeddings over word unigrams, bigrams and character

trigrams; average pooling; trained on purchase / impression / random negatives with a 3-part hinge loss)




Diagram 3b. Ranking: multi-task learning-to-rank DNN with LambdaRank-style listwise objective (synthesised from [1] [11] [17]; Airbnb's GBDT -> NN -> deep NN path [11])




Diagram 3c. Query understanding stack (synthesised from [1] [10] [18] [23]; rewrite step learned from reformulation logs in [23])





DIAGRAM 4: the real systems this mirrors

Diagram 4. Production references: Amazon (GBDT LTR + semantic retrieval), Airbnb (NN LTR evolution), Facebook/Etsy/Walmart (embedding-based retrieval) [8] [9] [11] [13] [14] [15]



Data & labels

Source	Label / use	Caveats
Search logs (implicit)	Graded: impression 0, click 1, dwell > T 2, add-to-cart 3, purchase 4 [1]	Position bias, presentation bias, only shown items labelled
Purchases	Strongest positive; Amazon trains on purchases [8] [9]	Sparse, delayed; some purchases look irrelevant to the query [28]
Impressed-not-purchased	Hard-ish negatives / middle band [8]	Not truly irrelevant
Random products	Easy negatives (or page 10+ results) [1] [8]	Too easy alone; add hard negatives [13]
Human judgements	ESCI 4-class (Exact, Substitute, Complement, Irrelevant): 130k queries, 2.6M judgements, 3 locales [10]	Costly; [1] estimates 100k queries x 10 results x 10 raters = 10M and rejects it as not scalable

Source	Label / use	Caveats
Catalog	Product tower inputs, attribute tags for QU	Noisy seller-entered text
Window	>= 1 week to cover weekly cycle; temporal split [1]	Holiday seasonality

Features

Group	Examples	Freshness
Query	Length, category distribution, head/torso/tail bucket, intent, historical CTR, embedding [1] [4]	Daily (head cached)
Product	Price, rating, #reviews, sales rank, stock, delivery speed, title/image embeddings, age	Price/stock real time; rest daily
Query-product	BM25 / TF-IDF unigram+bigram, attribute match (brand, color, size), query-category match, historical (q,p) CTR/CVR, embedding cosine [1] [4]	Hourly-daily
User	Past purchases/views in category, brand affinity, price sensitivity, Prime	Near real time
Context	Device, locale, time, previous queries in session [1]	Request time
Position (train only)	Displayed rank	Fixed at serving

Model choices (baseline -> advanced)

Stage	Baseline	Advanced	Tradeoff
QU	Rules + dictionaries + edit-distance spell	Neural query rewriting from reformulation logs (Amazon QUEEN [23]), BERT NER, LLM rewrites (offline for head queries)	Quality vs latency; cache head
Retrieval	Inverted index + TF-IDF/BM25, weighted linear relevance (term match 0.5, popularity 0.125, intent 0.0625) [1]; same signals unweighted in [4]	Two-tower EBR [8], personalized EBR [13] [14], hybrid with lexical [15]	Recall on tail vs precision on exact attrs
Stage-1	LR / small GBDT pointwise, AUC [1] [4]	Distilled small NN	Microseconds per item [1]
Stage-2	LambdaMART (GBDT) [1] [17] [31]	Multi-task DNN with LambdaRank loss [11] [25]; Etsy moved search ranking from GBDT to DNN [19]; cross-encoder (BERT) on top-50	DNN needs feature normalization and more data [11]
Re-rank	Business rules, dedupe	Diversity model [12], explore/exploit	Relevance vs diversity
Seasonality	Recency-weighted retrain	Seasonal-relevance model as ranking feature (Amazon [24])	Extra model to maintain

Loss

Model	Loss	Why
Two-tower	In-batch softmax / contrastive; 3-part hinge with purchase/impression/random [8]	Learn semantic match at scale
Stage-1	Binary cross-entropy (pointwise) [1]	Cheap, calibrated
Stage-2	LambdaRank / LambdaMART: pairwise with delta-NDCG weights [17]	Optimises ranking metric directly
Multi-task heads	Sum of BCE per head (click, ATC, buy)	Dense click signal helps sparse purchase
Debiasing	Inverse propensity weighting; unbiased LambdaMART [33] (XGBoost `lambdarank_unbiased` [31])	Remove position bias

Offline metrics

Metric	Stage	Note
Recall@k (k=100, 1000)	Retrieval	Did the purchased item enter the funnel?
NDCG@10	Ranking	Graded labels 0-4; chosen because relevance is non-binary [1] [4]
MRR	Ranking	Position of first purchased item [1]
AUC / log loss	Stage-1, heads	Pointwise quality [1] [4]
ESCI-judged NDCG / precision	Whole SERP	Human relevance, catches "buyable but irrelevant" [10]
Slices	All	Head vs tail queries, locale, new products, category

Online metrics / A-B

Metric	Type	Note
Conversion rate (purchases / search)	Primary	Business goal [1]
Revenue / GMV per search	Primary	Watch price-mix shift
CTR	Secondary	Prone to clickbait [1]
Successful session rate (dwell > T or ATC)	Secondary	[1] [4]
Zero-result rate, reformulation rate, time-to-first-click	Guardrail	QU quality signals
Latency p99, error rate	Guardrail	SLA
Interleaving	Fast pre-test	Higher sensitivity for ranking comparisons

Serving & latency budget

Component	Choice	Budget
QU	Cached results for head queries (~top 1M queries); online models for tail	10-15 ms
ANN	HNSW / PQ-quantized index, sharded by product id [14]	10-20 ms
Inverted index	Sharded Lucene/Elasticsearch-style	10-20 ms (parallel with ANN)
Feature fetch	Online KV (Redis/DynamoDB) [4]	< 10 ms [4]

Component	Choice	Budget
Stage-1 / Stage-2	CPU GBDT; GPU or CPU-optimised DNN, batch per request	10 ms / 30-40 ms
Total	p99	< 200 ms (assumption)

Monitoring

What	Signal	Action
Input drift	Query distribution, new tokens, category mix (holidays)	Refresh QU dictionaries, retrain
Feature health	Null rates, staleness of price/stock	Alert, fallback defaults
Quality	Zero-result rate, NDCG on daily human-judged sample [10]	Rollback
Train-serve skew	Logged serving features vs offline recomputed	Log features at serve time
Index	ANN recall vs brute force on sample, index age	Rebuild
Business	Conversion per search by slice	Alert on drops

Failure modes

Failure	Cause	Mitigation
Accessories outrank main product ("iphone" -> cases)	Click/purchase popularity beats relevance	ESCI relevance model as feature/gate [10]; product-type match
Inappropriate items on SERP	Offensive/adult products match query	P(inappropriate) filter model (LR/MART/DNN) before the blender [1]
Zero results on tail queries	Lexical mismatch, typos	Spell correct, query relaxation, semantic retrieval [8] [15]
Attribute violations ("red dress" shows blue)	Semantic retrieval ignores exact attrs	Hybrid lexical + attribute filters [15] [16]
Rich-get-richer	Feedback loop, position bias	IPW, exploration slots, position feature [33]
Cold-start products	No engagement stats	Content features, embedding retrieval, boost new items
Seasonality	Holiday query shift ("costume" in October)	Short retrain cycle, seasonal-relevance feature [24]
Spam / keyword stuffing	Sellers gaming titles	Spam classifier, quality features
Latency blow-up on broad queries	Huge candidate sets	Cap per-source candidates, early termination

Interviewer follow-ups

- How do you build relevance labels? Clicks vs purchases vs human ESCI judgements, and how do you combine them? [1] [10]
- How do you correct position bias in click logs (IPW, position-as-feature, randomized swaps)? [22] [33]
- Walk through query understanding for "apple watch band 41mm black": which models, in what order?
- Why two-stage ranking instead of one heavy model? Where does the cutoff (500) come from? [1] [4]

- Lexical vs semantic retrieval: when does each fail, and how do you merge them? [8] [15]
- How do you handle tail queries and zero-result searches?
- Pointwise vs pairwise vs listwise loss: why LambdaMART for stage 2? [17]
- Why can NDCG go up offline while conversion goes down online?
- How do you rank a brand-new product with no history?
- How would you add personalization without hurting relevance? [13] [14]
- How do you blend sponsored products with organic results?
- How do you design the A/B test; why might interleaving be used first?
- Real-time features for product search (price, stock): architecture and skew?
- How would you learn query rewrites from reformulation sessions? [23]
- How do you handle seasonal queries whose intent shifts over the year? [24]
- How would you blend text-search results with visual search in one SERP? [1]
- How would you use an LLM here (query rewriting, relevance labelling, cross-encoder distillation) within latency?
- How do you keep the ANN index fresh as millions of products change daily?

Portal comparison

Portal	Framing	Retrieval	Ranking	Metrics	Distinctive
alirezadir [1]	E-commerce text search, 50M DAU, CTR + conversion goal	Inverted index + expansion; weighted linear score	Stage-1 pointwise LR/MART -> stage-2 LambdaMART	NDCG offline; conversion, CTR, success session online	Graded 0-4 labels, blender with visual search, P(inappropriate) filter
Educative Grokking [3] [4]	General web search (scope, scale, personalization)	Document selection over inverted index	Layered funnel; stage-1 AUC, stage-2 LambdaMART	NDCG; CTR, successful session rate	Feature taxonomy; < 10 ms feature store (Redis/DynamoDB) [4]
Khang Pham [5] [6]	Airbnb search ranking (booking likelihood)	Location-based candidates	Binary classifier -> NN	Conversion; NDCG	Paid case study; free reading list of Amazon/Airbnb search papers [6]
Chip Huyen [7]	Open-ended exercise (Airbnb top-10, related searches)	Left to candidate	Left to candidate	Left to candidate	Emphasis on tradeoffs, compute cost
ByteByteGo [29]	Visual / video search (no e-commerce chapter)	Text + visual embeddings, ANN	Fusion and re-rank	MRR, recall@k	Multimodal fusion pattern reusable for product images
Hello Interview / Exponent [26] [27]	Generic retrieval -> rank pattern	Two-tower / ANN	Heavy ranker	Online/offline split	Framework, delivery timing

References

1. A. Dirafzoon, "Search System" (mlsd-search.md), alirezadir/Machine-Learning-Interviews, GitHub, 2023. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/mlsd-search.md
2. alirezadir, "ML System Design" template (lists text query search, typeahead), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md
3. Educative, "Grokking the Machine Learning Interview" (Search Ranking module; "Document selection" lesson), educative.io, n.d. https://www.educative.io/courses/grokking-the-machine-learning-interview/document-selection
4. janofsun, "Search Ranking" (study notes on Educative Grokking ML system design), GitHub, 2023. https://github.com/janofsun/janofsun.github.io/blob/master/source/_posts/Search%20Ranking.md
5. K. Pham, "machine-learning-interview" (Airbnb Search ranking case; offers from Google, LinkedIn, Coupang, Snap, Stitch Fix), GitHub, 2021. https://github.com/khangich/machine-learning-interview
6. K. Pham, "appliedml.md" (Amazon and Airbnb search reading list), GitHub, 2021. https://github.com/khangich/machine-learning-interview/blob/master/appliedml.md
7. C. Huyen, "Machine Learning Systems Design - Exercises", GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md
8. P. Nigam, Y. Song, et al., "Semantic Product Search", KDD (Amazon), 2019. https://arxiv.org/abs/1907.00937
9. D. Sorokina, E. Cantu-Paz, "Amazon Search: The Joy of Ranking Products", SIGIR, amazon.science, 2016. https://www.amazon.science/publications/amazon-search-the-joy-of-ranking-products
10. C. K. Reddy et al., "Shopping Queries Dataset: A Large-Scale ESCI Benchmark for Improving Product Search", arXiv (Amazon), 2022 (130,652 queries, ~2.6M judgements, US/ES/JP). https://arxiv.org/abs/2206.06588 (data: https://github.com/amazon-science/esci-data)
11. M. Haldar et al., "Applying Deep Learning To Airbnb Search", KDD, arXiv, 2018. https://arxiv.org/abs/1810.09591
12. Airbnb, "Managing Diversity in Airbnb Search", arXiv, 2020. https://arxiv.org/abs/2004.02621
13. J.-T. Huang et al., "Embedding-based Retrieval in Facebook Search", KDD, arXiv, 2020. https://arxiv.org/abs/2006.11632
14. R. Jha, S. Subramaniyam, E. Benjamin, T. Taula, "Unified Embedding Based Personalized Retrieval in Etsy Search", arXiv, 2023. https://arxiv.org/abs/2306.04833
15. A. Magnani et al., "Semantic Retrieval at Walmart", KDD, ACM DL, 2022. https://dl.acm.org/doi/abs/10.1145/3534678.3539164
16. Choi et al., "Semantic Product Search for Matching Structured Product Catalogs", arXiv, 2020. https://arxiv.org/abs/2008.08180
17. C. J. C. Burges, "From RankNet to LambdaRank to LambdaMART: An Overview", Microsoft Research MSR-TR-2010-82, 2010. https://www.microsoft.com/en-us/research/publication/from-ranknet-to-lambdarank-to-lambdamart-an-overview/
18. Uber Engineering, "Food Discovery with Uber Eats: Building a Query Understanding Engine", eng.uber.com, 2018. https://eng.uber.com/uber-eats-query-understanding/
19. Etsy Engineering, "Deep Learning for Search Ranking at Etsy", Code as Craft, 2022. https://www.etsy.com/codeascraft/deep-learning-for-search-ranking-at-etsy

20. E. Yan, "applied-ml" (Search & Ranking section), GitHub, 2020. https://github.com/eugeneyan/applied-ml
21. E. Yan, "System Design for Recommendations and Search", eugeneyan.com, 2021. https://eugeneyan.com/writing/system-design-for-discovery/
22. kevin-2023-code, "Amazon Machine Learning Engineer interview process" (community-compiled; lists the search retrieval and ranking prompt), GitHub, 2026. https://github.com/kevin-2023-code/Tech-Interview-Questions/blob/main/companies/amazon/interview-process-machine-learning-engineer.md
23. Amazon Science, "QUEEN: Neural query rewriting in e-commerce", 2021. https://www.amazon.science/publications/queen-neural-query-rewriting-in-e-commerce
24. Amazon Science, "Seasonal relevance in e-commerce search", 2021. https://www.amazon.science/publications/seasonal-relevance-in-e-commerce-search
25. M. Haldar et al., "Improving Deep Learning for Airbnb Search", arXiv, 2020. https://arxiv.org/abs/2002.05515
26. Hello Interview, "Recommendation Systems (ML System Design pattern)", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/patterns/recommendation-systems
27. Exponent, "Introduction to the ML System Design Interview" (course), tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro
28. Amazon Science, "Why Do People Buy Seemingly Irrelevant Items in Voice Product Search?", 2020. https://www.amazon.science/publications/why-do-people-buy-irrelevant-items-in-voice-product-search
29. A. Aminian & A. Xu, "Machine Learning System Design Interview" (ByteByteGo; chapters incl. Visual Search, YouTube Video Search), book overview, 2023. https://opencourser.com/book/xop33f/machine-learning-system-design-interview
30. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2020. http://patrickhalina.com/posts/ml-systems-design-interview-guide/
31. XGBoost, "Learning to Rank" tutorial (LambdaMART objectives, position debiasing), GitHub, 2024. https://github.com/dmlc/xgboost/blob/master/doc/tutorials/learning_to_rank.rst
32. V. Ha-Thuc et al., "Learning to Rank Personalized Search Results in Professional Networks" (LinkedIn), arXiv, 2016. https://arxiv.org/abs/1605.04624
33. Z. Hu et al., "Unbiased LambdaMART: An Unbiased Pairwise Learning-to-Rank Algorithm", WWW, ACM DL, 2019. https://dl.acm.org/doi/10.1145/3308558.3313447

08. Design Product Recommendations for Amazon ("Customers Also Bought" + Homepage Recs)

> Prompt as usually given: "Design the recommendation system behind Amazon's product detail page ('customers who bought this also bought') and the personalized homepage." Variants: "similar items" carousel, "frequently bought together", replacement items for out-of-stock products (Instacart, Chip Huyen ex. 3), cart add-on recs, recs in email.
>
> Sourcing note: at review time the web-search budget was exhausted and several hosts (amazon.science, arxiv.org, bytebytego.com, igotanoffer.com, hellointerview.com) did not resolve. (fetched) = read during review; (ch-ref) = verified in an earlier chapter of this atlas; (known) = canonical paper cited by DOI/arXiv ID. Company tags for this exact prompt are thinner than for feed/video prompts; treat them as indicative.

Company tags

Company	What is reported	Source
Amazon	MLE loop includes ML design. Product recs is the house problem: item-to-item CF was invented there [1][2][3]	[11]
Instacart	"Replacement product recommendation" is in the AIMLInterviews MLSD question list	[8]
Generic e-commerce	"Suggest replacement items for out-of-stock products" (Chip Huyen exercise 3)	[10]
Meta (Marketplace)	Marketplace recs named as a Meta MLSD prompt	[12]

Portals that cover it

Portal	Treatment	Link
ByteByteGo (Aminian & Xu, MLSDI)	No Amazon chapter. The closest is "Similar Listings on Vacation Rental Platforms" (session-based item embeddings), plus "Video Recommendation" for the homepage half	[13] [14]
Educative "Grokking the ML Interview"	Recommendation-system module (Netflix-style). Candidate gen with CF and embeddings, then a ranker	[15]
Educative / Khang Pham "ML System Design"	Case studies plus Wide & Deep and YouTube DNN reading	[9] [16]
alirezadir AIMLInterviews	Recsys template (CF, two-tower, LTR, metrics) and the Instacart prompt	[8]
Hello Interview	Recommendation-systems pattern page (retrieval, ranking, re-ranking)	[17]

Portal	Treatment	Link
Exponent / Aced	MLSD course and guide; the recsys framework applies directly	[18] [19]
Chip Huyen	Exercises 3 and 21 (replacement items, faster checkout)	[10] [20]
IGotAnOffer, Patrick Halina, DesignGurus	Amazon MLE guide, generic MLSD guides	[11] [21] [22]

Requirements & scale

Dimension	Value	Source
Surfaces	(a) Detail page "also bought/viewed" and "frequently bought together" (complements), item-anchored. (b) Homepage, user-anchored. (c) Cart and email	[1][2] [26]
Business goal	Incremental revenue/GMV and conversion, not just CTR	[2][3]
Functional	Top-K (about 10-50) items per widget, in stock, eligible, deduped, diversified	assumption
Catalog	Hundreds of millions of SKUs (long tail). Plan for 10^8-10^9 items	assumption
Users	About 300M active customers. Most are sparse, many are logged out	assumption
QPS	10^5+ widget requests/s at peak (several widgets per page view, Prime Day spikes)	assumption
Latency	Under 100 ms p99 per widget. Model scoring about 20-40 ms	assumption
Freshness	Session signals within seconds. Item-item tables daily to hourly. New SKUs within hours	assumption
Key constraint	Item-to-item similarity is computed offline; the online step is a lookup, so it scales independently of user count [1]	[1]

Diagram 1: End-to-end architecture (online serving path)

Figure 8.1: Online serving. Item-anchored ("also bought") and user-anchored (homepage) requests share one candidate-filter-rank-policy pipeline.




Diagram 2: Offline training & data pipeline

Figure 8.2: Offline pipeline. Logged impressions are joined with delayed purchase labels. Item-item tables, embeddings and the ranker are rebuilt on separate cadences.




Diagram 3: Model architecture

Figure 8.3: Two-stage model. A two-tower retriever and item-item CF feed a multi-task ranker. Its heads are combined into one expected-value score.





Diagram 4: Real system (Amazon item-to-item collaborative filtering)

Figure 8.4: Amazon's item-to-item CF, as described in Linden, Smith & York (2003) and Smith & Linden (2017). The expensive similar-items table is built offline. Online work only looks up and merges the neighbours of the items the user has interacted with [1][2][3].



Data & labels

Signal	Use as label?	Notes
Purchase (net of returns)	Primary positive	Sparse, delayed up to days. Use an attribution window [2]
Add-to-cart	Auxiliary positive	Denser than purchases, strong intent
Click on rec	Auxiliary positive	Densest. Rewards clickbait if used alone
Impression without click	Negative (ranker)	Only items that were actually shown. Watch position bias
Detail view / dwell	Feature + weak positive	Drives the "also viewed" widget
Rating / review	Feature	Too sparse and biased to use as a label
Co-purchase in the same basket or session	Item-item pair positive	Basis for "also bought" / "frequently bought together" [1]
Random catalog items	Negatives (retrieval)	In-batch and sampled negatives, with logQ correction [5]

Features

Group	Examples
User	Hashed user id, purchase categories (30/90/365 d), price sensitivity, Prime flag, locale
Session / context	Anchor ASIN, last-N viewed and searched, device, time, page type, cart contents
Item	ASIN id, brand, category path, price, rating, review count, stock, delivery speed
Item content	Title and description text embedding, image embedding (for cold start)
Item stats	Rec CTR, conversion rate, return rate (smoothed, by age bucket)
User x item	Category affinity, brand affinity, already-owned flag, i2i score to recent items
Anchor x candidate	Co-purchase lift, complement vs substitute type, price ratio

Model choices (baseline -> advanced)

Stage	Baseline	Advanced	Tradeoff
"Also bought"	Co-occurrence counts	Item-to-item CF with an expected-vs-observed correction [1][2]	Cheap and explainable. Weak on new items
"Frequently bought together"	Co-purchase pairs minus co-view pairs (removes substitutes)	Complement model with type-aware, diversified outputs (Amazon P-Companion) [26]	Separates complements from substitutes; handles cold-start anchors via content
Item similarity	Content (text/category) kNN	Item2vec / session embeddings (ByteByteGo similar-listings style) [13]	Covers cold start. Needs ANN
Homepage retrieval	Popular by category	Matrix factorization, then two-tower [4][5]	Two-tower personalizes and scales via ANN, but is costly to train
Sequential	Last-viewed neighbours	Transformer next-item model (e.g. SASRec) [24]	Captures intent shifts. Higher latency
Ranker	Logistic regression or GBDT on hand-made features	Wide & Deep / DLRM / DIN with multi-task heads [6][7][23][25]	Better calibration and accuracy. Needs a GPU/CPU serving budget
Re-rank	Business rules	MMR diversity plus a constrained optimizer (sponsored slots, margins)	Trades a little relevance for diversity and revenue

Loss functions

Model	Loss
Two-tower	Sampled softmax / in-batch softmax with logQ correction [5]. Optionally a hard-negative margin loss
Item embeddings	Skip-gram with negative sampling over sessions or baskets
Ranker heads	Per-task binary cross-entropy, summed with task weights (or uncertainty weighting). pBuy trained on clicked items, or as an ESMM-style pClick x pBuy chain to avoid selection bias [27]
Re-rank (optional)	Listwise (LambdaRank / softmax over the slate)

Offline metrics

Stage	Metric
Retrieval	Recall@K / hit-rate@K on next purchase, catalog coverage
Ranking	AUC and log loss per head, NDCG@K, calibration (predicted vs. observed)
Slate	Intra-list diversity, novelty, share of long-tail items
Evaluation	Time-based split (train on days 1..T, test on T+1). Counterfactual / IPS replay on exploration logs
Slices	New users, new items, categories, logged-out, mobile vs desktop

Online metrics / A-B

Type	Metric
Primary	Revenue or GMV per visit attributed to the widget, conversion rate

Type	Metric
Secondary	Widget CTR, add-to-cart rate, units per order
Guardrails	Return rate, page latency p99, sponsored revenue, complaints, sitewide sales (cannibalization)
Design	User-level randomization. 1-2 weeks to cover the purchase delay. Holdout for long-term effect. Interleaving for fast ranker comparisons

Serving & latency budget (assumption, per widget, p99)

Step	Budget	How
Request parse + user/session fetch	5 ms	Online feature store
Candidate gen (parallel)	15-25 ms	KV lookup of the item-item table (about 1 ms); ANN HNSW top-500
Filters	5 ms	Bloom filter of owned items, inventory cache
Feature assembly	10 ms	Batched multi-get
Ranking ~500 items	20-30 ms	CPU/GPU batched inference, quantized embeddings
Re-rank + policy	5 ms	In-process
Total	under 80-100 ms	Fallback: cached precomputed recs per user, or bestsellers

Monitoring

What	Signal
Data	Feature null rates and drift (PSI), label delay, event volume per surface
Model	Calibration per head, score distribution, online AUC from delayed labels
Business	Widget CTR and GMV per visit by surface, anomaly alerts during events (Prime Day)
System	p99 latency, fallback rate, ANN recall vs exact search, KV staleness
Ecosystem	Concentration (Gini of impressions), share of new and long-tail items

Failure modes

Failure	Mitigation
Popular items dominate "also bought" (e.g. batteries everywhere)	Expected-vs-observed similarity, IDF-style damping [2]
Recommending items the user just bought (non-consumables)	Owned-item filter. Allow consumables (replenishment)
Substitutes on the post-purchase page	Separate complement and substitute models by page context [2][26]
New SKU or new user cold start	Content-tower embeddings, category bestsellers, exploration slots
Out-of-stock or undeliverable recs	Real-time inventory filter; substitute recs (Instacart / Huyen prompt) [8][10]

Failure	Mitigation
Feedback loop / position bias	Exploration traffic, position feature at train time (set to a constant at serve time), IPS
Seasonal shift (holidays, Prime Day)	Faster retrains, recency-weighted features, short-window trending source
Training-serving skew	Point-in-time feature snapshots, logging the features used at serving

Interviewer follow-ups

- How would you compute item-item similarity for 10^8 items without O(N^2) work?
- "Also bought" vs "also viewed" vs "frequently bought together": should these be one model or three? How do you tell complements from substitutes?
- Why might cosine similarity on co-purchase counts over-recommend bestsellers? How do you fix it?
- Purchases arrive days late. How do you build labels and train daily?
- Click, add-to-cart or purchase: which do you optimize? How do you combine multi-task heads into one score?
- How do you handle a brand-new product with no interactions, or a logged-out user?
- How do you build "frequently bought together" so it shows a phone case for a phone, not another phone? What data separates complements from substitutes?
- How do you avoid recommending a second TV to someone who just bought one, while still recommending detergent?
- How do you rebuild the ANN index and item-item table without downtime? How stale is acceptable?
- How do you blend sponsored products with organic recs without hurting trust?
- How do you measure incrementality (would the user have bought it anyway)?
- Diversity: how would you stop the carousel showing 10 phone cases of the same type?
- How do you serve recs under 100 ms during Prime Day traffic spikes? What is the fallback?
- How do you evaluate offline when the logging policy biased what users saw?
- How would you add an LLM (for example, generating "why recommended" text or a semantic retrieval source)?

Portal comparison

Portal	Framing	Candidate gen	Ranker	Distinctive emphasis
Amazon papers [1][2][3]	Item-anchored, scale-first	Item-to-item CF table	Light heuristics (in 2003)	Offline table, online lookup; expected co-buy correction
ByteByteGo [13][14]	Similar listings (session-based) + video home feed	Session item embeddings + ANN; multi-source	Two-tower / DNN	Embeddings from co-occurrence in sessions; hybrid filtering
Educative Grokking [15]	Netflix-style personalized recs	CF/MF + content + embeddings	Pointwise DNN	Data-generation and staged funnel
alirezadir AIMLIntervie	Generic recsys template; Instacart replacement	User/item CF, MF, two-tower, content	Pointwise / pairwise /	9-step formula, metrics catalogue

Portal	Framing	Candidate gen	Ranker	Distinctive emphasis
ws [8]	prompt		listwise LTR	
Hello Interview [17]	Recsys pattern	Multi-source retrieval	Multi-stage ranking + re-ranking	Interview delivery and tradeoff talk
Chip Huyen [10][20]	Out-of-stock replacements, checkout speed	Open-ended	Open-ended	Business framing, data and deployment issues

References

1. G. Linden, B. Smith, J. York, "Amazon.com Recommendations: Item-to-Item Collaborative Filtering", IEEE Internet Computing, 2003. https://doi.org/10.1109/MIC.2003.1167344 (known)
2. B. Smith, G. Linden, "Two Decades of Recommender Systems at Amazon.com", IEEE Internet Computing, 2017. https://doi.org/10.1109/MIC.2017.72 (known)
3. Amazon Science, "The history of Amazon's recommendation algorithm", amazon.science, 2019. https://www.amazon.science/the-history-of-amazons-recommendation-algorithm (known; host unreachable at review)
4. P. Covington, J. Adams, E. Sargin, "Deep Neural Networks for YouTube Recommendations", RecSys / Google Research, 2016. https://research.google/pubs/pub45530/ (ch-ref)
5. X. Yi et al., "Sampling-Bias-Corrected Neural Modeling for Large Corpus Item Recommendations", RecSys / Google Research, 2019. https://research.google/pubs/sampling-bias-corrected-neural-modeling-for-large-corpus-item-recommendations/ (ch-ref)
6. H.-T. Cheng et al., "Wide & Deep Learning for Recommender Systems", arXiv, 2016. https://arxiv.org/abs/1606.07792 (ch-ref)
7. M. Naumov et al., "Deep Learning Recommendation Model for Personalization and Recommendation Systems (DLRM)", arXiv, 2019. https://arxiv.org/abs/1906.00091 (known; ID confirmed via fetched github.com/facebookresearch/dlrm)
8. alirezadir, "ML System Design" (recsys template; Instacart replacement-product prompt), AIMLInterviews, GitHub, 2025. https://github.com/alirezadir/AIMLInterviews/blob/main/src/MLSD/ml-system-design.md (fetched)
9. K. Pham, "machine-learning-interview", GitHub, 2021. https://github.com/khangich/machine-learning-interview (fetched)
10. C. Huyen, "Machine Learning Systems Design: Exercises" (ex. 3 replacement items, ex. 21 faster purchase), GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md (fetched)
11. IGotAnOffer, "Amazon Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/amazon-machine-learning-engineer-interview (ch-ref)
12. IGotAnOffer, "Meta Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/facebook-machine-learning-engineer-interview (ch-ref)
13. A. Aminian & A. Xu, "Similar Listings on Vacation Rental Platforms" (Machine Learning System Design Interview), ByteByteGo, 2023. https://bytebytego.com/course

s/machine-learning-system-design-interview/similar-listings-on-vacation-rental-platforms (ch-ref; same URL used in ch. 09; host unreachable at review)
14. A. Aminian & A. Xu, "Video Recommendation System" (Machine Learning System Design Interview, ch. 6), ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/video-recommendation-system (ch-ref)
15. Educative, "Grokking the Machine Learning Interview" (recommendation system module), educative.io, n.d. https://www.educative.io/courses/grokking-the-machine-learning-interview (ch-ref)
16. Educative / K. Pham, "Machine Learning System Design" (course), educative.io, 2021. https://educative.io/courses/machine-learning-system-design/introduction (ch-ref)
17. Hello Interview, "Recommendation Systems (ML System Design pattern)", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/patterns/recommendation-systems (ch-ref)
18. Exponent, "Introduction to the ML System Design Interview" (course), tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
19. Aced (formerly Exponent), "Machine Learning System Design Interview (2026 Guide)", aced.io, 2026. https://www.aced.io/blog/machine-learning-system-design-interview-guide (ch-ref)
20. C. Huyen, "Introduction to Machine Learning Interviews Book", huyenchip.com, 2021. https://huyenchip.com/ml-interviews-book/ (ch-ref)
21. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2020. http://patrickhalina.com/posts/ml-systems-design-interview-guide/ (ch-ref)
22. DesignGurus, "The Grokking series", designgurus.io, 2025. https://www.designgurus.io/grokking (ch-ref)
23. G. Zhou et al., "Deep Interest Network for Click-Through Rate Prediction" (Alibaba), arXiv, 2017. https://arxiv.org/abs/1706.06978 (known; ID confirmed via fetched github.com/zhougr1993/DeepInterestNetwork)
24. W.-C. Kang, J. McAuley, "Self-Attentive Sequential Recommendation (SASRec)", ICDM, 2018. https://arxiv.org/abs/1808.09781 (known; venue confirmed via fetched github.com/kang205/SASRec)
25. J. Ma et al., "Modeling Task Relationships in Multi-task Learning with Multi-gate Mixture-of-Experts", KDD, 2018. https://doi.org/10.1145/3219819.3220007 (known)
26. J. Hao et al., "P-Companion: A Principled Framework for Diversified Complementary Product Recommendation" (Amazon), CIKM, 2020. https://doi.org/10.1145/3340531.3412732 (known)
27. X. Ma et al., "Entire Space Multi-Task Model: An Effective Approach for Estimating Post-Click Conversion Rate (ESMM)" (Alibaba), SIGIR, 2018. https://arxiv.org/abs/1804.07931 (known)

09. Design Similar Listings and Search Ranking for Airbnb (Listing Embeddings, Two-Sided Marketplace)

> Prompt as usually given: "Design the 'similar listings' carousel on an Airbnb listing page", or "Design the system that returns the top 10 listings when a user searches for rentals in a location on Airbnb" (Chip Huyen, exercise 9 [5]). Variants: hotel or vacation-rental search ranking (Booking.com, Expedia, Vrbo style), "rental recommendation", Airbnb Experiences ranking [18], real-time in-session personalization.
>
> Sourcing note (review pass, Oct 2026): medium.com, arxiv.org, doi.org and bytebytego.com did not resolve from the build sandbox and the web-search budget was spent. (fetched) = read for this chapter. (listed) = title, year and URL confirmed in a curated GitHub list (eugeneyan/applied-ml, alirezadir, ByteByteGoHq, wzhe06/Reco-papers); text not re-read. (ch-ref) = verified in an earlier chapter. Check paper numbers against the PDF before quoting.

Company tags

Company	What is reported	Source
Airbnb	Chip Huyen's exercise list has "top 10 results for rental listings in a location on Airbnb" (ex. 9)	[5]
Airbnb	AIMLInterviews lists "Rental recommendation (Airbnb)" as a sample MLSD question	[7]
Airbnb	Khang Pham's ML design course has an "Airbnb Search ranking" case study	[8]
Airbnb-style marketplaces	ByteByteGo ch. 9, "Similar Listings on Vacation Rental Platforms". Its only Airbnb reference is the "Listing embeddings in search ranking" blog	[6][10] [17]

Portals that cover it

Portal	Treatment	Link
ByteByteGo (Aminian & Xu, MLSDI ch. 9)	Similar listings: session-based skip-gram listing embeddings, ANN retrieval and re-ranking. Chapter references also cite positional bias, random walks (with restart) and seasonality	[6] [10] [17]
Khang Pham (Educative / course)	"Airbnb Search ranking" case study (LTR, features, metrics)	[8][9]
Chip Huyen (MLSD exercises)	Open prompt, ex. 9 (Airbnb top-10 rental search)	[5]
alirezadir AIMLInterviews	"Rental recommendation (Airbnb)" in the question bank. Its company list has three Airbnb items, incl. "Applying Deep Learning To Airbnb Search"	[7] [11]
Educative "Grokking the ML Interview"	Search ranking and recommendation modules (generic funnel, not Airbnb-specific)	[12]

Portal	Treatment	Link
Hello Interview	Recommendation-systems pattern (retrieval, ranking, re-ranking); not Airbnb-specific	[13]
Community notes	junfanz1 "Awesome-AI-Review" summary of ByteByteGo ch. 8/9 (Airbnb)	[14]

Requirements & scale

Dimension	Value	Source
Surfaces	(a) "Similar listings" carousel on the listing detail page. (b) Search results for location + dates + guests. (c) Real-time re-ranking within a session	[1][2]
Business goal	Bookings (conversion), not clicks. The marketplace has two sides, so the host must also accept the booking (host rejection counts as a negative)	[1][3][16]
Functional	Return the top K (about 10-20 per page, roughly 18 per search page) listings that are available for the dates, match the filters and are bookable	assumption
Catalog	About 4.5M active listings when the paper was written (2018), now more than 7M. Inventory is spread across about 100k+ cities or markets	[1] / assumption
Training data	About 800M search click sessions for listing embeddings	[1]
Users	Hundreds of millions of guests. Most book once or twice a year, so per-user history is sparse	[1] / assumption
QPS	About 10^4-10^5 search and carousel requests per second at peak	assumption
Latency	Under 200 ms p99 end to end for search. The ranking model has about 30-50 ms for roughly 1-2k candidates	assumption
Freshness	Clicks and skips within the session take effect within seconds. Embeddings retrain daily. Availability and price must be real-time	[1]
Key constraints	Listings are unique items with limited availability; a listing booked for one guest's dates is gone. Queries are geo-bound. Cold start: new listings appear every day	[1][2]

Diagram 1: End-to-end architecture (online serving path)

Figure 9.1: Online serving. Search and the similar-listings carousel share retrieval, availability filtering, ranking and a marketplace re-ranker. Session signals feed real-time personalization features.




Diagram 2: Offline training & data pipeline

Figure 9.2: Offline pipeline. Two models train from the same logs. The listing embeddings (skip-gram over click sessions) are retrained daily. The booking ranker trains on impressions labelled with how far each one got toward a booking.




Diagram 3: Model architecture

Figure 9.3a: Listing embedding model (KDD 2018 [1]). Skip-gram with negative sampling over click sessions. The booked listing is a global context in every window, and some negatives come from the same market.




Figure 9.3b: Search ranker. Real-time embedding-similarity features join the classic features in a booking-optimized LambdaRank model (GBDT in 2018, later a DNN [1][2]).





Diagram 4: Real company system (Airbnb Journey Ranker, KDD 2023)

Figure 9.4: Multi-task "journey" ranking [16]. Positive milestones toward a booking and negative milestones such as cancellation or host rejection are each modelled as a task, then combined into one score.



Data & labels

Data	Use	Label / note
Click sessions (more than 30 s dwell, split on a 30-min gap)	Listing embeddings	Co-occurrence within window m=5 [1]
Booked sessions	Global context for embeddings	Booked listing = positive for every window [1]
Booking sessions (users x listing types)	User-type / listing-type embeddings	Long-term preference. Host rejections are explicit negatives [1]
Search impressions	Ranker	book=1, host contact=0.25, click=0.01, impression=0, host reject=-0.4 [1]
Skipped listings (shown above a click but not clicked)	EmbSkipSim feature, negatives	Implicit negative [1]
Reviews, ratings, calendar, host response	Features	Quality and trust signals

Features

Group	Examples	Freshness
Listing	Price per night, type, capacity, amenities, review count/score, booking rate, photo quality	Daily / hourly
Query	Location, distance to the query center, check-in date, length of stay, guests, lead time	Per request
Query x listing	Distance to the map center, price relative to market median, fit to the date range	Per request
User / guest	Past booked price, trip type, user_type embedding	Daily
Real-time session	EmbClickSim, EmbSkipSim, EmbLongClickSim, EmbWishlistSim, EmbInqSim, EmbLastLongClickSim [1]	Seconds
Host / marketplace	Host acceptance rate, instant-book flag, response time, superhost, cancellation history	Daily

Group	Examples	Freshness
Context	Device, locale, seasonality, holidays	Per request

Model choices (baseline -> advanced)

Stage	Option	Pros	Cons
Similar listings	Rule: same city + price band + type	Simple, no training	Ignores taste and style
Similar listings	Item CF (co-click/co-book matrix)	Uses behaviour	Sparse, poor cold start
Similar listings	Skip-gram embeddings + booked global context + market negatives [1]	Captures style and price within a market; cheap ANN	Clicks are not bookings; needs cold-start fill
Similar listings	GNN or two-tower with content (photos, text)	Better for new and rare listings	Heavier to train and serve
Ranking	Hand-tuned scoring function	Transparent	Plateaus quickly
Ranking	GBDT LambdaRank [1]	Strong on tabular data	Manual feature crosses
Ranking	DNN, then two-tower DNN [2][3]	Scales with data, learns crosses	Hard to debug; many failed attempts reported [2]
Ranking	Multi-task journey ranker [16]	Optimizes the full booking funnel and penalizes bad outcomes	Weighting the tasks is hard
Re-rank	Greedy MMR / diversity network [4]	Variety of location and price	Can lower per-item relevance
Re-rank	Learned diverse ranking: score each slot given the listings already placed above it [19]	Diversity learned from bookings, not hand-tuned	Sequential scoring costs latency

Loss functions

Model	Loss	Note
Listing embedding	Skip-gram negative-sampling log loss, plus booked-global and market-negative terms	[1]
User/listing type embedding	Same, with host-rejection negatives	Two-sided signal [1]
Ranker	Pairwise LambdaRank (booked > not-booked within a search)	Optimizes NDCG directly [1][2]
Multi-task	Sum of per-milestone BCE terms (weighted), plus a negative-outcome head	[16]

Offline metrics

Metric	Model	Note
Average rank of the eventually-booked listing	Embeddings	Rank the candidates by similarity to the last clicked listing [1]
NDCG@K / NDCU on booking	Ranker	Main gate for promotion [1][2]
Recall@K of ANN vs exact k-NN	Retrieval	Index quality
Coverage / new-listing share	Retrieval and re-rank	Cold start health
Calibration per market	Ranker	Required for multi-task combination

Online metrics / A-B

Metric	Type	Note
Bookings per search user, booking conversion	Primary	North star
Similar-carousel CTR and bookings from the carousel	Surface	2018 paper: about +21% carousel CTR and about +4.9% more guests finding their booked listing in the carousel [1]
Host acceptance rate, cancellations	Guardrail	Two-sided health [16]
GMV / nights booked, price mix	Business	Watch for a drift toward cheaper or pricier listings
Search latency, zero-result rate	Guardrail	
Interleaving (team-draft) wins	Fast pre-screen	Airbnb uses interleaving before A/B [15]

Serving & latency budget (assumption, search, p99)

Step	Budget	Note
Parse query + geo lookup	10 ms	Geocode, map bounds
Retrieval (geo index + ANN)	30 ms	2-5k candidates
Availability/price filter	30 ms	Calendar service, the largest cost
Feature fetch (batch)	30 ms	Online store + session store
Ranker inference	40 ms	1-2k listings, CPU/GPU batch
Re-rank + policy	10 ms	Diversity, dedupe, boosts
Network/serialization slack	40 ms	Total under 200 ms
Carousel (similar listings)	under 50 ms	Precomputed k-NN lists per listing, then filter by dates

Monitoring

Signal	Why
Embedding drift (neighbour overlap from day to day)	Daily retrain can reshuffle the similar lists
Feature freshness (session store lag)	Real-time features silently going stale
Score distribution per market	Calibration breaks in new or seasonal markets
New-listing impression share	Cold-start starvation
Host rejection / cancellation of ranked bookings	Marketplace quality

Signal	Why
Latency and calendar service error rate	Availability errors lead to empty or wrong results

Failure modes

Failure	Mitigation
Click-optimized embeddings surface listings people click but do not book	Booked listing as global context; rank on the booking label [1]
Similar listings from another city (cross-market leakage)	Market negatives in training [1]; geo filter at serving
New listings never shown	Cold-start embedding averaging [1]; exploration slots; new-listing boost
Position bias in logged labels	Position as a training feature with dropout; set to 0 at serving [3]
Many near-duplicate results (same building or host)	Diversity re-rank [4][19], host dedupe
Popular listings get booked out, so rankings go stale	Real-time availability filter; demand-aware features
Hosts reject the guest	P(host accept) head; host preference features [1][16]
Seasonality shift (holidays)	Time-based splits, daily retrain, seasonal features [10]
Cold-start listing with no clicks yet	Random walk with restart on the listing co-click graph, or content embedding, to seed neighbours [10]

Interviewer follow-ups

- Why train embeddings on click sessions rather than booking sessions? What do the booked global context and the market negatives each fix?
- How do you get an embedding for a listing created today (cold start)?
- How do you evaluate embeddings offline before an A/B test?
- How do you combine long-term preference (user_type) with in-session intent (EmbClickSim)?
- What is the label for ranking, and why use graded labels (book, contact, click, host reject) instead of a single click label?
- How do you handle the host side: rejections, acceptance rate, fairness to new hosts?
- How do you correct position bias in the training data?
- How do you enforce date availability and price filters without blowing the latency budget?
- How would you add diversity (location, price) without losing bookings?
- Pointwise vs pairwise vs listwise ranking: which one, and why?
- How do you trade off guest conversion against host revenue and platform GMV?
- How do you speed up ranking experiments? (interleaving, then A/B)
- What changes for map search, flexible dates, or "I'm flexible" queries with no location?
- How do you serve the similar-listings carousel: precomputed k-NN or online ANN?
- How do you detect that a daily embedding retrain broke similarity?
- How would you learn diversity from data instead of a hand-tuned MMR penalty? [19]

- How would ranking change for Airbnb Experiences, which have far less traffic? [18]

Portal comparison

Portal	Framing	Retrieval	Ranking	Distinctive emphasis
Airbnb papers [1][2] [3][16][19]	Search + similar listings, booking-optimized	Geo + embedding similarity	GBDT, then DNN, then two-tower, then multi-task; learned diversity	Graded labels, real-time embedding features, two-sided negatives
ByteByteGo ch. 9 [6][10] [14][17]	Session-based recs for similar listings	Skip-gram embeddings + ANN index	Light re-ranking (seen, filters)	Booked global context, same-region negatives, avg rank of booked listing, indexing pipeline; positional bias, seasonality
Khang Pham [8][9]	Airbnb search ranking	Candidate set by location	LTR (pointwise vs pairwise)	Features and metrics walkthrough
Chip Huyen [5]	Open prompt: top-10 rental search	Open-ended	Open-ended	Business framing, data problems
alirezadir AIMLInterviews [7][11]	Rental recommendation in the question bank	Generic recsys/search templates	Pointwise, pairwise or listwise LTR	Links to Airbnb papers in its company list
Educative / Hello Interview [12][13]	Generic search/recsys funnel	Multi-source retrieval	Multi-stage	Interview delivery and tradeoffs

References

1. M. Grbovic, H. Cheng, "Real-time Personalization using Embeddings for Search Ranking at Airbnb", KDD (Applied Data Science track), 2018. https://doi.org/10.1145/3219819.3219885 (listed)
2. M. Haldar et al., "Applying Deep Learning To Airbnb Search", KDD 2019 (arXiv 2018). https://arxiv.org/abs/1810.09591 ; https://doi.org/10.1145/3292500.3330658 (listed: eugeneyan/applied-ml, alirezadir)
3. M. Haldar et al., "Improving Deep Learning For Airbnb Search", arXiv / KDD, 2020. https://arxiv.org/abs/2002.05515 (listed: eugeneyan/applied-ml)
4. M. Abdool et al., "Managing Diversity in Airbnb Search", arXiv / KDD, 2020. https://arxiv.org/abs/2004.02621 (listed: eugeneyan/applied-ml)
5. C. Huyen, "Machine Learning Systems Design: Exercises" (ex. 9, Airbnb rental search), GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md (fetched)
6. A. Aminian & A. Xu, "Similar Listings on Vacation Rental Platforms" (Machine Learning System Design Interview, ch. 9), ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/similar-listings-on-vacation-rental-platforms (ch-ref; host unreachable in review)
7. alirezadir, "ML System Design" (sample questions: "Rental recommendation (Airbnb)"), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/b

lob/main/src/MLSD/ml-system-design.md (fetched)
8. K. Pham, "machine-learning-interview" (ML design case 6: Airbnb Search ranking), GitHub, 2021. https://github.com/khangich/machine-learning-interview (fetched)
9. Educative / K. Pham, "Machine Learning System Design" (course), educative.io, 2021. https://educative.io/courses/machine-learning-system-design/introduction (ch-ref)
10. ByteByteGo, "ml-bytebytego: Reference materials for ML System Design Interview" (ch. 9 references), GitHub, 2023. https://github.com/ByteByteGoHq/ml-bytebytego (fetched; ch. 9 lists 8 references incl. the Airbnb listing-embeddings blog, positional bias, random walk with restart, seasonality)
11. alirezadir, "ML at Companies" (Airbnb papers and blogs), GitHub, 2025. https://github.com/alirezadir/AIMLInterviews/blob/main/src/MLSD/ml-companies.md (fetched)
12. Educative, "Grokking the Machine Learning Interview", educative.io, n.d. https://www.educative.io/courses/grokking-the-machine-learning-interview (ch-ref)
13. Hello Interview, "Recommendation Systems (ML System Design pattern)", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/patterns/recommendation-systems (ch-ref)
14. junfanz1, "ML System Design Interview" notes (section "Airbnb: Similar Listings on Vacation Rental"), GitHub, n.d. https://github.com/junfanz1/Awesome-AI-Review/blob/main/System%20Design/ML%20System%20Design%20Interview.md (fetched)
15. Airbnb Engineering, "Beyond A/B Test: Speeding up Airbnb Search Ranking Experimentation through Interleaving", Medium, 2022. https://medium.com/airbnb-engineering/beyond-a-b-test-speeding-up-airbnb-search-ranking-experimentation-through-interleaving-7087afa09c8e (listed: eugeneyan/applied-ml)
16. C. H. Tan et al., "Optimizing Airbnb Search Journey with Multi-task Learning", KDD, 2023. https://github.com/wzhe06/Reco-papers/blob/master/Industry%20Recommender%20System/%5BAirbnb%5D%20Optimizing%20Airbnb%20Search%20Journey%20with%20Multi-task%20Learning.pdf (listed: PDF present in wzhe06/Reco-papers)
17. Airbnb Engineering, "Listing Embeddings in Search Ranking", Medium, 2018. https://medium.com/airbnb-engineering/listing-embeddings-for-similar-listing-recommendations-and-real-time-personalization-in-search-601172f7603e (listed: ByteByteGo ch. 9 refs, eugeneyan/applied-ml)
18. Airbnb Engineering, "Machine Learning-Powered Search Ranking of Airbnb Experiences", Medium, 2019. https://medium.com/airbnb-engineering/machine-learning-powered-search-ranking-of-airbnb-experiences-110b4b1a0789 (listed: eugeneyan/applied-ml)
19. Airbnb Engineering, "Learning To Rank Diversely", Medium, 2022. https://medium.com/airbnb-engineering/learning-to-rank-diversely-add6b1929621 (listed: eugeneyan/applied-ml)

10. Design a Visual Search / Image Similarity System (Pinterest Lens, Google Lens)

> Prompt as usually given: "A user uploads a photo, or crops a region of a Pin. Return the most visually similar images, ranked." Variants: "shop the look" (photo to buyable products), camera search (Lens), near-duplicate detection, "more like this", and text-to-image search (CLIP-style).
>
> Sourcing note: during review, only github.com was reachable from the build sandbox (arxiv.org, medium.com, bytebytego.com, igotanoffer.com and research.google failed DNS) and the web-search budget was spent. Tags: (fetched) = opened and checked in review; (ch-ref) = verified in another chapter of this atlas; (known) = canonical paper cited by arXiv ID, not re-fetched; (book) = structure from the published book. Company tags separate "built it" (engineering paper or post) from "asked it" (interview report).

Company tags

Company	Evidence	Notes	Source
Pinterest	Built it: Visual Search (2015), Visual Discovery / Lens (2017), unified embedding (2019)	The canonical system this prompt mirrors (Lens, Flashlight, Shop the Look)	[16] [17] [18]
Google	Built it: ScaNN ANN library (used for large-scale vector search); Lens product	Google MLE loops include an ML design round; no portal ties this exact prompt to Google	[12] [28] [34] [35]
Microsoft (Bing)	Built it: Bing Visual Search (KDD 2018)	Web-scale, responsive latency budget	[19]
eBay	Built it: Visual Search at eBay (KDD 2017)	Product image to listing	[20]
Alibaba	Built it: Pailitao visual search (KDD 2018)	Detection + category prediction + embedding	[21]
Meta	Built it: photo search (listed under Meta in alirezadir's ML-at-companies list)	Meta MLE loops include ML design; image-similarity prompt not confirmed by a portal	[6][13] [14]
Generic	Chip Huyen exercise 6: "return images associated with a query like in Google Images" (text-to-image variant)	Open question	[3]

Portals that cover it

Portal	Treatment	Link
ByteByteGo (Aminian & Xu, MLSDI), ch. 2 "Visual Search System"	The fullest treatment. Representation learning with contrastive loss, embedding + ANN, indexing pipeline, re-ranking	[1] [2]
Chip Huyen, ML Systems Design (exercises)	Exercise 6: text-query image search (Google Images); open question	[3]
alirezadir AIMLInterviews	Template lists "Image/Video search" and "Visual search" under search systems; search write-up lists multimodal (photo) search and a blender that merges visual search results	[4] [5] [6]
Educative "Grokking the ML Interview" / Khang Pham MLSD	Search and recommendation modules; retrieval and ranking cascade reusable here	[7] [8]
Exponent / Aced, Hello Interview	Generic MLSD framework and delivery timing	[9] [10]
IGotAnOffer, Patrick Halina	MLSD guides with example prompts and rubric	[11] [15]

Requirements & scale

Dimension	Value	Source
Functional	Input: image (photo or crop/bounding box). Output: top-K similar images, ranked	[1]
Functional (opt.)	Detect objects in the photo and let the user pick one; text + image query; shopping filter	[17][21]
Out of scope (book version)	Video; personalization (often added as a follow-up)	[1]
Non-functional	Low latency, high recall, safe results (no NSFW, no private Pins)	[1]
Catalog size	Billions of images (book uses about 100-200 billion for the Pinterest-style prompt)	[1] (typical)
Users / QPS	~100M+ DAU; ~1K-10K visual QPS at peak	typical assumption
Latency	p99 under ~200-300 ms end to end; embedding ~20-50 ms on GPU; ANN ~10-30 ms	typical assumption
Freshness	New images searchable within minutes to hours (incremental index)	[29]
Embedding size	64-512 dims float, or binarized / PQ-compressed for storage	[18][26]

Diagram 1: end-to-end serving architecture

Diagram 1. Online prediction path (query image -> embedding -> ANN -> filter -> rerank)




Diagram 1b. Indexing pipeline (runs beside serving)




Diagram 2: offline training & data pipeline

Diagram 2. Data, labels, training, evaluation, deployment and feedback



Diagram 3: model architecture

Diagram 3. Shared-weight (Siamese) image encoder trained with contrastive loss





Diagram 4: the real system (Pinterest unified visual embedding)

Diagram 4. Pinterest: one multi-task embedding for Lens, Shop the Look and Flashlight [18]



ANN index sizing (FAISS guidance)

Scale	Suggested index	Note	Source
100M-1B vectors	`IVF1048576_HNSW32` (2^20 lists, HNSW coarse quantizer)	Training slow; plan 30-256 training vectors per centroid	[33]
10M-100M	`IVF262144_HNSW32`	Train on GPU, rest on CPU, or two-level clustering	[33]
RAM-bound	OPQ + PQ (4-bit FastScan) or RaBitQ (~1 bit/dim)	All FAISS indexes live in RAM; HNSW costs ~(4d + 8M) bytes/vector	[33]
GPU	Plain IVF (IVF+HNSW not on GPU)	Use for batch backfill / re-index	[33]

Data & labels

Source	Positive	Negative	Pros	Cons	Source
User interactions	(query, clicked/saved result)	Shown-not-clicked, random	Matches product goal	Position bias, noisy, cold start	[1]
Self-supervision	(image, augmented view)	Other images in batch	Free, unlimited labels	Learns invariance, not "style"	[1] [23]
Image-text pairs	(image, caption / Pin text)	Other pairs in batch	Enables text-to-image search	Needs clean text	[22]
Human annotation	Same product / same object	Different product	High precision	Costly, slow	[1] [21]
Product catalog	Scene crop <-> catalog image of same SKU	Other SKUs, same category	Shopping relevance	Needs detection + matching	[18] [21]

Features

Group	Examples	Used in
Raw pixels	Resized 224x224 RGB, crop from detector box	Encoder

Group	Examples	Used in
Visual embedding	d-dim vector (float / binary / PQ code)	Retrieval, ranking
Image metadata	Category, detected objects, OCR text, quality, resolution, NSFW score	Filter, rank
Engagement	Saves, clicks, CTR of result image	Rank
Text	Pin title, board name, alt text (text tower or CLIP)	Rank, hybrid query
User (optional)	Recent interests, locale	Personalized re-rank

Model choices (baseline -> advanced)

Stage	Option	Tradeoff	Source
Baseline	Hand-crafted features (SIFT, color histograms) + LSH	Cheap, poor semantic similarity	[16]
v1	ImageNet-pretrained CNN, take penultimate layer	Easy, strong start; not tuned to task	[16][20]
v2	Fine-tuned encoder with contrastive / triplet loss	Task-aligned; needs labels and hard negatives	[1][24]
v3	Multi-task / proxy-based metric learning, one embedding for many products	One model to maintain; task balancing needed	[18]
v4	Foundation encoders (CLIP, DINOv2) + fine-tuning	Zero-shot text<->image; larger serving cost	[22][31]
Detector front end	Faster R-CNN / SSD style detector for crops	Better object-level matches; extra latency	[17][21]
ANN	Tree / LSH / clustering (IVF) / graph (HNSW) / ScaNN (anisotropic VQ, SOAR)	Recall vs memory vs latency	[1][26][27] [28][35]

Loss

Loss	Form	Note	Source
Contrastive (softmax / InfoNCE)	CE over sim(q, p) vs sim(q, n_i), with temperature	Book's main choice; scales with in-batch negatives	[1] [25]
Triplet	max(0, d(q,p) - d(q,n) + margin)	Sensitive to negative mining	[24]
Proxy-based softmax	Classify embedding against learned class proxies	Stable at scale; used by Pinterest	[18]
SimCLR NT-Xent	Two augmented views as positives	Self-supervised pretraining	[23]
CLIP symmetric CE	Image<->text matching matrix	Multimodal search	[22]

Offline metrics

Metric	What it measures	Note
Recall@K	Share of relevant items in top K	Main retrieval metric; also measure ANN recall vs exact kNN
Precision@K	Share of top K that is relevant	Ignores order
MRR	1 / rank of first relevant result	Good when one right answer (same product)

Metric	What it measures	Note
mAP	Mean of average precision over queries	Needs binary relevance; book's choice for binary labels [1]
nDCG	Graded relevance, position discounted	Needs graded labels [1]
Human side-by-side	Raters compare old vs new results	Used at Pinterest and Bing [16][19]

Online metrics / A-B

Metric	Notes
CTR on results	Primary engagement signal [1]
Saves / repins per search, add-to-cart (shopping)	Stronger intent than clicks
Time spent on suggested images (daily/weekly)	Book's secondary metric [1]
Search abandonment, zero-click rate	Guardrail
Latency p50/p99, error rate	Guardrail
A-B design	User-level split; re-index needed per arm when the embedding space changes (two indexes side by side)

Serving & latency budget (typical)

Step	Budget	Notes
Upload + preprocess	20-40 ms	Client-side resize to cut bytes
Object detection (opt)	20-40 ms	GPU; can run on device
Embedding	15-40 ms	GPU batching, FP16/INT8, distilled model
ANN retrieval	10-30 ms	HNSW or IVF-PQ in memory, sharded; fan-out + merge
Filter + feature fetch	10-20 ms	Feature store / KV lookups
Rank + re-rank	10-30 ms	Light GBDT or MLP over ~300 candidates
Total	~100-200 ms server side	Cache embeddings of popular query images

Monitoring

What	Signal
Embedding drift	Mean/variance of query embeddings, nearest-neighbor distance distribution
Index health	Index size, staleness (time since last build), ANN recall on a probe set
Model version mismatch	Query encoder version must equal index encoder version
Quality	CTR, zero-result rate, human rating samples per week
Safety	NSFW leakage rate in results, takedown latency
System	p99 latency per stage, GPU utilization, shard hot spots

Failure modes

Failure	Cause	Mitigation
Duplicate-heavy results	Many reposts of the same image	Near-dup clustering, dedupe at re-rank
Wrong object matched	Cluttered photo, background dominates	Detector + user-selected crop [17]
Space mismatch after retrain	Query and index encoders differ	Full backfill, atomic index swap, version pinning
Popularity / position bias in labels	Clicks reflect slot, not relevance	Position feature, randomized slots, IPS weighting
Unsafe or private results	Missing filters	Pre-filter at index time + post-filter at serve
ANN recall loss	Over-compressed PQ, poor graph params	Tune nprobe/efSearch; exact rerank on top 1000
Cold new images	Not yet indexed	Streaming incremental index [29][30]
Domain shift (camera vs Pin photos)	Training on clean Pins only	Train on camera-query logs (Lens task) [17][18]

Interviewer follow-ups

- How do you build training data without human labels? Clicks vs augmentation vs image-text pairs.
- Why contrastive loss over classification? What is the role of temperature and batch size?
- How do you mine hard negatives, and what goes wrong if negatives are too hard (false negatives)?
- Exact kNN over 10 billion vectors is too slow: compare LSH, IVF-PQ, HNSW and ScaNN on recall, memory and update cost.
- How do you handle retraining when every catalog embedding must be recomputed (backfill cost, dual index)?
- The user's photo has five objects. How do you know which one they mean?
- How do you remove near-duplicates and keep the results diverse?
- How would you add text to the query ("this chair but in blue")?
- How do you personalize visual search without losing visual relevance?
- How do you keep NSFW, private or copyrighted images out of results?
- How do you compress embeddings for billions of images (binarization, PQ, lower dims)?
- How do you evaluate offline when relevance is subjective (style vs exact product)?
- How do you detect that the model degraded after a deployment?
- How do you serve new images within minutes of upload?
- How do you handle positional bias in click labels?
- Your index is 1B x 256-d floats (~1 TB). How do you fit it in RAM per shard (PQ, RaBitQ, binarization) and what recall do you lose? [33]
- How do you blend visual results with text search results for the same query (blender stage)? [5][17]

Portal comparison

Portal	Framing	Model	Training data	Retrieval	Metrics
ByteByte Go [1][2]	Pinterest-like; image or crop in, ranked similar images out; no personalization	CNN/ViT encoder, contrastive (softmax over 1 pos + n neg)	Clicks as positives or self-supervised augmentations	Embedding service + ANN (tree, LSH, clustering); indexing pipeline; re-rank filters	MRR, Recall@K, Precision@K, mAP, nDCG; CTR, time spent
Pinterest papers [16][17] [18]	Real product: Lens, Flashlight, Shop the Look	Detector + CNN embedding; later one multi-task proxy-loss embedding	Engagement logs + curated product matches per task	Distributed kNN, binarized embeddings	Human relevance judgments + engagement A-B
Bing / eBay / Alibaba [19][20] [21]	Web / commerce visual search	Category prediction + detection + embedding; multi-stage rerank	Click logs, catalog, human labels	Inverted / ANN index over billions, multi-stage	Precision, relevance ratings, conversion
alirezadir / Educativ e [4][5] [7][8]	Generic retrieval + ranking template	Two-stage: retrieve then rank	Logs with graded labels	ANN or inverted index	nDCG, CTR, conversion
Chip Huyen [3]	Open exercise (text-to-image variant)	Left to candidate	Left to candidate	Left to candidate	Emphasis on data and serving trade-offs

References

1. A. Aminian & A. Xu, "Machine Learning System Design Interview" (ByteByteGo; ch. 2 Visual Search System), book overview, 2023. https://opencourser.com/book/xop33f/machine-learning-system-design-interview (ch-ref, book)
2. ByteByteGo, "Visual Search System" (MLSDI course chapter), bytebytego.com, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/visual-search-system (book; URL follows the pattern of chapter URLs verified in this atlas, not fetched)
3. C. Huyen, "Machine Learning Systems Design: Exercises", GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md (fetched)
4. alirezadir, "ML System Design" template, GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (fetched)
5. alirezadir, "Search system design" (mlsd-search.md), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/mlsd-search.md (fetched)
6. alirezadir, "ML at Companies" (ml-companies.md), GitHub, 2025. https://github.com/alirezadir/AIMLInterviews/blob/main/src/MLSD/ml-companies.md (fetched)
7. Educative, "Grokking the Machine Learning Interview", educative.io, 2024. https://www.educative.io/courses/grokking-the-machine-learning-interview (ch-ref)

8. Educative / Khang Pham, "Machine Learning System Design", educative.io, 2021. https://educative.io/courses/machine-learning-system-design/introduction (ch-ref)
9. Exponent, "Introduction to the ML System Design Interview", tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
10. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery (ch-ref)
11. IGotAnOffer, "Machine Learning System Design Interview", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/machine-learning-system-design-interview (ch-ref)
12. IGotAnOffer, "Google Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/google-machine-learning-engineer-interview (ch-ref)
13. IGotAnOffer, "Meta Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/facebook-machine-learning-engineer-interview (ch-ref)
14. Meta Engineering, "Under the hood: Photo Search", engineering.fb.com. https://engineering.fb.com/ml-applications/under-the-hood-photo-search/ (link listed in [6]; not fetched, host unreachable in review)
15. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2021. http://patrickhalina.com/posts/ml-systems-design-interview-guide/ (ch-ref)
16. Y. Jing et al., "Visual Search at Pinterest", KDD 2015. https://arxiv.org/abs/1505.07647 (known)
17. A. Zhai et al., "Visual Discovery at Pinterest", WWW 2017. https://arxiv.org/abs/1702.04680 (known)
18. A. Zhai, H.-Y. Wu, E. Tzeng, D. H. Park, C. Rosenberg, "Learning a Unified Embedding for Visual Search at Pinterest", KDD 2019. https://arxiv.org/abs/1908.01707 (ch-ref)
19. H. Hu et al., "Web-Scale Responsive Visual Search at Bing", KDD 2018. https://arxiv.org/abs/1802.04914 (known)
20. F. Yang et al., "Visual Search at eBay", KDD 2017. https://arxiv.org/abs/1706.03154 (known)
21. Y. Zhang et al., "Visual Search at Alibaba", KDD 2018. https://arxiv.org/abs/2102.04674 (known)
22. A. Radford et al., "Learning Transferable Visual Models From Natural Language Supervision" (CLIP), 2021. https://arxiv.org/abs/2103.00020 (ch-ref)
23. T. Chen et al., "A Simple Framework for Contrastive Learning of Visual Representations" (SimCLR), 2020. https://arxiv.org/abs/2002.05709 (known)
24. F. Schroff, D. Kalenichenko, J. Philbin, "FaceNet: A Unified Embedding for Face Recognition and Clustering" (triplet loss), 2015. https://arxiv.org/abs/1503.03832 (known)
25. A. van den Oord, Y. Li, O. Vinyals, "Representation Learning with Contrastive Predictive Coding" (InfoNCE), 2018. https://arxiv.org/abs/1807.03748 (known)
26. J. Johnson, M. Douze, H. Jegou, "Billion-scale similarity search with GPUs" (FAISS), 2017. https://arxiv.org/abs/1702.08734 (ch-ref)
27. Y. Malkov, D. Yashunin, "Efficient and robust approximate nearest neighbor search using HNSW graphs", 2016. https://arxiv.org/abs/1603.09320 (ch-ref)
28. R. Guo et al., "Accelerating Large-Scale Inference with Anisotropic Vector Quantization" (ScaNN), ICML 2020 (arXiv 2019). https://arxiv.org/abs/1908.10396 (ch-ref; venue confirmed via [35])
29. Pinterest Engineering, "Manas HNSW Streaming Filters", Medium, 2022. https://medium.com/pinterest-engineering/manas-hnsw-streaming-filters-351adf9ac1c4 (ch-ref)

30. Pinterest Engineering, "Evolving Pinterest's Embedding Retrieval Platform", Medium, 2023. https://medium.com/pinterest-engineering/evolving-pinterests-embedding-retrieval-platform-aede4e831e01 (ch-ref)
31. M. Oquab et al., "DINOv2: Learning Robust Visual Features without Supervision", 2023. https://arxiv.org/abs/2304.07193 (known)
32. Meta Engineering, "Faiss: A library for efficient similarity search", engineering.fb.com, 2017. https://engineering.fb.com/2017/03/29/data-infrastructure/faiss-a-library-for-efficient-similarity-search/ (ch-ref)
33. FAISS wiki, "Guidelines to choose an index", GitHub. https://github.com/facebookresearch/faiss/wiki/Guidelines-to-choose-an-index (fetched)
34. Google Research, "Announcing ScaNN: Efficient Vector Similarity Search", research.google, 2020. https://research.google/blog/announcing-scann-efficient-vector-similarity-search/ (ch-ref)
35. Google Research, "ScaNN: Scalable Nearest Neighbors" README (cites anisotropic VQ, ICML 2020, and SOAR, NeurIPS 2023), GitHub. https://github.com/google-research/google-research/tree/master/scann (fetched)

11. Design Multimodal Video Search (YouTube Search over Text + Visual + Audio)

> Prompt as usually given: "A user types a text query. Return the most relevant videos from a catalog of about 1B, ranked." The multimodal version asks you to search what is *inside* the video (frames, speech, on-screen text), not only the title and tags. Variants: in-video moment search ("find the scene where..."), podcast/audio search, query-by-image or query-by-clip, and personalised search.
>
> Sourcing note: during compilation and review the shared web-search budget was used up and most portal hosts, company blogs and arxiv.org could not be reached from the build sandbox. GitHub pages were fetched and read (re-checked in review: [3][4][5][6][7][8][11]). Each reference carries a tag. (fetched) means the page was read for this chapter. (ch-ref) means the URL was verified in another chapter of this atlas. (known) means a canonical paper cited by its arXiv ID. (book) means the structure is taken from the published book. Company tags separate "built it" (a paper or engineering blog exists) from "asked it" (an interview report). The "asked it" evidence is thin, so treat it as indicative only.

Company tags

Company	Evidence	Notes	Source
Google / YouTube	Built it: no public paper on YouTube *search* itself; adjacent public work is YouTube recs [18][37], YouTube-8M video understanding [38], VideoPrism video encoder [39], Google Search [23]. The book chapter is "YouTube Video Search". Asked it (indicative): Google MLE loops include ML design	Canonical framing of the problem	[1][2] [14][18] [23][37] [38][39]
Meta (FB / IG video, Reels)	Built it: photo search, Rosetta (text in images and video), embedding-based retrieval in FB search. Asked it (indicative): Meta MLE loops include ML design	Multimodal content understanding at billions scale	[6][15] [19][20] [21]
Netflix	Built it: in-video search (2023), listed in [7]	Mirrors the "moment search" variant	[7][22]
Spotify	Built it: natural-language podcast episode search (2022), listed in [7]	Mirrors the audio/ASR branch (dense + lexical hybrid)	[7][24]

TikTok, Amazon Prime Video and similar tags were removed in review: no interview report or public system write-up could be confirmed.

Portals that cover it


Portal	Treatment	Link
ByteByteGo (Aminian & Xu, MLSDI), ch. 4 "YouTube Video Search"	The fullest treatment. Visual search (two-tower, contrastive) plus text search (inverted index), fusion, re-ranking	[1][2]
alirezadir AIMLInterviews, "Multimodal video search" case	Book-style summary: 1B videos, 50M DAU, 10M labelled pairs, BERT + ViT/ViViT, MRR, watch time. Its MLSD template lists "Image/Video search" and "Multimodal search" as sample questions	[3][4]
alirezadir, "Image search" case	Same contrastive / ANN template for the visual tower	[5]
Chip Huyen, ML Systems Design exercises	Ex. 6 "return images associated with a query like in Google Images"; Ex. 14 trigger-word audio detection (audio branch)	[8]
Educative "Grokking the ML Interview" / Khang Pham MLSD	Search ranking (staged funnel, LTR) in [9]; Khang Pham's repo lists Airbnb search ranking and YouTube recs cases, not video search	[9][10] [11]
Exponent, Hello Interview, IGotAnOffer, Patrick Halina	Generic MLSD framework, timing, rubric. Use them for delivery, not for this problem's content	[12][13] [14][16] [17]

Requirements & scale

Dimension	Value	Source
Functional	Text query in, ranked list of videos out. Match title/desc/tags *and* visual content	[1][3]
Extended functional	Speech (ASR) and on-screen text (OCR) searchable; optional moment timestamps	assumption, [19] [22]
Personalisation	Not required in the book version; add as a follow-up	[3]
Users	50M DAU	[3]
Catalog	1B videos with title, description, tags	[3]
Training data	10M annotated (video, text query) pairs	[3]
Uploads	~500 hours of video per minute (YouTube-scale), so indexing must be streaming	assumption
QPS	50M DAU x ~5 searches/day = ~3k QPS avg, ~10k peak	assumption
Latency	p99 under 200-300 ms end to end; ANN under 20 ms per shard	assumption
Freshness	New upload searchable by text in minutes, by visual/ASR embedding within ~1 h	assumption
Languages	Open question in the source. Assume multilingual text encoder	[3]
Business goal	Higher CTR and total watch time from search	[3]

DIAGRAM 1: Online serving path

Figure 11.1 - Query-time path: hybrid retrieval (lexical + dense multimodal), fusion, ranking, policy re-rank.




Sources: two-path design (visual ANN plus Elasticsearch text search), fusion by weighted sum or re-rank model, then business-rule re-rank [1][3]. ASR and audio branches added per production systems [19][22][24].

Stage	Input -> output	Typical budget	Notes
Query understanding	raw text -> normalised q, lang, intent	10-20 ms	Spell-fix, synonym, safe-search intent
Query encode	q -> 256-768-d vector	5-15 ms (GPU/CPU distilled)	Cache top-1M head queries
Lexical retrieval	q -> ~1k docs	20-40 ms	BM25 over title/desc/tags/ASR/OCR [1][3]
Dense ANN (x3 indexes)	q_emb -> ~500-1k each	10-20 ms each, parallel	HNSW / ScaNN / FAISS-IVFPQ [25][26][27]

Stage	Input -> output	Typical budget	Notes
Fusion + filter	~3k -> ~400	5-10 ms	RRF or learned weights [1][28]
Ranker	~400 -> top 100	30-60 ms	GBDT or small cross-encoder; position-debiased labels [36]
Re-rank / policy	100 -> 20	5 ms	Rules [1][3]
Total		~150-250 ms p99	assumption

DIAGRAM 2: Offline indexing, training and data pipeline


Figure 11.2 - Two loops: (a) per-upload indexing of every modality, (b) periodic training of encoders and ranker from labels and search logs.



Sources: preprocessing steps (decode, sample, resize, normalise; text normalise, tokenise) [3]; indexing and ANN pipeline [5]; OCR for text in video [20]; ASR [32].

DIAGRAM 3: Model architecture


Figure 11.3 - Multimodal dual encoder (retrieval) plus learning-to-rank head.



Sources: two-tower with text encoder (BERT) and video encoder (frame-level ViT aggregated vs video-level ViViT) [1][3]; contrastive training [3][5]; CLIP image-text pretraining [29]; CLIP4Clip temporal pooling variants [30]; ViViT [31].

DIAGRAM 4: Variant - in-video moment search (Netflix / long-form)

Figure 11.4 - Moment search: index shots, not whole videos; return (video, t_start, t_end).



Sources: Netflix in-video search [7][22]; segment-level text-video retrieval [30][33].

Data & labels

Source	Label	Pros	Cons	Source
Human-annotated (query, video) pairs	Relevant / graded 0-4	Clean, measures relevance	Expensive; 10M pairs in book setup	[1][3]
Search logs	Click + watch > X s = positive; skip / quick-back = negative	Free, huge, fresh	Position bias, clickbait, popularity bias	[3]
Title/desc as weak caption	(title, video) pair	Billions of pairs	Noisy, SEO spam	[29] [33]
ASR transcript windows	(speech, clip) pair	Self-supervised alignment	Speech often not about visuals	[33] [34]
Query reformulation	q1 -> q2 within session	Negative for q1 results	Ambiguous	assumption
Debiased clicks	Clicks reweighted by inverse examination propensity	Removes position bias from log labels	Needs propensity estimates (randomisation or click model)	[36]

Features

Group	Features	Used at
Query	Tokens, language, length, intent class, query embedding, query popularity	Retrieval + rank
Video content	Frame embedding, audio/ASR embedding, OCR text, title/desc/tags, duration, language	Indexing + rank
Query-video	BM25 per field, cosine per modality, historical CTR / watch for (q, v)	Rank
Video quality	Views, like ratio, upload age, channel authority, policy flags	Rank + policy
User (optional)	Language, region, watch history embedding, subscriptions	Personalised rank
Context	Device, time, safe-search setting	Filter + rank

Model choices

Component	Baseline	Better	Advanced	Tradeoff	Source
Text matching	BoW / TF-IDF / BM25	word2vec avg	BERT-family encoder	Semantics vs cost	[1][3]
Video encoder	Frame-level ViT + mean pool	Frame ViT + temporal transformer (CLIP4Clip)	Video-level ViViT	Temporal info vs train/serve cost	[3][30] [31]
Audio	ASR text into lexical index	ASR text embedding	Audio encoder in joint space	Coverage vs index size	[32] [35]
Retrieval	Inverted index only	+ dense two-tower ANN	Per-modality ANN + learned fusion	Recall vs memory	[1][25]

Component	Baseline	Better	Advanced	Tradeoff	Source
Fusion	Weighted sum of scores	RRF	Learned LTR on all scores	Simplicity vs quality	[1][28]
Ranker	Hand-tuned weights	GBDT LambdaMART	Cross-encoder on top-50	Latency vs precision	assumption
Pretraining	ImageNet ViT	CLIP image-text	Video-text (HowTo100M, MIL-NCE, VideoCLIP)	Data domain match	[29] [33] [34]

Loss functions

Model	Loss	Notes	Source
Dual encoder	InfoNCE / softmax contrastive, in-batch negatives, temperature tau	Symmetric (q->v and v->q) as in CLIP	[3][29]
Dual encoder (noisy ASR pairs)	MIL-NCE	Several nearby clips count as positives	[34]
Hard-negative mining	Same loss with mined near-misses	Mine from ANN results of the previous model	assumption
Dual encoder, in-batch negatives	Sampled softmax with logQ correction	Popular videos appear as negatives too often; subtract log sampling prob	[37]
Ranker	LambdaRank / listwise softmax on graded labels	Optimises nDCG directly	assumption
Multi-objective rank	BCE(click) + regression(watch time)	Combine with weights at serve time	[14]

Offline metrics

Metric	Why	Source
MRR	Book choice: eval set is (video, text) pairs with one known positive	[1][3]
Recall@k (k=100-1000)	Retrieval stage: did the right video survive?	[3]
Precision@k, mAP	Considered, less fit for single-positive sets	[3]
nDCG@10	Graded human labels at rank stage	[5]
Per-modality ablation	Recall@k with visual / audio / text index off	assumption
Public benchmarks	MSR-VTT, HowTo100M-style text-video retrieval R@1/5/10	[30][33]

Online metrics & A/B

Metric	Verdict in source	Note
CTR	Rejected as primary: rewards clickbait, not relevance	[3]
Video completion rate	Rejected: partial watch can still be relevant	[3]
Total watch time from search	Chosen primary	[3]

Metric	Verdict in source	Note
Successful-session rate, zero-result rate, query reformulation rate	Add as guardrails	assumption
Latency p99, abandonment	Guardrails	assumption
Human side-by-side relevance ratings	Pre-launch gate	Rater guideline style as in [40]

Serving & latency

Concern	Choice	Source
Index size	1B x 256-d fp32 = ~1 TB per modality; PQ to 32-64 B/vec = 32-64 GB	[25][26]
ANN algorithm	IVF-PQ (FAISS), ScaNN, or HNSW; shard by video id, replicate for QPS	[25][26] [27]
Encoder serving	Query tower online (distilled, cached); video towers offline batch only	[3]
Encoder upgrade	Re-embed full catalog, dual-index, atomic swap; query + video towers must match	assumption
Cold start (new upload)	Lexical index in minutes; embeddings within ~1 h; freshness boost in re-rank	assumption
Cost control	Embed only sampled frames / shots; skip re-embedding low-view long tail	assumption

Monitoring

Signal	Alert on	Source
Zero-result and low-confidence query rate	Spike after index or model swap	assumption
Embedding drift	Mean cosine of query vs top-1 falling; distribution shift per language	assumption
Index health	Index lag behind uploads, shard recall vs brute-force sample	[26]
Online metrics	Watch time from search, CTR, reformulation rate by query segment	[3]
Policy	Rate of removed / borderline videos in top-10	assumption

Failure modes

Failure	Symptom	Mitigation
Clickbait thumbnails/titles	High CTR, short watch	Optimise watch time; quality features [3]
Keyword stuffing / tag spam	Lexical path returns irrelevant videos	Field weights, spam classifier, dense path cross-check
Visual-text mismatch	Video ranked for words only spoken, never shown (or vice versa)	Per-modality scores into ranker
ASR errors / low-resource languages	Missed matches	Multilingual encoders, phonetic fuzzy match

Failure	Symptom	Mitigation
Stale index after encoder change	Recall collapse	Version-locked towers, dual-write, shadow eval
Head-query bias	Long-tail queries poor	Hard negatives, query rewriting, human labels on tail
Harmful / policy content	Unsafe results for benign queries	Filter + demotion stage, safe-search

What production systems add beyond the portal answer

Addition	Why it matters	Source
Position-bias correction on click/watch labels	Log labels otherwise teach the ranker its own past order	[36]
logQ sampling-bias correction for in-batch negatives	Corrects popularity skew in two-tower training at YouTube scale	[37]
Pretrained video foundation encoder (YouTube-8M, VideoPrism)	Video tower is pretrained on large YouTube-derived data, then tuned for retrieval	[38][39]
Shot-level index for moments	Netflix indexes moments, not whole titles	[22]
Hybrid dense + lexical for spoken content	Spotify added semantic episode search alongside term matching	[24]
Text in frames (OCR) as a searchable field	Rosetta extracts text from images and video frames	[20]
Human rater guidelines and side-by-side evals	Launch gate independent of engagement metrics	[40]
Query autocomplete and spell correction	Many sessions start from suggestions; cuts zero-result queries	assumption

Interviewer follow-ups

- Why not just use Elasticsearch on titles? What does the visual tower add, and for which queries?
- Frame-level vs video-level encoder: how do you pick, and what does each cost to serve 1B videos? [3]
- How do you fuse lexical and dense scores? Why RRF vs a learned weight? [1][28]
- Why MRR offline and watch time online? Why not CTR? [3]
- How do you get 10M labelled pairs? What if you only have click logs (position bias)?
- How do you index audio: ASR text, audio embeddings, or both?
- The video encoder changes. How do you re-embed 1B videos without downtime?
- How do you make a video uploaded 5 minutes ago searchable?
- One embedding with fused modalities vs separate ANN indexes per modality: tradeoffs?
- How do you add personalisation without hurting relevance for new users?
- How would you return timestamps (moment search) instead of whole videos? [22]
- How do you handle multilingual queries against videos in another language?
- How do you measure and reduce index memory (PQ, dimension reduction)? [25]
- How do you stop the system surfacing harmful content for innocent queries?
- How would you use an LLM or VLM here (query rewriting, captioning frames into text)?

- Click logs are position-biased. How do you build unbiased labels? [36]
- In-batch negatives over-penalise popular videos. How do you correct it? [37]
- Would you pretrain the video tower yourself or start from a video foundation model? [38][39]

Portal comparison

Portal	Retrieval	Encoders	Fusion / rank	Metrics	Distinctive point
ByteByteGo ch. 4 [1][2]	Visual two-tower ANN + text inverted index	BERT text; ViT frames or ViViT	Weighted fusion, then business re-rank	MRR offline; watch time online	Explicit rejection of CTR and completion rate
alirezadir AIMLInterviews [3]	Same as book (summary); ANN for visual, Elasticsearch for text	Same; video encoder choice left open	Weighted sum or re-rank model	P@k, mAP, R@k, MRR; watch time	Gives scale numbers (1B, 50M DAU, 10M pairs); deployment and scaling/monitoring sections left empty
alirezadir image search [5]	Embedding + ANN (FAISS; tree, LSH, clustering), VQ/PQ	CNN / ViT, contrastive	Business-rule re-rank	MRR, R@k, nDCG; CTR, time spent	Positive sources: human, clicks, augmentation
Chip Huyen exercises [8]	Open question (Google Images)	n/a	n/a	n/a	Text query to images; separate audio trigger-word exercise
Educative / Khang Pham [9] [10][11]	Staged funnel (retrieval -> rank)	Generic search features	LTR	nDCG, engagement	Strong on LTR and data generation; weak on visual content
Production (Netflix, Meta, Spotify) [19] [21][22][24]	Hybrid lexical + embedding	CLIP-style, OCR, ASR	Learned	Internal	Moment-level index; text-in-video; NL podcast search

References

1. A. Aminian & A. Xu, "Machine Learning System Design Interview" (ByteByteGo; ch. 4 YouTube Video Search), book overview, 2023. https://opencourser.com/book/xop33f/machine-learning-system-design-interview (ch-ref, book)
2. ByteByteGo, "YouTube Video Search" (MLSDI course chapter), bytebytego.com, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/youtube-video-search (book; URL matches the chapter-URL pattern used across this atlas; host unreachable in review)
3. alirezadir, "Multimodal Video Search System" (mlsd-mm-video-search.md), GitHub, 2023. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/mlsd-mm-video-search.md (fetched)
4. alirezadir, "ML System Design" template (lists image/video, multimodal and visual search), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (fetched)
5. alirezadir, "Image Search System" (mlsd-image-search.md), GitHub, 2023. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/mlsd-image-sear

ch.md (fetched)
6. alirezadir, "ML at Companies" (ml-companies.md), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-companies.md (fetched)
7. Engineer1999, "A Curated List of ML System Design Case Studies", GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies (fetched)
8. C. Huyen, "Machine Learning Systems Design: Exercises", GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md (fetched)
9. Educative, "Grokking the Machine Learning Interview", educative.io, 2024. https://www.educative.io/courses/grokking-the-machine-learning-interview (ch-ref)
10. Educative / K. Pham, "Machine Learning System Design", educative.io, 2021. https://educative.io/courses/machine-learning-system-design/introduction (ch-ref)
11. K. Pham, "machine-learning-interview", GitHub, 2021. https://github.com/khangich/machine-learning-interview (fetched; lists Airbnb search ranking and YouTube recs)
12. Exponent, "Introduction to the ML System Design Interview", tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
13. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery (ch-ref)
14. IGotAnOffer, "Google Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/google-machine-learning-engineer-interview (ch-ref)
15. IGotAnOffer, "Meta Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/facebook-machine-learning-engineer-interview (ch-ref)
16. IGotAnOffer, "Machine Learning System Design Interview", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/machine-learning-system-design-interview (ch-ref)
17. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2020. http://patrickhalina.com/posts/ml-systems-design-interview-guide/ (ch-ref)
18. P. Covington, J. Adams, E. Sargin, "Deep Neural Networks for YouTube Recommendations", RecSys / Google Research, 2016. https://research.google/pubs/pub45530/ (ch-ref)
19. Meta Engineering, "Under the hood: Photo search", engineering.fb.com, 2017. https://engineering.fb.com/ml-applications/under-the-hood-photo-search/ (listed in [6])
20. Meta AI, "Rosetta: Understanding text in images and videos with machine learning", ai.facebook.com, 2018. https://ai.facebook.com/blog/rosetta-understanding-text-in-images-and-videos-with-machine-learning/ (listed in [6])
21. J.-T. Huang et al., "Embedding-based Retrieval in Facebook Search", KDD, 2020. https://arxiv.org/abs/2006.11632 (known)
22. Netflix Technology Blog, "Building In-Video Search", 2023. https://netflixtechblog.com/building-in-video-search-936766f0017c (listed in [7])
23. Google, "How Google Search works", google.com. https://www.google.com/search/howsearchworks/ (listed in [6])
24. Spotify Engineering, "Introducing Natural Language Search for Podcast Episodes", 2022. https://engineering.atspotify.com/2022/03/introducing-natural-language-search-for-podcast-episodes/ (listed in [7])
25. J. Johnson, M. Douze, H. Jegou, "Billion-scale similarity search with GPUs" (FAISS), 2017. https://arxiv.org/abs/1702.08734 (ch-ref)

26. R. Guo et al., "Accelerating Large-Scale Inference with Anisotropic Vector Quantization" (ScaNN), ICML, 2020. https://arxiv.org/abs/1908.10396 (ch-ref)
27. Y. Malkov, D. Yashunin, "Efficient and robust approximate nearest neighbor search using HNSW graphs", 2016. https://arxiv.org/abs/1603.09320 (ch-ref)
28. G. Cormack, C. Clarke, S. Buettcher, "Reciprocal Rank Fusion outperforms Condorcet and individual Rank Learning Methods", SIGIR, 2009. https://plg.uwaterloo.ca/~gvcormac/cormacksigir09-rrf.pdf (known)
29. A. Radford et al., "Learning Transferable Visual Models From Natural Language Supervision" (CLIP), 2021. https://arxiv.org/abs/2103.00020 (ch-ref)
30. H. Luo et al., "CLIP4Clip: An Empirical Study of CLIP for End to End Video Clip Retrieval", 2021. https://arxiv.org/abs/2104.08860 (known)
31. A. Arnab et al., "ViViT: A Video Vision Transformer", ICCV, 2021. https://arxiv.org/abs/2103.15691 (known)
32. A. Radford et al., "Robust Speech Recognition via Large-Scale Weak Supervision" (Whisper), 2022. https://arxiv.org/abs/2212.04356 (known)
33. A. Miech et al., "HowTo100M: Learning a Text-Video Embedding by Watching Hundred Million Narrated Video Clips", ICCV, 2019. https://arxiv.org/abs/1906.03327 (known)
34. A. Miech et al., "End-to-End Learning of Visual Representations from Uncurated Instructional Videos" (MIL-NCE), CVPR, 2020. https://arxiv.org/abs/1912.06430 (known)
35. R. Girdhar et al., "ImageBind: One Embedding Space To Bind Them All", CVPR, 2023. https://arxiv.org/abs/2305.05665 (known)
36. T. Joachims, A. Swaminathan, T. Schnabel, "Unbiased Learning-to-Rank with Biased Feedback", WSDM, 2017. https://arxiv.org/abs/1608.04468 (known)
37. X. Yi et al., "Sampling-Bias-Corrected Neural Modeling for Large Corpus Item Recommendations" (YouTube), RecSys, 2019. https://doi.org/10.1145/3298689.3346996 (known)
38. S. Abu-El-Haija et al., "YouTube-8M: A Large-Scale Video Classification Benchmark", Google, 2016. https://arxiv.org/abs/1609.08675 (known)
39. L. Zhao et al., "VideoPrism: A Foundational Visual Encoder for Video Understanding", Google, ICML, 2024. https://arxiv.org/abs/2402.13217 (known)
40. Google, "Search Quality Rater Guidelines", guidelines.raterhub.com. https://static.googleusercontent.com/media/guidelines.raterhub.com/en//searchqualityevaluatorguidelines.pdf (known)

12. Design Harmful Content Detection / Content Moderation (Facebook/Instagram Integrity)

> Prompt as usually given: "Users post text, images and videos on a social platform. Design a system that detects harmful posts (violence, nudity, hate speech, self-harm, spam, misinformation) and removes or demotes them." Variants: comment toxicity, hateful memes (image + text), message moderation in DMs or dating apps, LLM guardrails, spam/abusive accounts (actor-level integrity).
>
> Sourcing note: at review time (Oct 2026) web search was exhausted and ai.meta.com, about.fb.com, arxiv.org and bytebytego.com did not resolve from the build sandbox; only GitHub was reachable. Tags: (fetched) = read for this chapter; (repo-link) = URL appears verbatim in a fetched index (ByteByteGo's ml-bytebytego ch. 5 reference list [2] or the Engineer1999 list [11]); (ch-ref) = verified in another chapter; (known) = canonical paper by arXiv ID. Only "built it" company tags with a source are kept.

Company tags

Company	Evidence	Notes	Source
Meta (Facebook, Instagram)	Built it: WPIE, XLM-R + Linformer hate-speech models, Few-Shot Learner, TIES	The canonical "house problem" for Meta MLE / integrity loops; ByteByteGo ch. 5 frames it on a Facebook-like platform	[1][3][12] [13][14] [15][16] [18]
Pinterest	Built it: ML for misinformation, hate speech and self-harm; comment-health models	Pin-level multimodal classifiers using PinSage/visual/text embeddings	[20][21]
LinkedIn	Built it: viral spam detection; isolation forest for abuse	Spam / abusive actor framing	[22][23]
Bumble, Nextdoor, Whatnot, Slack	Built it: rude-message detection (multilingual DMs); harmful-comment prediction; GenAI marketplace-spam T&S; invite-spam blocking	Variant systems for DM / comment / marketplace prompts (as indexed in [11])	[24][25] [26][27]

Portals that cover it

Portal	Treatment	Link
ByteByteGo (Aminian & Xu, MLSDI), ch. 5 "Harmful Content Detection"	Fullest treatment: multimodal early fusion, multi-task heads, BCE per task, prevalence / proactive rate, demotion vs violation services	[1] [2]
alirezadir Machine-Learning-Interviews, "mlsd-harmful-content"	Condensed notes of the book chapter: 500M posts/day (~10K annotated), DistilmBERT + CLIP + VideoMoCo, gradient blending, focal loss; listed under "Harmful content / Spam detection" in the MLSD index	[3] [4]

Portal	Treatment	Link
Educative "Grokking the ML Interview" / Khang Pham MLSD	Generic classification + ranking templates (no dedicated chapter verified); reuse the classifier pattern	[5] [6]
Exponent, Hello Interview, IGotAnOffer, Patrick Halina	MLSD delivery frameworks and Meta MLE loop guides; no dedicated harmful-content chapter verified	[7] [8] [9] [10]
Engineer1999 curated case studies	Index of real T&S / spam / fraud systems from 20+ company blogs	[11]

Requirements & scale

Dimension	Value	Source
Functional	Input: a post (text, image(s), video, links, author). Output: per-category harm probabilities, action (remove / demote / send to review / allow), and a user-visible reason	[1][3]
Harm categories	Violence, nudity, hate speech (+ self-harm, spam, misinformation, bullying in variants)	[1][3][20]
Out of scope (book)	Harmful actors (fake / inauthentic accounts) and harmful acts; added as follow-ups	[3][37]
Explainability	Must tell the user which policy was violated; appeals flow	[1][3]
Volume	~500M new posts/day (~6K posts/s avg, ~15-20K/s peak)	[3] (book)
Labels	~10K posts hand-annotated (eval set); user reports ("natural labels") for the training set	[3] (book)
Languages	100+ languages; multilingual encoder required	[14][15]
Latency	Varies by category: blocking classes (CSAM, terror) pre-publish p99 < ~200-500 ms; most classes near-real-time (seconds to minutes) after publish; re-scoring on virality	[3] + typical assumption
Precision / recall	Auto-remove needs very high precision (~95%+); demotion and review queues trade precision for recall	typical assumption
Adversarial	Evasion (text in image, leetspeak, re-encoded media), fast drift of new harm types	[16][17]
Known-bad media	Re-uploads of known CSAM / terror / NCII media matched by perceptual hash before any model	[36]

Diagram 1: end-to-end serving architecture

Diagram 1. Online moderation path (post -> hash match -> cheap filters -> multimodal classifier -> policy engine -> remove / demote / review / allow)




Diagram 2: offline training & data pipeline

Diagram 2. Labels -> features -> multi-task training -> evaluation -> registry -> shadow/canary deploy, with reviewer and appeal feedback loops




Diagram 3: model architecture

Diagram 3. Early-fusion multimodal multi-task classifier (ByteByteGo / book design, with WPIE-style whole-post embedding) [1][3][13][29][31][33][34]




Diagram 4: real company system (Meta integrity stack)

Diagram 4. Meta-style layered integrity system: WPIE + XLM-R/Linformer + Few-Shot Learner + TIES (actor/interaction signals); borderline content is demoted, not removed [13][14][16][17][18][19][28]



Data & labels

Source	Label type	Pros	Cons
Human reviewers (contractors)	Gold, per-policy multi-label	Accurate, policy-aware; book uses them for the eval set [3]	Slow, costly (~10K labelled), reviewer wellbeing, disagreement; review tooling at scale [38]
User reports	Natural, noisy positive	Huge volume, fast	Brigading, bias, many false reports; few negatives
Appeals overturned	Label correction	Fixes false positives	Sparse, delayed
Hash banks (known violating media)	Exact / near-dup positive (PDQ, TMK+PDQF, vPDQ; shared via ThreatExchange / HMA) [36]	Zero-shot removal of re-uploads; cross-company sharing	Only known content
Synthetic / LLM-generated	Augmented positives	New harm types, rare languages	Distribution shift
Split strategy	Time-based split; dedup by media hash across splits	Avoids leakage of near-dup memes	-

Features

Group	Examples	Encoding
Text	Caption, hashtags, OCR from images, ASR from video, comments	Multilingual transformer (DistilmBERT / XLM-R) [15] [34][39]; comments aggregated
Image	Pixels, detected objects, faces	CLIP / SimCLR embedding [31][32]

Group	Examples	Encoding
Video	Frames, audio	VideoMoCo / frame-pooled image encoder + audio model [33]
Author	Account age, followers, prior violations, report rate, profanity rate	Numeric, bucketized; embedding of author
Interactions	Likes, shares, comments, reports, view velocity	Counts, ratios, time-decayed
Context	Time of day, device, country/language, group/page type	One-hot / embedding
Graph / actor	Interaction sequences, cluster membership	TIES-style temporal embeddings [18]

Model choices (baseline -> advanced)

Option	Description	Pros	Cons
Rules + keyword lists	Regex, blocklists, hash match	Instant, explainable	Low recall, easy to evade
Late fusion	One model per modality, combine scores	Simple, modular, debuggable	Misses harm that only appears in combination (hateful memes [35] [40])
Early fusion (book choice)	Concatenate/attend modality embeddings, one classifier	Captures cross-modal harm	Harder to train, needs more data
Single binary classifier	"harmful vs not"	Simple	No category -> no explanation; hard to set per-class thresholds
One model per category	Separate binary models	Independent tuning	N models to train/serve/maintain
Multi-label single head	One output layer, K sigmoids	One model	Shared features may not fit all classes
Multi-task (book choice)	Shared trunk + per-task heads	One model, data sharing helps rare classes, explainable	Task interference; loss weighting
Foundation / few-shot (FSL)	Policy-text entailment, LLM classifier [16][17]	Fast adaptation to new policies	Expensive; needs distillation for serving
Efficient transformer	XLM-R with Linformer linear attention [14][28]	Serve large multilingual model on every post	Approximation; engineering cost
LLM-as-reviewer	LLM judges borderline items with policy prompt	Explainable, flexible	Cost, latency, jailbreak / prompt-injection

Loss

Loss	When
Sum of per-task BCE	Default multi-task multi-label
Weighted BCE / class weights	Severe imbalance (prevalence often < 0.1%)
Focal loss [30]	Focus on hard, rare positives
Gradient blending [29]	One modality dominating or overfitting in multimodal training

Loss	When
Label smoothing / noise-robust loss	Noisy user-report labels

Offline metrics

Metric	Why
PR-AUC per category	Highly imbalanced data; ROC-AUC over-optimistic
Recall @ fixed precision (e.g. P >= 95%)	Matches auto-remove threshold
F1	Single threshold summary
ROC-AUC	Ranking quality, threshold-free
Per-language / per-market slices	Fairness and coverage across 100+ languages
Calibration (ECE)	Thresholds and severity x reach depend on calibrated probabilities

Online metrics / A-B

Metric	Definition
Prevalence	Harmful posts (or views) not prevented / all posts (views) [3][13]
Harmful impressions	Views of harmful content before action
Proactive rate	Detected by system / (system + user reports) [3][14]
Valid appeals rate	Successful (reversed) appeals / removals (false positive proxy) [3]
User reports per 1K views	Leading indicator of misses
Reviewer throughput / queue latency	Ops health
Guardrails	Engagement / creator retention of non-violating content (over-enforcement)
A-B caveat	Holdouts limited by ethics; rely on shadow scoring + enforcement on small % + interleaved reviewer audits

Serving & latency budget

Stage	Budget (typical)	Notes
Hash match	< 10 ms	Perceptual hash lookup
Rules / cheap filters	< 5 ms	In-process
Feature fetch	10-20 ms	Online KV store
Text encoder	10-30 ms	Distilled / quantized, GPU or CPU
Image encoder	20-50 ms	GPU batch, cached by media hash
Video	seconds (async)	Sample frames; score after publish
Fusion + heads	< 5 ms	Small MLP
Policy engine	< 5 ms	Thresholds per market
Total pre-publish (blocking classes)	~100-200 ms p99	Else async post-publish within seconds

Monitoring

Signal	Action
Score distribution drift per category / language	Alert, re-calibrate thresholds
Spike in user reports or appeals	Trigger re-scoring, retraining
Reviewer disagreement with model	Error analysis, label audit
New adversarial patterns (text-in-image, leetspeak)	Add to red-team set, retrain
Latency / GPU saturation	Fall back to cheaper text-only model
Prevalence dashboard (sampled reviewer audit)	North-star tracking

Failure modes

Failure	Mitigation
Adversarial evasion	OCR/ASR, augmentation, hash near-dup, fast few-shot updates
Label noise and reviewer bias	Multi-rater consensus, gold sets, noise-robust losses
Over-enforcement on dialects / minority languages	Per-slice metrics, fairness thresholds
One modality dominates	Gradient blending, modality dropout
New harm type (e.g. new scam, crisis event)	FSL / LLM classifier, rules as stop-gap
Viral harmful post before review	Prioritise by severity x predicted reach; re-score on velocity
Cold-start languages	Cross-lingual transfer (XLM-R)
Feedback loop bias (only reported posts labelled)	Random sampling for audits, active learning

Often-missed components (portal / real-system gaps)

Component	What to add	Source
Hash-sharing / hasher-matcher-actioner	Maintain banks of PDQ / TMK+PDQF / vPDQ hashes, sync with industry exchanges, act on matches before the classifier	[36]
Borderline-content demotion	Content close to (but not violating) policy gets reduced distribution, not removal; separate threshold band	[19]
Human review system at scale	Queue routing by policy + language, reviewer tooling, wellbeing (blur, time limits), QA on reviewer accuracy	[38]
Inauthentic-behaviour / actor layer	Account-level classifiers (fake accounts, coordinated behaviour) feed author-risk into post scoring	[18] [37]
Benchmarks for multimodal hate	Hateful Memes dataset and MMF baselines to test early vs late fusion	[35] [40]

Interviewer follow-ups

- How do you handle severe class imbalance (prevalence well under 1%)?
- Early vs late fusion: when does late fusion fail? (hateful memes)
- Why multi-task over one model per category? How do you weight task losses?
- How do you pick thresholds for remove vs demote vs human review?
- How do you prioritise the human-review queue (severity x reach)?

- How do you measure prevalence without labelling everything?
- How do you handle 100+ languages and low-resource languages?
- A new harm type appears today: how fast can you ship a classifier? (few-shot, rules, LLM)
- How do you defend against adversarial users (text in images, re-encoded video)?
- How do you deal with noisy, biased user-report labels and reviewer bias?
- Pre-publish blocking vs post-publish detection: what goes where and why?
- How would you detect harmful actors (fake accounts) rather than content? (TIES, graph)
- How do you explain decisions to users and handle appeals?
- How do you serve video cheaply at 500M posts/day?
- How would you use an LLM in this system without blowing latency and cost budgets?
- How would you share hashes of known violating media with other platforms, and how do you keep false matches low? [36]
- How do you treat borderline content differently from violating content? [19]
- How do you scale and quality-check the human review operation? [38]

Portal comparison

Portal	Framing	Model	Metrics emphasis	Distinctive points
ByteByteGo ch. 5 [1][2]	Multimodal post classifier on social media	Early fusion + multi-task heads, BCE sum	PR-AUC offline; prevalence, proactive rate, appeals online	Demotion vs violation services; gradient blending; focal loss
alirezadir notes [3]	Same as book, condensed	DistilmBERT + CLIP/SimCLR + VideoMoCo	F1, PR-AUC, ROC-AUC	Lists follow-ups: labeling bias, temporal signals, fake accounts, linear transformers
Meta engineering (real system) [13]-[17]	Layered integrity stack	WPIE, XLM-R + Linformer, FSL, TIES	Prevalence, proactive detection rate	Few-shot policy adaptation; RL-tuned enforcement
Pinterest engineering [20] [21]	Pin / comment health	Embedding-based multi-head classifiers	Precision at action thresholds	Uses existing Pin embeddings; batch + online scoring
Generic MLSD guides (Exponent, Hello Interview, IGotAnOffer, Halina) [7]-[10]	Framework-level	Classifier template	Precision/recall tradeoff	Emphasis on clarifying requirements and delivery structure

References

1. A. Aminian, A. Xu, "Machine Learning System Design Interview", ch. 5 "Harmful Content Detection", ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/harmful-content-detection (book)
2. ByteByteGo, "ml-bytebytego: references for Machine Learning System Design Interview", GitHub, 2023. https://github.com/ByteByteGoHq/ml-bytebytego (fetched)
3. alirezadir, "Harmful content detection" (mlsd-harmful-content.md), GitHub, 2024. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/mlsd-har

mful-content.md (fetched)
4. alirezadir, "ML system design" (ml-system-design.md), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (fetched)
5. Educative, "Grokking the Machine Learning Interview", educative.io, 2024. https://www.educative.io/courses/grokking-the-machine-learning-interview (ch-ref)
6. Educative / Khang Pham, "Machine Learning System Design", educative.io, 2021. https://educative.io/courses/machine-learning-system-design/introduction (ch-ref)
7. Exponent, "Introduction to the ML System Design Interview", tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
8. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery (ch-ref)
9. IGotAnOffer, "Meta Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/facebook-machine-learning-engineer-interview (ch-ref)
10. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2021. http://patrickhalina.com/posts/ml-systems-design-interview-guide/ (ch-ref)
11. Engineer1999, "A Curated List of ML System Design Case Studies", GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies (fetched)
12. A. Halevy et al., "Preserving Integrity in Online Social Networks", arXiv, 2020. https://arxiv.org/pdf/2009.10311.pdf (repo-link)
13. Meta AI, "Community Standards Enforcement Report" (WPIE), ai.facebook.com, 2020. https://ai.facebook.com/blog/community-standards-report/ (repo-link)
14. Meta AI, "How Facebook uses super-efficient AI models to detect hate speech", ai.facebook.com, 2020. https://ai.facebook.com/blog/how-facebook-uses-super-efficient-ai-models-to-detect-hate-speech/ (repo-link)
15. A. Conneau et al., "Unsupervised Cross-lingual Representation Learning at Scale" (XLM-R), 2019. https://arxiv.org/abs/1911.02116 (known)
16. Meta AI, "Harmful content can evolve quickly. Our new AI system adapts to tackle it" (Few-Shot Learner), ai.facebook.com, 2021. https://ai.facebook.com/blog/harmful-content-can-evolve-quickly-our-new-ai-system-adapts-to-tackle-it/ (repo-link)
17. Meta, "Meta's new AI system to help tackle harmful content", about.fb.com, 2021. https://about.fb.com/news/2021/12/metas-new-ai-system-tackles-harmful-content/ (repo-link)
18. N. Noorshams, S. Verma, A. Hofleitner, "TIES: Temporal Interaction Embeddings for Enhancing Social Media Integrity at Facebook", 2020. https://arxiv.org/pdf/2002.07917.pdf (repo-link)
19. Meta Transparency Center, "Content borderline to the Community Standards", transparency.fb.com. https://transparency.fb.com/features/approach-to-ranking/content-distribution-guidelines/content-borderline-to-the-community-standards/ (repo-link)
20. Pinterest Engineering, "How Pinterest fights misinformation, hate speech, and self-harm content with machine learning", Medium, 2021. https://medium.com/pinterest-engineering/how-pinterest-fights-misinformation-hate-speech-and-self-harm-content-with-machine-learning-1806b73b40ef (repo-link)
21. Pinterest Engineering, "How Pinterest powers a healthy comment ecosystem with machine learning", Medium, 2021. https://medium.com/pinterest-engineering/how-pin

terest-powers-a-healthy-comment-ecosystem-with-machine-learning-9e5c3414c8ad (repo-link)
22. LinkedIn Engineering, "Viral spam content detection at LinkedIn", 2023. https://engineering.linkedin.com/blog/2023/viral-spam-content-detection-at-linkedin (repo-link)
23. LinkedIn Engineering, "Detecting and preventing abuse on LinkedIn using isolation forests", 2019. https://engineering.linkedin.com/blog/2019/isolation-forest (repo-link)
24. Bumble Tech, "Multilingual message content moderation at scale (part 1)", Medium, 2021. https://medium.com/bumble-tech/multilingual-message-content-moderation-at-scale-ddd0da1e23ed (repo-link)
25. Nextdoor Engineering, "Using predictive technology to foster constructive conversations", 2022. https://engblog.nextdoor.com/using-predictive-technology-to-foster-constructive-conversations-4af437942bd4 (repo-link)
26. Whatnot Engineering, "How Whatnot Utilizes Generative AI to Enhance Trust and Safety", Medium, 2023. https://medium.com/whatnot-engineering/how-whatnot-utilizes-generative-ai-to-enhance-trust-and-safety-c7968eb6315e (repo-link)
27. Slack Engineering, "Blocking Slack Invite Spam With Machine Learning", 2021. https://slack.engineering/blocking-slack-invite-spam-with-machine-learning/ (repo-link)
28. S. Wang et al., "Linformer: Self-Attention with Linear Complexity", 2020. https://arxiv.org/pdf/2006.04768.pdf (repo-link)
29. W. Wang, D. Tran, M. Feiszli, "What Makes Training Multi-modal Classification Networks Hard?" (gradient blending), 2019. https://arxiv.org/pdf/1905.12681.pdf (repo-link)
30. T.-Y. Lin et al., "Focal Loss for Dense Object Detection", 2017. https://arxiv.org/abs/1708.02002 (known)
31. A. Radford et al., "Learning Transferable Visual Models From Natural Language Supervision" (CLIP), 2021. https://arxiv.org/abs/2103.00020 (ch-ref)
32. T. Chen et al., "A Simple Framework for Contrastive Learning of Visual Representations" (SimCLR), 2020. https://arxiv.org/abs/2002.05709 (ch-ref)
33. T. Pan et al., "VideoMoCo: Contrastive Video Representation Learning with Temporally Adversarial Examples", 2021. https://arxiv.org/pdf/2103.05905.pdf (repo-link)
34. V. Sanh et al., "DistilBERT, a distilled version of BERT", 2019. https://arxiv.org/abs/1910.01108 (known)
35. D. Kiela et al., "The Hateful Memes Challenge: Detecting Hate Speech in Multimodal Memes", 2020. https://arxiv.org/abs/2005.04790 (known)
36. Meta / Facebook, "ThreatExchange" (PDQ, TMK+PDQF, vPDQ hashing; HMA platform), GitHub. https://github.com/facebook/ThreatExchange (fetched)
37. Meta Transparency Center, "Inauthentic Behavior" (Community Standards), transparency.fb.com. https://transparency.fb.com/policies/community-standards/inauthentic-behavior/ (repo-link)
38. Meta @Scale, "Building and scaling human review system" (talk), facebook.com. https://www.facebook.com/atscaleevents/videos/1201751883328695/ (repo-link)
39. Hugging Face, "distilbert-base-multilingual-cased" model card. https://huggingface.co/distilbert-base-multilingual-cased (repo-link)
40. Meta AI Research, "MMF: Hateful Memes project (configs and baselines)", GitHub. https://github.com/facebookresearch/mmf/tree/main/projects/hateful_memes (fetched)

13. Design Event Recommendation (Eventbrite / Meetup) with Location and Time Constraints

> How the prompt is usually worded: "Design an event recommendation system like Eventbrite. Users should see personalized events they are likely to register for" (ByteByteGo ch. 7 [1][2]). The AIMLInterviews question bank lists it as "Event recommendation system (Eventbrite)" [3][4]. Variants: Meetup group and event suggestions, Facebook Events "Discover", local concerts and ticketing (Ticketmaster-style), "things to do this weekend near me".
>
> Sourcing note: re-checked on 2026-10-14. Only GitHub hosts resolved; bytebytego.com, uber.com, kaggle.com, arxiv.org, huyenchip.com, hellointerview.com and developers.google.com did not. (fetched) = read through GitHub on that date. (ch-ref) = verified in an earlier chapter. (known) = canonical page not re-read here. No Eventbrite or Meetup engineering post could be verified, so no production system is claimed.

Company tags

Company	What is reported	Source
Eventbrite	AIMLInterviews names the question "Event recommendation system (Eventbrite)" and gives a worked solution	[3][4]
Eventbrite-style platforms	ByteByteGo / Aminian & Xu MLSDI ch. 7, "Event Recommendation System", is framed on Eventbrite	[1][2] [5]
General MLE loops (Meta, Amazon)	Portals list "design a recommender for X" as a standard MLSD round; events is one common instance	[12] [13]

Portals that cover it

Portal	Treatment	Link
ByteByteGo (Aminian & Xu, MLSDI ch. 7)	Full chapter: pointwise LTR, location/time/social features, LR -> GBDT -> NN, mAP, online learning	[1] [2]
alirezadir AIMLInterviews	Worked notes "mlsd-event-recom": 100M DAU, 1M new events/month, 200 ms, two-stage funnel	[3] [4]
junfanz1 Awesome-AI-Review	Community summary of the ByteByteGo chapter (features, models, metrics, serving)	[5]
Educative "Grokking the ML Interview"	Generic recommendation and search-ranking modules; no event-specific chapter verified	[9]
Hello Interview	Recommendation-systems pattern (retrieval, ranking, re-ranking)	[10]

Portal	Treatment	Link
Exponent / Aced	General MLSD course and framework; no event-specific write-up verified	[11]
Chip Huyen, Khang Pham	No event exercise. Closest: Airbnb location search (Huyen ex. 9); Airbnb Search Ranking and Estimate Delivery Time cases (Pham)	[6] [7]

Requirements & scale

Dimension	Value	Source
Business goal	Increase ticket sales / registrations	[4]
Functional	Personalized list of upcoming events for a user, near the user (or a chosen city), in a usable time window; free and paid events	[1][4]
Users	About 100M DAU, worldwide, many languages	[4]
Catalog	About 1M new events per month. Live inventory of a few million events at any time	[4] / assumption
Latency	About 200 ms end to end (proposed)	[4]
QPS	About 2-5k average, 20-50k peak (100M DAU x a few feed loads per day)	assumption
Candidates	Millions of events -> hundreds after location/time filtering -> top K (10-50)	[4]
Key constraints	Events are short-lived and expire, so every event is cold start. Strict geo and time windows. Capacity limits (sold out). Interaction data is sparse	[1][4]
Freshness	Registration counts and "friends attending" are streaming features. Model retrains daily or continually	[1][5]
Privacy	Location and friend graph are sensitive; obey consent and coarsen location	[1]

Diagram 1: End-to-end architecture (online serving path)

Figure 13.1: Online serving. Hard location and time filters cut millions of events to a few hundred candidates. A pointwise ranker scores each user-event pair. A policy layer then handles diversity, freshness, sold-out events and promoted events.




Diagram 2: Offline training & data pipeline

Figure 13.2: Offline and continual pipeline. Registrations are joined to logged impressions. The label window closes at event start. Training uses a time-based split, because events expire and random splits leak future information.




Diagram 3: Model architecture

Figure 13.3: Pointwise ranker. Inputs are grouped as ByteByteGo groups them: user, event, location, time, social and price. The output is P(register). A two-task head (click and register) is an optional upgrade.





Diagram 4: Variant: the geo-time candidate index

Figure 13.4: Location and time handled as hard constraints at retrieval. Events are bucketed by geohash cell and start-time bucket. The query expands to neighbouring cells until enough candidates are found. Online events skip the geo step.



Data & labels

Item	Choice	Notes / source
Training row	(user, event, request time, features, label)	One row per shown pair [4]
Positive	Registered or bought a ticket after the impression, before the event starts	[1][4]
Negative	Shown, not registered (impressed negatives); optionally random in-radius events	[1] / assumption
Weak labels	Click, bookmark/like, share: auxiliary heads or weighted positives	[1][4]
Imbalance	Registrations are rare -> downsample negatives, focal or class-balanced loss	[1][4][5]
Leakage	Point-in-time features only; "registration count" must be the value at impression time	[2] ref 26
Split	Time-based (train on past weeks, validate on next week)	assumption
Public data	Kaggle "Event Recommendation Engine Challenge" (users, events, attendees, friends)	[21]

Features

Group	Examples	Computation
Location	Distance user-event, same city/state/country, walk score, transit score, gap from user's typical distance	Online at request (distance) + batch (scores) [1][5]
Time	Time remaining until start, gap from the user's typical lead time, travel time, day of week, hour	Online [1][5]
Social	Number/ratio of friends attending, friend invitations, host is a friend, similarity to friend-hosted events	Streaming [1][4]
User	Age (bucketized), gender, language, past registrations with time decay, user embedding	Batch [4][5]
Event	Category, price, duration, description text embedding, host popularity, registration count	Batch + streaming [4]
Price	Price, gap from the user's average paid price, free flag	Batch [1][5]
User-event similarity	Similarity of price, description and registration count to the user's past registered events; time-gap similarity	Batch + online [4]
Geo encoding	Lat/lng bucketing, geohash or cluster ids, distance to user's frequent places	Batch [2] ref 9
Feature crosses	Distance x time-to-start, price x user avg price (for LR / wide part)	Batch [2] ref 22
Context	Device, current location vs home location, weather (optional)	Online / assumption

Model choices (baseline -> advanced)

Stage	Model	Pros	Cons
0	Rule-based: nearest + soonest + most popular	No training, works on day one	Not personalized

Stage	Model	Pros	Cons
1	Logistic regression	Fast, interpretable	Misses non-linear interactions (distance x time) [1][5]
2	GBDT (XGBoost / LightGBM)	Strong on tabular features, little preprocessing [22]	Hard to train continually on streaming data [1][4]
3	DNN pointwise ranker	Non-linear, uses embeddings and text, fine-tunes incrementally	Needs more data and tuning [1][5]
4	Two-tower retrieval + multi-task DNN ranker	Personalized candidates beyond the geo filter; click + register heads	More infrastructure; sampling bias in retrieval [17][18]
Alt	Pairwise / listwise LTR (RankNet, LambdaMART)	Optimizes ordering directly	Harder to calibrate; ByteByteGo picks pointwise [1][8]

Loss functions

Loss	When
Binary cross-entropy	Default pointwise P(register) [1][5]
Focal loss	Heavy imbalance; down-weights easy negatives [19]
Class-balanced loss	Re-weights by effective number of samples per class [20]
Pairwise (RankNet) / LambdaRank	Pairwise LTR alternative [2] refs 2-4 [8]
Multi-task sum: a*BCE(click)* + *b*BCE(register)	Two-head ranker in Figure 13.3

Offline metrics

Metric	Use	Caveat
mAP	Primary choice: binary relevance (registered or not) [1][4]	Needs the full ranked list
nDCG@K	Graded relevance (register > bookmark > click)	Gain values must be chosen
Recall@K / Precision@K	Candidate generation quality	Ignore order [4]
MRR	Only first relevant item	Weak when many events fit [4]
Calibration / log loss	Needed if scores feed thresholds or ads	
Slices	City, new events (< 24 h), new users, online vs in-person	

Online metrics / A-B

Metric	Type
Registration / ticket conversion rate per session	Primary [1][4]
CTR	Engagement [1][4]
Bookmark / like rate	Engagement [1][4]
Revenue lift (paid tickets)	Business [1][4]
Attendance (check-in) rate, refunds, no-shows	Quality guardrail (assumption)

Metric	Type
Host-side: share of events with at least 1 registration	Marketplace fairness (assumption; see [16])
Latency p99, empty-result rate	System guardrail

Serving & latency budget (assumption, p99, ~200 ms total [4])

Step	Budget
Gateway + auth + context (geo lookup)	15 ms
Candidate generation (geo-time KV + ANN + social)	30 ms
Filtering (sold out, past, blocked)	10 ms
Feature fetch (feature store, batched)	40 ms
Ranking (~500 candidates, batched GBDT/DNN)	50 ms
Re-rank / policy + response	20 ms
Headroom	35 ms

Monitoring

What	Signal
Data	Feature null rate, geo lookup failures, stream lag for registration counts
Model	Score distribution drift, calibration by city, mAP on daily holdout
Product	CTR, conversion, empty results in low-density areas
Freshness	Share of shown events that are sold out or already started (should be ~0)
Fairness	Exposure share for small hosts and new events

Failure modes

Failure	Mitigation
Cold start for every new event	Content features (text embedding, category, host history), exploration slots [4]
New user with no history	Popularity in their city + onboarding interests
Sparse areas (rural)	Expand radius / time horizon, add online events
Showing sold-out or past events	Streaming capacity feature + hard filter at serve time
Label leakage from registration counts	Point-in-time feature joins [1]
Popularity feedback loop	Exploration, freshness boost, host exposure caps [14]
Wrong user location (VPN, travel)	Use device GPS when allowed; let user pick city
Privacy of location / friends	Coarsen location, honour consent [2] ref 24

Interviewer follow-ups

- Why is this a ranking problem and not plain classification? Pointwise vs pairwise vs listwise? [1][5]
- Events expire within days or weeks. How do you handle constant cold start? [4]
- Is location a hard filter or a feature? What happens in low-density areas?
- How do you compute distance and travel time efficiently for hundreds of candidates? [4]
- Which features are batch and which are streaming? How fresh must "registration count" be? [1][5]
- How do you handle extreme class imbalance? Focal loss vs downsampling, and how do you recalibrate? [1][4]
- GBDT or neural network, given continual learning needs? [1][4]
- Why mAP rather than nDCG or MRR here? [1][4]
- How do you avoid data leakage when building training data? [1]
- How would you use the friendship graph and invitations? Any privacy risks? [1][4]
- How do you add diversity (dates, categories) and freshness in re-ranking? [1][14]
- This is a two-sided marketplace. How do you keep exposure fair to new or small hosts? [1][16]
- How often do you retrain, and how would online learning work? [1][15]
- How do you rank online/virtual events that have no location?
- Paid promoted events: how do you blend them with organic ranking?
- RSVP vs paid registration: are they the same label? What about age groups and many languages? [4]
- Which features are batch vs real time, and what does each cost to serve? [2] ref 8
- How do you train without exposing users' locations or friend lists (privacy-preserving ML)? [2] ref 24

Portal comparison

Portal	Framing	Candidate step	Model	Metrics	Distinctive point
ByteByteGo ch. 7 [1][2][5]	Pointwise LTR, P(register)	Event filtering (location, type)	LR -> trees -> GBDT -> NN; picks NN for continual learning	mAP offline; CTR, conversion, bookmark, revenue	Deep location/time/social feature design; batch vs streaming
alirezadir AIMLInterviews [3][4]	Same, with explicit scale (100M DAU, 1M events/month, 200 ms)	Rule-based filters, millions -> hundreds	GBDT baseline, then NN	mAP; CTR, conversion, revenue	Lists open questions (RSVP vs register, age group, multilingual)
junfanz1 notes [5]	Summary of ByteByteGo	Same	Model comparison table	P/R@K, MRR, nDCG, mAP	Adds walk/transit-score features, decay weighting
Hello Interview / Educative [9][10]	Generic recsys funnel	Retrieval (embeddings) + ranking	Two-tower + DNN ranker	Recall@K, nDCG	No event-specific constraints; apply geo/time as filters

Portal	Framing	Candidate step	Model	Metrics	Distinctive point
Chip Huyen / Khang Pham [6][7]	No event case	n/a	n/a	n/a	Nearest analogues: Airbnb location search / search ranking

References

1. A. Aminian & A. Xu, "Event Recommendation System" (Machine Learning System Design Interview, ch. 7), ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/event-recommendation-system (URL follows ByteByteGo's chapter pattern; host unreachable on 2026-10-14)
2. ByteByteGo, "Reference Materials for ML System Design Interview" (Chapter 7: Event Recommendation System, 27 references; "[2] ref n" in the tables means that list's item n), GitHub, 2023. https://github.com/ByteByteGoHq/ml-bytebytego (fetched)
3. alirezadir, "ML System Design" (sample questions: "Event recommendation system (Eventbrite)"), AIMLInterviews, GitHub, 2025. https://github.com/alirezadir/AIMLInterviews/blob/main/src/MLSD/ml-system-design.md (fetched)
4. alirezadir, "Event recommendation system" (mlsd-event-recom), AIMLInterviews, GitHub, 2025. https://github.com/alirezadir/AIMLInterviews/blob/main/src/MLSD/mlsd-event-recom.md (fetched)
5. junfanz1, "ML System Design Interview" notes (Eventbrite event recommendation section), Awesome-AI-Review, GitHub, n.d. https://github.com/junfanz1/Awesome-AI-Review/blob/main/System%20Design/ML%20System%20Design%20Interview.md (fetched)
6. C. Huyen, "Machine Learning Systems Design: Exercises" (no event exercise; ex. 9 Airbnb location search), GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md (fetched)
7. K. Pham, "machine-learning-interview" (no event case; Airbnb Search Ranking and Estimate Delivery Time cases), GitHub, 2021. https://github.com/khangich/machine-learning-interview (fetched)
8. C. J. C. Burges, "From RankNet to LambdaRank to LambdaMART: An Overview", Microsoft Research TR, 2010. https://www.microsoft.com/en-us/research/wp-content/uploads/2016/02/MSR-TR-2010-82.pdf (URL from [2])
9. Educative, "Grokking the Machine Learning Interview", educative.io, n.d. https://www.educative.io/courses/grokking-the-machine-learning-interview (ch-ref)
10. Hello Interview, "Recommendation Systems (ML System Design pattern)", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/patterns/recommendation-systems (ch-ref)
11. Exponent, "Introduction to the ML System Design Interview" (course), tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
12. IGotAnOffer, "Meta Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/facebook-machine-learning-engineer-interview (ch-ref)
13. IGotAnOffer, "Amazon Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/amazon-machine-learning-engineer-interview (ch-ref)

14. Google for Developers, "Re-ranking" (freshness, diversity, fairness), Recommendation Systems course, n.d. https://developers.google.com/machine-learning/recommendation/dnn/re-ranking (URL from [2], ref 23)
15. C. Huyen, "Real-time machine learning: challenges and solutions", huyenchip.com, 2022. https://huyenchip.com/2022/01/02/real-time-machine-learning-challenges-and-solutions.html (URL from [2], ref 27)
16. Uber Engineering, "Food Discovery with Uber Eats: Recommending for the Marketplace", uber.com, 2018. https://www.uber.com/blog/uber-eats-recommending-marketplace/ (URL from [2], ref 25; host unreachable on 2026-10-14)
17. P. Covington, J. Adams, E. Sargin, "Deep Neural Networks for YouTube Recommendations", RecSys / Google Research, 2016. https://research.google/pubs/pub45530/ (ch-ref)
18. X. Yi et al., "Sampling-Bias-Corrected Neural Modeling for Large Corpus Item Recommendations", RecSys / Google Research, 2019. https://research.google/pubs/sampling-bias-corrected-neural-modeling-for-large-corpus-item-recommendations/ (ch-ref)
19. T.-Y. Lin et al., "Focal Loss for Dense Object Detection", arXiv, 2017. https://arxiv.org/abs/1708.02002 (known)
20. Y. Cui et al., "Class-Balanced Loss Based on Effective Number of Samples", arXiv, 2019. https://arxiv.org/abs/1901.05555 (known)
21. Kaggle, "Event Recommendation Engine Challenge", kaggle.com, 2013. https://www.kaggle.com/c/event-recommendation-engine-challenge (known; host unreachable on 2026-10-14)
22. XGBoost developers, "XGBoost Documentation", readthedocs, n.d. https://xgboost.readthedocs.io/en/stable/ (URL from [2])

14. Design Payment Fraud Detection (Stripe Radar / PayPal) with Real-Time Scoring

> Sourcing note (review, 2026-10-14): GitHub-hosted references [16][17][19][20][21] were re-fetched and their claims confirmed. Company blog domains (stripe.com, medium.com, eng.lyft.com, uber.com, portals) did not resolve from the review sandbox; refs [1]-[15], [25]-[27] were confirmed to exist with these exact titles/URLs via the curated index [20], and their content is summarized from the posts themselves, not re-read in this pass. Educative/Exponent/Hello Interview/Halina [18][22]-[24] were not re-fetched. Rows marked "typical assumption" are interview-standard estimates, not quoted numbers.

Company tags

Company	Evidence (built it = public engineering post; not proof of interview question)	Ref
Stripe	Built it: Radar, ML scorer on every card payment; similarity clustering for rings	[1][2][3]
PayPal	Built it: fraud-model CI/CD + shadow platform, real-time graph DB, multi-domain model	[4][5][6]
Uber, Lyft, Grab, Netflix, Wayfair, BlaBlaCar	Built it: production fraud/risk ML posts indexed in [20]	[8]-[15] [25][26]
Capital One	Adjacent only: ML for anti-money-laundering, not card-fraud scoring	[7]
Generic "Fraud detection system"	Listed under "Harmful content / Spam detection" in sample MLSD questions	[16]
Chip Huyen exercise	"each record is labelled as fraudulent or safe, how would you build a fraud detection algorithm?"	[17]

Removed in review: "Amazon" and "Airbnb" (no fetched source supports either tag).

Portals that cover the problem:

Portal	Coverage	Ref
alirezadir/Machine-Learning-Interviews	"Fraud detection system" under Other > Harmful content / Spam (verified)	[16]
chiphuyen/machine-learning-systems-design	Exercise 2: labelled fraudulent vs safe records (verified)	[17]
khangich/machine-learning-interview	"Fraud detection (TBD)" heading, no content (verified)	[19]
Engineer1999 curated case studies	~20 fraud/risk/payments posts indexed (verified)	[20]
ByteByteGo ML SDI (Aminian & Xu)	No fraud chapter; closest is ch. 5 Harmful Content Detection (verified)	[21]

Portal	Coverage	Ref
Educative "Grokking the ML SD Interview"	Reported to use fraud detection in its 6-step framework (not re-fetched)	[18]
Exponent, Hello Interview, Patrick Halina	Generic MLSD frameworks only; no fraud-specific page claimed	[22][23] [24]

Requirements & scale

Dimension	Value	Source
Functional	Score each payment/authorization; return allow / review / 3DS step-up / block	[1][2]
Functional	Merchant-defined rules on top of score; explanations for decisions	[1][2]
Functional	Analyst review queue; feedback (disputes, manual labels) into training	[4][9]
Latency	Score in the authorization path, well under ~100 ms end to end	[1]
Throughput	5k-50k payments/s peak (Black Friday 3-5x average)	typical assumption
Feature count	1,000+ signals per payment at Stripe Radar	[1]
Entities	100M-1B cards, devices, emails, IPs; millions of merchants	typical assumption
Fraud base rate	0.05%-0.5% of transactions (extreme imbalance)	typical assumption
Label delay	Chargebacks arrive days to ~90+ days after the charge	[1][3]
Availability	99.99%; fail-open or fail-to-rules if model is down	typical assumption
Cost asymmetry	Missed fraud = amount + fee; false decline = lost revenue + churn	[3][6]

DIAGRAM 1: Online real-time scoring path

Figure 14.1 - Authorization-time fraud scoring, steps 1-10 (request -> features -> model -> policy -> action)



DIAGRAM 2: Offline training and data pipeline

Figure 14.2 - Delayed-label pipeline with feedback loop




DIAGRAM 3: Model architecture

Figure 14.3 - Hybrid tabular + sequence + graph fraud classifier





DIAGRAM 4: Real system - Stripe Radar model evolution (as described in [1])

Figure 14.4 - From hand-built ensemble to a single deep network



Data & labels

Source	Label / use	Caveat
Fraudulent chargebacks	Positive label (strongest)	Delay of weeks; friendly fraud noise
Early fraud warnings / issuer reports	Faster positive signal	Coverage varies by network
Manual review outcomes	Positive/negative	Biased to borderline scores
Refunds flagged as fraud by merchant	Weak positive	Merchant-dependent
Matured non-disputed charges	Negative after window	Blocked charges never get labels

Source	Label / use	Caveat
Exploration holdout (tiny % allowed)	Unbiased estimate of true fraud rate	Costs real money
Weak supervision (heuristic labeling functions)	Extra noisy labels for unlabeled/new patterns [27]	Label noise; needs denoising

Features

Group	Examples
Transaction	amount, currency, MCC, card-present flag, time of day, amount vs merchant avg
Velocity (stream)	txns per card/IP/device/email in 1m, 1h, 24h; distinct cards per device
Identity / device	device fingerprint, browser, IP geo vs billing country, proxy/VPN flag
Card / issuer	BIN country, card age on network, prior declines, prior disputes
Network / graph	shared device/IP with known fraud, connected-component size, fraud-ring cluster [3][12]
Behavioral	checkout dwell time, typing speed, copy-paste of card number
Merchant	merchant dispute rate, vertical, account age

Model choices

Stage	Model	Pros	Cons
Baseline	Rules + logistic regression	Explainable, fast	Low recall, brittle
Standard	GBDT (XGBoost/LightGBM)	Strong on tabular, fast CPU inference	Weak on raw sequences/ids
Hybrid	Wide & Deep (GBDT + DNN)	Combines memorization + generalization	Two systems to maintain [1]
Advanced	Single deep net (residual MLP + embeddings)	Scales with features, one pipeline [1][11]	Needs more data, explainability tooling
Sequence	RNN/Transformer over event history; customer-journey embeddings [25]	Captures behavior change, ATO	Latency, state storage
Graph	GNN / graph features, similarity clustering	Catches rings, mule networks [3][6][12]	Real-time graph cost
Unsupervised	Isolation forest, autoencoder, graph anomaly	Novel attacks, no labels [10][13]	High FP, hard to tune

Loss

Option	When
Weighted binary cross-entropy	Default; weight positives or by dollar amount
Focal loss	Extreme imbalance, many easy negatives
Cost-sensitive / amount-weighted loss	Optimize dollars, not counts
Multi-task BCE (fraud, dispute, ATO)	Shared tower, sparse fraud labels
Calibration (Platt/isotonic) after training	Thresholds must map to stable probabilities

Offline metrics

Metric	Why
PR-AUC (not ROC-AUC)	Base rate under 1%
Recall at fixed FPR / block rate	Matches business constraint (e.g. block 0.5%)
Dollar-weighted recall / $ fraud caught	Large tickets matter more
Calibration (ECE, reliability)	Thresholds and merchant rules depend on it
Per-slice metrics	Country, MCC, new vs existing card, merchant size
Time-based backtest	Train on t, test on t+k; detects decay

Online metrics & A-B

Metric	Direction
Fraud chargeback rate (bps of volume)	Down
False-positive / good-user decline rate	Down [6]
Authorization / conversion rate	Up
Manual review volume & precision	Down / up
Net $ = fraud saved - lost good revenue - review cost	Up
A-B design	Randomize by merchant or card; long horizon because labels lag; use early-warning proxies

Serving & latency budget

Step	Budget (typical assumption)
Enrichment (BIN, geo-IP, device)	5-10 ms
Online feature store reads (KV, parallel)	5-15 ms
Graph lookups (1-2 hop, cached)	5-15 ms
Model inference (GBDT CPU or small DNN)	5-20 ms
Policy / rules engine	1-5 ms
Total p99	under ~100 ms [1]
Fallback	Timeout -> rules-only or last cached score; fail-open for low amounts

Monitoring

Signal	Action
Score distribution / block-rate drift	Alert; recalibrate thresholds
Feature null-rate, freshness lag of stream aggregates	Page on-call; fall back to rules
Early-warning fraud rate by segment	Detect new attack campaigns
Analyst-confirmed precision on review queue	Track quality daily
Shadow vs prod disagreement	Gate model promotion [4]
Per-merchant spikes	Auto-tighten rules for that merchant

Signal	Action
Attack-campaign detector (time-series anomaly on fraud signals)	Propose rules; analyst approves before deploy (human in loop) [8]
Entity-level anomaly watch (riders/drivers/cards)	Flag risky entities missed by txn model [9]

Failure modes

Failure	Mitigation
Label delay -> stale model	Proxy labels (early warnings, reviews); frequent retrains
Selection bias (blocked txns unlabeled)	Exploration holdout, counterfactual/IPS weighting
Adversarial adaptation	Fast retrain, rules for hotfixes, graph/ring features
Train/serve skew in velocity features	Same feature definitions offline and online, point-in-time joins
Feedback loop from own decisions	Log propensity; keep randomized holdout
Friendly fraud mislabeled as fraud	Separate dispute reason codes; multi-task heads
Cold start (new merchant/card)	Network-level priors, population features
Explainability / regulation	Reason codes, SHAP, merchant-facing insights [1][15]

Interviewer follow-ups

- Labels arrive 30-90 days late: how do you train and evaluate on recent data?
- You never see the outcome of blocked transactions: how do you estimate true recall?
- How do you choose the threshold, and does it differ per merchant or per amount?
- ROC-AUC is 0.99 but the business is unhappy: why, and what metric do you use instead?
- How do you compute "transactions per card in the last hour" consistently online and offline?
- How do you detect a fraud ring of many new cards using one device or IP?
- Fraudsters change tactics within days: how fast can you retrain and ship safely?
- How do you combine merchant rules with the ML score without double counting?
- What happens if the feature store or model server times out in the auth path?
- How do you run an A-B test when the outcome takes two months?
- How do you explain a decline to a merchant or regulator?
- How do you handle a new merchant with no history (cold start)?
- When do you add a 3DS step-up instead of a hard block?
- Would you use a GNN online, or precompute graph features? Why?
- How do you separate friendly fraud from true fraud in labels?
- A card-testing attack sends thousands of tiny charges from one merchant: which features and rules catch it?
- How do analysts and auto-generated rules coexist with the model, and who can ship a rule in minutes? [8]
- How would you reuse one model across products/domains without hurting good-user approval? [6]

Portal comparison

Portal	Framing	Model	Distinctive emphasis
Educative Grokking MLSD [18]	Reported fraud example in 6-step framework (not re-fetched)	Classical ML -> deep models	Data strategy, imbalance, offline vs online eval
Chip Huyen exercises [17]	Short open prompt on labelled fraud/safe records	Open	Imbalance, label quality, metric choice
alirezadir MLI [16]	Grouped with spam / harmful content detection	Classifier template	Reuse of detection template
Khang Pham repo [19]	Placeholder; framework from ads/feed chapters applies	GBDT / DNN	Feature engineering at scale
Stripe Radar blog [1]	Production system description	LR -> Wide&Deep -> pure DNN	Network data, 1000+ signals, sub-100 ms, explanations
PayPal tech blog [4][5][6]	Production deployment	Ensemble + graph	Shadow platform, real-time graph, reduce good-user declines
Uber Project RADAR [8]	Production attack detection	Time-series anomaly + rules	Early detection, human-in-the-loop rule generation

References

1. Stripe, "How we built it: Stripe Radar", stripe.com blog, 2023. https://stripe.com/blog/how-we-built-it-stripe-radar
2. Stripe, "A primer on machine learning for fraud detection", stripe.com guides. https://stripe.com/en-mx/guides/primer-on-machine-learning-for-fraud-protection
3. Stripe, "Similarity clustering to catch fraud rings", stripe.com blog. https://stripe.com/blog/similarity-clustering
4. PayPal Tech, "Deploying Large-scale Fraud Detection Machine Learning Models at PayPal", Medium. https://medium.com/paypal-tech/machine-learning-model-ci-cd-and-shadow-platform-8c4f44998c78
5. PayPal Tech, "How PayPal Uses Real-time Graph Database and Graph Analysis to Fight Fraud", Medium. https://medium.com/paypal-tech/how-paypal-uses-real-time-graph-database-and-graph-analysis-to-fight-fraud-96a2b918619a
6. PayPal Tech, "Multi-Domain Fraud Detection While Reducing Good User Declines, Part I", Medium. https://medium.com/paypal-tech/multi-domain-fraud-detection-while-reducing-good-user-declines-part-i-e8bba5b07da8
7. Capital One Tech, "How Machine Learning Can Help Fight Money Laundering", capitalone.com. https://www.capitalone.com/tech/machine-learning/how-machine-learning-can-help-fight-money-laundering/
8. Uber Engineering, "Project RADAR: Intelligent Early Fraud Detection System with Humans in the Loop", uber.com. https://www.uber.com/en-GB/blog/project-radar-intelligent-early-fraud-detection/
9. Uber Engineering, "Risk Entity Watch: Using Anomaly Detection to Fight Fraud", uber.com. https://www.uber.com/en-IN/blog/risk-entity-watch/
10. Grab Engineering, "Unsupervised graph anomaly detection: Catching new fraudulent behaviours", engineering.grab.com. https://engineering.grab.com/graph-anomaly-model
11. Lyft Engineering, "From shallow to deep learning in fraud", eng.lyft.com. https://eng.lyft.com/from-shallow-to-deep-learning-in-fraud-9dafcbcef743

12. Grab Engineering, "Graph for fraud detection", engineering.grab.com. https://engineering.grab.com/graph-for-fraud-detection
13. Lyft Engineering, "Fingerprinting fraudulent behavior", eng.lyft.com. https://eng.lyft.com/fingerprinting-fraudulent-behavior-6663d0264fad
14. Netflix Tech Blog, "Machine Learning for Fraud Detection in Streaming Services", Medium. https://netflixtechblog.medium.com/machine-learning-for-fraud-detection-in-streaming-services-b0b4ef3be3f6
15. Wayfair Tech, "Explainable Fraud Detection", aboutwayfair.com. https://www.aboutwayfair.com/tech-innovation/explainable-fraud-detection
16. alirezadir, "ML System Design" (ml-system-design.md), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md
17. C. Huyen, "Machine Learning Systems Design - Exercises", GitHub. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md
18. Educative, "The 6-step ML SD framework" (Grokking the ML System Design Interview), educative.io, 2025. https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/the-6-step-ml-sd-framework
19. K. Pham, "machine-learning-interview", GitHub. https://github.com/khangich/machine-learning-interview
20. Engineer1999, "A Curated List of ML System Design Case Studies", GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies
21. ByteByteGo, "ml-bytebytego: references for Machine Learning System Design Interview", GitHub, 2023. https://github.com/ByteByteGoHq/ml-bytebytego
22. Exponent, "Introduction to the ML System Design Interview", tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro
23. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery
24. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2021. http://patrickhalina.com/posts/ml-systems-design-interview-guide/
25. Wayfair Tech, "Introducing Melange: A Customer Journey Embedding System for Improving Fraud and Policy Abuse Detection", aboutwayfair.com. https://www.aboutwayfair.com/careers/tech-blog/introducing-melange-a-customer-journey-embedding-system-for-improving-fraud-and-scam-detection
26. BlaBlaCar Engineering, "How we built our machine learning pipeline to fight fraud at BlaBlaCar - Part 2", Medium. https://medium.com/blablacar/how-we-built-our-machine-learning-pipeline-to-fight-fraud-at-blablacar-part-2-476335f459b4
27. Swiggy Bytes, "DeFraudNet: An End-to-End Weak Supervision Framework to Detect Fraud in Online Food Delivery", bytes.swiggy.com. https://bytes.swiggy.com/defraudnet-an-end-to-end-weak-supervision-framework-to-detect-fraud-in-online-food-delivery-22366ddce461

15. Design ETA / Delivery Time Prediction (Uber, DoorDash, Amazon Delivery)

> Sourcing note: in this review run, company blogs, arXiv and ACM could not be fetched (proxy denial) and the web-search budget was spent. The GitHub portal repositories [7][8][9][12] were cloned and checked line by line. Company and paper references ([1]-[6], [10], [11], [13]) use their canonical URLs; four of them ([1], [10], [11], [13]) are also linked from those portal repositories. Rows marked "typical assumption" are standard interview estimates, not quoted numbers.

Company tags

Company	Evidence	Ref
Uber / Uber Eats	DeepETA: a transformer that predicts a residual on top of the routing-engine ETA	[1][2]
Uber Eats	Trip inferences and ML (food prep time) used to optimize delivery times	[11]
DoorDash	Multi-task deep ETA models with probabilistic outputs; long-tail ETA work	[3][13]
Google Maps	GNN over road "supersegments" for travel-time ETA	[4][5]
DiDi	Wide-Deep-Recurrent (WDR) travel-time model	[6]
Generic question	"Food delivery time approximation" is a sample MLSD question	[7][12]
Generic question	"Estimate Delivery time" is a module of Khang Pham's ML design course	[8]

Amazon, Instacart, Lyft and Grab use the same pattern in interviews, but this run found no source that ties them to the question, so they are not tagged.

Portals that cover the problem:

Portal	Coverage	Ref
khangich/machine-learning-interview	"Estimate Delivery time" course module (paid, rebrand.ly/mldesign); README lists Uber Eats and DoorDash dispatch reading	[8]
alirezadir (AIMLInterviews / Machine-Learning-Interviews)	"Food delivery time approximation" listed under "Other" sample questions; links Uber DeepETA	[7] [12]
chiphuyen/machine-learning-systems-design	Generic framework only (setup, data, modeling, serving); no ETA case	[9]

Requirements & scale

Dimension	Value	Source
Functional	Predict ETA before the order or request (quote) and refresh it during the trip	[1][3]
Functional	Serve several ETA stages (browse page, checkout, post-checkout tracking)	[3]
Functional	Decompose: prep time + courier to store + wait + store to customer	[10][11]

Dimension	Value	Source
Functional	Output a point estimate plus an interval ("25-35 min")	[3]
Consumers	Users (quote), dispatch/matching, pricing, supply positioning	[1][10]
Latency	Low single-digit ms per model call; ETA is called many times per request	[1]
Throughput	Uber: DeepETA is described as one of the highest-QPS models at the company	[1]
Throughput	50k-500k ETA calls/s at peak (dispatch scores many driver-order pairs)	typical assumption
Scale	Millions of orders a day, millions of road segments, 100k+ stores	typical assumption
Accuracy	Minimize MAE; bound the late rate (under-prediction costs more)	[1][3]
Freshness	Traffic and store-load features updated within seconds to minutes	[3][4]

DIAGRAM 1: Online ETA serving path

Figure 15.1 - Request -> routing base ETA -> feature fetch -> model -> post-process -> quote



DIAGRAM 2: Offline training & data pipeline

Figure 15.2 - Logs -> actual-time labels -> features -> training -> eval -> registry -> rollout





DIAGRAM 3: Model architecture

Figure 15.3 - Residual transformer over a routing-engine base ETA (DeepETA-style [1][2])



DIAGRAM 4: Variant - delivery ETA with leg heads and a distribution output

Figure 15.4 - Shared encoder, per-leg heads (interview pattern) and a probabilistic total-ETA head [3]



Data & labels

Item	Detail	Ref
Label (rides)	Actual pickup or trip duration from trip events	[1]
Label (delivery)	created -> dropoff; per-leg: prep, courier to store, wait, drive	[10][11]
Prep-time label	Not observed directly; inferred from courier arrival and pickup events	[11]
Residual label	actual - routing-engine ETA (narrower, easier target)	[1][2]
Label delay	Known only after completion (30-60 min); join by order id	typical assumption
Noise	Cancelled orders, GPS drift, courier batching, manual "picked up" taps	typical assumption
Splits	Time-based; hold out whole days; check per city and holidays	typical assumption
Volume	Hundreds of millions of historical trips for training	[1]

Features

Group	Examples	Freshness
Route	Distance, base routing ETA, turn count, highway share	per request
Traffic	Live segment speeds, historical speeds by hour of week	seconds-minutes [4]
Geo	Origin/destination geohash at several resolutions, hashed embeddings	static [1]
Time	Hour, weekday, holiday, minute of day (cyclical)	per request
Store	Historical prep time, open orders, cuisine, order size	minutes [3][11]
Supply	Idle couriers nearby, courier distance, acceptance rates	seconds [10]
Real-time load	Orders in the last N minutes at the store and in the area (long-tail signal)	minutes [13]
Context	Weather, events, product type (Eats vs rides, scheduled vs ASAP)	minutes

Model choices

Stage	Model	Pros	Cons
Baseline 0	Routing engine ETA (graph shortest path)	No training, explainable	Misses prep time and traffic quirks
Baseline 1	Historical average by (store, hour) + routing	Trivial	No interactions, cold start
Classic	GBDT (XGBoost/LightGBM) on tabular features	Strong, fast, interpretable	Hits a ceiling at Uber's data scale; Uber moved from XGBoost to DeepETA [1]
Deep residual	Transformer/MLP predicting the residual over base ETA	Scales with data, embeddings for geo	Needs careful latency work [1]
Graph	GNN over road supersegments	Captures how traffic spreads in space	Heavy infra; mainly for the travel leg [4][5]
Sequence	Wide-Deep-Recurrent over route links	Uses the link sequence	Long sequences, slower [6]
Multi-task / probabilistic	Shared encoder, stage or leg heads, distribution output	One model for many ETA stages; intervals for quotes	Harder to train and calibrate [3]

Loss

Loss	Why
MAE / L1	Robust to outliers, matches the MAE KPI
Huber	Smooth near 0, robust tails
Asymmetric Huber	Penalize lateness more than earliness; tunable [1]
Quantile (pinball) for p50/p80/p90	Gives intervals and SLA-aligned quotes
Distribution NLL (predict distribution parameters)	Full probabilistic forecast for quotes [3]
Multi-task sum + leg consistency	Total and sum of legs agree

Offline metrics

Metric	Notes
MAE, RMSE, MAPE	Overall and sliced by city, hour, distance, product
p50 / p90 absolute error	The tail matters for user trust
Late rate	Share of orders where actual > quoted (or > upper bound)
Interval coverage & width	Calibration of p10-p90 bands
Long-tail error	Error on the slowest few percent of orders (rush, storms) [13]
Bias by segment	Systematic early or late in new cities, rain, peak

Online metrics & A-B

Metric	Direction
On-time rate vs quote	Up
Conversion (checkout after quote)	Up; pessimistic ETAs lower it
Cancellations, "where is my order" support contacts	Down
Courier wait time at store (dispatch quality)	Down [10]
Guardrails: p99 latency, error rate, revenue	No regression
Design	Switchback or geo-cluster experiments (dispatch network effects)

Serving & latency budget

Step	Budget (typical assumption)
Routing engine base ETA	5-20 ms
Online feature fetch (Redis/Cassandra)	2-5 ms
Model inference (CPU, linear attention)	1-5 ms [1]
Post-processing, calibration, rules	<1 ms
Total per quote	under ~50 ms; dispatch scores thousands of pairs in batches

Step	Budget (typical assumption)
Tactics	Residual on base ETA, embedding caches, quantized or distilled models, fall back to routing ETA on timeout

Monitoring

Signal	Action
Rolling MAE and late rate by city-hour (once labels arrive)	Alert, roll back
Feature drift (traffic feed outage, stale store load)	Fall back to historical features
Prediction shift (mean ETA jump)	Check map or routing releases
Interval coverage	Recalibrate quantiles
Latency, timeouts, fallback rate	Scale out or simplify the model

Failure modes

Failure	Mitigation
Feedback loop: the quote shapes courier behavior and dispatch	Log exploration, causal eval, per-leg labels
Label leakage (future features in training)	Point-in-time feature snapshots
Cold-start stores or new cities	Hierarchical fallbacks (cuisine, region), shared embeddings
Extreme events (storms, concerts, rush peaks)	Real-time load features, surge flags, wider intervals [13]
Routing-engine changes shift the base ETA	Retrain the residual model, monitor bias
Quotes that are consistently optimistic	Asymmetric loss, quantile quoting, buffers
Batched multi-order trips	Explicit batch features or a separate model

Interviewer follow-ups

- Why predict a residual over the routing engine instead of the raw ETA? [1]
- How do you split a delivery ETA into legs, and do you train one model or many?
- How do you handle the higher cost of being late than early?
- How would you output an interval instead of one number, and calibrate it? [3]
- How do you encode lat/lng and very high-cardinality geo IDs? (geohash, feature hashing) [1]
- How do you get real-time traffic and store-load features into the model fast?
- How do you avoid leakage when building training data from logs?
- How do you update the ETA mid-trip as new GPS pings arrive?
- XGBoost vs a deep model: when does the deep model win, and at what latency? [1]
- How do you A/B test ETA changes given dispatch network effects? (switchback)
- How do you handle a new city or a new restaurant with no history?
- How do you keep accuracy on long-tail events such as storms or rush peaks? [13]
- How do you label food prep time when nobody records it? [11]
- What happens if the traffic feed or feature store goes down? (fallbacks)

- How does ETA feed dispatch, pricing and batching decisions? [10][11]
- Which metric would you report to the business, and why not only MAE?

Portal comparison

Portal	Framing	Model emphasis	Distinctive point
Khang Pham (khangich) [8]	"Estimate Delivery time" course module	Not public (paid course)	README pairs it with Uber Eats and DoorDash dispatch posts
alirezadir [7][12]	"Food delivery time approximation" sample question	Generic MLSD template	Listed next to proximity service; links DeepETA
Chip Huyen MLSD booklet [9]	Framework only	Data, modeling, serving steps	Stresses label definition and serving constraints
Uber DeepETA (company) [1][2]	Residual over routing engine	Linear-attention transformer, asymmetric Huber	Engineered for very high QPS
DoorDash (company) [3][13]	Delivery ETA at several stages	Multi-task, probabilistic forecasts	Quantile quotes; long-tail handling
Google Maps (company) [4][5]	Road travel time	GNN on supersegments	Models how traffic spreads in space

References

1. "DeepETA: How Uber Predicts Arrival Times Using Deep Learning", Uber Engineering Blog, 2022. https://www.uber.com/blog/deepeta-how-uber-predicts-arrival-times/
2. Hu, X., Binaykiya, T., Frank, E., Cirit, O., "DeeprETA: An ETA Post-processing System at Scale", arXiv, 2022. https://arxiv.org/abs/2206.02127
3. "Improving ETAs with multi-task models, deep learning, and probabilistic forecasts", DoorDash Engineering Blog, 2024. https://careersatdoordash.com/blog/improving-etas-with-multi-task-models-deep-learning-and-probabilistic-forecasts/
4. Derrow-Pinion, A. et al., "ETA Prediction with Graph Neural Networks in Google Maps", CIKM, 2021. https://arxiv.org/abs/2108.11482
5. "Traffic prediction with advanced Graph Neural Networks", DeepMind Blog, 2020. https://deepmind.google/discover/blog/traffic-prediction-with-advanced-graph-neural-networks/
6. Wang, Z., Fu, K., Ye, J., "Learning to Estimate the Travel Time", KDD, 2018. https://dl.acm.org/doi/10.1145/3219819.3219900
7. alirezadir, "ML System Design" notes (AIMLInterviews), GitHub. https://github.com/alirezadir/AIMLInterviews/blob/main/src/MLSD/ml-system-design.md
8. Khang Pham, "machine-learning-interview" repository, GitHub. https://github.com/khangich/machine-learning-interview
9. Chip Huyen, "machine-learning-systems-design", GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design
10. "Next-Generation Optimization for Dasher Dispatch at DoorDash", DoorDash Engineering Blog, 2020. https://doordash.engineering/2020/02/28/next-generation-optimization-for-dasher-dispatch-at-doordash/

11. "How Trip Inferences and Machine Learning Optimize Delivery Times on Uber Eats", Uber Engineering Blog, 2018. https://eng.uber.com/uber-eats-trip-optimization/
12. alirezadir, "Machine-Learning-Interviews" repository, GitHub. https://github.com/alirezadir/Machine-Learning-Interviews
13. "Improving ETA Prediction Accuracy for Long-tail Events", DoorDash Engineering Blog, 2021. https://doordash.engineering/2021/04/28/improving-eta-prediction-accuracy-for-long-tail-events/

16. Design Email Spam / Abuse / Bot Detection (Gmail Spam Filter, Twitter/X Bots)

> Prompt as usually given: "Design a system that classifies incoming email as spam / phishing / ham" or "Detect spam bots and fake accounts on a social network (Twitter/X, LinkedIn, Facebook)." Variants: comment / DM spam, invite spam (Slack), phone-lead spam (Zillow), viral spam posts (LinkedIn), fake-account registration, coordinated inauthentic behaviour.
>
> Sourcing note: at review time only github.com was reachable from the build sandbox (arxiv.org, medium.com, company blogs failed DNS) and web search was exhausted. Each reference carries a tag. (fetched) = GitHub page re-read during review. (repo-link) = URL appears verbatim in a fetched GitHub index (ByteByteGo ml-bytebytego, Engineer1999 case-study list, Botometer README, RETVec README). (ch-ref) = URL verified in another chapter of this atlas. (known) = canonical page cited from memory, not re-fetched. "Asked by" tags without a cited interview report were removed. Numbers marked "typical assumption" are standard interview estimates.

Company tags

Company	Evidence	Notes	Source
Google (Gmail)	Built it: RETVec robust text vectorizer (~200K params) deployed for Gmail spam per Google's blog [1]; RETVec repo itself does not name Gmail [2]	Canonical "email spam" system; [1] reports ~38% higher spam detection, ~19% fewer false positives and ~83% less TPU use vs prior vectorizer (not re-fetched)	[1] [2] [3]
X / Twitter	Built it: open-sourced trust-and-safety models (pNSFWMedia, pNSFWText, pToxicity, pAbuse) and visibility filters; no spam/bot model published	README: "several more models and rules" withheld "because of the adversarial nature of this area"	[4] [5]
Meta (Facebook, Instagram)	Built it: inauthentic-behaviour policy, integrity survey, TIES temporal interaction embeddings, abusive-account detection framework	Actor-level (account) detection; ByteByteGo ch. 5 cites these as follow-ups	[6] [7] [8] [9] [10]
LinkedIn	Built it: fake-account detection, isolation forest for abuse, viral spam content detection	Two-stage: at registration + post-registration activity	[11] [12] [13]
Pinterest, Slack, Zillow	Built it: spam clustering + automated rule creation; invite-spam ML; SpectroBrain phone-spam (semi-supervised)	Good "variant" systems	[14] [15] [16]
Academic (Indiana	Botometer: public Twitter bot-score service (v1-v4, BotometerLite); Botometer X is	Canonical bot-detection features and paper trail	[17] [18]

Company	Evidence	Notes	Source
Univ. OSoMe)	archival, scores from data collected before June 2023		[19]

Portals that cover it

Portal	Treatment	Link
alirezadir Machine-Learning-Interviews	Lists "Harmful content / Spam detection system" and "Fraud detection system" under "Other"; harmful-content notes list "detect fake accounts" as other topic	[20][21]
ByteByteGo (Aminian & Xu, MLSDI) ch. 5	Harmful content detection; harmful actors / fake accounts / abusive-account framework as follow-ups	[22][23]
Educative "Grokking the ML Interview" / Khang Pham MLSD	Classification template; "Fraud detection (TBD)" heading, empty, in Khang Pham's repo	[24][25] [26]
Chip Huyen MLSD exercises	Closest: exercise 2, fraud detection from labelled credit-card transactions	[27]
Exponent, Hello Interview, IGotAnOffer, Patrick Halina	General MLSD frameworks; integrity/spam frequently used as example classification prompt	[28][29] [30][31]
Engineer1999 curated case studies	Index of spam / abuse / fraud systems from company blogs	[32]

Requirements & scale

Dimension	Value	Source
Functional (email)	For each inbound message: spam / phishing / malware / promo / ham; action = reject at SMTP, send to Spam folder, warn banner, deliver	typical assumption
Functional (bots)	For each account: bot / fake / compromised score; action = challenge (CAPTCHA, phone verify), rate-limit, shadow-limit, suspend	[11][17] + typical assumption
Entities scored	Message, sender (IP, domain), account, URL, cluster (campaign)	typical assumption
Email volume	Billions of messages/day; ~100K-300K msg/s peak (interview assumption)	typical assumption
Account volume	~1M sign-ups/day; ~500M daily actions to score (posts, follows, DMs)	typical assumption
Latency	Email: p99 < 100-200 ms inside SMTP accept path; account sign-up: < 100 ms; batch account sweeps: hourly/daily	typical assumption
Precision	False positives (ham in spam, real user banned) are costly; target FPR < 0.1% on ham	typical assumption
Adversarial	Attackers adapt in hours: obfuscation (homoglyphs, LEET, typos), image spam, account farms	[1][2][4]
Languages	100+ languages; vocabulary-free text encoder preferred	[2][3]
Privacy	Email content is private: limited human labeling, on-device or aggregate features, data retention limits	typical assumption

Dimension	Value	Source
Sender policy (Gmail, 2024)	Bulk senders (>5K msgs/day to Gmail) must pass SPF + DKIM + DMARC, offer one-click unsubscribe, keep Postmaster spam rate < 0.3%: authentication results become hard features / gates	[34]

Diagram 1: end-to-end serving architecture

Diagram 1. Online email-spam path: SMTP -> reputation/rules -> feature fetch -> layered models -> policy engine -> deliver / spam folder / reject (with feature & model stores, logging).




Diagram 2: offline training & data pipeline

Diagram 2. Logging -> label sources (user reports, honeypots, analysts, rules) -> point-in-time feature join -> training -> adversarial eval -> registry -> shadow/canary -> deploy, with feedback loop.




Diagram 3: model architecture

Diagram 3. Multi-signal spam/phish classifier: robust char-level text encoder (RETVec- style) + URL/attachment + sender/reputation + recipient-context towers -> fusion -> multi-task heads.





Diagram 4: account-level bot / fake-account detection (Twitter/X, LinkedIn, Meta)

Diagram 4. Two-checkpoint bot detection: registration-time scoring + post-registration behavioural / graph models + campaign clustering, feeding challenges and enforcement.



Data & labels

Source	Type	Pros	Cons
"Report spam" / "Not spam" clicks	Explicit, user	Huge volume, fresh	Noisy (users report newsletters), biased to visible mail
Implicit (delete unread, never opened, unsubscribe)	Weak	Free	Very noisy; use as features or low-weight labels
Honeypot / spam-trap inboxes, seeded accounts	Ground truth spam	High precision, early	Not representative of targeted spam
Analyst review (sampled, privacy-reviewed)	Gold	Accurate eval set	Expensive, privacy constraints
Enforcement outcomes (suspended, appealed)	Account labels	Strong for bots	Delayed, feedback-loop bias
Rule / blocklist hits	Heuristic	Cheap	Model learns the rule; keep held-out
Semi-supervised / clustering	Propagated	Scales labels to campaigns	Error propagation [16][14]

Features

Group	Examples
Sender reputation	IP / ASN / domain age, SPF/DKIM/DMARC pass, historical spam rate, volume spikes, bounce rate

Group	Examples
Content	Raw text via robust char encoder, subject length, ALL CAPS ratio, HTML/text ratio, hidden text, OCR from images
URL / attachment	Domain age, redirect chain, URL shortener, known-bad hash, file type, macro presence; async sandbox detonation verdict for unknown attachments (feeds post-delivery re-scan)
Recipient context	Sender in contacts, prior replies, user's own report history, # recipients
Campaign	Near-duplicate cluster size (MinHash), burst rate, # distinct senders sharing template
Account behaviour (bots)	Account age, followers/following ratio, posts per hour, inter-action time entropy, default profile, username randomness [17][18]
Graph (bots)	Shared device/IP edges, clustering coefficient, reciprocity, neighbour bot scores [7][8]

Model choices (baseline -> advanced)

Stage	Model	Tradeoffs
0	Rules + blocklists + hash match	Instant, explainable; brittle, easily evaded
1	Naive Bayes / logistic on bag-of-words	Classic baseline; cheap; obfuscation breaks it
2	GBDT (XGBoost/LightGBM) on reputation + engineered features	Strong on tabular signals; fast; weak on raw text
3	Deep text model (char-CNN / RETVec + transformer, multilingual)	Robust to typos/homoglyphs; costlier; needs GPU/TPU budget [2][3]
4	Multimodal multi-task (text + URL + image + sender)	Shares signal across spam/phish/malware; harder to debug
5	Graph / temporal models for actors (GNN, TIES)	Catches coordinated bots; offline/near-line [8]
6	Unsupervised (isolation forest, clustering + auto-rules)	Finds new attacks without labels [12][14]
7	LLM-as-judge for borderline / analyst assist	Rich reasoning; too slow/expensive for every message
8	Few-shot adaptable large model (Meta Few-Shot Learner style)	New abuse policy enforced from a handful of examples in weeks, not months; heavy, used near-line [35]

Loss

Choice	When
Weighted BCE per head	Default multi-label (spam, phish, malware, promo)
Focal loss	Rare classes (phish, malware) with extreme imbalance [33]
Sample weights by label source	Honeypot > analyst > user report > implicit
Cost-sensitive / asymmetric	FP (ham to spam) costs more than FN
Contrastive / triplet on campaign pairs	Learn campaign embeddings for clustering

Offline metrics

Metric	Why
Recall at fixed FPR (e.g. FPR <= 0.1% on ham)	Operating-point metric that matches the business
PR-AUC	Imbalanced data; better than ROC-AUC
Per-slice FPR (language, sender type, new domains)	Fairness to legit small senders
Adversarial robustness	Accuracy on perturbed (typo/homoglyph) test set [2]
Calibration (ECE)	Thresholds and policy engine depend on calibrated scores
Time-split holdout	Detect decay against newest attacks

Online metrics / A-B

Metric	Direction
Spam-in-inbox rate (user "report spam" per 1K inbox mails)	Down
Ham-in-spam rate ("not spam" clicks per 1K spam-folder mails)	Down (guardrail)
Phishing click-through on delivered mail	Down
Bot prevalence (sampled audit) / fake sign-ups per day	Down
Prevalence (violating views / all views) and proactive rate (caught by system / all actioned)	Down / Up [21][22]
False suspensions, appeal overturn rate	Down (guardrail)
Time-to-detect new campaign	Down
Engagement of legit senders / legit new users	Neutral (guardrail)

- A/B caveat: adversaries see both arms; randomize by recipient, run short tests, and favour shadow mode + back-testing.

Serving & latency budget (email, p99 ~150 ms)

Step	Budget
SMTP edge + reputation lookup	10 ms
Rules / hash / blocklist	5 ms
Parse MIME, URLs, OCR (async for heavy images)	25 ms
Feature store fetch	15 ms
Stage-1 GBDT	2-5 ms
Stage-2 deep model (only uncertain ~10-20%)	20-40 ms on accelerator
Policy engine + write decision	10 ms
Headroom	~40 ms

- Post-delivery re-scan: messages already delivered can be moved to Spam when a campaign is later detected ("zero-hour" retro-actions).

Monitoring

Signal	Action
Score distribution shift per sender segment	Alert, re-calibrate thresholds

Signal	Action
Sudden rise in "not spam" clicks	Auto-rollback model / threshold
New cluster growth rate	Analyst queue, auto-rule
Feature freshness (reputation lag)	Page on-call
Label pipeline delay	Pause retraining
Per-language precision from sampled audits	Retrain / add data

Failure modes

Failure	Mitigation
Adversarial obfuscation (homoglyphs, LEET, zero-width chars)	Robust char encoder (RETVec), Unicode normalization, adversarial augmentation [2][3]
Image-only spam	OCR + image embeddings
Account warm-up (bots act human first)	Long-horizon behaviour models, graph signals
Feedback loop (only mail in inbox gets reported)	Exploration sample, honeypots, analyst audits
Legit bulk senders (newsletters) flagged	Promo class separate from spam; sender reputation; one-click unsubscribe
Label noise from user reports	Label model, per-user reliability weights
Model leaks via probing	Randomized thresholds, delayed actions, no fine-grained error messages
Compromised legit accounts	Account-takeover detection (login anomalies), not only content
Cold start new domains/IPs	Prior from ASN/registrar; conservative throttling

Interviewer follow-ups

- How do you get labels when email content is private and cannot be freely reviewed?
- How do you handle "report spam" noise (users reporting newsletters they subscribed to)?
- Spammers adapt in hours: how do you detect a brand-new campaign with zero labels?
- How would you make the text model robust to homoglyphs, typos and zero-width characters?
- Rules vs ML: when do you keep a hand-written rule, and how do rules feed the model?
- Choose the threshold: what is the cost of a false positive vs a false negative here?
- Why not one model for spam, phishing and malware? Multi-task vs separate models.
- How do you evaluate offline when attackers react to your deployed model?
- Bots: what features separate a bot from a power user or a legit automated account?
- How would you use the graph (shared IPs/devices, follow graph) to find bot rings?
- How do you avoid feedback loops where only inboxed mail can be reported?
- How do you serve billions of messages/day under 150 ms? What runs in the cascade?
- How do you A/B test when the adversary observes both arms?
- How would you add an LLM, and where in the cascade would it sit?
- How do you handle appeals and false suspensions, and use them as labels?
- How do sender-authentication rules (SPF/DKIM/DMARC, bulk-sender spam-rate caps) change what the model must learn? [34]

- How do you measure prevalence when most spam is never seen by users? (sampled audits, proactive rate) [21][22]

Portal comparison

Portal	Framing	Model emphasis	Distinctive point
ByteByteGo ch. 5 [22][23]	Harmful content on social platform; actors as follow-up	Multimodal multi-task NN, BCE per task, focal loss	Prevalence, proactive rate, appeals; references Meta abusive-account framework
alirezadir notes [20][21]	"Harmful content / Spam detection" in question list	DistilmBERT text, CLIP / SimCLR image, VideoMoCo video, multi-task NN	500M posts/day, natural labels for train, manual for eval
Educative / Khang Pham [24][25][26]	Generic binary classification template	GBDT -> deep; imbalance handling	Fraud/spam section is TBD in Khang Pham repo
Chip Huyen [27]	Fraud-classification exercise (closest analogue)	Supervised on labelled records	Focus on data/labels and metrics
Exponent / Hello Interview / Halina [28][29][31]	Framework-driven; spam is an example classifier prompt	Baseline -> advanced, cascade serving	Delivery framework, tradeoff discussion
Real systems [1]-[19]	Email: Gmail RETVec; social: Twitter T&S models, LinkedIn fake accounts, Botometer	Robust text encoders, GBDT + graph + clustering	Adversarial robustness and campaign clustering dominate

References

1. Google Security Blog, "Improving Text Classification Resilience and Efficiency with RETVec", security.googleblog.com, 2023. https://security.googleblog.com/2023/11/improving-text-classification.html (known)
2. Google Research, "RETVec: Resilient and Efficient Text Vectorizer" (repository), GitHub, 2023. https://github.com/google-research/retvec (fetched)
3. E. Bursztein et al., "RETVec: Resilient and Efficient Text Vectorizer", arXiv, 2023. https://arxiv.org/abs/2302.09207 (repo-link)
4. X / Twitter, "the-algorithm: trust_and_safety_models" (pNSFWMedia, pNSFWText, pToxicity, pAbuse), GitHub, 2023. https://github.com/twitter/the-algorithm/tree/main/trust_and_safety_models (fetched)
5. X / Twitter, "the-algorithm" (visibility filters), GitHub, 2023. https://github.com/twitter/the-algorithm (fetched)
6. Meta Transparency Center, "Inauthentic behavior" policy, transparency.fb.com. https://transparency.fb.com/policies/community-standards/inauthentic-behavior/ (repo-link)
7. A. Halevy et al., "Preserving Integrity in Online Social Networks", arXiv, 2020. https://arxiv.org/pdf/2009.10311.pdf (repo-link)
8. N. Noorshams, S. Verma, A. Hofleitner, "TIES: Temporal Interaction Embeddings for Enhancing Social Media Integrity at Facebook", arXiv, 2020. https://arxiv.org/pdf/2002.07917.pdf (repo-link)
9. Meta @Scale, "Temporal interaction embedding" (talk), facebook.com. https://www.facebook.com/atscaleevents/videos/730968530723238/ (repo-link)

10. "Abusive account detection framework" (talk), YouTube. https://www.youtube.com/watch?v=YeX4MdU0JNk (repo-link)
11. LinkedIn Engineering, "Automated Fake Account Detection at LinkedIn", engineering.linkedin.com, 2018. https://engineering.linkedin.com/blog/2018/09/automated-fake-account-detection-at-linkedin (known)
12. LinkedIn Engineering, "Detecting and preventing abuse on LinkedIn using isolation forests", 2019. https://engineering.linkedin.com/blog/2019/isolation-forest (repo-link)
13. LinkedIn Engineering, "Viral spam content detection at LinkedIn", 2023. https://engineering.linkedin.com/blog/2023/viral-spam-content-detection-at-linkedin (repo-link)
14. Pinterest Engineering, "Fighting Spam using Clustering and Automated Rule Creation", Medium, 2021. https://medium.com/pinterest-engineering/fighting-spam-using-clustering-and-automated-rule-creation-1c01d8c11a05 (repo-link)
15. Slack Engineering, "Blocking Slack Invite Spam With Machine Learning", 2021. https://slack.engineering/blocking-slack-invite-spam-with-machine-learning/ (repo-link)
16. Zillow Tech, "SpectroBrain: Detecting Phone Spam with Semi-Supervised Learning", zillow.com, 2023. https://www.zillow.com/tech/spectrobrain-detecting-phone-spam-with-semi-supervised-learning/ (repo-link)
17. OSoMe, Indiana University, "botometer-python" (Botometer X client), GitHub. https://github.com/osome-iu/botometer-python (fetched)
18. K.-C. Yang et al., "Scalable and Generalizable Social Bot Detection through Data Selection" (BotometerLite), arXiv, 2019. https://arxiv.org/abs/1911.09179 (repo-link)
19. M. Sayyadiharikandeh et al., "Detection of Novel Social Bots by Ensembles of Specialized Classifiers" (Botometer v4), arXiv, 2020. https://arxiv.org/abs/2006.06867 (repo-link)
20. alirezadir, "ML System Design" (ml-system-design.md), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (fetched)
21. alirezadir, "Harmful content detection" (mlsd-harmful-content.md), GitHub, 2024. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/mlsd-harmful-content.md (fetched)
22. A. Aminian, A. Xu, "Machine Learning System Design Interview", ch. 5 "Harmful Content Detection", ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/harmful-content-detection (ch-ref)
23. ByteByteGo, "ml-bytebytego: references for Machine Learning System Design Interview", GitHub, 2023. https://github.com/ByteByteGoHq/ml-bytebytego (fetched)
24. Educative, "Grokking the Machine Learning Interview", educative.io, 2024. https://www.educative.io/courses/grokking-the-machine-learning-interview (ch-ref)
25. Educative / K. Pham, "Machine Learning System Design", educative.io, 2021. https://educative.io/courses/machine-learning-system-design/introduction (ch-ref)
26. K. Pham, "machine-learning-interview", GitHub. https://github.com/khangich/machine-learning-interview (fetched)
27. C. Huyen, "Machine Learning Systems Design - Exercises", GitHub. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md (fetched)
28. Exponent, "Introduction to the ML System Design Interview", tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
29. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-

hurry/delivery (ch-ref)
30. IGotAnOffer, "Meta Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/facebook-machine-learning-engineer-interview (ch-ref)
31. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2021. http://patrickhalina.com/posts/ml-systems-design-interview-guide/ (ch-ref)
32. Engineer1999, "A Curated List of ML System Design Case Studies", GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies (fetched)
33. T.-Y. Lin et al., "Focal Loss for Dense Object Detection", arXiv, 2017. https://arxiv.org/abs/1708.02002 (known)
34. Google Workspace Admin Help, "Email sender guidelines", support.google.com, 2024. https://support.google.com/a/answer/81126 (known)
35. Meta, "Meta's New AI System Helps Tackle Harmful Content" (Few-Shot Learner), about.fb.com, 2021. https://about.fb.com/news/2021/12/metas-new-ai-system-tackles-harmful-content/ (repo-link)

17. Design Google Street View Face and License-Plate Blurring (Object Detection Pipeline)

> A privacy pipeline that finds every face and license plate in billions of panoramic street images and blurs them before publication. Unlike most chapters, there is no user request in the loop. The "serving path" is a high-throughput **batch inference** pipeline, the model is an **object detector**, and the business metric favours **recall** (a missed face is a privacy incident; an extra blur costs little).
>
> Research note: in the review pass only github.com URLs could be fetched (other hosts failed DNS resolution, and the search budget was used up). Tags: (verified) = fetched in the review; (ch-ref) = verified in an earlier chapter of this atlas; (known) = a stable arXiv or paper URL not re-fetched. Numbers in tables are typical assumptions unless they carry a citation.

Company tags

Company	What is reported	Source
Google	Owns the real system: automatic face and plate blurring in Street View since 2008 (ICCV 2009 paper)	[2] [3]
Google (interview)	ByteByteGo ch. 3 is titled "Google Street View Blurring System"	[1] [6]
Meta	Real comparable system: EgoBlur, open-source face and plate blurring for Project Aria egocentric data	[25]
Generic (any company)	alirezadir lists "Image blurring system" as a sample CV design question, with no company named	[4]

Portals that cover it

- ByteByteGo, Aminian & Xu, *Machine Learning System Design Interview*, ch. 3, "Google Street View Blurring System". This is the canonical write-up [1]. Its 27-item reference list on GitHub covers R-CNN family, YOLO, SSD, DETR, NMS, COCO eval, distributed training, GDPR, face-detection bias, active learning, human-in-the-loop [6].
- alirezadir / Machine-Learning-Interviews: CV section with two-stage (R-CNN, Fast/Faster R-CNN) and one-stage (YOLO, SSD) detectors, mAP, and "Image blurring system" as a sample question [4].
- Educative "Grokking the ML Interview" covers the related self-driving image segmentation case [7].
- Exponent, Hello Interview, Patrick Halina: generic delivery frameworks that this chapter maps onto a CV pipeline [8] [9] [10].
- Not covered: Chip Huyen's MLSD exercises have image retrieval and image classification but no detection or blurring exercise [12]; khangich/machine-learning-


interview has no CV design case [13].

Requirements & scale

Dimension	Value	Source
Functional	Input: street-level image or panorama. Output: the same image with every face and plate blurred	[1]
Objects	2 classes (human face, license plate). Optional extras: house numbers, people in private settings	[1] [2]
Primary objective	High recall at a fixed precision floor. A missed face is a privacy breach	[1] [2]
Reported quality (Google 2009)	About 89% of faces and 94-96% of plates blurred automatically	[2]
Latency	Not user-facing: batch, hours to days before publication	[1]
Throughput	About 1M+ new images a day; every panorama is about 75-100 MP (stitched from 8-15 cameras)	assumption
Total corpus	Tens of billions of images, re-run whenever the model is upgraded	assumption
Labelled data	About 1M images with bounding-box annotations (ByteByteGo's stated assumption)	[1]
Compliance	GDPR / local privacy law: raw imagery retention limits, deletion on request	[6]
User feedback	"Report a problem" button: users ask for extra blurring (whole house, person, car)	[3]
Fairness	Recall must hold across skin tones, ages, poses, plate formats from 100+ countries	assumption
Cost	GPU-hours per image dominate; tile and batch to keep accelerator use above 70%	assumption

Diagram 1 - End-to-end batch "serving" path

Diagram 1. Ingestion to publication: tiling, detection, NMS, policy, blurring, serving



- No feature store: the "features" are pixels plus metadata (camera id, GPS, time).
- The raw store is tightly access-controlled. Only blurred derivatives reach serving [2] [3].
- If the model is upgraded, the corpus is backfilled. Blurs are additive (new boxes are unioned with old ones), so the new model never un-blurs anything.

Diagram 2 - Offline training & data pipeline

Diagram 2. Labels, augmentation, training, recall-gated evaluation, registry, backfill




Diagram 3 - Model architecture

Diagram 3. Two-stage detector (Faster R-CNN + FPN), the ByteByteGo choice [1] [14] [16]





Diagram 4 - Variant: one-stage detector plus the 2009 Google cascade

Diagram 4. Alternative designs: one-stage dense detector vs the original production cascade [2] [15] [17]



Data & labels

Source	Label type	Size / volume	Notes	Source
Human-annotated Street View images	Bounding boxes, 2 classes	About 1M images	ByteByteGo assumption. Annotate tiles, keep "ignore" regions for crowds	[1]
Public face sets (WIDER FACE)	Boxes, with blur, pose and occlusion attributes	32k images, 394k faces	Pretraining and hard tiny-face cases	[18]
Public plate sets (country specific)	Boxes / corners	Varies	Plate shapes and scripts differ by country	assumption
User "Report a problem"	Image-level request plus a region	Ongoing	Noisy, and covers more than faces and plates (houses, cars)	[3]
Reviewer corrections	Missed or extra boxes	Sampled 0.1-1% of output	Gold set for monitoring	assumption
Synthetic	Pasted faces and plates, rendered weather	Unlimited	Fills rare slices	assumption
Active learning	Uncertain-band boxes sent to annotators	Ongoing	Cuts labelling cost; human-in-the-loop loop in ByteByteGo's refs	[6]

Features

Feature	Type	Used by	Notes
RGB pixels (tile)	Tensor	Backbone	Main signal, multi-scale
Image pyramid level / tile coords	Integer	Merge step	Maps boxes back to the panorama
Camera id, lens, projection	Categorical	Preprocess	Corrects equirectangular distortion
GPS / country	Categorical	Thresholds, plate model	Per-region plate formats

Feature	Type	Used by	Notes
Time of day, weather	Categorical	Eval slices	Night recall drops
Neighbour-frame boxes	Boxes	Temporal consistency	The same face seen from the next capture point

Model choices (baseline -> advanced)

Stage	Model	Pros	Cons	Source
Baseline	Haar / HOG sliding window + classifier (Viola-Jones style)	Cheap, explainable	Low recall on profile and small faces	[2]
Two-stage	Faster R-CNN + FPN	High accuracy, good on small objects. ByteByteGo's pick for offline batch	Slower, two-step training	[1] [14] [16]
Cascade	Cascade R-CNN	Better localisation at high IoU	More compute	[19]
One-stage	RetinaNet / YOLO / SSD	Fast, simple. Focal loss handles class imbalance	Historically weaker on tiny objects	[15] [17]
Specialist	RetinaFace for faces + plate detector	Best per-class recall	Two models to run	[20]
Transformer	DETR / ViTDet	No anchors or NMS (DETR); strong scaling	Slow convergence, compute-heavy	[21] [22]
Ensemble	Union of detectors -> verifier	Maximises recall	Cost, more false positives	assumption
Open-source reference	Meta EgoBlur face + plate detectors	Pretrained, released for privacy use	Tuned to egocentric Aria imagery	[25]

Loss

Component	Loss	Why
Classification	Cross-entropy over {bg, face, plate}, or focal loss	Background dominates, and focal loss down-weights easy negatives [15]
Box regression	Smooth L1 on (dx, dy, dw, dh), or GIoU / CIoU	GIoU is aligned with the IoU metric [23]
RPN (two-stage)	BCE objectness + smooth L1	Proposal quality
Recall bias	Class weights / lower positive IoU threshold for faces	A missed face costs more than an extra blur

Offline metrics

Metric	Definition	Target / use
IoU	Area of overlap / area of union	Match threshold, usually 0.5 [1]

Metric	Definition	Target / use
Precision, recall	At IoU >= 0.5	Report **recall at a fixed precision** (for example 0.98 recall at P >= 0.8)
AP / mAP	Area under the PR curve, averaged over classes (and IoU 0.5:0.95 COCO-style)	Main model-selection metric [1]
Recall by object size	Small (<16 px), medium, large	Tiny far faces are the hardest slice
COCO-style AP	AP@[0.5:0.95], AP_small/medium/large	Standard detection eval protocol [6]
Slice recall	Country, skin tone, night, occlusion, plate format	Fairness and coverage gates
Pixel coverage	Fraction of face pixels covered by any blur	Partial blur still counts as a leak

Online metrics / A-B

Metric	Definition	Notes
User privacy reports per 1M images	"Report a problem" blur requests	Main online signal [1] [3]
Reviewer-measured miss rate	Missed faces or plates in an audited sample	Gold metric, not delayed
Over-blur rate	Blurred non-targets (signs, posters)	Hurts imagery usefulness
Throughput / cost	Images per GPU-hour, backlog age	Publication SLA
A-B method	Not user-randomised. Use a shadow run on a holdout region plus a human audit of disagreements between old and new models	No traffic split needed

Serving & latency budget (per panorama, batch)

Step	Budget	Hardware / note
Fetch + decode + reproject	0.3-0.5 s	CPU workers
Tiling + pyramid (about 40-80 tiles)	0.1 s	CPU
Detection (batched tiles)	0.5-2 s	GPU/TPU, FP16/INT8, batch 16-64
Merge + NMS + policy	<0.1 s	CPU
Blur render + write	0.2 s	CPU
End-to-end	About 1-3 s compute; wall-clock SLA hours	Throughput matters, latency does not
Scale check	1M panos/day x 2 s = about 23 GPU-days/day, so about 25-50 GPUs	assumption

Monitoring

Signal	Alert on
Boxes per panorama (by class, region)	Sudden drop means a model or camera regression
Score distribution	Shift (new camera hardware, new country)
Reviewer miss rate on the gold sample	Above the SLA, for example >1% missed faces
User report rate	Spike by region or capture batch
Pipeline health	Backlog age, failed shards, GPU utilisation
Data drift	New plate formats, snow or night share, new lens

Failure modes

Failure	Cause	Mitigation
Missed tiny or distant faces	Low resolution	High-res tiles, P2 FPN level, multi-scale test-time augmentation
Faces split across tile seams	Tiling	Overlap tiles, merge with NMS in panorama coordinates
Equirectangular distortion at poles	Projection	Cube-map reprojection
False positives on posters, statues, billboards	Face-like patterns	Hard-negative mining. Over-blur is acceptable, so bias toward blurring
Blurring signs or business names	Plate-like text	Verifier, context features
Foreign plate formats	Domain shift	Per-country data, region thresholds
Demographic recall gaps	Biased training data	Stratified labelling, slice gates
Partial blur leaks identity	Tight box	Expand box margin, pixel-coverage metric
De-blurring attack	Weak blur	Irreversible blur (pixelate + noise), never ship the raw image
Model upgrade un-blurs	Replace instead of union	Union old and new boxes; boxes only ever get added

Interviewer follow-ups

- Why prioritise recall over precision, and how do you pick the operating threshold?
- Two-stage vs one-stage detector for an offline batch job: which and why? [1]
- How does NMS work, what goes wrong with crowds, and when would you use soft-NMS? [24]
- How do you handle 100-megapixel panoramas: downscale, tile, or multi-scale?
- How do you avoid duplicate or split boxes at tile boundaries?
- How do you get 1M labelled images cheaply? Active learning, pseudo-labels, user reports.
- How do you split train and test to avoid leakage between neighbouring frames of one street?
- mAP vs recall-at-precision: which do you report to the privacy team?
- How do you measure and guarantee recall across skin tones and countries?
- How would you A-B test a new model when there is no click signal?
- How do you backfill tens of billions of images when the model improves, and at what cost?

- How do you handle user requests to blur a whole house or car (out of model scope)?
- How would you run this on the capture vehicle (edge) instead of in the data centre?
- How would you extend it to new classes (house numbers, screens, ID cards)?
- How do GDPR and "right to be forgotten" requests change raw-data retention and training-set reuse? [6]
- How do you train on about 1M high-res images: data parallel vs model parallel? [6]
- Which samples go to annotators first (active learning on the uncertain band)? [6]
- How do you detect drift when new camera hardware ships?

Portal comparison

Portal	Framing	Model	Metrics	Distinctive points
ByteByteGo ch. 4 [1]	Batch privacy pipeline, 2 classes, about 1M labelled images	Two-stage (Faster R-CNN-like), compared with one-stage	IoU, precision, AP, mAP offline; user reports online	Full walk-through of NMS, augmentation, hard negatives, batch vs online prediction
Google ICCV 2009 (real system) [2]	Production privacy at Street View scale	Sliding-window detectors + post-processing classifier; separate plate detector	Recall of about 89% faces, 94-96% plates	Shows that recall-first operating points plus a manual-report path are the norm
Educative Grokking [7]	Self-driving perception (segmentation / detection)	CNN encoder-decoder, detectors	IoU, pixel accuracy	Same CV building blocks, real-time edge setting
alirezadir MLSD [4]	Generic template plus a CV detection cheat sheet	R-CNN family, YOLO, SSD	mAP, IoU	Concise checklists, no full case
Exponent / Hello Interview [8] [9]	Delivery framework applied to any prompt	Model-agnostic	Business vs model metrics	Interview pacing and communication
Meta EgoBlur (real system) [25]	Privacy blurring for egocentric AR data	Separate face and plate detectors	Not stated on repo page	Open-source weights; shows the same 2-class design in production

References

1. A. Aminian, A. Xu, "Machine Learning System Design Interview", ch. 3 "Google Street View Blurring System", ByteByteGo, 2023. Book overview: https://opencourser.com/book/xop33f/machine-learning-system-design-interview (ch-ref; ch. 3 title verified via [6])
2. A. Frome, G. Cheung, A. Abdulkader, M. Zennaro, B. Wu, A. Bissacco, H. Adam, H. Neven, L. Vincent, "Large-scale Privacy Protection in Google Street View", ICCV, 2009. https://research.google/pubs/pub35481/ (known; not re-verified in this run)
3. Google, "Street View: Privacy and policies / Report a problem", google.com, ongoing. https://www.google.com/streetview/policy/ (known; not re-verified in this run)
4. alirezadir, "ML system design" (ml-system-design.md), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md

(verified)
5. (removed: IGotAnOffer Google MLE page did not support any claim in this chapter)
6. ByteByteGo, "ml-bytebytego: references for Machine Learning System Design Interview", GitHub, 2023. https://github.com/ByteByteGoHq/ml-bytebytego (verified)
7. Educative, "Grokking the Machine Learning Interview", educative.io, 2024. https://www.educative.io/courses/grokking-the-machine-learning-interview (ch-ref)
8. Exponent, "Introduction to the ML System Design Interview", tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
9. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery (ch-ref)
10. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2021. http://patrickhalina.com/posts/ml-systems-design-interview-guide/ (ch-ref)
11. C. Huyen, "Introduction to Machine Learning Interviews" (ml-interviews-book), huyenchip.com, 2021. https://huyenchip.com/ml-interviews-book/ (ch-ref)
12. C. Huyen, "Machine Learning Systems Design: exercises", GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md (verified)
13. K. Pham, "machine-learning-interview", GitHub, 2021. https://github.com/khangich/machine-learning-interview (verified)
14. S. Ren, K. He, R. Girshick, J. Sun, "Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks", arXiv, 2015. https://arxiv.org/abs/1506.01497 (known)
15. T.-Y. Lin et al., "Focal Loss for Dense Object Detection" (RetinaNet), arXiv, 2017. https://arxiv.org/abs/1708.02002 (ch-ref)
16. T.-Y. Lin et al., "Feature Pyramid Networks for Object Detection", arXiv, 2016. https://arxiv.org/abs/1612.03144 (known)
17. J. Redmon et al., "You Only Look Once: Unified, Real-Time Object Detection", arXiv, 2015. https://arxiv.org/abs/1506.02640 (known)
18. S. Yang, P. Luo, C. C. Loy, X. Tang, "WIDER FACE: A Face Detection Benchmark", arXiv, 2015. https://arxiv.org/abs/1511.06523 (known)
19. Z. Cai, N. Vasconcelos, "Cascade R-CNN: Delving into High Quality Object Detection", arXiv, 2017. https://arxiv.org/abs/1712.00726 (known)
20. J. Deng et al., "RetinaFace: Single-stage Dense Face Localisation in the Wild", arXiv, 2019. https://arxiv.org/abs/1905.00641 (known)
21. N. Carion et al., "End-to-End Object Detection with Transformers" (DETR), arXiv, 2020. https://arxiv.org/abs/2005.12872 (known)
22. Y. Li, H. Mao, R. Girshick, K. He, "Exploring Plain Vision Transformer Backbones for Object Detection" (ViTDet), arXiv, 2022. https://arxiv.org/abs/2203.16527 (known)
23. H. Rezatofighi et al., "Generalized Intersection over Union", arXiv, 2019. https://arxiv.org/abs/1902.09630 (known)
24. N. Bodla et al., "Soft-NMS: Improving Object Detection With One Line of Code", arXiv, 2017. https://arxiv.org/abs/1704.04503 (known)
25. Meta / facebookresearch, "EgoBlur: Responsible Innovation in Aria", GitHub + arXiv, 2023. https://github.com/facebookresearch/EgoBlur ; https://arxiv.org/abs/2308.13093 (verified via GitHub)

18. Design Search Query Autocomplete / Typeahead with ML Ranking

> Source note: refs [1] [3] [5] [6] [14] [15] were fetched for this review. Several other domains (arXiv, ByteByteGo, Google, LinkedIn, Instacart, Algolia) could not be reached from this run; those references are well-known primary sources, and the Instacart and Algolia URLs are confirmed by the index in [15]. Rows marked " (assumption)" are typical interview defaults, not cited figures.

Company tags

Company / context	What links it to this problem	Source
Google (Search, Gmail)	Chip Huyen's exercise #5 uses Google's related searches. Gmail Smart Compose is the production neural-completion reference	[3] [9] [10]
Amazon (product search)	Session-aware QAC built as extreme multi-label ranking (KDD 2021)	[7]
Microsoft (Bing)	Personalized QAC learning-to-rank (SIGIR 2013) and rare-prefix QAC (CIKM 2015)	[5] [6]
LinkedIn	Partial, out-of-order, real-time typeahead over connections, companies, groups, skills (Cleo, open-sourced 2012)	[8] [14]
Instacart	ML-driven autocomplete for grocery search (2022)	[11]
Algolia (SaaS search)	Query Suggestions product built from search analytics	[12]
Meta, Uber, DoorDash, etc.	Often reported on forums as a search sub-problem. Not verified for this chapter	(unverified)

Portals that cover it

- alirezadir / AIMLInterviews lists "Autocompletion / typeahead suggestion system" as an NLP sample MLSD question [1].
- Chip Huyen, ML Systems Design exercises #5 (related searches) and #10 ("finish your sentence when you text") [3] [4].
- ByteByteGo / Alex Xu, *System Design Interview* Vol. 1, Ch. 13 "Design a Search Autocomplete System". This is the trie/infra version that most ML answers build on [2].
- DesignGurus / Educative Grokking, "Designing Typeahead Suggestion" (infra version) [13].
- Engineer1999 curated case-study list (Instacart, Algolia entries) [15].

Requirements & scale

Dimension	Value	Source
Functional	Return the top-K (5-10) completions for a prefix on every keystroke. Personalized, fresh (trending), safe	[2] [5]
Optional	Spelling-tolerant prefixes, entity suggestions (people, products), multi-language	[8] (assumption)
ML objective	Rank candidate completions by P(user selects completion and the search succeeds)	[5] [7]
DAU	10M users, 10 searches/day, about 20 chars/query, one request per keystroke	[2]
QPS	About 24k QPS average and about 48k peak in the Xu estimate. FAANG-scale is more than 100k (assumption)	[2]
Latency	Under 100 ms end-to-end, or the suggestions feel laggy. Model budget 5-20 ms (assumption)	[2]
Candidate pool	10M-1B distinct historical queries. Top-N per prefix is precomputed	[2] (assumption)
Freshness	Trending queries surface within minutes. Base index rebuilt daily or weekly	[2] (assumption)
Non-functional	Highly available, safe (no offensive or defamatory completions), privacy (no PII leakage)	(assumption)

Diagram 1: Online serving path

DIAGRAM 1: Online keystroke-to-suggestions path (synthesised from [2][5][6][7][8])




Diagram 2: Offline training & data pipeline

DIAGRAM 2: Logs to index and ranker, with feedback loop (synthesised from [2][5] [7][11])




Diagram 3: Model architecture

DIAGRAM 3: Two-stage QAC model, with LTR ranker and optional neural generator ([5][6][7][9])



Diagram 4: Real-system variants

DIAGRAM 4a: Amazon session-aware QAC as extreme multi-label ranking [7]





DIAGRAM 4b: LinkedIn typeahead (Cleo) multi-source fan-out [8] [14]



What production systems add beyond the portal answers

System	Addition often missed in interviews	Source
Bing (Shokouhi 2013)	Supervised personal ranker with a labeling strategy for offline data. Long-term history and location matter most. Up to 9% MRR gain over popularity	[5]
Bing (Mitra & Craswell 2015)	Synthetic candidates from mined query suffixes for unseen prefixes, ranked with n-gram and CLSM features	[6]
Amazon (Yadav et al. 2021)	Previous query in the session as input to an XMR model that retrieves completions directly	[7]
LinkedIn Cleo	Partial and out-of-order token matching, real-time index updates, one library across many entity types	[8] [14]
Gmail Smart Compose	Neural LM completion under a strict per-keystroke latency budget, with safety filtering of generated text	[9] [10]

Data & labels

Item	Choice	Note
Unit of example	(prefix, candidate, user, context) at each keystroke impression	[5]
Positive	Shown completion the user selected	Selection is the direct signal
Weak positive	Final submitted query that starts with the prefix but was not shown	Recovers recall when the user kept typing [5]
Negative	Shown, not selected	Position bias: down-weight or use IPS
Label weight	Boost when the downstream search succeeded (click, purchase)	[11] (assumption)
Cold data	Synthetic prefixes from full queries (all prefixes of q)	Standard bootstrap
Public benchmark	AOL query log (used with Bing logs in Shokouhi 2013)	[5]

Features

Group	Examples
Popularity	Global and per-geo frequency, time-decayed count, hourly trend velocity
Prefix-query	Completion length, prefix ends mid-word, fuzzy-match distance, out-of-order token match [14]
Suffix / semantic	N-gram suffix frequency, CLSM similarity of prefix and candidate (rare prefixes) [6]
Personal	Past issuance of q by user, recency, long-term history and location (the strongest personal signals in [5])
Session	Sim to previous queries in session, reformulation patterns [7]
Quality	Historical CTR at position, zero-result rate, downstream conversion [11]
Context	Time of day, device, locale, surface (web, app, voice)

Model choices

Stage	Option	Pros	Cons
Baseline	MostPopularCompletion from a trie	Simple, under 1 ms	Not personal, fails on rare prefixes
Retrieval	Trie/FST with precomputed top-N per node [2]	O(prefix len) lookup	Fixed vocab, rebuild cost
Retrieval	Suffix synthesis for rare prefixes [6]	Covers the long tail	Can produce nonsense
Retrieval	XMR / extreme classification [7]	Uses session context	Training complexity
Ranker	GBDT LambdaMART	Strong on tabular features, cheap	Weak on raw text
Ranker	Two-tower / cross DNN	Semantic and session aware	Latency, needs GPU or quantization
Generator	Char/subword LM + beam [9][10]	Open vocabulary	Safety risk, ms per token

Loss

Model	Loss
LTR ranker	Pairwise (RankNet) or LambdaRank/LambdaMART optimizing nDCG / MRR
Pointwise alt	Binary cross-entropy on selected vs shown, IPS-weighted
Generator	Token-level cross-entropy (next-char / next-token)
Safety filter	Binary or multi-label cross-entropy

Offline metrics

Metric	Meaning
MRR	Reciprocal rank of the eventually-submitted query [5]
Success@K / Recall@K	Target query appears in the top K
pSaved / eSaved	Probability-weighted keystrokes saved
nDCG@K	Graded by downstream success
Safety rate	Percent of prefixes that produce an offensive completion (red-team set)
Coverage	Percent of prefixes with at least 1 suggestion (rare-prefix tail) [6]

Online metrics / A/B

Metric	Type
Suggestion CTR / acceptance rate	Primary
Keystrokes per search, time to search	Primary (effort)
Downstream search success (click, purchase), reformulation rate	North star
Zero-result searches	Guardrail
p99 latency, error rate	Guardrail
Offensive-suggestion reports	Safety guardrail

Serving & latency budget

Step	Budget (assumption)
Client debounce + network	30-50 ms
Edge/prefix cache lookup	1-2 ms (high hit rate for short prefixes)
Candidate gen (trie + trending + personal, parallel)	5-10 ms
Filtering	1-2 ms
Feature fetch	3-5 ms
Ranker on ~200 candidates	5-15 ms (GBDT or a distilled DNN)
Re-rank / policy	1 ms
Total server	Under 40 ms. End-to-end under 100 ms [2]

Monitoring

What	Signal
Data	Log volume per keystroke, label join rate, feature null rate
Model	Score distribution drift, MRR on fresh holdout, CTR by position
Freshness	Lag from trending event to suggestion
Safety	Blocklist hits, user reports, sensitive-entity completions
System	Cache hit rate, p50/p99 latency, shard hotness

Failure modes

Failure	Mitigation
Offensive, defamatory or PII completions	Blocklists, classifier, human escalation, takedown pipeline
Rich-get-richer / position-bias loop	IPS, randomized exploration slots, counterfactual LTR
Rare or new prefixes return nothing	Suffix synthesis [6], neural generator, fuzzy match
Trending spikes missed	Streaming counts with time decay
Manipulation (query spam to push a completion)	Unique-user thresholds, anomaly detection
Latency spikes on 1-char prefixes	Precompute and cache short prefixes at the edge
Personal leakage on shared devices	Per-account history, opt-out, no cross-user PII

Interviewer follow-ups

- How do you generate labels when the user never clicks a suggestion and keeps typing?
- How do you correct for position bias in the selection logs?
- How do you handle a prefix never seen before (long tail)? [6]
- Trie with precomputed top-N vs on-the-fly ranking: what goes where? [2]
- How do you surface a breaking-news query within 5 minutes?
- How would you personalize without hurting the cache hit rate? [5]
- How do you use the previous query in the session? [7]

- How do you prevent offensive or legally risky completions?
- Would you use an LLM to generate completions? What are the latency and safety costs? [9]
- What offline metric best predicts online keystrokes saved?
- How do you handle typos in the prefix ("iphnoe")?
- How do you match out-of-order tokens ("york new" to "new york")? [14]
- Personalized ranker vs popularity: what gain is realistic? (Up to 9% MRR on Bing logs) [5]
- How do you support multiple languages and scripts (CJK input methods)?
- How do you stop adversaries from gaming the suggestions?
- How do you shard the index and keep it consistent during rebuilds?

Portal comparison

Portal	Framing	Core solution	ML depth
ByteByteGo Vol. 1 [2]	Infra system design	Trie with cached top-K per node, data-gathering service, weekly rebuild, sharding	Popularity only
DesignGurus / Grokking [13]	Infra system design	Trie, offline aggregation, partitioning, client-side tricks	Popularity only
Chip Huyen exercises [3]	ML exercise	Open-ended: related searches and sentence completion	Expects LM + ranking
alirezadir [1]	NLP MLSD question	Use the 6-step MLSD template	Ranking + NLP
Research / company blogs [5][6][7][11]	Production QAC	Candidate generation + LTR ranker, personalization, session context	Deep (LTR, XMR, embeddings)

References

1. alirezadir, "ML System Design" (sample questions: Autocompletion / typeahead), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md
2. A. Xu, "Design a Search Autocomplete System" (System Design Interview Vol. 1, Ch. 13), ByteByteGo, 2020. https://bytebytego.com/courses/system-design-interview/design-a-search-autocomplete-system
3. C. Huyen, "machine-learning-systems-design" exercises (#5 related searches, #10 autocompletion), GitHub, 2019. https://raw.githubusercontent.com/chiphuyen/machine-learning-systems-design/master/content/exercises.md
4. C. Huyen, "machine-learning-systems-design" booklet, GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design
5. M. Shokouhi, "Learning to Personalize Query Auto-Completion", SIGIR / Microsoft Research, 2013. https://www.microsoft.com/en-us/research/publication/learning-to-personalize-query-auto-completion/
6. B. Mitra & N. Craswell, "Query Auto-Completion for Rare Prefixes", CIKM / Microsoft Research, 2015. https://www.microsoft.com/en-us/research/publication/query-auto-completion-for-rare-prefixes/
7. N. Yadav et al., "Session-aware Query Auto-completion using Extreme Multi-label Ranking", KDD / arXiv, 2021. https://arxiv.org/abs/2012.07654

8. LinkedIn Engineering, "Cleo: the open source technology behind LinkedIn's typeahead search", linkedin.com, 2012. https://engineering.linkedin.com/open-source/cleo-open-source-technology-behind-linkedins-typeahead-search
9. Google AI Blog, "Smart Compose: Using Neural Networks to Help Write Emails", googleblog.com, 2018. https://ai.googleblog.com/2018/05/smart-compose-using-neural-networks-to.html
10. M. X. Chen et al., "Gmail Smart Compose: Real-Time Assisted Writing", KDD / arXiv, 2019. https://arxiv.org/abs/1906.00080
11. Instacart Tech, "How Instacart Uses Machine Learning-Driven Autocomplete to Help People Fill Their Carts", tech.instacart.com, 2022. https://tech.instacart.com/how-instacart-uses-machine-learning-driven-autocomplete-to-help-people-fill-their-carts-9bc56d22bafb
12. Algolia, "Feature Spotlight: Query Suggestions", algolia.com, 2023. https://www.algolia.com/blog/product/feature-spotlight-query-suggestions/
13. DesignGurus, "The Grokking series" (includes Designing Typeahead Suggestion), designgurus.io, 2025. https://www.designgurus.io/grokking
14. LinkedIn, "Cleo: partial, out-of-order and real-time typeahead search" (source repository), GitHub, 2012. https://github.com/linkedin/cleo
15. Engineer1999, "A Curated List of ML System Design Case Studies", GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies

19. Design Music Recommendation and Playlist Generation (Spotify Discover Weekly and Home)

> How the prompt is usually worded: "Design Spotify's 'Discover Weekly' playlist" [1] [2], or "Design the Spotify Home page: which shelves and which playlists or tracks each user sees". Variants: automatic playlist continuation ("add songs to this playlist") [22][23], radio or autoplay (next-track), "Daily Mix", podcast recommendations on Home [11][12], and conversational music recommendation (Amazon Music) [26].
>
> Sourcing note: this chapter was compiled and reviewed after the shared web-search budget had run out. Only GitHub hosts could be reached. engineering.atspotify.com, dl.acm.org, hackernoon.com and amazon.science did not resolve when re-checked in review. Sources marked (fetched) were read for this chapter through GitHub. Sources marked (ch-ref) were verified in earlier chapters of this atlas. Sources marked (known) are canonical papers or posts whose URLs were confirmed through curated GitHub lists [24][25] but whose text could not be re-read here. Numbers taken from them are flagged.

Company tags

Company	What is reported	Source
Spotify	The problem is Spotify's own product. "Design Spotify's 'Discover Weekly' playlist" appears in community MLSD question lists as a standard recommendation prompt	[1] [2] [3]
Meta	A company-tagged question bank lists "Design Spotify" (system design, medium) under Meta. This is the classic (non-ML) version; an open-source "Design Spotify" answer adds a `GET /api/recommendations/discover-weekly` endpoint, so the recommender is a natural deep-dive	[4] [35]
Amazon (Amazon Music), Apple (Apple Music), YouTube Music, Pandora, Deezer, SoundCloud	These companies run the same kind of product. No direct question report could be verified for this chapter, so treat this row as an inference	assumption
General MLE loops	One community guide asserts that almost every MLSD round includes a prompt such as "Design Spotify's Discover Weekly" (opinion, no data)	[2]

Portals and sources that cover it

Portal / source	Treatment	Link
Community MLSD notes (sharayu134, mdrijwan123, Gaurav14cs17)	[1] lists "Design Spotify's 'Discover Weekly' playlist" as a sample prompt; [2] cites Discover Weekly as a recsys impact example; [3] lists "Spotify: Discover Weekly hybrid approach" as a case study	[1][2] [3]

Portal / source	Treatment	Link
Chip Huyen (DMLS book resources)	Lists the Ciocca Discover Weekly article (CF + NLP + audio models) as reading. Her MLSD booklet [34] is generic and has no music content	[5][6]
ByteByteGo (Aminian & Xu)	No music chapter. Use the video-recommendation chapter (two-tower retrieval plus ranker) as the template	[28]
alirezadir AIMLInterviews	Video and game recommendation templates. No music file	[27]
Hello Interview	Generic recommendation-systems pattern (retrieval, ranking, re-ranking); no music write-up. See also E. Yan on discovery system design	[30] [32]
Exponent / Aced, Educative	Generic MLSD frameworks. No music-specific write-up could be verified	[29] [31]
Spotify engineering and research (the real system)	Discover Weekly hybrid (CF + NLP + audio), BaRT bandits on Home, CoSeRNN contextual user embeddings, Annoy then Voyager ANN, in-house experimentation platform	[6]-[20], [36]

Requirements & scale

Dimension	Value	Basis
Functional	(a) Discover Weekly: 30 new-to-user tracks per user, refreshed every Monday. (b) Home: rank shelves (cards) and the items inside each shelf. (c) Explain the slot ("Because you listened to X")	[6][8] (known)
Novelty constraint	Discover Weekly must exclude tracks the user has already played. Home can mix familiar and new content	[6] (known)
Users	Hundreds of millions of MAU. Assume 600M+ users and 100M+ tracks, plus podcasts and audiobooks	typical assumption
Weekly batch	600M users x 30 tracks = about 18B rows of slate per week. Spread over a 2-3 day batch window	assumption
Home QPS	About 50k QPS peak for Home loads, with 10-20 shelves per page	assumption
Latency	Home p99 under 200 ms server-side. Discover Weekly is offline (precomputed), with a single key-value read at request time	assumption
ANN scale	Spotify's Voyager is "queried hundreds of millions of times per day"	[19] (fetched)
Historical reach	Discover Weekly "reaches over 30 million users every week" (older figure quoted by a community guide)	[2] (fetched)
Non-functional	Freshness (new releases, new users), diversity and artist fairness, explainability, cost of weekly batch, privacy	[8][16] (known)

Diagram 1: End-to-end architecture (online serving path)

Figure 19.1 - Hybrid serving: Discover Weekly is precomputed in batch; Home is ranked online.




Diagram 2: Offline training & data pipeline

Figure 19.2 - Weekly batch for Discover Weekly plus daily retraining for Home rankers.




Diagram 3: Model architecture

Figure 19.3 - Hybrid retrieval (CF + content + contextual user tower) feeding a multi-task ranker.





Diagram 4: Variant - the real Spotify systems

Figure 19.4 - Discover Weekly as an ensemble of three model families, and Home ordered by a contextual bandit (BaRT).



Data & labels

Signal	Label use	Notes
Stream >= 30 s	Positive	A common "real listen" threshold. Treat as an assumption in interviews
Skip < 30 s	Negative (strong)	Position-dependent: skips late in a long session are weaker
Save / like / add to playlist	Strong positive, separate head	Sparse but high intent. Key Discover Weekly success signal
Impression with no play	Weak negative	Needs propensity logging to de-bias [8]
User playlists (co-occurrence)	Item-item similarity, CF training	The Million Playlist Dataset (RecSys Challenge 2018) was built from this signal [22]
Audio and web text	Content features for cold start	[7][15]

Features

Group	Examples
User	Long-term taste embedding, top artists and genres, listening diversity, account age, country
Session / context	Last N tracks (with skips), time of day, weekday, device (car, phone, speaker) [9]
Item	Track, artist and album embeddings, audio embedding, release date, popularity, language
User x item	Artist affinity, played-before flag, genre match, co-listen score, days since last artist play
Shelf (Home)	Shelf type, historical CTR, explanation type, position [8]

Model choices (baseline -> advanced)

Stage	Baseline	Advanced	Tradeoff
Retrieval	Item-item co-occurrence; implicit MF (ALS) + Annoy [18]	Two-tower with sequence user tower (CoSeRNN-like) + Voyager/HNSW [9][19][23][33]	MF is cheap and strong. The sequence tower adds context but costs more
Cold start (items)	Metadata and genre	Audio CNN regressing CF factors [7]	The audio model may recommend "sound-alike" tracks that are not good fits
Cold start (users)	Onboarding artist picks, popular in region	Bandit exploration	Exploration costs short-term engagement
Ranking	GBDT on hand features	Multi-task DNN (MMoE)	MTL needs weight tuning across objectives
Slate / page	Rule-based (diversity caps)	Contextual bandit (BaRT) [8], RL for diversity [16]	Bandits need propensity logging and careful off-policy evaluation

Loss functions

Model	Loss
Implicit MF	Weighted squared loss with confidence c = 1 + alpha * play_count (ALS)
Two-tower	Sampled softmax with in-batch negatives and logQ correction [21]

Model	Loss
Audio CNN	MSE to unit-normalised 40-d CF latent vectors; unit norm reduces popularity leakage, since factor norms correlate with popularity [7] (fetched)
Ranker heads	Binary cross-entropy per head; weighted sum
Bandit reward model	Logistic loss on stream given impression; IPS-weighted for off-policy [8]

Offline metrics

Metric	Use
Recall@k / HitRate@k	Retrieval on held-out next-week plays
NDCG@k, MAP	Ranking quality
R-precision, NDCG, "recommended songs clicks"	Playlist continuation (RecSys Challenge 2018) [22] (fetched)
Novelty, diversity, catalog coverage, artist Gini	Discover Weekly quality beyond accuracy [16]
Counterfactual (IPS / SNIPS) reward	Evaluate Home bandit policy offline [8]

Online metrics / A-B

Metric	Notes
Discover Weekly: share of users who stream, streams per user, saves per user, tracks added to library	Primary success metrics (assumption)
Home: shelf CTR, consumption minutes from Home, time to first stream	[10][11] (known)
Long-term: weekly active retention, return to Discover Weekly next Monday	Guardrail
Guardrails: skip rate, latency, crash rate, diversity and new-artist exposure	Spotify runs these on an in-house experimentation platform [20][36]
Latency guardrail as a distribution	Compare p90/p99 between arms, not only means (quantile tests at scale) [37]

Serving & latency budget (assumption, Home p99 about 200 ms)

Step	Budget
Feature fetch (user + context)	15 ms
Candidate generation (parallel ANN + co-listen + editorial)	30 ms
Filtering and dedupe	5 ms
Ranking (~1-2k items, batched)	60 ms
Bandit and diversity re-rank, explanations	20 ms
Network, serialisation, slack	70 ms
Discover Weekly read	Single KV lookup, under 10 ms

Monitoring

What	How
Data freshness	Lag of play-event ingestion; missing Monday batch alarms
Feature drift	PSI on user and item embeddings and on popularity distribution
Embedding/index health	ANN recall vs brute force on a sample; index build time [19]
Index distribution	Build ANN index once offline, ship static files, mmap them so many serving processes share one copy (Annoy design) [18]
Prediction drift	Mean p(stream) vs observed stream rate per shelf and country
Content health	Share of new artists, top-artist concentration, explicit-content leaks

Failure modes

Failure	Mitigation
Popularity bias / filter bubble	Novelty boost, diversity caps, RL for diverse consumption [16]
Cold-start tracks never surface	Audio and NLP content embeddings [7][15]; exploration slots
Shared accounts or kids' listening pollute taste	Session clustering; context-aware user embeddings [9]
Feedback loop (Home only shows what it already shows)	Logged propensities, epsilon exploration [8]
Sound-alike but wrong (covers, intros, remixes)	Dedupe by work id; CF signal outweighs audio when data exist [7]
Weekly batch fails or partially completes	Keep last week's list; incremental re-scoring

Interviewer follow-ups

- Discover Weekly must contain only tracks the user has not heard. Where do you enforce this, and how do you keep a played-set for 600M users?
- Why batch-compute Discover Weekly instead of serving it online? What changes if it must refresh daily?
- How do you recommend a track released yesterday with zero plays (audio CNN, NLP, artist prior)? [7]
- How do you handle a new user with no history?
- Is a skip negative? How do you treat skips in a workout session vs a focus session?
- How do you order the 30 tracks for flow (tempo, key, energy), not just relevance?
- How do you trade off familiarity vs discovery? What metric captures "discovery"?
- How would you rank shelves on Home and also pick the item inside each shelf? (BaRT) [8]
- How do you evaluate a new Home policy offline when logs come from the old policy? (IPS)
- How do you mix music, podcasts and audiobooks in one ranking? [11][12]
- How do you keep artist fairness or avoid over-exposing top labels? [16]
- Family plans and shared devices: how do you detect and separate listeners?

- Which ANN library and index parameters, and how do you measure recall loss? [18] [19]
- How do you ship a new ANN index to thousands of serving hosts without a memory spike? (static, mmap-shared index files) [18]
- The audio model regresses CF factors: why normalise the targets, and what happens to popular tracks if you do not? [7]
- How would you add an LLM ("AI DJ"-style commentary, or text prompts for playlists) on top of this stack?

Portal comparison

Source	Framing	Retrieval	Ranking	Distinctive point
Community MLSD notes [1][2][3]	"Design Discover Weekly"	CF + content	Generic ranker	Emphasise CF vs content and cold start
Chip Huyen DMLS resources [5] / Ciocca [6]	Case study	CF + NLP + audio ensemble	Not detailed	Three model families
ByteByteGo video rec (template) [28]	YouTube-style	Two-tower + ANN	Multi-task NN	Template to adapt; no music specifics
Hello Interview pattern [30]	Generic recsys	Multi-source retrieval	Ranker + re-rank	Stage-by-stage delivery
Spotify research [8][9]	Home + sessions	Contextual user embedding (CoSeRNN)	Bandit (BaRT) for cards	Explanations and exploration as first-class
RecSys Challenge 2018 [22][23]	Playlist continuation	MF, item-item, two-tower	Ensembles	R-precision and clicks metrics; public MPD data

References

1. sharayu134, "Notes: Machine Learning system design question types" (system..md), GitHub, 2025 (fetched). https://github.com/sharayu134/Notes/blob/main/Machine%20Lerning/system..md
2. mdrijwan123, "AI Engineering Guide: Recommendation Systems", GitHub, 2025 (fetched). https://github.com/mdrijwan123/AI_enginnering_guide/blob/main/Phase_2_Advanced_Systems_Jul_Sep_year_01/Month_06_September/Recommendation_Systems.md
3. Gaurav14cs17, "ml_system_design: 01 Recommendation Systems", GitHub, 2025 (fetched). https://github.com/Gaurav14cs17/ml_system_design/blob/main/01_recommendation_systems/README.md
4. kevin-2023-code, "Tech-Interview-Questions: Meta" (company question bank listing "Design Spotify"), GitHub, 2025 (fetched). https://github.com/kevin-2023-code/Tech-Interview-Questions/blob/main/companies/meta.md
5. C. Huyen, "Designing Machine Learning Systems: resources.md", GitHub, 2022 (fetched). https://github.com/chiphuyen/dmls-book/blob/main/resources.md
6. S. Ciocca, "Spotify's Discover Weekly: How machine learning finds your new music", HackerNoon, 2017 (known via [5]). https://hackernoon.com/spotifys-discover-weekly-how-machine-learning-finds-your-new-music-19a41ab76efe

7. S. Dieleman, "Recommending Music on Spotify with Deep Learning", benanne.github.io, 2014 (fetched via GitHub source). https://benanne.github.io/2014/08/05/spotify-cnns.html (source: https://github.com/benanne/benanne.github.io/blob/master/_posts/2014-08-05-spotify-cnns.md)
8. J. McInerney et al., "Explore, Exploit, and Explain: Personalizing Explainable Recommendations with Bandits", RecSys, 2018 (known). https://dl.acm.org/doi/10.1145/3240323.3240354
9. C. Hansen et al., "Contextual and Sequential User Embeddings for Large-Scale Music Recommendation", RecSys, 2020 (known). https://dl.acm.org/doi/10.1145/3383313.3412248
10. Spotify Engineering, "For Your Ears Only: Personalizing Spotify Home with Machine Learning", engineering.atspotify.com, 2020 (known). https://engineering.atspotify.com/2020/01/16/for-your-ears-only-personalizing-spotify-home-with-machine-learning/
11. Spotify Engineering, "The Rise (and Lessons Learned) of ML Models to Personalize Content on Home (Part I)", engineering.atspotify.com, 2021 (known). https://engineering.atspotify.com/2021/11/the-rise-and-lessons-learned-of-ml-models-to-personalize-content-on-home-part-i/
12. Spotify Engineering, "The Rise (and Lessons Learned) of ML Models to Personalize Content on Home (Part II)", engineering.atspotify.com, 2021 (known). https://engineering.atspotify.com/2021/11/the-rise-and-lessons-learned-of-ml-models-to-personalize-content-on-home-part-ii/
13. Spotify Engineering, "Reach for the Top: How Spotify Built Shortcuts in Just Six Months", engineering.atspotify.com, 2020 (known). https://engineering.atspotify.com/2020/04/15/reach-for-the-top-how-spotify-built-shortcuts-in-just-six-months/
14. B. Carterette, "Music Recommendation at Spotify" (slides), ACM SIGIR AFIRM, 2019 (known). http://sigir.org/afirm2019/slides/16.%20Friday%20-%20Music%20Recommendation%20at%20Spotify%20-%20Ben%20Carterette.pdf
15. E. Bernhardsson, "How Music Recommendation Works - And Doesn't Work", notes.variogram.com, 2012 (known). https://notes.variogram.com/2012/12/11/how-music-recommendation-works-and-doesnt-work/
16. Spotify Research, "Shifting Consumption towards Diverse Content via Reinforcement Learning", WSDM, 2021 (known). https://research.atspotify.com/shifting-consumption-towards-diverse-content-via-reinforcement-learning/ (paper: https://dl.acm.org/doi/10.1145/3437963.3441775)
17. Arize, "Embeddings at Spotify's Scale - How Hard Could It Be?", arize.com, 2023 (known). https://arize.com/resource/embeddings-at-scale-spotify-recsys/
18. Spotify, "Annoy: Approximate Nearest Neighbors Oh Yeah", GitHub, 2013- (fetched). https://github.com/spotify/annoy
19. Spotify, "Voyager: approximate nearest-neighbor search library (HNSW)", GitHub, 2023 (fetched). https://github.com/spotify/voyager
20. Spotify Engineering, "Spotify's New Experimentation Platform (Part 1)", engineering.atspotify.com, 2020 (known). https://engineering.atspotify.com/2020/10/29/spotifys-new-experimentation-platform-part-1/
21. X. Yi, J. Yang, L. Hong et al., "Sampling-Bias-Corrected Neural Modeling for Large Corpus Item Recommendations", RecSys / Google Research, 2019 (ch-ref). https://research.google/pubs/sampling-bias-corrected-neural-modeling-for-large-corpus-item-recommendations/

22. S. Antenucci, S. Boglio, E. Chioso, T. Scarlatti et al. (Creamy Fireflies, Politecnico di Milano), "Spotify RecSys Challenge 2018 solution" (MPD, automatic playlist continuation, metrics), GitHub, 2018 (fetched). https://github.com/tmscarla/spotify-recsys-challenge
23. J. Wortz, "Building Two Tower Models on Google Cloud from Spotify Data" (MPD two-tower + ANN), GitHub, 2022 (fetched). https://github.com/jswortz/spotify_mpd_two_tower
24. E. Yan, "applied-ml: Papers & tech blogs by companies sharing their work on data science & ML in production", GitHub, 2024 (fetched). https://github.com/eugeneyan/applied-ml
25. Engineer1999, "A Curated List of ML System Design Case Studies", GitHub, 2024 (fetched). https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies
26. Amazon Science, article on Amazon Music recommendation and conversational ML, amazon.science, 2022 (not re-verified; host unreachable in review, title unconfirmed). https://www.amazon.science/latest-news/how-amazon-music-uses-recommendation-system-machine-learning
27. alirezadir, "AIMLInterviews: MLSD video recommendation", GitHub, 2025 (ch-ref). https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/mlsd-video-recom.md
28. A. Aminian & A. Xu, "Machine Learning System Design Interview: Video Recommendation System", ByteByteGo, 2023 (ch-ref). https://bytebytego.com/courses/machine-learning-system-design-interview/video-recommendation-system
29. Educative, "The 6-step ML SD framework" (Grokking the ML System Design Interview), educative.io, 2025 (ch-ref). https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/the-6-step-ml-sd-framework
30. Hello Interview, "ML System Design Patterns: Recommendation Systems", hellointerview.com, 2025 (ch-ref). https://www.hellointerview.com/learn/ml-system-design/patterns/recommendation-systems
31. Aced (formerly Exponent), "Machine Learning System Design Interview (2026 Guide)", aced.io, 2026 (ch-ref). https://www.aced.io/blog/machine-learning-system-design-interview-guide
32. E. Yan, "System Design for Recommendations and Search", eugeneyan.com, 2021 (ch-ref). https://eugeneyan.com/writing/system-design-for-discovery/
33. P. Covington, J. Adams, E. Sargin, "Deep Neural Networks for YouTube Recommendations", RecSys / Google Research, 2016 (ch-ref). https://research.google/pubs/pub45530/
34. C. Huyen, "machine-learning-systems-design" booklet, GitHub, 2019 (fetched; generic, no Spotify content). https://github.com/chiphuyen/machine-learning-systems-design
35. evgenyvinnik, "llm-driven-system-design: Design Spotify" (includes a Discover Weekly endpoint), GitHub, 2025 (fetched). https://github.com/evgenyvinnik/llm-driven-system-design/blob/main/spotify/README.md
36. Spotify Engineering, "Spotify's New Experimentation Platform (Part 2)", engineering.atspotify.com, 2020 (URL confirmed via [24]). https://engineering.atspotify.com/2020/11/02/spotifys-new-experimentation-platform-part-2/
37. Spotify Engineering, "Comparing quantiles at scale in online A/B-testing", engineering.atspotify.com, 2022 (URL confirmed via [24]). https://engineering.atspotify.com/2022/03/comparing-quantiles-at-scale-in-online-a-b-testing

20. Design an ML-Driven Push Notification / Email System (What, When, How Often)

> Prompt as usually given: "We send push notifications and emails to re-engage users. Design an ML system that decides which notification to send, when to send it, and how many to send per user, without driving users to disable notifications or unsubscribe." Variants: "Rank candidate notifications for a social app", "LinkedIn notification volume optimization", "Duolingo practice reminders", "Email digest personalization", "Twitter/X push recommendations".

> Verification note: in this run the X/Twitter pushservice READMEs [6][7][8][9] and the alirezadir template [11] were fetched and checked. Web search was exhausted and most other hosts did not resolve, so papers [1]-[4] and portal pages marked (not re-fetched) rest on well-known publications or on links verified in earlier chapters (ch-ref). Paper entries point to a Google Scholar title search, so no URL is guessed.

Company tags

Company	Basis	Production system it mirrors
LinkedIn	Public notification-optimization papers [1][2] (not re-fetched)	Multi-objective volume optimization of activity notifications; survival model of user response state [1][2]
Pinterest	KDD 2018 paper on volume control [3] (not re-fetched)	Per-user weekly volume as the decision; models of long-term activity vs volume [3]
Duolingo	KDD 2020 bandit paper [4] (not re-fetched)	Picks a practice-reminder template with a "sleeping, recovering" bandit [4]
X / Twitter	Open-source release blog [5]; pushservice code fetched this run [6][7][8][9]	Target eligibility, candidate sources, light filter, light ranker, multi-task heavy ranker (ClemNet), take step, send [7][8][9]

Meta and "generic big tech" tags were removed: no source fetched in this run or in earlier chapters shows notification ranking as a reported interview question there.

Portals that cover it, or cover the building blocks

Portal	What it gives you	Link
ByteByteGo System Design Interview Vol. 1, "Design a Notification System"	Delivery infrastructure (notification servers, per-channel queues, workers, APNs/FCM/SMS/email, retries, templates, settings, rate limits, event tracking). No ML	[12] (not re-fetched)
ByteByteGo ML System Design Interview (feed / event recsys chapters)	The multi-stage ranking template reused here	[13][14] (ch-ref)
Hello Interview, recsys pattern	Retrieval -> ranking -> re-ranking pattern	[15] (ch-ref)

Portal	What it gives you	Link
alirezadir ML-Interviews	9-step MLSD formula (problem, metrics, architecture, data, features, model, serving, online testing, scaling/monitoring). No notification question in its list	[11] (fetched)
Chip Huyen, "Designing ML Systems"	Feedback loops, delayed labels, continual learning	[16]
Patrick Halina, MLSD guide	Interview delivery framework and metric discussion	[17] (ch-ref)
Exponent ML system design course	Framework and question bank	[10] (ch-ref)

Requirements & scale

Dimension	Value	Source
Functional	For each user and time slot, decide whether to send, which item/template, which channel (push, email, in-app) and when	[1][3][4]
Business goal	Long-term engagement (DAU/sessions) minus the cost of fatigue (disables, unsubscribes, churn)	[1][3]
Notification types	Activity (likes, comments, connections), recommendation (content, people), reminder (streak, practice), digest (email)	[1][4][7]
Two entry points	"Refresh" (should this user get a recommendation push now, pick best of many) vs "send" (a given candidate, e.g. a reply, is checked and delivered)	[7]
Users	100M-1B notifiable users	typical assumption
Candidates	10-100 eligible candidates per user per day; most are dropped	typical assumption
Decision QPS	Batch: ~1B users scored per day. Real-time events: ~50k-200k per second at peak	typical assumption
Latency	Real-time activity push: under 1 s for the decision, seconds end to end. Batch digests: hours	typical
Volume caps	Hard per-user caps (e.g. N per day / per week) plus quiet hours and local time zone	[3] + typical
Non-functional	Respect opt-outs and OS permission; dedupe across devices; privacy (GDPR, CAN-SPAM); idempotent delivery	[12] + typical

---

Diagram 1 - Online serving path

Figure 20.1 - Target eligibility, aggregation, light filtering, two-stage ranking, a volume policy with a take step, then scheduling and delivery. Mirrors X pushservice [7] plus the volume policy of [1][3].




Diagram 2 - Offline training & data pipeline

Figure 20.2 - Labels are joined to send logs by decision id. Open labels close within hours. Disable and churn labels need days, so they use a longer window and a separate head.




Diagram 3 - Model architecture

Figure 20.3 - Multi-task heavy ranker. Shared bottom with one head per outcome. A separate send-time head scores hour-of-week slots. Head outputs are combined into a utility. X's push heavy ranker is likewise multi-task (open and engagement) [8].




Diagram 4 - Real-system variants

Figure 20.4 - Three production patterns: LinkedIn/Pinterest volume optimization, the Duolingo bandit, and the X/Twitter pushservice funnel.



Data & labels

Label	Definition	Window	Notes
Open / click	Notification tapped or email clicked	1-24 h	Main positive. Apple Mail privacy proxy inflates email "opens", so prefer clicks
Engagement after open	Session of at least X sec, or a downstream action (like, reply)	1-24 h	Fights clickbait templates; X's heavy ranker predicts open and engagement [8]
Dismiss	Swiped away without opening	24 h	Weak negative
Disable / unsubscribe	Turned off push for app or type; email unsubscribe or spam report	7 d	Rare, costly; separate head, class weighting
Uninstall / churn	App uninstall, 28-day inactivity	7-28 d	Usually a guardrail metric, not a training label
Time to response	Time until user visits after a send (censored if never)	1-7 d	Survival-style label used for timing [2]
Incremental lift	Activity(sent) minus activity(held out)	1-7 d	Needs randomized holdout; for uplift models [18]

Features

Group	Examples
User	Tenure, DAU/WAU state, push/email open rate 7/28 d, last active ts, time zone, OS, permission state
Fatigue	Sends in last 1/24/168 h, time since last send, consecutive unopened sends, type mix sent recently

Group	Examples
Candidate	Type, actor-to-user affinity (messages, profile views), item age, item popularity, text/template embedding
Timing	Local hour/day, hour-of-week open histogram, currently active in app (then skip push, show in-app)
Channel	Push vs email vs in-app, device count, email domain
Cross	User x type open rate, user x template historical reward (bandit stats)

Model choices

Stage	Baseline	Advanced	Tradeoff
Send / no-send	Fixed caps + rules	Multi-objective utility with per-user threshold from a Lagrangian [1][3]	Better long-term balance; needs reliable P(disable)
Candidate pruning	Heuristic top-N per source	Light ranker (small MLP) before the heavy ranker [9]	Cuts heavy-ranker cost; may drop good candidates
What (heavy ranking)	LR / GBDT on P(open)	Multi-task NN with open, engagement and disable heads (X uses ClemNet [8]; MMoE is a common choice)	More capacity; harder calibration
Final pick	Take top-1	Take step: walk ranked list, apply heavy filters until one passes [7]	Expensive checks only on a few candidates
Template / copy	A/B test of templates	Contextual or sleeping-recovering bandit [4]	Adapts per user; needs exploration traffic
When	Send at a fixed hour	Per-user hour-of-week P(open) head, or survival model of response time [2]; delay queue	Delayed sends can arrive stale for activity
How often	Global cap	Per-user volume k_u by response curve or uplift model [3][18]	Uplift avoids credit for users who would return anyway
Email digest	Top-K by score	Listwise re-rank with diversity, subject-line generation (LLM)	LLM copy needs safety review and cost control

Loss

Head	Loss	Note
P(open), P(engage)	Binary cross-entropy, IPS-weighted by logged propensity	Corrects selection bias: only sent items have labels
P(disable), P(unsub)	Weighted BCE or focal loss	Very rare positives
Send time	Softmax CE over 168 slots, BCE per slot, or survival likelihood [2]	Only sent slots are observed; smooth with priors
Total	sum_k alpha_k * L_k	Tune alphas; MMoE reduces task conflict
Bandit	Reward = return within window; softmax with recency penalty [4]	Online, no gradient training

Offline metrics

Metric	Use
ROC-AUC / PR-AUC per head	Discrimination; PR-AUC for disable head
Log loss + calibration (ECE, reliability plot)	Utility uses raw probabilities, so calibration matters
Light-ranker recall@K of heavy-ranker top-1	Checks pruning does not drop the winner [9]
Opens-vs-sends curve on logs	Simulates volume policy; pick operating point
Off-policy estimate (IPS / doubly robust)	Estimate new policy value before A/B
Sliced metrics	By notification type, tenure, time zone, platform

Online metrics / A-B

Type	Metric
Primary	Sessions or DAU per user; incremental vs holdout [1]
Engagement	Open rate (CTR), click-through to session, time to open
Guardrails	Push disable rate, email unsubscribe and spam-report rate, uninstalls, sends per user
Experiment design	User-level randomization; long test (2-4 weeks) because fatigue builds slowly; long-term holdout group that receives no ML notifications
Pitfall	Higher volume always lifts short-term opens; judge on long-term DAU and disables

Serving & latency budget

Step	Budget (real-time push)	Batch digest
Event ingest + aggregation window	0.1-60 s (wait to batch "5 people liked")	n/a
Target eligibility + light filter + feature fetch	20-30 ms	Bulk read
Light ranker + heavy ranker	20-40 ms for under 100 candidates	Spark / batch inference over all users
Volume policy + take step + scheduling	Under 10 ms	Minutes
Delivery (APNs/FCM/SMTP)	Seconds (third party)	Spread over hours by time zone

Monitoring

Signal	Alert on
Sends per user per day distribution	Spikes (bug sends 50 pushes)
Open rate, disable rate by type	Sudden drops or rises
Prediction drift	Mean predicted P(open) vs observed
Delivery health	APNs/FCM error rate, email bounce, spam-folder rate
Feature freshness	Stale "last active" feature causes pushes to users already in app
Dedupe	Same notification sent twice across devices or channels

Failure modes

Failure	Mitigation
Notification fatigue: short-term opens up, long-term disables up	Disable head, per-user caps, long holdouts
Feedback loop: model only learns from what it sent	Epsilon exploration, propensity logging, IPS
Credit for users who would return anyway	Uplift model and randomized holdout [18]
Stale activity (a like from 3 days ago)	TTL on candidates; urgency-aware scheduler
Clickbait templates	Optimize engagement after open, not open alone
Thundering herd at 9:00 local time	Jitter send times; rate-limit delivery queues
Cold-start users	Priors by cohort; bandit exploration
Privacy / compliance	Respect consent, quiet hours, unsubscribe at once

Interviewer follow-ups

- How do you decide whether to send at all, not just which item to send?
- How do you trade off opens against disables and unsubscribes? How do you pick lambda? [1][3]
- How do you measure the incremental value of a notification vs a user who would return anyway? [18]
- How do you fix selection bias when labels exist only for sent notifications?
- How do you choose send time per user? What happens to time-sensitive activity? [2]
- How do you aggregate many small events into one notification?
- How do you pick among push, email and in-app?
- Why split a light ranker from a heavy ranker, and why run expensive filters only after ranking? [7][9]
- Why are disable labels hard, and how do you handle the long label delay?
- How would you use a bandit to choose the template, and why add a recency penalty? [4]
- Which online metric is primary, and why run the A/B test for weeks?
- How do you stop a bug from sending 50 pushes to one user?
- How do you handle new users with no history?
- Would you generate notification copy with an LLM? What are the risks?
- How do notifications interact with the feed ranker (do not notify about what the user just saw)?

Portal comparison

Source	Framing	Core solution	ML depth
ByteByteGo SDI Vol. 1 [12]	Infra system design	Notification servers, message queues, workers, APNs/FCM/SMTP, retries, opt-out settings, rate limits	None
ByteByteGo MLSDI feed/event chapters [13] [14]	ML recsys	Multi-stage funnel and pointwise ranker; reused here as the "what" component	Ranking
Hello Interview / alirezadir / Exponent [15][11][10]	Framework	Generic retrieval -> rank -> re-rank template and 9-step MLSD formula	Template only

Source	Framing	Core solution	ML depth
Chip Huyen [16]	ML systems	Delayed labels, feedback loops, continual learning, monitoring	Concepts
LinkedIn / Pinterest papers [1][2][3]	Production	Multi-objective volume optimization with constraints; per-user thresholds; survival timing	Deep (optimization)
Duolingo paper [4]	Production	Sleeping, recovering bandit for template choice	Deep (bandits)
X pushservice [6][7][8][9]	Production (open source)	Eligibility, light filter, light ranker, multi-task heavy ranker, take step	Deep (MTL ranking)

References

1. Y. Gao et al. (LinkedIn), "Near Real-time Optimization of Activity-based Notifications", KDD, 2018. Scholar search: https://scholar.google.com/scholar?q=%22Near+Real-time+Optimization+of+Activity-based+Notifications%22 (not re-fetched)
2. Y. Yuan et al. (LinkedIn), "A State Transition Model for Mobile Notifications via Survival Analysis", WSDM, 2019. Scholar search: https://scholar.google.com/scholar?q=%22A+State+Transition+Model+for+Mobile+Notifications+via+Survival+Analysis%22 (not re-fetched)
3. B. Zhao et al. (Pinterest), "Notification Volume Control and Optimization System at Pinterest", KDD, 2018. Scholar search: https://scholar.google.com/scholar?q=%22Notification+Volume+Control+and+Optimization+System+at+Pinterest%22 (not re-fetched)
4. K. P. Yancey & B. Settles (Duolingo), "A Sleeping, Recovering Bandit Algorithm for Optimizing Recurring Notifications", KDD, 2020. https://research.duolingo.com/papers/yancey.kdd20.pdf (host unreachable this run)
5. Twitter Engineering, "Twitter's Recommendation Algorithm", blog.x.com, 2023. https://blog.x.com/engineering/en_us/topics/open-source/2023/twitter-recommendation-algorithm (host unreachable this run)
6. Twitter, "the-algorithm" (README lists pushservice under Recommended Notifications), GitHub, 2023. https://github.com/twitter/the-algorithm (fetched)
7. Twitter, "pushservice" README (RefreshForPushHandler, SendHandler, light filter, take step), GitHub, 2023. https://github.com/twitter/the-algorithm/blob/main/pushservice/README.md (fetched)
8. Twitter, "Notification heavy ranker" (ClemNet, multi-task open and engagement), GitHub, 2023. https://github.com/twitter/the-algorithm/tree/main/pushservice/src/main/python/models/heavy_ranking (fetched)
9. Twitter, "Notification light ranker" (pre-selects candidates to cut heavy-ranking cost), GitHub, 2023. https://github.com/twitter/the-algorithm/tree/main/pushservice/src/main/python/models/light_ranking (fetched)
10. Exponent, "Introduction to the ML System Design Interview" (course), tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
11. alirezadir, "ML System Design" (9-step formula), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (fetched)

12. A. Xu, "Design a Notification System" (System Design Interview Vol. 1, ch. 10), ByteByteGo, 2020. https://bytebytego.com/courses/system-design-interview/design-a-notification-system (host unreachable this run)
13. A. Aminian & A. Xu, "Personalized News Feed" (Machine Learning System Design Interview, ch. 10), ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/personalized-news-feed (ch-ref)
14. A. Aminian & A. Xu, "Event Recommendation System" (Machine Learning System Design Interview, ch. 7), ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/event-recommendation-system (ch-ref)
15. Hello Interview, "Recommendation Systems (ML System Design pattern)", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/patterns/recommendation-systems (ch-ref)
16. C. Huyen, "Designing Machine Learning Systems", O'Reilly, 2022. https://www.oreilly.com/library/view/designing-machine-learning/9781098107956/ (not re-fetched)
17. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2021. http://patrickhalina.com/posts/ml-systems-design-interview-guide/ (ch-ref)
18. P. Gutierrez & J.-Y. Gerardy, "Causal Inference and Uplift Modelling: A Review of the Literature", PMLR 67, 2017. http://proceedings.mlr.press/v67/gutierrez17a.html (host unreachable this run)

21. Design Dynamic Pricing (Uber Surge, Airbnb Smart Pricing, Amazon Pricing)

> Sourcing note: live web fetch and search were unavailable when this chapter was reviewed. Every company post and paper below was checked against the curated GitHub indexes [10][11] (cloned locally), which link to it under the URL given here; [2], [6], [14] and the portal pages [17]-[21] are canonical URLs not re-fetched. Rows marked "typical" are standard interview assumptions, not quoted numbers.

Company tags

Company (reported / mirrored)	Evidence	Ref
Airbnb	Smart Pricing: booking-probability model, then price strategy model, then personalization; KDD paper with custom loss	[1][2]
Uber	Surge multiplier per hexagonal zone; demand forecasting with LSTMs and a forecasting platform	[3][4] [5][6]
Lyft	"Pricing at Lyft" (indexed under Anomaly Detection in [11]); causal forecasting for marketplace levers	[7][8]
Alibaba (Tmall)	Dynamic pricing framed as deep reinforcement learning (MDP over price changes), with field experiments	[13]
Alibaba (second-hand items)	Price suggestion for C2C listings from images + text (cold-start pricing for sellers)	[22]
Amazon	Probabilistic demand forecasting (DeepAR, MQ-RNN/CNN lineage); published work is about supply-chain forecasting, so its use as a pricing input is an interview assumption	[14] [15]
DoorDash	Supply/demand balance via ML forecasts plus levers (pay, promotions)	[16]

Portals that cover the problem:

Portal	Coverage	Ref
khangich/machine-learning-interview (Khang Pham)	Applied-ML index lists Airbnb "Optimal Pricing", Airbnb revenue-forecasting platform and Alibaba DRL pricing as study cases	[10] [23]
eugeneyan/applied-ml	Lists "Pricing at Lyft", Alibaba DRL pricing (Reinforcement Learning section), Alibaba price suggestion, Uber/Lyft/DoorDash/Amazon forecasting posts, Airbnb and DoorDash causal-inference posts	[11]
alirezadir/Machine-Learning-Interviews (MLSD notes)	No pricing chapter; its question list has "Ride matching system" and "Food delivery time approximation" (same marketplace stack)	[9]
chiphuyen/machine-learning-systems-design	Generic 4-step framework (project setup, data pipeline, modeling, serving); no pricing case	[12]

Portal	Coverage	Ref
ByteByteGo (Aminian & Xu)	No pricing chapter in the book; its Airbnb "similar listings" chapter is the closest marketplace case	[18]
Exponent, Educative, IGotAnOffer, Patrick Halina	Generic MLSD frameworks only; no pricing walkthrough confirmed	[17] [19] [20] [21]

Requirements & scale

Dimension	Value	Source
Functional (rides)	Return a price / surge multiplier for a (pickup zone, time) at request time	[3][7]
Functional (stays)	Suggest a nightly price per listing-night for the next ~1 year; host keeps min/max bounds	[1][2]
Functional (e-com)	Recommend price per SKU subject to margin, competitor and MAP constraints	[13] typical
Objective	Maximize revenue / GMV / bookings while balancing supply and demand	[1][3] [13]
Guardrails	Caps, smoothing, fairness, legal (e.g. emergency price caps), price-change frequency	typical
Latency	Rides: price quote under ~100 ms p99 (precomputed per zone); stays: batch daily	typical
Freshness	Rides: zone multiplier refreshed every ~1-2 min; stays: daily batch; e-com: hourly-daily	typical
Scale	Rides: ~1e5 hex zones x city, ~1e4-1e5 quote QPS peak; stays: ~7e6 listings x 365 nights	typical
Explainability	Hosts/drivers need reasons ("high demand", "local events")	[1]
Upfront price	Rides: fare fixed at request time from predicted distance/duration x zone multiplier, so ETA/route error becomes pricing error	typical
Host control	Stays: suggestions are opt-in; host can accept per night or turn on automatic pricing within min/max	[1]

Diagrams

DIAGRAM 1: Online serving - ride quote path plus per-zone surge loop (Uber/Lyft style)




DIAGRAM 2: Offline training and data pipeline with feedback loop




DIAGRAM 3: Model architecture (Airbnb-style 3-stage + rides demand/supply forecaster)





DIAGRAM 4: Variant - e-commerce pricing as reinforcement learning / contextual bandit



Components often missed

Component	Why it matters	Ref
Revenue / booking forecasting platform	Market-level forecasts feed pricing and finance planning; separate from per-listing models	[23]
Causal impact measurement (synthetic control / ML counterfactuals)	Pricing changes cannot always be randomized; estimate effect from observational data	[24]
Variance reduction / heterogeneous effects on flat A/B results	Pricing tests are noisy; heterogeneous-effect models find segment-level lift hidden in a flat average	[25]
Supply levers beside price (driver pay, incentives)	Balance can be restored on the supply side, not only by raising price	[16]
Price anomaly detector	Catches bad multipliers or stale zone state before customers see them	[7] [11]
Image/text price suggestion for new items	Cold start when no booking or sales history exists	[22]

Data & labels

Source	Label / use	Pitfall
Quote log (price shown, context)	Conversion at shown price (booked=1)	Only one price observed per context: no counterfactual
Bookings / trips	Revenue, accepted price	Survivorship: unbooked nights look "too expensive"
Unbooked nights	Upper bound signal for strategy loss [2]	Missing-not-at-random (host blocked, low demand)
Randomized price tests / explore traffic	Unbiased elasticity estimates	Cost of exploration, fairness concerns
Supply (driver GPS, availability calendars)	Supply forecast targets	Supply reacts to price (endogenous)
External (events, weather, holidays, competitor prices)	Exogenous features	Sparse, late-arriving

Features

Group	Examples
Spatial	H3 hex id, neighbour demand, distance to airport/venue [6]
Temporal	hour, DOW, holiday, lead time (days to check-in), seasonality
Real-time marketplace	open requests, idle drivers, ETA, acceptance rate, search volume (last 5-60 min)
Item / listing	beds, location, review score, amenities, historical ADR, occupancy
Market	competitor/comparable prices, market occupancy, price index
User (careful)	price sensitivity segment; often excluded for fairness / legal reasons
Forecasts	predicted demand, supply, quantiles as features to the policy

Model choices

Stage	Baseline	Advanced	Tradeoff
Demand forecast	Seasonal naive, Prophet/ARIMA per	LSTM / DeepAR global models, quantile outputs [3][14]	Global DL handles cold zones and events; harder to debug

Stage	Baseline	Advanced	Tradeoff
	zone		
Price response	Logistic regression on log price	GBDT / DNN with monotonic constraint in price	Monotonicity keeps demand curve sane
Elasticity	Log-log regression per segment	Causal ML (DML, uplift), randomized tests [8]	Confounding: high price coincides with high demand
Price decision	Rule: m = clip(D/S)	Constrained optimization over demand curve; strategy regression [2]	Rules are explainable; optimizers need guardrails
Exploration	Fixed small random price jitter	Contextual bandit / DRL [13]	Bandit regret vs. learning speed; trust

Loss functions

Model	Loss
Booking probability	Binary cross-entropy (+ calibration)
Demand forecast	MSE / MAPE / quantile (pinball) loss for P10-P90
Strategy (Airbnb)	Asymmetric hinge-like loss: booked nights penalize under-pricing, unbooked nights penalize over-pricing [2]
RL policy	Expected discounted revenue/profit; TD loss (DQN) or policy gradient [13]

Offline metrics

Metric	Use
MAPE / WAPE / pinball loss	Forecast quality per zone x horizon
AUC, log loss, calibration	Booking-probability model
Price Decrease Recall (PDR)	Of unbooked nights, share where model suggested a lower price [2]
Booking Regret	How far below booked price the suggestion went (money left on table) [2]
Counterfactual revenue (IPS / DR estimators)	Off-policy value of a new pricing policy
Backtest in simulator	Supply/demand balance, wait times under replayed demand

Online metrics & A/B

Metric	Notes
Revenue / GMV / profit per session	Primary business objective
Conversion (quote -> book), occupancy, ADR	Airbnb host outcomes; host adoption of suggestions [1]
Rider wait time / ETA, fulfilment rate, unfulfilled requests	Rides marketplace health
Driver utilization and earnings	Supply-side health
Long-term retention, complaints, price-shock rate	Guardrail metrics

Metric	Notes
Host adoption of price suggestions	Share of nights where hosts accept / enable suggestions [1]
Experiment design	Marketplace interference: use switchback (city x time slices) or geo-randomization, not user-level A/B

Serving & latency budget (rides, typical)

Step	Budget
Gateway + auth	10 ms
Feature fetch (zone state, forecasts) from Redis	10 ms
Candidate grid + constraints	5 ms
Model scoring (or read precomputed zone multiplier)	20 ms
Policy / smoothing / logging	10 ms
Total p99	~60-100 ms
Batch path (stays / e-com)	Nightly Spark job writes price per listing-night to KV store

Monitoring

Signal	Alert
Price distribution per market	Sudden jumps, multiplier stuck at cap
Forecast error drift	MAPE above threshold per city
Feature freshness	Stream lag > 2 min
Conversion vs. expected	Calibration drift
Price anomalies	Erroneous or stale prices per region; [11] files "Pricing at Lyft" [7] under anomaly detection
Fairness / legal	Prices in protected areas, emergency-state caps

Failure modes

Failure	Mitigation
Feedback loop: price changes demand, model learns its own policy	Exploration traffic, causal estimation, logged propensities
Oscillation (surge on/off, drivers chase zones)	Temporal + spatial smoothing, hysteresis
Extreme events (concerts, storms, emergencies)	Event features, caps, manual overrides [3]
Cold-start listing / new city	Hierarchical / global models, comparable listings
Data leakage (future bookings in features)	Point-in-time joins, time-based split
Adversarial supply (drivers going offline to trigger surge)	Anomaly detection on supply, use forecasts not raw counts
PR / trust damage	Reason codes, caps, transparency to hosts/riders

Interviewer follow-ups

- How do you estimate price elasticity when price is confounded with demand?
- You only observe the outcome at the price you showed; how do you build labels for "optimal price"?
- Why might a custom asymmetric loss beat plain regression on booked prices?
- How do you A/B test pricing in a two-sided marketplace with interference (switchback vs. geo)?
- How do you prevent surge oscillation and drivers gaming zones?
- What granularity for zones and time windows, and why hexagons?
- How do you handle a sudden extreme event or a public emergency (price gouging laws)?
- Forecast-then-optimize vs. end-to-end RL: tradeoffs and safety?
- How do you evaluate a new policy offline before exposing users (IPS, simulators)?
- How do you cold-start pricing for a new listing, new SKU or new city?
- How do you incorporate host/seller preferences and bounds into the model output?
- Would you personalize price per user? Discuss fairness, legal and trust issues.
- How fresh must features be, and what happens if the stream is delayed?
- How would you explain a price to a host or rider?
- When is raising driver pay (supply lever) better than raising rider price?
- How do you measure pricing impact when you cannot randomize (synthetic control, ACE-style counterfactuals)?
- Upfront fares: how do ETA/distance prediction errors propagate into price and who absorbs them?
- E-commerce: how do you avoid price wars or tacit collusion when competitors also run repricing bots?

Portal comparison

Portal	Framing	Core model	Distinctive emphasis
Airbnb engineering [1][2] (cited via Khang Pham index [10])	Suggest listing-night price	Booking prob. -> strategy regression -> personalization	Custom asymmetric loss; PDR and booking regret metrics
Uber engineering [3][4][5]	Zone surge multiplier	Demand forecasting (LSTM) + supply/demand ratio	Extreme events; H3 hex spatial index; forecasting platform
Lyft engineering [7][8]	Ride pricing system	Forecasts + causal models	Causal forecasting of lever effects; post indexed under anomaly detection [11]
Alibaba paper [13] (via eugeneyan index [11])	Tmall SKU pricing as MDP	DQN / DDPG	Reward design (difference of revenue conversion), offline pretraining
Generic MLSD portals (Exponent, Educative, IGotAnOffer, Halina) [17] [19]-[21]; ByteByteGo has no pricing chapter [18]	Apply the generic framework: forecast + business objective	GBDT baseline -> DL	Requirements, metrics, serving, monitoring (no pricing walkthrough confirmed)

References

1. "Learning Market Dynamics for Optimal Pricing", Airbnb Engineering & Data Science (Medium), 2018. https://medium.com/airbnb-engineering/learning-market-dynamics-for-optimal-pricing-97cffbcc53e3
2. Ye, P. et al., "Customized Regression Model for Airbnb Dynamic Pricing", KDD (ACM), 2018. https://dl.acm.org/doi/10.1145/3219819.3219830
3. "Engineering Extreme Event Forecasting at Uber with Recurrent Neural Networks", Uber Engineering Blog, 2017. https://eng.uber.com/neural-networks/
4. "Forecasting at Uber: An Introduction", Uber Engineering Blog, 2018. https://eng.uber.com/forecasting-introduction/
5. "Meet Michelangelo: Uber's Machine Learning Platform", Uber Engineering Blog, 2017. https://eng.uber.com/michelangelo-machine-learning-platform/
6. "H3: Uber's Hexagonal Hierarchical Spatial Index", Uber Engineering Blog, 2018. https://www.uber.com/blog/h3/
7. "Pricing at Lyft", Lyft Engineering Blog, 2022. https://eng.lyft.com/pricing-at-lyft-8a4022065f8b
8. "Causal Forecasting at Lyft (Part 1)", Lyft Engineering Blog, 2022. https://eng.lyft.com/causal-forecasting-at-lyft-part-1-14cca6ff3d6d
9. alirezadir, "Machine-Learning-Interviews" (MLSD notes), GitHub, 2024. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md
10. Khang Pham, "machine-learning-interview" applied ML index, GitHub, 2021. https://github.com/khangich/machine-learning-interview/blob/master/appliedml.md
11. Eugene Yan, "applied-ml" (papers and tech blogs on ML in production), GitHub, 2023. https://github.com/eugeneyan/applied-ml
12. Chip Huyen, "machine-learning-systems-design", GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design
13. Liu, J. et al., "Dynamic Pricing on E-commerce Platform with Deep Reinforcement Learning", arXiv, 2019. https://arxiv.org/abs/1912.02572
14. Salinas, D. et al., "DeepAR: Probabilistic Forecasting with Autoregressive Recurrent Networks", arXiv, 2017. https://arxiv.org/abs/1704.04110
15. "The history of Amazon's forecasting algorithm", Amazon Science, 2021. https://www.amazon.science/latest-news/the-history-of-amazons-forecasting-algorithm
16. "Managing Supply and Demand Balance Through Machine Learning", DoorDash Engineering Blog, 2021. https://doordash.engineering/2021/06/29/managing-supply-and-demand-balance-through-machine-learning/
17. Exponent, "ML System Design" course introduction, tryexponent.com, 2024. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro
18. Ali Aminian & Alex Xu, "Machine Learning System Design Interview", ByteByteGo, 2023. https://bytebytego.com
19. Educative, "Grokking the Machine Learning Interview", educative.io, 2023. https://www.educative.io/courses/grokking-the-machine-learning-interview
20. IGotAnOffer, "Machine learning system design interview guide", igotanoffer.com, 2024. https://igotanoffer.com/en/advice/machine-learning-system-design-interview
21. Patrick Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2021. http://patrickhalina.com/posts/ml-systems-design-interview-guide/

22. Alibaba, "Vision-based Price Suggestion for Online Second-hand Items", arXiv, 2020. https://arxiv.org/abs/2012.06009
23. Jerry Chu, "Airbnb's data platform of revenue forecasting", Medium (listed under Airbnb in [10]). https://medium.com/@jerry.chu/airbnbs-data-platform-of-revenue-forecasting-2e95a01122e6
24. "Artificial Counterfactual Estimation (ACE): Machine Learning-Based Causal Inference at Airbnb", Airbnb Engineering (Medium), 2022. https://medium.com/airbnb-engineering/artificial-counterfactual-estimation-ace-machine-learning-based-causal-inference-at-airbnb-ee32ee4d0512
25. "Leveraging Causal Modeling to Get More Value from Flat Experiment Results", DoorDash Engineering Blog, 2020. https://doordash.engineering/2020/09/18/causal-modeling-to-get-more-value-from-flat-experiment-results/

22. Design Job Recommendation / Candidate Matching (LinkedIn Jobs, Indeed)

> Prompt as usually given: "Design the 'Jobs you may be interested in' module for LinkedIn (or Indeed's home-page job feed). Given a member, recommend job postings they are likely to apply to and be a good fit for." Variants: "Rank candidates for a recruiter" (the reverse direction: talent search / Recruiter), "Job search ranking", "Job alert emails", "Match resumes to job descriptions with LLMs".

> Compilation note: arxiv.org, linkedin.com and the portal sites were blocked by the network proxy in both the writing and review runs, and the web-search budget was used up. All 12 GitHub sources were re-checked in review by cloning them and searching the cited text. Sources marked (fetched) were read this way. Sources marked (ch-ref) were verified in earlier chapters of this atlas. Papers that could not be checked point to a Google Scholar search for the exact title, so no URL is guessed. Figures marked "approx." should be checked against the cited paper.

Company tags

Company	Basis	Production system it mirrors
LinkedIn	Khang Pham names LinkedIn as a source of real questions [17] (fetched); LinkedIn has published its job-recsys stack for nearly a decade [1][2][6][8]	JYMBII ("Jobs You May Be Interested In"): GLMix, then GDMix, then LiRank, then 360Brew [2][3][4][6][8]
LinkedIn (reverse direction)	Recruiter / talent search is LinkedIn's other matching product [14][13]	Recruiter search and recommendations; fairness-aware re-ranking [13][14]

Indeed appears in the title only as a product analogue (a two-sided job marketplace). No source checked here shows Indeed, ZipRecruiter, Glassdoor or the big generic-recsys companies asking this exact prompt, so they get no company tag.

Portal coverage. No major portal checked in this run has a dedicated "job recommendation" chapter. The building blocks come from these:

Portal / source	What it gives you for this problem	Link
ByteByteGo MLSDI (Aminian & Xu)	No jobs chapter [19] (fetched). The Event Recommendation and PYMK chapters are the closest templates	[19]
alirezadir ML-Interviews	No jobs question [16] (fetched). Lists "ride matching" and "friend / follower recommendation" (tagged Facebook, Twitter, LinkedIn) as the closest two-sided problems. Its "ML at Companies" page links LinkedIn Recruiter and two-tower posts [15]	[15][16]
Khang Pham, "Machine	"LinkedIn Feed Ranking" case and LinkedIn named as a question source [17] (fetched)	[17]

Portal / source	What it gives you for this problem	Link
Learning Design Interview"		
Hello Interview recsys pattern	Retrieval -> ranking -> re-ranking pattern	[20] (ch-ref)
shafaypro CrackingMachineLearningInterview	Generic recsys stage latency targets (retrieval ~1000 candidates in < 20 ms; ranking < 50 ms)	[26] (fetched)
Exponent / Educative / IGotAnOffer / Patrick Halina	MLSD framework and recsys question banks	[21][22] [24][23] (ch-ref)
Chip Huyen	Delayed labels, feedback loops, continual learning. No jobs exercise in her booklet [18] (fetched)	[18][25]

Requirements & scale

Dimension	Value	Source
Functional	Given a member (and an optional query or context), return the top-K active jobs. Support "Jobs you may be interested in", job alerts (email/push) and "similar jobs"	[1] + typical
Two-sided goal	Member applies AND the employer is interested (recruiter replies, "hearing back"). Optimize for qualified applications, not clicks	[6][7]
Hard constraints	Job is open, location / remote match, visa, seniority, language. Dedupe reposts. Respect employer targeting	typical assumption
Members	~1B registered, ~100M+ weekly job seekers	typical assumption
Catalog	~10-50M active postings. High churn: new jobs every second, most expire in 30-60 days	typical assumption
QPS	~10k-50k recommendation requests/s at peak, plus batch job-alert generation for ~100M members per day	typical assumption
Latency	p99 ~150-200 ms end to end. Retrieval ~20-30 ms, ranking ~50 ms	typical assumption; [26]
Freshness	New job is retrievable within minutes. Member activity features within seconds to minutes	typical assumption
Fairness / legal	No use of protected attributes. Monitor exposure parity (gender, region). Explainability for "why this job"	[13]
Per-job capacity	Popular jobs saturate (hundreds of applicants). Spread applications across postings	[1]

Diagram 1 - Online serving path

DIAGRAM 1: End-to-end serving for "Jobs you may be interested in" (synthesised from [1][6][10][12][26])




Diagram 2 - Offline training & data pipeline

DIAGRAM 2: Training data, delayed employer labels and the feedback loop (synthesised from [1][2][4][11][25])




Diagram 3 - Model architecture

DIAGRAM 3: Two-tower retrieval + multi-task ranker with mixed-effects personalization (synthesised from [3][4][5][6][7])





Diagram 4 - The real system: LinkedIn's job-recsys lineage and the LLM variant

DIAGRAM 4: How LinkedIn's JYMBII stack evolved, and the 360Brew prompt-as-ranker variant (from [1][2][3][4][6][7][8])



Data & labels

Label	Definition	Notes
View / click	Member opens the job detail page	Abundant, noisy. Title clickbait inflates it
Save	Bookmark	Mid-strength positive
Apply	Clicked apply (on-site "Easy Apply" or offsite redirect)	Primary member-side label. Offsite applies are only partly observed
Qualified apply	Apply that meets the job's requirements, or that the employer rates as a fit	LinkedIn reports this metric [6]
Recruiter reply / "hearing back"	Employer views, messages or advances the applicant	Delayed by days to weeks; sparse [7]
Dismiss / "not interested"	Explicit negative	Strong negative. Also a filter signal
Impressed, no action	Weak negative	Position-biased; downweight or use IPS

Features

Group	Examples
Member	Standardized title and seniority, skills (from the LinkedIn Knowledge Graph taxonomy [32]), industry, location, years of experience, open-to-work preferences (titles, locations, remote)
Member activity	Last N viewed / applied / dismissed jobs (as embeddings), searches, saved alerts, application velocity
Job	Standardized title, required skills, seniority, company, industry, location, remote flag, salary, posting age, #applicants so far, employer response rate
Member x job	Skill overlap (Jaccard, weighted), title similarity (DeText-style text match [5]), seniority gap, distance / commute, has connections at company, past apply to same company
Graph	GNN embeddings of member, job, company and skill nodes (LiGNN [7]). Key for cold-start jobs
Marketplace	Job's current application count vs. its target, applicant quality so far (for exposure capping)

Group	Examples
Context	Surface (feed, email, push), device, hour, position (training only)
Standardization (pre-step)	Map free-text titles, skills, companies and locations to canonical entity ids before any feature is built; both towers and the search index depend on it [32]

Model choices (baseline -> advanced)

Stage	Option	Pros	Cons
Baseline	Content match: skills / title TF-IDF or BM25 + rules	No training data needed. Explainable	Ignores behavior. Poor ranking
Retrieval	Structured search query built from profile (title, skills, location) [12]	Hard constraints become index filters	Low recall on adjacent titles
Retrieval	Two-tower embeddings + ANN [30]	Semantic recall. Handles new jobs via content tower	Loses fine-grained interactions
Retrieval	Learned job-matching retrieval and GNN job embeddings (LinkedIn 2024) [28][29]	Learns from apply / hire outcomes; helps cold-start jobs	Graph and training infra cost
Retrieval	GPU exhaustive / model-based retrieval (LiNR) [10]	Exact top-k with attribute pre-filters	Needs GPU index infrastructure
Ranking	GLMix: global LR + per-member + per-job random effects [2][3]	Strong personalization. Cheap. Interpretable	Linear. Manual crosses
Ranking	GDMix: deep fixed effect + per-entity LR [4]	Deep text matching plus personalization	Two-stage training complexity
Ranking	Multi-task DCN / transformer ranker (LiRank) [6]	Learns crosses and sequences. Multiple objectives	Heavier serving; calibration needed
Re-rank / teacher	LLM ranker (360Brew: 150B decoder on Mixtral 8x22B, 30+ tasks across 8+ surfaces) [8][9]	Zero-shot cold start; reads full text; one model for many tasks	Very costly. Pre-production
Employer preference	Per-job / per-recruiter model of which applicants get hearing-back ("learning hiring preferences") built on the Feathr feature store [11]	Adds the employer side to the value function	Sparse, delayed labels
Employer side	Recruiter / talent search ranker + fairness-aware re-rank [13][14]	Covers the reverse match	Separate system and labels

Loss

Component	Loss
Two-tower retrieval	Sampled / in-batch softmax with log-Q correction for popularity, or contrastive loss on (member, applied job) pairs
Ranker heads	Sum of weighted BCE per task: L = a*BCE(view) + b*BCE(apply) + c*BCE(reply on applied rows)

Component	Loss
Mixed effects	Logistic loss with L2 on each random-effect block, fit by coordinate descent with offsets [2][4]
Bias handling	Inverse propensity weights by position, or a position feature set to a constant at serving
LLM ranker	Next-token cross-entropy on the verbalized answer ("will apply") [8]

Offline metrics

Metric	Use
Recall@K (retrieval)	Share of later-applied jobs found in the top 500-1000 candidates
AUC / log loss per head	Ranker quality per task. LinkedIn and 360Brew report AUC [6][8]
NDCG@K / MAP@K	List quality with graded labels (apply > save > view)
Calibration (ECE, predicted / observed)	Needed because heads are multiplied in the value function
Slice metrics	By country, seniority, new members, new jobs, and for fairness by gender where legally allowed [13]
Coverage / Gini of applies per job	Marketplace health: does the model concentrate applies on a few jobs?

Online metrics / A-B

Type	Metric
Primary (two-sided)	Qualified applications per member [6]; hearing-back / recruiter-reply rate [7]
Member side	Apply rate, saves, sessions with job activity, job-alert email CTR
Employer side	Applicants per job (median, not mean), share of jobs with at least N qualified applicants, recruiter InMail / reply rate
Guardrails	Dismiss rate, unsubscribes from alerts, latency, fairness exposure ratios [13], scam-job reports
Long-term	Confirmed hires (sparse; use as a validation, not as a training target)
Experiment design	Marketplace interference: treatment members compete for the same jobs. Use job-side or market (region) randomization, or ego-cluster designs [31]

Serving & latency budget (~180 ms p99, typical assumption)

Step	Budget	Notes
Feature fetch (member)	10 ms	KV store (Venice-style [27])
Candidate generation (parallel)	25 ms	Search index + ANN + graph + fresh sources
Filtering	5 ms	Bloom filters for applied / hidden; job status cache
L1 light ranker (~1000)	20 ms	GBDT or small DNN on CPU
Job feature fetch (~200)	15 ms	Batched multi-get
L2 heavy ranker (~200)	50 ms	GPU or optimized CPU; quantized [6]

Step	Budget	Notes
Re-rank / policy	10 ms	Exposure caps, diversity, explanations
Network + overhead	45 ms	
Batch path (alerts)	Hours	Precompute top-K for ~100M members nightly, then refresh with fresh jobs

Monitoring

What	Signal
Data	Feature null rates, schema drift, title-standardization failures, embedding drift for new job families
Model	Online vs. offline AUC per head, calibration drift, score distribution shift
Marketplace	Applicant concentration (Gini), jobs with zero impressions, new-job time-to-first-impression
Fairness	Exposure and apply-rate parity across groups; audits of protected attributes leaking through proxies [13]
Business	Qualified applies, reply rate, alert unsubscribes; alarms on sudden drops
Trust	Scam / fraudulent job reports, spammy reposts slipping through filters

Failure modes

Failure	Mitigation
Popular jobs flooded with applicants, so employer reply rate falls	Per-job exposure caps; optimize P(reply given apply); downweight jobs near capacity [1]
Cold-start jobs never shown (no interactions)	Content / GNN job tower, freshness boost, exploration slots
Cold-start members (empty profile)	Use location + title from onboarding, popular-near-you, ask preferences. 360Brew's gain over the production model is largest for members with few interactions, so an LLM ranker or teacher helps here [9]
Delayed recruiter labels make training stale	Train the apply head daily; train the reply head on a lagged window; use survival-style or delayed-feedback correction
Clickbait titles optimize views, not applies	Optimize apply and qualified-apply heads, not view
Bias / discrimination (gender, age proxies)	Drop protected attributes and proxies; fairness-aware re-ranking [13]; audits
Expired or filled jobs still recommended	Real-time job status stream into the filter stage
Feedback loop narrows the member's job types	Exploration, diversity on title / company, "adjacent role" retrieval
Duplicate / scam jobs	Dedup by text hash and embedding; trust and safety classifier before indexing
A/B results biased by marketplace interference	Market-level or job-side randomization

Interviewer follow-ups

- What exactly is a positive label: view, apply, or the recruiter replying? How do you handle a label that arrives two weeks late?
- How do you avoid sending 2,000 applicants to one popular job while other jobs get none?
- A job was posted five minutes ago. How does it get into the candidate set and get a score?
- A new member has an empty profile. What do you recommend on day one?
- How would you put hard constraints (location, visa, remote) into retrieval instead of filtering afterwards?
- Why multi-task instead of one P(apply) model? How do you set the weights in the value function?
- How do you randomize an A/B test when treatment and control members compete for the same jobs?
- How do you make sure the system does not discriminate by gender or age, even through proxies?
- Offsite applies are not observed. How does that bias training, and what do you do about it?
- How do you build the reverse system (rank candidates for a recruiter)? What changes?
- How would you use an LLM here: features, retrieval embeddings, a re-ranker, or a teacher? What is the cost per request?
- How do you generate "why you are seeing this job" explanations?
- What features would leak the label (for example applicant count updated after the impression)?
- How do you serve job-alert emails for 100M members every day?
- How would you detect and remove scam job postings before they reach recommendations?
- Millions of postings use free-text titles ("Rockstar Dev II"). How do you standardize titles and skills so retrieval and features work [32]?
- How do you learn what each employer actually hires for (hiring preferences) and use it in ranking [11]?

Portal comparison

Source	Framing	Core solution	What it misses for jobs
ByteByteGo MLSDI (event recsys, PYMK chapters) [19]	Generic user-to-item recsys	Candidate generation + pointwise LightGBM / DNN ranker; offline and online metrics	No two-sided labels, no exposure capping
alirezadir ML-Interviews [15][16]	6-step template; question list	Points to ride matching and friend recommendation as analogues; links LinkedIn Recruiter and two-tower posts	No worked jobs design
Khang Pham [17]	LinkedIn Feed Ranking case	Same LinkedIn-style ranking with logistic regression to deep models, AUC and engagement metrics	Feed, not jobs; no employer label
Hello Interview / Exponent / Educative [20][21][22]	Recsys pattern and framework	Retrieval -> ranking -> re-ranking, two-tower and multi-task	Marketplace and fairness only briefly

Source	Framing	Core solution	What it misses for jobs
LinkedIn papers and repos [1]-[10]	Production	GLMix to GDMix to LiRank to 360Brew; qualified-apply and hearing-back metrics; per-job capacity	Interview-level time limits (too deep for 45 min)
Chip Huyen [18][25]	ML systems concepts	Delayed labels, feedback loops, continual learning	No jobs case

References

1. K. Kenthapadi, B. Le, G. Venkataraman (LinkedIn), "Personalized Job Recommendation System at LinkedIn: Practical Challenges and Lessons Learned", RecSys, 2017. Scholar search: https://scholar.google.com/scholar?q=%22Personalized+Job+Recommendation+System+at+LinkedIn%3A+Practical+Challenges+and+Lessons+Learned%22 (known; not fetched)
2. LinkedIn, "Photon ML" repository README (GLMix adopted by "jobs search and recommendation"), GitHub, 2016-2020. https://github.com/linkedin/photon-ml (fetched)
3. X. Zhang, Y. Zhou, Y. Ma, B.-C. Chen, L. Zhang, D. Agarwal (LinkedIn), "GLMix: Generalized Linear Mixed Models For Large-Scale Response Prediction", KDD, 2016. http://www.kdd.org/kdd2016/papers/files/adf0562-zhangA.pdf (ch-ref)
4. LinkedIn, "GDMix: Generalized Deep Mixed Model" repository README (job recommendation example), GitHub, 2020. https://github.com/linkedin/gdmix (fetched)
5. LinkedIn, "DeText: A Deep Neural Text Understanding Framework for Ranking and Classification Tasks", GitHub, 2020. https://github.com/linkedin/detext (fetched)
6. F. Borisyuk et al. (LinkedIn), "LiRank: Industrial Large Scale Ranking Models at LinkedIn", KDD / arXiv, 2024. https://arxiv.org/abs/2402.06859 (ch-ref)
7. F. Borisyuk et al. (LinkedIn), "LiGNN: Graph Neural Networks at LinkedIn", KDD / arXiv, 2024. https://arxiv.org/abs/2402.11139 (ch-ref)
8. 360Brew Team (LinkedIn), "360Brew: A Decoder-only Foundation Model for Personalized Ranking and Recommendation", arXiv, 2025. https://arxiv.org/abs/2501.16450 (ch-ref)
9. LLMPersonalization (LinkedIn), "360Brew-V1" repository and report, GitHub, 2025. https://github.com/LLMPersonalization/360Brew-V1 (fetched: README and 360brew_v1.pdf, which state 150B parameters, Mixtral 8x22 base, 30+ tasks, pre-production)
10. F. Borisyuk et al. (LinkedIn), "LiNR: Model Based Neural Retrieval on GPUs at LinkedIn", arXiv, 2024. https://arxiv.org/pdf/2407.13218 (ch-ref)
11. Feathr project (LinkedIn), talk slides incl. "Learning Hiring Preferences: The AI Behind LinkedIn Jobs" use case, GitHub, 2022. https://github.com/feathr-ai/feathr/tree/main/docs/talks (fetched: both talk PDFs list this use case)
12. LinkedIn Engineering, "Did you mean 'Galene'?", LinkedIn Engineering Blog, 2014. https://engineering.linkedin.com/blog/2014/03/did-you-mean-galene (ch-ref)
13. S. C. Geyik, S. Ambler, K. Kenthapadi (LinkedIn), "Fairness-Aware Ranking in Search and Recommendation Systems with Application to LinkedIn Talent Search", KDD / arXiv, 2019. https://arxiv.org/abs/1905.01989 (ch-ref)

14. LinkedIn Engineering, "The AI Behind LinkedIn Recruiter search and recommendation systems", LinkedIn Engineering Blog, 2019. https://engineering.linkedin.com/blog/2019/04/ai-behind-linkedin-recruiter-search-and-recommendation-systems (URL from [15]; not fetched)
15. alirezadir, "ML at Companies" (LinkedIn section), AIMLInterviews, GitHub, 2025. https://github.com/alirezadir/AIMLInterviews/blob/main/src/MLSD/ml-companies.md (fetched)
16. alirezadir, "ML System Design" (sample questions; no jobs question), Machine-Learning-Interviews, GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (fetched)
17. K. Pham, "machine-learning-interview" (LinkedIn Feed Ranking case; LinkedIn named as question source), GitHub, 2021. https://github.com/khangich/machine-learning-interview (fetched)
18. C. Huyen, "Machine Learning Systems Design: Exercises" (checked: no jobs exercise), GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md (fetched)
19. ByteByteGo, "ml-bytebytego: Reference materials for ML System Design Interview" (chapter list; no jobs chapter), GitHub, 2023. https://github.com/ByteByteGoHq/ml-bytebytego (fetched)
20. Hello Interview, "Recommendation Systems (ML System Design pattern)", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/patterns/recommendation-systems (ch-ref)
21. Exponent, "Introduction to the ML System Design Interview" (course), tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
22. Educative, "Grokking the Machine Learning Interview", educative.io, n.d. https://www.educative.io/courses/grokking-the-machine-learning-interview (ch-ref)
23. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2021. http://patrickhalina.com/posts/ml-systems-design-interview-guide/ (ch-ref)
24. IGotAnOffer, "Machine Learning System Design Interview", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/machine-learning-system-design-interview (ch-ref)
25. C. Huyen, "Designing Machine Learning Systems", O'Reilly, 2022. https://www.oreilly.com/library/view/designing-machine-learning/9781098107956/ (ch-ref)
26. shafaypro, "Recommendation System" (system_design/recommendation_system.md; stage latency targets), CrackingMachineLearningInterview, GitHub, n.d. https://github.com/shafaypro/CrackingMachineLearningInterview/blob/master/system_design/recommendation_system.md (fetched)
27. LinkedIn, "Venice: Derived Data Platform for Planet-Scale Workloads", GitHub, 2022-2026. https://github.com/linkedin/venice (repo existence checked in review)
28. LinkedIn, "LinkSAGE: Optimizing Job Matching Using Graph Neural Networks", 2024. Scholar search: https://scholar.google.com/scholar?q=%22LinkSAGE%3A+Optimizing+Job+Matching+Using+Graph+Neural+Networks%22 (known; not fetched)
29. LinkedIn, "Learning to Retrieve for Job Matching", KDD, 2024. Scholar search: https://scholar.google.com/scholar?q=%22Learning+to+Retrieve+for+Job+Matching%22 (known; not fetched)
30. G. Chakravorty, "Personalized Recommendations IV: Two Tower Models for Retrieval", LinkedIn Pulse, n.d. https://www.linkedin.com/pulse/personalized-recommendations-iv-two-tower-models-gaurav-chakravorty/ (URL from [15]; not fetched)

31. G. Saint-Jacques et al. (LinkedIn), "Using Ego-Clusters to Measure Network Effects at LinkedIn", arXiv, 2019. https://arxiv.org/abs/1903.08755 (ch-ref)
32. LinkedIn Engineering, "Building The LinkedIn Knowledge Graph", LinkedIn Engineering Blog, 2016. https://engineering.linkedin.com/blog/2016/10/building-the-linkedin-knowledge-graph (URL from [15]; not fetched)

23. Design Restaurant / Food Recommendations and Store Ranking (DoorDash, Uber Eats)

> Prompt as usually given: "Design the home feed for a food-delivery app. Given a user who opens the app at a location and time, rank the restaurants (stores) and dishes to show." Variants: rank stores in a cuisine filter, "dishes you may like" carousel, ranking after a search query, a carousel-of-carousels homepage, cold start for new users or new stores, and grocery item substitutions.
>
> Sourcing note: in both the compile and review passes, web search was used up and only GitHub-hosted pages could be read (uber.com, doordash.engineering and arxiv.org were blocked). In review, every (list) title, year and URL was re-checked against [10][11]; [15][16][17] were re-read. Labels used below: (fetched) means the page was read for this chapter. (list) means the exact title, year and URL were taken from a fetched curated list ([10][11]); those posts could not be opened, so the details given for them are the author's summary of the published system. (ch-ref) means the source was already verified in an earlier chapter. (known) means a canonical paper cited by its arXiv ID or DOI. No portal page that reports this exact question at a named company could be opened, so treat the company tags as indicative.

Company tags

Company	What is reported / why it is tagged	Source
DoorDash	Publishes the matching production system: store feed with embeddings, homepage explore/exploit, cuisine filter. Khang Pham's "Food delivery" list links the store-feed post	[4][5][6] [15]
Uber (Uber Eats)	Publishes the "Food Discovery with Uber Eats" series: marketplace recs, query understanding, graph learning. Khang Pham links the query-understanding and trip-optimization posts	[1][2][3] [15][41]
Instacart (and DoorDash grocery)	AIMLInterviews lists "Replacement product recommendation" (Instacart) as a question. Contextual-bandit and substitution posts	[16][30] [32]
Swiggy, Delivery Hero, Grubhub	Publish restaurant learning-to-rank, dish-search ranking, cold-start ranking and query embeddings. Not confirmed as interview prompts	[12][13] [14][31] [39]
Zomato, Deliveroo, Grab, Meituan	Not tagged: same marketplace pattern, but no interview report or ranking post found in [10][11]	none

Portals that cover it

Portal	Coverage	Link
Khang Pham (khangich, Educative "ML System Design")	"Food delivery" reading list: Uber Eats query understanding, DoorDash personalized store feed, dispatch	[15]
alirezadir AIMLInterviews	9-step MLSD formula. Food-related prompts are "Food delivery time approximation" and Instacart "Replacement product recommendation"; the recsys template is reused	[16]
ByteByteGo (Aminian & Xu)	No food chapter. Closest: "Event Recommendation" (location-aware, LTR) and "Video Recommendation" (multi-stage)	[18] [19] [20]
Educative "Grokking the ML Interview"	Recsys module (candidate gen, then ranker). Same funnel	[21]
Hello Interview	Recommendation-systems pattern (retrieve, rank, re-rank)	[22]
Exponent	MLSD course. Framework applies	[23]
Chip Huyen exercises	No food prompt (re-checked). Ex. 3 (replacement items) is the closest	[17]
Curated lists (eugeneyan applied-ml, Engineer1999)	Index the DoorDash, Uber Eats, Swiggy and Delivery Hero posts used here	[10] [11]

Requirements & scale

Dimension	Value	Source
Surfaces	Home feed (vertical store list plus horizontal carousels), cuisine filter, dish carousel, post-search ranking	[5][6][1] [7]
Functional	Return about 50-200 ranked stores, all open and deliverable to the address. Group them into carousels. Show an ETA and fee on each	assumption
Hard constraints	Delivery radius, store open now, the store's kitchen not overloaded, ETA under a cap	[2]
Objectives	Conversion (order), GMV, retention. Marketplace balance across eaters, merchants and couriers. Exposure for new stores	[2][5]
Users	10^7-10^8 monthly active. Many low-frequency users. New users need cold-start ranking	assumption, [13]
Catalog	10^5-10^6 stores in total, but only about 10^2-10^4 are eligible at one location	assumption
QPS	10^4-10^5 feed requests/s at the lunch and dinner peaks (sharp time-of-day spikes)	assumption
Latency	Under 200 ms p99 for the feed. Ranking under 50 ms	assumption
Freshness	Store open/busy status and ETA in real time (seconds). Embeddings daily	assumption
Key difference from e-commerce recs	Retrieval is geo-filtering, not ANN over the whole catalog. Supply-side state (prep time, couriers) changes the ranking	[2][5]

Diagram 1: End-to-end architecture (online serving path)

Figure 23.1: Online serving path. Geo-eligibility retrieval, then real-time filters, a multi-task ranker and a marketplace-aware re-ranker that builds the carousel

layout. Event stream and online store follow DoorDash's Kafka/Flink and Redis posts [33][34][35].




Diagram 2: Offline training & data pipeline

Figure 23.2: Offline pipeline. Impression logs are joined with orders and delivery outcomes to build labels. Graph/session embeddings and the ranker are retrained daily.




Diagram 3: Model architecture (multi-task store ranker with graph embeddings)

Figure 23.3: Ranker. Graph-learned user and store embeddings (Uber Eats) and session-based store2vec similarity (DoorDash) feed a shared-bottom multi-task network.





Diagram 4: Real systems (Uber Eats graph learning, DoorDash explore/exploit)

Figure 23.4: Two published patterns. Left: Uber Eats bipartite graph to GraphSAGE embeddings to a ranking feature [1]. Right: DoorDash homepage with a UCB-style exploration bonus on top of the predicted conversion [5]. Both posts were unreachable in review; the formula and reported lifts are the author's summary.



Data & labels

Signal	Label use	Notes
Impression to click (store page view)	Positive for the CTR head	Heavy position bias. Log position and carousel
Click to order	Positive for the CVR head (main business label)	Sparse. Attribution window, e.g. 24 h
Order value (GMV), basket size	Regression or weight	Business objective [2]
Reorder within 30 days, rating	Long-term satisfaction	Delayed labels
Late delivery, cancel, refund, low rating	Negative or "bad experience" head	Penalizes slow or overloaded stores [2]
Store page view without order	Weak negative	Possibly closed or high fee
Unseen stores	Not negative	Use exploration traffic and propensities [5]

Features

Group	Examples	Freshness
User	Order history (stores, cuisines, dishes), price sensitivity, dietary tags, user embedding [1][4]	Daily plus session
Context	Time of day, weekday, meal slot, weather, location H3 cell [28], device, active filter [6]	Request
Store static	Cuisine, price band, rating, menu embedding, photos [8], age (new store)	Daily
Store real-time	Open/closed, quoted ETA [29], prep-time load, courier supply, fee, promo	Seconds
Cross	cos(user, store) from store2vec [4] or GNN [1], prior orders at store, cuisine affinity x store cuisine [6]	Request
Locality	Store popularity in the cell, local cuisine popularity [6]	Hourly
Dish / menu tags	Cuisine, dish type, dietary tags on menu items (human-in-the-loop tagging for cold start) [40]	Daily
Streaming aggregates	Store orders and views in last N minutes, user session clicks; Kafka + Flink jobs written to a Redis online store [33][34][35]	Seconds

Model choices (baseline -> advanced)

Stage	Option	Tradeoff
Baseline	Popularity in area x distance, sorted by ETA	No personalization, but a strong cold-start fallback [13]
Embeddings v1	store2vec: word2vec over session store sequences. User = mean of ordered-store vectors [4][25]	Cheap. Ignores graph structure
Embeddings v2	GraphSAGE on user-dish/store bipartite graph [1][24]	Inductive (new dishes), costly to train
Ranker v1	Logistic regression / GBDT pointwise on pCVR	Fast and interpretable
Ranker v2	LambdaMART / pairwise LTR (Swiggy-style) [12]	Optimizes the list. Single objective
Ranker v3	Multi-task DNN / MMoE (CTR, CVR, GMV, bad-exp) [26]	Handles multiple objectives. Needs weight tuning
Policy	Value model with marketplace terms + UCB/Thompson exploration [2][5][30]	Fairness to new stores vs short-term CVR

Stage	Option	Tradeoff
Cold-start users	Context-only model (location, time, device), popular-in-cell [13]	No history required

Loss functions

Component	Loss
GNN embeddings	Max-margin (hinge) ranking loss with hard negatives [1]
store2vec	Skip-gram with negative sampling [4][25]
CTR / CVR / bad-exp heads	Binary cross-entropy (CVR trained on clicked rows or ESMM-style over impressions)
GMV head	MSE or Huber on log(GMV)
LTR variant	LambdaRank / pairwise logistic [12]
Total	Weighted sum of the head losses. Weights tuned against online metrics

Offline metrics

Metric	Why
AUC per head (CTR, CVR)	Pointwise quality [1]
NDCG@k, MRR on ordered store	List quality for the feed
Recall@k of candidate generation	The ordered store must survive retrieval
Calibration (predicted / observed)	Needed because scores are combined with GMV and ETA
Slice metrics	New users, new stores, city, meal slot
Coverage / diversity	Share of stores and cuisines exposed

Online metrics / A-B

Metric	Type
Conversion rate (sessions with an order), orders per user	Primary
GMV per session, take rate	Business
CTR on feed and carousels	Engagement (guardrail against clickbait)
7/28-day retention, reorder rate	Long-term
Delivery time, lateness, cancel rate	Marketplace guardrail [2]
Merchant exposure Gini, new-store first-order rate	Supply-side fairness [5]
Experiment design	Geo or time-sliced switchback when supply interference matters. Otherwise user-level A-B. Use CUPAC (model predictions as covariate) to cut variance [37] [38]

Serving & latency budget (assumption, p99)

Step	Budget
Context + geo candidate lookup (H3 index)	15 ms
Real-time filters (open, ETA service, busy)	20 ms
Feature fetch (online store, batched)	25 ms
Ranker inference (about 500 stores, batched GPU/CPU)	40 ms
Re-rank, exploration, carousel assembly, ads	20 ms
Network and serialization overhead	30 ms
Total	about 150 ms (under 200 ms SLA)
Caching	Per-cell popular lists and per-user embeddings cached. Fall back to the cached feed when the ranker times out

Monitoring

What	Signal
Feature drift	ETA and prep-load distributions, missing store-state features
Prediction drift	Mean pCVR by city and meal slot vs observed
Business	Conversion, GMV, cancel rate dashboards by market
Supply health	Busy-store exposure, late-delivery rate of top-ranked stores
Freshness	Embedding job lag, online/offline feature skew (platform: Michelangelo-style [27])
Exploration	Share of explore impressions, new-store conversion
Model accuracy	Logged predictions vs outcomes per model, alert on drift (DoorDash monitoring post) [36]

Failure modes

Failure	Mitigation
Recommending closed, overloaded or out-of-radius stores	Hard real-time filters and a busy penalty [2]
Rich-get-richer (popular stores dominate)	UCB exploration bonus, new-store boosts [5]
Position bias in labels	Log position, position feature at train time and constant at serve time, or IPS
Cold-start user	Context-only model, popular-in-cell, onboarding cuisine picks [13]
Cold-start store	Content/menu embedding, inductive GNN, explore slots [1]
Meal-time shift (breakfast vs dinner)	Time features, per-meal-slot models or slices [6]
Feedback loop on ETA (rank fast stores, they get overloaded)	Include live load, cap exposure per store
Promotions distort labels	Promo flag feature. Separate ads auction slots

Interviewer follow-ups

- How is retrieval different here from YouTube-scale ANN? (Answer: geo-eligibility shrinks the set to about 10^3.)
- How do you combine pCTR, pCVR, GMV and ETA into one score, and how do you set the weights?
- How do you handle a store that is popular but currently backed up in the kitchen?
- Cold start for a new user with no orders, and for a newly onboarded restaurant?
- How would you add exploration without hurting conversion? UCB vs Thompson sampling? [5][30]
- How do you learn store embeddings? Session word2vec vs graph neural network, and why? [1][4]
- How do you rank dishes vs stores, and how do you build carousels (row selection plus in-row ranking)?
- What labels do you use? Click, order, reorder? Which attribution window?
- How do you correct for position bias in a two-dimensional carousel layout?
- How do you A-B test when treatments compete for shared courier supply (switchback, geo experiments)?
- How do sponsored listings (ads) blend with organic ranking?
- How does ranking change for a search query vs the browse feed? [3][9]
- How would you ensure fairness or exposure for small merchants?
- What do you monitor at the dinner peak, and what is the fallback if the ranker times out?
- How would you personalize the cuisine filter order itself? [6]
- How do you rank dishes inside a store or in dish search (query-dish relevance)? [39]
- How do you compute "orders in the last 15 minutes" features and keep online/offline values consistent? [34][35]
- How do you reach significance on small marketplace experiments (variance reduction, CUPAC)? [37]

Portal comparison

Source	Framing	Retrieval	Ranker	Distinctive emphasis
Uber Eats blog [1][2]	Marketplace recs for eaters, merchants and couriers	Geo + graph embeddings	Personalized ranker with GNN similarity features	Multi-objective marketplace, GraphSAGE
DoorDash blog [4][5][6]	Home feed, carousels, cuisine filter	Geo + store2vec / knowledge-graph candidates	pCVR ranker + UCB exploration	Explore/exploit, local popularity
Khang Pham [15]	Food-delivery reading list	Points to DoorDash / Uber Eats posts	(Reading-based)	Real-system case studies
ByteByteGo [18][19]	Event recs (location-aware), video recs	Multi-source + ANN	Pointwise LTR / multi-task DNN	Location and time features; funnel design
alirezadir AIMLInterviews [16]	Generic recsys template	CF, two-tower	Pointwise / pairwise / listwise LTR	9-step formula; food prompts are ETA and substitutions
Swiggy / Delivery Hero	Restaurant LTR, new-user ranking	Geo-eligible list	LTR / cold-start model	Cold start and dish search

Source	Framing	Retrieval	Ranker	Distinctive emphasis
[12][13][39]				

References

1. Uber Engineering, "Food Discovery with Uber Eats: Using Graph Learning to Power Recommendations", eng.uber.com, 2019. https://eng.uber.com/uber-eats-graph-learning/ (list; host unreachable)
2. Uber Engineering, "Food Discovery with Uber Eats: Recommending for the Marketplace", eng.uber.com, 2018. https://eng.uber.com/uber-eats-recommending-marketplace/ (list)
3. Uber Engineering, "Food Discovery with Uber Eats: Building a Query Understanding Engine", eng.uber.com, 2018. https://eng.uber.com/uber-eats-query-understanding/ (list, ch-ref)
4. DoorDash Engineering, "Personalized Store Feed with Vector Embeddings", doordash.engineering, 2018. https://doordash.engineering/2018/04/02/personalized-store-feed-with-vector-embeddings/ (list; [15] links an older copy at blog.doordash.com)
5. DoorDash Engineering, "Homepage Recommendation with Exploitation and Exploration", doordash.engineering, 2022. https://doordash.engineering/2022/10/05/homepage-recommendation-with-exploitation-and-exploration/ (list)
6. DoorDash Engineering, "Personalized Cuisine Filter Based on Customer Preference and Local Popularity", doordash.engineering, 2020. https://doordash.engineering/2020/01/27/personalized-cuisine-filter/ (list)
7. DoorDash Engineering, "Powering Search & Recommendations at DoorDash", doordash.engineering, 2017. https://doordash.engineering/2017/07/06/powering-search-recommendations-at-doordash/ (list)
8. DoorDash Engineering, "Selecting the Best Image for Each Merchant Using Exploration and Machine Learning", doordash.engineering, 2023. https://doordash.engineering/2023/01/04/selecting-the-best-image-for-each-merchant-using-exploration-and-machine-learning/ (list)
9. DoorDash Engineering, "Things Not Strings: Understanding Search Intent with Better Recall", doordash.engineering, 2020. https://doordash.engineering/2020/12/15/understanding-search-intent-with-better-recall/ (list)
10. E. Yan, "applied-ml" (curated list), GitHub, 2024. https://github.com/eugeneyan/applied-ml (fetched)
11. Engineer1999, "A Curated List of ML System Design Case Studies", GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies (fetched)
12. Swiggy Bytes, "Learning To Rank Restaurants", bytes.swiggy.com, 2021. https://bytes.swiggy.com/learning-to-rank-restaurants-c6a69ba4b330 (list)
13. Delivery Hero Tech, "Personalisation @ Delivery Hero: Ranking restaurants for new users", tech.deliveryhero.com, 2023. https://tech.deliveryhero.com/personalisation-delivery-hero-ranking-restaurants-for-new-users/ (list)
14. Delivery Hero Tech, "Personalisation @ Delivery Hero: Understanding Customers", tech.deliveryhero.com, 2023. https://tech.deliveryhero.com/personalisation-at-delivery-hero-understanding-customers/ (list)

15. K. Pham, "machine-learning-interview" (Food delivery section), GitHub, 2021. https://github.com/khangich/machine-learning-interview (fetched)
16. alirezadir, "ML System Design" (9-step formula; question list), AIMLInterviews, GitHub, 2025. https://github.com/alirezadir/AIMLInterviews/blob/main/src/MLSD/ml-system-design.md (fetched)
17. C. Huyen, "Machine Learning Systems Design: Exercises", GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md (fetched)
18. A. Aminian & A. Xu, "Video Recommendation System" (Machine Learning System Design Interview), ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/video-recommendation-system (ch-ref)
19. A. Aminian & A. Xu, "Event Recommendation System" (Machine Learning System Design Interview), ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/event-recommendation-system (ch-ref)
20. A. Aminian & A. Xu, "Similar Listings on Vacation Rental Platforms", ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/similar-listings-on-vacation-rental-platforms (ch-ref)
21. Educative, "Grokking the Machine Learning Interview", educative.io, n.d. https://www.educative.io/courses/grokking-the-machine-learning-interview (ch-ref)
22. Hello Interview, "Recommendation Systems (ML System Design pattern)", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/patterns/recommendation-systems (ch-ref)
23. Exponent, "Introduction to the ML System Design Interview", tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
24. W. Hamilton, R. Ying, J. Leskovec, "Inductive Representation Learning on Large Graphs (GraphSAGE)", arXiv, 2017. https://arxiv.org/abs/1706.02216 (known)
25. T. Mikolov et al., "Efficient Estimation of Word Representations in Vector Space", arXiv, 2013. https://arxiv.org/abs/1301.3781 (known)
26. J. Ma et al., "Modeling Task Relationships in Multi-task Learning with Multi-gate Mixture-of-Experts", KDD, 2018. https://doi.org/10.1145/3219819.3220007 (ch-ref)
27. Uber Engineering, "Meet Michelangelo: Uber's Machine Learning Platform", uber.com, 2017. https://www.uber.com/en-DE/blog/michelangelo-machine-learning-platform/ (ch-ref)
28. Uber Engineering, "H3: Uber's Hexagonal Hierarchical Spatial Index", uber.com, 2018. https://www.uber.com/blog/h3/ (ch-ref)
29. DoorDash Engineering, "Improving ETAs with multi-task models, deep learning, and probabilistic forecasts", careersatdoordash.com, 2024. https://careersatdoordash.com/blog/improving-etas-with-multi-task-models-deep-learning-and-probabilistic-forecasts/ (ch-ref)
30. Instacart Tech, "Using Contextual Bandit models in large action spaces at Instacart", tech.instacart.com, 2023. https://tech.instacart.com/using-contextual-bandit-models-in-large-action-spaces-at-instacart-cb7ab4d8fa4f (list)
31. Grubhub Bytes, "Query2vec: Search query expansion with query embeddings", bytes.grubhub.com, 2019. https://bytes.grubhub.com/search-query-embeddings-using-query2vec-f5931df27d79 (list)
32. DoorDash Engineering, "Evolving DoorDash's Substitution Recommendations Algorithm", doordash.engineering, 2022. https://doordash.engineering/2022/09/08/evolving-doordashs-substitution-recommendations-algorithm/ (list)

33. DoorDash Engineering, "Building a Scalable ML Feature Store with Redis, Binary Serialization, and Compression", doordash.engineering, 2020. https://doordash.engineering/2020/11/19/building-a-gigascale-ml-feature-store-with-redis/ (list)
34. DoorDash Engineering, "Building Riviera: A Declarative Real-Time Feature Engineering Framework", doordash.engineering, 2021. https://doordash.engineering/2021/03/04/building-a-declarative-real-time-feature-engineering-framework/ (list)
35. DoorDash Engineering, "Building Scalable Real Time Event Processing with Kafka and Flink", doordash.engineering, 2022. https://doordash.engineering/2022/08/02/building-scalable-real-time-event-processing-with-kafka-and-flink/ (list)
36. DoorDash Engineering, "Maintaining Machine Learning Model Accuracy Through Monitoring", doordash.engineering, 2021. https://doordash.engineering/2021/05/20/monitor-machine-learning-model-drift/ (list)
37. DoorDash Engineering, "Improving Experimental Power through Control Using Predictions as Covariate", doordash.engineering, 2020. https://doordash.engineering/2020/06/08/improving-experimental-power-through-control-using-predictions-as-covariate-cupac/ (list)
38. DoorDash Engineering, "Meet Dash-AB: The Statistics Engine of Experimentation at DoorDash", doordash.engineering, 2022. https://doordash.engineering/2022/05/24/meet-dash-ab-the-statistics-engine-of-experimentation-at-doordash/ (list)
39. Swiggy Bytes, "Using Deep Learning for Ranking in Dish Search", bytes.swiggy.com, 2021. https://bytes.swiggy.com/using-deep-learning-for-ranking-in-dish-search-4df2772dddce (list)
40. DoorDash Engineering, "Using a Human-in-the-Loop to Overcome the Cold Start Problem in Menu Item Tagging", doordash.engineering, 2020. https://doordash.engineering/2020/08/28/overcome-the-cold-start-problem-in-menu-item-tagging/ (list)
41. Uber Engineering, "How Trip Inferences and Machine Learning Optimize Delivery Times on Uber Eats", eng.uber.com, 2018. https://eng.uber.com/uber-eats-trip-optimization/ (list)

24. Design an LLM-Powered Enterprise Q&A / RAG Assistant (Chat over Company Documents)

> How the prompt is usually worded: "Design an assistant that lets employees ask natural-language questions over internal documents (wiki, Google Drive, Confluence, Slack, tickets, PDFs) and get grounded answers with citations. Users must only see what they are allowed to see." Variants: "Chat with your docs / ChatPDF", "LLM customer-support bot over a help center", "Enterprise search with LLM answers", "On-call copilot over runbooks", "Agentic RAG".

> Verification note (review pass): the shared web-search budget was used up, and only github.com and anthropic.com resolved. uber.com, linkedin.com, arxiv.org, huyenchip.com, github.blog, pinecone.io and igotanoffer.com did not. Tags used below:
>
> - (fetched): opened and checked in this run.
> - (repo-link): the exact URL was found in a GitHub list fetched in this run ([3], [11] or [21]). The page itself could not be opened.
> - (ch-ref): verified in ch. 01 of this atlas.
> - (not verified): neither opened nor found in a fetched list.
>
> Figures marked "approx." come from memory of the cited post and should be checked against it.

Company tags

Company / context	Basis	Production system it mirrors
Any company with a "GenAI / LLM system design" round	alirezadir lists "Enterprise search or RAG assistant" as **Tier 1: Almost always** in 2026 GenAI rounds [2] (fetched). The ML-SD template lists "RAG document Q&A / chat with your docs" and "Enterprise / semantic search with LLM answers" [1] (fetched)	Generic retrieve -> rerank -> ground -> generate
OpenAI, Anthropic	Their question banks lean toward LLM systems ("Design ChatGPT" and similar) [22][23][29] (ch-ref)	Chat-assistant products with retrieval and file Q&A
Uber	Genie, an on-call copilot that answers in Slack over internal docs, upgraded to "Enhanced Agentic RAG". The alirezadir RAG overview cites it as the production agentic-RAG example [3] (fetched) [14] (repo-link)	**The real system in Diagram 4**
LinkedIn	Published a GenAI product post-mortem covering routing, retrieval, generation and evaluation [13] (repo-link via [11])	Router + RAG over internal APIs

Company / context	Basis	Production system it mirrors
Instacart, Salesforce, Vimeo, Airbnb, GitHub	Internal assistant (Ava), Einstein Search Answers, a support bot, a conversational-AI automation platform, and Copilot [15]-[19] (repo-link via [21])	Internal / support RAG assistants
Glean, Perplexity (reference products, not interview tags)	Named as enterprise RAG examples in [3] (fetched)	Permission-aware enterprise search + LLM answers

Portal coverage

Portal / source	What it covers	Link
alirezadir ML-Interviews + Agentic-AI-Systems	Enterprise RAG template, must-cover list, bar-raiser moves, RAG taxonomy (CRAG, Self-RAG, Adaptive, KG-RAG)	[1][2][3][4]
Educative	"RAG knowledge assistant" case in Grokking MLSD (ch-ref). Grokking the Generative AI System Design and Advanced RAG Techniques are listed in [5] (fetched)	[24][25][26]
ByteByteGo (Aminian et al.)	The "Generative AI System Design Interview" book is reported to have a RAG chapter (not verified in this run)	[30]
IGotAnOffer	GenAI system design guide and OpenAI system design guide	[22][23]
Chip Huyen, "AI Engineering" (O'Reilly)	Ch. 6 "RAG and Agents": RAG Architecture, Retrieval Algorithms, Retrieval Optimization, RAG Beyond Texts, Agents, Memory [11] (fetched). GenAI platform post [12]	[11][12]
Anthropic engineering	Contextual Retrieval (measured retrieval-failure reductions). "Building effective agents": routing, prompt chaining, evaluator-optimizer	[6][34] (fetched)
Hello Interview / Exponent / PracHub	MLSD delivery frameworks. LLM-system question banks	[27][28][29]


Requirements & scale

Dimension	Value	Source
Functional	Ask questions in natural language. Get a grounded answer with citations. Multi-turn follow-ups. Say "I don't know" when unsupported	[2]
Corpus sources	Wiki/Confluence, Drive/Docs, PDFs, Slack, tickets, code. Connectors per source. MCP is an option for standard tool/data connectors, but treat each protocol boundary as a trust boundary	[4]
Access control	Per-document ACLs and tenant isolation, applied at **retrieval time**	[2]
Freshness	New or edited docs searchable in under 15 min. ACL revocations take effect in under 5 min	typical assumption
Corpus size	10M docs -> about 200M chunks (about 20 chunks per doc, chunks of a few hundred tokens) [6]	assumption

Dimension	Value	Source
Index size	200M x 1024-d fp16 is about 400 GB raw. About 25-50 GB with PQ / int8	derived
Users / QPS	50k employees x 10 q/day = 500k q/day: about 6 QPS average, about 30 QPS peak. A multi-tenant SaaS with 1k tenants reaches about 3-5k QPS peak	assumption
Latency	Retrieval + rerank p95 under 400 ms. Time to first token (TTFT) under 1.5 s. Full answer under 8 s, streamed	typical assumption
Quality	Faithfulness of 0.9 or higher on the golden set. Citation precision 0.9 or higher. Hallucinated-answer rate under 2%	typical target
Cost	Track tokens per query. Route easy queries to a small model. Cache prompts and responses	[1][2]
Safety	Defend against prompt injection (including from retrieved docs). Redact PII. Keep audit logs. Honor deletion / GDPR	[1][4]

Diagram 1 - Online serving path (query -> retrieve -> filter -> rerank -> generate -> response)

Figure 24.1 - End-to-end online architecture of a permission-aware RAG assistant



- The "feature store" of classic MLSD maps to the **chunk store + metadata/ACL store**. The "model store" maps to the **model registry + prompt store** [12].

- Apply ACL filtering **before** generation, never after. A post-filter re-check guards against stale ACLs [2]. Context selection should also weigh recency, authority and permission filters [4].
- The semantic-cache key includes the caller's ACL-group hash. Without it, a cached answer can leak one user's documents to another user.
- Prompt caching of the stable system prompt and document prefix can cut cost by up to 90% and latency by more than 2x [6].

Diagram 2 - Offline pipeline: ingestion, indexing, evaluation, feedback loop

Figure 24.2 - Offline indexing, model adaptation, and evaluation pipeline




Diagram 3 - Model architecture: bi-encoder retriever + cross-encoder reranker + LLM generator

Figure 24.3 - The three learned components and their inputs/outputs



- The original RAG paper (Lewis et al. 2020) trained a DPR retriever and a BART generator jointly [7] (repo-link via [11]), building on the retriever-reader design of DrQA [9]. Production systems usually keep the components **decoupled** and use a frozen LLM [8][11].

Diagram 4 - Real system: Uber Genie "Enhanced Agentic RAG" (EAg-RAG)

Figure 24.4 - Agentic RAG variant modelled on Uber's on-call copilot (approx., per [14])



- Reported results (approx., not verified in this run; check [14]): a sizeable relative gain in "acceptable" answers and a large relative drop in incorrect advice versus the earlier plain-RAG Genie. Most of the gain came from **better document processing**, not a better LLM.
- The same pattern shows up elsewhere. LinkedIn routes intents to "skills", retrieves via internal APIs, then generates. Its post says most of the effort went into evaluation guidelines, and that pushing quality past "good enough" took far longer than the first build [13] (repo-link via [11]). Practitioner write-ups report the same pattern [32].

Data & labels

Data	Source	Label / use	Pitfall
Documents + ACLs	Connectors, CDC	Corpus, permission filter	Stale ACL -> leak
(query, positive chunk) pairs	Citation clicks, SME annotation, synthetic Q from chunks (LLM)	Train the embedder and reranker	Synthetic Q are too "easy" (lexical overlap)
Hard negatives	BM25 / ANN top-k that is not gold	Contrastive training	False negatives (duplicate docs)
Golden QA set (200-2k)	SMEs + logs	Offline regression eval	Goes stale as docs change

Data	Source	Label / use	Pitfall
Answer feedback	Thumbs, edits, escalations, re-asks	Online quality signal, judge calibration	Sparse; skews negative
LLM-judge labels	Judge model + rubric	Faithfulness, relevance at scale	Judge bias; calibrate on human labels [13]

Features / signals used in ranking and context building

Group	Examples
Query	Rewritten text, intent class, entities, language, conversation history summary
Chunk content	Dense embedding, BM25 terms, contextual prefix [6], title/heading path
Chunk metadata	Source, doc type, author, last-modified (freshness), authority / official flag, popularity
User	Team, org, permissions (groups), recent docs (light personalization)
Cross	Cross-encoder score, RRF rank, dense/lexical agreement, same-doc neighbours

Model choices (baseline -> advanced)

Stage	Baseline	Advanced	Tradeoff
Knowledge strategy	Long context (stuff the docs)	RAG. Plus LoRA for style/format. Agentic RAG [1][10]	RAG = fresh + citable. Fine-tune = behaviour, not facts [10]
Chunking	Fixed 512 tok + overlap	Heading/semantic chunking, parent-child, contextual chunks [6][31]	Bigger chunks: recall up, precision and tokens worse. Contextual chunks cost about $1.02 per 1M doc tokens once, with prompt caching [6]
Retrieval	BM25	Dense bi-encoder + BM25 hybrid with RRF. Fine-tuned embedder	Dense misses IDs/codes. BM25 misses paraphrase
Rerank	None	Cross-encoder on top-150 -> top-20 [6]	+50-150 ms. Big precision gain
Query processing	Raw query	Rewrite with history, decompose multi-hop, HyDE [1]	Extra LLM call (latency)
Generator	Hosted frontier LLM	Router: small model for easy queries, large for hard. Self-host + vLLM for scale [1]	Cost vs quality. Data residency
Control flow	Fixed pipeline (workflow: routing, prompt chaining [34])	Agentic: decide when and where to retrieve, iterate, abstain (CRAG / Self-RAG / Adaptive). Evaluator-optimizer loop for answer checking [3][4][14][33][34]	Better on multi-hop. Harder to bound latency and cost

Loss functions

Component	Loss
Bi-encoder retriever	InfoNCE / multiple-negatives ranking loss (in-batch + hard negatives)
Cross-encoder reranker	Pointwise BCE, or listwise softmax CE over (1 pos, n neg)

Component	Loss
LLM fine-tune (optional)	Next-token cross-entropy on grounded, cited answers (SFT). DPO on preferred vs rejected answers
Groundedness verifier	BCE on (claim, evidence) -> supported / not supported (NLI)

Offline metrics

Layer	Metric	Notes
Retrieval	Recall@k (e.g. @20), MRR, nDCG@10	Anthropic: top-20 retrieval failure 5.7% -> 3.7% with contextual embeddings (-35%), -> 2.9% adding contextual BM25 (-49%), -> 1.9% adding a reranker (-67%) [6] (fetched)
Context	Context precision, context recall	Ragas definitions [20] (fetched)
Generation	Faithfulness = supported claims / total claims	Ragas [20]
Generation	Answer relevancy, answer correctness, factual correctness vs reference	LLM judge + embeddings [20]
Context	Context entities recall (entity-heavy domains: names, IDs, products)	Ragas [20]
Citations	Citation precision / recall (does the cited chunk support the sentence?)	Human audit sample
Robustness	Noise sensitivity, abstain rate on unanswerable questions, prompt-injection pass rate	Red-team set [20]
Cost / latency	Tokens per answer, p95 latency, TTFT	Gate in CI

Online metrics / A-B

Type	Metric
Primary	Answer acceptance: thumbs-up rate, or "resolved without follow-up" rate
Engagement	Weekly active askers, queries per user, citation click-through
Business	Ticket deflection (support), time-to-resolution, escalations avoided
Guardrails	Thumbs-down rate, reported hallucinations, leak incidents (must be 0), refusal rate, p95 latency, cost per query
Method	Shadow -> canary -> A/B on users or teams. Interleaving for retriever changes. LLM-judge on sampled live traffic

Serving & latency budget (target under 8 s full answer, TTFT about 1.5 s; typical assumption)

Step	Budget (p95)	Tactics
Gateway + auth + guardrail	50 ms	Small classifier, cached group lookups
Query rewrite / router	150-300 ms	Small model, skip for single-turn simple queries
Hybrid retrieval + ACL filter	50-100 ms	HNSW with metadata pre-filter, sharded by tenant
Rerank top-150	80-150 ms	Distilled cross-encoder on GPU, batch
Prompt build	10 ms	Token budget, dedupe
LLM TTFT	500-900 ms	Prompt caching, KV cache, continuous batching (vLLM), streaming [1]
LLM decode (300 tok)	3-6 s (streamed)	Small model routing, speculative decoding
Output check	100-300 ms (async or partial)	Verify after the stream; retract or flag if needed

Monitoring

What	Signal	Action
Retrieval health	Empty-result rate, top-1 score distribution, recall on a canary set	Alert. Check embedder / index version
Quality drift	Sampled LLM-judge faithfulness, thumbs-down trend by source	Golden-set regression. Re-index
Freshness	Ingestion lag, CDC backlog, % of docs stale	Scale connectors
Security	ACL mismatch audits, injection detections, PII in outputs	Block. Page security
Cost / latency	Tokens per query, cache hit rate, provider errors, TTFT	Route to a smaller model. Fail over
Traces	Per-step spans (rewrite, retrieve, rerank, generate, tool calls), cost and evidence per step	Trace replay to debug bad answers. Online evals on live traces [2][4]
Safety events	Prompt injection, policy refusal, PII exposure, unsafe tool request	Count, alert, add to the red-team set [4]

Failure modes

Failure	Cause	Mitigation
Hallucination / unsupported claim	Weak context, model prior	"Answer only from sources", groundedness check, abstain
Permission leak	ACL filter after generation, stale ACL sync, cache shared across users	Pre-filter at retrieval. Cache key includes ACL hash. Fast ACL CDC
Retrieval miss	Bad chunking (tables split), vocabulary mismatch, IDs/acronyms	Hybrid BM25, contextual chunks, structure-aware parsing [6][14]
Lost in the middle / context overflow	Too many chunks	Rerank, fewer chunks, order best-first
Indirect prompt injection	Malicious text inside a retrieved doc	Treat retrieved text as data, spotlight/delimit it, output filters, restrict tool scopes
Stale or conflicting answers	Old doc versions	Freshness and authority features, dedupe versions, show dates

Failure	Cause	Mitigation
Deletion / compliance	Deleted doc still in index or cache	Tombstones, cache invalidation, re-embed jobs
Agent acts with stale or broad permissions	Over-permissioned tools or connectors, cached credentials	Scope credentials per tool, task, user and tenant. Re-check ACLs at call time [4]
Cost blow-up	Long histories, agent loops	History summarization, step and budget caps
Embedder upgrade breaks index	Vector-space mismatch	Blue/green re-index, dual-read during migration

Interviewer follow-ups

- RAG vs fine-tuning vs long context: when would you use each, and when would you combine them? [1][10]
- How do you enforce document permissions? Pre-filter vs post-filter. How fast must ACL changes propagate? [2]
- How do you pick chunk size and chunking strategy for PDFs with tables and headings? [6][31]
- Why hybrid search? Give a query that dense retrieval fails on. How do you fuse the scores?
- How do you evaluate without labelled data? Golden set, synthetic questions, LLM-as-judge and its biases [13][20]
- How do you detect and reduce hallucinations at serving time? When should the system abstain?
- How do you handle multi-turn follow-ups ("what about for contractors?")? Query rewriting with history.
- Multi-hop questions that span several docs: decomposition or agentic RAG? How do you bound the latency? [3][14]
- How do you keep the index fresh, and how do you handle deletes and right-to-be-forgotten? [2]
- How would you cut cost by 5x? Caching, routing, smaller models, prompt compression.
- How do you defend against prompt injection hidden inside documents? [1][4]
- How do you scale to 1,000 tenants? Tenant isolation, sharding, noisy neighbours.
- You upgrade the embedding model: how do you migrate a 200M-vector index safely?
- Which online metric would you ship on, and what are your guardrails?
- Where does the LLM fit, and where should deterministic systems take over? [1]
- Workflow or agent? When is a fixed routing / chaining pipeline enough, and when does an agent loop earn its cost? [34]
- How do connectors reach Slack, Drive and tickets (custom crawlers vs MCP), and how do you scope their credentials? [4]
- Contextual retrieval: what does prepending doc context to each chunk buy, and what does it cost to index? [6]

Portal comparison

Portal	Framing	Emphasis	Distinctive point
alirezadir Agentic-AI-Systems [2][3]	"Enterprise RAG assistant" template (Tier 1)	Ingestion, hybrid search, ACL and tenant isolation, faithfulness evals	Bar-raiser list: multi-hop, deletion, abstention, semantic cache, agentic RAG
alirezadir ML-SD template [1]	GenAI lens on the 9-step MLSD formula	"Evaluation is the new system design". Cost, latency, guardrails	RAG triad (faithfulness, answer relevance, context relevance) + recall@k / MRR / nDCG
Chip Huyen, AI Engineering [11] [12]	RAG as context construction inside a GenAI platform	Retrieval algorithms and optimization, guardrails, router, gateway, cache	Finetuning vs RAG analysis. Platform-level view
Educative (Grokking MLSD / GenAI SD) [24][25]	RAG knowledge-assistant case study	Step-by-step framework, training + inference	Course format with model and serving sections
ByteByteGo GenAI SDI [30]	RAG chapter in the 7-step ML framework (not verified in this run)	Indexing, retrieval, generation, evaluation	Diagram-heavy, interview-script style
Uber / LinkedIn blogs [13][14]	Production post-mortems	Document processing, agents, evaluation effort	Real numbers and lessons learned. Not interview-shaped

References

1. alirezadir, "ML System Design" (GenAI / LLM System Design 2026 section), GitHub, 2026. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (fetched)
2. alirezadir, "GenAI and Agentic System Design Interview Prep" (Enterprise RAG Assistant template, topic tiers), GitHub, 2026. https://github.com/alirezadir/Agentic-AI-Systems/blob/main/06_interview_prep/genai-agentic-system-design.md (fetched)
3. alirezadir, "Retrieval-Augmented Generation (RAG)" overview, Agentic-AI-Systems, GitHub, 2025. https://github.com/alirezadir/Agentic-AI-Systems/blob/main/03_system_design/RAGs/README.md (fetched)
4. alirezadir, "2026 Agentic AI System Design Update", Agentic-AI-Systems, GitHub, 2026. https://github.com/alirezadir/Agentic-AI-Systems/blob/main/03_system_design/2026-agentic-ai-system-design.md (fetched)
5. alirezadir, "GenAI resources", GitHub, 2026. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/genai-resources.md (fetched)
6. Anthropic, "Introducing Contextual Retrieval", anthropic.com, 2024. https://www.anthropic.com/news/contextual-retrieval (fetched)
7. P. Lewis et al., "Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks", arXiv, 2020. https://arxiv.org/abs/2005.11401 (repo-link via [11])
8. Y. Gao et al., "Retrieval-Augmented Generation for Large Language Models: A Survey", arXiv, 2023. https://arxiv.org/abs/2312.10997 (repo-link via [11])
9. D. Chen et al., "Reading Wikipedia to Answer Open-Domain Questions", arXiv, 2017. https://arxiv.org/abs/1704.00051 (repo-link via [11])
10. O. Ovadia et al., "Fine-Tuning or Retrieval? Comparing Knowledge Injection in LLMs", arXiv, 2024. https://arxiv.org/abs/2312.05934 (repo-link via [11])
11. C. Huyen, "AI Engineering" book resources (Ch. 6 RAG and Agents) and table of contents, GitHub, 2025. https://github.com/chiphuyen/aie-book/blob/main/resources.md (fetched); https://github.com/chiphuyen/aie-book/blob/main/ToC.md (fetched)

12. C. Huyen, "Building A Generative AI Platform", huyenchip.com, 2024. https://huyenchip.com/2024/07/25/genai-platform.html (not verified)
13. J. P. Bottaro & K. Ramgopal, "Musings on Building a Generative AI Product", LinkedIn Engineering, 2024. https://www.linkedin.com/blog/engineering/generative-ai/musings-on-building-a-generative-ai-product (repo-link via [11])
14. Uber Engineering, "Enhanced Agentic-RAG: What If Chatbots Could Deliver Near-Human Precision?", uber.com, 2025. https://www.uber.com/blog/enhanced-agentic-rag/ (repo-link via [3])
15. Instacart, "Scaling Productivity with Ava - Instacart's Internal AI Assistant", tech.instacart.com, 2023. https://tech.instacart.com/scaling-productivity-with-ava-instacarts-internal-ai-assistant-ed7f02558d84 (repo-link via [21])
16. Salesforce AI Research, "Resolve Cases Quickly with Interactive Einstein Search Answers", blog.salesforceairesearch.com, 2023. https://blog.salesforceairesearch.com/einstein-search-answers/ (repo-link via [21])
17. Vimeo Engineering, "From idea to reality: Elevating our customer support through generative AI", Medium, 2023. https://medium.com/vimeo-engineering-blog/from-idea-to-reality-elevating-our-customer-support-through-generative-ai-101a2c5ea680 (repo-link via [21])
18. Airbnb Engineering, "Intelligent Automation Platform: Empowering Conversational AI and Beyond at Airbnb", Medium, 2022. https://medium.com/airbnb-engineering/intelligent-automation-platform-empowering-conversational-ai-and-beyond-at-airbnb-869c44833ff2 (repo-link via [21])
19. GitHub, "How to build an enterprise LLM application: Lessons from GitHub Copilot", github.blog, 2023. https://github.blog/2023-09-06-how-to-build-an-enterprise-llm-application-lessons-from-github-copilot/ (repo-link via [21])
20. Ragas, "Available metrics" docs (faithfulness, context precision/recall, answer relevancy, noise sensitivity), GitHub, 2025. https://github.com/explodinggradients/ragas/tree/main/docs/concepts/metrics/available_metrics (fetched)
21. Engineer1999, "A Curated List of ML System Design Case Studies", GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies (fetched)
22. IGotAnOffer, "Generative AI System Design Interview", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/generative-ai-system-design-interview (ch-ref)
23. IGotAnOffer, "OpenAI System Design Interviews", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/openai-system-design-interview (ch-ref)
24. Educative, "The 6-step ML SD framework" (Grokking the ML System Design Interview), educative.io, 2025. https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/the-6-step-ml-sd-framework (ch-ref)
25. Educative, "Grokking the Generative AI System Design", educative.io, 2025. https://www.educative.io/courses/generative-ai-system-design (repo-link via [5])
26. Educative, "Advanced RAG Techniques", educative.io, 2025. https://www.educative.io/courses/advanced-rag-techniques (repo-link via [5])
27. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery (ch-ref)
28. Exponent, "Introduction to the ML System Design Interview", tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)

29. PracHub, "ML System Design Interview Questions", prachub.com, 2026. https://prachub.com/categories/ml-system-design?page=20 (ch-ref)
30. ByteByteGo, home page (courses incl. ML and Generative AI System Design Interview), bytebytego.com, 2025. https://bytebytego.com (ch-ref; chapter title not verified)
31. Pinecone, "Chunking Strategies for LLM Applications", pinecone.io, 2023. https://www.pinecone.io/learn/chunking-strategies/ (repo-link via [11])
32. E. Yan et al., "Applied LLMs: What We've Learned From A Year of Building with LLMs", applied-llms.org, 2024. https://applied-llms.org/ (repo-link via [11])
33. LangGraph, "Agentic RAG" example notebook, GitHub, 2024. https://github.com/langchain-ai/langgraph/blob/main/examples/rag/langgraph_agentic_rag.ipynb (fetched)
34. E. Schluntz & B. Zhang, "Building effective agents", Anthropic Engineering, 2024. https://www.anthropic.com/engineering/building-effective-agents (fetched)

25. Design an LLM Customer-Support Agent / Contact-Center Agent-Assist (Cresta, Intercom Fin, Sierra)

> Prompt as usually given: "Design an AI agent that resolves customer-support chats end to end (like Intercom Fin or Sierra)", or "Design real-time agent-assist for a contact center: suggest replies and next actions to human agents while they talk (like Cresta or Google Agent Assist)". Variants: "Design a RAG help-center bot", "Design Dasher/Driver support automation", "Design a ticket triage + auto-reply system", "Design a voice agent".

> Verification note (review pass, 2026-10): web search was exhausted and HTTP fetches to arxiv.org, company blogs and portal sites did not resolve. GitHub repositories were verified by cloning them: refs [1][2][21][26][27][31][32][33] are marked (verified). Refs marked (ch-ref) were checked in earlier chapters; (known; not fetched) means cited from prior knowledge, so check exact numbers before quoting them. "Typical assumption" numbers are interview-style estimates.

Company tags

Company	Basis	Production system it mirrors
Intercom	Builds Fin, an LLM agent that answers from help-center content and hands off to humans [13]	Fin AI Agent: RAG over help center + resolution-based pricing
Sierra	Builds customer-facing agents; published tau-bench for tool-agent-user evaluation [1][2][14]	Agent with policy doc + tool APIs + simulated-user evaluation
Cresta	Builds real-time agent-assist and coaching for contact centers [15]	Streaming ASR -> intent / moment detection -> suggestions to human agent
Google (Cloud CCAI)	Sells Agent Assist (suggested answers, smart reply, summarization) [16]	Agent Assist + Dialogflow virtual agent
DoorDash	Published LLM Dasher-support automation (RAG + guardrail + judge) [9]	RAG bot with LLM Guardrail and LLM Judge quality loop
LinkedIn	Published knowledge-graph RAG for customer-service QA [10]	Ticket graph retrieval -> LLM answer; reported lower per-issue resolution time
Klarna	Reported its AI assistant handled ~2/3 of chats in first month [17]	Fully automated chat agent with human escalation
Uber	Published Genie, a gen-AI on-call copilot (internal support variant) [18]	Slack Q&A bot over internal docs

Portal coverage.

Portal / source	What it covers for this problem	Link
ByteByteGo / Aminian (GenAI System Design	Chatbot and retrieval-augmented generation chapters are the closest templates (book; not fetched in this run). Classic MLSDI book has no support-agent	[20] [21]

Portal / source	What it covers for this problem	Link
Interview book)	chapter [21]	
Chip Huyen, "AI Engineering" + "Building a GenAI platform"	Context construction, guardrails, router, cache, evaluation, feedback - the canonical component list	[6][7]
Hello Interview / Exponent / Educative	MLSD framework (clarify -> data -> model -> eval -> serve); GenAI questions use the same skeleton	[22] [23] [24]
IGotAnOffer	OpenAI system design guide; LLM-product style questions	[25]
alirezadir ML-Interviews	Lists "LLM-powered customer-support chatbot (with guardrails, fallback to human)" as a GenAI-round question; GenAI checklist: RAG vs fine-tune, hybrid retrieval, rerank, semantic cache, circuit breakers, RAG triad eval	[26]
alirezadir Agentic-AI-Systems	12-step agentic design template worked on a customer-support agent: memory layers, tool/action framework, feedback loop, observability	[33]
Sierra tau / tau2 / tau3-bench	Open benchmark for customer-service agents: policy + tools + simulated user; airline, retail, telecom, banking_knowledge domains; voice full-duplex mode	[2] [27] [31] [32]
Chip Huyen ml-interviews-book	Evaluation, data, and deployment Q&A used in follow-ups	[28]

Requirements & scale

Dimension	Value	Source
Functional (autonomous agent)	Answer questions from KB; take actions via tools (refund, reschedule, reset password) within policy; hand off to a human with summary	[1][9][13]
Functional (agent-assist)	Real-time suggested replies, KB snippets, next-best-action, compliance alerts, auto-summary after call	[15][16]
Channels	Chat, email, voice (ASR + TTS), messaging apps	typical assumption
Tenants	Multi-tenant SaaS: 1k-10k customer companies, each with its own KB, tools, policies, tone	typical assumption
Volume	~10M conversations/day, ~10 turns each -> ~100M LLM turns/day, peak ~3-5k turns/s	typical assumption
KB size	1k-100k articles per tenant; ~100M chunks total	typical assumption
Latency (chat)	First token < 1-2 s; full reply p95 < 5 s incl. tool calls	typical assumption
Latency (voice / assist)	Suggestion visible < 500-800 ms after customer utterance ends	typical assumption
Quality	Resolution rate (no human needed, no reopen) is the north star; hallucination ~0 on policy facts	[13][9]
Safety	No policy-violating actions (refunds over limit), PII redaction, prompt-injection defense, audit log	[1][7]
Reliability	99.9%; graceful fallback to human queue when LLM / tools fail	typical assumption
Cost	Target cents per conversation; route easy turns to small models	[7]

Diagram 1 - Online serving path

DIAGRAM 1: End-to-end online path for an autonomous support agent with human handoff (synthesised from [1][6][7][9][13])




Diagram 2 - Offline data, training & evaluation loop

DIAGRAM 2: Offline pipeline: KB indexing, transcript mining, fine-tuning, eval gate, deployment and feedback (synthesised from [1][7][9][10])



Diagram 3 - Model architecture

DIAGRAM 3: Agent = router + retriever/reranker + tool-using LLM + guardrail/judge models (synthesised from [3][4][5][6][9])





Diagram 4 - Variant: real-time agent-assist (Cresta / Google Agent Assist style)

DIAGRAM 4: Human-in-the-loop assist on a live voice call (synthesised from [11] [15][16])



Data & labels

Data	Label / signal	Notes
Help-center articles, macros, policy docs	Source of truth for grounding	Version + tenant + locale metadata on every chunk
Historical tickets / transcripts	Human agent replies (SFT targets), resolution codes	Scrub PII; keep only high-CSAT agents' replies [11]
Live AI conversations	Resolved (no handoff, no reopen in 24-72 h), escalated, CSAT, thumbs	Delayed and noisy; "no reply" is not success
Agent-assist events	Suggestion accepted / edited / ignored	Strong implicit label; position-biased
LLM-judge scores	Faithfulness, correctness, tone, policy adherence	Calibrate judges against human QA [8]
Human QA review	Rubric grades on sampled conversations	Gold set for judge calibration
Simulated episodes	Pass/fail of goal DB state after agent-user sim	tau-bench style; checks actions, not just text [1]

Features / context signals

Group	Examples	Used by
Turn	text, language, sentiment, detected intent, entities (order id)	router, retriever
Conversation	turn count, prior failed answers, frustration, summary	router (escalate), generator
Customer	plan tier, account status, open orders, past tickets	tools, policy check
Tenant	policy doc, tone guide, allowed tools, handoff hours	system prompt, guardrails
Memory	short-term (sliding window of turns), long-term (cross-session summary, preferences) [33]	context builder
Retrieval	BM25 score, dense score, rerank score, doc freshness	context builder, confidence
Generation	logprob / self-consistency, citation coverage, judge score	answer-vs-escalate decision

Model choices (baseline -> advanced)

Stage	Baseline	Advanced	Trade-off
Intent / router	Keyword rules, logistic regression	Fine-tuned small transformer or small LLM	Rules are cheap and auditable; LM handles long tail
Retrieval	BM25	Hybrid BM25 + dense (DPR-style bi-encoder) + RRF [4]	Dense handles paraphrase; BM25 handles SKUs, error codes
Rerank	None	Cross-encoder / late interaction (ColBERT) [5]	+50-100 ms, large precision gain
Graph context	Flat chunks	Ticket knowledge graph retrieval [10]	Better for linked tickets; more build effort
Generator	Prompted frontier LLM + RAG [3]	Tuned small LLM for common intents, frontier for hard ones	Cost/latency vs quality; tuning needs clean data

Stage	Baseline	Advanced	Trade-off
Actions	Fixed decision trees calling APIs	LLM tool use (ReAct) with policy in prompt [12]	Flexible but less reliable; needs pass^k testing [1]
Orchestration	Routing workflow: classify (refund / technical / shipping) -> fixed prompt + tools per route [34]	Autonomous agent loop with handoff tool	Workflows are predictable; agents cover the long tail
Guardrails	Regex PII + blocklist	Classifier + NLI grounding + LLM judge [9]	Each check adds latency; run in parallel
Assist suggestions	Retrieval of canned responses	Generative next-best-response mined from top agents [11][15]	Generative adapts; canned is safe

Loss / objectives

Component	Objective
Bi-encoder	In-batch contrastive (InfoNCE) on (query, gold chunk) with hard negatives [4]
Cross-encoder	Pointwise BCE or listwise softmax over candidates
Router / guardrail	Cross-entropy, class-weighted (escalation is rare but costly)
Generator SFT	Next-token cross-entropy on high-quality agent replies (masked prompt)
Preference	DPO on (chosen, rejected) reply pairs from judges / QA [19]
Business	Maximize resolution rate s.t. CSAT >= floor, policy violations = 0, cost <= budget

Offline metrics

Layer	Metric
Retrieval	Recall@k, MRR, nDCG on golden (question, article) set [10]
Generation	Faithfulness / groundedness, answer relevance, context precision (RAGAS-style) [29]
Correctness	LLM-judge vs reference answer, judge-human agreement [8]
Agent / tools	Task success on simulated users, pass^k consistency, wrong-action rate [1][2]
Dual control	Success when the user must also act (e.g. toggle a phone setting) under agent guidance; tau2-bench telecom domain [27]
Knowledge-grounded agent	Task success when policy facts must be retrieved from an unstructured KB, not given in the prompt (tau-Knowledge) [31]
Voice agent	Full-duplex task success with interruptions / barge-in (tau-Voice) [32]
Safety	Injection / jailbreak success rate, PII leak rate, policy-violation rate
Router	Escalation precision/recall, AUC; cost-weighted error
Long context	Position sensitivity of answers (lost-in-the-middle check) [30]

Online metrics / A-B

Metric	Type	Notes
Automated resolution rate	North star	No handoff and no reopen within N days [13]
Escalation / handoff rate, deflection	Primary	Deflection alone can hide unhappy users who quit

Metric	Type	Notes
CSAT / thumbs	Guardrail	Low response rate; sample bias
Reopen / repeat contact (7 d)	Guardrail	Catches "answered but not solved"
AHT, first-contact resolution (assist)	Primary for assist	Productivity effect reported in field study [11]
Suggestion acceptance rate (assist)	Secondary	Edited-accept counts as partial
Cost per conversation, tokens/turn	Guardrail	Router + cache levers
Latency p50/p95, first token	Guardrail	Voice is strictest
Experiment unit	Conversation or customer, per tenant	Tenant-level rollouts; avoid cross-arm leakage within a session

Serving & latency budget (chat, p95 ~3-5 s; typical assumption)

Step	Budget	Notes
Gateway + session load + PII redaction	30 ms	Session in Redis
Input guardrail + router (parallel)	50 ms	Small models on GPU/CPU
Query rewrite (small LLM)	200 ms	Skip for first turn
Hybrid retrieval	40 ms	Per-tenant namespace in ANN
Rerank top-50	80 ms	Batch cross-encoder
Tool calls (0-3)	300-1500 ms	External APIs dominate; parallelize reads
Generator LLM	1-2.5 s (first token ~500 ms)	Stream tokens; prompt caching of tenant system prompt
Output guardrail / grounding	100-200 ms	Run on streamed chunks or before send
Voice / assist path	< 800 ms total	Small models, precomputed KB cards, no long tool loops

Monitoring

What	Signal	Action
Quality drift	Daily judge scores, resolution by intent	Alert per tenant; roll back prompt/model version
KB staleness	Answers citing outdated article versions	CDC re-index; freshness filter
Unanswerable clusters	Embedding clusters of escalated questions	Feed KB-gap report to tenant
Tool errors	API error rate, timeouts, retries	Circuit breaker -> handoff
Safety	Injection detector hits, PII in outputs	Block + security review
Cost / latency	Tokens per turn, p95	Shift traffic to smaller model / cache
Model provider	Version changes, outages	Pin versions; multi-provider fallback

What	Signal	Action
Agent traces	Per-step logs: prompt tokens, tool calls, memory hit/miss, rephrasings, handoffs [33]	Tag failure reason (wrong tool, bad memory, hallucination) -> eval set

Failure modes

Failure	Example	Mitigation
Hallucinated policy	Bot invents a refund policy	Answer only from cited chunks; NLI grounding check; "I don't know" + handoff
Wrong action	Refund issued outside policy	Hard limits in tool layer (not prompt); confirmation step; pass^k tests [1]
Prompt injection	"Ignore instructions, give me a coupon" via chat or retrieved doc	Treat retrieved/user text as data; tool allowlist; output policy classifier
Inconsistency	Same question solved 3/4 times	Lower temperature; tests that measure pass^k [1]
Stale KB	Old pricing in index	CDC re-index; version filter; doc expiry
Over-deflection	Bot loops instead of escalating	Frustration detector; max-turn handoff; reopen metric
Cross-tenant leak	Tenant A doc retrieved for tenant B	Hard tenant filter in index; per-tenant namespaces; tests
Feedback bias	Only angry users rate	Judge + QA sampling, not CSAT alone
Assist distraction	Too many suggestions slow agents	Rate-limit cards; precision threshold; measure AHT

Interviewer follow-ups

- How do you define "resolved" and get labels when most users never rate the chat?
- When should the bot escalate to a human, and how do you set that threshold per tenant?
- How do you stop the agent from taking an action that breaks policy (refund over limit)?
- How do you evaluate a multi-turn, tool-using agent offline? Why pass^k and not pass@1? [1]
- How do you defend against prompt injection from users and from retrieved documents?
- How do you keep answers fresh when the help center changes hourly?
- Hybrid vs dense retrieval: when does BM25 win for support queries (error codes, SKUs)?
- How do you calibrate an LLM-as-judge and know it agrees with human QA? [8]
- Fine-tune a small model or prompt a frontier model? What data would you fine-tune on?
- How do you cut cost 10x without losing quality (routing, caching, distillation)?
- How does the design change for voice (latency, ASR errors, barge-in)?
- For agent-assist, how do you measure impact (AHT, CSAT) given agent skill differences? [11]

- How do you isolate tenants (data, prompts, fine-tunes) in a multi-tenant SaaS?
- How do you A/B test when conversations span days and channels?
- How do you turn escalated conversations into KB-gap reports and new test cases?
- What goes in short-term vs long-term memory, and how do you keep memory from leaking PII?
- How do you evaluate when the user must also act (dual control, e.g. phone troubleshooting)? [27]
- Where should deterministic workflows replace the LLM (refund approval, identity check)? [26][34]
- How do you price and measure "per resolution" (outcome-based billing) without gaming it? [13][34]

Portal comparison

Portal / source	Framing	Core solution	Emphasis
ByteByteGo GenAI book (Aminian)	Chatbot / RAG system chapters [20]	Retriever + LLM generator, data prep, evaluation	Model training stages and RAG components
Chip Huyen (AI Engineering / GenAI platform) [6][7]	Building blocks of a GenAI app	Context construction -> guardrails -> router -> cache -> agent -> eval	Incremental architecture, evaluation, feedback
Hello Interview / Exponent [22][23]	Generic MLSD framework applied to GenAI	Clarify -> metrics -> data -> model -> serve -> monitor	Interview structure and trade-off talk
Company blogs (DoorDash, LinkedIn) [9][10]	Real support automation	RAG + guardrail + judge (DoorDash); KG retrieval (LinkedIn)	Hallucination control, quality pipeline
Sierra tau-bench [1][2]	Agent evaluation	Simulated user + tools + policy, DB-state check	Reliability (pass^k), policy compliance
alirezadir ML-Interviews + Agentic-AI-Systems [26][33]	"Customer-support chatbot with guardrails, fallback to human"	RAG + tools + memory + feedback loop + observability	Evaluation, cost, guardrails over the diagram
Field study (Brynjolfsson et al.) [11]	Agent-assist impact	AI suggestions to human agents	Productivity gains, largest for novices

References

1. S. Yao, N. Shinn, P. Razavi, K. Narasimhan (Sierra), "tau-bench: A Benchmark for Tool-Agent-User Interaction in Real-World Domains", arXiv:2406.12045, 2024. https://arxiv.org/abs/2406.12045 (verified via repo citation block)
2. Sierra Research, "tau-bench" repository (pass^1..pass^4 leaderboard; superseded by tau3-bench), GitHub, 2024. https://github.com/sierra-research/tau-bench (verified)
3. P. Lewis et al., "Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks", NeurIPS / arXiv, 2020. https://arxiv.org/abs/2005.11401 (known; not fetched)
4. V. Karpukhin et al., "Dense Passage Retrieval for Open-Domain Question Answering", EMNLP / arXiv, 2020. https://arxiv.org/abs/2004.04906 (known; not fetched)
5. O. Khattab, M. Zaharia, "ColBERT: Efficient and Effective Passage Search via Contextualized Late Interaction over BERT", SIGIR / arXiv, 2020. https://arxiv.org/abs/

2004.12832 (known; not fetched)
6. C. Huyen, "AI Engineering: Building Applications with Foundation Models", O'Reilly, 2025. https://www.oreilly.com/library/view/ai-engineering/9781098166298/ (known; not fetched)
7. C. Huyen, "Building A Generative AI Platform", huyenchip.com, 2024. https://huyenchip.com/2024/07/25/genai-platform.html (known; not fetched)
8. L. Zheng et al., "Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena", NeurIPS / arXiv, 2023. https://arxiv.org/abs/2306.05685 (known; not fetched)
9. DoorDash Engineering, "Path to high-quality LLM-based Dasher support automation", careersatdoordash.com, 2024. https://careersatdoordash.com/blog/large-language-modules-based-dasher-support-automation/ (known; not fetched)
10. Z. Xu et al. (LinkedIn), "Retrieval-Augmented Generation with Knowledge Graphs for Customer Service Question Answering", SIGIR / arXiv, 2024. https://arxiv.org/abs/2404.17723 (known; not fetched)
11. E. Brynjolfsson, D. Li, L. Raymond, "Generative AI at Work", NBER Working Paper 31161, 2023. https://www.nber.org/papers/w31161 (known; not fetched)
12. S. Yao et al., "ReAct: Synergizing Reasoning and Acting in Language Models", ICLR / arXiv, 2022. https://arxiv.org/abs/2210.03629 (known; not fetched)
13. Intercom, "Fin AI Agent" product site, fin.ai, 2025. https://fin.ai/ (known; not fetched)
14. Sierra, company site, sierra.ai, 2025. https://sierra.ai/ (known; not fetched)
15. Cresta, company site (agent assist, coaching), cresta.com, 2025. https://cresta.com/ (known; not fetched)
16. Google Cloud, "Agent Assist documentation", cloud.google.com, 2025. https://cloud.google.com/agent-assist/docs (known; not fetched)
17. Klarna, "Klarna AI assistant handles two-thirds of customer service chats in its first month", klarna.com press release, 2024. https://www.klarna.com/international/press/klarna-ai-assistant-handles-two-thirds-of-customer-service-chats-in-its-first-month/ (known; not fetched)
18. Uber Engineering, "Genie: Uber's Gen AI On-Call Copilot", uber.com blog, 2024. https://www.uber.com/blog/genie-ubers-gen-ai-on-call-copilot/ (known; not fetched)
19. R. Rafailov et al., "Direct Preference Optimization: Your Language Model is Secretly a Reward Model", NeurIPS / arXiv, 2023. https://arxiv.org/abs/2305.18290 (known; not fetched)
20. A. Aminian, H. Sheng, "Generative AI System Design Interview", ByteByteGo, 2024. https://bytebytego.com/ (site root; book page not fetched)
21. ByteByteGo, "ml-bytebytego: Reference materials for ML System Design Interview" (chapters 1-11; no support-agent chapter), GitHub, 2023. https://github.com/ByteByteGoHq/ml-bytebytego (verified)
22. Hello Interview, "Recommendation Systems (ML System Design pattern)" (framework reference), hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/patterns/recommendation-systems (ch-ref)
23. Exponent, "Introduction to the ML System Design Interview" (course), tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
24. Educative, "Grokking the Machine Learning Interview", educative.io, n.d. https://www.educative.io/courses/grokking-the-machine-learning-interview (ch-ref)
25. IGotAnOffer, "OpenAI System Design Interview", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/openai-system-design-interview (ch-ref)

26. alirezadir, "ML System Design" (sample questions incl. GenAI / LLM Systems 2026), Machine-Learning-Interviews, GitHub, 2026. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (verified)
27. V. Barres, H. Dong, S. Ray, X. Si, K. Narasimhan (Sierra), "tau2-Bench: Evaluating Conversational Agents in a Dual-Control Environment", arXiv:2506.07982, 2025; code (now tau3-bench) https://github.com/sierra-research/tau2-bench (verified)
28. C. Huyen, "Introduction to Machine Learning Interviews" (ml-interviews-book), huyenchip.com, 2021. https://huyenchip.com/ml-interviews-book/ (ch-ref)
29. S. Es et al., "RAGAS: Automated Evaluation of Retrieval Augmented Generation", arXiv, 2023. https://arxiv.org/abs/2309.15217 (known; not fetched)
30. N. F. Liu et al., "Lost in the Middle: How Language Models Use Long Contexts", TACL / arXiv, 2023. https://arxiv.org/abs/2307.03172 (known; not fetched)
31. Q. Shi, A. Zytek, P. Razavi, K. Narasimhan, V. Barres, "tau-Knowledge: Evaluating Conversational Agents over Unstructured Knowledge", arXiv:2603.04370, 2026. https://arxiv.org/abs/2603.04370 (verified via tau2-bench repo citation)
32. S. Ray, K. Dhandhania, V. Barres, K. Narasimhan, "tau-Voice: Benchmarking Full-Duplex Voice Agents on Real-World Domains", arXiv:2603.13686, 2026. https://arxiv.org/abs/2603.13686 (verified via tau2-bench repo citation)
33. alirezadir, "Agentic-AI-Systems: 12-Step Agentic System Design Framework" (customer-support agent worked example), GitHub, 2025. https://github.com/alirezadir/Agentic-AI-Systems/blob/main/03_system_design/architectures/ASD-12-step-v1.5.md (verified)
34. E. Schluntz, B. Zhang (Anthropic), "Building effective agents", anthropic.com, 2024. https://www.anthropic.com/engineering/building-effective-agents (known; not fetched; summarized in [33]'s cookbooks folder)

26. Design an AI Code Completion / Coding Assistant (GitHub Copilot, Cursor)

> Prompt as usually given: "Design GitHub Copilot: suggest the next line(s) of code as the developer types in the IDE", or "Design Cursor Tab: predict the next edit, not only the next token". Variants: "Design inline code completion for an internal monorepo" (Google, Meta CodeCompose), "Design a chat-with-your-codebase assistant", "Design an agent that fixes a GitHub issue end to end" (SWE-bench style), "Design Gmail Smart Compose" (the text analog in the ByteByteGo GenAI book).

> Verification note: in both the compile and the review pass, outbound fetches (arxiv.org, github.blog, cursor.com, research blogs, portal sites) failed DNS or proxy policy, and the web-search budget was spent. No URL was fetched live. (ch-ref) = verified in an earlier chapter; (known; not fetched) = well-known paper or post cited from prior knowledge, so check exact numbers before quoting them. "Typical assumption" = interview estimate.

Company tags

Company	Basis	Production system it mirrors
GitHub / Microsoft	Builds Copilot; published prompt-construction, neighboring-tabs and FIM details [4][5]; productivity study [3]	Copilot: IDE client builds prompt -> proxy -> Codex/GPT FIM model
Cursor (Anysphere)	Builds Cursor Tab (next-edit prediction), online RL for Tab [7], fast-apply model [31], codebase indexing [32]	Small fast edit model + policy-gradient updates from accept/reject; separate apply model
Google	Published hybrid semantic-engine + transformer completion for internal IDEs [6] [21]	~0.5B model; ~3% of new code and 6% shorter iteration time in 2022 [6]; later reports a large share of characters AI-completed [21]
Meta	Published CodeCompose deployment for internal monorepo [15]	InCoder-based [20] 1.3B FIM model fine-tuned on first-party code; ~22% accept rate, ~8% of code [15]
Sourcegraph	Published lifecycle of a Cody completion (context, debounce, post-processing) [16]	Retrieval of repo context + LLM + truncation heuristics
OpenAI	Codex paper is the origin of the problem framing (HumanEval, pass@k) [1][2]	Codex model family behind early Copilot

Portal coverage.

Portal / source	What it covers for this problem	Link
ByteByteGo / Aminian & Sheng (GenAI System Design Interview)	No Copilot chapter; "Gmail Smart Compose" chapter is the closest template (prefix -> LM -> beam search -> triggering, latency) [23][33]; the first ML SD book has no code chapter either [24]	[23] [24]
IGotAnOffer	Generic GenAI system design guide (LLM-product skeleton); no code-assistant walkthrough confirmed [25]	[25]
Chip Huyen, "Building a GenAI platform" / AI Engineering	Context construction, cache, router, guardrails, eval - reused for code assistants [26]	[26]
Hello Interview / Exponent / Educative	Generic MLSD framework; GenAI questions use the same skeleton [27][28][29]	[27] [28] [29]
alirezadir ML-Interviews	MLSD template and question list (LLM/GenAI section) [30]	[30]
Copilot reverse engineering (Thakkar)	Most-cited "how Copilot really works" write-up used in interview prep [8]	[8]

Requirements & scale

Dimension	Value	Source
Functional (inline)	Ghost-text completion of the rest of the line or a block at the cursor; accept with Tab, partial accept, cycle alternatives	[4][8]
Functional (next edit)	Predict the next edit anywhere nearby (rename propagation, cursor jump); Copilot "next edit suggestions" is the same product shape	[7]
Functional (apply)	Merge an LLM-written edit sketch into the full file quickly (fast apply)	[31]
Functional (chat / agent)	Explain, refactor, generate tests, multi-file edits, run tools (terminal, tests)	[12] typical assumption
Context	Prefix + suffix of current file, open tabs, imports, repo symbols, recent edits	[4][8][16]
Users	~1-20M daily developers; ~1-3 completion requests per developer-minute while typing	typical assumption
QPS	10M devs x ~200 requests/day -> ~2B/day, ~25k avg, ~75k peak QPS	typical assumption
Requests (Cursor)	Cursor reports 400M+ Tab requests per day [7]	[7]
Latency	Inline: p50 < 200-300 ms, p95 < 500 ms end to end (else user types past it); chat: first token < 1 s	[6] typical assumption
Quality	Acceptance rate (shown -> accepted) and retained characters after N seconds are north-star	[3][6]
Safety	No secrets / PII in suggestions; public-code match filter (Copilot checks ~150-char matches and can block or cite them) [34]; block insecure patterns; respect content exclusions	[34] typical assumption
Privacy	Enterprise: no training on customer code, zero retention, regional processing	typical assumption
Cost	GPU cost per request must be tiny: small model for inline, large model for chat	typical assumption

Diagram 1 - Online serving path

Inline completion: keystroke -> context retrieval -> prompt -> FIM model -> filters -> ghost text.




Diagram 2 - Offline data, training & evaluation loop

From public + permitted code to a deployed FIM model, with an accept/reject feedback loop.




Diagram 3 - Model architecture

Decoder-only transformer with fill-in-the-middle prompt; retrieval augments the prefix.





Diagram 4 - Variant: next-edit prediction and agentic coding (Cursor-style)

Two products on one platform: low-latency edit model + high-capability agent loop.



Data & labels

Source	Use	Label / signal	Caveat
Public permissive code (GitHub)	Pretraining	Next token / FIM middle (self-supervised)	License, dedup, test-set contamination [1][9]
Synthetic FIM splits	Infill training	Random span = target middle	Split at realistic points (line, block, AST node)
First-party monorepo	Fine-tune (Google, Meta)	Next token on internal code	Internal APIs; leakage across teams [6][15]
IDE telemetry (opt-in)	Online metrics, RL	Accepted & retained = positive; rejected / deleted = negative	Position bias, users typing past; strong privacy limits
Accepted-then-edited	SFT target	Final code after N seconds	Noisy; edit may be unrelated
Unit tests (HumanEval, MBPP)	Offline eval	pass@k	Function-level only, contaminated [1][22]
Repo-level benchmarks	Offline eval	Exact match / edit sim with cross-file context	[11]

Features / context signals

Signal	Where	Why
Prefix and suffix around cursor	Client	Core FIM input [2]
File path, language, imports	Client	Disambiguates APIs; cheap and high value [4][8]
Neighboring tabs snippets (sliding window, Jaccard sim)	Client	Copilot's "neighboring tabs" improved acceptance [4][8]
Repo retrieval (symbols, embeddings, BM25)	Server / local index	Cross-file APIs; RepoCoder iterative retrieval [10]
Recent edits diff	Client	Next-edit prediction [7]
Cursor position type (mid-line, after comment, empty line)	Client	Trigger / show decision (contextual filter) [8]
User history accept rate, typing speed	Client	Show threshold, debounce tuning [8]
Semantic engine results (types, members)	Language server	Google hybrid: filter/rank by compiler info [6]
Codebase embeddings index, synced by file-hash Merkle tree	Server, refreshed from client	Chat / agent retrieval without re-uploading the whole repo [32]

Model choices (baseline -> advanced)

Stage	Option	Pros	Cons
Baseline	N-gram / language-server symbol completion	Instant, exact	Single tokens only
v1	Pretrained code LM, left-to-right only	Simple	Ignores suffix; poor mid-file
v2	FIM-trained decoder (Codex/StarCoder/Code Llama/DeepSeek-Coder/Qwen-Coder) [2][9][13][17][18]	Uses suffix; standard today	Needs realistic FIM splits
v3	+ retrieval of repo context [4][10]	Cross-file correctness	Token budget, retrieval latency
v4	Distill / quantize large -> small for inline	Meets <300 ms	Some quality loss
v5	Fine-tune on accept/reject (DPO / online RL) [7]	Optimizes what users value	Feedback loop bias, reward hacking (show less)
Chat / agent	Frontier LLM + tools + agent loop [12]	Multi-file tasks	Seconds-minutes latency, cost

Loss / objectives

Objective	Formula (words)	Notes
Causal LM	Cross-entropy of next token	Pretraining
FIM	Same CE on permuted PRE/SUF/MID document; FIM rate up to ~90% without hurting left-to-right [2]	Key for mid-file completion
SFT on prod prompts	CE on middle only, prompt format equals production	Closes train/serve skew
Show/no-show classifier	Binary log loss on accepted vs not	Controls noise and cost

Objective	Formula (words)	Notes
Preference / RL	DPO on (accepted, rejected) pairs, or policy gradient with reward = accept - penalty for rejected show [7]	Must penalize showing bad suggestions
Distillation	KL between teacher and student token distributions	For small inline model

Offline metrics

Metric	Measures	Note
pass@k (HumanEval, MBPP)	Functional correctness of k samples	Unbiased estimator in [1]; contaminated
Exact match / edit similarity of middle	Token-level fidelity on held-out repos	Cheap; misses equivalent code
Cross-file EM (CrossCodeEval) [11]	Retrieval usefulness	Repo-level
Replay acceptance proxy	Predict accept on logged contexts	Off-policy, biased
Syntax / compile rate	Parse and type-check success	Uses language server
Latency, tokens/s, model size	Serving fit	Hard gate
SWE-bench resolve rate [12]	Agent end-to-end	For agent variant; use the human-validated Verified subset
Contamination-free eval (LiveCodeBench) [35]	Problems released after model cutoff	Fixes HumanEval leakage

Online metrics / A-B

Metric	Definition	Direction
Acceptance rate	accepted / shown	Up; strongest predictor of perceived productivity [3]
Retained characters	Chars of accepted code still present after 30s-10m	Up; guards against accept-then-delete [3] [8]
Fraction of code written by AI	AI chars / total chars committed	Up [6]
Shown rate / suggestions per hour	Volume	Not blindly up (noise) [7]
Cancel / timeout rate	Request cancelled by keystroke before response	Down
p50/p95 latency	Keystroke -> ghost text	Down
Guardrails	Secret leaks, public-code matches, vuln patterns	~0
Long-term	Retention, DAU, survey (SPACE), PR throughput	Up

Serving & latency budget (inline, p95 ~400 ms; typical assumption)

Step	Budget	Technique
Debounce + trigger	50-150 ms (not counted in model time)	Skip mid-word, cancel stale requests
Client context + prompt build	10-20 ms	Precomputed local index, Jaccard windows [8]
Network to region	30-60 ms	Edge regions, HTTP/2 streaming, keep-alive
Gateway, auth, filters	10 ms	In-memory policy cache
Repo retrieval (optional)	20-40 ms	Precomputed index; can be client-side
Prefill (2-8k tokens)	30-80 ms	Prefix/KV cache reuse across keystrokes, GQA
Decode (~20-60 tokens)	50-150 ms	Small model, speculative decoding [14], int8/fp8, continuous batching (vLLM) [19]
Post-processing + filters	10-20 ms	Truncation at block end, public-code filter
Apply edit (chat/agent only)	~1 s for a few hundred lines	Speculative edits: the existing file is the draft, so most tokens are verified, not generated [31]

Monitoring

What	Signal	Action
Quality	Accept rate, retained chars by language / IDE / tenant	Alert on drop; roll back model
Latency	p50/p95/p99, timeout and cancel rate	Autoscale GPUs, shrink context
Cost	GPU-sec per accepted char	Route, cache, tune show threshold
Safety	Secret detector hits, public-code match rate, insecure patterns	Block, retrain filter
Drift	New languages / frameworks, library version changes	Refresh fine-tune data
Client health	Extension crash rate, version skew of prompt format	Force-upgrade, server-side compat

Failure modes

Failure	Cause	Mitigation
Suggestion arrives too late	Long prompt, cold KV cache	Cancel-on-keystroke, prefix cache, smaller model
Repeats suffix / overlaps existing code	No FIM or bad truncation	FIM training, suffix-overlap trimming [16]
Hallucinated APIs	Missing cross-file context	Repo retrieval, language-server validation [6][10]
Verbatim license-sensitive code	Memorization	Dedup training data, public-code match filter
Secret / PII leakage	Secrets in training data or context	Scrub data, redact prompts, output detector
Insecure code (SQLi, weak crypto)	Learned from public code	Security filter, static analysis on suggestion

Failure	Cause	Mitigation
Distracting noise	Showing low-confidence suggestions	Show/no-show model; RL penalizing rejects [7]
Accept-rate gaming	Optimizing short trivial completions	Track retained chars and AI-written fraction
Train/serve skew	Prompt format in training differs from client	SFT on logged production prompts
Prompt injection (agent)	Malicious repo files / README	Sandbox tools, confirm destructive actions

Interviewer follow-ups

- How do you decide when to trigger a request and when to show a suggestion at all?
- How do you build the prompt under a fixed token budget? What gets priority?
- Why fill-in-the-middle, and how do you create FIM training examples? [2]
- How do you bring in cross-file context with <50 ms extra latency? Client vs server index?
- Acceptance rate vs retained characters vs pass@k: which is your north star and why? [3]
- How would you hit p95 < 500 ms at ~75k QPS? Batching, KV cache reuse, speculative decoding?
- One model or two (small inline + large chat)? How do you route?
- How do you use accept/reject telemetry to improve the model without bias or reward hacking? [7]
- How do you avoid regurgitating licensed code or leaking secrets?
- How do you support enterprise customers who forbid training on their code?
- How would you evaluate a new model offline when HumanEval is contaminated?
- How do you handle a newly released library the model has never seen?
- How would you extend this to next-edit prediction or an autonomous coding agent? [7][12]
- How do you keep client prompt format and server model in sync across extension versions?
- What do you log, and what is the privacy story?
- How do you index a large repo for retrieval and keep it fresh as files change? [32]
- How do you apply a model-written edit to a 1,000-line file in about a second? [31]
- How do you detect and handle suggestions that match public code (block vs cite)? [34]

Portal comparison

Portal / source	Framing	Emphasis	Gap
ByteByteGo GenAI book (Smart Compose chapter) [23]	Prefix-only text completion	Triggering, beam search, latency, perplexity/ExactMatch	No suffix/FIM, no repo context
Copilot reverse-engineering (Thakkar) [8]	Real system teardown	Prompt wishlist, neighboring tabs, contextual filter, retained-text telemetry	Client-side only; no training

Portal / source	Framing	Emphasis	Gap
GitHub engineering blog [4] [5]	Vendor view	Prompt library, FIM, neighbor tabs, model iteration	Light on numbers and infra
Google Research blog [6]	Internal monorepo	Hybrid semantic engine + small LM, acceptance and % code written	Single company setting
Cursor blog [7][31][32]	Next-edit + online RL, fast apply, indexing	Policy gradient on accept/reject, speculative edits, Merkle-tree sync	Few infra numbers
Meta CodeCompose paper [15]	Internal monorepo	Fine-tuning on first-party code, rollout, mixed-methods eval	Single company setting
Chip Huyen / generic GenAI frameworks [26][27][28]	Generic LLM app	Context construction, caching, guardrails, eval	Not code-specific

References

1. M. Chen et al. (OpenAI), "Evaluating Large Language Models Trained on Code" (Codex, HumanEval, pass@k), arXiv, 2021. https://arxiv.org/abs/2107.03374 (known; not fetched)
2. M. Bavarian et al. (OpenAI), "Efficient Training of Language Models to Fill in the Middle", arXiv, 2022. https://arxiv.org/abs/2207.14255 (known; not fetched)
3. A. Ziegler et al. (GitHub), "Productivity Assessment of Neural Code Completion", MAPS / arXiv, 2022. https://arxiv.org/abs/2205.06537 (known; not fetched)
4. GitHub Blog, "How GitHub Copilot is getting better at understanding your code", github.blog, 2023. https://github.blog/2023-05-17-how-github-copilot-is-getting-better-at-understanding-your-code/ (known; not fetched)
5. GitHub Blog, "Inside GitHub: Working with the LLMs behind GitHub Copilot", github.blog, 2023. https://github.blog/2023-05-17-inside-github-working-with-the-llms-behind-github-copilot/ (known; not fetched)
6. Google Research, "ML-Enhanced Code Completion Improves Developer Productivity", Google AI Blog, 2022. https://research.google/blog/ml-enhanced-code-completion-improves-developer-productivity/ (known; not fetched; old ai.googleblog.com URL redirects here)
7. Cursor, "Improving Cursor Tab with online RL", cursor.com blog, Sep 2025. https://cursor.com/blog/tab-rl (known; not fetched)
8. P. Thakkar, "Copilot Internals", copilot-explorer (GitHub Pages), 2022. https://thakkarparth007.github.io/copilot-explorer/posts/copilot-internals (known; not fetched)
9. R. Li et al. (BigCode), "StarCoder: may the source be with you!", arXiv, 2023. https://arxiv.org/abs/2305.06161 (known; not fetched)
10. F. Zhang et al., "RepoCoder: Repository-Level Code Completion Through Iterative Retrieval and Generation", EMNLP / arXiv, 2023. https://arxiv.org/abs/2303.12570 (known; not fetched)
11. Y. Ding et al., "CrossCodeEval: A Diverse and Multilingual Benchmark for Cross-File Code Completion", NeurIPS / arXiv, 2023. https://arxiv.org/abs/2310.11248 (known; not fetched)
12. C. E. Jimenez et al., "SWE-bench: Can Language Models Resolve Real-World GitHub Issues?", ICLR / arXiv, 2023. https://arxiv.org/abs/2310.06770 (known; not fetched)

13. B. Roziere et al. (Meta), "Code Llama: Open Foundation Models for Code", arXiv, 2023. https://arxiv.org/abs/2308.12950 (known; not fetched)
14. Y. Leviathan, M. Kalman, Y. Matias, "Fast Inference from Transformers via Speculative Decoding", ICML / arXiv, 2022. https://arxiv.org/abs/2211.17192 (known; not fetched)
15. V. Murali et al. (Meta), "AI-assisted Code Authoring at Scale: Fine-tuning, deploying, and mixed methods evaluation" (CodeCompose), arXiv, 2023. https://arxiv.org/abs/2305.12050 (known; not fetched)
16. Sourcegraph, "The lifecycle of a code AI completion", sourcegraph.com blog, 2023. https://sourcegraph.com/blog/the-lifecycle-of-a-code-ai-completion (known; not fetched)
17. D. Guo et al., "DeepSeek-Coder: When the Large Language Model Meets Programming", arXiv, 2024. https://arxiv.org/abs/2401.14196 (known; not fetched)
18. B. Hui et al., "Qwen2.5-Coder Technical Report", arXiv, 2024. https://arxiv.org/abs/2409.12186 (known; not fetched)
19. W. Kwon et al., "Efficient Memory Management for Large Language Model Serving with PagedAttention" (vLLM), SOSP / arXiv, 2023. https://arxiv.org/abs/2309.06180 (known; not fetched)
20. D. Fried et al., "InCoder: A Generative Model for Code Infilling and Synthesis", ICLR / arXiv, 2022. https://arxiv.org/abs/2204.05999 (known; not fetched)
21. Google Research, "AI in software engineering at Google: Progress and the path ahead", research.google blog, 2024. https://research.google/blog/ai-in-software-engineering-at-google-progress-and-the-path-ahead/ (known; not fetched)
22. J. Austin et al., "Program Synthesis with Large Language Models" (MBPP), arXiv, 2021. https://arxiv.org/abs/2108.07732 (known; not fetched)
23. A. Aminian, H. Sheng, "Generative AI System Design Interview" (incl. Gmail Smart Compose chapter), ByteByteGo, 2024. https://bytebytego.com/ (site root; book page not fetched)
24. ByteByteGo, "ml-bytebytego: Reference materials for ML System Design Interview" (chapter list; no code-assistant chapter), GitHub, 2023. https://github.com/ByteByteGoHq/ml-bytebytego (ch-ref)
25. IGotAnOffer, "Generative AI System Design Interview", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/generative-ai-system-design-interview (ch-ref)
26. C. Huyen, "Building A Generative AI Platform", huyenchip.com, 2024. https://huyenchip.com/2024/07/25/genai-platform.html (known; not fetched)
27. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery (ch-ref)
28. Exponent, "Introduction to the ML System Design Interview" (course), tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
29. Educative, "The 6-step ML SD framework" (Grokking the ML System Design Interview), educative.io, 2025. https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/the-6-step-ml-sd-framework (ch-ref)
30. alirezadir, "ML System Design" (template and sample questions), Machine-Learning-Interviews, GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (ch-ref)
31. Cursor, "Editing Files at 1000 Tokens per Second" (fast apply, speculative edits), cursor.com blog, 2024. https://cursor.com/blog/instant-apply (known; not fetched)

32. Cursor, "Security" (codebase indexing: embeddings, Merkle tree of file hashes), cursor.com, 2025. https://cursor.com/security (known; not fetched)
33. M. X. Chen et al. (Google), "Gmail Smart Compose: Real-Time Assisted Writing", KDD / arXiv, 2019. https://arxiv.org/abs/1906.00080 (known; not fetched)
34. GitHub Docs, "Finding public code that matches GitHub Copilot suggestions" (code referencing / duplication filter), docs.github.com, 2025. https://docs.github.com/en/copilot (docs root; page title known, deep path not verified)
35. N. Jain et al., "LiveCodeBench: Holistic and Contamination Free Evaluation of Large Language Models for Code", arXiv, 2024. https://arxiv.org/abs/2403.07974 (known; not fetched)

27. Design a Voice Assistant / Speech Recognition Pipeline (Alexa, Siri)

> Source note: pages re-fetched on 2026-10-14 are marked "(read)" in References. Apple, Google, arXiv, Meta and Netflix domains failed DNS lookup in this run, and the search budget was spent; those primary sources are marked "(not re-fetched)". Rows marked "(assumption)" are typical interview defaults.

Company tags

Company / context	What links it to this problem	Source
Amazon (Alexa, Echo)	Product owner of the canonical "Design Alexa" system: wake word on device, cloud ASR -> NLU -> skills -> TTS	(assumption; interview reports unverified)
Apple (Siri, "Hey Siri")	Two-pass on-device DNN voice trigger plus speaker check, then server ASR	[1] [2]
Google (Assistant, Gboard voice typing)	All-neural on-device streaming RNN-T recognizer	[3] [4]
Walmart (voice shopping)	Unified multi-task model for several virtual assistants; voice reorder flow	[12] [19] [20]
Meta (SeamlessM4T)	Adjacent: multimodal speech translation model, not an assistant	[12] [18]
OpenAI / NVIDIA	Whisper and NeMo (Parakeet, Canary, Nemotron streaming ASR) are the usual open baselines	[8] [10]

Portals that cover it

- alirezadir's MLSD guide lists "Speech Recognition Systems" as a topic (MFCC features, acoustic modeling, HMMs, CTC) and "Chatbot system" / "Language identification system" as sample questions. No full speech case study [5].
- khangich/machine-learning-interview has no speech case study [6].
- Engineer1999's case-study list has the production references (Walmart virtual assistants and voice reorder, Netflix speech/music detection, Meta SeamlessM4T). No Alexa, Siri or wake-word entry [12].
- ByteByteGo / Aminian, Exponent, Educative, Hello Interview: no dedicated speech chapter confirmed. Candidates apply the generic framework (see Chapter 1). (assumption)
- Open-source production toolkits act as the "solution key": WeNet [9], NeMo [10], openWakeWord [11], Whisper [8].

Requirements & scale

Dimension	Value	Source
Functional	Wake word -> transcribe -> understand intent and slots -> execute skill -> spoken reply	[1] (assumption)
Secondary	Multi-language, far-field (3-5 m), barge-in, follow-up mode, speaker ID / personalization	[2] (assumption)
Devices	100M-500M devices. About 1B utterances/day (assumption)	(assumption)
QPS	About 10k average and 30-50k peak ASR streams. Each stream is long-lived over 2-10 s	(assumption)
Latency	Wake detect under 200 ms. Partial transcripts every 80-200 ms. End-of-speech to first TTS audio under 1 s	[10] (assumption)
Accuracy	WER 5-8% on assistant traffic. Wake word: FRR under 5%, FA under 0.5/hour (openWakeWord targets)	[11]
Power	Always-on detector runs on a DSP or low-power core at a few mW	[1]
Privacy	Audio stays on device until the trigger fires. Opt-in audio retention for training	[1] (assumption)
Vocabulary	Open vocabulary plus 100k+ contact, song and skill entities that need contextual biasing	[4] (assumption)

Diagram 1: End-to-end online serving path


Figure 27.1: Online path from microphone to spoken response (cascade architecture)



- Cascade = wake -> ASR -> NLU -> DM -> TTS. Each box can be swapped and A/B tested on its own.
- Two-pass on-device trigger with a server check follows the Apple "Hey Siri" design [1] [2].

Diagram 2: Offline training & data pipeline

Figure 27.2: Data flywheel for wake word, ASR and NLU models



- Federated learning or on-device personalization can replace raw-audio upload for privacy. (assumption)
- openWakeWord trains wake models on 100% synthetic TTS positives plus about 30k hours of negatives [11].

Diagram 3: Model architectures

Figure 27.3a: Streaming ASR (Conformer transducer, two-pass)




Figure 27.3b: Wake word detector and NLU heads





Diagram 4: Alternative - end-to-end / LLM speech assistant

Figure 27.4: Cascade vs. speech-LLM design



- Whisper is an encoder-decoder Transformer that handles transcription, translation, language ID and VAD as token tasks. Model sizes run from 39M to 1.55B parameters [8].
- A common hybrid: keep the on-device wake word and streaming ASR, and route long-tail queries that NLU rejects to an LLM. (assumption)

Data & labels

Model	Positive / label	Negative / hard negatives	Source of labels
Wake word	Utterances of "Alexa" / "Hey Siri" across accents and distances	TV, music, similar words ("election", "Alexis")	Accepted triggers + human audit, synthetic TTS [11]
ASR	Audio -> verbatim transcript	n/a	Human transcription, pseudo-labels from a teacher, weak labels
NLU	Utterance -> domain, intent, slot spans	Out-of-domain utterances	Annotators, grammar-generated data, user corrections
Endpointer	End-of-query frame	Mid-sentence pauses	Forced alignment of transcripts
Implicit	Task success, no rephrase within 30 s	Barge-in, "no, I said..."	Interaction logs (assumption)

Features

Stage	Features
Frontend	Log-mel filterbanks (80-dim), beamformed channel, AEC residual
Wake word	Frame posteriors, speaker embedding (d-vector), device playback state
ASR context	Contact list, recent media, installed skills, locale, device type (biasing)
NLU	Tokens, ASR confidence, n-best, previous turn intent, device capabilities, time
Skill ranking	Skill popularity, user history, entity match score, latency

Model choices

Component	Baseline	Advanced	Tradeoff
Wake word	GMM-HMM keyword / small DNN	DS-CNN two-stage + speaker verification [1] [2]	Size and power vs. false accepts
ASR	Hybrid DNN-HMM + n-gram LM + WFST	Streaming Conformer RNN-T + 2nd-pass rescorer [3] [4] [7] [13]	E2E is smaller and fits on device but is harder to bias
ASR (offline)	CTC encoder	Attention enc-dec (Whisper) [8]	Accuracy vs. no streaming
Unified	Separate streaming / full models	U2 / WeNet: one model, CTC + attention rescoring [9]	One model to maintain
NLU	Per-domain CRF + logistic regression	Joint BERT intent + slot, multi-task [16] [19]	Latency vs. accuracy
DM	Rules + state machine	Learned policy / LLM fallback	Control vs. coverage
TTS	Concatenative	Neural (Tacotron/FastSpeech + vocoder)	Naturalness vs. compute

Loss functions

Model	Loss
Augmentation	SpecAugment [14]; SSL pretraining (wav2vec 2.0 [15])
Wake word	Frame-level cross-entropy, or max-pooling loss over the keyword window
ASR	RNN-T loss (marginalizes over alignments). CTC as auxiliary. CE for the attention decoder. MWER fine-tuning
Distillation	KL(teacher logits, student logits) + RNN-T
NLU	CE(intent) + token CE or CRF NLL(slots), weighted sum
Speaker ID	GE2E / triplet loss on embeddings

Offline metrics

Component	Metric
Wake word	FRR at a fixed FA/hour (DET curve), detection latency
ASR	WER, entity/named-WER, sliced by accent, noise, far-field, domain. Real-time factor
Endpointer	EP50/EP90 latency, early-cutoff rate
NLU	Intent accuracy, slot F1, semantic error rate (SemER)
End-to-end	Task completion on replayed golden set, latency p50/p90/p99

Online metrics / A-B

Metric	Meaning
Task success / user satisfaction (predicted)	North star. Model-estimated from implicit signals
Rephrase / repeat rate	Proxy for ASR or NLU error
Barge-in / abandonment	Wrong or slow response
False wake rate per device-day	Privacy and annoyance guardrail

Metric	Meaning
Latency (user-perceived)	End-of-speech -> first audio
Engagement	Daily active devices, queries/device

Serving & latency budget

Step	Budget (assumption)	Where
Wake word stage 1 + 2	50-200 ms after end of keyword	Device DSP / AP
Network uplink	50-100 ms	Edge PoP
Streaming ASR	Partials in about 150 ms. Final 100-200 ms after endpoint	GPU/CPU pool. Batched streams
Endpointing	200-500 ms of trailing silence (adaptive)	Device or cloud
NLU + entity resolution	30-50 ms	CPU
DM + skill call	100-300 ms (third-party skill timeout)	Microservices
TTS first chunk	50-150 ms	GPU, streaming
Total	Under 1 s from end-of-speech to first audio	

- On-device ASR removes the network hop and works offline. Google shipped an all-neural on-device RNN-T recognizer for Gboard (2019, about 80 MB after quantization) [3] [4].
- NVIDIA Nemotron-3.5-ASR-Streaming (cache-aware FastConformer) exposes a tunable latency of 80 ms to 1 s and 240-2400 concurrent streams per H100 [10].

Monitoring

Signal	Alert on
WER on daily human-transcribed sample	Regression by locale or device
False wake rate	Spikes. A TV ad saying "Alexa" causes mass false wakes
Rephrase rate per intent	New intent failures or a catalog change
Latency p99 per stage	Drift caused by a skill or GPU saturation
Input drift	SNR distribution, language mix, new device firmware
Out-of-vocabulary entities	New song or celebrity names (biasing lists need refresh)

Failure modes

Failure	Mitigation
False accepts from media / ads	Cloud verifier, audio fingerprint blocklist of broadcast ads, speaker ID
Accent / dialect bias in WER	Slice metrics, targeted data collection, per-locale models
Rare entity misrecognition	Contextual biasing FST, personal LM, NLU fuzzy entity resolution
Early endpointing cuts the user off	Learned endpointer with a semantic completeness signal

Failure	Mitigation
ASR error cascades into wrong action	Pass n-best + confidence to NLU. Confirm destructive or purchase actions
Privacy incidents (accidental recordings)	On-device processing, retention limits, opt-in review
Cold start for new language	Multilingual pretrain + SSL, synthetic TTS data

Interviewer follow-ups

- How do you keep false wakes under X per day without hurting recall? Where does each stage run?
- Why use two-stage wake word detection instead of one larger model? What is the power budget?
- What happens when a TV ad says the wake word to millions of devices at once?
- Hybrid HMM vs. CTC vs. RNN-T vs. attention: which works for streaming, and why?
- How do you recognize a user's contact names or a song released yesterday (contextual biasing)?
- How do you decide the user has finished speaking (endpointing), and what does it trade off?
- What runs on device and what in the cloud? Offline mode? Model compression (int8, pruning, distillation)?
- How do you get labels at scale without transcribing everything? (Pseudo-labels, implicit feedback, SSL)
- How do you evaluate fairness across accents and dialects?
- How do you propagate ASR uncertainty into NLU?
- How would you add a new language with only 100 hours of labeled data?
- How do you A/B test an ASR model when the north-star metric is task success?
- How do you personalize to a household's voices while protecting privacy (federated learning)?
- Would you replace the cascade with a speech-LLM? Latency, cost and controllability?
- How do you scale GPU serving for long-lived streaming connections (stickiness, batching)?

Components often missed

Component	Why it matters	Source
Device arbitration	Several Echo devices hear one wake word; only the best-SNR device answers	(assumption)
Device-directed speech detection	Follow-up mode without the wake word needs a "talking to me?" classifier	(assumption)
Language ID	Picks the ASR model in multilingual homes	[5] [8]
Voice activity detection	Gates ASR compute and drives endpointing	[8]
Punctuation, casing, inverse text normalization	"set alarm for seven thirty" -> "7:30" before NLU and display	[10] (assumption)
Acoustic features and HMM/CTC basics	Portal syllabus asks for MFCCs, acoustic models, CTC	[5]

Component	Why it matters	Source
Streaming GPU capacity	Concurrent streams per GPU sets fleet size	[10]

Extra follow-ups: How do you pick which device answers when three Echos hear "Alexa"? How do you support follow-up questions without the wake word and without false accepts?

Portal comparison

Source	Framing	Distinctive emphasis
Apple ML Research (Hey Siri) [1] [2]	Voice trigger as the core problem	Two-pass on-device DNN, thresholds, speaker vector, false-trigger mitigation
Google Research / He et al. [3] [4]	On-device streaming ASR	RNN-T, quantization, latency vs. server models
OpenAI Whisper [8]	Single multitask model	Weak supervision at scale, robust offline transcription, not streaming
WeNet / NeMo [9] [10]	Production toolkits	Unified streaming/non-streaming, CTC + attention rescoring, latency knobs
openWakeWord [11]	Open wake word recipe	Frozen embedding backbone, synthetic positives, FA/hr and FRR targets
alirezadir / generic MLSD portals [5]	NLP topic list (speech recognition, chatbot, language ID)	Feature extraction, acoustic modeling, HMM, CTC; no end-to-end assistant design

References

1. "Hey Siri: An On-device DNN-powered Voice Trigger for Apple's Personal Assistant", Apple Machine Learning Research, 2017. https://machinelearning.apple.com/research/hey-siri (not re-fetched)
2. "Personalized Hey Siri", Apple Machine Learning Research, 2018. https://machinelearning.apple.com/research/personalized-hey-siri (not re-fetched)
3. "An All-Neural On-Device Speech Recognizer", Google AI Blog, 2019. https://ai.googleblog.com/2019/03/an-all-neural-on-device-speech.html (not re-fetched)
4. He et al., "Streaming End-to-end Speech Recognition For Mobile Devices", arXiv / ICASSP, 2018-2019. https://arxiv.org/abs/1811.06621 (not re-fetched)
5. alirezadir, "Machine-Learning-Interviews: ML System Design", GitHub, 2024. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (read 2026-10-14)
6. khangich, "machine-learning-interview", GitHub, 2023. https://github.com/khangich/machine-learning-interview (read 2026-10-14)
7. Gulati et al., "Conformer: Convolution-augmented Transformer for Speech Recognition", arXiv, 2020. https://arxiv.org/abs/2005.08100 (not re-fetched)
8. Radford et al., "Robust Speech Recognition via Large-Scale Weak Supervision" (Whisper), OpenAI / GitHub, 2022. https://github.com/openai/whisper (read 2026-10-14) and https://arxiv.org/abs/2212.04356 (not re-fetched)
9. WeNet, "Production First and Production Ready End-to-End Speech Recognition Toolkit", GitHub, 2021-2022. https://github.com/wenet-e2e/wenet (read 2026-10-14). WeNet 2.0 paper: https://arxiv.org/abs/2203.15455 (not re-fetched)

10. NVIDIA, "NeMo" (ASR: Parakeet, Canary, Nemotron-3.5-ASR-Streaming cache-aware FastConformer), GitHub, 2025-2026. https://github.com/NVIDIA/NeMo (read 2026-10-14)
11. dscripka, "openWakeWord", GitHub, 2023. https://github.com/dscripka/openWakeWord (read 2026-10-14)
12. Engineer1999, "A Curated List of ML System Design Case Studies" (Netflix speech/music detection, Meta SeamlessM4T, Walmart unified multi-task virtual-assistant model), GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies (read 2026-10-14)
13. Graves, "Sequence Transduction with Recurrent Neural Networks" (RNN-T), arXiv, 2012. https://arxiv.org/abs/1211.3711 (not re-fetched)
14. Park et al., "SpecAugment: A Simple Data Augmentation Method for ASR", arXiv, 2019. https://arxiv.org/abs/1904.08779 (not re-fetched)
15. Baevski et al., "wav2vec 2.0: A Framework for Self-Supervised Learning of Speech Representations", arXiv, 2020. https://arxiv.org/abs/2006.11477 (not re-fetched)
16. Chen et al., "BERT for Joint Intent Classification and Slot Filling", arXiv, 2019. https://arxiv.org/abs/1902.10909 (not re-fetched)
17. Netflix Tech Blog, "Detecting Speech and Music in Audio Content", 2023. https://netflixtechblog.com/detecting-speech-and-music-in-audio-content-afd64e6a5bf8 (listed in [12]; not re-fetched)
18. Meta AI, "SeamlessM4T: foundational multimodal model for speech translation", 2023. https://ai.meta.com/blog/seamless-m4t/ (listed in [12]; not re-fetched)
19. Walmart Global Tech, "A Unified Multi-task Model for Supporting Multiple Virtual Assistants in Walmart", Medium, 2022. https://medium.com/walmartglobaltech/a-unified-multi-task-model-for-supporting-multiple-virtual-assistants-in-walmart-2b077c2c96e (listed in [12]; not re-fetched)
20. Walmart Global Tech, "Voice Reorder Experience: add Multiple Product Items to your shopping cart", Medium, 2022. https://medium.com/walmartglobaltech/voice-reorder-experience-add-multiple-product-items-to-your-shopping-cart-59d20fc61797 (listed in [12]; not re-fetched)

28. Design a Machine Translation System (Google Translate)

> Prompt as usually given: "Design Google Translate: translate text between any two of N languages", or "Design a system that auto-translates user-generated content (reviews, posts, messages) into the viewer's language". Variants: "Translate a whole web page or document while keeping its formatting", "Add a low-resource language with almost no parallel data", "Real-time speech-to-speech translation", "Translate product listings for an e-commerce marketplace".

> Compilation note: in both the drafting and review runs the shared web-search budget was used up and only github.com resolved (arxiv.org, research.google, blog hosts and portal sites did not). Sources marked (fetched) were read directly; the review run re-read [10][15][16][21][22][24][25][26][27]. Sources marked (ch-ref) were verified in earlier chapters of this atlas. Sources marked (known; not fetched) are well-known papers or posts cited from prior knowledge; check them before relying on exact numbers. Scale numbers marked "typical assumption" are interview estimates, not published figures.

Company tags

Company	Basis	Production system it mirrors
Google	Builds Google Translate; published GNMT [1], zero-shot multilingual NMT [3], massively multilingual NMT [4] and the "next thousand languages" work [5]	Single multilingual Transformer/hybrid model, wordpieces, TPU serving, quantized inference
Meta	Builds feed/message translation; published M2M-100 [7] and NLLB-200 (200 languages, 54.5B MoE + distilled 1.3B/600M) [6][21]	Many-to-many model, distilled for serving, used for Facebook/Instagram/Wikipedia content
Amazon (AWS Translate), Microsoft (Translator), Apple (Translate app, on-device), DeepL	Ship MT products (tag reflects the product, not verified interview reports)	Same cascade: lang-ID -> segment -> NMT -> post-process
Airbnb, LinkedIn, Booking.com	Translate user-generated listings/reviews/posts in product (tag reflects the product; interview reports not verified)	Batch + on-demand translation of UGC with caching

Portal coverage.

Portal / source	What it covers for this problem	Link
ByteByteGo / Aminian & Sheng, "Generative AI System Design Interview"	Has a dedicated "Google Translate" chapter (encoder-decoder Transformer, tokenization, beam search, BLEU/METEOR, language detection) - from prior knowledge, not fetched [23]	[23]

Portal / source	What it covers for this problem	Link
alirezadir ML-Interviews	Lists "Machine Translation" / "Seq2seq models, NMT, Transformers" under NLP seq2seq tasks; links "MT for 1000 languages" [5] and NLLB under "Scaling data collection" [24]	[24]
Chip Huyen, ML Systems Design exercises	No MT exercise; closest is ex. 17 "predict the language a text is written in" (the lang-ID stage of this design) [25]	[25]
ByteByteGo "ML System Design Interview" (2023)	No MT chapter (11 chapters, all ranking/vision) [26]	[26]
Khang Pham, machine-learning-interview	No MT case study; RNN/seq2seq fundamentals only [27]	[27]
Hello Interview / Exponent / Educative	Generic MLSD/GenAI delivery framework applied to MT (requirements -> data -> model -> eval -> serving) [28][29][30]	[28] [29] [30]

Requirements & scale

Dimension	Value	Source
Functional	Translate text (and docs/web pages) between any pair of N languages; auto-detect source language; alternatives per phrase; user feedback ("suggest an edit")	[1][23]
Languages	100-250 languages -> 10k-60k directions; one model must cover all of them	Google 133 (2022) + 110 via PaLM 2 (2024); NLLB 200 [5] [6][31]
Traffic	~100B+ words/day reported for Google Translate (2016); assume ~50k-200k QPS peak of short segments	known; not fetched / typical assumption
Latency	p95 < 200-300 ms for a short sentence (interactive); documents can be async	typical assumption
Quality	Beat previous model on BLEU/chrF/COMET and human MQM/SxS per direction; no regressions on high-traffic pairs	[1][16][17]
Robustness	Keep named entities, numbers, markup, formatting; no hallucination; handle code-switching, typos	[1][4]
Safety	No added toxicity; gender-bias handling; profanity masking optional	typical assumption
Cost	GPU/TPU minutes dominate; cache hit rate 20-40% on popular segments	typical assumption
Freshness	New model monthly/quarterly; glossary/terminology updates live	typical assumption

Diagram 1 - Online serving path

Diagram 1. Online request path: lang-ID -> segment -> cache -> route -> NMT decode (candidates) -> QE re-rank -> post-process/policy -> response.




Diagram 2 - Offline data, training & evaluation loop

Diagram 2. Offline pipeline: mined + licensed + back-translated data -> filtering -> multilingual training -> distillation -> eval (auto + human) -> registry -> canary.




Diagram 3 - Model architecture

Diagram 3. Multilingual encoder-decoder Transformer with a target-language token (the Google/NLLB design), plus the decode loop.




Diagram 4 - Variant: LLM-based translation and low-resource expansion

Diagram 4. Hybrid system: fast NMT for most traffic; LLM path for hard/long/document context; low-resource languages bootstrapped from monolingual data (Google 1000-language recipe [5], NLLB [6]).



Data & labels

Source	Volume (typical)	Label quality	Notes
Licensed / curated parallel (UN, EU, subtitles, books)	10M-1B pairs for high-resource pairs	High	Domain skew (legal, formal)
Web-mined bitext (sentence-embedding alignment)	Billions of pairs	Medium/noisy	Needs alignment-score + lang-ID filtering [4][6]
Back-translated monolingual	Unlimited	Synthetic source, real target	Sampled BT beats beam BT; tag `<BT>` [9]
Human post-edits / "suggest an edit"	Small	High but adversarial risk	Use for eval + fine-tune after vetting
Implicit signals (copy, share, re-query, edit distance)	Huge	Weak	Proxy labels for QE / online metrics
Human ratings (MQM, side-by-side)	Thousands per direction	Gold	Eval only; expensive [17]
Benchmark sets (FLORES-200, NLLB-MD, Toxicity-200)	~1-3k sentences per language	Gold	Held-out eval; decontaminate web data against them [21]

Features / inputs

Input	Use
Source subword tokens (BPE / SentencePiece)	Encoder input [8][10]
Target-language token `<2xx>`	Selects output language in one shared model [3]
Detected source language + confidence	Routing; ambiguity handling
Domain / formality / glossary tags	Controlled generation, terminology constraints
Document context (previous sentences)	Pronouns, consistency (doc-level variant)

Input	Use
Markup / entity placeholders	Preserved and restored after decode
User locale, app surface	Routing, gender/formality defaults

Model choices (baseline -> advanced)

Stage	Model	Pros	Cons
Baseline 0	Phrase-based SMT	Interpretable, small data ok	Poor fluency; replaced by NMT [1]
Baseline 1	Seq2seq LSTM + attention (GNMT: 8+8 layers, wordpieces) [1]	Big quality jump (~60% fewer errors vs PBMT on some pairs)	Sequential, slow training
Standard	Transformer encoder-decoder [2]	Parallel training, SOTA quality; hybrids (Transformer enc + RNN dec) used in production [19]	Quadratic attention on long docs
Scale	One multilingual model with <2xx> token [3][4]	Transfer to low-resource, zero-shot, one deployment	Capacity dilution ("curse of multilinguality") for high-resource pairs
Capacity	Sparse MoE (NLLB 54.5B) [6]	More capacity at same FLOPs	Serving memory, load balancing
Serving	Distilled student, deep-encoder / shallow-decoder, int8 [11][20][22]	3-10x cheaper, small quality loss	Extra training stage
Frontier	LLM translation (prompted / fine-tuned); Google used PaLM 2 to add 110 languages [31]	Doc context, style control, rare phenomena	Cost, latency, hallucination/omission
Decoding	QE re-rank or MBR over n-best/samples (COMET-MBR with CometKiwi QE) [15]	Higher human-rated quality than beam top-1	N x scoring cost; metric overfitting

Loss / objectives

Objective	Where	Notes
Token cross-entropy, label smoothing 0.1	Main NMT training	Teacher forcing [2]
MoE load-balance auxiliary loss	MoE layers	Prevents expert collapse [6]
Sequence-level KD (train on teacher beam output)	Student	Simpler targets, enables greedy decode [11]
Denoising / MASS-style objective	Monolingual data, low-resource	[5]
Minimum-risk training / RL on BLEU or COMET	Optional fine-tune	Watch metric gaming
QE regression (MSE vs DA/MQM scores)	QE re-ranker	CometKiwi-style [15]

Offline metrics

Metric	Type	Use / caveat
BLEU (sacreBLEU)	n-gram overlap	Standard, reproducible signatures; weak correlation at high quality [12][13]
chrF / chrF++	char n-gram	Better for morphologically rich languages; FLORES/NLLB headline [6]
COMET	Neural, reference-based	Best correlation with humans in WMT; ship/no-ship [14] [18]
BLEURT	Neural, reference-based	Google-trained metric [16]
CometKiwi / QE	Reference-free	Runtime re-rank, monitoring of live traffic [15]
MQM / side-by-side human eval	Human	Final gate on top directions [17]
Added-toxicity rate (Toxicity-200 word lists)	Rules	Catches toxicity introduced by the model, per language [21]
Targeted test suites	Rules	Numbers, named entities, gender, toxicity, hallucination, omission

Online metrics / A-B

Metric	Signal
Copy / share rate of output	Usefulness
Re-query / edit rate, "suggest edit" rate	Dissatisfaction proxy
Thumbs up/down rate	Explicit quality
Session length, follow-up searches	Engagement
p50/p95 latency, error rate, cost per 1k chars	Guardrails
Live QE score distribution per pair	Quality drift without references
UGC variant: engagement on translated posts/reviews	Downstream value

Serving & latency budget (p95 ~250 ms short segment; typical assumption)

Step	Budget	Technique
Gateway + auth	10 ms	
Lang-ID + segmentation + masking	5-10 ms	fastText-style classifier, rules
Cache / translation memory lookup	5 ms	Key includes model version
Queue + dynamic batching	10-30 ms	Bucket by length and pair
Encoder	10-20 ms	int8/fp16/bf16 or AWQ int4, layer fusion, padding removal, batch reordering [22]
Beam decode (k=4, ~20 tokens)	60-120 ms	KV cache, shallow decoder, speculative decoding
QE re-rank n-best	15-30 ms	Small QE model; skip for cached/high-confidence
Post-process + policy	5-10 ms	Detok, restore entities, filters

Other: per-pair model tiers; on-device small models for offline mode (Apple/Google offline packs); async batch pipeline for documents and UGC backfills.

Monitoring

What	How
Quality drift per language pair	Live QE scores, sampled human eval weekly
Input drift	Lang-ID mix, length, script, new slang/entities
Hallucination / omission	Length-ratio alarms, attention coverage, QE outliers
Toxicity / bias incidents	Classifier on outputs, user reports
Latency / cost	p95 by pair and tier, GPU utilization, cache hit rate
Feedback poisoning	Rate-limit and cluster suspicious "suggest edit" submissions

Failure modes

Failure	Mitigation
Hallucination on short/odd input (repeats, unrelated text)	QE gate, copy-through for untranslatable strings, length-ratio check
Omission of clauses	Coverage checks, QE, MBR decoding
Wrong source language (code-switching, short text)	Lang-ID confidence threshold, show "Detected X" with override
Named entities / numbers mistranslated	Placeholder masking, constrained decoding
Gender bias ("the doctor" -> masculine)	Gender-specific alternatives shown to user
Low-resource pairs poor quality	Pivot through English, BT, multilingual transfer [4][5]
Off-target language (zero-shot outputs wrong language)	Target-lang check on output, more direct-pair data [3][7]
Test-set contamination from web mining	Decontaminate against FLORES/WMT sets
Toxic or adversarial training data	Toxicity filtering in data pipeline [6]

Interviewer follow-ups

- One multilingual model vs one model per pair: what breaks at 200 languages (N^2 models)?
- How does the target-language token enable zero-shot translation, and when does it fail?
- How do you get training data for a language with almost no parallel text?
- Why sample (not beam) when generating back-translation data?
- BLEU went up but users complain: which metrics and human evals do you trust and why?
- How do you evaluate quality on live traffic with no reference translations?
- How do you hit p95 < 250 ms at 100k QPS? Batching, distillation, quantization, caching.
- How do you preserve HTML/markup, numbers and named entities?
- How do you handle gender ambiguity and bias in the output?

- How do you detect and prevent hallucinations and omissions?
- When would you route to an LLM instead of the NMT model, and how do you cap cost?
- How do you use "suggest an edit" feedback safely (spam, poisoning)?
- How would you add document-level context or formality control?
- How do you roll out a new model without regressing any of 10k+ directions?
- Speech-to-speech variant: cascade (ASR -> MT -> TTS) vs direct model tradeoffs?
- Offline mode: how do you fit a pair model on a phone (size, int8, vocab) and keep it fresh?
- When is MBR / QE re-ranking worth N-times scoring cost, and how do you avoid metric gaming? [15]
- How do you measure added toxicity across 200 languages? [21]

Portal comparison

Portal / source	Framing	Emphasis	Gap
ByteByteGo GenAI book, "Google Translate" chapter [23]	GenAI system: encoder-decoder Transformer	Tokenization, training stages, beam search, BLEU/METEOR, language detection, serving	Light on multilingual data mining and MoE
alirezadir ML-Interviews [24]	MT as a core NLP seq2seq topic	Seq2seq, NMT, Transformers; links 1000-language scaling paper [5]	Topic list only, no worked design
Chip Huyen exercises [25]	Language identification exercise	The lang-ID front-end only	No MT design
Google papers/blogs [1][3][4][5]	Real system	GNMT, zero-shot <2xx> token, massively multilingual, 1000 languages	Research framing, little serving infra
Meta NLLB [6][21]	Real system, open models	Data mining, MoE, distillation, FLORES-200, NLLB-MD, Toxicity-200	Not an interview framework
Generic MLSD frameworks (Hello Interview, Exponent, Educative) [28][29][30]	6-step framework	Requirements -> data -> model -> eval -> serving -> monitoring	No MT-specific depth

References

1. Y. Wu et al. (Google), "Google's Neural Machine Translation System: Bridging the Gap between Human and Machine Translation", arXiv, 2016. https://arxiv.org/abs/1609.08144 (known; not fetched)
2. A. Vaswani et al., "Attention Is All You Need", NeurIPS / arXiv, 2017. https://arxiv.org/abs/1706.03762 (known; not fetched)
3. M. Johnson et al. (Google), "Google's Multilingual Neural Machine Translation System: Enabling Zero-Shot Translation", TACL / arXiv, 2016. https://arxiv.org/abs/1611.04558 (known; not fetched)
4. N. Arivazhagan et al. (Google), "Massively Multilingual Neural Machine Translation in the Wild: Findings and Challenges", arXiv, 2019. https://arxiv.org/abs/1907.05019 (known; not fetched)

5. A. Bapna et al. (Google), "Building Machine Translation Systems for the Next Thousand Languages", arXiv, 2022. https://arxiv.org/abs/2205.03983 (link verified via alirezadir repo, fetched)
6. NLLB Team (Meta), "No Language Left Behind: Scaling Human-Centered Machine Translation", arXiv, 2022. https://arxiv.org/abs/2207.04672 (known; not fetched; model facts confirmed in [21])
7. A. Fan et al. (Meta), "Beyond English-Centric Multilingual Machine Translation" (M2M-100), JMLR / arXiv, 2020. https://arxiv.org/abs/2010.11125 (known; not fetched)
8. R. Sennrich, B. Haddow, A. Birch, "Neural Machine Translation of Rare Words with Subword Units" (BPE), ACL / arXiv, 2016. https://arxiv.org/abs/1508.07909 (known; not fetched)
9. S. Edunov et al., "Understanding Back-Translation at Scale", EMNLP / arXiv, 2018. https://arxiv.org/abs/1808.09381 (arXiv id confirmed in fairseq README, fetched: https://github.com/facebookresearch/fairseq/blob/main/examples/backtranslation/README.md)
10. T. Kudo, J. Richardson, "SentencePiece: A simple and language independent subword tokenizer and detokenizer", EMNLP / arXiv, 2018. https://arxiv.org/abs/1808.06226 (known; not fetched); code: https://github.com/google/sentencepiece (fetched)
11. Y. Kim, A. M. Rush, "Sequence-Level Knowledge Distillation", EMNLP / arXiv, 2016. https://arxiv.org/abs/1606.07947 (known; not fetched)
12. K. Papineni et al., "BLEU: a Method for Automatic Evaluation of Machine Translation", ACL, 2002. https://aclanthology.org/P02-1040/ (known; not fetched)
13. M. Post, "A Call for Clarity in Reporting BLEU Scores" (sacreBLEU), WMT / arXiv, 2018. https://arxiv.org/abs/1804.08771 (known; not fetched)
14. R. Rei et al., "COMET: A Neural Framework for MT Evaluation", EMNLP / arXiv, 2020. https://arxiv.org/abs/2009.09025 (known; not fetched)
15. Unbabel, "COMET" repository (CometKiwi reference-free QE: wmt22-cometkiwi-da, wmt23-cometkiwi-da-xl/xxl; comet-mbr re-ranking), GitHub, 2020-2024. https://github.com/Unbabel/COMET (fetched)
16. Google Research, "BLEURT: Learning Robust Metrics for Text Generation" repository, GitHub, 2020. https://github.com/google-research/bleurt (fetched)
17. M. Freitag et al. (Google), "Experts, Errors, and Context: A Large-Scale Study of Human Evaluation for Machine Translation" (MQM), TACL / arXiv, 2021. https://arxiv.org/abs/2104.14478 (known; not fetched)
18. T. Kocmi et al. (Microsoft), "To Ship or Not to Ship: An Extensive Evaluation of Automatic Metrics for Machine Translation", WMT / arXiv, 2021. https://arxiv.org/abs/2107.10821 (known; not fetched)
19. M. X. Chen et al. (Google), "The Best of Both Worlds: Combining Recent Advances in Neural Machine Translation" (RNMT+, hybrid), ACL / arXiv, 2018. https://arxiv.org/abs/1804.09849 (known; not fetched)
20. J. Kasai et al., "Deep Encoder, Shallow Decoder: Reevaluating Non-autoregressive Machine Translation", ICLR / arXiv, 2020. https://arxiv.org/abs/2006.10369 (known; not fetched)
21. Meta AI, "fairseq - No Language Left Behind (nllb branch)": NLLB-200 MoE 54.5B, dense 3.3B/1.3B, distilled 1.3B/600M; FLORES-200, NLLB-MD, Toxicity-200 benchmarks, GitHub, 2022. https://github.com/facebookresearch/fairseq/tree/nllb (fetched)

22. OpenNMT, "CTranslate2: fast inference engine for Transformer models" (FP16/BF16/INT16/INT8, AWQ INT4, layer fusion, padding removal, batch reordering), GitHub, 2019-2025. https://github.com/OpenNMT/CTranslate2 (fetched)
23. A. Aminian, H. Sheng, "Generative AI System Design Interview" (incl. "Google Translate" chapter), ByteByteGo, 2024. https://bytebytego.com/ (site root; chapter content from prior knowledge, not fetched)
24. alirezadir, "ML System Design" (NLP topics: "Machine Translation - Seq2seq models, NMT, Transformers"; "MT for 1000 languages" link), Machine-Learning-Interviews, GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (fetched)
25. C. Huyen, "Machine Learning Systems Design: Exercises" (ex. 17 language identification), GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md (fetched)
26. ByteByteGo, "ml-bytebytego: Reference materials for ML System Design Interview" (chapter list; no MT chapter), GitHub, 2023. https://github.com/ByteByteGoHq/ml-bytebytego (fetched)
27. K. Pham, "machine-learning-interview", GitHub, 2021. https://github.com/khangich/machine-learning-interview (fetched; no MT case study)
28. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery (ch-ref)
29. Exponent, "Introduction to the ML System Design Interview" (course), tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
30. Educative, "The 6-step ML SD framework" (Grokking the ML System Design Interview), educative.io, 2025. https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/the-6-step-ml-sd-framework (ch-ref)
31. Google, "110 new languages are coming to Google Translate" (PaLM 2), The Keyword blog, 2024. https://blog.google/products/translate/google-translate-new-languages-2024/ (known; not fetched)

29. Design a Document Understanding / Invoice Extraction System (OCR + Layout + LLM)

> How the prompt is usually worded: "Design a system that takes scanned or digital invoices (PDF, photo, email attachment) and returns structured fields (vendor, invoice number, dates, totals, tax, line items), then posts them to an ERP / accounts-payable system." Variants: "Receipt scanning for expense reports", "Intelligent document processing (IDP) like AWS Textract or UiPath Document Understanding", "KYC / ID-document extraction", "Parse PDFs into Markdown/JSON for an LLM pipeline", "Insurance-claim form digitization".

> Source note (review pass, 2026-10): github.com and raw.githubusercontent.com resolved; uber.com, docs.aws.amazon.com, docs.uipath.com and arxiv.org were blocked by the proxy.
>
> - (fetched): read in a fetch run.
> - (listed in [n]): the URL appears in curated list [n], which was fetched.
> - (ch-ref): verified in ch. 01 or ch. 24 of this atlas.
> - (not opened): canonical URL cited from memory. Check before relying on it.
>
> Numbers marked "approx." or "assumption" are typical values, not sourced figures.

Company tags

Company / context	Basis	Production system it mirrors
Amazon (AWS)	Owns Textract, whose AnalyzeExpense API returns normalized invoice/receipt fields and line items [10] (fetched). AWS IDP reference pipeline: classify -> extract -> enrich -> validate -> human review [9] (fetched)	Textract + Comprehend + A2I + Bedrock (Diagram 4)
Uber	"Uber's Real-Time Document Check" for driver documents [13] (listed in [7]). A GenAI invoice-processing post [11] is cited but not opened	Document verification; OCR -> LLM -> review
Google	Research on extracting structured data from templatic documents (form-like invoices) [14] (listed in [8])	Candidate generation + field scoring
Microsoft	LayoutLMv2 / LayoutLMv3 / TrOCR / DiT research [3][5][6] (fetched)	Layout-aware transformer extractor
Dropbox	Built an in-house OCR pipeline (word detector + word recognizer) and indexed text from billions of images [15][16] (listed in [7][8])	OCR stage of Diagram 1
Scribd	Document-type classification and metadata extraction [17][18][30] (listed in [7][8])	Classifier + extractor stages

Company / context	Basis	Production system it mirrors
Nanonets	Receipt information extraction with graph convolutional networks [8] (listed in [8])	Graph-based KIE over OCR boxes
UiPath	Sells Document Understanding; product docs describe a digitize -> classify -> extract -> validate -> train loop [26] (not opened)	Human validation station feeds retraining
Any "GenAI system design" loop	alirezadir lists "OCR/Text recognition system" under CV prompts and LLM content-processing systems under GenAI [1] (fetched)	OCR + LLM structured output

Portal coverage

Portal / source	What it covers	Link
alirezadir ML-Interviews	"OCR/Text recognition system" listed as a CV MLSD prompt. 9-step MLSD template	[1]
Chip Huyen, MLSD exercises	Closest exercise: #23, QA that "extract[s] an answer from a large collection of documents" [2] (fetched)	[2]
Educative (Grokking MLSD / GenAI SD)	6-step framework. GenAI course covers document / multimodal pipelines (case title not verified)	[20][21]
ByteByteGo / Aminian & Xu	No dedicated invoice chapter verified. Reuse the 7-step framework and the GenAI book's multimodal chapters	[22]
IGotAnOffer, Exponent, Hello Interview	Generic MLSD / GenAI delivery frameworks used to structure this answer	[23][24] [25]
Curated case-study lists	Engineer1999 and eugeneyan/applied-ml index the OCR, layout and extraction posts above	[7][8]

Requirements & scale


Dimension	Value	Source
Functional	Ingest PDF, TIFF, JPG, email. Classify doc type. Extract header fields + line-item table. Normalize (dates, currency, vendor ID). Validate. Send low-confidence docs to human review. Post to ERP	[9][10]
Output schema	~20-40 header fields + N line items (description, qty, unit price, amount, tax code)	typical assumption; CORD has 5 superclasses / 42 subfields [12]
Volume	1M docs/day at a large enterprise or BPO. ~12 docs/s average, ~50/s peak. ~2-3 pages per doc	assumption
Latency	Async batch: p95 under 60 s end-to-end. Sync API (receipt app): p95 under 3-5 s per page	assumption
Accuracy	Field-level F1 of 0.95 or higher on key fields. Totals exact-match 99%+ after validation. Straight-through-processing (STP) rate 70-90%	typical target
Vendors / templates	100k+ vendors, long-tail layouts. New layouts appear daily	assumption
Languages	50-100+ scripts. Handwriting is a minority but real	assumption; PP-OCR covers 50-109 languages [19]

Dimension	Value	Source
Compliance	PII and bank details: encryption, retention limits, audit trail, region pinning	typical assumption
Cost	Target under $0.01-0.05 per page. LLM calls only where needed	assumption

Diagram 1 - Online serving path (ingest -> digitize -> classify -> extract -> validate -> route)

The ranking template maps as follows: candidate generation = OCR tokens and regions, ranking = field tagging / LLM extraction, re-ranking/policy = validation rules and confidence routing.


Figure 29.1 - End-to-end online architecture of an invoice extraction service



- The "feature store" of classic MLSD maps to the **vendor store** (vendor master data, per-vendor layout priors, past corrected values). The "model store" maps to the **model registry + prompt store**.
- Confidence routing is the policy layer. Thresholds are set per field and per tenant to hit a target precision on auto-posted fields.
- The AWS reference pipeline has the same stages: classification, extraction, enrichment, validation, human review (A2I) [9].

Diagram 2 - Offline training & data pipeline (corrections -> labels -> train -> eval)


Figure 29.2 - Offline data flywheel for document extraction



- Human corrections are the main label source. This is UiPath's "Digitize -> Classify -> Extract -> Validate -> Train" loop [26] (not opened).
- Split by vendor, not by document. A random split leaks layouts and inflates F1.

Diagram 3 - Model architecture: OCR + layout transformer, and the OCR-free / LLM variant

Figure 29.3 - Three extractor families and their inputs/outputs



- (A) is cheap, fast and well calibrated. It needs labeled token data per field.
- (B) avoids OCR errors and is a single model. Reported CORD score about 91 (91.3 TED accuracy for the v2 checkpoint) and 0.7-1.2 s per image [4] (fetched).
- (C) is zero/few-shot and handles new vendors and fields. It costs more per page, can hallucinate values, and its confidence is harder to calibrate.

Diagram 4 - Real system: AWS intelligent document processing (IDP) reference pipeline

Figure 29.4 - AWS IDP reference flow (Textract + Comprehend + A2I + Bedrock) [9][10]



AnalyzeExpense output contract (what to mirror in your own schema) [10]

Element	Content
Summary fields	Normalized `Type` per field (e.g. `TOTAL`, `VENDOR_NAME`); unmatched keys returned as `OTHER` with the raw label
Line-item groups	Each row is an `EXPENSE_ROW` with `ITEM`, `QUANTITY`, `PRICE`, `UNIT_PRICE`, `PRODUCT_CODE`
Grounding	Page number + bounding box + polygon for every label and value
Confidence	Per label and per value; drives the A2I routing threshold
Sibling APIs	AnalyzeID for ID documents (KYC variant); `analyze_expense` / `analyze_id` wrappers in Textractor [31]

- Keep the raw key text next to the normalized type. Reviewers and the label builder need it.
- The AWS repo also ships an agentic variant on Bedrock AgentCore with Analyzer, Matcher, Extractor, Validator and Troubleshooter agents, plus a Bedrock Prompt Flows variant with per-document flows and A2I review [9] (fetched).
- Uber's GenAI invoice post [11] (not opened) describes the same shape: OCR -> LLM extraction -> human-in-the-loop UI. Its numbers are not verified here.

Data & labels

Source	Label type	Notes
Human review corrections	Gold field values (+ bbox)	Best signal. Biased toward low-confidence docs
ERP posted values	Weak labels (value only)	Map to OCR tokens with fuzzy match. Noisy for repeated numbers

Source	Label type	Notes
Annotation campaigns	Boxes + field + relation labels	Costly. Spend on new vendors and active-learning samples
Public sets	FUNSD [27], CORD [12], SROIE [28], DocVQA [29], RVL-CDIP	Pretraining / benchmarks. Domain shift vs real AP invoices
Synthetic	Rendered templates, SynthDoG [4]	Cold start, rare fields, new languages

Features / signals

Group	Examples
Text	OCR tokens, subword embeddings, OCR confidence per word
Layout	Normalized bbox, reading order, block/table/cell IDs, distance to keywords ("Total", "IVA")
Visual	Page patches, font size/bold, lines and table rulings, logos, stamps
Document	Doc type, page index, language, born-digital vs scanned, DPI / blur score
Vendor priors	Vendor ID (from VAT ID / IBAN / logo), known field positions, past values, currency
Context	PO data for matching, tenant schema, expected tax rates

Model choices (baseline -> advanced)

Stage	Baseline	Advanced	Tradeoff
OCR	Tesseract / cloud OCR	DB detector + CRNN / TrOCR [6], PP-OCRv5 (109-language rec) / PP-OCRv6 (1.5M-34.5M params, 50 langs) [19]	Accuracy on noisy scans vs cost; handwriting needs TrOCR-class models
Layout / tables	Heuristic line detection	DiT / LayoutLMv3 layout, table-structure model, PP-StructureV3 [19]	Better tables vs GPU cost
Classifier	TF-IDF + logistic regression on OCR text	DiT / LayoutLMv3 fine-tuned [5][3]	Visual cues matter for look-alike docs
KIE	Regex + per-vendor templates	LayoutLMv2/v3 token tagging [3][5]; graph models [8]	Templates break on layout drift; learned models generalize
End-to-end	n/a	Donut (OCR-free) [4]; PaddleOCR-VL-1.6, 0.9B params [19]	One model, but harder grounding and long-page limits
GenAI	Prompted LLM on OCR text	VLM with JSON schema + few-shot from vendor store; fine-tuned small VLM	Zero-shot new fields vs hallucination, cost, latency
Router	Single model	Cheap model first, escalate low-confidence docs to LLM	Cuts cost; adds complexity

Loss functions

Model	Loss
Text detector (DB)	BCE / dice on probability + threshold maps
Text recognizer	CTC (CRNN) or cross-entropy (TrOCR seq2seq)
Classifier	Cross-entropy, class-weighted for rare doc types
Token tagger	Token-level cross-entropy over BIO tags (+ CRF optional)

Model	Loss
Relation head	Binary cross-entropy over key-value / row-membership pairs
Donut / VLM SFT	Next-token cross-entropy on the serialized JSON
Pretraining (LayoutLMv3)	MLM + masked image modeling + word-patch alignment [3]

Offline metrics

Metric	Use
CER / WER	OCR quality, sliced by scan quality and language
Field-level precision / recall / F1, exact match	Core KIE metric. Report per field (total matters more than memo)
Normalized edit distance / ANLS	Partial credit for strings (DocVQA style)
Line-item table F1 (row + cell)	Hardest part of invoices
Tree edit distance accuracy	Donut-style JSON output [4]
STP rate at precision >= 99%	Business-aligned: share of docs that skip review
Calibration (ECE), coverage-risk curve	Needed to set routing thresholds
Unseen-vendor slice	Generalization to new layouts

Online metrics / A-B

Metric	Notes
Straight-through-processing rate	Primary. Docs auto-posted without human touch
Human touch time per doc, fields corrected per doc	Reviewer effort
Post-posting error rate	Errors found later in ERP (payment errors, duplicate payments)
End-to-end latency, backlog age	SLA
Cost per page	OCR + GPU + LLM tokens

- A-B by tenant or by document hash. Shadow mode first: compare to the champion on the same docs.
- Guardrail: auto-posted precision must not drop, even if STP rises.

Serving & latency budget (async, p95 under 60 s per 3-page doc; sync receipt p95 under 5 s)

Step	Budget (approx.)	Notes
Ingest, split, render	0.5-2 s	CPU pool
OCR + layout	0.3-1 s / page	GPU batch; skip OCR for born-digital text
Classify	50-100 ms	Small model
KIE layout transformer	100-300 ms / page	GPU, batch by page
LLM / VLM extraction (if routed)	2-10 s	Only for low-conf or new vendors; constrained JSON

Step	Budget (approx.)	Notes
Validate + normalize	under 100 ms	Rules + vendor lookups
Queueing slack	rest	Autoscale on queue depth

Monitoring

Signal	Alert on
OCR confidence distribution, blank-page rate	Scanner or upload change
Per-field confidence and review rate	Drift for a vendor or tenant
Correction rate per field / vendor	New layout or model regression
Validation failure rate (sum checks)	Line-item extraction breaking
Doc-type mix, language mix	New document types arriving
LLM: JSON parse failures, invented values (not in OCR text), token cost	GenAI-specific
Latency, queue depth, GPU use	SLA risk

Failure modes

Failure	Mitigation
Poor scans, skew, stamps over text	Pre-processing, quality score, ask for re-upload
Multi-page tables, line items spanning pages	Page-level context, table stitching, sum validation
Look-alike numbers (invoice # vs PO # vs order #)	Key-value relation head, vendor priors, LLM with bbox citation
Locale formats (1.234,56 vs 1,234.56; DD/MM vs MM/DD)	Locale from vendor country, currency, validation
LLM hallucinated fields	Require the value to appear in OCR text; abstain; route to review
Prompt injection in document text	Treat doc text as data; schema-constrained output; no tool calls from doc content
New vendor layouts	VLM fallback, active learning, fast few-shot via vendor store
Duplicate / fraudulent invoices	Hash + fuzzy dedupe, bank-detail-change alerts
Label noise from weak ERP labels	Confidence-weighted loss, audit samples

Interviewer follow-ups

- How do you get training labels without a big annotation budget? (review corrections, ERP weak labels, synthetic data)
- OCR + layout model vs OCR-free (Donut) vs VLM/LLM: which do you pick and why?
- How do you extract line-item tables, including tables that span pages?
- How do you produce a calibrated per-field confidence from an LLM?
- How do you set thresholds for auto-posting vs human review? What is the business metric?
- How do you handle a vendor never seen before?
- How do you stop the LLM from inventing a total or a bank account number?

- How do you split train/test to avoid layout leakage?
- How do you handle multi-document PDFs (invoice + PO + delivery note in one file)?
- How would you cut cost per page by 10x?
- How do you support 50+ languages and handwriting?
- How do you detect drift when a big vendor changes its template?
- How do you protect PII and bank details, and meet data-residency rules?
- What do you log so reviewer corrections become training data?
- Buy (Textract / Document AI style API) or build? When does a managed API's fixed schema (`OTHER` fields) stop being enough?
- How do you keep raw key text, normalized type and bbox together so every field is auditable? [10]

Portal comparison

Portal / source	Framing	Emphasis	Distinctive point
alirezadir ML-Interviews [1]	"OCR/Text recognition system" as a CV prompt; 9-step template	Problem framing, data, metrics, serving	Generic template applied to OCR
Chip Huyen MLSD exercises [2]	Document QA exercise (#23), not extraction	Retrieval over documents	Bridge to RAG (ch. 24)
Educative / ByteByteGo [20][22]	Framework-driven; no dedicated invoice case verified	Step-by-step MLSD	Reuse CV + GenAI chapters
AWS IDP repo [9]	Production reference, not interview-shaped	Classify -> extract -> enrich -> validate -> A2I	Agentic validator / matcher variant
UiPath DU [26]	Product framework	Digitize -> Classify -> Extract -> Validate -> Train	Human validation station feeds retraining
Model repos (unilm, Donut, PaddleOCR) [3][4][19]	Model-level	Architecture, benchmarks	Concrete numbers: FUNSD F1 0.92 (v3 large), CORD ~91 (Donut)

References

1. alirezadir, "ML System Design" (CV and GenAI prompt lists), GitHub, 2026. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (fetched)
2. C. Huyen, "Machine Learning Systems Design: Exercises", GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md (fetched)
3. Y. Huang et al., "LayoutLMv3: Pre-training for Document AI with Unified Text and Image Masking", ACM Multimedia, 2022. https://github.com/microsoft/unilm/tree/master/layoutlmv3 (fetched); https://arxiv.org/abs/2204.08387 (linked from repo)
4. G. Kim et al., "OCR-free Document Understanding Transformer" (Donut), ECCV, 2022. https://github.com/clovaai/donut (fetched); https://arxiv.org/abs/2111.15664 (linked from repo)

5. Microsoft, "unilm" repo (LayoutLMv2, DiT and other Document AI models), GitHub, 2024. https://github.com/microsoft/unilm (fetched); LayoutLMv2 https://arxiv.org/abs/2012.14740 (linked from repo); DiT https://arxiv.org/abs/2203.02378 (linked from repo)
6. M. Li et al., "TrOCR: Transformer-based Optical Character Recognition with Pre-trained Models", arXiv, 2021. https://arxiv.org/abs/2109.10282 (linked from repo)
7. Engineer1999, "A Curated List of ML System Design Case Studies", GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies (fetched)
8. E. Yan, "applied-ml" (includes Nanonets "Information Extraction from Receipts with Graph Convolutional Networks", 2021), GitHub, 2024. https://github.com/eugeneyan/applied-ml (fetched); https://nanonets.com/blog/information-extraction-graph-convolutional-networks/ (listed in [8])
9. AWS Samples, "aws-ai-intelligent-document-processing", GitHub, 2025. https://github.com/aws-samples/aws-ai-intelligent-document-processing (fetched)
10. AWS, "Analyzing Invoices and Receipts" (Textract AnalyzeExpense), Amazon Textract Developer Guide, 2024. https://docs.aws.amazon.com/textract/latest/dg/invoices-receipts.html; GitHub source of the page https://github.com/awsdocs/amazon-textract-developer-guide/blob/master/doc_source/invoices-receipts.md (fetched, raw)
11. Uber Engineering, "Advancing Invoice Processing Efficiency at Uber with GenAI", uber.com, 2024. https://www.uber.com/blog/advancing-invoice-processing-with-genai/ (not opened)
12. S. Park et al., "CORD: A Consolidated Receipt Dataset for Post-OCR Parsing", NeurIPS Document Intelligence Workshop, 2019. https://github.com/clovaai/cord (fetched); https://openreview.net/pdf?id=SJl3z659UH (linked from repo)
13. Uber Engineering, "Uber's Real-Time Document Check", uber.com, 2022. https://www.uber.com/en-GB/blog/ubers-real-time-document-check/ (listed in [7])
14. Google AI, "Extracting Structured Data from Templatic Documents", Google AI Blog, 2020. https://ai.googleblog.com/2020/06/extracting-structured-data-from.html (listed in [8])
15. Dropbox, "Creating a Modern OCR Pipeline Using Computer Vision and Deep Learning", dropbox.tech, 2017. https://dropbox.tech/machine-learning/creating-a-modern-ocr-pipeline-using-computer-vision-and-deep-learning (listed in [8])
16. Dropbox, "Using Machine Learning to Index Text from Billions of Images", dropbox.tech, 2018. https://dropbox.tech/machine-learning/using-machine-learning-to-index-text-from-billions-of-images (listed in [8])
17. Scribd, "Identifying Document Types at Scribd", tech.scribd.com, 2021. https://tech.scribd.com/blog/2021/identifying-document-types.html (listed in [7][8])
18. Scribd, "Information Extraction at Scribd", tech.scribd.com, 2021. https://tech.scribd.com/blog/2021/information-extraction-at-scribd.html (listed in [7])
19. PaddlePaddle, "PaddleOCR" (PP-OCRv5/v6, PP-StructureV3, PaddleOCR-VL), GitHub, 2026. https://github.com/PaddlePaddle/PaddleOCR (fetched)
20. Educative, "The 6-step ML SD framework" (Grokking the ML System Design Interview), educative.io, 2025. https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/the-6-step-ml-sd-framework (ch-ref)
21. Educative, "Grokking the Generative AI System Design", educative.io, 2025. https://www.educative.io/courses/generative-ai-system-design (ch-ref)

22. ByteByteGo, home page (ML and Generative AI System Design Interview courses), bytebytego.com, 2025. https://bytebytego.com (ch-ref)
23. IGotAnOffer, "Generative AI System Design Interview", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/generative-ai-system-design-interview (ch-ref)
24. Exponent, "Introduction to the ML System Design Interview", tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
25. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery (ch-ref)
26. UiPath, "Document Understanding" documentation (framework: digitize, classify, extract, validate, train), docs.uipath.com, 2025. https://docs.uipath.com/document-understanding (not opened)
27. G. Jaume et al., "FUNSD: A Dataset for Form Understanding in Noisy Scanned Documents", arXiv, 2019. https://arxiv.org/abs/1905.13538 (not opened)
28. Z. Huang et al., "ICDAR2019 Competition on Scanned Receipt OCR and Information Extraction" (SROIE), arXiv, 2021. https://arxiv.org/abs/2103.10213 (not opened)
29. M. Mathew et al., "DocVQA: A Dataset for VQA on Document Images", arXiv, 2020. https://arxiv.org/abs/2007.00398 (not opened)
30. Scribd, "Categorizing user-uploaded documents", tech.scribd.com, 2021. https://tech.scribd.com/blog/2021/categorizing-user-uploaded-documents.html (listed in [7])
31. AWS Samples, "amazon-textract-textractor" (analyze_expense, analyze_id), GitHub, 2025. https://github.com/aws-samples/amazon-textract-textractor (fetched)

30. Design Demand Forecasting for Inventory (Amazon Supply Chain, Instacart)

> Sourcing note: web search was exhausted and company-blog / portal domains were blocked in this review run. Every company tag and portal row below was re-checked against cloned copies of the GitHub indexes [23]-[27], which list the cited posts and papers ([1]-[22], [30], [31]) under forecasting or availability. Rows marked "typical" are standard interview assumptions, not quoted numbers.

Company tags

Company (reported / mirrored)	Evidence	Ref
Amazon	Multi-horizon quantile forecaster (MQ-RNN -> MQ-CNN -> MQ-Transformer) feeds buying; RL ordering policy research	[1][2][4][5]
Amazon (AWS)	DeepAR, GluonTS, Chronos: open probabilistic forecasting models	[3][6][8]
Instacart	Real-time item availability (P(in stock)) for hundreds of millions of items; lost-demand modeling	[9][10][11] [30][31]
DoorDash	Ensemble time-series forecasting; holiday cascade model; supply/demand balance	[12][13][14] [15]
Uber	Forecasting platform; LSTM extreme-event forecasting	[16][17]
Zalando, Ocado, Mercado Libre, Grubhub, Lyft	Item / order-volume demand forecasting in production	[18][19][20] [21][22]

Portals that cover the problem:

Portal	Coverage	Ref
eugeneyan/applied-ml	"Forecasting" section: Amazon, Uber, DoorDash, Grubhub, Lyft, LinkedIn Greykite	[23]
Engineer1999 ML case-study list	Zalando, DoorDash (ensemble, holiday), Grubhub, Ocado, Mercado Libre, Lyft forecasting; 4 Instacart availability posts; Instacart lost demand	[24]
khangich/machine-learning-interview (Khang Pham)	Per-company applied-ML index; forecasting posts under Uber, Airbnb, Gojek	[25]
alirezadir/Machine-Learning-Interviews	No forecasting chapter; framework covers split-by-time, seasonality/trend features, batch vs online prediction	[26]
chiphuyen/machine-learning-systems-design; "Designing ML Systems"	Generic framework; no forecasting chapter; batch vs online prediction, drift	[27] [29]

Requirements & scale

Dimension	Value	Source
Functional	Forecast demand per (SKU, location, day) for horizon 1-52 weeks; output quantiles (P10/P50/P90)	[1][2]
Functional (downstream)	Turn forecast into order quantity / safety stock; flag stock-outs	[5]
Functional (Instacart)	P(item in stock at store now) for every item-store, used at search/checkout	[9][10]
Scale (Amazon)	Hundreds of millions of products, many fulfillment centers	[1] typical
Scale (Instacart)	Hundreds of millions of item-store pairs	[9]
Freshness	Batch: daily/weekly reforecast; availability: minutes	typical
Latency	Batch job hours (SLA before buying run); availability lookup < 10 ms from cache	typical
Non-functional	Calibrated uncertainty, cold-start for new SKUs, robustness to holidays/shocks (COVID)	[1][13] [15]
Business objective	Minimize holding + lost-sales cost; maximize in-stock rate	[5]

Diagram 1 - End-to-end architecture

Diagram 1. Serving path: batch forecasts -> inventory policy -> orders, plus real-time availability lookups.




Diagram 2 - Offline training & data pipeline

Diagram 2. Training loop with censored-demand correction, backtesting, and feedback.




Diagram 3 - Model architecture

Diagram 3. MQ-CNN style multi-horizon quantile forecaster (Amazon) [1][2].





Diagram 4 - Variant: forecast-then-optimize vs end-to-end policy

Diagram 4. Two-stage (classic) vs Amazon's deep RL buying policy [5].



Data & labels

Item	Choice	Note
Label	Units demanded per SKU x location x day/week	Sales are censored when out of stock
Censoring	Mask stock-out periods, or impute via availability model	Instacart availability doubles as a censoring signal [9]
Lost demand	Estimate demand never observed (searches / carts for out-of-stock items) and add back to labels	Instacart "Modeling the unseen" [31]
Hierarchy	SKU -> category -> dept; store -> region -> national	Reconcile (top-down / MinT)
Splits	Rolling-origin backtests by time, never random	[26]
Cold start	New SKUs: attribute/text embeddings, similar-item priors	[18]
Anomalies	Remove one-off bulk orders, data outages; tag holidays	[13]

Features

Group	Examples
Lags / windows	Demand lag 1/7/14/28/364, rolling mean/std, trend, days since last sale
Calendar	Day of week, holidays, paydays, seasonality Fourier terms
Price & promo	Current/planned price, discount depth, promo flag, competitor price
Inventory	On-hand, stock-out flags, in-transit, vendor lead time
Item static	Category, brand, size, embeddings, life-cycle stage
Location	Store/FC id embedding, region, demographics, weather
Real-time (availability)	Shopper "found / not found", last restock time, store feed recency [9][10]

Model choices

Stage	Model	Pros	Cons
Baseline	Seasonal naive, moving avg, ETS/ARIMA per series	Simple, interpretable	No cross-series learning, poor on sparse SKUs
Classic ML	GBDT (LightGBM) on lag features, quantile objective	Strong on tabular (M5 winners [28])	Separate model per horizon/quantile
Deep global	DeepAR (autoregressive, likelihood)	Probabilistic, cold-start via sharing [3]	Error accumulation over long horizons
Deep multi-horizon	MQ-RNN / MQ-CNN / MQ-Transformer	Direct multi-horizon quantiles, Amazon prod [1][2][4]	Larger infra
Attention	Temporal Fusion Transformer	Interpretable variable selection [7]	Heavier training
Foundation	Chronos (pretrained on many series)	Zero-shot for new series [6]	Less domain covariates
Ensemble	Stack of above (DoorDash ELITE-style)	Robust	Ops complexity [12]
Decision	Newsvendor / RL policy	Optimizes cost directly [5]	Needs simulator

Loss

Loss	When
Pinball (quantile) loss, summed over horizons	Default for inventory (asymmetric costs) [2]
Negative log-likelihood (neg. binomial / Tweedie)	Count, intermittent demand (DeepAR) [3]
Tweedie / Poisson in GBDT	Zero-inflated SKUs
Cost-weighted loss (holding vs lost-sale)	Align with business critical ratio
Policy reward (RL)	End-to-end buying [5]

Offline metrics

Metric	Why
wQL / CRPS	Quality of full distribution
WAPE / MAPE / sMAPE	Point accuracy, volume-weighted
Bias (mean error)	Systematic over/under-forecasting
Quantile coverage (P90 hit rate ~ 90%)	Calibration
Simulated in-stock rate & holding cost	Decision-level backtest
Sliced: new SKUs, holidays, promos, long tail	Catch hidden failures

Online metrics / A-B

Metric	Note
In-stock rate / fill rate	Primary customer outcome
Lost sales, substitution rate	Instacart: items not found [9]
Inventory holding cost, days of supply	Over-stock signal

Metric	Note
Waste / spoilage (perishables)	Grocery
Delivery promise accuracy	Downstream
Test design	Store/FC-level or SKU-cluster randomization, switchback; long tests (weeks)

Serving & latency budget

Path	Budget	Mechanism
Nightly forecast run	~2-4 h for all series	Distributed batch (Spark/Ray), partition by SKU (typical)
Policy / order generation	~1 h	Vectorized newsvendor per SKU-node
Availability lookup	< 10 ms p99	Precomputed scores in KV cache [10]
Availability refresh	Minutes	Stream updates from shopper events [10]
What-if planner query	~1 s	Cached forecasts + on-demand re-solve

Monitoring

Signal	Action
Rolling WAPE / bias vs backtest	Alert, roll back champion
Input drift (price feed, missing stores)	Block run, fallback to last forecast
Regime shift (COVID, viral item)	Event-triggered retrain, shorter windows [15]
Override rate by planners	Proxy for trust
Stock-out and overstock outliers	Root-cause by SKU

Failure modes

Failure	Mitigation
Censored demand -> forecast spiral down	Stock-out masking, availability-aware labels
Holiday / promo spikes	Holiday features, cascade model [13]
New SKU cold start	Hierarchical priors, similar-item embeddings, foundation model [6]
Intermittent demand	Count likelihoods, Croston-style baselines
Feedback loop (forecast drives stock drives sales)	Treat as causal; simulate policy [5][22]
Data outages	Freshness checks, last-good fallback
Overconfident intervals	Calibrate quantiles, conformal adjustment

Interviewer follow-ups

- How do you get true demand when sales are censored by stock-outs?
- Point vs probabilistic forecast: why quantiles for inventory? Which quantile to order at?

- One global model vs per-series models: tradeoffs at 100M+ series?
- How do you forecast for a brand-new SKU or a new store?
- How do you handle promotions and price changes you plan in the future (known covariates)?
- How would you reconcile forecasts across SKU / category / region hierarchy?
- How do you backtest correctly without leakage?
- How did COVID-like shocks break models, and how would you retrain? [15]
- How do lead time and vendor uncertainty enter the order quantity?
- How do you A/B test a forecasting model when inventory takes weeks to react?
- How does forecasting interact with pricing (forecast depends on price)? [22]
- Batch vs real-time: when would Instacart-style availability need streaming? [10]
- How would you use an RL policy instead of forecast-then-optimize? [5]
- How do you handle intermittent, long-tail SKUs?
- How do you estimate demand you never observed (lost demand from out-of-stock searches)? [31]
- How do you keep the availability score fresh for 200M+ item-store pairs without rescoring everything? [30]
- What latency/compute budget for the nightly run, and how to parallelize?

Portal comparison

Portal	Framing	Model emphasis	Distinctive
Amazon Science / papers [1][2][5]	Multi-horizon quantile forecast feeding buying	MQ-CNN, MQ-Transformer, RL policy	Decision-aware, forking sequences
Instacart engineering [9][10][11]	P(in stock) per item-store in real time	ML scorer + streaming signals	Serving architecture, consistency
DoorDash engineering [12][13][14]	Order/supply volume forecasting	Ensemble stacking, holiday cascade	Ensemble ops, holiday handling
eugeneyan applied-ml / Khang Pham [23][25]	Case-study index	Points to Uber, Amazon, Lyft posts	Reading list, not a walkthrough
alirezadir / Chip Huyen [26][27][29]	Generic MLSD framework	Time-based splits, batch prediction, drift	Applies to any problem

References

1. "The history of Amazon's forecasting algorithm", Amazon Science, 2021. https://www.amazon.science/latest-news/the-history-of-amazons-forecasting-algorithm
2. Wen, R. et al., "A Multi-Horizon Quantile Recurrent Forecaster", arXiv, 2017. https://arxiv.org/abs/1711.11053
3. Salinas, D. et al., "DeepAR: Probabilistic Forecasting with Autoregressive Recurrent Networks", arXiv, 2017. https://arxiv.org/abs/1704.04110
4. Eisenach, C. et al., "MQTransformer: Multi-Horizon Forecasts with Context Dependent and Feedback-Aware Attention", arXiv, 2020. https://arxiv.org/abs/2009.14799
5. Madeka, D. et al., "Deep Inventory Management", arXiv, 2022. https://arxiv.org/abs/2210.03137

6. Ansari, A. F. et al., "Chronos: Learning the Language of Time Series", arXiv, 2024. https://arxiv.org/abs/2403.07815
7. Lim, B. et al., "Temporal Fusion Transformers for Interpretable Multi-horizon Time Series Forecasting", arXiv, 2019. https://arxiv.org/abs/1912.09363
8. "GluonTS: Probabilistic time series modeling in Python", GitHub (awslabs), 2024. https://github.com/awslabs/gluonts
9. "How Instacart Modernized the Prediction of Real Time Availability for Hundreds of Millions of Items While Saving Costs", Instacart Tech Blog, 2023. https://tech.instacart.com/how-instacart-modernized-the-prediction-of-real-time-availability-for-hundreds-of-millions-of-items-59b2a82c89fe
10. "Instacart's Item Availability Architecture: Solving for scale and consistency", Instacart Tech Blog, 2023. https://tech.instacart.com/instacarts-item-availability-architecture-solving-for-scale-and-consistency-f5661acb20a6
11. "How Instacart's Item Availability Evolved Over the Pandemic", Instacart, 2023. https://www.instacart.com/company/how-its-made/how-instacarts-item-availability-evolved-over-the-pandemic/
12. "How DoorDash Built an Ensemble Learning Model for Time Series Forecasting", DoorDash Engineering Blog, 2023. https://doordash.engineering/2023/06/20/how-doordash-built-an-ensemble-learning-model-for-time-series-forecasting/
13. "How DoorDash Improves Holiday Predictions via Cascade ML Approach", DoorDash Engineering Blog, 2023. https://doordash.engineering/2023/08/31/how-doordash-improves-holiday-predictions-via-cascade-ml-approach/
14. "Managing Supply and Demand Balance Through Machine Learning", DoorDash Engineering Blog, 2021. https://doordash.engineering/2021/06/29/managing-supply-and-demand-balance-through-machine-learning/
15. "Retraining Machine Learning Models in the Wake of COVID-19", DoorDash Engineering Blog, 2020. https://doordash.engineering/2020/09/15/retraining-ml-models-covid-19/
16. "Forecasting at Uber: An Introduction", Uber Engineering Blog, 2018. https://eng.uber.com/forecasting-introduction/
17. "Engineering Extreme Event Forecasting at Uber with Recurrent Neural Networks", Uber Engineering Blog, 2017. https://eng.uber.com/neural-networks/
18. "Deep Learning based Forecasting: a case study from the online fashion industry" (Zalando), arXiv, 2023. https://arxiv.org/abs/2305.14406
19. "Finding the sweet spot", Ocado Group, 2021. https://careers.ocadogroup.com/blogs/careers-blogs/our-technologies/finding-the-sweet-spot
20. "Marketplace Forecasting: Sales or Demand? Why not both?", Mercado Libre Tech (Medium), 2021. https://medium.com/mercadolibre-tech/global-time-series-forecasting-models-for-item-level-demand-and-sales-forecasts-in-our-marketplace-aee2956957ae
21. "Forecasting Grubhub Order Volume At Scale", Grubhub Bytes, 2022. https://bytes.grubhub.com/forecasting-grubhub-order-volume-at-scale-a966c2f901d2
22. "Causal Forecasting at Lyft (Part 1)", Lyft Engineering Blog, 2022. https://eng.lyft.com/causal-forecasting-at-lyft-part-1-14cca6ff3d6d
23. Eugene Yan, "applied-ml", GitHub, 2023. https://github.com/eugeneyan/applied-ml
24. Engineer1999, "A Curated List of ML System Design Case Studies", GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies
25. Khang Pham, "machine-learning-interview" applied ML index, GitHub, 2021. https://github.com/khangich/machine-learning-interview/blob/master/appliedml.md

26. alirezadir, "Machine-Learning-Interviews" (MLSD notes), GitHub, 2024. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md
27. Chip Huyen, "machine-learning-systems-design" exercises, GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md
28. "M5 Forecasting - Accuracy", Kaggle, 2020. https://www.kaggle.com/competitions/m5-forecasting-accuracy
29. Chip Huyen, "Designing Machine Learning Systems", O'Reilly, 2022. https://www.oreilly.com/library/view/designing-machine-learning/9781098107956/
30. "Predicting the real-time availability of 200 million grocery items in US & Canada stores", Instacart Tech Blog. https://tech.instacart.com/predicting-real-time-availability-of-200-million-grocery-items-in-us-canada-stores-61f43a16eafe
31. "Modeling the unseen", Instacart Tech Blog. https://tech.instacart.com/modeling-the-unseen-6a51c9a02430

31. Design Anomaly Detection for Metrics/Monitoring and Transactions

> Sourcing note: for this chapter the shared web-search budget had run out and most portal and company-blog domains could not be reached from the build environment. The facts below come from pages that were fetched (GitHub repos: Microsoft anomalydetector, Twitter AnomalyDetection, Yahoo EGADS, LinkedIn luminol, Numenta NAB, Meta Kats, curated case-study indexes, interview repos). References marked "(not fetched)" are well-known engineering posts/papers whose URLs were not re-checked. A later review pass also found every external host blocked (proxy 403), so no URL was re-fetched in that pass either; unverifiable company tags and portal claims were removed or marked. Rows marked "typical assumption" are interview-standard estimates.

Company tags

Company (reported / mirrored)	Evidence	Ref
Microsoft	Built it: SR-CNN service (KDD 2019); multivariate MTAD-GAT; Azure Anomaly Detector (retiring 1 Oct 2026)	[1][2][27] [28]
LinkedIn	Built it: ThirdEye business-metric monitoring + RCA; luminol; isolation forest	[3][4][5]
Uber	Built it: Argos real-time outage alerts; Risk Entity Watch (fraud anomalies)	[6][7]
Twitter / X	Built it: Seasonal Hybrid ESD (S-H-ESD) open-source detector	[8][9]
Yahoo	Built it: EGADS generic time-series anomaly framework (KDD 2015)	[10][11]
Netflix	Built it: RAD, robust-PCA outlier detection on big data	[12]
Meta	Built it: Kats toolkit (CUSUM, outlier, trend, change-point detectors)	[13]
Grab, Capital One, Walmart	Graph anomaly fraud; app-failure detection; sensor-anomaly forecasting	[14][15] [16]

Portals that cover the problem:

Portal	Coverage	Ref
alirezadir/Machine-Learning-Interviews	No named chapter; MLSD template covers drift detection, alarms, metric dashboards	[17]
chiphuyen/machine-learning-systems-design	Exercise 2: labelled fraud vs safe card purchases (transaction variant)	[18]
khangich/machine-learning-interview	"Fraud detection (TBD)" placeholder	[19]
Engineer1999 curated case studies	Indexes Uber, Grab, Walmart anomaly posts; Capital One, Microsoft incident mgmt	[20]
Educative Grokking ML System Design	Generic 6-step framework; no anomaly chapter verified (fraud variant unconfirmed)	[21]
ByteByteGo (Aminian & Xu)	No dedicated chapter; monitoring covered inside every chapter	[22]

Portal	Coverage	Ref
Exponent, Hello Interview	Generic MLSD frameworks applied to detection problems	[23] [24]
Atlas cross-ref	Ch. 14 (payment fraud) for the supervised transaction path	ch. 14

Requirements & scale

Dimension	Value	Source
Functional	Ingest millions of time series (KPIs, infra metrics); flag anomalous points/windows	[1][3]
Functional	Severity score + anomaly window + peak timestamp (not just a binary flag)	[5]
Functional	Group related alerts; root-cause hints (dimension drill-down, correlated metrics)	[3][5]
Functional	Transaction mode: score each event, route to block / review / allow	[7][18]
Functional	User feedback (true/false alert) and per-metric sensitivity tuning	[1][3]
Non-functional	Detection delay: seconds-1 min (infra), <100 ms per event (transactions)	[2] / typical
Non-functional	Low alert fatigue: precision prioritized for paging; recall for fraud	typical
Scale	1M-100M series, 1-60 s granularity => 100k-10M points/s	typical assumption
Scale (Microsoft)	Service handles millions of time series across Microsoft products	[2] (not fetched)
Labels	Very sparse (<0.1-1% anomalous); mostly unlabeled; delayed fraud labels	[2][7]
Seasonality	Daily/weekly cycles, holidays, deploy-driven level shifts	[8][10]

Diagram 1: Online detection path (streaming)

Diagram 1 - End-to-end online architecture for metric and transaction anomaly detection




Diagram 2: Offline training & data pipeline

Diagram 2 - Offline pipeline: history, labels, model fitting, evaluation, deployment




Diagram 3: Model architecture

Diagram 3 - Forecast-residual detector with SR-CNN scorer (metrics) and hybrid event scorer (transactions)





Diagram 4: Real-world system (ThirdEye-style monitoring + RCA)

Diagram 4 - Business-metric monitoring with dimension drill-down root-cause analysis (LinkedIn ThirdEye / luminol pattern)



Data & labels

Source	Label type	Notes
Incident tickets / postmortems	Weak positive windows	Coarse timing; map to affected series
On-call ack / "not an anomaly" clicks	Explicit feedback	Biased to alerted points only (no FN signal) [3]
Synthetic injection (spikes, level shifts, dips)	Strong, free	Used to train SR-CNN without manual labels [1][2]
Chargebacks, analyst reviews	Delayed positive (fraud)	30-90 day delay; censoring for recent data [7]
Public benchmarks (NAB, Yahoo S5)	Labelled windows	NAB: 58 series, real + artificial [25][10]

Features

Group	Examples	Path
Raw window	Last w points, normalized	Metrics
Decomposition	Trend, seasonal, residual (STL); spectral saliency	Metrics
Calendar	Hour-of-day, day-of-week, holiday, deploy flag	Both
Cross-series	Sibling dimension values, correlated metric deltas	Metrics / RCA
Multivariate window	N correlated metrics x w steps (input to MTAD-GAT)	Metrics [27]
Velocity	Txns per card/device/IP in 1m/1h/24h	Transactions
Entity history	Typical amount, merchant category, geo distance	Transactions
Graph	Shared device/payment instrument, community anomaly	Transactions [14]

Model choices (baseline -> advanced)

Stage	Model	Pros	Cons
0	Static thresholds / rules	Simple, explainable	Breaks with seasonality, high fatigue
1	Rolling mean + k-sigma, week-over-week	Cheap, per-series	Sensitive to outliers in baseline
2	Robust stats: median/MAD, S-H-ESD	Handles seasonality, robust [8] [9]	Batch-ish, tuning max_anoms
3	Forecast + residual (Holt-Winters, Prophet, EGADS TMM/ADM)	Interpretable band [10]	One model per series; cold start
4	Robust PCA (RAD), isolation forest	Multivariate, unlabeled [12][4]	Hard to explain per point
5	SR-CNN (global, trained on synthetic)	No labels, one model for millions [1][2]	Needs good injection design
6	LSTM/Transformer AE or forecaster	Complex patterns, multivariate	Cost, drift, needs GPUs
7	Supervised GBDT/DNN on events (fraud)	Best precision with labels [18]	Label delay, misses novel attacks
8	Meta-learner choosing algo per series	Scales tuning [13]	Extra system complexity
9	Multivariate GAT (MTAD-GAT: feature + time attention, forecast + reconstruction)	Catches cross-metric anomalies; per-variable attribution [27]	Group of metrics must be pre-defined; GPU training

Loss

Model	Loss / objective
Forecaster	MSE or quantile (pinball) loss for prediction band
SR-CNN	Cross-entropy on injected-anomaly labels per point [2]
Autoencoder	Reconstruction MSE on (mostly) normal data
Isolation forest	None (path length => score)
Supervised fraud	Weighted BCE / focal loss for class imbalance; cost-sensitive threshold

Offline metrics

Metric	Why
Precision / recall / F1 on points	Baseline [1]
Point-adjusted or delay-aware F1	Segment counts if detected within delay k of start [1][30]
Caveat: point-adjust inflation	PA can make random scores look strong; report PA%K or raw F1 too [29]
NAB score (Standard, Low-FP, Low-FN profiles)	Rewards early detection, penalizes FP [25]
Detection delay (median, p95)	Time-to-detect matters for outages
Alerts per series per week	Proxy for alert fatigue
PR-AUC, recall @ fixed FPR, $ loss caught	Transaction / fraud mode

Online metrics / A-B

Metric	Notes
MTTD (mean time to detect)	vs. incidents discovered by humans/customers
% incidents caught by detector first	Coverage of real outages
Alert precision (ack rate as true)	From on-call feedback [3]
Pages per on-call shift	Fatigue guardrail
Fraud $ loss, false decline rate, review queue size	Transaction mode
A-B design	Shadow mode + interleaved alert rules; can't randomize outages, so backtest + shadow

Serving & latency budget

Step	Metrics path	Transaction path
Ingest + aggregate	10-60 s roll-up window	5 ms
Feature fetch	Window from in-memory state	10-20 ms (online store)
Model scoring	<1 ms per series per tick (vectorized)	5-20 ms
Threshold + post-process	~1 s batching	2 ms
Total	under 1-2 min point-to-alert	under 50-100 ms

Step	Metrics path	Transaction path
Scaling trick	Partition by series id; batch thousands of series per CPU call	Cache entity aggregates

Monitoring (of the detector itself)

Signal	Action
Alert volume spike across many series	Likely upstream data issue; global suppression
Missing data / late points	Distinguish "no data" from "drop to zero" (no-data check in aggregator, Diagram 1)
Score distribution drift	Recalibrate thresholds
Feedback FP rate per series	Auto-lower sensitivity or switch algo
Fraud: score PSI, approval rate	Rollback model

Failure modes

Failure	Mitigation
Alert storms from one root cause	Group by topology/dimension; RCA [3][5]
Seasonality / holiday false positives	Seasonal decomposition, holiday calendar, wo1w/wo2w baselines
Level shift after deploy keeps alerting	Change-point detection, adapt baseline quickly [13]
Anomaly contaminates baseline	Robust stats (median/MAD), exclude flagged points from fit [8]
Cold-start series	Global model (SR-CNN), borrow from sibling series
Sparse / low-volume metrics	Poisson models, larger windows, minimum-volume gates
Adversaries adapt (fraud)	Unsupervised + supervised hybrid; graph features [14]
Feedback only on alerted points	Periodic random audits for false negatives

Interviewer follow-ups

- How do you handle daily/weekly seasonality and holidays without per-series manual tuning?
- Supervised vs unsupervised: what if you have almost no labels?
- How do you generate training labels (synthetic injection, incident logs) and avoid leakage?
- How do you evaluate when anomalies are segments, not points (point-adjusted F1, delay)?
- How do you reduce alert fatigue and group alerts from one root cause?
- How would you do root-cause analysis across dimensions (country x platform x version)?
- How do you scale to 10M series with one model vs one model per series?
- How do you distinguish a real drop from missing/late data?
- What happens after a deploy causes a permanent level shift?
- How do you set thresholds per series; how do you let users tune sensitivity?
- For transactions: how do you combine rules, supervised model and anomaly score?

- How do you handle delayed fraud labels and feedback loops from blocked transactions?
- How do you monitor the detector itself (meta-monitoring)?
- Multivariate: detect anomalies across correlated metrics jointly, and attribute to a variable? [27]
- Why can point-adjusted F1 overstate a detector, and what would you report instead? [29]
- Build vs buy: what if the managed service you depend on is retired? [28]
- Can an LLM help summarize incidents / suggest root causes? [26]

Portal comparison

Portal / source	Framing	Model emphasis	Distinctive point
Educative Grokking MLSD [21]	Generic 6-step framework (no verified anomaly chapter)	Applied by candidate	Framework walk-through
Chip Huyen exercises [18]	Labelled fraud vs safe records	Supervised; class imbalance	Short prompt, open-ended
alirezadir MLSD template [17]	Monitoring section of every design	Drift detection via stats/hypothesis tests	Alarms on pipeline, metrics
Microsoft SR-CNN / MTAD-GAT [1][2][27]	Metric anomaly service at scale	SR + CNN (univariate); graph attention (multivariate)	No labels; delay-aware F1
LinkedIn ThirdEye / luminol [3][5]	Business KPI monitoring	Baselines + RCA correlation	Dimension drill-down, feedback UI
Twitter S-H-ESD / Yahoo EGADS [8][10]	Time-series outliers	Robust stats / forecast + threshold	Pluggable TMM + ADM modules

References

1. Microsoft, "anomalydetector: SR-CNN implementation", GitHub. https://github.com/microsoft/anomalydetector
2. H. Ren et al., "Time-Series Anomaly Detection Service at Microsoft", KDD 2019, arXiv, 2019. https://arxiv.org/abs/1906.03821 (not fetched)
3. LinkedIn Engineering, "Introducing ThirdEye: LinkedIn's Business-Wide Monitoring Platform", engineering.linkedin.com, 2019. https://engineering.linkedin.com/blog/2019/01/introducing-thirdeye--linkedins-business-wide-monitoring-platfor (not fetched)
4. LinkedIn Engineering, "Detecting and preventing abuse on LinkedIn using isolation forests", engineering.linkedin.com, 2019. https://engineering.linkedin.com/blog/2019/isolation-forest
5. LinkedIn, "luminol: anomaly detection and correlation library", GitHub. https://github.com/linkedin/luminol
6. Uber Engineering, "Identifying Outages with Argos, Uber Engineering's Real-Time Monitoring and Root-Cause Exploration Tool", uber.com, 2015. https://www.uber.com/blog/argos-real-time-alerts/ (not fetched)
7. Uber Engineering, "Risk Entity Watch: Using Anomaly Detection to Fight Fraud", uber.com. https://www.uber.com/en-IN/blog/risk-entity-watch/
8. Twitter, "AnomalyDetection (Seasonal Hybrid ESD) R package", GitHub, 2015. https://github.com/twitter/AnomalyDetection

9. Twitter Engineering, "Introducing practical and robust anomaly detection in a time series", blog.twitter.com, 2015. https://blog.twitter.com/engineering/en_us/a/2015/introducing-practical-and-robust-anomaly-detection-in-a-time-series (not fetched)
10. Yahoo, "EGADS: Extensible Generic Anomaly Detection System", GitHub. https://github.com/yahoo/egads
11. N. Laptev, S. Amizadeh, I. Flint, "Generic and Scalable Framework for Automated Time-series Anomaly Detection", KDD 2015. https://s.yimg.com/ge/labs/v2/uploads/kdd2015.pdf
12. Netflix Tech Blog, "RAD - Outlier Detection on Big Data", netflixtechblog.com, 2015. https://netflixtechblog.com/rad-outlier-detection-on-big-data-d6b0494371cc (not fetched)
13. Meta (Facebook Research), "Kats: toolkit to analyze time series data", GitHub. https://github.com/facebookresearch/Kats
14. Grab Engineering, "Unsupervised graph anomaly detection: Catching new fraudulent behaviours", engineering.grab.com. https://engineering.grab.com/graph-anomaly-model
15. Capital One Tech, "Automated detection, diagnosis & remediation of app failure", capitalone.com. https://www.capitalone.com/tech/machine-learning/automated-detection-diagnosis-remediation-of-application-failure/
16. Walmart Global Tech, "Forecast Anomalies in Refrigeration with PySpark & Sensor-data", Medium. https://medium.com/walmartglobaltech/forecast-anomalies-in-refrigeration-with-pyspark-sensor-data-195f23ae24e2
17. alirezadir, "ML System Design" (ml-system-design.md), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md
18. C. Huyen, "Machine Learning Systems Design - Exercises", GitHub. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md
19. K. Pham, "machine-learning-interview", GitHub. https://github.com/khangich/machine-learning-interview
20. Engineer1999, "A Curated List of ML System Design Case Studies", GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies
21. Educative, "The 6-step ML SD framework" (Grokking the ML System Design Interview), educative.io, 2025. https://www.educative.io/courses/grokking-the-machine-learning-system-design-interview/the-6-step-ml-sd-framework
22. ByteByteGo, "ml-bytebytego: references for Machine Learning System Design Interview", GitHub, 2023. https://github.com/ByteByteGoHq/ml-bytebytego
23. Exponent, "Introduction to the ML System Design Interview", tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro
24. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery
25. Numenta, "NAB: The Numenta Anomaly Benchmark", GitHub. https://github.com/numenta/NAB
26. Microsoft Research, "Large-language models for automatic cloud incident management", microsoft.com, 2023. https://www.microsoft.com/en-us/research/blog/large-language-models-for-automatic-cloud-incident-management/
27. H. Zhao et al., "Multivariate Time-series Anomaly Detection via Graph Attention Network" (MTAD-GAT, Microsoft), ICDM 2020. https://arxiv.org/abs/2009.02040 (not fetched)

28. Microsoft Learn, "What is Anomaly Detector?" (retirement notice: no new resources from 20 Sep 2023; service retired 1 Oct 2026), learn.microsoft.com. https://learn.microsoft.com/en-us/azure/ai-services/anomaly-detector/overview (not fetched)
29. S. Kim et al., "Towards a Rigorous Evaluation of Time-series Anomaly Detection", AAAI 2022. https://arxiv.org/abs/2109.05257 (not fetched)
30. H. Xu et al., "Unsupervised Anomaly Detection via Variational Auto-Encoder for Seasonal KPIs in Web Applications" (Donut; introduces point-adjust), WWW 2018. https://arxiv.org/abs/1802.03903 (not fetched)

32. Design Fake Review Detection and Review Ranking (Amazon, Yelp)

> Prompt as usually given: "Design a system that detects fake / incentivized / spam reviews on an e-commerce or local-business platform, and ranks the remaining reviews so the most helpful ones appear first." Variants: opinion-spam detection, fake reviewer / review-ring detection, "Most helpful" review ordering, Yelp "recommended vs. not recommended" reviews, app-store review fraud, LLM-generated review detection.
>
> Sourcing note: non-GitHub hosts (arxiv.org, acm.org, aaai.org, aboutamazon.com, yelp.com) could not be reached from the review sandbox and web search was exhausted. Tags: (fetched) = page read and claim checked. (repo-link) = URL listed verbatim in a fetched GitHub page. (ch-ref) = URL verified in another chapter. (known) = canonical page cited from memory, not re-fetched. No portal lists this exact prompt; company tags below are evidence of the system, not interview reports. "Typical assumption" numbers are interview estimates, not company disclosures.

Company tags

Company	Evidence	Notes	Source
Amazon	Mirrors it: Amazon review graph (upu, usu, uvu relations) is a standard fake-reviewer benchmark (CARE-GNN, DGL FraudAmazon)	Product reviews + "Most helpful" ordering; no Amazon production paper verified here	[1][3] [28]
Yelp	Mirrors it: YelpChi labels come from Yelp's own review filter ("not recommended")	Filter behavior studied externally [4]; embeddings blog is adjacent (not spam)	[4][5] [7][28]
Alibaba (Xianyu)	Built it: GAS - GCN-based spam review detection deployed on Xianyu second-hand marketplace	Best documented production "review spam" GNN	[8][9]
App-store review systems	Academic: FdGars detects fraudsters in an online app review system (WWW 2019 workshop)	No company tag claimed	[10]
Meta, LinkedIn, Pinterest	Adjacent only: integrity / spam systems cited by ByteByteGo ch. 5 and case-study lists, not review prompts	Same actor-graph + content-classifier pattern	[12] [13] [29] [30]

Portals that cover it

Portal	Treatment	Link
alirezadir Machine-Learning-Interviews	No dedicated review prompt; closest listed: "Harmful content / Spam detection", "Fraud detection", "Sentiment analysis", "Proximity service / Yelp"	[14]


Portal	Treatment	Link
ByteByteGo (Aminian & Xu, MLSDI) ch. 5	Harmful content detection template (multimodal, multi-task, harmful actors as follow-up) is the usual base	[15][16]
Educative "Grokking the ML Interview" / Khang Pham MLSD	Classification + ranking templates; reuse for detector + helpfulness ranker	[17][18] [19]
Chip Huyen MLSD exercises	Closest: fraud classification exercise with labelled records	[20]
Exponent, Hello Interview, IGotAnOffer, Patrick Halina	Generic MLSD frameworks only; no review-fraud prompt verified	[21][22] [23][24]
Engineer1999 case-study list	No review-fraud case; nearest are Pinterest spam clustering, LinkedIn viral spam, Whatnot GenAI trust & safety	[27]
safe-graph paper lists (academic)	Canonical graph-based review-spam methods (GAS, CARE-GNN, GraphConsis, FdGars)	[8][10] [25]

Requirements & scale

Dimension	Requirement	Source / note
Functional 1	Score every new review for fake / spam / incentivized / LLM-generated; actions: publish, hide ("not recommended"), hold for human review, remove + penalize account	Typical assumption
Functional 2	Detect fake reviewers and review rings (groups), retroactively remove reviews	[3][11]
Functional 3	Rank surviving reviews per product/business ("Most helpful", "Recommended") with recency, diversity, personalization	[4][6]
Non-functional	Precision first on removal (false removal hurts trust, legal risk); recall on rings; explainable decisions for appeals	Typical assumption
Review write QPS	~50-500 reviews/s peak (tens of millions/year)	Typical assumption
Review read QPS	~50k-200k review-page renders/s (ranking served from cache)	Typical assumption
Latency	Sync pre-publish check p99 < 200 ms; deep graph/LLM checks async in minutes; ranking read p99 < 50 ms	Typical assumption
Catalog / users	100M-1B products/businesses, 100M-500M reviewers, 1B+ historical reviews	Typical assumption
Label prevalence	Fake rate ~5-20% of submissions, highly skewed; YelpChi ~14.5% spam (commonly reported)	[5][7] (known)

Diagram 1 - Online architecture

Diagram 1: Write path (detect) and read path (rank) for reviews



- Read path: filter (status = published, not fake, language) -> rank (helpfulness model) -> re-rank (diversity of star ratings, recency, verified purchase boost, media) -> cache per item.
- Star rating aggregate recomputed only from trusted reviews (fake-adjusted average).

Diagram 2 - Offline training & data pipeline

Diagram 2: Labels, features, training, deployment and feedback loop




Diagram 3 - Model architecture

Diagram 3: Multi-signal fake review detector + helpfulness ranker



Diagram 4 - Real system: Xianyu GAS and review graphs

Diagram 4: Alibaba Xianyu GAS (GCN-based Anti-Spam) as reported in [8][9]



- Lesson: user-linked edges (rur) are highly homophilous; product-linked edges are mostly camouflaged, so relation-aware neighbor filtering (CARE-GNN) matters [1].

Data & labels

Source	Label type	Issue	Mitigation
Moderator decisions	Hard, high precision	Expensive, biased to flagged items	Active learning, uncertainty sampling
Platform filter output (e.g. Yelp not-recommended)	Proxy	Model learns its own past filter	Hold-out random audits
Paid-review stings / leaked review-farm lists	Hard positives, rings	Rare, bursty	Label propagation over graph
Account bans, deleted accounts	Weak, delayed	Label leakage, delay	Point-in-time joins
Helpful / unhelpful votes	Ranker label	Position bias, rich-get-richer	IPW, Bayesian smoothing, exploration slots
Synthetic LLM fakes	Augmentation	Distribution mismatch	Red-team generation per release

Features

Group	Examples
Text	Encoder embedding, length, sentiment extremity, duplicate/near-dup hash (MinHash), template phrases, LLM-perplexity / detector score
Reviewer behavior	Account age, review count, review burst per day, rating deviation from item mean, fraction 5-star, verified-purchase ratio
Item behavior	Review velocity spikes, rating distribution shift, seller-linked accounts
Network / device	Shared IP, device fingerprint, payment instrument, geo mismatch with business
Graph	GNN embeddings over review-user-item-device graph, co-review group density, ring membership
Ranking	Helpfulness votes (smoothed), media present, detail/aspect coverage, recency, reviewer reputation

Model choices

Stage	Baseline	Advanced	Tradeoff
Rules	Blocklists, velocity caps	Auto-generated rules from clusters	Fast, explainable; brittle
Review detector	Logistic regression / GBDT on behavior + n-grams	Transformer text + GBDT fusion, multi-task	Text alone weak vs. skilled writers
Reviewer / ring	Co-review frequent itemset mining	Hetero GNN (GAS, CARE-GNN, GraphConsis), dense-subgraph detection	Graph catches coordination; costly, async
LLM-generated	Perplexity heuristics	Fine-tuned detector + LM-embedding + GNN	Arms race, false positives on non-native writers

Stage	Baseline	Advanced	Tradeoff
Actor-level	Per-account aggregates	Temporal interaction embeddings over account action sequences (Facebook TIES)	Catches fake accounts before they review; needs event history [29]
Moderation assist	Manual queue triage	LLM classifier/explainer for queue items (Whatnot GenAI T&S pattern)	Faster triage + rationale for appeals; cost, prompt drift [30]
Ranker	Sort by helpful votes / Wilson score	LambdaMART / DNN with quality + trust features	Votes biased by position

Loss

Model	Loss
Detector	Weighted BCE or focal loss per head; multi-task sum with head weights
GNN	Node/edge BCE with relation-aware neighbor sampling; class-balanced sampling
Ring	Unsupervised density / clustering score, or contrastive loss on group embeddings
Ranker	Pairwise / listwise (LambdaRank) on helpful-vote preferences, debiased with IPW

Offline metrics

Model	Metric
Detector	PR-AUC, recall at fixed precision (e.g. 95%), calibration (ECE)
Ring	Ring recall, precision of top-K suspicious groups
Ranker	NDCG@5/10, MAP on held-out vote data
Fairness slices	FPR by locale, language, new vs. tenured user, small business
Benchmarks	AUC / recall on YelpChi and Amazon fraud graphs (DGL FraudYelp / FraudAmazon) [1][28]

Online metrics / A-B

Metric	Direction
Fake prevalence on served reviews (audited sample)	Down
Appeal overturn rate, false takedown rate	Down
Moderator queue size / time-to-action	Down
Helpful-vote rate, review-section CTR, scroll depth	Up
Conversion / return rate (e-commerce), booking rate (local)	Up / neutral
Seller / business complaints	Down

- A-B caveat: adversaries adapt; use holdout audit samples and per-market rollouts rather than user-level split for enforcement.

Serving & latency budget

Step	Budget (p99)
Rules + rate limit	10 ms

Step	Budget (p99)
Online feature fetch	30 ms
Text encoder (distilled)	60 ms
GBDT + fusion head	20 ms
Decision + write	30 ms
Total sync write path	< 200 ms
GNN / ring / LLM async	minutes-hours
Ranked review read (cached)	< 50 ms

Monitoring

Signal	Alert on
Score distribution drift per locale/category	PSI shift
Sudden review velocity on item/seller	Burst attack
Hold/reject rate	Spike or collapse
Appeal overturn rate	Precision drop
Label delay / moderator agreement	Label quality
LLM-text detector hit rate	New generator release

Failure modes

Failure	Mitigation
Camouflaged fraudsters (aged accounts, mixed honest reviews)	Relation-aware GNN, behavior over long windows
LLM-written fakes evade text models	Behavior + graph signals over text-only; red-team retraining
Competitor "review bombing" negative fakes	Item-level anomaly detection, temporary lock
Honest bursts (viral event, launch) flagged	Context features (traffic, sales), human review
Feedback loop: ranker hides reviews -> no votes	Exploration slots, IPW
Over-removal hurts small businesses / non-native writers	Slice metrics, high-precision removal, soft demotion

Interviewer follow-ups

- How do you get labels when ground truth is mostly unobservable?
- Fake review vs. fake reviewer vs. review ring: which entity do you model and why?
- How would you detect coordinated review groups that individually look normal?
- How do you handle LLM-generated reviews that are fluent and unique?
- Sync vs. async: what must be decided before the review is visible?
- How do you set thresholds for hide vs. remove vs. human review?
- How do you avoid penalizing non-native speakers or new legitimate users?
- How do you recompute the star average once fakes are removed retroactively?
- How do you debias helpful votes for position and age in the ranker?

- How would you diversify top reviews across positive and negative ratings?
- How do you evaluate a detector when the adversary adapts to it?
- What graph would you build, and how do you scale GNN inference to 1B reviews?
- How do you handle incentivized reviews (free product) vs. outright fake?
- How do you explain decisions for appeals and legal compliance?
- Would you model accounts (action sequences) before they post, not just reviews? [29]
- Where can an LLM help (queue triage, rationale) without becoming the sole judge? [30]

Portal comparison

Portal	Framing	Core model	Distinctive emphasis
ByteByteGo ch. 5 (adapted)	Harmful content classification	Multimodal multi-task fusion	Harmful actors, human review queue [15]
alirezadir	Spam / fraud detection templates	Classifier + features	Checklist of MLSD steps [14]
Educative / Khang Pham	Classification then ranking	GBDT / DNN	Metrics, sampling, serving [17] [18][19]
Chip Huyen exercises	Fraud classification	Supervised with label delay	Data/label issues [20]
Academic (safe-graph, CARE-GNN, GAS)	Graph anomaly detection	Hetero GNN	Camouflage, relation-aware sampling [1][8][25]
ByteByteGo ch. 5 references	Integrity at scale	Multimodal + actor embeddings (TIES)	Human review system, trending abuse [12][16][29]

References

1. Y. Dou et al., "Enhancing Graph Neural Network-based Fraud Detectors against Camouflaged Fraudsters" (CARE-GNN, code + YelpChi/Amazon data), GitHub, 2020. https://github.com/YingtongDou/CARE-GNN (fetched)
2. Y. Dou et al., "Enhancing Graph Neural Network-based Fraud Detectors against Camouflaged Fraudsters", CIKM 2020 / arXiv. https://arxiv.org/abs/2008.08692 (repo-link; venue confirmed in CARE-GNN README)
3. J. Ni, "Amazon Review Data (2018)", nijianmo.github.io, 2018. https://nijianmo.github.io/amazon/index.html (known)
4. A. Mukherjee et al., "What Yelp Fake Review Filter Might Be Doing?", ICWSM, 2013. https://ojs.aaai.org/index.php/ICWSM/article/view/14389 (known)
5. ODDS, "YelpChi dataset", Stony Brook University. http://odds.cs.stonybrook.edu/yelpchi-dataset/ (repo-link)
6. Yelp Engineering, "Yelp Content As Embeddings", engineeringblog.yelp.com, 2023. https://engineeringblog.yelp.com/2023/04/yelp-content-as-embeddings.html (repo-link)
7. S. Rayana, L. Akoglu, "Collective Opinion Spam Detection: Bridging Review Networks and Metadata", KDD, 2015. https://www.andrew.cmu.edu/user/lakoglu/pubs/15-kdd-collectiveopinionspam.pdf (repo-link)
8. A. Li et al., "Spam Review Detection with Graph Convolutional Networks" (GAS, Xianyu), CIKM 2019 / arXiv. https://arxiv.org/abs/1908.10679 (repo-link)

9. safe-graph, "DGFraud-TF2: GAS implementation", GitHub. https://github.com/safe-graph/DGFraud-TF2/tree/main/algorithms/GAS (repo-link)
10. J. Wang et al., "FdGars: Fraudster Detection via Graph Convolutional Networks in Online App Review System", WWW Companion, 2019. https://dl.acm.org/citation.cfm?id=3316586 (repo-link)
11. "Fake Reviewer Group Detection in Online Review Systems", ICDM Workshop / arXiv, 2021. https://arxiv.org/pdf/2112.06403.pdf (repo-link)
12. A. Halevy et al., "Preserving Integrity in Online Social Networks", arXiv, 2020. https://arxiv.org/pdf/2009.10311.pdf (repo-link: ByteByteGo ch. 5 ref 4)
13. Pinterest Engineering, "Fighting Spam using Clustering and Automated Rule Creation", Medium, 2021. https://medium.com/pinterest-engineering/fighting-spam-using-clustering-and-automated-rule-creation-1c01d8c11a05 (repo-link)
14. alirezadir, "ML System Design" (ml-system-design.md), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (fetched)
15. A. Aminian, A. Xu, "Machine Learning System Design Interview", ch. 5 "Harmful Content Detection", ByteByteGo, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/harmful-content-detection (ch-ref)
16. ByteByteGo, "ml-bytebytego: references for Machine Learning System Design Interview", GitHub, 2023. https://github.com/ByteByteGoHq/ml-bytebytego (fetched)
17. Educative, "Grokking the Machine Learning Interview", educative.io, 2024. https://www.educative.io/courses/grokking-the-machine-learning-interview (ch-ref)
18. Educative / K. Pham, "Machine Learning System Design", educative.io, 2021. https://educative.io/courses/machine-learning-system-design/introduction (ch-ref)
19. K. Pham, "machine-learning-interview", GitHub. https://github.com/khangich/machine-learning-interview (ch-ref)
20. C. Huyen, "Machine Learning Systems Design - Exercises", GitHub. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md (ch-ref)
21. Exponent, "Introduction to the ML System Design Interview", tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
22. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery (ch-ref)
23. IGotAnOffer, "Meta Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/facebook-machine-learning-engineer-interview (ch-ref)
24. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2021. http://patrickhalina.com/posts/ml-systems-design-interview-guide/ (ch-ref)
25. safe-graph, "graph-fraud-detection-papers", GitHub. https://github.com/safe-graph/graph-fraud-detection-papers (fetched)
26. safe-graph, "DGFraud: A Deep Graph-based Toolbox for Fraud Detection", GitHub. https://github.com/safe-graph/DGFraud (fetched)
27. Engineer1999, "A Curated List of ML System Design Case Studies", GitHub, 2024. https://github.com/Engineer1999/A-Curated-List-of-ML-System-Design-Case-Studies (fetched)
28. DGL, "Yelp & Amazon Fraud Graph Dataset" (FraudYelp / FraudAmazon), fraud.py, GitHub. https://github.com/dmlc/dgl/blob/master/python/dgl/data/fraud.py (repo-link)

29. Facebook, "TIES: Temporal Interaction Embeddings for Enhancing Social Media Integrity at Facebook", arXiv, 2020. https://arxiv.org/pdf/2002.07917.pdf (repo-link: ByteByteGo ch. 5 ref 21)
30. Whatnot Engineering, "How Whatnot Utilizes Generative AI to Enhance Trust and Safety", Medium, 2023. https://medium.com/whatnot-engineering/how-whatnot-utilizes-generative-ai-to-enhance-trust-and-safety-c7968eb6315e (repo-link)

33. Design Semantic Search and Duplicate Question Detection (Quora, Stack Overflow)

> Prompt as usually given: "When a user types a new question on Quora or Stack Overflow, show similar existing questions and flag likely duplicates before they post." Variants: "merge duplicate questions offline", "semantic search over a Q&A corpus", and "related questions" in the side panel. Chip Huyen's exercise #11 asks it almost verbatim [7].
>
> Sourcing note: in the review pass the web-search budget was used up and arxiv.org, stackoverflow.blog, quora.com, kaggle.com and huggingface.co were unreachable from the sandbox. GitHub pages were fetched and read (exercise numbers re-checked against the raw file). Each reference carries a tag. (fetched) means the page was read for this chapter. (ch-ref) means the URL was verified in another chapter of this atlas. (known) means a canonical paper or post cited by its stable URL but not re-read for this chapter. The "asked it" evidence for company tags is thin, so treat it as indicative only.

Company tags

Company	Evidence	Notes	Source
Quora	Built it: the Question Pairs dataset (2017), a Kaggle competition, and an engineering post on deep-learning question matching	The canonical version of this problem	[10] [11] [12]
Stack Overflow / Stack Exchange	Built it: "similar questions" while you type, the "close as duplicate" workflow, and semantic search (2023). Asked it: Chip Huyen exercise #11 frames it as "StackOverflow similar questions"	Moderator duplicate closures give free labels	[7] [13]
Meta	Built it: embedding-based retrieval in Facebook Search. Asked it (indicative): MLE loops cover search and retrieval design	The same two-tower and ANN template	[16] [24]
Google, Amazon, LinkedIn	Asked it (indicative): text search and semantic search appear in MLSD question banks for these loops. No interview report was confirmed in this run	Treat as *likely*, not confirmed	[2][5] [25] [26]
Reddit, Zendesk-style support desks, Discourse forums	Same pattern: deflecting a ticket or post to an existing answer. No interview report was confirmed	Variant: "suggest a help-centre article"	assumption

Portals that cover it

Portal	Treatment	Link
Chip Huyen, ML Systems Design exercises	#11 "StackOverflow similar questions" and #8 "Quora answer ranking". Prompts only, no solution	[7]

Portal	Treatment	Link
alirezadir AIMLInterviews	Lists "text query search (full-text and semantic)". The search case study gives the staged funnel, LTR and NDCG	[1][2]
Educative "Grokking the ML Interview" (Search Ranking)	Document selection, then staged ranking, then NDCG. Use it as the generic template	[3]
Khang Pham, ML Design Interview / repo	No dedicated case. Search ranking (Airbnb) and embedding papers are the nearest	[4]
ByteByteGo (Aminian & Xu)	No dedicated chapter. "YouTube Video Search" and "Visual Search" supply the dual-encoder and ANN pattern	[5][6]
Exponent, Hello Interview, IGotAnOffer, Patrick Halina	Generic MLSD framework and delivery advice	[25][26] [27][28]
sentence-transformers docs (practitioner reference)	Bi-encoder retrieval, cross-encoder rerank, paraphrase mining. Includes a Quora-duplicates training recipe	[8][9][29]

Requirements & scale

Dimension	Value	Source
Functional (online)	As the user types a title or body, return the top-k similar questions (k is about 5-10)	[7]
Functional (dup flag)	Show a "possible duplicate" banner when P(dup) is at least a threshold. Moderators can close or merge	[13], assumption
Functional (offline)	Mine duplicate clusters across the corpus and merge them into a canonical question	[9]
Functional (search)	Natural-language search box over questions and answers, using lexical and semantic retrieval	[13]
Corpus	Stack Overflow has about 24M questions, Quora has hundreds of millions	assumption (typical)
Labelled pairs	Quora QQP: 404,290 labelled pairs [8]; about 37% positive	[8][10][11]
QPS	Search plus typeahead-similar: about 1-5k QPS average, about 15k peak	assumption
Latency	p99 under 150 ms for the similar-questions panel. Can be debounced to every 300-500 ms of typing	assumption
Freshness	New question searchable within a minute or two through a streaming embed-and-upsert	assumption
Precision need	The dup banner needs high precision, about 0.9 or higher. A false "duplicate" frustrates new users	assumption
Languages	Usually English-first. The multilingual follow-up uses a multilingual encoder	assumption
Business goal	Fewer duplicate posts, more answers reused, faster time-to-answer, less moderator load	assumption

DIAGRAM 1: Online serving path

Figure 33.1 - Query-time path: debounce, then hybrid retrieval (BM25 + ANN), then filtering, cross-encoder ranking, and the duplicate decision and policy.




DIAGRAM 2: Offline training and data pipeline

Figure 33.2 - Labels come from moderator closures, user clicks and merges. Two models are trained (bi-encoder and cross-encoder), then the corpus is re-indexed and the duplicate threshold is calibrated.




DIAGRAM 3: Model architecture

Figure 33.3 - Bi-encoder (Siamese, shared weights) for retrieval and a cross-encoder for the precise duplicate score. The cross-encoder's logit plus metadata go into a GBDT that outputs a calibrated P(dup).

```
      RETRIEVAL: BI-ENCODER (offline corpus side, online query side)

 question A (title [SEP] body[:256])      question B (title [SEP] body[:256])
           |                                          |
           v                                          v
 +---------------------+    shared weights   +---------------------+
 | Transformer encoder |<------------------->| Transformer encoder |
 | (MiniLM/MPNet/E5)   |                     | (MiniLM/MPNet/E5)   |
 +----------+----------+                     +----------+----------+
            | mean-pool                                 | mean-pool
            v                                           v
      +-----------+                               +-----------+
      | u (d=384) |                               | v (d=384) |
      +-----+-----+                               +-----+-----+
            |            cos(u, v) / temperature        |
            +--------------------+----------------------+
                                 v
           loss: MNRL (in-batch softmax over B-1 negatives + hard negs)

      PRECISION: CROSS-ENCODER + BLEND

 "[CLS] q_title q_body [SEP] c_title c_body [SEP]"   (<= 512 tokens)
                      |
                      v
 +-----------------------------------------+
 | Transformer (BERT/DeBERTa), full attention |
 | across both questions                   |
 +----------------------+------------------+
                        | [CLS] -> linear -> logit s_ce
                        v
 +-----------------------------------------+   meta: tag Jaccard, cos(u,v),
 | GBDT / LR blend                         |<--BM25 score, c has accepted ans,
 | -> calibrated P(dup) (Platt / isotonic) |   votes, age gap, same author
 +----------------------+------------------+
                        v
           P(dup) -> rank score + dup banner if P >= tau
```

DIAGRAM 4: Variant, offline duplicate mining and Quora's 2017 approach

Figure 33.4 - (a) Batch paraphrase mining for merge and cleanup [9], and (b) the model family from Quora's 2017 engineering post [12] and the QQP-era literature [17][18].

```
(a) OFFLINE MINING (nightly, corpus-wide)

+------------+  embed   +-------------+ kNN (k=10) +---------------+ pairs with
| all Qs     |--------->| corpus emb  |----------->| candidate     | cos >= t1
| (N ~ 10^7) |  (GPU)   | matrix      | ANN/chunked| pairs ~N*k    |-----------+
+------------+          +-------------+            +---------------+           |
                                                                               v
+--------------------+  edges P>=tau   +------------------+  score  +-------------+
| Merge queue:       |<----------------| Graph: connected |<--------| Cross-enc   |
| canonical = most   |  clusters       | components /     |         | rescoring   |
| answers/views;     |                 | cap cluster size |         +-------------+
| moderator review   |                 +------------------+
+--------------------+

(b) QUORA-STYLE PAIR CLASSIFIER (2017)

 q1 --> embed (GloVe) --> LSTM/attention --> h1 --+
                                                  +-> [h1, h2, |h1-h2|, h1*h2]
 q2 --> embed (GloVe) --> LSTM/attention --> h2 --+        |
                                                           v
                        hand features (word overlap,  --> MLP / RF --> P(dup)
                        TF-IDF cos, length diff)
 Baseline: random forest on hand features. Later: LSTM and decomposable attention.
 BiMPM became a strong reference on QQP.
```

Data & labels

Source	Label type	Volume / note	Pitfall
Moderator "closed as duplicate" links	Strong positive (a, b)	Stack Overflow-scale, millions; used as labels in early forum work [15]	Biased to popular canonical targets
Reopened after dup-close	Negative or hard negative	Small	Noisy, depends on the moderator
Quora QQP	Binary human label	404k pairs, about 37% positive	Sampling bias. Not random pairs [11]
Panel click plus "this answers my question"	Weak positive	Very large	Position bias. Needs debiasing or IPS
Posted anyway after the panel was shown	Weak negative	Large	User may not have read it
Random pairs	Easy negative	Unlimited	Too easy on its own
BM25 and ANN top-k non-dups	Hard negative	Mined per epoch	False negatives (unlabelled dups)
Human raters	Gold eval set	5-20k pairs, stratified	Cost. Keep a fresh monthly sample

Features

Group	Features	Used by
Text (dense)	Bi-encoder cos(u, v), cross-encoder logit	Retrieval, ranker
Text (lexical)	BM25, TF-IDF cos, word or char n-gram Jaccard, edit distance, length diff	Blend, baseline
Entity / code	Shared tags, library names, error strings, code-block overlap (Stack Overflow)	Blend
Candidate quality	Has accepted answer, answer count, score, views, closed or locked	Blend, policy
Temporal	Candidate age, age gap, tag-version drift (for example Python 2 vs 3)	Blend
User / context	Asker reputation, site, language, entry surface (ask page vs search)	Policy, threshold

Model choices

Stage	Baseline	Advanced	Trade-off
Retrieval	BM25 over title and body	Fine-tuned bi-encoder plus ANN, hybrid with BM25 through RRF	Dense covers paraphrase. BM25 covers exact error strings and code [14][16][22][32]
Query understanding	Lower-case, strip code noise	Spell-check, normalisation, expansion, tag/intent prediction	Front of the funnel in the portal search template [1]
Pair scoring	LR or RF on lexical features	Cross-encoder (BERT/DeBERTa) fine-tuned on dup pairs	About 100x the compute per pair. Limit to the top ~100 [23][29]
Late interaction	n/a	ColBERT (token-level MaxSim)	Better than a bi-encoder, but a larger index [20]
Blend	Cross-encoder score alone	GBDT on CE logit plus quality and meta	Lets you push answered or accepted canonical questions up

Stage	Baseline	Advanced	Trade-off
LLM	n/a	LLM judge for borderline P in [0.4, 0.7], or a rewrite of the query	Latency and cost. Use offline or async
Clustering	Threshold on pairs	Connected components with cluster-size caps	Transitive chains drift. Cap size and re-verify

Loss functions

Model	Loss	Notes
Bi-encoder	MultipleNegativesRankingLoss (in-batch softmax, InfoNCE)	Needs positives only. Larger batches help [8][19]
Bi-encoder (pairs)	OnlineContrastiveLoss (margin 0.5)	Uses labelled 0/1 pairs and focuses on hard pairs [8]
Multi-task	MNRL plus ContrastiveLoss, alternating batches	One for ranking, one for classification [8]
Cross-encoder	Binary cross-entropy on (q, c, y)	Calibrate afterwards with Platt or isotonic
Blend ranker	LambdaMART (nDCG) or logloss	Pairwise if graded labels exist
Distillation	MSE or KL from cross-encoder to bi-encoder scores	Improves recall without serving cost

Offline metrics

Stage	Metric	Target example
Retrieval	Recall@100 of the known dup target	0.95 or higher
Ranking	MRR, nDCG@10, Hit@5	Report by slice
Dup classifier	PR-AUC, precision at the threshold, recall at precision 0.9	Precision at tau of 0.9 or higher
Calibration	ECE or a reliability plot	Needed for a stable tau
Benchmarks	QQP accuracy and F1; BEIR Quora (10k queries, 523k docs) and CQADupStack (13,145 queries, 457k docs) nDCG@10	Sanity check vs public models [11][21][33]
Slices	New tags, low-resource languages, code-heavy questions, very short titles	No slice regresses more than 2%

Online metrics & A/B

Metric	Direction	Note
Duplicate post rate (later closed as dup)	Down	Primary north star
Ask-flow deflection: user leaves satisfied after clicking a similar Q	Up	Guard against it suppressing genuinely new questions
Time to first useful answer	Down	Includes deflected sessions
Similar-panel CTR, search success rate	Up	Session-level
Successful-session rate, dwell on the clicked question	Up	CTR alone can reward clickbait titles [1]

Metric	Direction	Note
Wrongly closed-as-dup or reopen rate	Down (guardrail)	Hurts new users
New-question volume and answerer engagement	Not down (guardrail)	Too much deflection starves the community
Latency p99, error rate	Within SLO	Infrastructure guardrail

Serving & latency

Step	Budget (p99)	Notes
Debounce and query cleaning	about 5 ms	Client debounce of 300-500 ms is not counted
Bi-encoder query embed (CPU/ONNX or GPU)	about 10-15 ms	Distilled MiniLM, int8
ANN (HNSW, sharded) plus BM25 in parallel	about 15-20 ms	k about 200 each
Fusion, filters, feature fetch	about 15 ms	Batched feature-store read
Cross-encoder on ~50-100 pairs (GPU, batched)	about 40-60 ms	Truncate bodies. Cache popular candidates
GBDT, policy, response	about 10 ms	
Total	about 120-150 ms	Search path. The dup check at submit can take longer

Monitoring

Signal	Alert on
Embedding drift (mean cos to centroid, new-tag share)	Shift beyond a baseline band
P(dup) score distribution and banner rate	Sudden jump or drop (threshold or calibration broke)
Reopen rate after an auto-suggested dup	Rise above the guardrail
ANN recall vs exact kNN, measured on a sample (HNSW / IVF-PQ) [30][31][34]	Recall@100 below 0.95
Index freshness lag (post to searchable)	More than 5 min
Latency p99 and GPU queue depth	SLO breach

Failure modes

Failure	Example	Mitigation
Near-miss paraphrase	"How to sort a list in Python" vs "...in Java"	Entity and tag features, cross-encoder, hard negatives
Version drift	Python 2 vs 3 answers now wrong	Recency and version features. Prefer canonical questions with recent edits
Over-deflection	New edge-case questions get marked dup	High tau, "not a dup" button, guardrail metric
Transitive chain drift	A~B~C~D but A is not D	Cap cluster size, re-verify edges with the CE

Failure	Example	Mitigation
Label bias	Moderators favour popular targets	Human audit set, IPS on click labels
Lexical-only blind spot	Exact error string missed by dense retrieval	Hybrid BM25 plus dense with RRF
Spam and SEO copies	Copied questions cluster with real ones	Spam classifier upstream, author features
Cold index after model swap	New embeddings are not comparable with the old index	Full re-embed, blue/green index swap
Asymmetric neighbours in mining	B is A's top match but A is not B's, so (A,B),(B,C) chains appear	Symmetrise pairs, re-score with the CE, then cluster [9]
Quadratic mining cost	All-pairs compare is impractical beyond about 10k questions	Chunked top-k mining (`query_chunk_size`, `corpus_chunk_size`, `max_pairs`) or ANN [9]

Interviewer follow-ups

- Is "similar" the same as "duplicate"? How do the two surfaces differ in threshold and metric?
- Where do labels come from, and how do you handle false negatives among mined hard negatives?
- Bi-encoder vs cross-encoder: why use both, and where does each run?
- How do you set and maintain the duplicate threshold tau? What happens when the calibration drifts?
- How do you prevent leakage when splitting pairs (the same question in train and test)?
- How do you handle code snippets, stack traces and exact error messages?
- How do you re-index 20M+ questions when the embedding model changes, without downtime?
- How do you make a new question searchable within a minute?
- How do you evaluate offline vs online? Which metric is the north star?
- How do you stop over-deflection that discourages new questions?
- How do you handle multilingual sites (for example, Stack Overflow in Portuguese)?
- How would you mine and merge duplicate clusters offline? Why not use pure transitive closure?
- Where would an LLM help (query rewrite, borderline judging, answer synthesis), and at what cost?
- How do you debias click labels from the similar-questions panel?
- How do you scale ANN to 10^8 vectors (PQ, sharding, memory per vector)?
- Paraphrase mining returns asymmetric pairs: how do you turn them into stable clusters? [9]
- How many candidates should the cross-encoder see (about 100 is the common default), and why? [29]
- Which public benchmark would you sanity-check on (BEIR Quora, CQADupStack)? [33]

Portal comparison

Portal	Framing	Retrieval	Scoring model	Metrics emphasis
Chip Huyen exercises [7]	#11 "StackOverflow similar questions", prompt only	Left to the candidate	Left to the candidate	Open-ended
Educative Grokking, Search Ranking [3]	Generic search ranking	Inverted index plus embeddings (document selection)	Staged LR to LambdaMART or DNN	nDCG, session success
alirezadir search case [1]	Generic text search funnel	Inverted index, weighted linear score	Pointwise stage 1 then pairwise LambdaMART	P@k, MRR, nDCG, CTR
ByteByteGo video and visual search [5][6]	Text-to-item search	Dual encoder plus ANN, fused with text search	Contrastive dual encoder	MRR, CTR, watch time
sentence-transformers docs [8][9][29]	Practitioner semantic search and dup mining	Bi-encoder plus ANN, optional BM25	Cross-encoder rerank	IR metrics (Recall, MRR, nDCG)
Quora engineering 2017 [12]	Pair classification (dup or not)	Not covered (pairwise)	RF baseline, then LSTM and attention	Accuracy and F1 on QQP

References

1. alirezadir, "Search System" (mlsd-search.md), GitHub, 2023. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/mlsd-search.md (fetched)
2. alirezadir, "ML System Design" template (lists text query search: full-text and semantic), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (fetched)
3. Educative, "Grokking the Machine Learning Interview", "Document selection" lesson (Search Ranking), educative.io, n.d. https://www.educative.io/courses/grokking-the-machine-learning-interview/document-selection (ch-ref)
4. K. Pham, "machine-learning-interview", GitHub, 2021. https://github.com/khangich/machine-learning-interview (fetched)
5. ByteByteGo, "YouTube Video Search" (MLSDI course chapter), bytebytego.com, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/youtube-video-search (ch-ref)
6. ByteByteGo, "Visual Search System" (MLSDI course chapter), bytebytego.com, 2023. https://bytebytego.com/courses/machine-learning-system-design-interview/visual-search-system (ch-ref)
7. C. Huyen, "Machine Learning Systems Design: Exercises" (#8 Quora answer ranking, #11 StackOverflow similar questions), GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design/blob/master/content/exercises.md (fetched)
8. UKPLab, sentence-transformers, "Quora Duplicate Questions" training example, GitHub, 2024. https://github.com/UKPLab/sentence-transformers/tree/master/examples/sentence_transformer/training/quora_duplicate_questions (fetched)
9. UKPLab, sentence-transformers, "Paraphrase Mining" application, GitHub, 2024. https://github.com/UKPLab/sentence-transformers/tree/master/examples/sentence_transformer/applications/paraphrase-mining (fetched)

10. Quora, "First Quora Dataset Release: Question Pairs", quoradata.quora.com, 2017. https://quoradata.quora.com/First-Quora-Dataset-Release-Question-Pairs (known)
11. Kaggle, "Quora Question Pairs" competition, kaggle.com, 2017. https://www.kaggle.com/c/quora-question-pairs (known)
12. Quora Engineering, "Semantic Question Matching with Deep Learning", quoraengineering.quora.com, 2017. https://quoraengineering.quora.com/Semantic-Question-Matching-with-Deep-Learning (known)
13. Stack Overflow Blog, "Ask like a human: Implementing semantic search on Stack Overflow", stackoverflow.blog, 2023. https://stackoverflow.blog/2023/07/31/ask-like-a-human-implementing-semantic-search-on-stack-overflow/ (known)
14. N. Reimers, I. Gurevych, "Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks", EMNLP, arXiv, 2019. https://arxiv.org/abs/1908.10084 (known)
15. D. Bogdanova et al., "Detecting Semantically Equivalent Questions in Online User Forums", CoNLL, ACL Anthology, 2015. https://aclanthology.org/K15-1013/ (known)
16. J.-T. Huang et al., "Embedding-based Retrieval in Facebook Search", KDD, arXiv, 2020. https://arxiv.org/abs/2006.11632 (ch-ref)
17. Z. Wang, W. Hamza, R. Florian, "Bilateral Multi-Perspective Matching for Natural Language Sentences" (BiMPM, evaluated on QQP), arXiv, 2017. https://arxiv.org/abs/1702.03814 (known)
18. A. Parikh et al., "A Decomposable Attention Model for Natural Language Inference", arXiv, 2016. https://arxiv.org/abs/1606.01933 (known)
19. M. Henderson et al., "Efficient Natural Language Response Suggestion for Smart Reply" (in-batch negatives), arXiv, 2017. https://arxiv.org/abs/1705.00652 (known)
20. O. Khattab, M. Zaharia, "ColBERT: Efficient and Effective Passage Search via Contextualized Late Interaction over BERT", SIGIR, arXiv, 2020. https://arxiv.org/abs/2004.12832 (known)
21. N. Thakur et al., "BEIR: A Heterogeneous Benchmark for Zero-shot Evaluation of IR Models" (includes Quora, CQADupStack), arXiv, 2021. https://arxiv.org/abs/2104.08663 (known)
22. V. Karpukhin et al., "Dense Passage Retrieval for Open-Domain Question Answering", arXiv, 2020. https://arxiv.org/abs/2004.04906 (known)
23. R. Nogueira, K. Cho, "Passage Re-ranking with BERT", arXiv, 2019. https://arxiv.org/abs/1901.04085 (known)
24. IGotAnOffer, "Meta Machine Learning Engineer Interview", igotanoffer.com, 2025. https://igotanoffer.com/blogs/tech/facebook-machine-learning-engineer-interview (ch-ref)
25. Exponent, "Introduction to the ML System Design Interview", tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
26. IGotAnOffer, "Machine Learning System Design Interview", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/machine-learning-system-design-interview (ch-ref)
27. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery (ch-ref)
28. P. Halina, "ML Systems Design Interview Guide", patrickhalina.com, 2020. http://patrickhalina.com/posts/ml-systems-design-interview-guide/ (ch-ref)
29. UKPLab, sentence-transformers, "Retrieve & Re-Rank" application, GitHub, 2024. https://github.com/UKPLab/sentence-transformers/tree/master/examples/sentence_transformer/applications/retrieve_rerank (fetched)

30. J. Johnson, M. Douze, H. Jegou, "Billion-scale similarity search with GPUs" (FAISS), arXiv, 2017. https://arxiv.org/abs/1702.08734 (ch-ref)
31. Y. Malkov, D. Yashunin, "Efficient and robust approximate nearest neighbor search using HNSW graphs", arXiv, 2016. https://arxiv.org/abs/1603.09320 (ch-ref)
32. G. Cormack, C. Clarke, S. Buettcher, "Reciprocal Rank Fusion outperforms Condorcet and individual Rank Learning Methods", SIGIR, 2009. https://plg.uwaterloo.ca/~gvcormac/cormacksigir09-rrf.pdf (ch-ref)
33. BEIR authors, "BEIR: A Heterogeneous Benchmark for Information Retrieval" (dataset table incl. Quora, CQADupStack), GitHub, 2021. https://github.com/beir-cellar/beir (fetched)
34. Meta FAIR, "Faiss" library repository, GitHub, 2024. https://github.com/facebookresearch/faiss (fetched)

34. Design a Text-to-Image Generation Service (Midjourney, DALL-E) with Safety and Serving

> Turn a text prompt (plus optional reference image, style, or aspect ratio) into 1-4 high-quality images in seconds. The service must stay safe at both the prompt and the pixel level, and cost cannot run away. In this design the "candidates" are N sampled images. "Ranking" means choosing among them by aesthetic and alignment scores, and "policy" covers safety classifiers, watermarking and provenance.

> Research note: pages re-fetched in review: [1] [2] [3] [31] [32] [36] [37]. arXiv, openai.com, bytebytego.com and c2pa.org were unreachable from the sandbox; those entries are well-known papers or pages cited from prior knowledge and marked as such.

Company tags

Company / product	Why it is tagged	Source
OpenAI (DALL-E 2/3, GPT image)	Builds and documents this exact system (system cards)	[1] [8]
Midjourney	Product named in the common framing of this problem ("design Midjourney")	[29]
Google (Imagen), Meta (Emu)	Ship production text-to-image models. Product-based tag, not a verified question report	[6] [41]
Stability AI	Open reference stack: SD 1.x, SDXL, Turbo	[2] [3] [7]
Generic GenAI / MLE loops (FAANG, AI labs)	Repo prep guides list "Image-generation pipeline" as a role-specific GenAI design topic	[32]

Verified company reports (LeetCode Discuss, Blind) could not be gathered in this run. Treat the rows above as product-based tags.

Portals that cover it

Portal	Coverage	Link
ByteByteGo, Aminian & Sheng, "Generative AI System Design Interview"	Dedicated "Text-to-Image Generation" chapter, plus neighbouring chapters on high-res synthesis and personalized headshots	[29]
Educative, "Grokking the Generative AI System Design"	Text, image, speech and video generation case studies	[30] [31]
alirezadir / Agentic-AI-Systems interview prep	Lists "Image-generation pipeline" (Tier 3, role-specific)	[32]
Chip Huyen, "Building a GenAI Platform"	Generic GenAI serving stack (guardrails, caching, routing); not text-to-image specific	[35]

Requirements & scale

Dimension	Requirement	Note / source
Functional	Text prompt -> 1-4 images. Options: aspect ratio, style, seed, negative prompt, variations, upscale, inpaint / outpaint with a mask, image prompt	DALL-E 2 offered inpainting and variations [1]. Others are typical
Resolution	1024x1024 native, 2-4x upscale optional	SDXL trained at 1024^2, multi-aspect [3] [7]
Latency	Interactive: p50 ~5-10 s for 4 images, preview at ~1 s. Turbo mode: under 1 s	Assumption. 1-4 step distilled models [12] [13]
Throughput	10M images/day ~ 115 img/s average, ~3-5x at peak	Typical assumption
Users	10-20M MAU, heavy-tailed usage, paid tiers	Assumption
Safety	Block CSAM, sexual, violent, hateful, public-figure and deceptive content at prompt and output	[1]
Provenance	Invisible watermark plus C2PA metadata on every image	[2] [3] [28] [40]
Cost	GPU-seconds per image is the main cost lever. Sell GPU time by tier (fast / relax / turbo style queues)	Assumption (Midjourney-style tiers)
Availability	99.9%. Degrade to fewer steps or images under load	Assumption
Abuse	Per-user rate limits, anomaly detection, account enforcement	[1]

DIAGRAM 1: Online serving path

Figure 34.1: End-to-end request path (prompt to safe, watermarked images)




- Steps 1 and 6 follow the DALL-E pattern: input filters on prompts and uploads, then output filters, with independent filters as a known gap [1]. The SD reference script also ships a post-hoc safety checker [2]
- Step 2 (LLM prompt rewrite) is the DALL-E 3 pattern: descriptive captions at training time, upsampled prompts at inference [8]

- Step 3 only hits for an identical prompt + seed + options + model version; diffusion is deterministic given the seed
- Step 8: the SD reference stack applies an invisible watermark to every output [2] [3]; C2PA adds a signed manifest [28]

DIAGRAM 2: Offline data and training pipeline


Figure 34.2: Data curation, training, alignment, eval and deployment loop



- Data filtering: NSFW/violence classifiers plus hate-symbol caption filters. Filtering is tuned to avoid demographic skew (DALL-E 2 found the filter reduced images of women) [1]
- SD v1.2-1.4 trained on LAION-Aesthetics (aesthetic > 5.0, size >= 512, low watermark prob.) and dropped the text 10% of the time to enable CFG [2] [16]
- Recaptioning: DALL-E 3 trained on synthetic descriptive captions [8]. Quality tuning on a small curated set: Meta Emu [41]

DIAGRAM 3: Model architecture (latent diffusion with cross-attention)


Figure 34.3: Latent diffusion / DiT generator with classifier-free guidance



- LDM: diffusion in an 8x-downsampled VAE latent with cross-attention conditioning [2] [4]. SD1 uses an ~860M U-Net and a ~123M frozen CLIP ViT-L/14 [2]
- SDXL: two text encoders (OpenCLIP ViT-G + CLIP ViT-L), 1024^2 multi-aspect training, plus a refiner used only as img2img [3] [7]
- CFG [9]; DDPM/DDIM [10] [11]; DiT [14]; MM-DiT with rectified flow (SD3) [15]

DIAGRAM 4: Alternatives (pixel cascade vs latent vs distilled)

Figure 34.4: Three production generator families and where each one fits



- Imagen: frozen T5-XXL plus a 64 -> 256 -> 1024 cascade [6]. DALL-E 2: CLIP prior plus diffusion decoder plus 2 upsamplers [5]
- SDXL-Turbo uses adversarial diffusion distillation [3] [12]. LCM [13]. Guided distillation [39]

Data & labels

Data	Source	Label / signal	Use	Ref
Image-alt-text pairs	Web crawl (LAION-5B scale), licensed stock	Weak caption	Pretraining	[16]
Synthetic dense captions	VLM captioner	Descriptive caption	Better prompt following	[8]
Curated high-aesthetic set	Human-selected	"Photogenic" yes/no	Quality fine-tune	[41]
Pairwise preferences	Users choose 1 of N (upscale/download)	Win/loss pair	Reward model, DPO	[19] [27]
Expert ratings	Annotators	1-7 alignment/fidelity	ImageReward-style RM	[20]
Safety labels	Trust & safety raters, red teams	Policy category	Prompt/image classifiers	[1] [22]
Abuse reports	User flags	Violation	Enforcement, classifier retraining	[1]

Features / conditioning inputs

Input	Encoding	Notes
Prompt text	CLIP / OpenCLIP / T5 token embeddings	CLIP [23]; T5 improves spelling and composition [6] [15]
Negative prompt	Same encoder, replaces null in CFG	User control
Size / aspect / crop coords	Micro-conditioning embeddings	SDXL conditioning trick [7]

Input	Encoding	Notes
Seed	Initial noise z_T	Reproducibility, variations
Reference image / pose / edges	VAE latent, ControlNet branch	[25]
Style / subject	LoRA or DreamBooth adapters	Personalization [24]
Safety context	User tier, region, history	Gate thresholds, not fed to the generator

Model choices (baseline -> advanced)

Stage	Option	Pros	Cons
Baseline	GAN (StyleGAN-T)	1-step, fast	Mode collapse, weak text alignment
Baseline 2	Autoregressive over VQ tokens (DALL-E 1, Parti)	Reuses LLM infra	Slow token-by-token decode
Standard	Latent diffusion U-Net + CLIP [4]	Open, efficient, mature	Weak at text and counting
Advanced	MM-DiT + rectified flow + T5 [15]	Scales well, better typography	Bigger, needs more GPU
Pixel cascade	GLIDE / Imagen / unCLIP [38] [6] [5]	Strong alignment	3 models, cost
Fast path	ADD / LCM distillation [12] [13]	1-4 steps	Lower diversity
Alignment	Diffusion-DPO / reward fine-tune [27]	Matches user taste	Reward hacking
Safety-in-model	Safe Latent Diffusion guidance [21], concept erasure fine-tune [43]	Survives removal of external filters	Over-suppresses, collateral concept damage

Loss

Component	Loss	Ref
Denoiser	MSE on epsilon (or v / flow velocity) at random t	[10] [15]
CFG enabler	Drop text 10% of the time (unconditional branch)	[2] [9]
VAE	L1/perceptual + KL + patch-GAN	[4]
Reward model	Bradley-Terry pairwise logistic on preferences	[19] [20]
Preference tuning	Diffusion-DPO objective	[27]
Distillation	Adversarial + score distillation (ADD) / consistency	[12] [13]
Safety classifiers	Multi-label BCE, recall-weighted	Assumption

Offline metrics

Metric	Measures	Caveat	Ref
FID (COCO-30k zero-shot)	Realism / distribution match	Poor match with human preference	[17]
Inception Score	Quality and diversity	ImageNet-biased	[33]
CLIPScore	Prompt-image alignment	Saturates, bag-of-words	[18]

Metric	Measures	Caveat	Ref
PickScore / ImageReward	Predicted human preference	Can be gamed	[19] [20]
T2I-CompBench, GenEval	Attributes, counting, position, colour binding (GenEval uses object detectors)	Narrow prompts	[26] [42]
Prompt suites for human eval	DrawBench (Imagen), PartiPrompts (Parti)	Fixed prompts can be overfit	[6] [34]
Memorization rate	Near-duplicate outputs vs training set for sampled prompts	Needs dedup index over training data	[45]
Human side-by-side	Win rate on aesthetics, alignment, artifacts	Expensive. The final gate	[7] [8]
Safety eval	Attack success rate on red-team prompt suites, NSFW leak rate	Needs adversarial refresh	[1] [22]
Bias audit	Demographic distribution for neutral prompts	Requires a labelled audit set	[1]

Online metrics / A-B

Metric	Type
Download / upscale / share rate per generation	Primary engagement
Reroll rate, prompt edit rate	Dissatisfaction (lower is better)
Pairwise pick rate (new vs old model shown side by side)	Model preference
p50/p95 time-to-first-image, queue wait	Latency guardrail
GPU-seconds per kept image	Cost guardrail
Prompt block rate, false-block appeals, user reports per 1k images	Safety guardrails
Paid conversion, retention D7/D30	Business

Serving & latency budget (4 images, 1024^2, standard mode)

Stage	Budget	Technique
Gateway, auth, quota	20 ms	Edge
Prompt safety (blocklist + classifier + LLM judge)	100-300 ms	Small models, cached verdicts
LLM prompt rewrite	300-800 ms	Small LLM, run in parallel with safety, cancel on block
Queue wait	0-several s	Priority queues by tier, autoscale on queue depth
Text encode	10-30 ms	Cache by prompt hash
Denoise (25-30 steps, batch 4, CFG batched x2)	2-6 s on A100/H100 class GPUs	fp16/bf16, FlashAttention, TensorRT/torch.compile, DPM-Solver
VAE decode	100-300 ms	Tiled decode
Output safety + re-rank	50-150 ms	Batched CLIP-based heads
Watermark + C2PA + upload	50-100 ms	Async upload to CDN
Streaming previews	Every k steps	Latent preview decoder for perceived latency

- Cost levers: fewer steps (distilled model for free tier), shared-batch CFG, feature caching across steps (DeepCache [44]), scale-to-zero LoRA adapters, result cache for repeated prompt+seed
- Fleet: separate pools for base, upscale and inpaint. Preemptible GPUs for the "relax" tier

Monitoring

Signal	Alert on
Safety filter block rate by category and locale	Spikes (new jailbreak) or drops (classifier broken)
User reports per 1k images	Above SLO
Output-classifier vs human-review disagreement	Drift in safety models
Prompt distribution (embedding clusters)	New trend or attack campaign
Aesthetic / CLIPScore of served images	Quality regression after deploy
GPU utilization, queue depth, OOMs	Capacity
Watermark detection rate on sampled outputs	Provenance pipeline broken

Failure modes

Failure	Mitigation	Ref
Jailbreak via "visual synonyms" (ketchup for blood), misspellings, other languages	Output classifiers, LLM judge, adversarial red-teaming loop	[1] [22]
Benign prompt + benign upload = harmful combination	Joint multimodal safety check	[1]
Safety filter bypass on open weights	In-model safety guidance, concept erasure	[21] [22] [43]
Over-filtering silences groups / demographic skew	Bias audits, calibrated thresholds	[1]
Deepfakes of public figures, non-consensual imagery	Face-match block, name stripping in rewrite, provenance	[1] [28]
Copyright / living-artist style mimicry	Artist-name filters, training opt-outs, data licensing	[8]
Watermark removal (cropping a visible signature)	Invisible watermark plus C2PA plus server-side lookup	[1] [3] [40]
Poor text rendering, hands, counting	T5 encoder, DiT, recaption, reward fine-tuning	[6] [8] [15]
Low diversity after distillation or DPO	Mix of teacher outputs, diversity metrics	[12] [27]
GPU queue blowup at launch	Tiered queues, degrade steps, waitlist	[1]
Memorization / training-image extraction	Dedupe training data, near-dup check on outputs	[45]

Interviewer follow-ups

- Why diffusion over GANs or autoregressive token models? What does each trade off in quality, diversity and latency?
- Why run diffusion in latent space? What do you lose (VAE artifacts on text and faces)?

- Explain classifier-free guidance. What happens as w goes up, and how do you train for it (null-text dropout)?
- How would you get ~10 s generation time for 4 images down to under 1 s? (Distillation, schedulers, batching, caching, hardware.)
- Web captions are noisy. How do you improve prompt following? (Recaptioning, LLM prompt rewrite.)
- Where do safety filters go, and why is a prompt filter alone not enough?
- How do you measure "quality" offline when FID disagrees with humans?
- Design the human evaluation: side-by-side protocol, rater agreement, prompt set (PartiPrompts/DrawBench-style).
- How would you use implicit user feedback (upscale and download picks) to improve the model? What are the bias risks?
- How do you stop deepfakes of public figures and generation of copyrighted characters?
- How do you watermark outputs, and how robust is the watermark to crops, compression and screenshots?
- How do you schedule GPUs across free and paid tiers and handle a 10x launch spike?
- How do you support personalization (DreamBooth/LoRA) at scale without one GPU per user?
- How would you detect a new jailbreak campaign in production?
- How do you check that the model is not reproducing memorized training images?
- How do you design inpainting / outpainting (mask channel, masked-latent conditioning) and image prompts?
- Which offline benchmark would you gate on (GenEval, T2I-CompBench, PartiPrompts), and why not FID alone?

Portal comparison

Portal	Framing	Model emphasis	Safety / serving depth	Unique angle
ByteByteGo GenAI SDI [29]	"Text-to-image like Midjourney"	Diffusion vs autoregressive, U-Net/DiT, CFG, recaptioning	Prompt safety, prompt enhancement, harm detection, super-resolution in the serving pipeline	Explicit metrics section (IS, FID, CLIPScore, human eval)
Educative Grokking GenAI SD [30]	Image generation as one of text/image/speech/video modalities	Training, inference, scaling	Evaluation and scaling chapters	Cross-modality comparison
alirezadir Agentic-AI-Systems [32]	"Image-generation pipeline" as a Tier-3 role-specific topic	Not detailed	Not detailed	Positions it as a specialist question
Chip Huyen GenAI platform [35]	Generic GenAI app stack	Model-agnostic	Guardrails, cache, router, observability	Platform view reusable here
OpenAI system cards [1] [8]	Real deployment	unCLIP / DALL-E 3 recaptioning	Data filters, input/output filters, rate limits, red teaming	Ground truth on the production safety stack

References

1. OpenAI, "DALL-E 2 Preview - Risks and Limitations" (system card), GitHub, 2022. https://github.com/openai/dalle-2-preview/blob/main/system-card.md (fetched)
2. CompVis, "Stable Diffusion" repository README, GitHub, 2022. https://github.com/CompVis/stable-diffusion (fetched)
3. Stability AI, "Generative Models" repository (SDXL, SDXL-Turbo), GitHub, 2023. https://github.com/Stability-AI/generative-models (fetched)
4. R. Rombach et al., "High-Resolution Image Synthesis with Latent Diffusion Models", arXiv, 2021. https://arxiv.org/abs/2112.10752 (prior knowledge)
5. A. Ramesh et al., "Hierarchical Text-Conditional Image Generation with CLIP Latents" (DALL-E 2), arXiv, 2022. https://arxiv.org/abs/2204.06125 (prior knowledge)
6. C. Saharia et al., "Photorealistic Text-to-Image Diffusion Models with Deep Language Understanding" (Imagen), arXiv, 2022. https://arxiv.org/abs/2205.11487 (prior knowledge)
7. D. Podell et al., "SDXL: Improving Latent Diffusion Models for High-Resolution Image Synthesis", arXiv, 2023. https://arxiv.org/abs/2307.01952 (prior knowledge)
8. J. Betker et al., "Improving Image Generation with Better Captions" (DALL-E 3), OpenAI, 2023. https://cdn.openai.com/papers/dall-e-3.pdf (prior knowledge)
9. J. Ho, T. Salimans, "Classifier-Free Diffusion Guidance", arXiv, 2022. https://arxiv.org/abs/2207.12598 (prior knowledge)
10. J. Ho et al., "Denoising Diffusion Probabilistic Models", arXiv, 2020. https://arxiv.org/abs/2006.11239 (prior knowledge)
11. J. Song et al., "Denoising Diffusion Implicit Models", arXiv, 2020. https://arxiv.org/abs/2010.02502 (prior knowledge)
12. A. Sauer et al., "Adversarial Diffusion Distillation" (SDXL-Turbo), arXiv, 2023. https://arxiv.org/abs/2311.17042 (prior knowledge)
13. S. Luo et al., "Latent Consistency Models", arXiv, 2023. https://arxiv.org/abs/2310.04378 (prior knowledge)
14. W. Peebles, S. Xie, "Scalable Diffusion Models with Transformers" (DiT), arXiv, 2022. https://arxiv.org/abs/2212.09748 (prior knowledge)
15. P. Esser et al., "Scaling Rectified Flow Transformers for High-Resolution Image Synthesis" (SD3), arXiv, 2024. https://arxiv.org/abs/2403.03206 (prior knowledge)
16. C. Schuhmann et al., "LAION-5B: An Open Large-Scale Dataset for Training Next Generation Image-Text Models", arXiv, 2022. https://arxiv.org/abs/2210.08402 (prior knowledge)
17. M. Heusel et al., "GANs Trained by a Two Time-Scale Update Rule Converge to a Local Nash Equilibrium" (FID), arXiv, 2017. https://arxiv.org/abs/1706.08500 (prior knowledge)
18. J. Hessel et al., "CLIPScore: A Reference-free Evaluation Metric for Image Captioning", arXiv, 2021. https://arxiv.org/abs/2104.08718 (prior knowledge)
19. Y. Kirstain et al., "Pick-a-Pic: An Open Dataset of User Preferences for Text-to-Image Generation", arXiv, 2023. https://arxiv.org/abs/2305.01569 (prior knowledge)
20. J. Xu et al., "ImageReward: Learning and Evaluating Human Preferences for Text-to-Image Generation", arXiv, 2023. https://arxiv.org/abs/2304.05977 (prior knowledge)
21. P. Schramowski et al., "Safe Latent Diffusion: Mitigating Inappropriate Degeneration in Diffusion Models", arXiv, 2022. https://arxiv.org/abs/2211.05105 (prior knowledge)

22. J. Rando et al., "Red-Teaming the Stable Diffusion Safety Filter", arXiv, 2022. https://arxiv.org/abs/2210.04610 (prior knowledge)
23. A. Radford et al., "Learning Transferable Visual Models From Natural Language Supervision" (CLIP), arXiv, 2021. https://arxiv.org/abs/2103.00020 (prior knowledge)
24. N. Ruiz et al., "DreamBooth: Fine Tuning Text-to-Image Diffusion Models for Subject-Driven Generation", arXiv, 2022. https://arxiv.org/abs/2208.12242 (prior knowledge)
25. L. Zhang et al., "Adding Conditional Control to Text-to-Image Diffusion Models" (ControlNet), arXiv, 2023. https://arxiv.org/abs/2302.05543 (prior knowledge)
26. K. Huang et al., "T2I-CompBench: A Comprehensive Benchmark for Open-world Compositional Text-to-image Generation", arXiv, 2023. https://arxiv.org/abs/2307.06350 (prior knowledge)
27. B. Wallace et al., "Diffusion Model Alignment Using Direct Preference Optimization", arXiv, 2023. https://arxiv.org/abs/2311.12908 (prior knowledge)
28. C2PA, "Coalition for Content Provenance and Authenticity" (content credentials spec), c2pa.org, 2024. https://c2pa.org/ (prior knowledge)
29. A. Aminian, H. Sheng, "Generative AI System Design Interview" (incl. "Text-to-Image Generation" chapter), ByteByteGo, 2024. https://bytebytego.com/ (site root; chapter content from prior knowledge, host unreachable in review)
30. Educative, "Grokking the Generative AI System Design", educative.io, 2025. https://www.educative.io/courses/generative-ai-system-design (description confirmed via [31])
31. A. Dirafzoon, "GenAI Learning Resources", GitHub (Machine-Learning-Interviews), 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/genai-resources.md (fetched)
32. A. Dirafzoon, "GenAI & Agentic System Design" interview prep, GitHub (Agentic-AI-Systems), 2025. https://github.com/alirezadir/Agentic-AI-Systems/blob/main/06_interview_prep/genai-agentic-system-design.md (fetched)
33. T. Salimans et al., "Improved Techniques for Training GANs" (Inception Score), arXiv, 2016. https://arxiv.org/abs/1606.03498 (prior knowledge)
34. J. Yu et al., "Scaling Autoregressive Models for Content-Rich Text-to-Image Generation" (Parti, PartiPrompts), arXiv, 2022. https://arxiv.org/abs/2206.10789 (prior knowledge)
35. C. Huyen, "Building A Generative AI Platform", huyenchip.com, 2024. https://huyenchip.com/2024/07/25/genai-platform.html (prior knowledge; host unreachable in review)
36. Hugging Face, "Diffusers" library, GitHub, 2024. https://github.com/huggingface/diffusers (fetched)
37. A. Dirafzoon, "Machine-Learning-Interviews" repository, GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews (fetched)
38. A. Nichol et al., "GLIDE: Towards Photorealistic Image Generation and Editing with Text-Guided Diffusion Models", arXiv, 2021. https://arxiv.org/abs/2112.10741 (prior knowledge)
39. C. Meng et al., "On Distillation of Guided Diffusion Models", arXiv, 2022. https://arxiv.org/abs/2210.03142 (prior knowledge)
40. Google DeepMind, "SynthID" (watermarking AI-generated content), deepmind.google, 2023. https://deepmind.google/technologies/synthid/ (prior knowledge)
41. X. Dai et al., "Emu: Enhancing Image Generation Models Using Photogenic Needles in a Haystack", arXiv, 2023. https://arxiv.org/abs/2309.15807 (prior knowledge)
42. D. Ghosh et al., "GenEval: An Object-Focused Framework for Evaluating Text-to-Image Alignment", arXiv, 2023. https://arxiv.org/abs/2310.11513 (prior knowledge)

43. R. Gandikota et al., "Erasing Concepts from Diffusion Models", arXiv, 2023. https://arxiv.org/abs/2303.07345 (prior knowledge)
44. X. Ma et al., "DeepCache: Accelerating Diffusion Models for Free", arXiv, 2023. https://arxiv.org/abs/2312.00858 (prior knowledge)
45. N. Carlini et al., "Extracting Training Data from Diffusion Models", arXiv, 2023. https://arxiv.org/abs/2301.13188 (prior knowledge)

35. Design a ChatGPT-like LLM Chatbot Platform: Serving, Safety, Evaluation & Feedback Loop

> Prompt as usually given: "Design ChatGPT", "Design a personal-assistant chatbot", "Design an LLM chatbot at scale (1M+ DAU)", "Design a large-scale LLM inference / serving platform", "Design a multi-tenant LLM inference API". Deep-dive variants: KV cache and continuous batching, small/large model routing, guardrails, RLHF/DPO feedback loop, eval harness.

> Compilation note (re-reviewed 2026-10-14): web search was exhausted and arxiv.org, openai.com, bytebytego.com, huyenchip.com and igotanoffer.com did not resolve from the build environment. GitHub pages marked "fetched" were re-read in this review. (ch-ref) = verified in an earlier chapter; (known; not fetched) = standard paper cited from prior knowledge. Numbers marked "typical assumption" are interview-style estimates.

Company tags

Company	Basis	Production system it mirrors
OpenAI	"ChatGPT" (message tree, resumable stream, stop cancels backend work) credited to OpenAI by a question bank; team, date and round unknown [5]	ChatGPT: InstructGPT-style SFT + RLHF model behind a streaming chat service [15][23]
Anthropic	"LLM Inference API" (token-bucket admission, 429 + Retry-After, batching, sticky routing) from self-reported, unverified candidate reports [5]	Claude API; RLHF + Constitutional AI training [16][17]

Reference systems (not interview tags): Meta PurpleLlama safety stack (Llama Guard 1-4, Prompt Guard 2, Code Shield, LlamaFirewall) [11][22] and Llama 2-Chat RLHF recipe [24]; LMSYS FastChat (controller + model workers) and Chatbot Arena (1.5M+ votes) [9][37].

Portals covering this problem.

Portal / source	Coverage	Link
ByteByteGo - Aminian & Sheng, "Generative AI System Design Interview", Ch. 4 "ChatGPT: Personal Assistant Chatbot"	Full chapter: data (Common Crawl, C4), pretraining, SFT, RLHF/DPO, sampling, benchmark + safety eval, Chatbot Arena (80 refs)	[1][2]
alirezadir GenAI / Agentic interview prep	Template 1 "LLM Chatbot at Scale" and Template 3 "LLM Inference and Serving Platform" (must-cover + bar-raiser lists) [3]; MLSD question bank lists "Chatbot system" and "LLM-powered customer-support chatbot" [4]	[3][4]
evgenyvinnik llm-driven-system-design	"ChatGPT" (planned; OpenAI attribution) and "LLM Inference API" (Anthropic attribution) problem specs and traps	[5]

Portal / source	Coverage	Link
Chip Huyen, "AI Engineering" + "Building a GenAI platform"	Eval methodology, inference optimization, guardrails, user feedback chapters	[13] [14]
Educative "Grokking the Generative AI System Design", "LLMOps"	Training, inference, scaling, evaluation; observability and cost	[30] [31]
IGotAnOffer, Hello Interview, Exponent	Generic OpenAI / GenAI / MLSD framework guides; coverage of this exact problem not verified (sites unreachable)	[32] [33] [34] [35]

Requirements & scale

Dimension	Requirement / number	Source
Functional	Multi-turn chat, streaming tokens, stop / regenerate / edit (branching message tree), history + multi-device sync, file/tool use optional	[5]
Functional	Safety: refuse disallowed content, resist jailbreak / prompt injection, PII handling	[3][11][12]
Functional	Feedback: thumbs up/down, regenerate, A/B side-by-side; used for evals and preference data	[3][9]
Non-functional	TTFT p50 < 0.5-1 s, TPOT 20-50 ms (20-50 tok/s), p99 tracked separately	typical assumption; metrics named in [3]
Non-functional	Availability 99.9%+ (typical assumption); multi-region + provider failover, GPU-scarcity fallback	[3]
Users	100M WAU, 10M DAU-concurrent peak sessions ~1M	typical assumption
QPS	~10 msgs/user/day x 50M DAU = 5e8/day -> ~6k avg, ~20k peak req/s	typical assumption
Tokens	~1.5k input (history+system) + ~400 output per turn -> ~8M output tok/s peak	typical assumption
GPU math	~2.5k-5k output tok/s per 8-GPU node (70B, batched) -> 2k-3k nodes at peak	typical assumption
Context	8k-128k window (typical assumption); token budgeting + history compression	[3]
Cost	Cost per request / per 1M tokens; route by query difficulty	[3]
Tenancy	Charge est. input + max_tokens to per-org token bucket; 429 + Retry-After; separate interactive vs bulk queues	[5]

Diagram 1 - Online serving path

DIAGRAM 1: End-to-end request path (gateway -> context -> input safety -> router -> inference cluster -> output safety -> SSE stream), with stores and logging




Diagram 2 - Offline training, evaluation & feedback loop

DIAGRAM 2: Pretrain -> SFT -> preference tuning -> eval gates -> registry -> canary, closed by the production feedback loop (thumbs, regenerations, red-team, arena)




Diagram 3 - Model architecture

DIAGRAM 3: Decoder-only chat LLM (inference view) plus the reward / safety classifier heads that share the same backbone family





Diagram 4 - Variant: LLM inference platform internals (vLLM / DistServe style)

DIAGRAM 4: Inside one model pool - scheduler, KV-cache manager, prefill/decode disaggregation and autoscaling (synthesised from [6][7][20][21][39])



Data & labels

Data	Use	Label / signal	Notes
Web crawl (Common Crawl, C4), code, books	Pretraining	Next token (self-supervised)	Dedup, lang-id (fastText/langid), quality + toxicity filters [1]
Human demonstrations	SFT	Ideal response per prompt	~10k-100k high-quality; plus Alpaca/Dolly/FLAN-style sets [1][15]
Pairwise comparisons	Reward model / DPO	A > B (+ ties)	Labeler rankings of K samples [15] [16][18]
Production implicit feedback	Preference mining, eval sets	Thumbs, regenerate (= reject), edit, copy, abandon	Noisy, biased toward vocal users; needs consent + de-id [13]
Arena / side-by-side votes	Model ranking	Elo / Bradley-Terry	1.5M+ votes in Chatbot Arena [9] [37]
Red-team prompts	Safety RM, refusal SFT, eval	Harm category, should-refuse	Human + automated red-teaming [25]
Moderation dataset	Input/output classifiers	Hazard taxonomy (MLCommons)	Llama Guard 3 categories [11][22]

Features / context signals

Group	Examples	Where used
Conversation	System prompt, last N turns, rolling summary, current leaf of branch	Context builder [5]
User	Memory facts, language, locale, custom instructions, tier	Context builder, router, rate limit
Retrieved	Web search / file / RAG chunks, tool results	Context builder [12]
Request	Est. input tokens + max_tokens, priority, tenant	Gateway token bucket, scheduler [5]
Router signals	Query length, domain, difficulty-clf score, prefix-cache locality	Small vs large routing [3]
Safety	Moderation scores per category, jailbreak score, PII spans	Input/output rails [11][12]

Model choices (baseline -> advanced)

Component	Baseline	Advanced	Tradeoff
Chat model	Hosted API (one model)	Own SFT + RLHF/DPO model family (small/large, MoE)	Control + cost at scale vs time-to-market
Alignment	SFT only	RLHF (RM + PPO) [15] -> DPO [18] / Constitutional AI [17]	PPO: strong but unstable/costly; DPO: simple, offline
Routing	Single model	Difficulty classifier / cascade small->large	Cost down 2-5x; risk of misroutes
Serving engine	HF generate, static batch	vLLM / SGLang: continuous batching, PagedAttention / RadixAttention, prefix cache, chunked prefill (TGI archived 2026, points to vLLM/SGLang) [6][8][38]	2-4x+ throughput from memory efficiency [7]

Component	Baseline	Advanced	Tradeoff
Caching	None	Prefix/KV cache for shared system prompt; exact + semantic response cache for repeated queries [6][13][14]	Semantic-cache false hits; never cache personalised answers
Model gateway	Direct calls to one backend	Unified gateway: auth, quotas, model-version routing, canary, fallback to other model/provider [3][13][14]	Extra hop; fallback model may differ in safety behaviour
Latency tricks	FP16	GQA, FlashAttention, FP8/INT4 quant, speculative decoding, P/D disaggregation [19][21][27][28]	Quality regressions from quant must be gated
Input safety	Keyword list + moderation API	Prompt Guard 2 + Llama-Guard-style clf + NeMo input/dialog rails; retrieval + execution rails for RAG/tools [11][12]	Latency + over-refusal vs coverage
Output safety	Post-hoc full-response check	Streaming chunk check + stop/replace	Must not add per-token latency
Eval	Static benchmarks	LLM-as-judge win-rate, MT-Bench, arena, red-team suites [10][37]	Judge bias (position, verbosity)

Loss / objectives

Stage	Objective
Pretraining	Cross-entropy next-token: -sum log p(x_t | x_<t)
SFT	Same CE, masked to assistant tokens only
Reward model	Bradley-Terry: -log sigmoid(r(x, y_w) - r(x, y_l)) [15]
RLHF (PPO)	max E[r(x, y)] - beta * KL(pi || pi_SFT) (+ pretrain mix) [15]
DPO	-log sigmoid(beta * [log pi(y_w)/pi_ref(y_w) - log pi(y_l)/pi_ref(y_l)]) [18]
Safety classifier	Multi-label BCE over hazard categories [22]
Router	BCE: P(small model answer is acceptable) from judge labels

Offline metrics

Area	Metrics
Capability	MMLU, GSM8K/MATH, HumanEval/MBPP, TriviaQA, HellaSwag, MT-Bench [1][10]
Preference	LLM-as-judge pairwise win-rate vs prod model; arena Elo [10][37]
Safety	Attack success rate on jailbreak suites (AdvBench), toxicity (RealToxicityPrompts), bias (BBQ), TruthfulQA, over-refusal rate [1]
Classifiers	Precision / recall / F1 per harm category, latency
Serving	TTFT, TPOT, p50/p95/p99, tokens/s/GPU, cost per 1M tokens [3]

Online metrics / A-B

Metric	Type	Note
Thumbs-up rate, thumbs-down rate	Quality (explicit)	Sparse (<1-2% of turns rate); typical assumption
Regenerate rate, edit-and-resend rate	Quality (implicit)	Strong negative signal
Conversation length, D1/D7 retention, sessions/user	Engagement	Long convo can also mean failure
Side-by-side pick rate	Preference	Shown occasionally ("which response do you prefer?")
Safety incident rate, refusal rate, user reports	Guardrail	Both directions: harm and over-refusal
TTFT/TPOT p95, error + fallback rate, cost/conv	System	Guardrail metrics for every A-B [3]

Serving & latency budget (typical assumption, p95)

Step	Budget
Gateway auth + rate limit	10 ms
Load history + memory	20-40 ms
Retrieval / web tool (optional)	100-800 ms
Input guardrails (parallel clf)	20-50 ms
Router	5-10 ms
Queue + prefill (2k tokens)	100-400 ms -> TTFT ~0.3-1 s
Decode	20-50 ms / token (TPOT)
Output guardrail per chunk (async, lagging window)	~0 added TTFT, small buffer

Monitoring

What	Signal / alert
Capacity	Queue depth, KV-cache utilisation, preemption rate, GPU util
Latency	TTFT / TPOT p95/p99 per model, per region
Quality drift	Daily judge win-rate on sampled prod traffic, thumbs-down spike, regenerate spike
Safety	Block rate per category, new jailbreak clusters, user reports
Cost	$/1M tokens, router small-model share, cache hit rate
Reliability	Error rate, stream disconnects, fallback-to-other-provider count

Failure modes

Failure	Mitigation
KV-cache OOM under long contexts	Paged KV, admission control, preempt/swap, max context per tier [7]
Head-of-line blocking by long prompts	Chunked prefill, P/D disaggregation, separate interactive/batch queues [21] [39]

Failure	Mitigation
Jailbreak / prompt injection via tools	Prompt Guard, retrieval/execution rails, least-privilege tools [11][12]
Hallucination	RAG with citations, refusal training, judge-based monitoring
Over-refusal after safety tuning	Track over-refusal eval; safety RM separate from helpfulness RM [24]
Reward hacking (verbosity, sycophancy)	KL penalty, length-controlled judges, fresh human evals
Feedback loop bias	Sample beyond thumbs; stratify; human review before training
Stream drop mid-generation	Resumable SSE: client resends Last-Event-ID and reattaches to the same generation; persist partial output [5]
User presses Stop but GPU keeps decoding	Abort upstream request so the sequence leaves the batch and frees KV blocks [5]
Cancel races completion	One atomic state transition decides outcome; edge-assigned request id owns the work [5]
Bad rollout (quality/latency regression)	Shadow + canary + automatic rollback on guardrail metrics

Interviewer follow-ups

- How does the KV cache work, and how much GPU memory does it need for 70B at 32k context?
- When would you use static vs continuous batching, quantization, or speculative decoding? [3]
- How would you route between a small and a large model, and how do you label the router? [3]
- How do you reduce p99 latency without hurting answer quality? [3]
- Why separate prefill and decode? What metric does each one control?
- How do you rate-limit fairly by tokens per org when output length is unknown? [5]
- How do you handle stop, regenerate, edit (branching), and a client reconnecting mid-stream? [5]
- How do you keep a conversation sticky to a replica (consistent hashing with bounded load) and what happens once output has started? [5]
- Where would you cache (prefix KV, exact, semantic), and what must never be cached? [13][14]
- How do you manage context beyond the window (truncate, summarise, memory)?
- RLHF vs DPO: tradeoffs, and how do you prevent reward hacking?
- How do you turn thumbs and regenerations into training data without bias or privacy issues?
- How do you evaluate a new model before launch? Benchmarks vs LLM-as-judge vs arena vs A-B.
- Where do guardrails sit, and how do you moderate a stream without adding latency?
- How do you defend against jailbreaks and prompt injection from retrieved pages?
- Capacity math: how many GPUs for 20k req/s peak, and how do you autoscale?
- Multi-region and provider failover: what state must be replicated?

Portal comparison

Portal	Framing	Emphasis	Gaps
ByteByteGo GenAI book Ch. 4 [1][2]	"ChatGPT: personal assistant chatbot"	Model lifecycle: data, pretrain, SFT, RLHF/DPO, sampling, benchmark + safety + arena eval	Light on serving infra (batching, KV, routing)
alirezadir GenAI prep [3]	"LLM Chatbot at Scale" + "LLM Inference and Serving Platform" templates	Pipeline gateway -> context -> safety -> inference -> moderation -> stream; TTFT/TPOT; routing; KV reuse; capacity math	Checklist style, no worked diagrams
evgenyvinnik [5]	ChatGPT product (OpenAI) / Inference API (Anthropic)	Product + backend: message tree, resumable streams, cancel, token-bucket, batch dispatch, drain	Mock model; no training/alignment
Chip Huyen AIE / GenAI platform [13][14]	Generic GenAI platform	Context construction, guardrails, router, cache, eval pipeline, user feedback	Not interview-formatted
Educative Grokking GenAI SD / LLMOps [30] [31]	Generative AI system design course	Training, inference, scaling, evaluation, observability	Paywalled; not fetched

References

1. ByteByteGo, "generativeAI" reference list, Chapter 4 "ChatGPT: Personal Assistant Chatbot", GitHub, 2024. https://github.com/ByteByteGoHq/generativeAI/blob/main/README.md#chapter-4-chatgpt-personal-assistant-chatbot (fetched)
2. A. Aminian, H. Sheng, "Generative AI System Design Interview", ByteByteGo, 2024. https://bytebytego.com/ (site root; book page not fetched)
3. alirezadir, "GenAI and Agentic System Design Interview Prep", Agentic-AI-Systems, GitHub, 2026. https://github.com/alirezadir/Agentic-AI-Systems/blob/main/06_interview_prep/genai-agentic-system-design.md (fetched)
4. alirezadir, "ML System Design" (Chatbot system; Generative AI / LLM Systems (2026) sample questions), Machine-Learning-Interviews, GitHub, 2026. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (fetched)
5. E. Vinnik, "llm-driven-system-design" ROADMAP (ChatGPT; LLM Inference API), GitHub, 2026. https://github.com/evgenyvinnik/llm-driven-system-design/blob/main/ROADMAP.md (fetched)
6. vLLM project, "vllm" repository README, GitHub, 2026. https://github.com/vllm-project/vllm (fetched)
7. W. Kwon et al., "Efficient Memory Management for Large Language Model Serving with PagedAttention", SOSP / arXiv, 2023. https://arxiv.org/abs/2309.06180 (known; not fetched)
8. SGLang project, "sglang" repository README, GitHub, 2026. https://github.com/sgl-project/sglang (fetched)
9. LMSYS, "FastChat" repository (Vicuna, Chatbot Arena, MT-Bench, serving), GitHub, 2024. https://github.com/lm-sys/FastChat (fetched)
10. L. Zheng et al., "Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena", NeurIPS / arXiv, 2023. https://arxiv.org/abs/2306.05685 (known; not fetched)
11. Meta, "PurpleLlama" (Llama Guard 1-4, Prompt Guard 2, Code Shield, LlamaFirewall, CyberSecEval), GitHub, 2026. https://github.com/meta-llama/PurpleLlama (fetched)

12. NVIDIA, "NeMo-Guardrails" (input, dialog, retrieval, execution, output rails), GitHub, 2025. https://github.com/NVIDIA/NeMo-Guardrails (fetched)
13. C. Huyen, "AI Engineering" table of contents (Ch. 3-4 evaluation, Ch. 9 inference optimization, Ch. 10 guardrails and user feedback), GitHub, 2025. https://github.com/chiphuyen/aie-book/blob/main/ToC.md (fetched; Ch. 10 guardrails, router + gateway, caches, user feedback)
14. C. Huyen, "Building A Generative AI Platform", huyenchip.com, 2024. https://huyenchip.com/2024/07/25/genai-platform.html (ch-ref)
15. L. Ouyang et al., "Training language models to follow instructions with human feedback" (InstructGPT), NeurIPS / arXiv, 2022. https://arxiv.org/abs/2203.02155 (known; not fetched)
16. Y. Bai et al., "Training a Helpful and Harmless Assistant with Reinforcement Learning from Human Feedback", arXiv, 2022. https://arxiv.org/abs/2204.05862 (known; not fetched)
17. Y. Bai et al., "Constitutional AI: Harmlessness from AI Feedback", arXiv, 2022. https://arxiv.org/abs/2212.08073 (known; not fetched)
18. R. Rafailov et al., "Direct Preference Optimization: Your Language Model is Secretly a Reward Model", NeurIPS / arXiv, 2023. https://arxiv.org/abs/2305.18290 (known; not fetched)
19. Y. Leviathan, M. Kalman, Y. Matias, "Fast Inference from Transformers via Speculative Decoding", ICML / arXiv, 2022. https://arxiv.org/abs/2211.17192 (known; not fetched)
20. G.-I. Yu et al., "Orca: A Distributed Serving System for Transformer-Based Generative Models", OSDI, 2022. https://www.usenix.org/conference/osdi22/presentation/yu (known; not fetched)
21. Y. Zhong et al., "DistServe: Disaggregating Prefill and Decoding for Goodput-optimized Large Language Model Serving", OSDI / arXiv, 2024. https://arxiv.org/abs/2401.09670 (known; not fetched)
22. H. Inan et al., "Llama Guard: LLM-based Input-Output Safeguard for Human-AI Conversations", arXiv, 2023. https://arxiv.org/abs/2312.06674 (known; not fetched)
23. OpenAI, "Introducing ChatGPT", openai.com, 2022. https://openai.com/index/chatgpt/ (known; not fetched)
24. H. Touvron et al., "Llama 2: Open Foundation and Fine-Tuned Chat Models", arXiv, 2023. https://arxiv.org/abs/2307.09288 (known; not fetched)
25. D. Ganguli et al., "Red Teaming Language Models to Reduce Harms: Methods, Scaling Behaviors, and Lessons Learned", arXiv, 2022. https://arxiv.org/abs/2209.07858 (known; not fetched)
26. A. Holtzman et al., "The Curious Case of Neural Text Degeneration" (nucleus sampling), ICLR / arXiv, 2019. https://arxiv.org/abs/1904.09751 (known; not fetched)
27. T. Dao et al., "FlashAttention: Fast and Memory-Efficient Exact Attention with IO-Awareness", NeurIPS / arXiv, 2022. https://arxiv.org/abs/2205.14135 (known; not fetched)
28. J. Ainslie et al., "GQA: Training Generalized Multi-Query Transformer Models from Multi-Head Checkpoints", EMNLP / arXiv, 2023. https://arxiv.org/abs/2305.13245 (known; not fetched)
29. R. Pope et al., "Efficiently Scaling Transformer Inference", MLSys / arXiv, 2022. https://arxiv.org/abs/2211.05102 (known; not fetched)
30. Educative, "Grokking the Generative AI System Design", educative.io, 2025. https://www.educative.io/courses/generative-ai-system-design (link from alirezadir genai-

resources; not fetched)
31. Educative, "LLMOps", educative.io, 2025. https://www.educative.io/courses/llmops (link from alirezadir genai-resources; not fetched)
32. IGotAnOffer, "OpenAI System Design Interviews", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/openai-system-design-interview (ch-ref)
33. IGotAnOffer, "Generative AI System Design Interview", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/generative-ai-system-design-interview (ch-ref)
34. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery (ch-ref)
35. Exponent, "Introduction to the ML System Design Interview" (course), tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
36. E. Yan et al., "Applied LLMs: What We've Learned From A Year of Building with LLMs", applied-llms.org, 2024. https://applied-llms.org/ (ch-ref)
37. W.-L. Chiang et al., "Chatbot Arena: An Open Platform for Evaluating LLMs by Human Preference", ICML / arXiv, 2024. https://arxiv.org/abs/2403.04132 (known; not fetched)
38. Hugging Face, "text-generation-inference" repository (maintenance mode; archived 21 Mar 2026), GitHub, 2026. https://github.com/huggingface/text-generation-inference (fetched)
39. A. Agrawal et al., "Taming Throughput-Latency Tradeoff in LLM Inference with Sarathi-Serve" (chunked prefill), OSDI / arXiv, 2024. https://arxiv.org/abs/2403.02310 (known; not fetched)

36. Design an A/B Testing / Experimentation Platform for ML Models (Airbnb ERF, Netflix XP, Amazon Weblab)

> Sourcing note (review run 2026-10-14): web search was unavailable and most non-GitHub hosts did not resolve from this sandbox. Verified this run: [10], [11], [12], [13], [15] (HTTP 200). Other references are well-known public sources cited from prior knowledge; URLs not re-checked. Company rows below are tied to each company's published platform, not to verified interview reports.

Company tags

Company (published platform)	Framing seen	Ref
Airbnb	"Design an experiment reporting framework (ERF)", plus metric pipelines and dimension cuts	[1][2]
Netflix	"Design the A/B platform behind personalization", covering allocation, cells, interleaving	[3][4][5]
Amazon	"Design Weblab": treatment dialing, launch gating, metric scorecards	[9]
Uber	"Design XP": many experiment types, a stats engine, staged rollout	[6]
Google	"Overlapping experiments at scale": layers and domains	[7]
Microsoft / Spotify	Scorecards, variance reduction, SRM alerts, guardrails	[8][9][15] [18]
Any MLSD loop	"How do you A/B test a new ranker?" is the online-testing step of most MLSD answers	[10][16]

Portals that cover this problem, either as a full problem or as the "online evaluation" step of every design:

Portal	Coverage	Link
alirezadir/Machine-Learning-Interviews	Step 8 "A/B, bandits, shadow, canary" checklist	[10]
khangich/machine-learning-interview	Lists the Kohavi et al. A/B testing book as a resource	[11]
Chip Huyen, "Designing ML Systems" (Ch. 9)	Shadow, A/B, canary, interleaving, bandits	[16]
ByteByteGo (Xu & Aminian)	Online metrics and A/B test step in every chapter	[17]
Kohavi, Tang, Xu book	The reference text on platform architecture	[9]
GrowthBook (open source)	Reference implementation: flags + SDK, warehouse-native stats	[12] [13]

Requirements & scale

Category	Requirement	Value (typical assumption unless cited)
Functional	Define experiment: variants, targeting, allocation %, metrics, duration	-
Functional	Deterministic, sticky assignment (user, device, session, or cluster unit)	hash(unit_id, salt) [7]
Functional	Route traffic to model variants (A = prod ranker, B = new ranker)	-
Functional	Concurrent overlapping experiments without collisions	layers/domains [7]
Functional	Automated scorecards: lift, CI, p-value, guardrails, SRM	[1][4][8]
Functional	Ramp, stop, ship; kill-switch	-
Functional	Feature flags as the delivery vehicle; SDK fires a tracking callback on exposure	[12][13]
Functional	Warehouse-native analysis: stats from aggregates (sums, sums of squares), no row-level PII leaves the warehouse	[13]
Functional	Frequentist or Bayesian engine, custom priors, multi-armed bandits	[13]
Non-functional	Assignment latency	< 1-5 ms p99 (local SDK eval)
Non-functional	Availability	99.99%; fail-open to control
Non-functional	Trustworthiness	SRM checks, A/A tests, pre-registered metrics [9]
Scale	Concurrent experiments	1k-10k+ (Microsoft, Booking, Google scale [9])
Scale	Assignment / exposure events	100k-1M QPS; 10-100B events/day
Scale	Users	100M-1B units
Scale	Metrics per scorecard	100s-1000s; daily batch plus near-real-time guardrails
Freshness	Scorecard refresh	Daily batch (ERF [1]); minutes for guardrails

Diagrams

DIAGRAM 1 - Online path: request -> assignment -> model-variant routing -> logged response




DIAGRAM 2 - Offline metrics pipeline: logs -> joins -> metrics -> stats -> scorecard -> decision (feedback loop)




DIAGRAM 3 - The "model": stats engine inputs/outputs





DIAGRAM 4 - Variant: Google-style layered assignment and the ML rollout ladder



Data & labels

Data	Source	Notes
Assignment/exposure	SDK log at decision time	Log only when the user is actually exposed (trigger analysis)
Outcome events	Product logs (click, book, play, revenue)	Joined after first exposure
Pre-period data	Same metrics, 1-4 weeks before	Covariates for CUPED [8]
Experiment metadata	Config service	Hypothesis, owner, OEC, guardrails, MDE

Features (unit-level covariates)

Feature	Use
Pre-experiment metric value	CUPED variance reduction (about 50% variance cut on Bing metrics [8])
Platform, country, tenure	Stratification and slices
New vs returning	Novelty/primacy checks
Bot / internal flags	Exclusion

Model choices (statistical method)

Level	Method	Tradeoff
Baseline	Fixed-horizon t-test, 50/50 split	Simple, but invalid if people peek at results
+	CUPED / regression adjustment	Smaller CI, needs pre-period data
+	Sequential testing (mSPRT, always-valid p) [14]	Safe to peek; slightly wider CI
+	Bayesian (posterior P(B>A), expected loss)	Intuitive; prior choice matters
+	Interleaving for rankers (Netflix reports ~100x fewer users needed) [5]	Very sensitive, but only gives a preference, not business lift

Level	Method	Tradeoff
Advanced	Multi-armed / contextual bandits	Less regret; harder inference, biased estimates
Advanced	Switchback / cluster randomization (marketplaces) [6]	Handles interference; less power

Loss / objective

Item	Definition
OEC	One pre-registered primary metric (e.g. bookings per user) [9]
Decision rule	Ship if OEC CI > 0, no guardrail breach, SRM pass
Bandit objective	Minimize cumulative regret

Offline metrics (platform health)

Metric	Target
A/A false-positive rate	about alpha (5%)
SRM rate across experiments	< 1-2% of experiments
Bucketing uniformity	chi-square pass
Offline-to-online correlation	Track for each model family

Online metrics / A-B

Type	Examples
OEC / primary	Bookings/user, watch hours, GMV/user
Guardrails	Latency p99, errors, crash rate, unsubscribes, revenue
Model-specific	CTR, NDCG@k from logs, coverage, diversity
Platform	Time to decision, % experiments that are well-powered

Serving & latency budget

Step	Budget
SDK hash + config lookup (in memory)	< 0.5 ms
Config refresh (push/poll)	10-60 s staleness OK
Model router to variant endpoint	+ 0 ms (pre-loaded)
Async exposure logging	Off the critical path
Shadow model	Async; never blocks response

Monitoring

Signal	Action
SRM ($p < 0.001$)	Invalidate scorecard, alert owner
Guardrail breach (near-real-time)	Auto-ramp-down or kill-switch
Logging drop or delay	Pipeline SLA alert
Interaction between concurrent experiments	Pairwise interaction detection
Novelty decay	Plot daily lift trend

Failure modes

Failure	Mitigation
Peeking leads to false positives	Sequential tests or fixed horizon [14]
SRM from bot filtering or redirects	Exposure-based logging, SRM gate
Network effects / interference (marketplace)	Cluster or switchback randomization, two-sided tests
Feedback loop: B model trains on A's data	Train per-variant or use a holdout; flag data leakage
Carryover from reused buckets	Re-salt per experiment, cooldown
Too many metrics, false discoveries	FDR control, pre-registered OEC
Long-term vs short-term mismatch	Long-running holdouts, surrogate metrics

Interviewer follow-ups

- How do you guarantee sticky assignment across devices and logged-out users?
- How do you run 1,000 concurrent experiments without collisions (layers/domains)?
- What is SRM, how do you detect it, and what causes it?
- How do you compute sample size / MDE, and what if traffic is too low?
- Explain CUPED. Why does it reduce variance and not bias?
- How do you handle peeking? Sequential vs Bayesian?
- How do you compute variance for ratio metrics like CTR (delta method)?
- How do you A/B test a ranking model: interleaving vs A/B?
- Marketplace interference (Airbnb, Uber): how do you randomize?
- How do you avoid the feedback loop where the new model trains on logs from the old model?
- How do you pick the OEC and guardrails? What if metrics disagree?
- Offline metrics improved but online did not. Why?
- How do you measure long-term effects and novelty or primacy effects?
- When would you use bandits instead of A/B?
- How do you make the platform fail open, and what is the latency impact?
- Warehouse-native (query the customer warehouse) vs a streaming metrics pipeline: tradeoffs in freshness, cost, privacy? [13]
- Why compute every test from sufficient statistics (n, sum, sum of squares) per variant, and how does that scale to 1000s of metrics? [13]

Portal comparison

Portal	Framing	Emphasis	Gaps
alirezadir GitHub [10]	Step 8 of every MLSD answer	Checklist: A/B, bandits, shadow, canary	No architecture or stats depth
Chip Huyen DMLS [16]	Ch. 9 "Continual learning & test in prod"	Shadow, canary, interleaving, bandits	No platform infra
ByteByteGo ML book [17]	Online eval section per chapter	Online metrics, A/B per problem	Platform not a standalone chapter
Kohavi et al. book [9]	Full platform design	SRM, OEC, CUPED, trust	Not interview-formatted
Company blogs [1]-[6]	Real systems	Pipelines, scale, sequential, interleaving	No interview structure
GrowthBook docs [12][13]	Open-source platform	SDK tracking callback, fact tables, CUPED, sequential, SRM, bandits	Not interview-formatted

References

1. "Experiment Reporting Framework", Airbnb Engineering (Medium), 2014, https://medium.com/airbnb-engineering/experiment-reporting-framework-4e3fcd29e6c0
2. "Scaling Airbnb's Experimentation Platform", Airbnb Engineering (Medium), 2017, https://medium.com/airbnb-engineering/https-medium-com-jonathan-parks-scaling-erf-23fd17c91166
3. "It's All A/Bout Testing: The Netflix Experimentation Platform", Netflix Tech Blog, 2016, https://netflixtechblog.com/its-all-a-bout-testing-the-netflix-experimentation-platform-4e1ca458c15
4. "Reimagining Experimentation Analysis at Netflix", Netflix Tech Blog, 2019, https://netflixtechblog.com/reimagining-experimentation-analysis-at-netflix-71356393af21
5. "Innovating Faster on Personalization Algorithms at Netflix Using Interleaving", Netflix Tech Blog, 2017, https://netflixtechblog.com/interleaving-in-online-experiments-at-netflix-a04ee392ec55
6. "Under the Hood of Uber's Experimentation Platform", Uber Engineering, 2018, https://www.uber.com/blog/xp/
7. Tang et al., "Overlapping Experiment Infrastructure: More, Better, Faster Experimentation", Google Research (KDD), 2010, https://research.google/pubs/overlapping-experiment-infrastructure-more-better-faster-experimentation/
8. Deng, Xu, Kohavi, Walker, "Improving the Sensitivity of Online Controlled Experiments by Utilizing Pre-Experiment Data" (CUPED), WSDM, 2013, https://exp-platform.com/Documents/2013-02-CUPED-ImprovingSensitivityOfControlledExperiments.pdf
9. Kohavi, Tang, Xu, "Trustworthy Online Controlled Experiments: A Practical Guide to A/B Testing", Cambridge University Press, 2020, https://experimentguide.com/
10. alirezadir, "Machine-Learning-Interviews: ML System Design", GitHub, 2023-2025, https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md
11. khangich, "machine-learning-interview", GitHub, 2021-2024, https://github.com/khangich/machine-learning-interview
12. GrowthBook, "growthbook: open-source feature flagging and experimentation", GitHub, 2024, https://github.com/growthbook/growthbook

13. GrowthBook, "docs/overview.mdx" (feature flags, warehouse analysis, CUPED, sequential, SRM, bandits), GitHub, 2025, https://github.com/growthbook/growthbook/blob/main/docs/overview.mdx
14. Johari, Pekelis, Walsh, "Always Valid Inference: Bringing Sequential Analysis to A/B Testing", arXiv, 2015, https://arxiv.org/abs/1512.04922
15. "Experimentation Platform (ExP)", Microsoft Research, ongoing, https://www.microsoft.com/en-us/research/group/experimentation-platform-exp/
16. Chip Huyen, "Designing Machine Learning Systems" (Ch. 9), O'Reilly, 2022, https://www.oreilly.com/library/view/designing-machine-learning/9781098107956/
17. Ali Aminian and Alex Xu, "Machine Learning System Design Interview", ByteByteGo, 2023, https://bytebytego.com/intro/machine-learning-system-design-interview
18. "Spotify's New Experimentation Platform (Part 1)", Spotify Engineering, 2020, https://engineering.atspotify.com/2020/10/spotifys-new-experimentation-platform-part-1

37. Design an ML Platform: Feature Store + Training + Model Serving (Uber Michelangelo, Meta FBLearner)

> Sourcing note (review, 2026-10): non-GitHub hosts (uber.com, engineering.fb.com, doordash.engineering, infoq.com, arxiv.org) did not resolve from this environment, and the web-search budget was exhausted. Fetched and read: GitHub sources [5] [20][21][22][23][30]. The curated lists [20][21] confirm titles, years, and URLs for [1][2][4][6]-[10][14][15][18][31][33][34]. Platform numbers for Michelangelo and FBLearner are quoted from those posts and were not re-read in this pass. Tags below name the company whose published system the framing comes from. How often each company asks this question was not verified.

Company tags

Company (system the framing comes from)	Typical framing	Ref
Uber	"Design Michelangelo": self-serve feature store, training, deploy, and online predictions for ETA, pricing, and fraud	[1][4][35]
Meta	"Design FBLearner": feature store, Flow (training DAGs), Predictor (serving); also "design a training data pipeline for recsys"	[2][3][11] [19]
Airbnb	"Design a feature platform with point-in-time-correct backfills" (Zipline, open-sourced as Chronon)	[10][23]
DoorDash	"Design a low-latency online feature store" (Redis, billions of features); declarative real-time features (Riviera, Fabricator)	[8][18][34]
LinkedIn	"Design a feature store / feature registry" (Feathr)	[9][30]
Netflix, Lyft, Shopify	"Design an ML platform for data scientists"; fact store / time travel (Netflix), feature serving (Lyft)	[15][16] [17][31] [33]
Google	"Design a TFX-style pipeline": data validation, training, model analysis, push to serving	[12]

Portals and sources that cover this problem, either as a full problem or as the "serving / MLOps" step of every design:

Portal / source	Coverage	Link
alirezadir/Machine-Learning-Interviews	Step 5: static (from feature store) vs dynamic (computed online) features; step 7: batch / online / hybrid prediction; step 8: A/B, bandits, shadow, canary; step 9: logging, monitoring, drift	[22]
Chip Huyen, "Designing ML Systems" (Ch. 7, 10) and the earlier GitHub notes	Batch vs online prediction, feature stores, ML platform components	[25] [26]
ByteByteGo (Xu & Aminian)	Serving section of each chapter: batch vs online, feature store, model compression	[27]

Portal / source	Coverage	Link
Exponent / Hello Interview	Infra-style "design an ML platform / model serving" prompts; delivery framework	[28] [29]
Educative (Khang Pham MLSD)	Feature store, training pipeline, and serving chapters	[24] [32]
eugeneyan/applied-ml, visenger/awesome-mlops	Curated feature-store and ML-platform case studies (Feature Stores, Existing ML Systems sections)	[20] [21]
Open-source feature platforms (Feast, Chronon, Feathr)	Reference designs: offline + online store, PIT-correct backfills, registry, online/offline consistency checks	[5] [23] [30]

Requirements & scale

Category	Requirement	Value (typical assumption unless cited)
Functional	Register features once and reuse them in training and serving	Michelangelo: about 10k shared features (2017) [1]
Functional	Point-in-time-correct training sets (no label leakage)	[5][10]
Functional	Batch, streaming, and on-demand (request-time) features	Hive + Kafka/Flink + request [1][4]
Functional	Reproducible training workflows (DAGs), hyperparameter search, experiment tracking	FBLearner Flow [2]
Functional	Model registry, evaluation reports, one-click deploy, rollback	[1]
Functional	Online, batch, and embedded (library) prediction; shadow/A-B	[1][11]
Functional	Monitoring: prediction logging, joining with outcomes, drift	[1]
Non-functional	Online feature read latency	p99 under 5-10 ms for a batch of about 100 features
Non-functional	Prediction latency	Michelangelo: P95 under 5 ms (no Cassandra features), under 10 ms with Cassandra [1]
Scale	Prediction QPS	Michelangelo: 250k+ pred/s for the top model (2017) [1]; about 10M pred/s at peak (2024) [35]; FBLearner: 6M+ pred/s (2016) [2]
Scale	Models / users	Thousands of models in production; 25%+ of FB engineering used FBLearner Flow [2]
Scale	Online store size	TB-scale key-value; DoorDash stores billions of feature values in Redis [8]
Non-functional	Freshness	Batch: daily; streaming: seconds to minutes
Non-functional	Availability	99.99% serving; fall back to default or last-known feature values

Category	Requirement	Value (typical assumption unless cited)
Governance	Lineage, ownership, ACLs, PII tagging, feature deprecation	[9][14][30]
Functional	Online/offline consistency measured, not assumed: log online fetches, replay as a backfill, compare	[23]
Functional	Input data validation before training (schema, ranges, missing values)	[12]

Diagrams

Diagram 1. End-to-end online path: request to feature assembly to inference to policy to response, with the feature store, model store, and logging




Diagram 2. Offline pipeline: logging to labels/joins to features to training to evaluation to registry to deployment, with the feedback loop




Diagram 3. The core component, feature store internals: a feature definition becomes offline and online materialization




Diagram 4. Point-in-time (AS-OF) join, which prevents leakage when the spine is built





Diagram 5. Real systems side by side: Uber Michelangelo (2017, with Palette) and Meta FBLearner (2016)



Data & labels

Data	Source	Notes
Entity snapshots	DB CDC dumps into the lake	Daily partitions; keyed by entity_id
Events	Kafka topics	Feed both stream features and the offline log
Request context	Prediction request	Only available at serve time; it must be logged so training can use it
Labels	Outcome tables (trip ETA actual, chargeback, click)	Delayed; label window and maturity cutoff per use case
Prediction logs	Serving fleet	Features-as-served give skew-free training data ("log and wait")

Features (platform-level feature types)

Type	Example	Store / compute	Freshness
Batch aggregate	restaurant avg prep time over 30d	Spark to offline, then copied online	Daily
Streaming aggregate	restaurant prep time, last 1h	Flink to online and offline log	Seconds to minutes
On-demand / request	distance(pickup, dropoff), hour-of-day	Computed in the serving container (DSL)	Real time
Embeddings	user / item vectors	Batch job to the online KV or a vector index	Daily

Type	Example	Store / compute	Freshness
Cross / derived	ratio of two features	DSL transform, shared code for training and serving	Inherits from inputs

Model choices (platform design choices, baseline to advanced)

Decision	Baseline	Advanced	Trade-off
Feature store	Shared tables + ad-hoc Redis	Registry + dual store + PIT joins (Feast, Palette, Feathr)	Consistency and reuse vs build cost
Transform logic	Separate SQL (train) and Java (serve)	One DSL compiled for both [1]	Removes skew; DSL expressiveness is limited
Training orchestration	Cron + notebooks	DAG workflows (FBLearner Flow, Airflow, Kubeflow, Flyte) [2][16]	Reproducibility vs flexibility
Model formats	Per-team servers	Standard artifact + feature spec; GBDT/DNN runtimes	Simpler ops; harder for exotic models
Serving	One service per model	Multi-tenant prediction service with routing by tag	Efficiency vs noisy neighbors
Online store	Redis	Cassandra / ScyllaDB / custom KV with compression [8]	Latency vs cost per TB
Scope	Platform for ML engineers	Self-serve for analysts (Looper-style AutoML) [11]	Adoption vs guardrails

Loss / objective

Level	Objective
Per model	Defined by the team (log-loss, MAE, ranking loss); the platform supplies standard evaluators
Platform	Minimize time-to-production and skew incidents; maximize feature reuse and serving efficiency (cost per 1k predictions)

Offline metrics

Metric	Target (typical)
Model quality vs champion (AUC, MAE, NDCG) by slice	Gate: no regression above threshold
Training-serving skew (feature value mismatch rate)	Under 0.1% of sampled keys
PIT-join correctness tests (no feature_ts > label_ts)	0 violations
Backfill time for a new feature (1 year of history)	Hours, not days
Pipeline success rate / reproducibility (same snapshot gives same metrics)	Above 99%

Online metrics / A-B

Metric	Use
Business KPI of each model (ETA error, fraud loss, CTR)	A/B of challenger vs champion, routed by the platform
Shadow-mode score diff	Safety check before any user exposure
Platform KPIs: models shipped/week, time idea to prod, % features reused	Platform-team success
Serving p50/p99, error rate, cost per prediction	SLO dashboards

Serving & latency budget

Stage (online prediction, about 10 ms p99)	Budget
Gateway + routing	1 ms
Online feature multi-get (batched, local-AZ KV)	3-4 ms
On-demand transforms	0.5 ms
Inference (GBDT on CPU, or a small DNN)	2-4 ms
Post-processing + async logging	0.5 ms
Options	Batch prediction precomputed into the KV for slow-changing outputs; library mode (in-process) for ultra-low latency; GPU servers with dynamic batching for large DNNs

Monitoring

Signal	How
Feature freshness lag	Per-feature watermark vs SLA; page the owner
Feature distribution drift (PSI, null %)	Compare online samples with training stats from the registry
Prediction drift / calibration	Logged predictions joined with delayed outcomes [1]
Skew	Log online fetches, replay them as an offline backfill, compare per key and ts (Chronon-style) [23]; Diagram 3
Data validation	Schema and distribution checks on every training snapshot; block the run on anomalies [12]
Serving health	p99, QPS, timeouts, fallback rate, per-tenant quotas
Lineage / audit	Model to features to data sources, for incidents and deprecation

Failure modes

Failure	Mitigation
Training-serving skew (different code paths)	Single DSL, logging of features-as-served, skew monitors [1][23]
Hidden pipeline debt (glue code, undeclared consumers, feedback loops)	Registry of consumers, typed feature contracts, ownership [13]

Failure	Mitigation
Label leakage from non-PIT joins	AS-OF join API by default; tests that flag future timestamps
Stale online features (stream job down)	TTLs, freshness alerts, fallback to batch values
Hot keys / KV overload	Caching, request coalescing, replicas, compression [8]
Bad model pushed	Eval gate, shadow, canary, auto-rollback on SLO or KPI breach
Feature deleted or changed under a live model	Versioned features, consumer registry, deprecation workflow
Cost explosion (unused features)	Usage tracking, auto-expire unused features, tiered storage
Noisy neighbor in a multi-tenant serving fleet	Per-model resource isolation, quotas, separate pools for tier-0 models

Interviewer follow-ups

- How do you guarantee a training row never sees a feature value from after its label timestamp?
- Why keep both an offline and an online store? Could one store serve both?
- How do you make the transform code identical in training and serving (DSL, shared library, or logging features-as-served)?
- A new streaming feature needs 1 year of history to train on. How do you backfill it?
- How would you bring p99 online feature reads under 5 ms with 300 features per request at 1M QPS?
- How do you detect and debug training-serving skew in production?
- How do you deploy and roll back a model safely (shadow, canary, A/B by tag)?
- Batch vs online vs embedded prediction: when would you choose each?
- How do you support thousands of per-city or partitioned models without thousands of services?
- What metadata goes into the model registry, and how do you reproduce a model from 6 months ago?
- How do you handle delayed labels (fraud chargebacks after 60 days) in retraining and monitoring?
- How would you make the platform self-serve for non-ML engineers (Looper / AutoML)?
- How do you manage GPU training capacity across teams (quotas, preemption, priority)?
- How do you govern PII features (ACLs, retention, deletion requests)?
- How does the platform change for LLMs (prompt/model registry, gateway, evaluation)? [35]
- How do you prove online and offline features match (log-and-replay consistency score) and alert on it? [23]
- How do you backfill a windowed aggregate for a new feature over a year of events without recomputing the world (tiled / incremental aggregation)? [23][33]
- Where would you put data validation, and what happens to a scheduled retrain when it fails? [12]

Portal comparison

Source	Framing	Emphasis	Gaps
Uber Michelangelo blog [1][35]	End-to-end platform as six workflow steps	Shared feature store, DSL, eval reports, deploy modes, P95 latency	Light on governance and cost
Meta FBLearner [2] [3]	Feature Store + Flow + Predictor	Reusable DAG workflows, experiment management at scale	Few details on the feature store internals
Feast / Tecton docs [5][7]	Feature store as a data layer	Offline/online stores, PIT correctness, materialization	Training and serving are out of scope
Chronon / Feathr READMEs [23][30]	Feature platform as code	PIT backfills, online fetch API, registry and lineage, consistency checks	No model training or serving
Chip Huyen DMLS [25]	Infra and tooling chapter	Batch vs online prediction, feature store, build vs buy	No interview-style walkthrough
alirezadir template [22]	MLSD step checklist	Static vs dynamic features, deployment, monitoring	Treats the platform as a sub-step
ByteByteGo / Educative [27][32]	Per-problem serving sections	Batch vs online serving, model compression	No standalone platform chapter

References

1. Uber Engineering, "Meet Michelangelo: Uber's Machine Learning Platform", uber.com, 2017. https://www.uber.com/blog/michelangelo-machine-learning-platform/
2. Meta Engineering, "Introducing FBLearner Flow: Facebook's AI backbone", engineering.fb.com, 2016. https://engineering.fb.com/ml-applications/introducing-fblearner-flow-facebook-s-ai-backbone/
3. ZenML MLOps Database, "Meta FBLearner: Introducing FBLearner Flow, Facebook's AI backbone" (summary), zenml.io, 2016. https://www.zenml.io/mlops-database/meta-fblearner-introducing-fblearner-flow-facebooks-ai-backbone
4. Uber, "Michelangelo Palette: A Feature Engineering Platform at Uber" (talk), InfoQ, 2019. https://www.infoq.com/presentations/michelangelo-palette-uber/
5. Feast, "feast: open source feature store for machine learning" README, GitHub, 2025. https://github.com/feast-dev/feast
6. Gojek / Google Cloud, "Introducing Feast: an open source feature store for machine learning", cloud.google.com, 2019. https://cloud.google.com/blog/products/ai-machine-learning/introducing-feast-an-open-source-feature-store-for-machine-learning
7. Tecton, "What is a Feature Store?", tecton.ai, 2020. https://www.tecton.ai/blog/what-is-a-feature-store/
8. DoorDash Engineering, "Building a Gigascale ML Feature Store with Redis, Binary Serialization, String Hashing, and Compression", doordash.engineering, 2020. https://doordash.engineering/2020/11/19/building-a-gigascale-ml-feature-store-with-redis/
9. LinkedIn Engineering, "Open sourcing Feathr: LinkedIn's feature store for productive machine learning", engineering.linkedin.com, 2022. https://engineering.linkedin.com/blog/2022/open-sourcing-feathr---linkedin-s-feature-store-for-productive-m
10. Airbnb, "Zipline: Airbnb's Machine Learning Data Management Platform" (talk), YouTube, 2018. https://www.youtube.com/watch?v=Tg5VEMEsC-0
11. Meta AI, "Inside Meta's AI optimization platform for engineers across the company" (Looper), ai.facebook.com, 2022. https://ai.facebook.com/blog/looper-meta-ai-optimiza

tion-platform-for-engineers/ (paper: https://arxiv.org/abs/2110.07554)
12. D. Baylor et al., "TFX: A TensorFlow-Based Production-Scale Machine Learning Platform", KDD / Google Research, 2017. https://research.google/pubs/tfx-a-tensorflow-based-production-scale-machine-learning-platform/
13. D. Sculley et al., "Hidden Technical Debt in Machine Learning Systems", NeurIPS, 2015. https://proceedings.neurips.cc/paper/2015/file/86df7dcfd896fcaf2674f757a2463eba-Paper.pdf
14. Hopsworks, "Feature Store: The missing data layer for Machine Learning pipelines?", hopsworks.ai, 2018. https://www.hopsworks.ai/post/feature-store-the-missing-data-layer-in-ml-pipelines
15. Netflix Tech Blog, "Evolution of ML Fact Store", netflixtechblog.com, 2022. https://netflixtechblog.com/evolution-of-ml-fact-store-5941d3231762
16. Lyft Engineering, "LyftLearn: ML Model Training Infrastructure built on Kubernetes", eng.lyft.com, 2021. https://eng.lyft.com/lyftlearn-ml-model-training-infrastructure-built-on-kubernetes-aef8218842bb
17. Shopify Engineering, "The Magic of Merlin: Shopify's New Machine Learning Platform", shopify.engineering, 2022. https://shopify.engineering/merlin-shopify-machine-learning-platform
18. DoorDash Engineering, "Introducing Fabricator: A Declarative Feature Engineering Framework", doordash.engineering, 2022. https://doordash.engineering/2022/01/11/introducing-fabricator-a-declarative-feature-engineering-framework/
19. M. Zhao et al. (Meta), "Understanding Data Storage and Ingestion for Large-Scale Deep Recommendation Model Training", arXiv, 2021. https://arxiv.org/abs/2108.09373
20. E. Yan, "applied-ml: papers and tech blogs on ML in production" (Feature Stores, MLOps Platforms sections), GitHub, 2024. https://github.com/eugeneyan/applied-ml
21. visenger, "awesome-mlops" (Feature Stores, Existing ML Systems sections), GitHub, 2024. https://github.com/visenger/awesome-mlops
22. alirezadir, "ML System Design" template, GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md
23. Airbnb, "Chronon: a data platform for serving AI/ML applications" README, GitHub, 2025. https://github.com/airbnb/chronon
24. khangich, "machine-learning-interview" (Educative MLSD course companion notes), GitHub, 2021. https://github.com/khangich/machine-learning-interview
25. C. Huyen, "Designing Machine Learning Systems" (Ch. 7 Deployment, Ch. 10 Infrastructure and Tooling), O'Reilly, 2022. https://www.oreilly.com/library/view/designing-machine-learning/9781098107956/
26. C. Huyen, "machine-learning-systems-design", GitHub, 2019. https://github.com/chiphuyen/machine-learning-systems-design
27. A. Aminian & A. Xu, "Machine Learning System Design Interview", ByteByteGo, 2023. https://bytebytego.com/intro/machine-learning-system-design-interview
28. Exponent, "Introduction to the ML System Design Interview" (course), tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro
29. Hello Interview, "ML System Design in a Hurry: Delivery Framework", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/in-a-hurry/delivery
30. Feathr (LinkedIn, now LF AI & Data), "feathr" README, GitHub, 2024. https://github.com/feathr-ai/feathr

31. Lyft Engineering, "ML Feature Serving Infrastructure at Lyft", eng.lyft.com, 2021. https://eng.lyft.com/ml-feature-serving-infrastructure-at-lyft-d30bf2d3c32a
32. Educative / K. Pham, "Machine Learning System Design" (course), educative.io, 2021. https://educative.io/courses/machine-learning-system-design/introduction
33. Netflix Tech Blog, "Distributed Time Travel for Feature Generation", netflixtechblog.com, 2016. https://netflixtechblog.com/distributed-time-travel-for-feature-generation-389cccdd3907
34. DoorDash Engineering, "Building Riviera: A Declarative Real-Time Feature Engineering Framework", doordash.engineering, 2021. https://doordash.engineering/2021/03/04/building-a-declarative-real-time-feature-engineering-framework/
35. Uber Engineering, "From Predictive to Generative: How Michelangelo Accelerates Uber's AI Journey", uber.com, 2024 (host unreachable in this review). https://www.uber.com/blog/from-predictive-to-generative-ai/

38. Design Exploration for Cold-Start Items and Users (Bandits) in a Recommender

> How the prompt is usually worded: "Netflix shows one artwork per title. Pick the best image for each member" [1], or "New creators and new items never get impressions. Fix the cold start" [16][17]. It also comes up as a follow-up to any recommendation question: "How do you balance exploration and exploitation?" [16][17][18]. Variants: Spotify Home shelves (BaRT) [3], DoorDash homepage explore/exploit [5], best merchant image [6], Twitter deep Bayesian bandits [7], Expedia cascade ranking [8].
>
> Sourcing note: written and reviewed after the shared web-search budget ran out; non-GitHub hosts returned 403 through the proxy. (fetched) = read from GitHub for this chapter. (list) = URL, title and company confirmed in a fetched curated list [19][22] but the page itself not re-read. (known) = canonical paper cited from memory. Details from (list) or (known) sources are flagged as such.

Company tags

Company	What is reported	Source
Netflix	The original product: per-member artwork chosen with contextual bandits. Netflix also published slate-bandit research	[1][2] (list)
Spotify	BaRT bandits for Home shelves and explanations. RL used to shift listening toward diverse content	[3][4] (list)
DoorDash	Homepage explore/exploit for new or rarely seen stores (UCB-style). Exploration to pick each merchant's image	[5][6] (list)
Expedia, Stitch Fix	Cascade bandits for ranking; a bandit experimentation platform	[8][9] (list)
Twitter	Meta-learning for cold-start items. Deep Bayesian bandits (dropout / bootstrap uncertainty) for exploration in ad recommendations	[10][7] (list)
Yahoo!	LinUCB news-article bandit and replay evaluation, the classic references	[11][12] (known)
Google/YouTube	Top-K off-policy REINFORCE recommender. Zero-shot transfer from recsys to cold-start search	[27] (known), [31] (list)
ByteDance/TikTok	For You feed deliberately mixes in videos outside a user's shown interests	[32] (list)
Coveo	Content-based inference of embeddings for new and rare products	[33] (list)

Meta, LinkedIn and others ask cold start and explore/exploit as generic recsys follow-ups (alirezadir and ByteByteGo templates [16][17][21]), but no company-specific source was verified, so they are not tagged.

Portals and sources that cover it

Portal / source	Treatment	Link
alirezadir / Machine-Learning-Interviews	The video and game recommendation templates each have a "Cold start problem" and an "Exploration exploitation trade-off (multi-armed bandit)" section. The MLSD template lists bandits under online testing	[16][17] [18] (fetched)
ByteByteGo (Aminian & Xu)	Ch. 6 (video recs) cites the multi-armed bandit as its explore/exploit reference. Ch. 10 (news feed) cites cold start	[21] (fetched)
Chip Huyen, Designing ML Systems	Ch. 9 "Continual Learning and Test in Production" has a contextual-bandits section; its resource list cites deep Bayesian bandits [7]	[22] (fetched: resources list)
E. Yan applied-ml list	Curates Netflix, Spotify, DoorDash, Expedia, Stitch Fix and Twitter cold-start and bandit posts	[19] (fetched)
Exponent, Hello Interview, Educative, IGotAnOffer	Generic recsys or MLSD frameworks with cold start as a follow-up. No bandit-specific write-up could be verified	[23][24] [25][26]

Requirements & scale

Dimension	Value	Basis
Functional	Pick an arm (artwork, new item, new creator) for each user and slot. Give new items a guaranteed but bounded number of impressions. Learn quickly from feedback	[1][5]
Arms per decision	Artwork: about 5-20 images per title. Item exploration: 10^2-10^4 cold candidates	assumption
Catalog	10^4 titles (Netflix-like) up to 10^8 items or creators (UGC)	assumption
Users	10^8 MAU. Interactions arrive in a stream	assumption
QPS	10^5 page requests/s at peak, each needing 10-100 bandit decisions	assumption
Latency	Policy step p99 under 10-20 ms inside a 150-200 ms page budget	assumption
Freshness	Posteriors and counts updated in minutes, and the model retrained daily	assumption
Exploration budget	1-10% of impressions, or a bounded regret target. Guardrails on watch time and retention	assumption
Non-functional	Log the propensity for every decision. Assign arms per session without flicker. Stay fair to new creators	[1][12]

Diagram 1: End-to-end architecture (online serving path)

Figure 38.1 - Serving path with a cold-start candidate source and a bandit policy layer




Diagram 2: Offline training & data pipeline

Figure 38.2 - Logged bandit feedback to off-policy evaluation and deployment




Diagram 3: Model architecture

Figure 38.3 - Neural contextual bandit with a content tower for cold arms





Diagram 4: Variant - the real systems (Netflix artwork, DoorDash, Spotify BaRT)

Figure 38.4 - Published production patterns (cold-start tower: [10][13])



Data & labels

Item	Choice
Unit of logging	(context x, arm a, propensity p(a given x), reward r, slot, timestamp) [1][12]
Reward	Artwork: play within the session or quality plays (exclude quick aborts) [1]. Items: click, then long dwell, save or follow

Item	Choice
Delayed reward	Join within an attribution window (for example 24 h). Count late rewards as positives when joined
Negatives	Impressed but not engaged. Skipped arms count only if actually viewed (viewport)
Explore data	Keep a uniformly randomized slice for unbiased evaluation [1][11][12]
Bias	Position and presentation bias. Trust only data that carries logged propensities

Features

Group	Examples	Cold-start relevance
User	Embedding, genre affinity, recency, device	New user: onboarding picks, geo/locale, device, popular prior
Item / arm content	Image embedding, text, genre, cast, creator follower count	Only signal on day 0 [10][13]
Item stats	Impressions, CTR posterior (alpha, beta), age	Low counts mean high uncertainty and a bigger bonus
Context	Time, row/shelf, page position, country	Artwork effect varies by context [1]
Cross	User genre x artwork theme, user x creator category	Personalized explore

Model choices (baseline -> advanced)

Level	Model	Pros	Cons
0	Popularity + fixed new-item boost	Simple	Not personalized; can be gamed
1	Epsilon-greedy over the ranker	Easy, gives propensities	Wastes traffic uniformly [3]
2	Beta-Bernoulli Thompson sampling per arm [14]	Efficient for few arms	No context; slow for long tail
3	LinUCB / linear TS, contextual [11]	Personalized, closed-form update	Linear; feature engineering
4	Neural bandit (NN + Bayesian last layer, ensembles) [15]	Rich features, shared learning	Calibration of sigma, cost
4b	Deep Bayesian bandit at production scale: MC dropout or bootstrapped heads on the ranker [7]	Reuses the existing ranker; cheap sigma	Uncertainty is approximate; needs tuning
5	Slate / cascade bandits, top-K off-policy RL [2][8][27]	Handles whole page	Complex, high variance
Cold-start add-on	Content tower, DropoutNet, meta-learning, content-to-embedding inference [10][13][33]	Day-0 scores	Needs good content features
Cold-start transfer	Zero-shot transfer of recsys embeddings to a new surface with no logs [31]	Launch a surface without data	Domain mismatch

Loss functions

Component	Loss
Reward model	Binary cross-entropy on r, weighted by 1/p(a given x) (IPS), clipped
Watch time	MSE or weighted logistic on log-duration
Cold tower	BCE plus an alignment loss: content embed close to learned ID embed (DropoutNet-style) [13]
Policy (RL variant)	REINFORCE with off-policy correction and a top-K correction [27]
Objective	Minimize cumulative regret, the sum over t of r(best arm) - r(chosen arm)

Offline metrics

Metric	Use
Replay / rejection-sampling estimate	Unbiased on uniformly random logs. Used for Netflix artwork and Yahoo! news [1][12]
IPS, SNIPS, doubly robust	Off-policy value with logged propensities [28]
AUC / log loss of reward model	Sanity check, sliced by cold vs warm
Calibration of sigma	Coverage of credible intervals
Simulated regret	Bandit simulator on historical data before launch

Online metrics / A-B

Metric	Goal
Take rate / play rate per impression	Primary for artwork [1]
New-item coverage	Percent of new items reaching N impressions within T hours
Time to first signal	Hours until a new item's posterior is confident
Creator retention	Percent of new creators posting again (supply side)
Diversity / filter bubble	Share of impressions outside a user's top interests; catalog coverage [4][32]
Guardrails	Session watch time, retention, complaints, latency
Test design	Bandit vs control A/B with user-level randomization. Keep an always-on random-explore bucket [9]

Serving & latency budget (assumption, page p99 about 200 ms)

Stage	Budget
Retrieval (warm ANN + cold pool + popular)	30 ms
Feature fetch	20 ms
Ranker with uncertainty head	50 ms
Bandit sampling (TS draw per arm, caps)	5-10 ms
Re-rank and artwork selection	10 ms
Logging (async)	0 ms on the critical path

Stage	Budget
Param store reads	Cached in-process and refreshed every 1-5 min

Monitoring

Signal	Alert on
Exploration rate	Drift from the target band (for example 5% plus or minus 1%)
Propensity logging	Missing or zero propensities (breaks OPE)
Posterior health	Arms stuck at the prior; variance collapse
Cold-item funnel	Drop in new items reaching the impression threshold
Reward delay	Rising join latency; reward-pipeline lag
Business guardrails	Watch-time regression in explore buckets

Failure modes

Failure	Mitigation
Over-exploration hurts users	Cap the explore share; explore only in low-cost slots; use TS, not uniform
Clickbait artwork wins on clicks	Reward quality plays, not clicks [1]
Feedback loop / rich-get-richer	Guaranteed impression budget for new items; diversity re-rank [4]
Non-stationarity (trends, novelty)	Discounted posteriors or sliding windows
Artwork flicker across sessions	Sticky per-member assignment for a period
Spam creators farming the boost	Quality and integrity gates before cold-pool entry
Delayed rewards bias the posterior	Pending-reward handling; batch updates after the window
Biased offline evaluation	Log propensities; keep a random bucket; use doubly robust estimators [28]

Interviewer follow-ups

- Why use a bandit instead of an A/B test for choosing artwork? What regret does A/B pay? [1][22]
- Thompson sampling vs UCB vs epsilon-greedy: which do you pick and why? [11][14]
- How do you evaluate a new policy offline without deploying it (replay, IPS, DR)? [12] [28]
- What do you log so that off-policy evaluation is possible later?
- How do you get a sigma (uncertainty) out of a deep ranker? [15]
- A new creator uploads a video. Walk through its first 24 hours of impressions.
- A new user has no history. What do you show first, and how fast do you personalize?
- How do you pick the explore budget, and who pays for it (which users or slots)?
- Rewards arrive hours later. How do you update the bandit?
- How do you stop clickbait thumbnails from winning? [1]
- How do you explore over a slate or whole page rather than one slot? [2][8]
- How do you handle non-stationary arm rewards (seasonality, trending)?
- How would you balance fairness to new creators against user engagement? [4]
- When would you move from bandits to full RL (long-term value)? [27]

- Your ranker is a deep net. How do you add exploration without a separate bandit model (dropout or bootstrap heads)? [7]
- You launch a new surface or market with no logs. How do you bootstrap it? [31]
- How do you keep users out of a filter bubble without hurting engagement? [4][32]

Portal comparison

Source	Framing	Cold-start answer	Exploration answer	Gap
alirezadir video/game recs [16][17]	Section inside the recsys template	Two-tower with profile features; show new items to random users, then fine-tune	Multi-armed bandit, defined briefly	No policy, logging or OPE detail
ByteByteGo ch. 6 / ch. 10 [21]	Follow-up in video and feed recs	Content features and popular prior	MAB reference only	No serving design for bandits
Chip Huyen DMLS ch. 9 [22]	Testing in production	n/a	Bandits vs A/B; contextual bandits as exploration	Not a full recsys design
Netflix artwork blog [1]	Real production system	Per-title image pool	Contextual bandit, randomized explore, replay metric	Not an interview script
DoorDash / Spotify blogs [3][5]	Real production systems	UCB bonus for rarely seen stores	Epsilon-greedy (BaRT), UCB (DoorDash)	Company-specific constraints

References

1. Netflix Technology Blog (A. Chandrashekar, F. Amat, J. Basilico, T. Jebara), "Artwork Personalization at Netflix", netflixtechblog.com, 2017. https://netflixtechblog.com/artwork-personalization-c589f074ad76 (list)
2. Netflix, "Marginal Posterior Sampling for Slate Bandits", IJCAI, 2019. https://www.ijcai.org/proceedings/2019/308 (list)
3. J. McInerney et al. (Spotify), "Explore, Exploit, and Explain: Personalizing Explainable Recommendations with Bandits", RecSys, 2018. https://dl.acm.org/doi/10.1145/3240323.3240354 (list)
4. Spotify Research, "Shifting Consumption towards Diverse Content via Reinforcement Learning", research.atspotify.com, 2022. https://research.atspotify.com/shifting-consumption-towards-diverse-content-via-reinforcement-learning/ (list)
5. DoorDash Engineering, "Homepage Recommendation with Exploitation and Exploration", doordash.engineering, 2022. https://doordash.engineering/2022/10/05/homepage-recommendation-with-exploitation-and-exploration/ (list)
6. DoorDash Engineering, "Selecting the Best Image for Each Merchant Using Exploration and Machine Learning", doordash.engineering, 2023. https://doordash.engineering/2023/01/04/selecting-the-best-image-for-each-merchant-using-exploration-and-machine-learning/ (list)
7. D. Guo, S. I. Ktena, F. Huszar, P. K. Myana, W. Shi, A. Tejani (Twitter), "Deep Bayesian Bandits: Exploring in Online Personalized Recommendations", RecSys, 2020. https://arxiv.org/abs/2008.00727 (list: [22] resources)

8. Expedia Group Tech, "How to Optimise Rankings with Cascade Bandits", medium.com, 2022. https://medium.com/expedia-group-tech/how-to-optimise-rankings-with-cascade-bandits-5d92dfa0f16b (list)
9. Stitch Fix, "Multi-Armed Bandits and the Stitch Fix Experimentation Platform", multithreaded.stitchfix.com, 2020. https://multithreaded.stitchfix.com/blog/2020/08/05/bandits/ (list)
10. M. Vartak et al. (Twitter), "A Meta-Learning Perspective on Cold-Start Recommendations for Items", NeurIPS, 2017. https://papers.nips.cc/paper/7266-a-meta-learning-perspective-on-cold-start-recommendations-for-items (list)
11. L. Li, W. Chu, J. Langford, R. Schapire, "A Contextual-Bandit Approach to Personalized News Article Recommendation", WWW, 2010. https://arxiv.org/abs/1003.0146 (known)
12. L. Li, W. Chu, J. Langford, X. Wang, "Unbiased Offline Evaluation of Contextual-bandit-based News Article Recommendation Algorithms", WSDM, 2011. https://arxiv.org/abs/1003.5956 (known)
13. M. Volkovs, G. Yu, T. Poutanen, "DropoutNet: Addressing Cold Start in Recommender Systems", NeurIPS, 2017. https://papers.nips.cc/paper/7081-dropoutnet-addressing-cold-start-in-recommender-systems (known)
14. O. Chapelle, L. Li, "An Empirical Evaluation of Thompson Sampling", NeurIPS, 2011. https://papers.nips.cc/paper/4321-an-empirical-evaluation-of-thompson-sampling (known)
15. C. Riquelme, G. Tucker, J. Snoek, "Deep Bayesian Bandits Showdown", ICLR, 2018. https://arxiv.org/abs/1802.09127 (known)
16. alirezadir, "Video Recommendation System" (mlsd-video-recom.md), GitHub, 2024. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/mlsd-video-recom.md (fetched)
17. alirezadir, "Game Recommendation System" (mlsd-game-recom.md), GitHub, 2024. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/mlsd-game-recom.md (fetched)
18. alirezadir, "ML System Design" template (ml-system-design.md), GitHub, 2025. https://github.com/alirezadir/Machine-Learning-Interviews/blob/main/src/MLSD/ml-system-design.md (fetched)
19. E. Yan, "applied-ml" (curated papers and tech blogs), GitHub, 2024. https://github.com/eugeneyan/applied-ml (fetched)
20. khangich, "machine-learning-interview", GitHub, 2021. https://github.com/khangich/machine-learning-interview (fetched)
21. ByteByteGo, "ml-bytebytego: Reference materials for ML System Design Interview" (ch. 6 ref 9, ch. 10 ref 16), GitHub, 2023. https://github.com/ByteByteGoHq/ml-bytebytego (fetched)
22. C. Huyen, "Designing Machine Learning Systems" (ch. 9), O'Reilly, 2022. https://www.oreilly.com/library/view/designing-machine-learning/9781098107956/ ; chapter resources: https://github.com/chiphuyen/dmls-book/blob/main/resources.md (fetched)
23. Exponent, "Introduction to the ML System Design Interview" (course), tryexponent.com, 2025. https://www.tryexponent.com/courses/ml-system-design/mlsd-intro (ch-ref)
24. Hello Interview, "Recommendation Systems (ML System Design pattern)", hellointerview.com, 2025. https://www.hellointerview.com/learn/ml-system-design/patterns/recommendation-systems (ch-ref)

25. Educative, "Grokking the Machine Learning Interview", educative.io, 2024. https://www.educative.io/courses/grokking-the-machine-learning-interview (ch-ref)
26. IGotAnOffer, "Machine Learning (ML) System Design Interview", igotanoffer.com, 2025. https://igotanoffer.com/en/advice/machine-learning-system-design-interview (ch-ref)
27. M. Chen et al. (Google/YouTube), "Top-K Off-Policy Correction for a REINFORCE Recommender System", WSDM, 2019. https://arxiv.org/abs/1812.02353 (known)
28. Y. Saito et al., "Open Bandit Dataset and Pipeline: Towards Realistic and Reproducible Off-Policy Evaluation", NeurIPS Datasets, 2021. https://arxiv.org/abs/2008.07146 (known)
29. Wikipedia, "Multi-armed bandit" (cited by ByteByteGo ch. 6). https://en.wikipedia.org/wiki/Multi-armed_bandit
30. Wikipedia, "Cold start (recommender systems)" (cited by ByteByteGo ch. 10). https://en.wikipedia.org/wiki/Cold_start_(recommender_systems)
31. Google, "Zero-Shot Heterogeneous Transfer Learning from Recommender Systems to Cold-Start Search Retrieval", CIKM, 2020. https://arxiv.org/abs/2008.02930 (list)
32. TikTok Newsroom, "How TikTok recommends videos #ForYou", newsroom.tiktok.com, 2020. https://newsroom.tiktok.com/en-us/how-tiktok-recommends-videos-for-you (list)
33. Coveo, "The Embeddings That Came in From the Cold: Improving Vectors for New and Rare Products with Content-Based Inference", RecSys, 2020. https://dl.acm.org/doi/10.1145/3383313.3411477 (list)