

✔ Congratulations! You passed!

Grade
received 83.33%

Latest Submission
Grade 83.33%

To pass 80% or
higher

Go to next item

1.

1 / 1 point

Error analysis

$m_{cv} = 500$ examples in cross validation set.

Algorithm misclassifies ~~100~~ ¹⁰⁰⁰ of them.

Manually examine 100 examples and categorize them based on common traits.

- Pharma: 21
- Deliberate misspellings (w4tches, med1cine): 3
- Unusual email routing: 7
- Steal passwords (phishing): 18
- Spam message in embedded image: 5

Which of these is a way to do error analysis?

- ☐ Collecting additional training data in order to help the algorithm do better.
- ☐ Calculating the test error J_{test}
- ☒ Manually examine a sample of the training examples that the model misclassified in order to identify common traits and trends.
- ☐ Calculating the training error J_{train}

✔ Correct


Correct. By identifying similar types of errors, you can collect more data that are similar to these misclassified examples in order to train the model to improve on these types of examples.

2.

1 / 1 point

Data augmentation

Augmentation: modifying an existing training example to create a new training example.



We sometimes take an existing training example and modify it (for example, by rotating an image slightly) to create a new example with the same label. What is this process called?

- ☒ Data augmentation
- ☐ Bias/variance analysis
- ☐ Error analysis
- ☐ Machine learning diagnostic


✔ Correct

Yes! Modifying existing data (such as images, or audio) is called data augmentation.

3.

0.5 / 1 point

Transfer learning



Option 1: only train **output layers** parameters.

Option 2: **train all parameters**.

What are two possible ways to perform transfer learning? Hint: two of the four choices are correct.

- ☐ You can choose to train all parameters of the model, including the output layers, as well as the earlier layers.
- ☐ Download a pre-trained model and use it for prediction without modifying or re-training it.
- ☒ You can choose to train just the output layers' parameters and leave the other parameters of the model fixed.



Correct

Correct. The earlier layers of the model may be reusable as is, because they are identifying low level features that are relevant to your task.

- ☒ Given a dataset, pre-train and then further fine tune a neural network on the same dataset.



This should not be selected