

✔ Congratulations! You passed!

Grade
received 80%

Latest Submission
Grade 80%

To pass 80% or
higher

Go to next item

1. Suppose your training examples are sentences (sequences of words). Which of the following refers to the j^{th} word in the i^{th} training example?

1 / 1 point

- ☒ $x^{(i)<j>}$
☐ $x^{<i>(j)}$
☐ $x^{(j)<i>}$
☐ $x^{<j>(i)}$


Expand

✔ Correct

We index into the i^{th} row first to get the i^{th} training example (represented by parentheses), then the j^{th} column to get the j^{th} word (represented by the brackets).

2. Consider this RNN:

0 / 1 point



True/False: This specific type of architecture is appropriate when $T_x = T_y$

- ☒ False
☐ True


Expand

✘ Incorrect

It is appropriate when the input sequence and the output sequence have the same length or size.

3. To which of these tasks would you apply a many-to-one RNN architecture? (Check all that apply).

1 / 1 point



- ☐ Speech recognition (input an audio clip and output a transcript)
☒ Sentiment classification (input a piece of text and output a 0/1 to denote positive or negative sentiment)

✔ Correct
Correct!

- ☐ Image classification (input an image and output a label)
☒ Gender recognition from speech (input an audio clip and output a label indicating the gender)

speaker's gender)


✓ Correct
Correct!

↗ Expand

✓ Correct
Great, you got all the right answers.

4. Using this as the training model below, answer the following:

0 / 1 point



True/False: At the t^{th} time step the RNN is estimating $P(y^{<t>})$


- ☐ False
- ☒ True

↗ Expand

✗ Incorrect
In a training model we try to predict the next steps based on the knowledge of all prior steps.

5. You have finished training a language model RNN and are using it to sample random sentences, as follows:

1 / 1 point



True/False: In this sample sentence, step t uses the probabilities output by the RNN to randomly sample a chosen word for that time-step. Then it passes this selected word to the next time-step.

- ☐ False
- ☒ True

↗ Expand

✓ Correct
Step t uses the probabilities output by the RNN to randomly sample a chosen word for that time-step. Then it passes this selected word to the next time-step.

6. True/False: If you are training an RNN model, and find that your weights and activations are all taking on the value of NaN ("Not a Number") then you have a vanishing gradient problem.

1 / 1 point

- ☐ True
- ☒ False

✓ Expand

✓ Correct

Vanishing and exploding gradients are common problems in training RNNs, but in this case, your weights and activations taking on the value of NaN implies you have an exploding gradient problem.

7. Suppose you are training an LSTM. You have a 10000 word vocabulary, and are using an LSTM with 100-dimensional activations $a^{<t>}$. What is the dimension of Γ_u at each time step?

1 / 1 point

- ☐ 1
- ☒ 100
- ☐ 300
- ☐ 10000

✓ Expand

✓ Correct

Correct, Γ_u is a vector of dimension equal to the number of hidden units in the LSTM.

8. Here are the update equations for the GRU.

1 / 1 point

GRU

$$\tilde{c}^{<t>} = \tanh(W_c[\Gamma_r * c^{<t-1>}, x^{<t>}] + b_c)$$

$$\Gamma_u = \sigma(W_u[c^{<t-1>}, x^{<t>}] + b_u)$$

$$\Gamma_r = \sigma(W_r[c^{<t-1>}, x^{<t>}] + b_r)$$

$$c^{<t>} = \Gamma_u * \tilde{c}^{<t>} + (1 - \Gamma_u) * c^{<t-1>}$$

$$a^{<t>} = c^{<t>}$$

Alice proposes to simplify the GRU by always removing the Γ_u . I.e., setting $\Gamma_u = 0$. Betty proposes to simplify the GRU by removing the Γ_r . I.e., setting $\Gamma_r = 1$ always. Which of these models is more likely to work without vanishing gradient problems even when trained on very long input sequences?

- ☐ Alice's model (removing Γ_u), because if $\Gamma_r \approx 0$ for a timestep, the gradient can propagate back through that timestep without much decay.
- ☐ Alice's model (removing Γ_u), because if $\Gamma_r \approx 1$ for a timestep, the gradient can propagate back through that timestep without much decay.
- ☒ Betty's model (removing Γ_r), because if $\Gamma_u \approx 0$ for a timestep, the gradient can propagate back through that timestep without much decay.
- ☐ Betty's model (removing Γ_r), because if $\Gamma_u \approx 1$ for a timestep, the gradient can propagate back through that timestep without much decay.

✓ Expand

✓ Correct

Yes. For the signal to backpropagate without vanishing, we need $c^{<t>}$ to be highly dependent on $c^{<t-1>}$.

9. Here are the equations for the GRU and the LSTM:

1 / 1 point

GRU

$$\tilde{c}^{<t>} = \tanh(W_c[\Gamma_r * c^{<t-1>}, x^{<t>}] + b_c)$$

$$\Gamma_u = \sigma(W_u[c^{<t-1>}, x^{<t>}] + b_u)$$

$$\Gamma_r = \sigma(W_r[c^{<t-1>}, x^{<t>}] + b_r)$$

$$c^{<t>} = \Gamma_u * \tilde{c}^{<t>} + (1 - \Gamma_u) * c^{<t-1>}$$

$$a^{<t>} = c^{<t>}$$

LSTM

$$\tilde{c}^{<t>} = \tanh(W_c[a^{<t-1>}, x^{<t>}] + b_c)$$

$$\Gamma_u = \sigma(W_u[a^{<t-1>}, x^{<t>}] + b_u)$$

$$\Gamma_f = \sigma(W_f[a^{<t-1>}, x^{<t>}] + b_f)$$

$$\Gamma_o = \sigma(W_o[a^{<t-1>}, x^{<t>}] + b_o)$$

$$c^{<t>} = \Gamma_u * \tilde{c}^{<t>} + \Gamma_f * c^{<t-1>}$$

$$a^{<t>} = \Gamma_o * c^{<t>}$$

From these, we can see that the Update Gate and Forget Gate in the LSTM play a role similar to _____ and _____ in the GRU. What should go in the blanks?

- ☒ Γ_u and $1 - \Gamma_u$
- ☐ Γ_u and Γ_r
- ☐ $1 - \Gamma_u$ and Γ_r

☐ Γ_r and Γ_u

[Expand](#)

✓ **Correct**
Yes, correct!

10. Your mood is heavily dependent on the current and past few days' weather. You've collected data for the past 365 days on the weather, which you represent as a sequence as $x^{<1>}, \dots, x^{<365>}$. You've also collected data on your mood, which you represent as $y^{<1>}, \dots, y^{<365>}$. You'd like to build a model to map from $x \rightarrow y$. Should you use a Unidirectional RNN or Bidirectional RNN for this problem?

1 / 1 point

- ☐ Unidirectional RNN, because the value of $y^{<t>}$ depends only on $x^{<t>}$, and not other days' weather.
- ☐ Bidirectional RNN, because this allows the prediction of mood on day t to take into account more information.
- ☐ Bidirectional RNN, because this allows backpropagation to compute more accurate gradients.
- ☒ Unidirectional RNN, because the value of $y^{<t>}$ depends only on $x^{<1>}, \dots, x^{<t>}$, but not on $x^{<1>}, \dots, x^{<365>}$.

[Expand](#)

✓ **Correct**