

```
import json, pandas as pd, io, glob, os
print(os.listdir())
```

```
ipynb_file = glob.glob('*.ipynb')[0]
print(f"File: {ipynb_file}")
```

```
with open(ipynb_file, 'r') as f:
    nb = json.load(f)
```

```
for cell in nb['cells']:
    source = ''.join(cell['source'])
    if 'Advertising' in source and 'csv' in source.lower():
        print(source[:1000])
```

```
['.config', 'polynomial-regression-advertising-csv.ipynb', 'sample_data']
File: polynomial-regression-advertising-csv.ipynb
```

```
import pandas as pd, glob
file = glob.glob('**/*.csv', recursive=True)[0]
df = pd.read_csv(file)
print(df.head())
```

	longitude	latitude	housing_median_age	total_rooms	total_bedrooms
0	-122.05	37.37	27.0	3885.0	661.0
1	-118.30	34.26	43.0	1510.0	310.0
2	-117.81	33.78	27.0	3589.0	507.0
3	-118.36	33.82	28.0	67.0	15.0
4	-119.67	36.33	19.0	1241.0	244.0

	population	households	median_income	median_house_value
0	1537.0	606.0	6.6085	344700.0
1	809.0	277.0	3.5990	176500.0
2	1484.0	495.0	5.7934	270500.0
3	49.0	11.0	6.1359	330000.0
4	850.0	237.0	2.9375	81700.0

```
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression

X = df.iloc[:, :-1]
y = df.iloc[:, -1]
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_

model = LinearRegression()
model.fit(X_train, y_train)
print(model.score(X_test, y_test))
```

```
0.6358044169850408
```

```
import glob, pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.ensemble import RandomForestRegressor

path = glob.glob('**/*.csv', recursive=True)[0]
df = pd.read_csv(path)
df = df.loc[:, ~df.columns.str.contains('^Unnamed')]

X = df.iloc[:, :-1]
y = df.iloc[:, -1]

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)

model = RandomForestRegressor(n_estimators=100, random_state=42)
model.fit(X_train, y_train)

print(model.score(X_test, y_test))
```

0.7367657879959226