PROJECT REPORT

Automated Healthcare Data Quality & Bias Audit Tool

Maternal Health / Obstetrics | 500 Patient Records | 8 Clinical Columns

Domain	Maternal Health / Obstetrics
Dataset	500 records — 8 clinical columns (PatientID, Age, DeliveryType, LaborDuration, Complications, LOS, Readmitted, Location)
Standards	NDHM | ICMR | FDA 21 CFR Part 11 | FDA AI/ML SaMD
Tool Files	audit.py (897 LOC) | batch_audit.py (262) | generate_pdfs.py (577) | generate_test_data.py (71)
Language	Python 3 — pandas, matplotlib, scipy, reportlab
Test Files	6 variants: clean, missing values, impossible values, duplicates, selection bias, measurement bias
Performance	All 6 files processed in under 2 seconds each | Max 1.51s
Outputs	JSON report, 8-panel PNG dashboard, comparison chart, compliance PDF — per file

1. Executive Summary

This report documents the design, implementation, and verified results of an automated data quality and bias audit tool built specifically for maternal health datasets. The tool ingests any CSV or Excel healthcare file, executes five quality checks and four bias detectors, scores the dataset against NDHM, ICMR, and FDA regulatory thresholds, and produces JSON results, an 8-panel PNG dashboard, a comparison report, and a regulatory compliance PDF — all in under two seconds per file.

Six variants of a real 500-patient obstetrics dataset were constructed and audited, each embedding a specific type of flaw. The tool detected every injected issue with 100% accuracy across all six files: missing clinical fields, clinically impossible values, duplicate records, rural patient exclusion, and systematic under-documentation of Cesarean delivery complications.

Files Audited	Detection Rate	Bias Categories	Max Runtime
6 / 6	100%	4 types	1.51 seconds

2. Project Overview

2.1 Objective

Healthcare datasets routinely contain data entry errors, missing records, and hidden demographic biases that produce incorrect clinical conclusions or systematically unfair AI models. This project builds a complete, reproducible audit pipeline that:

- Scans any healthcare CSV or Excel file and produces a scored quality report card
- Detects four categories of bias: selection, measurement, historical, and algorithmic
- Checks compliance against NDHM, ICMR, and FDA 21 CFR Part 11 regulatory thresholds
- Generates visual dashboards, a side-by-side comparison chart, and a compliance PDF automatically
- Processes any file under 10 seconds — actual performance is under 2 seconds per file

2.2 Source Dataset

The base dataset (test_clean.csv) contains 500 maternal health patient records with the following eight-column schema:

Column	Type	Valid Range	Description
PatientID	Integer	1 – 500	Unique patient identifier
Age	Integer	18 – 45 years	Maternal age at time of delivery (mean: 29.5)
DeliveryType	Category	Vaginal / Cesarean	Mode of delivery — 351 Vaginal, 149 Cesarean
LaborDuration	Float	0 – 72 hours	Duration of active labour in hours
Complications	Category	Yes / No	Complication recorded — 99 Yes, 401 No
LOS	Float	2 – 30 days	Inpatient length of stay (mean: 5.0 days)
Readmitted	Category	Yes / No	30-day readmission — 69 Yes, 431 No
Location	Category	Urban / Rural	Hospital location — 305 Urban, 195 Rural

2.3 Six Test Files

Six variants were generated from the clean baseline — each embedding one specific flaw to verify a distinct detection capability:

#	Filename	Flaw Injected	Purpose
1	test_clean.csv	None — original clean dataset	Gold standard / comparison baseline
2	test_missing.csv	Age NaN rows 50–100 (10.2%) | Complications NaN rows 20–40 (4.2%)	Tests completeness detection
3	test_impossible.csv	Age = 50 for rows 10–20 (max is 45) | LOS = 1 for rows 30–40	Tests validity and consistency checks
4	test_duplicates.csv	First 50 rows appended twice — 9.1% duplicate rate in 550-row file	Tests uniqueness and ID duplication
5	test_selection_bias.csv	All 195 rural patients removed — dataset is 100% Urban	Tests selection bias detection
6	test_measurement_bias.csv	18 Cesarean complication records flipped from Yes to No	Tests measurement bias detection

3. Tool Architecture

3.1 File Structure

Script	Lines	Responsibility
audit.py	897	Main engine: load file, run all checks, compute scores, save JSON and PNG report
batch_audit.py	262	Batch runner: processes all 6 test files and generates side-by-side comparison chart
generate_test_data.py	71	Creates all 6 test variants by injecting specific flaws into test_clean.csv
generate_pdfs.py	577	Generates comparison_report.pdf and compliance.pdf via ReportLab

3.2 Processing Pipeline

Every file runs through five sequential steps:

1. Load — detect CSV or Excel format and read into a pandas DataFrame
2. Quality checks — run completeness, validity, uniqueness, and consistency in parallel
3. Bias checks — run selection, measurement, historical, and algorithmic detectors
4. Scoring — compute weighted 0-100 score, assign grade A-D, evaluate regulatory thresholds
5. Output — write results JSON and 8-panel dark-theme PNG dashboard to the output directory

3.3 Output Files Per Run

File	Contents
<name>_audit.json	All issues, bias flags, component scores, regulatory flags, processing time
<name>_report.png	8-panel dashboard: score gauge, component bars, missing chart, severity pie, bias bar, histogram, issues table, compliance checklist
comparison_report.png	Side-by-side chart comparing all 6 files across every metric
comparison_report.pdf	Formatted comparison report with per-file analysis and methodology table
compliance.pdf	NDHM / ICMR / FDA alignment matrix, informed consent checklist, remediation guide

4. Quality Checking Module

The quality module runs four independent checks. Each returns a 0-1 score and a list of standardised issue dictionaries. Every issue carries: type, column, severity (HIGH / MEDIUM / LOW), the problematic value, a human-readable message, and a specific remediation recommendation.

4.1 Completeness

Flags columns with missing values above regulatory thresholds:

- MISSING_HIGH (HIGH severity): column missing rate > 20% — exceeds ICMR maximum
- MISSING_MODERATE (MEDIUM): column missing rate > 5% — exceeds FDA 21 CFR Part 11 threshold

Scoring formula: max(0, 1.0 - overall_missing_rate x 3). A dataset with 33% overall missing scores zero.

4.2 Validity

Checks each column against obstetrics-specific clinical valid ranges:

Column	Valid Range	Clinical Rationale
Age	18 – 45	Maternal reproductive age; values outside are biologically implausible
LOS	2 – 30	Minimum 2 days for inpatient birth; over 30 days is an extreme outlier
LaborDuration	0 – 72	Labour over 72 hours requires escalation; 0-72 covers all normal deliveries

Statistical outlier check also runs per column: if more than 5% of values have |Z-score| > 3, a MEDIUM flag is raised.

4.3 Uniqueness

- DUPLICATE_ROWS (HIGH if rate > 5%): exact full-row duplicates — FDA threshold is < 1%
- DUPLICATE_ID (HIGH): duplicate values in any column named 'id' or 'patient'

Scoring: max(0, 1.0 - duplicate_rate x 5). A 20% duplicate rate yields a score of zero.

4.4 Consistency

Applies obstetrics-specific cross-field logic:

- LOS_TOO_LOW (HIGH): any inpatient record with LOS < 2 days
- LOS_CESAREAN_LOW (MEDIUM): mean Cesarean LOS < mean Vaginal LOS — Cesarean requires longer recovery
- AGE_OUT_OF_RANGE (HIGH): maternal age outside 18-45 as a secondary cross-check layer

5. Bias Detection Module

The bias detector runs four independent checks. Protected attributes recognised in this dataset include: Location, DeliveryType, gender, sex, race, ethnicity, religion, caste, income, and insurance_type. Each check returns a list of standardised flag dictionaries carrying type, attribute, severity, message, and recommendation.

5.1 Selection Bias

Flags datasets where demographic groups are under-represented — making any trained model non-generalisable to excluded populations:

- Location balance: flags if any Location group (Urban/Rural) falls below 10% of the dataset
- Rural absence: specifically flags complete exclusion of rural patients — a known health-equity risk
- Age spread: flags if the dataset age range spans fewer than 10 years

Detected in File 5: Rural patients = 0% of 305 records. Urban-only datasets cannot inform rural maternal health policy or train generalisable models.

5.2 Measurement Bias

Flags systematic differences in how outcomes are recorded across delivery type groups — the most clinically dangerous bias type in obstetrics data:

- Complication rate disparity: flags if Cesarean complication rate is more than 30% below Vaginal rate
- Score column disparity: for any column containing 'score', 'rating', or 'index', flags if group means differ by over 30%

Detected in File 6: Cesarean rate dropped to 12.1% vs Vaginal 17.9% — a 33% relative gap caused by flipping 18 records from Yes to No.

5.3 Historical Bias

Applies the 4/5ths disparate impact rule to outcome columns by demographic group. If the complication or readmission rate ratio between best- and worst-performing Location groups falls below 0.80, a historical care-access inequity is flagged. This catches entrenched rural vs. urban outcome disparities that accumulate over time in health systems.

5.4 Algorithmic Bias

Detects proxy variables — numeric columns with strong correlation to a protected attribute (Spearman $r > 0.50$, $p < 0.05$). Proxy variables encode group bias into any ML model even

when the protected column is removed from training. Identified proxies trigger a MEDIUM flag with specific decorrelation recommendations.

6. Scoring and Regulatory Compliance

6.1 Weighted Score Formula

The overall quality score (0–100) is a weighted average of five dimensions:

Dimension	Weight	What Is Measured
Completeness	30%	Per-column missing rate penalised at 3x the rate if thresholds exceeded
Validity	25%	Impossible clinical values + statistical outliers per column (|Z| > 3 in > 5% of values)
Uniqueness	20%	Exact duplicate rows (rate x 5) and duplicate identifier column values
Consistency	10%	Domain-logic violations: LOS < 2 days, Age > 45, Cesarean LOS below Vaginal
Bias-Free	15%	Bias flag count: each flag deducts 12 points from this dimension

Grade scale: A >= 85 (Excellent) | B >= 70 (Good) | C >= 55 (Needs Work) | D < 55 (Do Not Use)

6.2 Regulatory Compliance Flags

A dataset is marked COMPLIANT only when its overall score is >= 70 AND all four regulatory thresholds pass:

Regulatory Flag	Standard	Threshold	Triggered In
Missing rate in critical fields	FDA 21 CFR Part 11	> 5%	File 2 (Age: 10.2%)
Duplicate record rate	FDA Data Integrity	> 1%	File 4 (9.1%)
Impossible clinical values present	NDHM Quality Standard	Any	File 3 (22 records)
Three or more bias flags	FDA AI/ML SaMD Guidance	>= 3	Not triggered in test set

7. Audit Results

7.1 Summary Table

File	Score	Grade	Missing	Dups	Impossible	Bias Flags	Time	Status
Clean Baseline	98.5	A	0.0%	0	0	0	1.41s	PASS
Missing Values	96.9	A	1.8%	0	0	0	1.39s	PASS
Impossible Values	95.2	A	0.0%	0	22	0	1.51s	FAIL
Duplicate Rows	89.4	A	0.0%	50	0	0	1.39s	FAIL
Selection Bias	98.2	A	0.0%	0	0	1	1.22s	PASS
Measurement Bias	96.7	A	0.0%	0	0	1	1.37s	PASS

7.2 Comparison Dashboard

The batch audit generates a multi-panel comparison chart covering overall scores, a quality-dimensions heatmap, issue counts by type, missing data rates, and per-file recommendations:

Maternal Health Dataset Aud
Overall Quality Scores
Pass (70)
Good (85)
Score /100
98 [A]
97 [A]
95 [A]
89 [A]
98 [A]
File 1 Clean
File 2 Missing Values
File 3 Impossible Values
File 4 Duplicates
File 5 Selection Bias
Quality Dimensions Heatmap
Completeness
Validity
Uniqueness
Bias-Free
100 95 100 100
100 100 93 100
100 100 100 54
100 100 100 100
File 1 Clean
File 2 Missing Values
File 3 Impossible Values
File 4 Duplicates
Issues by Type
Quality Issues
Duplicates
Bias Flags
File 1 Clean
File 2 Missing Values
File 3 Impossible Values
File 4 Duplicates
File 5 Selection Bias
File 6 Measurement Bias
Summary Ta

7.3 File-by-File Analysis

File 1: Clean Baseline (test_clean.csv)

Score	Grade	Completeness	Validity	Uniqueness	Status
98.5	**A**	100/100	100/100	100/100	**PASS**

The clean file establishes the quality gold standard. All 500 records are complete, unique, and within valid clinical ranges. The single MEDIUM consistency flag — Cesarean mean LOS (4.97 days) slightly below Vaginal (5.01 days) — reflects a genuine cohort pattern rather than a data error. Zero bias flags. This file is suitable for model training without modification.

Issues detected:

- [MEDIUM] LOS_CESAREAN_LOW — Cesarean mean LOS marginally below Vaginal (a baseline clinical observation, not a data error)

Maternal Health Datas
test_clean.csv
Overall Quality Score
98
Grade: A
COMPLIANT
Component Scores
bias_free
consistency
uniqueness
validity
completeness
0
20
40
60
Issues by Severity
0%
100%
MED
Bias Flags by Type
1.0
0.8
0.6
0.4
0.2
0.0
No Bias Detected
0.0
0.2
0.4
0.6
Top Issues & Recommenda

File 2: Missing Values (test_missing.csv)

Score	Grade	Completeness	Validity	Uniqueness	Status
96.9	**A**	94.6/100	100/100	100/100	**PASS**

Two MEDIUM issues detected. Age is missing for rows 50-100 (10.2%), triggering the FDA 21 CFR Part 11 critical-field threshold of <5%. Complications is missing for rows 20-40 (4.2%), which falls below the critical threshold and is not flagged as HIGH. The Completeness dimension drops to 94.6/100 but the overall score remains compliant because overall missing rate (1.8%) is well within the 20% ICMR ceiling.

Issues detected:

- [MEDIUM] MISSING_MODERATE — Age missing for 51 rows (10.2%), exceeds 5% FDA threshold
- [MEDIUM] LOS_CESAREAN_LOW — baseline pattern persists


Maternal Health Datas
test_missing.cs
Overall Quality Score
97
Grade: A
COMPLIANT
Component Scores
bias_free
consistency
uniqueness
validity
completeness
0
20
40
60
Issues by Severity
0%
100%
MED
Bias Flags by Type
1.0
0.8
0.6
0.4
0.2
0.0
No Bias Detected
0.0
0.2
0.4
0.6
Top Issues & Recommenda

File 3: Impossible Values (test_impossible.csv)

Score	Grade	Completeness	Validity	Uniqueness	Status
95.2	A	100/100	92.7/100	100/100	FAIL

Four HIGH-severity issues detected across two independent modules. The validity check fires first on the 11 Age=50 and 11 LOS=1.0 records using domain range tables. The consistency check then independently re-catches the same records through domain-logic rules (LOS_TOO_LOW, AGE_OUT_OF_RANGE). This dual detection demonstrates the value of layered checking: both modules must agree before a record is cleared. NDHM Quality Standard flag raised; dataset is NON-COMPLIANT.

Issues detected:

- [HIGH] IMPOSSIBLE_VALUE — 11 Age values = 50, outside valid range 10-45
- [HIGH] IMPOSSIBLE_VALUE — 11 LOS values = 1.0, outside valid range 2-30
- [HIGH] LOS_TOO_LOW — 11 inpatient records with LOS < 2 days
- [HIGH] AGE_OUT_OF_RANGE — 11 maternal ages exceed 45

Bias / regulatory flags:

- NDHM Quality Standard: Impossible clinical values detected

Maternal Health Datas
test_impossible.c
Overall Quality Score
95
Grade: A
ON-COMPLIAN
Component Scores
bias_free
consistency
uniqueness
validity
completeness
70
0
20
40
60
Issues by Severity
0%
100%
HIGH
Bias Flags by Type
1.0
0.8
0.6
0.4
0.2
0.0
No Bias Detected
0.0
0.2
0.4
0.6
Top Issues & Recommenda

File 4: Duplicate Rows (test_duplicates.csv)

Score	Grade	Completeness	Validity	Uniqueness	Status
89.4	**A**	100/100	100/100	54.5/100	**FAIL**

50 rows appended twice create a 550-row file with 9.1% duplicate rate — nine times the FDA maximum. Both the row-level and ID-level uniqueness checks fire simultaneously, catching the problem from two angles. The Uniqueness dimension collapses to 54.5/100, reducing the overall score to 89.4. The FDA Data Integrity regulatory flag is raised. This simulates a common ETL failure: a source data extract ingested twice without deduplication.

Issues detected:

- [HIGH] DUPLICATE_ROWS — 50 exact duplicate rows (9.1% of 550), FDA threshold <1%
- [HIGH] DUPLICATE_ID — PatientID has 50 non-unique values
- [MEDIUM] LOS_CESAREAN_LOW — baseline pattern persists

Bias / regulatory flags:

- FDA Data Integrity: Duplicate records exceed 1% threshold


Maternal Health Datas
test_duplicates.c
Overall Quality Score
89
Grade: A
ON-COMPLIAN
Component Scores
bias_free
consistency
uniqueness
54
validity
completeness
0
20
40
60
Issues by Severity
LOW
0%
MED
33%
67%
HIGH
Bias Flags by Type
1.0
0.8
0.6
No Bias Detected
0.4
0.2
0.0
0.0
0.2
0.4
0.6
Top Issues & Recommenda

File 5: Selection Bias (test_selection_bias.csv)

Score	Grade	Completeness	Validity	Uniqueness	Status
98.2	**A**	100/100	100/100	100/100	**PASS**

Perfectly clean on quality metrics: no missing data, no duplicates, no impossible values. Yet it is fatally biased. All 195 rural patients were removed, leaving a 100% urban dataset. The Bias-Free dimension drops from 100 to 88. Any model trained on this file cannot generalise to rural populations, which represent 39% of the original cohort. The file is technically compliant on quality but requires a critical scope-limitation disclaimer. The tool correctly separates quality and equity concerns.

Bias / regulatory flags:

- SELECTION_BIAS — Rural patients are completely absent (0% of 305 records)

Maternal Health Data
test_selection_bia
Overall Quality Score
98
Grade: A
COMPLIANT
Component Score
bias_free
consistency
uniqueness
validity
completeness
0
20
40
60
Issues by Severity
No Issues
Detected
1.0
0.8
0.6
0.4
0.2
0.0
0.0
0.2
0.4
0.6
0.8
1.0
Bias Flags by Typ
1
0
SELECTION
BIAS
Top Issues & Recommen

File 6: Measurement Bias (test_measurement_bias.csv)

Score	Grade	Completeness	Validity	Uniqueness	Status
96.7	**A**	100/100	100/100	100/100	**PASS**

Superficially clean: zero missing data, zero duplicates, no impossible values. The bias is subtle and dangerous. Eighteen Cesarean complication records were silently flipped from Yes to No, reducing the Cesarean complication rate from ~24% to 12.1% while Vaginal remained at 17.9%. The 33% relative gap triggers the measurement bias detector. A model trained on this file would systematically underestimate post-Cesarean complication risk — precisely the real-world pattern that perpetuates obstetric harm in under-resourced clinical settings.

Issues detected:

- [MEDIUM] LOS_CESAREAN_LOW — baseline pattern persists

Bias / regulatory flags:

- MEASUREMENT_BIAS — Cesarean complication rate (12.1%) much lower than Vaginal (17.9%), possible under-documentation


Maternal Health Datas
test_measurement_bi
Overall Quality Score
97
Grade: A
COMPLIANT
Component Scores
bias_free
consistency
uniqueness
validity
completeness
0
20
40
60
Issues by Severity
0%
100%
MED
Bias Flags by Type
1
0
MEASUREMENT BIAS
Top Issues & Recommenda

8. Regulatory Compliance Mapping

Every automated check the tool performs maps to a named regulatory requirement:

Audit Check	Standard	Threshold	Detected In
Missing > 5% in critical fields	FDA 21 CFR Part 11 §11.10	< 5%	File 2 (Age 10.2%)
Missing > 20% overall	ICMR Guidelines §4.3	< 20%	Not triggered
Duplicate records	FDA Data Integrity	< 1%	File 4 (9.1%)
Duplicate patient identifiers	NDHM Patient Registry	Zero	File 4 (50 IDs)
Maternal age outside 18-45	NDHM Obstetrics Standard	18-45 yrs	File 3 (11 records)
LOS < 2 days (inpatient)	NDHM Clinical Minimum	>= 2 days	File 3 (11 records)
Cesarean LOS < Vaginal LOS	NDHM Clinical Logic	Ces >= Vag	Files 1-4, 6
Statistical outliers |Z| > 3	ICMR Guidelines §5.1	< 5%/col	Not triggered
Rural patients < 10% of dataset	ICMR Equity / NDHM	> 10%	File 5 (0% rural)
Complication rate disparity > 30%	FDA AI/ML SaMD Guidance	< 30% gap	File 6 (33% gap)
Location-based outcome disparity	ICMR Equity (4/5ths rule)	Ratio >= 0.80	Where applicable
Proxy variable correlation r > 0.50	FDA Algorithmic Fairness	r < 0.50	Not triggered

9. Recommendations per File

File 1 — Clean Baseline

- No critical actions required. Suitable for model training as-is.
- Note the slight Cesarean LOS trend; verify it reflects local clinical practice and not a systematic coding pattern.
- Use as the reference distribution when validating future data collections from the same EHR system.

File 2 — Missing Values

- Impute Age with the median value (29.5 years); document the imputation method in the model card.
- Treat missing Complications as a separate binary indicator ('was this field assessed?') rather than imputing Yes/No.
- Apply multiple imputation (MICE) for statistically valid confidence intervals in downstream analyses.

File 3 — Impossible Values

- Query the source EHR to retrieve correct Age for the 11 records where Age = 50.
- Verify the 11 LOS = 1.0 records: are these day-case deliveries mislabelled as inpatient admissions?
- Add hard validation constraints to the data-entry form: Age must be 18-45, LOS must be >= 2 for any inpatient record.

File 4 — Duplicate Rows

- Run df.drop_duplicates() to remove all 50 exact duplicate rows before any analysis.
- Identify and fix the ETL pipeline step that caused the double-import — likely a source extract re-run without deduplication.
- Add a UNIQUE constraint on PatientID in the source database to prevent recurrence.

File 5 — Selection Bias

- Collect data from rural health centres and district hospitals before training any clinical AI model.
- If rural data remains unavailable, document the scope limitation in the model card and restrict deployment to urban facilities.
- Apply inverse-probability weighting (IPW) to correct the urban-heavy distribution for any statistical analysis.

File 6 — Measurement Bias

- Audit clinical coding practices at each contributing site specifically for Cesarean patient records.
- Cross-check all Cesarean records marked No Complications against surgical notes and discharge summaries.
- Retrain clinical coders on complication documentation standards; Cesarean complications must be coded with equal rigour to Vaginal.
- Set a minimum expected complication rate range (15-30%) as a recurring data quality trigger in future audits.

10. Success Criteria Verification

All four measurable success criteria defined at project inception were met:

Criterion	Target	Result
Catches all quality issues (missing values, impossible values, duplicates)	100% detection	**Detected in Files 2, 3, and 4**
Flags bias correctly in Files 5 and 6	Both detected	**Selection bias (File 5), Measurement bias (File 6)**
Processes each file in under 10 seconds	< 10 s per file	**Max 1.51s | Average 1.38s**
Provides actionable recommendation per issue	Per-issue guidance	**Every issue and flag includes a recommendation field**

11. Conclusion

The automated healthcare data quality and bias audit tool meets all stated project goals. By modularising quality checks and bias detectors as independent, composable functions — and grounding every threshold in a named regulatory standard — the tool produces reports that are technically correct, clinically meaningful, and immediately actionable for data engineering and research teams.

The obstetrics domain specialisation is central to its value. Generic data-quality scanners would flag missing values and duplicates but would miss the Cesarean complication under-documentation in File 6 and the rural exclusion in File 5 — the two most clinically consequential flaws. These required domain-specific rules: the Cesarean vs. Vaginal complication rate comparison and the urban/rural equity check.

All deliverables are fully reproducible. Running generate_test_data.py followed by batch_audit.py and generate_pdfs.py recreates the entire pipeline from the source CSV in under 15 seconds, with no manual steps required.