Certified reliability for any routing solver: screening buffered plans against travel-time uncertainty

Suhan Ali
Independent researcher, Lahore, Pakistan
syedsuhanali9@gmail.com ORCID 0009-0004-5079-7684

Abstract

Delivery firms promise time windows but plan with fixed travel times, and padding every trip says nothing about how reliable a plan is. We add a reliability layer to an unchanged routing solver. The solver plans with internal deadlines brought forward by up to an hour, capped so that no customer becomes unreachable; plans are simulated under correlated, time-dependent delays; and a plan is certified on independent simulated days with an exact binomial bound, so that it misses the target with probability at most 5%, whatever the solver. The guarantee is only as good as the delay model: under random incidents or a stronger morning peak, 86 and 78 of 130 certificates failed. Certifying against five models removed every failure but certified 76 of 159 instances instead of 131, with 0.65 more vehicles. Under the modelled delays, in four studies (three preregistered), none of the 666 certified plans failed on fresh days, 20% padding was never certified on a synthetic instance, and the gain came from the buffers and the screen, not the objective. Testing candidates in a fixed order certifies the cheapest qualifying plan with the same guarantee.

Keywords: vehicle routing; time windows; travel-time uncertainty; simulation; chance constraints; reliability certification

1 Introduction

A courier company that promises to deliver between 10:00 and 11:00 must decide which driver visits which customers, and in what order, so that every visit falls inside its window. This is the vehicle routing problem with time windows (VRPTW; Solomon, 1987; Toth and Vigo, 2014). Routing software usually solves it with one fixed table of travel times, but real travel times change with the time of day and with random events, and because a driver serves customers one after another, an early delay pushes every later visit towards the end of its window.

The common protection is padding: planning as if every trip took, say, 20% longer. It works with any solver, but it spends the same protection on quiet and congested trips, and it says nothing about the result: a planner who pads by 20% does not know whether the plan will be on time on 60% of days or on 99%. Methods that model the uncertainty directly, through chance constraints, recourse or robust optimization, spend protection more carefully (Laporte et al., 1992; Li et al., 2010; Errico et al., 2018; Agra et al., 2013; Ehmke et al., 2015), but they need a solver built for that model, which most firms do not have and cannot easily adopt. Simheuristics, which rank solutions by simulated reliability (Juan et al., 2015), are tied to their own search and report an estimate from the scenarios that guided it.

This paper takes the systems view of a firm that already has a routing solver and wants a reliability statement it can act on. We wrap the existing solver in a layer with three steps. The solver is asked for

a small family of plans whose internal deadlines, which customers never see, are brought forward by a buffer between 0 and 60 minutes. Each plan is simulated on 1000 days with time-of-day congestion and correlated random delays, and one plan is selected. The selected plan is then simulated on 5000 further days that were not used to produce or choose it, and it is *certified* if an exact binomial lower bound on its probability of a successful day reaches the target.

The certificate is a statement about the simulated delay model, and this is the layer's main vulnerability. When real delays are harsher than modelled, certificates fail: under random incidents and under a stronger morning peak, 86 and 78 of 130 certificates failed on fresh days. Certifying against several models at once removes these failures, but fewer instances then receive a certificate and the plans use more vehicles (Section 6.7). We report both sides throughout.

The contribution is a practical, reproducible reliability layer and the evidence for it, not new statistical theory: the guarantees rest on standard results, which we state for this setting and use as tools. The paper makes five contributions.

1. *A solver-independent certificate.* Applying the standard a posteriori argument of sampled chance-constrained programming (Luedtke and Ahmed, 2008; Campi and Garatti, 2008), we show that, under the modelled delays, the probability that a certified plan misses the reliability target is at most the chosen error level, for any solver, candidate family, selection rule or fallback, including a simheuristic used as the solver (Theorem 1). Testing the candidates in a fixed order, from the largest buffer down, then certifies the cheapest qualifying plan with the same guarantee (Proposition 4); this certified 228 of 265 instances against 218 for the screened plan, at no measurable cost. On fresh simulated days, none of the 666 plans certified in the main analysis failed its certificate, and we measure how the certificate fares when the delay model is wrong.

2. *A reachability cap.* A capped deadline never makes a customer unreachable (Lemma 1); it removes most screening failures and also repairs a budgeted robust model.

3. *The cost of reliability.* A buffered plan reaching 95% exists on twice as many instances as a plan padded by up to 50%, and uses fewer vehicles where both exist; this compares what the families can reach, not what the procedure selects.

4. *Certificates under a wrong delay model.* A certificate carries over to real delays no worse than modelled (Proposition 1), and certifying against a set of models guarantees each of them (Proposition 2); this removed every failure under harsher delays, at a measured cost. Certified slowdown and shift margins (Propositions 5 and 6) say how much slower than modelled, in percent or in minutes, every trip may be before a certificate breaks, and show why most certificates were fragile.

5. *Evidence beyond synthetic data.* Three confirmatory studies with hypotheses published in advance, benchmark instances, 40 real Amazon routes with delays fitted to New York taxi trips, and ablations that separate the screen from the objective. Real pickup operations with GPS tracks show which records a certificate can rest on (Appendix C), and Proposition 3 says how many days of history a certificate without a delay model needs.

2 Related work

Routing with random travel times has been studied for more than three decades (Laporte et al., 1992; Gendreau et al., 1996; Kenyon and Morton, 2003); Gendreau et al. (2016) survey the open problems. One line of work states on-time service as a chance constraint and optimizes it directly. Li et al. (2010) combine chance constraints and recourse in a tabu search, Ehmke et al. (2015) embed per-customer service levels in a routing heuristic, Taş et al. (2014) add time dependence with soft windows, Bomboi et al. (2022) check feasibility under correlated, time-dependent travel times, and Errico et al. (2018) solve the problem with stochastic service times exactly. Robust and risk-based models replace the probability with an uncertainty set or a risk index: Agra et al. (2013) solve a robust VRPTW with budgeted uncertainty sets in the sense of Bertsimas and Sim (2004), and Jaillet et al. (2016) and Zhang et al. (2019) route to minimize indices of how far arrival times can breach their windows. Closest in structure to the present paper, Zhang et al. (2021) minimize a service fulfilment risk index under a Wasserstein ambiguity set built from travel-time samples, and show that the problem reduces to the sample version with every deadline brought forward by a buffer. Their bound holds over the ambiguity set, the buffer is set by its radius, and the method lives inside a dedicated solver. Serrano et al. (2026) learn travel-time distributions from context. All of these build the uncertainty model into a specialist optimizer.

The internal deadlines used here are closest to self-imposed time windows, in which the carrier sets its own windows inside the promised ones so that slack absorbs delays (Jabali et al., 2015). Vareias et al. (2019) assess service reliability for such windows, and Hosseini et al. (2025) design the windows offered to customers under correlated travel times. Here the promised windows are fixed and the buffer is one number per plan, not a window per customer.

Simheuristics (Juan et al., 2015) are the closest methodological relative. They simulate promising solutions of a metaheuristic and use the simulated cost or reliability to steer and rank the search; Abdullahi et al. (2025) add an explicit reliability analysis for a sustainable routing problem with stochastic travel times and demands. Our layer does not change the search, so any solver, a simheuristic included, can produce the candidates, and the days used to make and choose a plan are never used to certify it, which is what makes an exact, finite-sample guarantee possible.

That separation is standard in stochastic programming. In sample approximations of chance-constrained programs, a candidate solution found on one sample is checked for feasibility on an independent sample (Luedtke and Ahmed, 2008; Ahmed and Shapiro, 2008), and the scenario approach gives a priori guarantees for convex problems (Campi and Garatti, 2008). We apply the a posteriori version to routing plans, where the problem is not convex and the guarantee must not depend on the solver. The exact binomial bound of Clopper and Pearson (1934) gives the certificate; the Wilson bound (Wilson, 1927), which behaves well near one (Brown et al., 2001), is used for the cheaper screen.

3 Problem and model

3.1 Routing model

Let $N = \{0, 1, \ldots, n\}$ be the nodes, with depot 0 and customers $C = N \setminus \{0\}$, and let V be a homogeneous fleet with capacity Q and maximum shift length H. Customer i has demand δ_i, service time s_i and a promised window $[l_i, u_i]$ in which service must start. The nominal distance and planning time of arc (i, j)

are d_{ij} and $\bar{t}_{ij}$. With binary arc variables x_{ijv}, assignment variables z_{iv} and vehicle-use variables y_v, service start times a_{iv}, depot departure and return times d_v, r_v, and slack deficits $G_{iv} \geq 0$, a plan satisfies

$$\sum_{v \in V} z_{iv} = 1, \quad \sum_j x_{ijv} = \sum_j x_{jiv} = z_{iv} \ (i \in C), \quad \sum_{j \in C} x_{0jv} = \sum_{i \in C} x_{i0v} = y_v, \quad \sum_{i \in C} \delta_i z_{iv} \leq Q y_v, \tag{1}$$

$$l_i z_{iv} \leq a_{iv} \leq u_i z_{iv}, \qquad a_{jv} \geq a_{iv} + s_i + \bar{t}_{ij} - M(1 - x_{ijv}), \qquad a_{jv} \geq d_v + \bar{t}_{0j} - M(1 - x_{0jv}), \tag{2}$$

$$r_v \geq a_{iv} + s_i + \bar{t}_{i0} - M(1 - x_{i0v}), \qquad 0 \leq d_v \leq r_v \leq H y_v, \qquad G_{iv} \geq a_{iv} - (u_i - s^*) z_{iv}, \tag{3}$$

for all $v \in V$, where M is a sufficiently large constant and $s^* = 15$ minutes is a target slack before the end of each window. The time constraints exclude subtours. Four criteria describe a plan: distance cost $F_1 = c \sum d_{ij} x_{ijv}$, slack deficit $F_2 = \sum G_{iv}$, driver time $F_3 = \sum_v (r_v - d_v)$ and vehicles used $F_4 = \sum_v y_v$. The planner minimizes

$$Z = \sum_{k=1}^{4} w_k \frac{F_k - L_k}{\max\{U_k - L_k, 1\}}, \tag{4}$$

where L_k and U_k are the smallest and largest values of F_k among four solutions that each minimize one criterion, and $w = (0.5693, 0.2643, 0.1055, 0.0609)$ is the principal eigenvector of an Analytic Hierarchy Process comparison matrix (Saaty, 1980) with consistency ratio 0.025, fixed before any experiment. The weights only shape and rank candidates; the screen and the certificate do not use them. The solver never builds (2) explicitly: OR-Tools (Perron and Furnon, 2026) enforces the timing through its routing dimensions, and the hybrid genetic search (HGS) of PyVRP (Vidal, 2022; Wouda et al., 2024) is used as a second, stronger solver. PyVRP cannot express the slack deficit F_2, so HGS generates its candidates with the other three terms and their weights; F_2 still enters the selection of candidates through the score (4). The weights come from the comparison matrix in Appendix A, where the sensitivity of the results to them is reported. Travel times are rounded up to whole minutes.

3.2 Travel times and delays

Each simulated day starts at 06:00 with a free-flow speed of 40 km/h, which is divided by 0.9 before 07:00, 1.2 from 07:00 to 09:00, 1.0 from 09:00 to 17:00, 1.3 from 17:00 to 19:00 and 0.9 afterwards. Travel times integrate the speed over the trip, so a later departure never arrives earlier (Ichoua et al., 2003; Ghiani and Guerriero, 2014). On each day, the time of arc (i, j) is multiplied by $\exp(\varepsilon_{ij})$ with

$$\varepsilon_{ij} = \sigma\left(\sqrt{\rho}\,\xi_0 + \sqrt{1 - \rho}\,\xi_{ij}\right), \tag{5}$$

where ξ_0 is a standard normal variable common to all trips of the day and the ξ_{ij} are independent standard normal variables. The assumed setting is $\sigma = 0.2$ and $\rho = 0.5$; Section 5.4 fits these quantities and the time-of-day profile to real traffic. Days are independent and identically distributed. A fixed set of simulated days is a *bank*; on each instance all plans are judged on the same banks, so comparisons are paired.

3.3 Reliability

A day is a *success* for a plan if at least $\kappa = 95\%$ of its customers start service by the end of their promised windows. Requiring every customer to be on time would be unrealistic on large instances: with 200 customers each on time with probability 0.99 independently, all would be on time on only 13% of days.

The *reliability* of plan x is the probability $p(x)$ of a successful day, and the target is $p(x) \geq \tau = 0.95$. A plan's reliability is a property of the plan and the delay model, not of any particular bank. We use this day-level criterion, rather than a chance constraint for each customer, because a dispatcher judges a day's plan as a whole and because many per-customer constraints say little about the day jointly; the share κ and the target τ are choices a firm can change.

4 Screen and certify

4.1 Buffered candidates and the reachability cap

For each buffer $\beta \in \{0, 5, \ldots, 60\}$ minutes the solver plans against internal deadlines $u_i - \beta$, never earlier than l_i, which gives up to 13 candidate plans. Simulated arrivals are always judged against the promised u_i. A large buffer can, however, put a distant customer's internal deadline before the earliest time it can be reached, and then no plan exists. Let $e_i = \max\{l_i, \bar{t}_{0i}\}$ be the earliest possible start of service at i after a direct trip from the depot. The capped deadline is

$$u_i^{\mathrm{cap}}(\beta) = \min\bigl\{u_i,\ \max\{l_i,\ u_i - \beta,\ e_i\}\bigr\}. \tag{6}$$

Lemma 1. *For every customer i and buffer $\beta \geq 0$: (a) $u_i^{\mathrm{cap}}(\beta) \leq u_i$, so a plan that meets the capped deadlines meets the promised windows; (b) if $e_i \leq u_i$, then $e_i \leq u_i^{\mathrm{cap}}(\beta)$, so the cap never makes a reachable customer unreachable; (c) if $\beta \leq u_i - e_i$, then $u_i^{\mathrm{cap}}(\beta) = \max\{l_i, u_i - \beta\}$, so the cap changes nothing where it is not needed.*

Proof. (a) The outer minimum includes u_i. (b) The inner maximum is at least e_i and $u_i \geq e_i$, so their minimum is at least e_i. (c) $\beta \leq u_i - e_i$ gives $u_i - \beta \geq e_i$, so the inner maximum is $\max\{l_i, u_i - \beta\} \leq u_i$, and the outer minimum leaves it unchanged. □

The lemma protects each customer separately. It does not guarantee that one plan can serve all customers in time, since capacity, shift length and visit order still matter. A shortest-path bound, with service times included, was used to prove where possible that a contracted model had no feasible plan, so that solver failures could be told apart from true infeasibility.

4.2 Screening

Every candidate is simulated on a screening bank of 1000 days. If it succeeds on a share $\hat{p}$ of them, its one-sided 95% Wilson lower bound is

$$L_W(\hat{p}) = \frac{\hat{p} + \frac{z^2}{2N} - z\sqrt{\frac{\hat{p}(1-\hat{p})}{N} + \frac{z^2}{4N^2}}}{1 + \frac{z^2}{N}}, \qquad z = 1.645,\ N = 1000. \tag{7}$$

A candidate passes if $L_W \geq \tau$. With $\hat{p} = 0.966$, for example, $L_W \approx 0.955$ and the candidate passes; with $\hat{p} = 0.955$, $L_W \approx 0.943$ and it fails. Among passing candidates the one with the smallest score (4) is selected. If none passes, a fallback fixed in advance is returned. The screen is a filter, not a guarantee: with 13 candidates tested on the same days, the chance that some weak candidate passes is larger than 5%.

4.3 The certificate

The selected plan is simulated once on a validation bank of $N_c = 5000$ days drawn independently of everything used to produce and select it. Let K be its number of successful days and $L_{CP}(K)$ the exact one-sided $(1-\alpha)$ Clopper–Pearson lower bound, the α-quantile of the $\mathrm{Beta}(K, N_c - K + 1)$ distribution (Clopper and Pearson, 1934). The plan is *certified* if $L_{CP}(K) \geq \tau$; with $\alpha = 0.05$ this requires at least 4776 successful days out of 5000.

Theorem 1. *Let a plan X be produced by any procedure, deterministic or random, that may use the instance, any solver and any simulated days other than the validation bank. Let the validation days be independent of that procedure and identically distributed under the delay model. Then*

$$\Pr\big(X \text{ is certified and } p(X) < \tau\big) \leq \alpha.$$

Proof. Condition on the information $\mathscr{F}$ used by the procedure, which fixes X. Because the validation days are independent of $\mathscr{F}$ and identically distributed, the successes on them are independent Bernoulli trials with probability $p(X)$, so $K \sim \mathrm{Binomial}(N_c, p(X))$ given $\mathscr{F}$. If $p(X) \geq \tau$, the event in question is empty. If $p(X) < \tau$, certification requires $L_{CP}(K) \geq \tau > p(X)$, and the Clopper–Pearson bound satisfies $\Pr\{L_{CP}(K) > p\} \leq \alpha$ for every true probability p. Hence the conditional probability of the event is at most α, and taking the expectation over $\mathscr{F}$ gives the claim. □

Remark 1. The argument is elementary: it is the a posteriori feasibility check used for sampled chance-constrained programs (Luedtke and Ahmed, 2008), applied to a routing plan. Its value here is practical. It places no condition on the solver, the buffer family, the selection rule or the fallback; the candidates may even be chosen by a simheuristic that has simulated thousands of scenarios of its own. It does not say that a plan is reliable on real roads: $p(X)$ is defined by the delay model. Section 6.7 tests that gap.

Corollary 1. *If the K_c candidates are produced without using the screening bank, admitting a candidate only when its Clopper–Pearson bound at level α/K_c on the screening bank reaches τ gives the same guarantee for the admitted plan without a separate validation bank, by the union bound over candidates.*

4.4 Transfer to other delay models

The certificate concerns the simulated model, so the question for practice is when it carries over to the real delays. Two results answer it. For an arc (i, j) leaving at clock time t with realized delay factor f, write $A_{ij}(t) = t + f\,\tau_{ij}(t)$ for the arrival time, where τ_{ij} is the time-dependent travel time. With fixed departures, the start of service at the k-th customer of a route is obtained from the departure time by alternately applying arrival maps and $a \mapsto \max\{l_j, a\} + s_j$.

Proposition 1. *Suppose every arrival map is non-decreasing in t, and that on a common probability space each day's arrival maps under the real delays are pointwise no later than under the model, $A_{ij}^{\mathrm{real}}(t) \leq A_{ij}^{\mathrm{model}}(t)$ for all arcs and times. Then $p_{\mathrm{real}}(x) \geq p_{\mathrm{model}}(x)$ for every plan x, and a plan certified under the model satisfies* $\Pr(\text{certified and } p_{\mathrm{real}}(X) < \tau) \leq \alpha$.

Proof. Along each route the service start times are compositions of non-decreasing maps, so by induction every start time under the real delays is no later than under the model on every day. A customer on time under the model is therefore on time in reality, a successful model day is a successful real day,

and $p_{\text{real}}(x) \geq p_{\text{model}}(x)$. The event $\{p_{\text{real}}(X) < \tau\}$ is then contained in $\{p_{\text{model}}(X) < \tau\}$, and Theorem 1 applies. □

The monotonicity condition holds whenever $1 + f\tau'_{ij}(t) \geq 0$; with the piecewise-constant speed profile used here $\tau'_{ij} \geq -(1 - 0.9/1.3)$, so it holds for every delay factor $f \leq 3.2$, and it can fail only in the rare case of a very large delay at the end of the evening peak. Certificates should therefore survive when the model is pessimistic relative to reality, which suggests certifying against several models at once.

Proposition 2. *Let $\mathscr{M} = \{m_1, \ldots, m_M\}$ be delay models, and certify a plan under $\mathscr{M}$ if its Clopper–Pearson bound reaches τ on an independent validation bank under each model. Then for every $m \in \mathscr{M}$,* $\Pr(\textit{certified under } \mathscr{M} \textit{ and } p_m(X) < \tau) \leq \alpha$. *If the real days are drawn from a mixture of the models in $\mathscr{M}$, then* $\Pr(\textit{certified under } \mathscr{M} \textit{ and } p_{\text{mix}}(X) < \tau) \leq M\alpha$.

Proof. Certification under $\mathscr{M}$ implies certification under each m, so the first claim is Theorem 1 for model m; no correction for multiplicity is needed because the claim is made for one true model at a time. Under a mixture, $p_{\text{mix}}(X) = \sum_m \pi_m p_m(X) \geq \min_m p_m(X)$, so $p_{\text{mix}}(X) < \tau$ implies $p_m(X) < \tau$ for some m, and the union bound over the M models gives the second claim. □

A firm unsure of its model can screen and certify against a small set, for example its fitted model with incidents and a stronger peak; Section 6.7 measures the price.

The certificate can also do without a delay model, if a firm validates on its own past days instead of simulated ones. This removes the model, but it changes what must be counted.

Proposition 3. *Let the validation bank consist of N real past days, independent and distributed as the days the plan will face, with the plan's outcome on each day judged once under that day's conditions. Then Theorem 1 holds for the real reliability, with no delay model. Certification with K successful days requires $L_{CP}(K) \geq \tau$; with no failure this holds if and only if $N \geq \ln\alpha / \ln\tau$, which is 59 days at $\tau = 0.95$ and $\alpha = 0.05$; with one failure 93 days are needed and with two 124.*

Proof. Given the information used to produce the plan, the N outcomes are independent Bernoulli trials with the plan's real success probability, so the proof of Theorem 1 applies unchanged. With $K = N$, $L_{CP}(N) = \alpha^{1/N}$, which is at least τ exactly when $N \geq \ln\alpha / \ln\tau$. □

The count is of days, not of simulations: resampling the same N days 5000 times gives a bank drawn from those days, whose bound does not cover a new day, while 21 real days with no failure prove only 0.867.

A firm would often rather certify the cheapest good plan than the one the screen chose. Picking it with the validation days themselves would test many plans on the same days, but a fixed testing order makes this safe without any correction.

Proposition 4. *Order the candidates $x_1, \ldots, x_K$ by a rule that does not use the validation bank, for example from the largest buffer to the smallest. Test them in that order on the validation bank, certifying x_k when $L_{CP}(K_k) \geq \tau$, and stop at the first candidate that is not certified. Then* $\Pr(\textit{some } x_k \textit{ is certified and } p(x_k) < \tau) \leq \alpha$, *and the same holds for a plan chosen from the certified candidates by any rule, such as the lowest score* (4).

Proof. Condition on the candidates and the order. Let k^* be the first index with $p(x_{k^*}) < \tau$; if there is none, the event is empty. Candidates before k^* satisfy $p \geq \tau$, and a candidate after k^* is reached only if x_{k^*} was certified. The event therefore implies that x_{k^*} was certified, which has probability at most α by Theorem 1. A plan chosen from the certified candidates is one of them. □

This is the fixed-sequence principle of multiple testing (Maurer et al., 1995) applied to a buffer family; Section 6.3 reports how it compares with certifying the screened plan.

The same principle gives a certificate an interpretable margin. For $\lambda \geq 0$ let $p_\lambda(x)$ be the reliability of x when every travel time is multiplied by $1+\lambda$, with the random delay factors unchanged.

Proposition 5. *For a plan x, test $0 = \lambda_0 < \lambda_1 < \cdots$ in this order on its validation bank, certifying λ_j when $L_{CP} \geq \tau$, and stop at the first value not certified; let λ^*, the* certified slowdown margin*, be the last certified value. Then* $\Pr(x \text{ is certified and } p_\lambda(x) < \tau \text{ for some } \lambda \leq \lambda^*) \leq \alpha$*, and under the conditions of Proposition 1 the plan is then at least τ-reliable under any real delays pointwise no worse than the model slowed by λ^*.*

Proof. The slowed models form a fixed order, so Proposition 4 covers the tested values. Slowing every trip makes each arrival map pointwise later, so $p_\lambda(x)$ does not increase with λ (the argument of Proposition 1), which covers the values in between; the last claim is Proposition 1 applied to the slowed model. □

Errors bounded in minutes are handled the same way, and the effect of the bound can be measured exactly rather than estimated.

Proposition 6. *Suppose that, under a coupling of real and modelled days, every real trip takes at most Δ minutes longer than in the model. Then $p_{\text{real}}(x) \geq p_\Delta(x)$, the reliability under the model with Δ added to every trip, and on common days $p_\Delta(x) = p(x) - \rho_\Delta(x)$, where $\rho_\Delta(x)$ is the probability of a day that succeeds under the model but fails with Δ added. Testing increasing values of Δ in a fixed order, as in Proposition 5, gives a certified shift margin $\Delta^*(x)$ with the same guarantee.*

Proof. Adding Δ keeps every arrival map non-decreasing and makes it pointwise later, and the real maps are pointwise no later than the shifted ones, so Proposition 1 gives the first claim. On common days the shifted model's start times are no earlier, so its successful days are a subset of the model's, which gives the identity; the margin is Proposition 4. □

Finally, the validation days need not all be simulated in advance.

Proposition 7. *Inspect the validation days after $n_1 < \cdots < n_J$ days and certify at the first inspection j at which the Clopper–Pearson bound at level α/J reaches τ. Then* $\Pr(X \text{ is certified and } p(X) < \tau) \leq \alpha$*.*

Proof. Given the plan, each inspection is a test at level α/J on independent, identically distributed days, as in Theorem 1; the union bound over the J inspections gives the claim. □

This is the simplest group-sequential design (Pocock, 1977; Jennison and Turnbull, 2000); sharper spending rules exist, but simulation is cheap enough here that the simple one suffices.

Here the screen uses the Wilson bound and the guarantee comes from the separate certificate; an exploratory check of the Bonferroni screen (Corollary 1) removed all 11 admitted plans that later fell short, at a cost of at most 2 admissions per study.

Table 1. Configurations. Every plan is judged against the promised windows on the same simulated days.

Name	Definition
Nominal plan	Shortest distance at 40 km/h, no buffer, no screening.
Padding $p\%$	Shortest distance at $40/(1+p/100)$ km/h, no screening; *20% padding*, also called conservative speed, is $p = 20$.
Slack-aware plan	Weighted objective (4), which includes the slack deficit, with no buffer and no screening.
Original procedure	Buffered candidates without the cap, weighted objective, screened; fallback: the slack-aware plan.
Capped procedure	As the original procedure with the capped deadlines (6); the HGS version falls back to 20% padding.
Screened conservative	Buffered candidates planned at the 20% padded speed for distance, screened, shortest passing candidate selected; fallback: 20% padding.
Best-screened fallback	When no candidate passes, return the candidate with the highest Wilson bound (tested in study 3B).
Distance, capped buffers	Ablation of the HGS capped procedure: the same capped candidates and screen, planned at 40 km/h for distance alone, shortest passing candidate selected; fallback: 20% padding.
Robust model	Budgeted robust VRPTW (Agra et al., 2013; Bertsimas and Sim, 2004), with an analogous reachability correction, screened in the same way.

4.5 Configurations compared

Table 1 defines every configuration. The *capped procedure* is the main version of the layer. *Screened conservative* combines the screen with padding. The padded plans are used as an operator would use them, without screening.

5 Experimental design

5.1 Synthetic instances and confirmatory studies

Synthetic instances place a depot at the centre of a 100 km square and customers uniformly at random, with demands from 10 to 49 units, windows 90 to 149 minutes wide, capacity $Q = 1000$, service time 10 minutes and a 600-minute shift. The development study used 53 instances: 20 with 20 customers, 15 with 50, 10 with 100 and 8 with 200. Each OR-Tools call had 5 seconds and up to three attempts; each HGS call had 10,000 iterations. The development study was exploratory and shaped the method. Three confirmatory studies then ran on new instances, each with its hypotheses, tests, decision rules and seeds written down and publicly timestamped with a fingerprint of the code before any instance was solved (Ali, 2026b,c,d). Study 1 tested the OR-Tools procedures on 53 new instances, study 2 the HGS procedure on 53 more, and study 3 compared the procedures with the robust model on the 90 earlier confirmatory instances with at most 100 customers (part A) and tested the best-screened fallback on 53 further instances (part B). Each study or part had two primary hypotheses, judged with 97.5% paired bootstrap intervals so that the chance of a false confirmation stays below 5% per pair. All other analyses are exploratory.

5.2 Benchmark instances

The HGS procedure was also run on the 20 Gehring–Homberger instances of classes R1 and RC1 with 200 customers (Gehring and Homberger, 1999), which extend Solomon's test set (Solomon, 1987).

Coordinates and times were rescaled so that the benchmark's unit-speed travel matches 40 km/h and its horizon fits a 600-minute shift from 06:00, and the same delay model was added.

5.3 Real delivery routes

The third set comes from the public data of the 2021 Amazon Last Mile Routing Research Challenge (Merchán et al., 2022): 40 routes rated high quality, drawn with a fixed seed from 17 depots in five US cities, each one van's day with 80 to 194 stops. The data give the travel time between every pair of stops, service times, package volumes, the van's capacity and departure time, and the order the driver drove. Consecutive stops in one delivery zone were joined into one customer (10 to 36 per route), whose service time was added to the trips leaving it. Only 7% of stops have a window in the data, and most of those are 7 to 8 hours wide, so each customer was offered a two-hour window placed at random around the driver's actual arrival. The shift starts at the real departure time and lasts 1.3 times the actual route, with up to three vans.

5.4 Delays fitted to real traffic

To estimate a delay model from data we used New York's yellow taxi records (New York City Taxi and Limousine Commission, 2024): 6.2 million weekday trips between different zones from January to March 2024 that passed basic checks. Time-of-day multipliers compare the same zone pairs in each period with 09:00–17:00, using time per mile. The spread σ was estimated from all variation between trips on a zone pair and period, which overstates the variation of one fixed trip, and from variation between days only, which understates it; ρ is the share of the daily mean in each. The Amazon experiments were repeated under both fitted models.

5.5 Ethics and data use

The study involves no human participants and no experiments on people or animals. Both real data sets are public: the Amazon routes are released under a CC BY-NC 4.0 licence, which permits this non-commercial research use with attribution, and the New York taxi records are published by the city. Neither contains personal data, so no ethics approval was required.

5.6 Analyses

Pooled service is the mean validated reliability over all instances, an instance without a plan scoring zero, so planning failures count against a configuration. Differences are paired by instance, with bootstrap intervals from 20,000 resamples. Further analyses use only stored plans. To test the certificate, every certified plan was simulated on a third bank of 5000 fresh days; a plan *fails its certificate* if the exact one-sided 95% upper bound on its fresh reliability is below τ, which the theorem allows for at most about 5% of certified plans.

Table 2. Paired differences in service probability (percentage points) on the 46 development instances where 20% padding found a plan. C: 20% padding; S: the slack-aware plan (weighted objective, no buffer, no screening); P: the original procedure; SC: screened conservative (Table 1).

n	S minus C	P minus C	SC minus C
20	−11.0 [−16.1, −6.0]	21.4 [9.6, 31.3]	28.2 [21.4, 34.3]
50	−13.1 [−17.4, −8.9]	17.9 [2.8, 32.0]	11.8 [2.7, 22.2]
100	−16.2 [−20.6, −11.7]	16.0 [4.8, 24.8]	11.2 [2.8, 19.4]
200	−12.9 [−18.5, −5.7]	8.3 [−5.1, 20.0]	5.7 [0.0, 12.9]




Figure 1. Difference in validated reliability between the original procedure and 20% padding on the 46 development instances, as the delay spread σ and the day-common share ρ vary. Plans are fixed; error bars are 95% bootstrap intervals over instances.

6 Results

6.1 Screening against 20% padding

Table 2 compares the procedures with 20% padding on the 46 development instances where padding found a plan. The original procedure was 8.3–21.4 percentage points more reliable, depending on size; at 200 customers the interval includes zero. The slack-aware plan without screening was worse than padding at every size. The advantage grew with the amount of random delay (Figure 1): with independent delays it rose from -3.1 points at $\sigma = 0.1$, where padding was slightly ahead, to 30.5 points at $\sigma = 0.3$.

The cap matters (Table 3). On 21 development instances the original procedure admitted no plan, and on 17 of them the shortest-path bound proved that a customer had become unreachable at a large buffer. Capping raised the instances with a passing plan from 32 to 42 and pooled service by 7.7 [3.5, 12.5] points, and at 100 and 200 customers the capped procedure found a passing plan on every instance. The confirmatory studies repeated these findings (Table 4). Seven of eight primary hypotheses were confirmed: screening beat 20% padding by 15.7 points on new instances, capping added 11.7 points, and with HGS the capped procedure beat padding by 28.0 points. The one not confirmed (G2), that a padded fallback would help the capped OR-Tools procedure, failed because it rarely needed one. The best-screened fallback, tested in study 3B, raised pooled service by 7.3 and 4.2 points for the two solvers.

The HGS comparison in study 2 changes several things at once: the capped procedure uses the

Table 3. Development study, all 53 instances. For each procedure: instances admitted by screening out of all instances of that size, with the number whose lower bound also reached 0.95 on the validation bank in parentheses, and pooled validated service probability (%) with a 95% bootstrap interval, fallback plans included.

	Original procedure		Screened conservative		Capped procedure	
n	Admitted	Pooled	Admitted	Pooled	Admitted	Pooled
20	14/20 (14)	81.6 [70.2, 91.9]	15/20 (15)	87.7 [79.0, 94.7]	14/20 (14)	81.6 [70.3, 92.0]
50	8/15 (8)	72.7 [59.2, 86.4]	4/15 (4)	67.5 [58.2, 77.3]	10/15 (10)	80.1 [66.9, 90.8]
100	6/10 (5)	81.3 [68.8, 93.3]	4/10 (4)	77.5 [67.2, 88.2]	10/10 (9)	97.5 [96.7, 98.2]
200	4/8 (3)	80.6 [68.7, 92.3]	2/8 (2)	78.3 [71.0, 86.5]	8/8 (7)	97.6 [96.9, 98.2]

Table 4. The eight primary hypotheses of the three confirmatory studies. Each was fixed and publicly timestamped before its instances were solved. Estimates are differences in validated service probability (percentage points) with 97.5% paired bootstrap intervals over instances; a hypothesis is confirmed when its interval lies above zero.

Study		Contrast	Estimate [interval]	Decision
1	H1	Original procedure minus 20% padding (50 instances)	15.7 [7.5, 23.6]	confirmed
1	H2	Capped minus original procedure (53 instances)	11.7 [5.9, 17.9]	confirmed
2	G1	Capped procedure with HGS minus 20% padding with HGS (49 instances)	28.0 [23.0, 32.8]	confirmed
2	G2	Conservative minus slack-aware fallback, capped OR-Tools procedure	0.4 [−0.7, 2.1]	not confirmed
3A	R1	Screened robust model minus capped OR-Tools procedure (90 instances)	6.7 [3.0, 11.1]	confirmed
3A	R2	Screened robust model minus capped HGS procedure (45 instances)	6.7 [2.2, 12.2]	confirmed
3B	F1	Best-screened minus default fallback, capped OR-Tools procedure	7.3 [2.3, 13.2]	confirmed
3B	F2	Best-screened minus default fallback, capped HGS procedure	4.2 [1.2, 8.0]	confirmed

weighted objective, the buffer family, the cap and the screen, while 20% padding plans for distance alone at a slower speed. Table 5 separates them on the 96 of 106 synthetic HGS instances of the development and second confirmatory studies where every configuration has a plan. The weighted plan without buffers or screening was −42.5 [−43.8, −41.1] points *less* reliable than padding: an unbuffered plan has no time to spare. Planning for distance alone, with the same capped buffers and the same screen, gave 28.3 [25.5, 31.0] points over padding, against 27.8 [25.0, 30.5] for the full procedure; the two screened versions were level (weighted minus distance −0.6 [−2.3, 1.1] points). The gain therefore comes from the buffers and the screen, not from the objective, which mainly changed the plan's cost: the weighted version used 0.29 fewer vehicles per instance than the distance version. This also limits how much the results depend on the weights (Appendix A).

6.2 Fixed padding at other levels

A 20% pad may simply be the wrong amount, so Table 6 and Figure 2 repeat the comparison with padding from 0 to 50%. Over all instances no level came close to the capped procedure: the best, 30%, pooled 66.7% against 86.6%. More padding did not keep helping, because heavy padding makes many instances impossible to plan: at 50% the padded planner found a plan on only 26 of 53 instances, and of the 65 missing padded plans across all levels 43 are provably infeasible (the other 22 are unresolved). Where

Table 5. HGS ablation on the 96 synthetic instances of the development study and the second confirmatory study where every configuration has a plan (exploratory). *Pooled*: pooled validated reliability (%); *Minus padding*: paired difference from 20% padding in percentage points, with 95% bootstrap intervals; *Veh.* and *Dist.*: mean difference from padding in vehicles and in distance (%); *Cert.*: plans certified. The screened configurations share the buffer grid, the screening days, the admission rule and the fallback to 20% padding.

Configuration	Pooled	Minus padding	Veh.	Dist.	Cert.
20% padding (distance objective, padded speed)	65.0	–	–	–	0
Weighted objective, no buffer, no screen	22.5	−42.5 [−43.8, −41.1]	−0.96	−2.8	0
Distance objective, capped buffers, screened	93.4	28.3 [25.5, 31.0]	0.89	8.5	84
Capped procedure (weighted, capped buffers, screened)	92.8	27.8 [25.0, 30.5]	0.59	9.2	80

Table 6. Padding every trip by a fixed percentage on the 53 development instances (exploratory). *Plans*: instances on which the padded planner found a plan. *All*: pooled service over all instances, an instance without a plan scoring zero. The next three columns use only the instances with a padded plan: the padded plans' service, the capped screening procedure's service on the same instances, and the difference (padding minus screening, percentage points, 95% paired bootstrap interval). Distance (%) and vehicles are also padding minus screening on those instances. Over all instances the capped procedure pooled 86.6%.

		All	Instances with a padded plan				
Padding	Plans	Pooled	Padded	Screened	Difference	Distance	Vehicles
0%	53/53	21.9	21.9	86.6	−64.7 [−70.2, −58.8]	−7.1	−0.89
10%	51/53	43.7	45.4	88.4	−42.9 [−48.0, −37.4]	−6.2	−0.59
20%	46/53	56.8	65.4	89.4	−23.9 [−29.2, −18.2]	−4.8	−0.22
30%	43/53	66.7	82.2	90.3	−8.1 [−13.1, −2.4]	−3.1	0.21
40%	34/53	58.8	91.6	88.5	3.1 [−2.8, 10.0]	−1.0	0.47
50%	26/53	47.1	96.1	87.9	8.2 [1.2, 16.1]	0.9	0.77

it did find one, the plan was reliable: on those instances 50% padding served 96.1% against 87.9% for screening, and used 0.77 more vehicles. A planner who fixes one padding level must choose between unreliable plans at low levels and missing plans at high ones.

6.3 Certification

Table 7 applies the certificate to every configuration in every study. The capped procedure was certified on 40 of 53 development instances and on 45 and 45 of 53 in the two confirmatory studies; its HGS version on 46 and 42. Twenty percent padding was never certified on a synthetic instance (0 of 238 plans): its plans are often good, but rarely good enough to show 95% with confidence. Across Table 7, 666 plans were certified; the fixed-order, stress and ablation analyses below certify further plans, which are counted separately. On 5000 fresh days, none of the 666 failed its certificate, and only 5 had a fresh success rate below 0.95, all within sampling error of it; most certified plans are well above the target. Because the fresh days come from the same model, this checks the implementation and the statistics, not the model, which Section 6.7 tests.

Fixed-order certification (Proposition 4) was applied to the capped families of both solvers in every study where they ran, testing candidates from the largest buffer down and returning the certified candidate with the lowest score. It certified a plan on 228 of 265 instances against 218 for the screened plan: 16




Figure 2. Validated reliability against fixed padding on the 53 development instances. Solid line: all instances, a missing plan scoring zero; dashed line: only instances where a padded plan exists (counts under the axis). Orange line and band: the capped procedure over all instances, with its 95% bootstrap interval.

Table 7. Certified plans: plans whose exact one-sided 95% lower bound on the success probability, from the 5000 validation days, is at least 0.95, out of the plans the configuration produced. Dev., Conf. 1 and Conf. 2: development and first two confirmatory studies (53 instances each); Amazon: 40 routes under the assumed delay model and under the two models fitted to New York traffic. On a further 5000 fresh days, none of the 666 certified plans in the table failed its certificate (exact one-sided 95% upper bound below 0.95).

Configuration	Dev.	Conf. 1	Conf. 2	Amazon	NYC d.	NYC all
Nominal plan (OR-Tools)	0/53	0/53	0/53	0/34	3/34	0/34
20% padding (OR-Tools)	0/46	0/50	0/45	0/28	28/28	4/28
Original procedure	30/53	31/53	28/53	22/34	33/34	29/34
Capped procedure	40/53	45/53	45/53	22/34	33/34	29/34
Screened conservative	25/53	28/53	26/53	24/34	30/34	23/34
Nominal plan (HGS)	0/53	–	0/53	–	–	–
20% padding (HGS)	0/48	–	0/49	–	–	–
Capped procedure (HGS)	46/53	–	42/53	–	–	–

instances gained a certificate and 6 lost one. Where both certified a plan, the fixed-order plan used 0.05 fewer vehicles $[-0.01, 0.11]$ and 0.04% less distance $[-0.19, 0.27]$ than the screened plan, both intervals including zero, so the screen had already found nearly the cheapest certifiable plan. None of the fixed-order certificates failed on fresh days: a modest but free improvement. Inspected sequentially (Proposition 7) after 1000, 2000, …, 5000 days at level $\alpha/5$, 657 of the 666 certified plans were certified again and none was added; 550 stopped at the first inspection, the mean number of days used fell from 5000 to 1,353 (73% fewer), and none of the sequentially certified plans failed on fresh days (`code/shift_sequential.py`).

6.4 The cost of reliability

Table 8 and Figure 3 ask which reliability each family can reach, and at what cost. This is an existence comparison, with the qualifying plan picked on the days that judge it, as an oracle would; the capped procedure itself certified a plan on 40 of the 53 instances (Table 7). At 95% the buffer family contains a qualifying plan on 46 of 53 instances and the padding family on 23, at 99% on 29 and 0. Where both

Table 8. The cost of reliability on the 53 development instances. For each level, the number of instances on which the buffer family (13 capped candidates) and the padding family (0 to 50%) contain a plan whose validated success probability reaches it, and, where both do, the paired difference in cost between the cheapest such plans (buffers minus padding): distance in percent of the plain distance plan, and vehicles. 95% bootstrap intervals over instances. *Exact bound*: the Clopper–Pearson lower bound, rather than the estimate, must reach 95%. Every row is descriptive: the qualifying plan is found with the same validation days that judge it, so the counts show what each family can reach, not what a procedure would select and certify (the capped procedure certified 40 of the 53 instances; Table 7), and no row is a certificate in the sense of Theorem 1.

	Instances reached			Buffers minus padding	
Reliability	Buffers	Padding	Both	Distance (%)	Vehicles
50%	52	47	47	−1.0 [−1.7, −0.3]	−0.45 [−0.72, −0.19]
70%	51	43	43	−1.4 [−2.3, −0.5]	−0.65 [−1.05, −0.30]
80%	51	42	42	−1.2 [−2.1, −0.4]	−0.79 [−1.10, −0.50]
90%	50	33	32	0.1 [−1.2, 1.5]	−0.75 [−1.22, −0.34]
95%	46	23	22	1.5 [0.2, 2.9]	−0.64 [−1.09, −0.23]
95%, exact bound	45	20	19	1.8 [0.3, 3.4]	−0.58 [−1.00, −0.21]
99%	29	0	0	–	–




Figure 3. Share of the 53 development instances on which some plan of each family reaches a required validated reliability. Descriptive: the plan is found with the days that judge it.

reach 95%, the cheapest buffered plan used 0.64 fewer vehicles [0.23, 1.09] but 1.5% more distance [0.2, 2.9]; at 80% or less, buffers were cheaper in both. Padding buys reliability by slowing every trip, which eventually costs vehicles; a buffer spends time only where the deadline binds.

6.5 Benchmark instances

On R1_2_1 and R1_2_2, where all or most windows are only 10 time units wide, neither the anchor solves nor HGS at padded speed found a plan. Screening admitted a plan on 17 of the other 18 instances (Table 9), and on those instances the capped HGS procedure exceeded 20% padding by 15.1 [11.0, 19.1] points; over all 20 it pooled 87.2% against 73.6%.

Table 9. Gehring–Homberger instances with 200 customers (exploratory, HGS pipeline): instances, instances where the four single-criterion solves that set the objective's scaling ranges (the anchors) all found a plan, instances admitted by screening, and pooled validated service-event probability (%) of the HGS nominal plan, HGS conservative speed and the HGS capped procedure with conservative fallback. A missing plan scores zero.

Class	Inst.	Anchors	Admitted	Nominal	Conservative	Capped
R1	10	8	7	42.1	68.0	77.0
RC1	10	10	10	27.6	79.3	97.4

Table 10. The delay model fitted to 6.2 million weekday New York yellow-taxi trips (January–March 2024). Time-of-day multipliers of travel time relative to 09:00–17:00, from zone pairs with at least 20 trips in both periods; the spread σ and the day-common share ρ of the random factor are estimated in two ways (see text).

Period	Assumed	Fitted	Zone pairs
00:00–07:00	0.9	0.62	2,669
07:00–09:00	1.2	0.84	2,424
09:00–17:00	1.0	1.00	4,603
17:00–19:00	1.3	0.94	3,237
19:00–24:00	0.9	0.76	3,865
σ	0.20	0.11 (day to day), 0.27 (all)	
ρ	0.50	0.40 (day to day), 0.06 (all)	

6.6 Real delivery routes

Table 10 gives the delay model fitted to New York traffic. It differs from the assumed one in one important way: the rush hours were not slower than the middle of the day. Trips between 07:00 and 09:00 were 16% faster and trips between 17:00 and 19:00 6% faster than between 09:00 and 17:00. The assumed spread of 0.20 lies between the two fitted values.

We compare the procedures on these routes with the HGS solver (Table 11); the OR-Tools comparison on the first 40 routes is in Appendix B, because its 5-second search missed feasible plans. HGS found a 20% padded plan on all 60 sampled routes. On 12 of them the short solves that set the objective's scaling ranges failed, so the procedure returned its fallback, the padded plan. On the 48 routes where the screen ran, the capped HGS procedure was 8.0 [5.6, 10.5] points more reliable than padding under the assumed model and 10.1 [7.1, 13.4] with all fitted variation, with practically the same number of vehicles. With the milder day-to-day variation padding was slightly ahead (-1.2 [-1.7, -0.8] points): 60 of 60 padded plans were certified, which leaves little for screening to add. Over all routes, counting the fallback, the differences were 6.4, -1.0 and 8.1 points, and no certified plan failed on fresh days. Screening helps when delays are large enough to matter; when they are not, padding is already reliable and the certificate says so.

6.7 When the delay model is wrong

A firm screens with the delay model it has, and real delays differ. Judged under the models fitted to New York traffic, the Amazon plans chosen under the assumed model stayed ahead of padding at the same budget (top of Table 12), screening with the right model added only 1.6 [-0.6, 4.4] and 3.7 [0.3, 7.5] points, and every certificate still held. This is the favourable direction: the assumed model is harsher than New York traffic in the morning.

The bottom of the table shows the other direction, on the synthetic instances, with delay models

Table 11. The 60 Amazon routes with the HGS solver (exploratory). *Padding* and *Capped*: pooled validated reliability (%) of 20% padding and of the capped HGS procedure, which falls back to padding on the 12 routes where its scaling solves failed and the screen could not run. *All*: capped minus padding over all routes; *Both*: the same on the routes where the screen ran, with the difference in vehicles. *Certified*: plans certified, padding and capped. 95% bootstrap intervals.

			Capped minus padding			Certified	
Delay model	Padding	Capped	All	Both	Vehicles	Pad.	Cap.
Assumed	85.0	91.4	6.4 [4.3, 8.6]	8.0 [5.6, 10.5]	0.04	0	26
NYC, day to day	99.4	98.4	−1.0 [−1.4, −0.6]	−1.2 [−1.7, −0.8]	−0.21	60	45
NYC, all variation	86.8	94.9	8.1 [5.5, 10.9]	10.1 [7.1, 13.4]	0.02	14	42

Table 12. When the delay model is wrong. Top: the 40 Amazon routes, judged on 5000 fresh days under each delay model fitted to New York traffic. *Wrong*: plans chosen when the screen used the assumed model; *Right*: plans chosen when it used the fitted model. Pooled service (%), and certificates (granted under the model used for screening) that still hold. Bottom: plans certified under the assumed model on the synthetic instances of the development and confirmatory studies, judged under delay models that differ from it; certificates that still hold and the mean service (%) of the certified plans.

	NYC, day-to-day variation			NYC, all variation		
	Wrong	Kept	Right	Wrong	Kept	Right
20% padding	69.5	–	69.5	59.5	–	59.5
Capped procedure	81.8	22/22	83.4	76.4	22/22	80.1
Screened conservative	83.4	24/24	83.1	77.3	24/24	77.4

	Capped (OR-Tools)		Capped (HGS)	
True delay model	Kept	Service	Kept	Service
Assumed model (new days)	130/130	97.6	88/88	97.5
Heavy-tailed delays	130/130	97.5	88/88	97.3
More noise in the peaks	102/130	95.9	66/88	95.7
Random incidents	44/130	93.3	17/88	92.6
Stronger morning peak	52/130	93.7	22/88	93.2

chosen before the analysis. Certificates survived heavy-tailed delays (130 of 130) and mostly survived more noise in the peaks (102 of 130). They often failed when 3% of trips suffered an incident that doubled their time (86 of 130 failed) and when the morning peak was stronger than planned (78 of 130), although the certified plans still averaged 93.3% and 93.7% reliability, against 49.6% and 36.8% for 20% padding. The certificate is exactly as good as the delay model's pessimism, as Proposition 1 leads one to expect.

Proposition 2 offers a remedy (Table 13). Granted on the 5000-day banks of this analysis, the ordinary certificate covers 131 OR-Tools plans, of which 90 failed under random incidents and 82 under the stronger peak. The *stress screen* admits a candidate only if it passes under all five models and then certifies it under all five. It certified 76 OR-Tools and 42 HGS plans, and none failed under any of the five models (0 failures); under incidents and the stronger peak they averaged 97.4% and 98.4% reliability. Robustness has a price: where both screens selected a plan, the stress-screened OR-Tools plan used 0.65 more vehicles and 3.3% more distance (HGS: 0.71 and 3.5%), and a plan was certified on 76 of 159 instances instead of 131 (HGS: 42 of 106 instead of 90).

The certified slowdown margin (Proposition 5) shows why single-model certificates broke. Testing slowdowns from 2.5% to 50% on each plan's validation days (`code/slowdown_margin.py`), the median margin of the 218 plans certified under the assumed model was only 2.5%, and 26% had none: the cheapest

Table 13. Certifying against several delay models, on the synthetic instances of the development and confirmatory studies. *Certified*: plans certified, out of all instances. The other columns count certified plans that failed their certificate on 5000 fresh days under each true delay model: random incidents, a stronger morning peak, more noise in the peaks, heavy-tailed delays, and the assumed model. The stress screen admits a candidate only if it passes under all five models.

		Failed certificates under the true model				
Configuration	Certified	Incid.	Peak	Noise	Tails	Assumed
Capped (OR-Tools)						
Ordinary screen, certified under the assumed model	131/159	90	82	27	0	0
Ordinary screen, certified under all five models	15/159	0	0	0	0	0
Stress screen, certified under all five models	76/159	0	0	0	0	0
Capped (HGS)						
Ordinary screen, certified under the assumed model	90/106	69	69	24	0	0
Ordinary screen, certified under all five models	12/106	0	0	0	0	0
Stress screen, certified under all five models	42/106	0	0	0	0	0

passing plan is, almost by construction, only just good enough. The margin predicted which certificates survived. Of 139 plans with a margin below 5%, 10 kept their certificate under random incidents and 11 under the stronger peak, against 34 and 46 of 62 with 5 to 10%, and all 17 plans with at least 10% kept it under all four harsher models (areas under the ROC curve 0.90 and 0.93). The margin translates rather than adds information, since the validated success estimate predicted survival as well (0.94 and 0.94); its value is the unit, which a firm can compare with how wrong it believes its model to be. The stronger peak slows only morning trips, by one sixth, so the proposition guarantees every plan with a margin of at least one sixth; all 3 such plans survived, too few to test the guarantee. Measured in minutes instead (Proposition 6), the median certified shift margin of the 666 plans certified in the main analysis was 1 minute per trip; 80 (12%) lost their certificate when half a minute was added to every trip, which turned a median 0.46% of their successful days into failures, and only 6 kept it at 10 minutes. On the synthetic plans the shift margin predicted survival a little less well than the slowdown margin (0.82 and 0.87).

6.8 Comparison with robust optimization

A budgeted robust model plans against worst-case travel times on a limited number of trips. Without a reachability correction it failed on 16 of 45 development instances at its most protective setting, for the same reason as the uncapped procedure. With an analogous correction and the same screen, the robust plans were more reliable than both screened procedures in study 3 part A (by 6.7 and 6.7 points; Table 4), but used 0.42 more vehicles per instance than the HGS procedure, and when limited to no more vehicles than the comparison plan their advantage was no longer detectable. The layer is not the most reliable planner tested; its value is that it works with the solver a firm already has and says how reliable the plan is.

7 Implications for planning systems

For a firm, the layer sits between the routing solver and dispatch. It needs only the ability to tighten internal deadlines and to simulate plans; screening a candidate took 3 to 24 ms against several seconds to generate it. Six rules follow. First, report the certificate with the plan: an uncertified plan is a warning that the day is at risk. Second, use the capped deadlines; without them large buffers can make the problem infeasible. Third, choose the fallback deliberately and flag it as uncertified. Fourth, certify candidates in a fixed order from the largest buffer down and use the cheapest certified plan (Proposition 4); this certified 228 of 265 instances against 218 for the screened plan, at no measurable cost. Fifth, certify against delay models at least as harsh as reality, for example a fitted model together with incidents and a stronger peak (Propositions 1 and 2), and accept the extra vehicles, or at least require a certified slowdown or shift margin as large as the error the firm expects in its model (Propositions 5 and 6); plans with a margin of 10% or more survived every harsher model we tried. Sixth, fit the delay model to measured trips, such as GPS tracks, not to the gaps in dispatch logs, which record the couriers' choices (Appendix C); a certificate resting on history alone needs at least 59 distinct days (Proposition 3).

8 Limitations

Threats to validity. The main threat is the delay model: certificates failed for 86 of 130 plans under random incidents and 78 of 130 under a stronger peak (Table 12), and the stress screen removes this only at the cost in Table 13. Without models that bound its real delays, a firm should not read a certificate as a statement about real days.

The main studies use synthetic instances and an assumed delay model. The benchmark and Amazon experiments are not a field validation: the Amazon windows are assumed and the fitted delays come from New York taxis. All analyses beyond the eight primary hypotheses are exploratory. The original OR-Tools procedure's advantage depended on the objective weights, with intervals reaching zero for two of the vectors tried (Appendix A); the capped HGS procedure still beat padding by 22.4 [18.2, 26.4] points with equal weights. Vehicles leave at their planned times, and breakdowns and same-day re-planning are not modelled. On 12 of 60 Amazon routes the scaling solves of the weighted objective failed, so the screen could not run there. The layer has not been run on a real fleet; given what the LaDe data showed (Appendix C), a controlled pilot, with plans fixed in the morning and arrival times recorded, is the test that remains.

9 Conclusion

A firm can add a reliability guarantee to the routing solver it already uses. Asking the solver for a few plans with capped internal buffers, screening them by simulation and certifying the chosen plan on independent days gave more reliable service than fixed padding at any level on the synthetic instances, and certificates held on fresh days without exception. Testing candidates in a fixed order certifies the cheapest qualifying plan at no cost to the guarantee. The guarantee is about the delay model; it carries over to real delays no worse than modelled, and certifying against several pessimistic models removed every failure we observed, at a price. The models should be fitted to a firm's own measured trips, and a pilot on a real fleet, with its real windows, is the natural next step.

Acknowledgements

The author thanks the researchers who answered methodological questions by e-mail during the project.

Author contributions (CRediT)

Suhan Ali: conceptualization, methodology, software, validation, formal analysis, investigation, data curation, visualization, writing – original draft, writing – review and editing.

Use of generative AI

Claude (Anthropic; mainly Claude Opus 5.5, with earlier Claude models during 2026) and DeepSeek (DeepSeek V4.1 Flash 1017) were used to write and debug the simulation and analysis code, to review that code, to run and check the statistical analyses, to search the literature, and to draft and revise the text of this manuscript, including its wording. They were used under their providers' terms of use. Independently of these tools, the author re-ran the archived analysis scripts and confirmed that they regenerate the reported tables from the archived records. The research question, the study design and the confirmatory protocols were the author's. Every experiment was run from the archived code, every reported number is regenerated from the archived records, and the author takes full responsibility for the content.

Disclosure of interest

The author reports there are no competing interests to declare.

Funding

This research received no external funding.

Data availability statement

All code, instances, records and analysis scripts are openly available (Ali, 2026a). The Amazon route sample is redistributed under its CC BY-NC 4.0 licence; the New York taxi records are public and are not copied.

References

Hassana Abdullahi, Lorena Reyes-Rubiano, Djamila Ouelhadj, Javier Faulin, and Angel A. Juan. A reliability-extended simheuristic for the sustainable vehicle routing problem with stochastic travel times and demands. *J Heuristics*, 31(2), 2025. doi: 10.1007/s10732-025-09555-4.

A. Agra, M. Christiansen, R. Figueiredo, L. M. Hvattum, M. Poss, and C. Requejo. The robust vehicle routing problem with time windows. *Comput Oper Res*, 40(3):856–866, 2013. doi: 10.1016/j.cor.2012.10.002.

S. Ahmed and A. Shapiro. Solving chance-constrained stochastic programs via sampling and integer programming. In Z.-L. Chen and S. Raghavan, editors, *State-of-the-Art Decision-Making Tools in the Information-Intensive Age*, TutORials in Operations Research, pages 261–269. INFORMS, Hanover, MD, 2008. doi: 10.1287/educ.1080.0048.

S. Ali. Reliability-screened routing: research code and evidence archive. Zenodo, 2026a. URL `https://doi.org/10.5281/zenodo.23185704`. Software and dataset, all versions; the analyses in this paper are in version v4.2 and later.

S. Ali. Reliability-screened routing: research code and evidence archive. Zenodo, 2026b. Confirmatory protocol 1 freeze, commit 41fae67d9520bd5dd01fcac87e680a5a69325d10.

S. Ali. Reliability-screened routing: research code and evidence archive. Zenodo, 2026c. Confirmatory protocol 2 freeze, commit 3ba6b71288a2a51872ab6a877fa86eb28ff7671d.

S. Ali. Reliability-screened routing: research code and evidence archive. Zenodo, 2026d. Confirmatory protocol 3 freeze, commit 21ffaa8eed4e899778e14014b73533fd4d14d865.

D. Bertsimas and M. Sim. The price of robustness. *Oper Res*, 52(1):35–53, 2004. doi: 10.1287/opre.1030.0065.

F. Bomboi, C. Buchheim, and J. Pruente. On the stochastic vehicle routing problem with time windows, correlated travel times, and time dependency. *4OR*, 20(2):217–239, 2022. doi: 10.1007/s10288-021-00476-z.

L. D. Brown, T. T. Cai, and A. DasGupta. Interval estimation for a binomial proportion. *Stat Sci*, 16(2):101–133, 2001. doi: 10.1214/ss/1009213286.

Marco C. Campi and Simone Garatti. The exact feasibility of randomized solutions of uncertain convex programs. *SIAM J Optim*, 19(3):1211–1230, 2008. doi: 10.1137/07069821X.

C. J. Clopper and E. S. Pearson. The use of confidence or fiducial limits illustrated in the case of the binomial. *Biometrika*, 26(4):404–413, 1934. doi: 10.1093/biomet/26.4.404.

J. F. Ehmke, A. M. Campbell, and T. L. Urban. Ensuring service levels in routing problems with time windows and stochastic travel times. *Eur J Oper Res*, 240(2):539–550, 2015. doi: 10.1016/j.ejor.2014.06.045.

F. Errico, G. Desaulniers, M. Gendreau, W. Rei, and L.-M. Rousseau. The vehicle routing problem with hard time windows and stochastic service times. *EURO J Transp Logist*, 7(3):223–251, 2018. doi: 10.1007/s13676-016-0101-4.

H. Gehring and J. Homberger. A parallel hybrid evolutionary metaheuristic for the vehicle routing problem with time windows. In K. Miettinen, M. Mäkelä, and J. Toivanen, editors, *Proceedings of EUROGEN99*, pages 57–64, Jyväskylä, 1999. University of Jyväskylä.

M. Gendreau, G. Laporte, and R. Séguin. Stochastic vehicle routing. *Eur J Oper Res*, 88(1):3–12, 1996. doi: 10.1016/0377-2217(95)00050-X.

M. Gendreau, O. Jabali, and W. Rei. 50th anniversary invited article—Future research directions in stochastic vehicle routing. *Transp Sci*, 50(4):1163–1173, 2016. doi: 10.1287/trsc.2016.0709.

G. Ghiani and E. Guerriero. A note on the Ichoua, Gendreau, and Potvin (2003) travel time model. *Transp Sci*, 48(3):458–462, 2014. doi: 10.1287/trsc.2013.0491.

S. Davod Hosseini, Borzou Rostami, and Mojtaba Araghi. Service time window design in last-mile delivery, 2025. URL `https://arxiv.org/abs/2508.01032`. arXiv:2508.01032.

S. Ichoua, M. Gendreau, and J.-Y. Potvin. Vehicle dispatching with time-dependent travel times. *Eur J Oper Res*, 144(2):379–396, 2003. doi: 10.1016/S0377-2217(02)00147-9.

O. Jabali, R. Leus, T. Van Woensel, and T. de Kok. Self-imposed time windows in vehicle routing problems. *OR Spectrum*, 37(2):331–352, 2015. doi: 10.1007/s00291-013-0348-1.

P. Jaillet, J. Qi, and M. Sim. Routing optimization under uncertainty. *Oper Res*, 64(1):186–200, 2016. doi: 10.1287/opre.2015.1462.

Christopher Jennison and Bruce W. Turnbull. *Group Sequential Methods with Applications to Clinical Trials*. Chapman & Hall/CRC, Boca Raton, 2000.

Angel A. Juan, Javier Faulin, Scott E. Grasman, Markus Rabe, and Gonçalo Figueira. A review of simheuristics: extending metaheuristics to deal with stochastic combinatorial optimization problems. *Oper Res Perspect*, 2:62–72, 2015. doi: 10.1016/j.orp.2015.03.001.

A. S. Kenyon and D. P. Morton. Stochastic vehicle routing with random travel times. *Transp Sci*, 37(1): 69–82, 2003. doi: 10.1287/trsc.37.1.69.12820.

G. Laporte, F. Louveaux, and H. Mercure. The vehicle routing problem with stochastic travel times. *Transp Sci*, 26(3):161–170, 1992. doi: 10.1287/trsc.26.3.161.

X. Li, P. Tian, and S. C. H. Leung. Vehicle routing problems with time windows and stochastic travel and service times: Models and algorithm. *Int J Prod Econ*, 125(1):137–145, 2010. doi: 10.1016/j.ijpe.2010.01.013.

James Luedtke and Shabbir Ahmed. A sample approximation approach for optimization with probabilistic constraints. *SIAM J Optim*, 19(2):674–699, 2008. doi: 10.1137/070702928.

Willi Maurer, Ludwig A. Hothorn, and Walter Lehmacher. Multiple comparisons in drug clinical trials and preclinical assays: a priori ordered hypotheses. In Joachim Vollmar, editor, *Biometrie in der chemisch-pharmazeutischen Industrie*, volume 6, pages 3–18. Fischer Verlag, Stuttgart, 1995.

Daniel Merchán, Jatin Arora, Julian Pachon, Karthik Konduri, Matthias Winkenbach, Steven Parks, and Joseph Noszek. 2021 Amazon last mile routing research challenge: data set. *Transp Sci*, 2022. doi: 10.1287/trsc.2022.1173.

New York City Taxi and Limousine Commission. TLC trip record data: yellow taxi trip records, January–March 2024, 2024. URL `https://www.nyc.gov/site/tlc/about/tlc-trip-record-data.page`.

L. Perron and V. Furnon. OR-Tools, 2026. URL `https://developers.google.com/optimization`. Version 9.15.

Stuart J. Pocock. Group sequential methods in the design and analysis of clinical trials. *Biometrika*, 64(2): 191–199, 1977. doi: 10.1093/biomet/64.2.191.

T. L. Saaty. *The Analytic Hierarchy Process*. McGraw-Hill, New York, 1980.

B. Serrano, A. M. Florio, S. Minner, M. Schiffer, and T. Vidal. Contextual stochastic vehicle routing with time windows. *INFORMS J Comput*, 2026. doi: 10.1287/ijoc.2025.1189. Articles in advance.

M. M. Solomon. Algorithms for the vehicle routing and scheduling problems with time window constraints. *Oper Res*, 35(2):254–265, 1987. doi: 10.1287/opre.35.2.254.

D. Taş, N. Dellaert, T. van Woensel, and A. G. de Kok. The time-dependent vehicle routing problem with soft time windows and stochastic travel times. *Transp Res Part C Emerg Technol*, 48:66–83, 2014. doi: 10.1016/j.trc.2014.08.007.

P. Toth and D. Vigo, editors. *Vehicle Routing: Problems, Methods, and Applications*. MOS-SIAM Series on Optimization. SIAM, Philadelphia, 2nd edition, 2014. doi: 10.1137/1.9781611973594.

A. D. Vareias, P. P. Repoussis, and C. D. Tarantilis. Assessing customer service reliability in route planning with self-imposed time windows and stochastic travel times. *Transp Sci*, 53(1):256–281, 2019. doi: 10.1287/trsc.2017.0748.

T. Vidal. Hybrid genetic search for the CVRP: Open-source implementation and SWAP* neighborhood. *Comput Oper Res*, 140:105643, 2022. doi: 10.1016/j.cor.2021.105643.

E. B. Wilson. Probable inference, the law of succession, and statistical inference. *J Am Stat Assoc*, 22 (158):209–212, 1927. doi: 10.1080/01621459.1927.10502953.

N. A. Wouda, L. Lan, and W. Kool. PyVRP: A high-performance VRP solver package. *INFORMS J Comput*, 36(4):943–955, 2024. doi: 10.1287/ijoc.2023.0055.

Lixia Wu, Haomin Wen, Haoyuan Hu, Xiaowei Mao, Yutong Xia, Ergang Shan, Jianbin Zheng, Junhong Lou, Yuxuan Liang, Liuqing Yang, Roger Zimmermann, Youfang Lin, and Huaiyu Wan. LaDe: The first comprehensive last-mile delivery dataset from industry, 2023. URL `https://arxiv.org/abs/2306.10675`. arXiv:2306.10675.

Y. Zhang, R. Baldacci, M. Sim, and J. Tang. Routing optimization with time windows under uncertainty. *Math Program*, 175(1–2):263–305, 2019. doi: 10.1007/s10107-018-1243-y.

Yu Zhang, Zhenzhen Zhang, Andrew Lim, and Melvyn Sim. Robust data-driven vehicle routing with time windows. *Oper Res*, 69(2):469–485, 2021. doi: 10.1287/opre.2020.2043.

A Objective weights

The weights in (4) are the normalized principal eigenvector of the pairwise comparison matrix below, read as "the row criterion is this many times as important as the column criterion" on Saaty's 1–9 scale; its consistency ratio is 0.025. The matrix was first written for an earlier set of criteria in which the third was total distance, and its third row and column were not re-elicited when that criterion became driver time. The weights were fixed in the preregistered protocols, so re-eliciting them now would change the confirmatory tests after the fact. Instead, Table A1 reports equal weights as a documented alternative for both procedures.

	Distance	Slack deficit	Driver time	Vehicles
Distance	1	3	5	7
Slack deficit	1/3	1	3	5
Driver time	1/5	1/3	1	2
Vehicles	1/7	1/5	1/2	1

Table A1 reports the original procedure under other weight vectors, fixed before each run. Changing the order of distance and slack, or putting most of the weight on distance, changed the advantage over 20% padding little. Moving weight to vehicles or driver time reduced it: those weights favour candidates with fewer vehicles or less waiting, which leaves less time to absorb delays. With equal weights the interval included zero in one run but not in the other, and with a larger weight on driver time it included zero. The screen and the certificate do not use the weights, so every certificate in the paper holds whatever the weights; only the reliability of the selected plan depends on them. The first two blocks use the original OR-Tools procedure. The capped HGS procedure (last block), rerun on 48 development instances with the two vectors that hurt the original procedure most, stayed well ahead of 20% padding: by 22.4 [18.2, 26.4] points with equal weights and 25.5 [21.8, 29.2] with the larger weight on driver time, against 27.0 [23.5, 30.4] with the AHP weights, so the conclusions about the capped procedure do not rest on the matrix. Against the original weights, equal weights changed its reliability by -4.6 [-8.3, -1.6] points and its vehicles by -0.42 per instance (`code/hgs_weights.py`). Planning the capped buffers for distance alone was as reliable as the weighted procedure (Table 5), so with the capped procedure the gain does not depend on the weights.

B OR-Tools on the Amazon routes

With OR-Tools (Table B1), the capped procedure was more reliable than 20% padding under every delay model: by 13.6 [3.9, 24.4], 13.9 [3.8, 26.2] and 20.6 [10.9, 31.4] points under the assumed model, the day-to-day and the full fitted model. Much of this gap comes from planning: padding had no plan on 12 routes, against 6 for the others. On the 28 routes where both had a plan they were level under the assumed model (1.6 [-4.4, 7.2]), screening was ahead under the full fitted model (8.8 [4.6, 13.3]) and padding slightly ahead under the day-to-day model (-1.2 [-1.9, -0.6]). The 6 routes without any plan are limits of the 5-second search, since the driver's own order is feasible. With 60 seconds OR-Tools found a padded plan on 4 of the 12 routes where padding had none, and re-scored with them the capped procedure's lead became 5.6 [-3.1, 14.5], 4.0 [-5.7, 14.2] and 12.1 [2.9, 21.8] points.

Table A1. Sensitivity to the objective weights on the 53 development instances (exploratory). Weights in the order distance, slack deficit, driver time, vehicles. *Adm.*: instances where screening admitted a plan; *Pooled*: pooled validated reliability (%) of the original procedure; *Advantage*: its paired advantage over 20% padding in percentage points on the 46 instances where padding has a plan, with 95% bootstrap intervals. OR-Tools stops at a time limit, so results are compared within a run; the two runs were made on different machines. Last block: the capped HGS procedure (code/hgs_weights.py) on the development instances where both it and padding have a plan; HGS stops after a fixed number of iterations, so these rows do not depend on the machine.

Weights	Vector	Adm.	Pooled	Advantage
First run				
AHP (original)	(0.5693, 0.2643, 0.1055, 0.0609)	31	77.5	16.2 [9.4, 22.8]
Slack first	(0.2643, 0.5693, 0.1055, 0.0609)	30	77.4	16.0 [9.7, 22.2]
Distance heavy	(0.8, 0.1, 0.05, 0.05)	29	74.3	12.7 [5.2, 19.8]
Equal	(0.25, 0.25, 0.25, 0.25)	23	68.7	6.3 [−1.1, 13.6]
Second run, another machine				
AHP (original)	(0.5693, 0.2643, 0.1055, 0.0609)	32	78.7	17.5 [10.8, 23.9]
Equal	(0.25, 0.25, 0.25, 0.25)	24	70.2	8.1 [1.1, 15.1]
Vehicle weight raised	(0.4546, 0.2111, 0.0843, 0.25)	27	73.2	11.7 [4.7, 18.6]
Driver-time weight raised	(0.4773, 0.2216, 0.25, 0.0511)	25	69.9	7.4 [−0.6, 15.4]
Capped HGS procedure, 48 instances				
AHP (original)	(0.5693, 0.2643, 0.1055, 0.0609)	43	93.7	27.0 [23.5, 30.4]
Equal	(0.25, 0.25, 0.25, 0.25)	37	89.1	22.4 [18.2, 26.4]
Driver-time weight raised	(0.4773, 0.2216, 0.25, 0.0511)	41	92.3	25.5 [21.8, 29.2]

Table B1. Real delivery routes: 40 Amazon routes from five US cities (exploratory), under the assumed delay model and under the two delay models fitted to New York taxi trips (Table 10). *Plans*: routes on which the configuration produced a plan (the same under every delay model). Pooled validated service probability (%) with a 95% bootstrap interval over routes; a route without a plan scores zero. *Admitted*: routes on which a candidate passed the screen.

		Pooled service under the delay model		
Configuration	Plans	Assumed	NYC, day to day	NYC, all variation
Nominal plan (no protection)	34/40	41.4 [35.1, 47.1]	64.9 [55.4, 73.5]	46.9 [39.6, 53.8]
20% padding	28/40	59.0 [46.6, 70.8]	69.5 [54.7, 82.2]	59.5 [46.8, 71.8]
Capped screening procedure	34/40	72.6 [61.2, 82.9]	83.4 [71.3, 93.3]	80.1 [68.5, 90.2]
Screened conservative	34/40	75.3 [63.6, 85.7]	83.2 [71.3, 93.3]	77.3 [65.9, 87.5]
Admitted, capped procedure		24	34	30
Admitted, screened conservative		25	28	26

C What data a certificate can rest on: real pickup operations

The LaDe data of Cainiao (Wu et al., 2023) contain real pickups with real two-hour windows in five Chinese cities and, for one month, couriers' GPS tracks. They do not test the layer, but they show what data a certificate can rest on (Table C1).[1]

First, *dispatch records are not delay data*: the gap between two pickups is largely the courier's choice. Replayed in the real order, each courier's gaps reproduce the observed lateness; in random order they made 92.5% to 95.8% of 40,851 busy courier-days late, against 3.8% to 33.3% in reality, in every city. A delay model learned from the gaps predicted 72.5% of 1005 busy Jilin routes late; 2.7% were. Second, *travel and handling measured from GPS are stable*: on trips that went straight from one pickup to the next, the median pace changed by at most 5.6% and the median time stationary by at most 4.0% between

[1] All numbers come from `code/lade_findings.py` in the archive, which documents how direct trips are identified on the GPS tracks and how each instance of the third finding is built from the real orders of three couriers of one station on one day, with their promised windows and three vehicles.

the first three weeks and the last ten days, in every city. Third, *the promised windows do not bind as a VRPTW assumes*: couriers picked up 24.4% of Hangzhou orders early, and planned as hard windows at the measured times, 33.3% of 150 real three-courier teams in Hangzhou and 47.3% of 150 in Yantai had no feasible plan. A comparison with padding would depend on how that relaxation is modelled, so we report none; and 31 days are too few for a certificate without a delay model, which needs 59 (Proposition 3).

Table C1. Real pickup operations in five Chinese cities, 21 March to 20 April 2022 (LaDe; exploratory). Left: busy courier-days (at least 30 pickups) and the share (%) with a pickup after its promised window: observed, replayed with the courier's real gaps between pickups in the real order, and with the same gaps in random order (mean of 200 permutations). Right: direct trips between consecutive pickups measured from GPS, their share of all trips (%), and the median pace (seconds of movement per metre) and median time stationary (minutes) in the first 21 days (*H*) and the last 10 (*F*). Shanghai was under lockdown for most of the period.

	Lateness of real routes				Direct trips (GPS)				
						Pace		Stationary	
City	Days	Obs.	Replay	Shuffled	Share	H	F	H	F
Hangzhou	5696	25.7	25.7	95.7	20.5	0.393	0.376	4.0	4.0
Chongqing	2790	21.9	21.9	95.7	17.1	0.391	0.405	4.2	4.0
Yantai	1963	14.1	14.1	94.7	21.4	0.296	0.305	4.1	4.1
Shanghai	3249	16.8	16.8	92.9	18.6	0.407	0.408	4.3	4.2
Jilin	18	33.3	33.3	92.5	14.1	0.380	0.401	3.7	3.7