Experiment 2

Student Name: Suhani Rawat **UID:** 23BAI70070
Branch: BE CSE AIML **Section/Group:** 23AIT-KRG G1
Semester: 6th **Date of Performance:** 14 January 2026
Subject Name: Full Stack **Subject Code:** 23CSH-382

1. **Title:**
   Routing, Protected Routes & Context-Based State Management in EcoTrack

2. **Aim:**
   To implement Single Page Application (SPA) navigation in the EcoTrack application using React Router, secure application routes using context-based authentication, and extend nested dashboard routing through follow-up enhancements.

3. **Objective:**
   After completing this experiment and its follow-up tasks, the student will be able to:
   1. Configure client-side routing in a React application using React Router
   2. Implement SPA navigation without full page reloads
   3. Design and apply protected routes using route-guard patterns
   4. Manage shared authentication state using React Context API
   5. Implement nested routing to build dashboard-style layouts
   6. Extend existing nested routes by adding new dashboard sections
   7. Implement logout functionality by updating shared context state
   8. Analyze route access behavior and explain redirection logic
   9. Understand the role of Context API in shared state management and its comparison with Redux at an introductory level

4. Implementation/Code:

- AuthContext.jsx:

```jsx
import { createContext, useContext, useState } from "react";

const AuthContext = createContext(null);

export const AuthProvider = ({children}) => {
    const [isAuthenticated, setIsAuthenticated] = useState(false);

    return (
        <AuthContext.Provider value = {{isAuthenticated, setIsAuthenticated}}>
            {children}
        </AuthContext.Provider>
    )
}

export const useAuth = () => useContext(AuthContext);
```

- ProtectedRoute.jsx:

```jsx
import { Navigate } from "react-router-dom";
import { useAuth } from "../context/AuthContext";
import { children } from "react";

const ProtectedRoute = ({children}) => {
    const {isAuthenticated} = useAuth();

    if(!isAuthenticated) {
        return <Navigate to = "/login" replace/>
    }
    return children;
}

export default ProtectedRoute;
```

- Logs.jsx:

```jsx
import logs from "../data/logs";

const Logs = () => {
    return (
        <div>
            <h1>Logs</h1>
            <ol>
                {logs.map((log) => (
                    <li key={log.id}>
                        {log.activity}: {log.carbon} kg CO2
                    </li>
                ))}
            </ol>
        </div>
    )
}

export default Logs;
```

- Login.jsx:

```jsx
import { useAuth } from "../context/AuthContext";
import { useNavigate } from "react-router-dom";

const Login = () => {
    const {setIsAuthenticated} = useAuth();
    const navigate = useNavigate();

    const handleLogin = () => {
        setIsAuthenticated(true);
        navigate("/");
    }
    return (
        <>
        <h3>Login</h3>
        <button onClick={handleLogin}>Login</button>
        </>
    )
}
export default Login;
```

- Logout.jsx:

```jsx
import { useEffect } from "react";
import { useNavigate } from "react-router-dom";
import { useAuth } from "../context/AuthContext";

const Logout = () => {
  const { setIsAuthenticated } = useAuth();
  const navigate = useNavigate();

  useEffect(() => {
    setIsAuthenticated(false);
    navigate("/login");
  }, [setIsAuthenticated, navigate]);

  return <p>Logging you out...</p>;
}

export default Logout;
```

- DashboardSettings, DashboardSummary, DashboardAnalytics:

```jsx
const DashboardSettings = () => {
    return (
        <h3>These are the settings</h3>
    )
}

export default DashboardSettings;
```

```jsx
const DashboardSummary = () => {
    return (
        <h3>This is a Summary</h3>
    )
}

export default DashboardSummary;
```

```jsx
const DashboardAnalytics = () => {
    return (
        <h3>This is a Analysis</h3>
    )
}

export default DashboardAnalytics;
```

- DashboardLayout.jsx:

```jsx
import { Link, Outlet } from "react-router-dom";

const DashboardLayout = () => {
    return (
        <>
        <h3>Dashboard</h3>

        <nav>
            <Link to = "settings">Settings</Link>{" "}
            <Link to = "summary">Summmary</Link>{" "}
            <Link to = "analytics">Analytics</Link>
        </nav>

        <hr />
        <Outlet />
        </>

    )
}

export default DashboardLayout;
```

- Header.jsx:

```jsx
import { Link } from "react-router-dom";
import { useAuth } from "../context/AuthContext";

const Header = () => {
    const {isAuthenticated} = useAuth();
    return (
        <header style = {{
            padding: '10px',
            backgroundColor: '#5499f8',
            color : 'white',
            textAlign: 'center',
        }}>
            <h1>EcoTrack</h1>
            <Link to = "/">Dashboard</Link>{" "}
            <Link to = "/logs">Logs</Link>{" "}
            {isAuthenticated ? (
                <Link to = "/logout">Logout</Link>
            ) : (
                <Link to = "/login">Login</Link>
            )}
        </header>
    )
}
export default Header;
```

- App.jsx:

```jsx
import { Route, Routes } from "react-router-dom";
import Login from "./pages/Login";
import Logout from "./pages/Logout";
import DashboardAnalytics from "./pages/DashboardAnalytics";
import DashboardLayout from "./pages/DashboardLayout";
import DashboardSummary from "./pages/DashboardSummary";
import DashboardSettings from "./pages/DashboardSettings";
import ProtectedRoute from "./routes/ProtectedRoute";
import Logs from "./pages/logs";
import Header from "./components/Header";

function App() {
    return (
        <>
        <Header />
        <Routes>
            <Route path = "/Login" element = {<Login/>} />
            <Route path = "/Logout" element = {<Logout/>}/>
            <Route path = "/"
            element = {
                <ProtectedRoute>
                <DashboardLayout/>
                </ProtectedRoute>
            }>
            <Route index element = {<DashboardSummary/>}/>
            <Route path = "settings" element = {<DashboardSettings/>}/>
            <Route path = "summary" element = {<DashboardSummary/>}/>
            <Route path = "analytics" element = {<DashboardAnalytics/>}/>
            </Route>
            <Route path = "/logs"
            element = {
                <ProtectedRoute>
                <Logs/>
                </ProtectedRoute>
            }>
            </Route>
        </Routes>
        </>
    )
}
export default App;
```

5. Output



6. Learning Outcome

- We learnt about React Apps and how to create them.
- We learnt about reduce function and how it replaces map and filter.
- We learnt about the use of hooks.
- We learnt about Authentication and index pages
- We learnt the use of useContext and useState.
- We learnt about the flow of a React project.