```
#include <iostream>
using namespace std;

int main() {
    int a[5], b[5], choice;
    int sum = 0, largest;

    cout << "Enter 5 elements of first array: ";
    for (int i = 0; i < 5; i++) {
        cin >> a[i];
    }

    cout << "Enter 5 elements of second array: ";
    for (int i = 0; i < 5; i++) {
        cin >> b[i];
    }

    cout << "\n1. Addition of arrays";
    cout << "\n2. Subtraction of arrays";
    cout << "\n3. Multiplication of arrays";
    cout << "\n4. Find largest element";
    cout << "\n5. Calculate average";
    cout << "\nEnter your choice: ";
    cin >> choice;

    switch (choice) {
        case 1:
            for (int i = 0; i < 5; i++) {
                cout << a[i] + b[i] << " ";
            }
            break;

        case 2:
            for (int i = 0; i < 5; i++) {
                cout << a[i] - b[i] << " ";
            }
            break;

        case 3:
            for (int i = 0; i < 5; i++) {
                cout << a[i] * b[i] << " ";
            }
            break;

        case 4:
            largest = a[0];

            for (int i = 1; i < 5; i++) {
```

```
            if (a[i] > largest) {
                largest = a[i];
            }
        }

        cout << "Largest element = " << largest;
        break;

    case 5:
        for (int i = 0; i < 5; i++) {
            sum = sum + a[i];
        }

        cout << "Average = " << sum / 5.0;
        break;

    default:
        cout << "Invalid choice";
  }

  return 0;
}
```

