

# ASSIGNMENT-10 EE17B109

April 15, 2019

## 1 Introduction

In this experiment we will be trying to do convolution operation on various signals and using both methods of linear convolution and circular convolution. In the theory class we have analyzed the advantages of using circular convolution over using linear convolution when we are receiving continuous samples of inputs. We will also be analysing the effect of passing the signal  $x = \cos(0.2\pi n) + \cos(0.85\pi n)$  through a given filter. At last we will be analysing the cross-correlation output of the Zadoff–Chu sequence.


## 2 Importing packages

```
In [1]: import numpy as np
import csv
from scipy import signal
import matplotlib.pyplot as plt
from math import *
import pandas as pd
```

## 3 Filter sequence

Now we will use the `signal.freqz` function to visualize the filter in frequency domain.


```
In [2]: a = np.genfromtxt('h.csv', delimiter=',')
w, h = signal.freqz(a)
fig, ax = plt.subplots(2, sharex=True)
plt.grid(True, which="all")
ax[0].plot(w, (abs(h)), "b")
ax[0].set_title("Filter Magnitude response")
ax[0].set_xlabel("Frequency(w rad/s)")
ax[0].set_ylabel("Amplitude dB")
angle = np.unwrap(np.angle(h))
ax[1].plot(w, angle, "g")
ax[1].set_title("Filter Phase response")
ax[1].set_xlabel("Frequency(w rad/s)")
ax[1].set_ylabel("Phase")
plt.show()
```



Here I have plotted both the magnitude and phase response of the filter in the appropriate frequency range. It is clear from the plot that the given filter is a low-pass filter with a cutoff frequency of about 0.75 rad/s.

#### 4 Given Signal:


```
In [3]: n = np.linspace(1,2**10,2**10)
        x = np.cos(0.2*pi*n) + np.cos(0.85*pi*n)
        fig2,bx = plt.subplots(1,sharex=True)
        bx.plot(n,x)
        bx.set_title("Sequence plot")
        bx.set_xlabel("n")
        bx.set_ylabel("x")
        bx.set_xlim(0,40)
        plt.show()
```



Clearly the input sequence has frequency components of  $0.2\pi = 0.628$  rad/s and  $0.85\pi = 2.669$  rad/s.

## 5 Passing signal through Filter

```
In [4]: y = np.convolve(x,a,mode="same")
fig3,cx = plt.subplots(1,sharex=True)
cx.plot(y)
cx.set_title("Filtered output plot using linear convolution ")
cx.set_xlabel("n")
cx.set_ylabel("y")
cx.set_xlim(0,40)
plt.show()
```




We can clearly see that it acted as a low pass filter

## 6 Using Circular Convolution

```
In [5]: a_adjusted = np.pad(a,(0,len(x)-len(a)),"constant")
        y1 = np.fft.ifft(np.fft.fft(x) * np.fft.fft(a_adjusted))
        fig4,dx = plt.subplots(1,sharex=True)
        dx.plot(y1)
        dx.set_title("Filtered output plot using circular convolution ")
        dx.set_xlabel("n")
        dx.set_ylabel("y")
        dx.set_xlim(0,40)
        plt.show()
```

```
/home/suhas/anaconda3/lib/python3.6/site-packages/numpy/core/numeric.py:492: ComplexWarning: C
return array(a, dtype, copy=False, order=order)
```




in order to compute the output using circular-convolution I am initially padding my signals in to avoid overlapping of the output over itself. By doing this we will be getting the output sequence just like linear convolution.

## 7 Circular Convolution using linear stitching

```
In [6]: N = len(a) + len(x) - 1
        fil = np.concatenate([a,np.zeros(N-len(a))])
        y_modified = np.concatenate([x,np.zeros(N-len(x))])
        y2 = np.fft.ifft(np.fft.fft(y_modified) * np.fft.fft(fil))
        fig5,fx = plt.subplots(1,sharex=True)
        fx.plot(y2)
        fx.set_title("Filtered output plot using linear convolution as circular convolution ")
        fx.set_xlabel("n")
        fx.set_ylabel("y")
        fx.set_xlim(0,40)
        plt.show()
```


/home/suhas/anaconda3/lib/python3.6/site-packages/numpy/core/numeric.py:492: ComplexWarning: Casting complex values to real discards the imaginary part  
 return array(a, dtype, copy=False, order=order)



We clearly see that the output is exactly similar to the one which we got by linear convolution. Hence it is seen that by padding the sequence appropriately we will be able to achieve the output using circular convolution.

## 8 Zadoff Sequence

```
In [7]: zadoff = pd.read_csv("x1.csv").values[:,0]
        zadoff = np.array([complex(zadoff[i].replace("i","j")) for i in range(len(zadoff))])
        zw,zh = signal.freqz(zadoff)
        fig5,ex = plt.subplots(2,sharex=True)
        plt.grid(True,which="all")
        ex[0].plot(zw,(abs(zh)), "b")
        ex[0].set_title("zadoff Magnitude response")
        ex[0].set_xlabel("Frequency(w rad/s)")
        ex[0].set_ylabel("Zadoff Amplitude dB")
        angle_z = np.unwrap(np.angle(zh))
        ex[1].plot(zw,angle_z, "g")
        ex[1].set_title("Zadoff Phase response")
        ex[1].set_xlabel("Frequency(w rad/s)")
        ex[1].set_ylabel("Phase")
        plt.show()
```




Properties of Zadoff-Chu sequence: (a) It is a complex sequence. (b) It is a constant amplitude sequence. (c) The autocorrelation of a Zadoff-Chu sequence with a cyclically shifted version of itself will give a peak at that delay. (d) Correlation of Zadoff-Chu sequence with the delayed version of itself will give a peak at that delay.

## 9 Co-relation with shifting with itself

```
In [10]: zadoff_modified = np.concatenate([zadoff[-5:], zadoff[:-5]])
```

```
z_out = np.correlate(zadoff, zadoff_modified, "full")
fig7, gx = plt.subplots(1, sharex=True)
plt.grid(True, which="all")
gx.plot((abs(z_out)), "b")
gx.set_title(" correlation of zadoff and shifted Z Magnitude ")
gx.set_xlabel("n")
gx.set_ylabel("Magnitude")
plt.show()
```



We clearly see a peak at shifted magnitude frequency correspondent

## 10 Conclusion

Hence through this assignment we are able to take the output of a system for a given signal using convolution. We approached convolution using linear method and circular method. We use padding to make the filter of appropriate size before we do the circular convolution. Later we analysed the crosscorrelation function of Zadoff–Chu sequence with its circularly shifted version of itself. We observe a sharp peak in appropriate location according to the circular shift done.