

```
[1]: from sklearn.feature_extraction.text import TfidfVectorizer
import numpy as np
import wikipedia
import random
```

```
CONVERGENCE_DELTA = 1e-5
MAXIMUM_ITERATIONS = 200
```

```
[2]: given_articles = [
    'Linear algebra',
    'Data Science',
    'Artificial intelligence',
    'European Central Bank',
    'Financial technology',
    'International Monetary Fund',
    'Basketball',
    'Swimming',
    'Cricket'
]
```

```
[3]: class KMeans():
    def __init__(
        self,
        x_train,
        y_train,
        num_clusters=3,
        seed: str = "random",
    ):
        self.dataset = x_train
        self.targets = y_train
        self.k = num_clusters
        self.num_features = x_train.shape[1]
        self.num_samples = x_train.shape[0]
        if seed == "random":
            self.centroids = self.random_initialise_centroids()
        elif seed == "custom":
            self.centroids = self.initialise_from_data()
        else:
            raise ValueError("Choose a seed between ['random', 'custom']")
        self.old_centroids = np.copy(self.centroids)
        self.cluster_labels = np.zeros(self.num_samples, dtype=int)
        for i in range(self.num_samples):
            self.cluster_labels[i] = np.argmin(
                np.linalg.norm(self.dataset[i]-self.centroids, ord=2, axis=1))

    def random_initialise_centroids(self):
```

```

mean = np.mean(self.dataset, axis = 0)
std = np.std(self.dataset, axis = 0)
return np.random.randn(self.k, self.num_features)*std + mean

def initialise_from_data(self):
    centroids = np.copy(self.dataset[np.random.choice(
        self.num_samples, self.k, replace=(False if self.k <= self.
→num_samples else True))])
    return centroids

def get_centroid_labels(self):
    centroid_labels = np.zeros(self.k)
    for i in range(self.k):
        count = np.bincount(self.targets[self.cluster_labels == i])
        if len(count) > 0:
            centroid_labels[i] = np.argmax(count)
    return centroid_labels

def calculate_loss(self):
    loss = np.mean(np.linalg.norm(
        self.dataset - self.centroids[self.cluster_labels], ord=2, axis=1),
→axis=0)
    return loss

def fit(self):
    for i in range(MAXIMUM_ITERATIONS):
        # assigning clusters to all data points
        for i in range(self.num_samples):
            self.cluster_labels[i] = np.argmin(
                np.linalg.norm(self.dataset[i]-self.centroids, ord=2,
→axis=1))
        prev_centers = np.copy(self.centroids)
        converged = True
        for i in range(self.k):
            allotted = self.dataset[self.cluster_labels == i]
            if len(allotted) > 0:
                self.centroids[i] = np.mean(allotted, axis=0)
            else:
                self.centroids[i] = np.zeros(self.num_features)
            if np.linalg.norm(prev_centers[i] - self.centroids[i]) >
→CONVERGENCE_DELTA:
                converged = False
        loss = self.calculate_loss()
        if converged is True:
            print(f"TOTAL ITERATIONS = {i}")
            break
        self.old_centroids = np.copy(self.centroids)

```

```
[4]: articles = []
    for article_name in given_articles:
        text = wikipedia.page(article_name, preload=True).content
        articles.append(text)
    vectorizer = TfidfVectorizer(stop_words={'english'})
    x_train = vectorizer.fit_transform(articles).toarray()
    y_train = np.arange(len(given_articles))
    k = [4, 8, 12]
    losses = []
```

```
[21]: random.seed(60)
    np.random.seed(60)
```

```
[45]: for num_clusters in k:
        kmeans = KMeans(x_train, y_train, num_clusters=num_clusters, seed='custom')
        print(f"\n-----\nNUMBER OF CLUSTERS = \u2192{num_clusters}")
        kmeans.fit()
        losses.append(kmeans.calculate_loss())
        clusters = [[] for i in range(num_clusters)]
        for i, article in enumerate(given_articles):
            index = kmeans.cluster_labels[i]
            clusters[index].append(article)
        for i, cluster in enumerate(clusters):
            print("Cluster no. {}: {}".format(i+1, cluster))
```

```
-----
NUMBER OF CLUSTERS = 4
TOTAL ITERATIONS = 3
Cluster no. 1: ['Data Science']
Cluster no. 2: ['Basketball', 'Swimming', 'Cricket']
Cluster no. 3: ['European Central Bank', 'Financial technology', 'International Monetary Fund']
Cluster no. 4: ['Linear algebra', 'Artificial intelligence']
```

```
-----
NUMBER OF CLUSTERS = 8
TOTAL ITERATIONS = 7
Cluster no. 1: ['Financial technology']
Cluster no. 2: ['Artificial intelligence']
Cluster no. 3: ['Data Science']
Cluster no. 4: ['International Monetary Fund']
Cluster no. 5: ['Swimming']
Cluster no. 6: ['Linear algebra']
Cluster no. 7: ['European Central Bank']
Cluster no. 8: ['Basketball', 'Cricket']
```

```
-----  
NUMBER OF CLUSTERS = 12  
TOTAL ITERATIONS = 11  
Cluster no. 1: ['Financial technology']  
Cluster no. 2: ['Basketball', 'Cricket']  
Cluster no. 3: ['Data Science']  
Cluster no. 4: ['European Central Bank']  
Cluster no. 5: []  
Cluster no. 6: ['Swimming']  
Cluster no. 7: ['Linear algebra']  
Cluster no. 8: []  
Cluster no. 9: ['Artificial intelligence']  
Cluster no. 10: []  
Cluster no. 11: ['International Monetary Fund']  
Cluster no. 12: []
```