Code for implementation of Q10 ACCURACY OBTAINED = 0.847 Confusion matrix is attached below

Q10 Code

October 22, 2021

```
[1]: import numpy as np
     from tensorflow.keras.datasets import mnist
     from typing import List
     import seaborn as sns
     import matplotlib.pyplot as plt
[2]: def load_data():
         (x_train, y_train), (x_test, y_test) = mnist.load_data()
         x train = x train / 255
         x_test = x_test / 255
         x_train = x_train.reshape(x_train.shape[0], -1)
         x_test = x_test.reshape(x_test.shape[0], -1)
         digits = []
         targets = []
         for i in range(10):
             images = x_train[y_train == i]
             digits.append(images[np.random.choice(
                 len(images), 1000, replace=False)])
             targets.append(np.full((1000,), i))
         x_train = np.vstack(digits)
         y_train = np.hstack(targets)
         permutation = np.random.permutation(x_train.shape[0])
         x_train = x_train[permutation]
         y_train = y_train[permutation]
         test_indices = np.random.choice(x_test.shape[0], 1000)
         x_test = x_test[test_indices]
         y_test = y_test[test_indices]
         return (x_train, y_train), (x_test, y_test)
```

```
[3]: def LeastSquares(A, b, reg=1.0):
    return np.linalg.inv((A.T @ A) + reg * np.eye(A.shape[1])) @ (A.T @ b)
```

```
[4]: def confusion_matrix(y_true, y_pred, labels: List = []):
         matrix = np.zeros((len(labels), len(labels)), dtype=int)
         for i in range(len(y_pred)):
             matrix[y_true[i], y_pred[i]] += 1
         return matrix
[5]: def main():
         (x_train, y_train), (x_test, y_test) = load_data()
         classifier = np.zeros((x_train.shape[1], 10))
         for i in range(10):
             b = 2*(y_train == i) - 1
             classifier[:, i] = LeastSquares(x_train, b, reg=1.0)
         y_pred = np.argmax(x_test @ classifier, axis=1).astype(int)
         print(f"Accuracy : {np.mean(y_pred == y_test)}")
         cnf_matrix = confusion_matrix(y_test, y_pred, labels=range(10))
         sns.heatmap(cnf_matrix, annot=True, cmap="Blues", fmt="d")
         plt.title("Confusion Matrix")
         plt.xlabel("Predicted Label")
         plt.ylabel("True Label")
         plt.show()
     if __name__ == "__main__":
         main()
```

Accuracy: 0.847

