

Mean, Var, and Std

HackerRank

mean

The *mean* tool computes the arithmetic mean along the specified axis.

```
import numpy

my_array = numpy.array([ [1, 2], [3, 4] ])

print numpy.mean(my_array, axis = 0)      #Output : [ 2.  3.]
print numpy.mean(my_array, axis = 1)      #Output : [ 1.5  3.5]
print numpy.mean(my_array, axis = None)   #Output : 2.5
print numpy.mean(my_array)                #Output : 2.5
```

By default, the axis is **None**. Therefore, it computes the mean of the flattened array.

var

The *var* tool computes the arithmetic variance along the specified axis.

```
import numpy

my_array = numpy.array([ [1, 2], [3, 4] ])

print numpy.var(my_array, axis = 0)      #Output : [ 1.  1.]
print numpy.var(my_array, axis = 1)      #Output : [ 0.25  0.25]
print numpy.var(my_array, axis = None)   #Output : 1.25
print numpy.var(my_array)                #Output : 1.25
```

By default, the axis is **None**. Therefore, it computes the variance of the flattened array.

std

The *std* tool computes the arithmetic standard deviation along the specified axis.

```
import numpy

my_array = numpy.array([ [1, 2], [3, 4] ])

print numpy.std(my_array, axis = 0)      #Output : [ 1.  1.]
print numpy.std(my_array, axis = 1)      #Output : [ 0.5  0.5]
print numpy.std(my_array, axis = None)   #Output : 1.11803398875
print numpy.std(my_array)                #Output : 1.11803398875
```

By default, the axis is **None**. Therefore, it computes the standard deviation of the flattened array.

Task

You are given a 2-D array of size $N \times M$.
Your task is to find:

1. The mean along axis 1

1/2

2. The var along axis 0
3. The std along axis *None*

Input Format

The first line contains the space separated values of N and M .
The next N lines contains M space separated integers.

Output Format

First, print the *mean*.
Second, print the *var*.
Third, print the *std*.

Sample Input

```
2 2
1 2
3 4
```

Sample Output

```
[ 1.5  3.5]
[ 1.  1.]
1.11803398875
```

2/2

```
Change Theme Language Python 3 ↕ ↺ ⚙ ⋮

1 import numpy
2 x,y=input().split()
3 my_array=numpy.array([list(map(int,input().split())) for _ in range(int(x))])
4 print(numpy.mean(my_array,axis=1))
5 print(numpy.var(my_array,axis=0))
6 print(round(numpy.std(my_array,axis=None),11))
7
8
```