

A**ACCESS**

Journeys and environments that preserve choice

I**INCLUSION**

Participation without profiling or repeated disclosure

W**WELL-BEING**

Practical support without health or distress inference

Accessibility, inclusion, and well-being teams

A complete decision-oriented catalogue of 80 practical questions for a privacy-preserving Talking Abacws service.

FOUNDATIONAL BOUNDARY

The service supports person-owned planning from practical requirements a person chooses to state for a particular purpose and time. It must not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; inspect speech or work content; create productivity or wellness scores; or use health, casework or personal emergency-plan records. All sensing, integrations and analytics are proposed until deployment, mapping, commissioning, permission and current health are independently verified. Current authoritative owners, competent professionals and emergency command always take precedence. The service never certifies accessibility or replaces their decisions.

80 questions | 8 categories | 6 substantive fields per question

Purpose, status and non-negotiable boundaries

PURPOSE

This catalogue frames operational questions that accessibility, inclusion, and well-being teams can ask of a proposed Talking Abacws service. Every record connects a real decision to proportionate evidence, current authority, an explicit method, quantified uncertainty, safe failure and an authorised action. It does not claim that any sensor, integration, feature or analytical capability is deployed.

PERSON-OWNED REQUIREMENTS

Use only practical requirements a person chooses to state for a particular purpose and time. Offer choices, show trade-offs, minimise retention and let the person amend or withdraw information. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need from behaviour, location, sensor data, service use or prior interaction.

EVIDENCE STATUS AND HISTORICAL PLAN

All sensing, integrations and analytics remain proposed until deployment, mapping, commissioning, permission and current health are independently verified. The May 2021 floor plan is historical spatial reference only. It cannot establish current room use, access, services, hazards, routes, features or closures. Every claim exposes coverage, provenance, time, staleness and conflicts.

AUTHORITY AND PROHIBITED USES

Current authoritative owners, incident command and competent professionals always take precedence. The service must not certify accessibility, safety or compliance; replace professional, service-owner or emergency decisions; use health, casework or personal emergency-plan records; identify or track people; inspect speech or work content; promise outcomes; authorise access; or control assets.

Turn a question into a safe operational answer

1 ASK

State the decision and time

2 BOUND

Use chosen requirements only

3 VERIFY

Check owners, permission and health

4 ANALYSE

Apply the declared minimum evidence

5 QUALIFY

Expose uncertainty and conflicts

6 ACT

Take an authorised human decision

FOUR HONEST ANSWER STATES

1 Verified enough

All decision-critical evidence is current and complete for the stated interval.

2 Qualified

Usable only with named gaps, trade-offs and uncertainty.

3 Human check required

A competent on-site or service-owner check is needed before use.

4 Not enough evidence

No conclusion; state the smallest safe check and accountable owner.

MINIMUM EVIDENCE

Minimum evidence is defined per question before data is inspected. A missing critical route link, absent permission, unresolved owner conflict, unknown clock offset or safety restriction cannot be averaged away. A healthy device may still be stale, mapped to the wrong asset or blind to a temporary barrier. Each answer remains inside its decision interval and applies its declared age, coverage and quality thresholds.

SAFE FAILURE

Say what is known, what is unknown, why the gap matters and who can verify it. Offer a verified alternative where one exists. Never fill a gap with a disability inference, historical-plan assumption, unverified sensor reading, generic accessibility claim or promise that an asset or service will work.

How to read every question record

STAKEHOLDER QUESTION

A natural operational question tied to a decision, place and time - not a general accessibility score.

SENSORS AND TELEMETRY

Proposed physical evidence, asset/location coverage, timing, aggregation, acceptance tests, privacy guards and known blind spots.

AUTHORITATIVE SUPPORTING DATA

Current source owners, precedence, effective/observed/retrieved times, permissions, provenance, staleness and conflict handling.

ANALYSIS REQUIRED

Operation type, decision interval, pre-declared minimum evidence, method, quantified uncertainty and a safe failure action.

ANSWER BOUNDARY

What the service must not infer, disclose, promise, certify, authorise or control, and who retains decision authority.

WHY THIS IS USEFUL

The concrete action enabled: publish, verify, fix, relocate, re-time, staff, communicate, escalate, prioritise or withhold a claim.

TIME SEMANTICS

Effective time: when a rule, booking or closure applies. Observed time: when a condition was measured, inspected or acknowledged. Retrieved time: when the service obtained the evidence. A claim is current only when all three support the stated decision interval.

Journeys, arrival and person-owned planning

AI-001

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which step-free route can we publish for the stated journey window, and which critical link still needs an on-site check?

SENSORS AND TELEMETRY	Proposed evidence: door-contact, powered-door, lift-service, gate-state and route-obstruction telemetry. Coverage: every mapped link and decision point between the person-selected arrival point and destination, including the full fallback path. Timing/alignment: on state change with a one-minute heartbeat and five-minute route summaries; use a common clock. Aggregation: by asset and route segment, never by traveller. Quality gate: accept only mapped and commissioned assets with permission, clock skew <=2 seconds, >=95% uptime during the journey window and state age <=5 minutes. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: manual barriers, staff-only dependencies, short-lived queues and unmapped works may remain invisible; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the current access-route register, entrance hours, live closure notices, lift status and destination location (Estates Operations, Security, Space Management and the destination service owner). Corroborating sources: competent route inspections and current incident instructions. Precedence: a live owner restriction or competent on-site inspection outranks schedules, telemetry, generated routes and historical drawings. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a live asset state older than 5 minutes or an inspection outside its stated validity window. Conflict handling: keep disagreement visible and refer it to the relevant Estates or Security duty owner.
ANALYSIS REQUIRED	Operation: critical-path route validation. Decision interval: the requested departure-to-arrival window plus a stated buffer. Minimum evidence: verified start and destination plus current evidence for every critical step-free link and any staffed dependency. Method: exclude unusable links, apply only person-selected requirements, test the route end to end and expose distance, level changes, doors, lifts and fallback points. Quantified uncertainty: report critical-evidence completeness as n/N, plus the count of unverified critical links, oldest evidence age and maximum clock skew; a single unresolved critical link prevents a verified route claim. Safe failure: withhold the route claim, name the exact segment and accountable checker, and offer only an independently verified alternative.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not reveal the person's route or destination beyond the permitted task, promise uninterrupted passage, or treat a sensor-open state as permission to enter. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Estates, Security and the destination owner.
WHY THIS IS USEFUL	Enables the team to publish a defensible route, commission a targeted check, move the activity or contact the person before travel.

AI-002

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which lawful arrival point best meets the person's stated set-down, distance, gradient, shelter, lighting and noise requirements, with trade-offs shown?

SENSORS AND TELEMETRY	Proposed evidence: bay-occupancy, kerb-obstruction, entrance-state, route-state, illuminance, sound-level and local weather telemetry. Coverage: each authorised public set-down, parking and pedestrian arrival zone together with its onward route. Timing/alignment: on change or every 1-5 minutes, using the slowest source age as the option age; use a common clock. Aggregation: by arrival zone and route; no vehicle or visit histories. Quality gate: require mapped zones, commissioned devices, permission, clock skew <=5 seconds, >=90% coverage and no critical source older than 10 minutes. Privacy guard: No number plates, faces, phone identifiers, vehicle tracking or linkage between arrival and building use. Known limits: illegal stopping, off-site disruption, very short obstructions and subjective comfort cannot be proved; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: designated set-down and parking records, entrance status, access-route records and transport service notices (Parking Services, Security, Estates Operations and the relevant transport provider). Corroborating sources: the person-selected criteria and any current traffic, works or weather restriction. Precedence: current legal and operational restrictions outrank availability sensors, static maps, customary practice and historical patterns. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: live status older than 10 minutes, a timetable superseded by a newer version, or a restriction without an effective end time. Conflict handling: keep disagreement visible and refer it to Parking Services or Security, with Estates for the onward route.
ANALYSIS REQUIRED	Operation: person-owned multi-criteria option comparison. Decision interval: the planned drop-off and collection windows. Minimum evidence: at least two current lawful options, or one option plus an explicit statement that no comparison is possible, with verified onward-route evidence. Method: filter by non-negotiable stated requirements, then present trade-offs rather than a hidden composite accessibility score. Quantified uncertainty: report critical-evidence completeness as n/N, plus missing attributes and whether the preferred option changes when non-mandatory criterion weights vary by +/-20%; report a tie when rank is unstable. Safe failure: present the verified facts and owner contacts without naming a single preferred arrival point.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer why a criterion was selected, reserve or guarantee a bay, authorise stopping, or disclose arrival arrangements to unrelated services. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Parking Services, Security, transport operators and Estates.
WHY THIS IS USEFUL	Enables the team to give a choice the person can control and identify when transport, parking, staffing or estate coordination is needed.

Journeys, arrival and person-owned planning

AI-003

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Can today's verified route reasonably be relied on at the expected arrival time, or must we schedule a same-day recheck?

SENSORS AND TELEMETRY	Proposed evidence: time-series state from route doors, lifts, gates, weather-exposed links and anonymous zone-flow counters. Coverage: all critical segments of the verified route and its first viable fallback. Timing/alignment: on change with five-minute summaries; forecast inputs must end no more than 10 minutes before retrieval; use a common clock. Aggregation: as short segment-level histories with no individual trajectories. Quality gate: require verified mapping and permissions, clock skew <=5 seconds, >=95% live-asset uptime and at least 8 comparable historical windows for any forecast. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: telemetry cannot predict every fault, obstruction, queue, staff decision or emergency closure; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: scheduled works, event plans, room moves, entrance hours, lift maintenance and current incident notices (Estates Operations, Events, Timetabling, Security and relevant transport owners). Corroborating sources: live asset states and recent verified route inspections. Precedence: confirmed current restrictions outrank schedules; approved future changes outrank trend-based prediction; owner notices outrank model output. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a live state older than 5 minutes, a schedule without current approval status, or a forecast input window with >10% missing data. Conflict handling: keep disagreement visible and refer it to the owner of the affected route asset or current incident.
ANALYSIS REQUIRED	Operation: time-dependent route feasibility forecast. Decision interval: from retrieval to expected arrival plus a conservative arrival buffer. Minimum evidence: a route verified now, all approved changes overlapping the window, and adequate recent data for every forecasted critical asset. Method: combine deterministic schedules with recent state trends; never convert forecast probability into a present fact. Quantified uncertainty: report critical-evidence completeness as n/N, plus an 80% prediction interval only when >=8 comparable windows and <10% missingness exist; also list planned-change, fault and coverage uncertainty separately. Forecast output must remain explicitly probabilistic and must not overwrite the last verified route state. Safe failure: do not forecast; request same-day verification and retain the last verified route only as historical context.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not tell the person that a future route will work, infer travel tolerance, or use prior journeys to predict their needs or attendance. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person and the operational owners of each route asset.
WHY THIS IS USEFUL	Enables the team to decide whether to confirm the plan, communicate uncertainty, change the arrival time or prepare a fallback before the journey.

AI-004

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which fully verified fallback should we prepare if the planned entrance, lift or corridor fails during the journey window?

SENSORS AND TELEMETRY	Proposed evidence: door, lift, gate, obstruction and anonymous congestion-state telemetry. Coverage: every alternative link that can connect the same arrival point and destination without relying on the failed segment. Timing/alignment: on change with a one-minute heartbeat while disruption is active; use a common clock. Aggregation: by alternative route and dependency; never by affected person. Quality gate: require every physical link to be mapped and commissioned, all critical states <=5 minutes old, clock skew <=2 seconds and >=95% uptime during the disruption. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: staff availability, keys, local permissions and temporary arrangements may not have sensor evidence; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: live closure decisions, the approved alternative-route register, staffed-access arrangements and destination opening status (Estates Operations, Security, Space Management and the destination service owner). Corroborating sources: current asset status and named staff confirmation where the fallback depends on human action. Precedence: the incident or asset owner decides what is open; a staffed confirmation outranks an automated availability indication for staff-dependent links. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a live state older than 5 minutes or a staff confirmation older than the stated disruption interval. Conflict handling: keep disagreement visible and refer it to the incident lead or affected asset owner.
ANALYSIS REQUIRED	Operation: contingency-route search and dependency validation. Decision interval: the active disruption and the person's travel window. Minimum evidence: one end-to-end alternative with every critical link, permission and staffed dependency verified for the whole interval. Method: remove the failed link, test all remaining paths against stated requirements, and rank fallbacks by fewest new dependencies rather than shortest distance alone. Quantified uncertainty: report critical-evidence completeness as n/N, plus unverified dependency count, added distance and time range; if any critical dependency is unverified the fallback is not fully checked. Safe failure: state that no verified fallback is available, escalate for a human route check, and consider relocation or remote participation.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not send a person through a staff-only or restricted route, assume staff will be present, or disclose who is affected by the disruption. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the incident lead, Estates, Security, destination owner and the person.
WHY THIS IS USEFUL	Provides the team with a specific contingency, exposes what it depends on and supports timely relocation, re-timing or staffed assistance.

Journeys, arrival and person-owned planning

AI-005

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

What realistic journey-time range should we communicate, including lift waits, slower links and usable rest points?

SENSORS AND TELEMETRY	Proposed evidence: anonymous segment-flow counts, lift-call and arrival events, door-cycle data and route condition states. Coverage: the planned route, each lift bank used and mapped rest points, excluding private or staff-only areas. Timing/alignment: at 30-second to 5-minute intervals depending on source; align all inputs within 5 seconds; use a common clock. Aggregation: as route-segment distributions and lift-bank wait distributions, with no trip reconstruction. Quality gate: require mapped assets, permission, >=90% usable data, no critical state older than 5 minutes and at least 20 comparable anonymous observations for a numeric range. Privacy guard: No device tracking, face or gait analysis, person-level speed, visit linkage or inference about mobility. Known limits: individual pace, stopping choice, assistance, crowds outside coverage and unusual events remain unknown; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current route and lift status, opening hours and verified rest-point inventory (Estates Operations, Security and Space Management). Corroborating sources: current event schedules and privacy-safe aggregate operational statistics. Precedence: a current closure or inspection outranks historical journey-time data; owner-defined access conditions outrank model estimates. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: live state older than 5 minutes or comparable observations collected before a material route or service change. Conflict handling: keep disagreement visible and refer it to the relevant route or lift owner.
ANALYSIS REQUIRED	Operation: time-range estimation. Decision interval: the person's selected departure and arrival window. Minimum evidence: a verified route plus >=20 comparable anonymous segment/lift observations with <=10% missingness, or a manually checked conservative estimate. Method: sum segment and transfer distributions without assigning a personal walking speed; include a person-selected rest allowance separately. Quantified uncertainty: report critical-evidence completeness as n/N, plus median and 90th-percentile time with an 80% bootstrap interval; list uncovered segments and do not provide a numeric range when data are sparse. Safe failure: give route facts and a conservative planning buffer chosen by the person, or request a human timing check.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer a person's speed, stamina, fatigue, condition or need to rest, and do not present an aggregate time as a personal guarantee. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person and operational route owners.
WHY THIS IS USEFUL	Enables the team to give a transparent planning range, decide whether an earlier arrival is prudent and identify where a timed human check would add value.

AI-006

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which route options avoid only the conditions the person has chosen to state, without turning preferences into a disability profile?

SENSORS AND TELEMETRY	Proposed evidence: route-topology, gradient survey, door/lift state, anonymous density, sound-level, lighting and weather telemetry. Coverage: all candidate public routes between the selected start and destination, including indoor and outdoor alternatives. Timing/alignment: static attributes on controlled version and live conditions every 1-5 minutes; use a common clock. Aggregation: by route segment and condition band, never by person or device. Quality gate: require current mapped geometry from competent survey, commissioned live sensors, permission, clock skew <=5 seconds and all critical state ages <=10 minutes. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: subjective experience, unmapped micro-barriers, transient groups and off-site conditions may not be represented; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current route, gradient and access-feature records plus live closures (Estates Operations, Security and the relevant external-route owner). Corroborating sources: person-selected avoid/prefer criteria, current event plans and weather alerts. Precedence: the person controls the criteria; live restrictions and competent survey outrank sensor-derived condition bands and historical mapping. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: live conditions older than 10 minutes or static attributes after a recorded physical change. Conflict handling: keep disagreement visible and refer it to the owner of the affected route segment.
ANALYSIS REQUIRED	Operation: constraint-based route option generation. Decision interval: the stated journey window. Minimum evidence: one or more end-to-end candidate routes with every non-negotiable criterion evidenced at segment level. Method: filter by stated avoid conditions, then show remaining options with distance, time and evidence gaps; do not create a hidden personal profile. Quantified uncertainty: report critical-evidence completeness as n/N, plus criteria coverage as verified attributes/required attributes and report the maximum age of each live condition; no option is suitable when a non-negotiable attribute is unknown. Safe failure: return no matching verified route, identify the blocking criterion and offer owner verification or a change of destination/time.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer why a condition is avoided, remember it beyond the stated purpose without consent, or describe a route as suitable for a diagnostic group. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Estates, Security and route owners.
WHY THIS IS USEFUL	Supports person-owned choice without profiling and helps the team target the one condition or segment that prevents a usable option.

Journeys, arrival and person-owned planning

AI-007

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which set-down and collection location is lawful, safely connected to the onward route and least likely to create a new barrier?

SENSORS AND TELEMETRY	Proposed evidence: authorised-bay occupancy, kerb and obstruction state, local traffic flow, entrance state, lighting and weather telemetry. Coverage: each designated set-down or collection zone and the complete pedestrian link to a current entrance. Timing/alignment: on change or every minute during the requested window; route inputs every 5 minutes; use a common clock. Aggregation: by zone and time band with no plate, driver or passenger history. Quality gate: require legal zone mapping, commissioned devices, permission, clock skew <=5 seconds, >=90% coverage and last live update <=5 minutes. Privacy guard: No number-plate recognition, faces, vehicle re-identification, booking linkage or passenger inference. Known limits: brief illegal stopping, driver behaviour, roadside hazards beyond coverage and future availability cannot be proved; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current parking and traffic restrictions, designated set-down rules, entrance status and route closure notices (Parking Services, Security, Estates Operations and local transport or highway owners). Corroborating sources: transport booking details supplied by the person only when needed for coordination. Precedence: legal restrictions, traffic management and live owner instructions outrank occupancy telemetry and convenience. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a traffic or bay state older than 5 minutes or a restriction without a confirmed effective period. Conflict handling: keep disagreement visible and refer it to Parking Services, Security or the relevant highway authority.
ANALYSIS REQUIRED	Operation: lawful set-down option validation. Decision interval: the requested arrival and collection windows. Minimum evidence: a lawful zone, current entrance and end-to-end pedestrian route, with any dwell or vehicle-size restriction verified. Method: filter out prohibited or route-disconnected zones and present distance, gradient, shelter and uncertainty as separate facts. Quantified uncertainty: report critical-evidence completeness as n/N, plus zone state age, route gap count and whether availability is observed now or merely permitted; never express future bay availability above observed evidence. Safe failure: provide lawful locations and contact instructions only, or escalate for a managed set-down arrangement.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not guarantee a space, direct unsafe stopping, infer who will travel, or disclose a transport booking beyond those arranging it. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, driver, Parking Services, Security and relevant transport/highway owners.
WHY THIS IS USEFUL	Enables the team to issue lawful, route-connected instructions and identify when a managed arrival or steward is required.

AI-008

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Is the external section of the route sufficiently verified for the forecast light, rain, wind, ice, leaves and surface conditions?

SENSORS AND TELEMETRY	Proposed evidence: illuminance, local temperature, surface-temperature, precipitation, wind, drainage and route-obstruction telemetry. Coverage: all exposed segments, ramps, crossings and entrance approaches on the planned route. Timing/alignment: every 1-5 minutes with weather alerts on change; align route and weather sources within 30 seconds; use a common clock. Aggregation: by exposed segment and hazard type. Quality gate: require mapped exposed segments, commissioned and calibrated devices, permission, >=90% coverage and no critical measurement older than 10 minutes. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: local pooling, black ice, fallen debris, surface damage and shadows may be missed without inspection; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current grounds inspection, gritting and closure records, lighting fault status and severe-weather instructions (Estates Grounds, Security, Health and Safety and relevant external-route owners). Corroborating sources: local weather observations and forecasts. Precedence: a competent inspection or closure decision outranks sensor readings; observed local condition outranks general forecast. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: weather telemetry older than 10 minutes, inspection older than its declared validity or any unresolved lighting fault on a critical segment. Conflict handling: keep disagreement visible and refer it to the grounds or incident duty owner.
ANALYSIS REQUIRED	Operation: weather-and-light route readiness check. Decision interval: the travel window and the preceding treatment or inspection period. Minimum evidence: current evidence for every exposed critical segment plus the latest inspection or treatment status when ice, debris or flooding is plausible. Method: compare measurements with owner-defined operating triggers, overlay confirmed treatments and require visual verification for hazards instruments cannot see. Quantified uncertainty: report critical-evidence completeness as n/N, plus sensor tolerance, spatial coverage gaps and oldest inspection age; one uncovered critical segment prevents a positive readiness statement. Safe failure: do not recommend the exposed route; offer a verified sheltered route, change of time, or immediate competent inspection.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not claim a surface is safe from telemetry alone, infer a person's tolerance of weather or darkness, or overrule a closure or gritting decision. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Grounds, Security, Health and Safety and route owners.
WHY THIS IS USEFUL	Enables the team to decide whether to publish the route, request treatment or inspection, use a sheltered alternative, or warn that evidence is insufficient.

Journeys, arrival and person-owned planning

AI-009

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Can the attendee and their chosen companion, personal assistant, assistance dog or mobility equipment use the same route without avoidable separation?

SENSORS AND TELEMETRY	Proposed evidence: door clear-width status where instrumented, lift-car availability, gate state, route obstruction, queue density and assistance-dog relief-area condition telemetry. Coverage: the entire candidate route, lifts, controlled entrances and any relief stop the person elects to use. Timing/alignment: on change or every 1-5 minutes during the journey window; use a common clock. Aggregation: by asset and route segment, with no person/equipment tracking. Quality gate: require current competent dimensional records, commissioned live devices, permission and all critical live states <=5 minutes old. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: swept-path fit, turning manoeuvres, dog behaviour, temporary furniture and staff practice cannot be established by sensors alone; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current route dimensions, lift capacities, entrance rules, assistance-dog policy and companion access arrangements (Estates Operations, Security, Space Management and the destination service owner). Corroborating sources: the person-stated equipment dimensions or accompaniment requirement, supplied only for this task. Precedence: person-provided dimensions and current operational rules outrank generic equipment assumptions; competent survey outranks historical plan geometry. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a dimensional record after an unverified layout change or live status older than 5 minutes. Conflict handling: keep disagreement visible and refer it to the relevant asset owner and destination service owner.
ANALYSIS REQUIRED	Operation: same-route compatibility and separation-risk check. Decision interval: the planned journey and attendance window. Minimum evidence: verified critical dimensions and rules for every constrained link plus one end-to-end route that keeps the party together. Method: test the stated equipment/envelope against each link, flag assisted or sequential passage, and distinguish physical fit from permission and staff availability. Quantified uncertainty: report critical-evidence completeness as n/N, plus clearance margin with survey tolerance, unresolved-rule count and any link requiring human manoeuvre confirmation; no positive claim if margin is within measurement tolerance. Safe failure: state the exact unresolved link and arrange a competent route trial or alternative entrance/room.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer the relationship or reason for accompaniment, record assistance-dog or equipment use as a personal trait, or separate the party for operational convenience without the person's agreement. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, companion, Security, Estates and destination owner.
WHY THIS IS USEFUL	Enables the team to prevent avoidable separation, test the real constrained link and arrange a route or destination that works for the whole party.

AI-010

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which claims in the proposed journey answer are evidence-complete, which are qualified, and exactly what must a person verify before publication?

SENSORS AND TELEMETRY	Proposed evidence: health, heartbeat, mapping and timestamp telemetry for every data source used in the journey answer. Coverage: all route assets, external conditions, integrations and manual checks contributing to the answer. Timing/alignment: continuously for automated sources and at retrieval for manual sources; use a common clock. Aggregation: as claim-to-source coverage, not a single system-health score. Quality gate: require independent confirmation of deployment, mapping, commissioning, permission, source clock and current health for every critical source. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: a healthy feed can still be mapped wrongly, stale in meaning or blind to a temporary barrier; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the source-owner register, data-sharing permissions, commissioning records, route records and live operational notices (each contributing service owner and the Talking Abacws data steward). Corroborating sources: competent inspection evidence and the generated claim-source trace. Precedence: current owner statements and inspections outrank automated health indicators; a complete provenance chain does not override a live restriction. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: any source beyond its claim-specific age limit, unknown owner and version, missing permission or unresolved mapping conflict. Conflict handling: keep disagreement visible and refer it to the owner of the affected claim, coordinated by the data steward.
ANALYSIS REQUIRED	Operation: claim-level evidence sufficiency assessment. Decision interval: the exact journey decision and publication time. Minimum evidence: a source, owner, permission, time and health result for every critical claim plus explicit evidence for each route link. Method: build a claim-evidence matrix, classify each claim as verified, qualified, human-check or unsupported, and prohibit averaging across critical gaps. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified critical claims/total, unresolved conflict count, oldest evidence age and maximum clock skew; 100% critical-claim coverage is required for a verified journey. Safe failure: publish only qualified facts, name the smallest check and accountable owner, or withhold the journey answer.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not convert technical completeness into an accessibility certificate, conceal conflicts, or ask the person to compensate for an evidence gap by disclosing more personal information. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the data steward, source owners, competent checker and the person.
WHY THIS IS USEFUL	Enables the team to publish only evidence-complete claims, commission the smallest blocking check and keep unsupported journey claims out of guidance.

Entrances, routes, lifts and accessible circulation

AI-011

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which entrance can we currently name as open and step-free, and what staffing or access-control dependencies must be disclosed?

SENSORS AND TELEMETRY	Proposed evidence: entrance-door, powered-operator, gate, intercom and local route-state telemetry. Coverage: every designated public and approved alternative step-free entrance, including the approach and first internal decision point. Timing/alignment: on change with one-minute heartbeat; staff-dependent status confirmed at the start of each duty period; use a common clock. Aggregation: by entrance and dependency. Quality gate: require mapped and commissioned entrance assets, permission, clock skew <=2 seconds, >=95% uptime and no critical state older than 5 minutes. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: door state does not prove lawful access, clear approach, usable hardware or staff response; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current entrance designation, opening hours, access-control rules, staffing rota and closure notices (Security, Estates Operations and the building/service owner). Corroborating sources: competent entrance inspection and live incident instructions. Precedence: Security or incident instructions and competent inspection outrank door telemetry, published hours and historical maps. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: live state older than 5 minutes or staffing confirmation outside its duty period. Conflict handling: keep disagreement visible and refer it to the Security or building duty manager.
ANALYSIS REQUIRED	Operation: entrance availability and dependency check. Decision interval: now or the stated arrival window. Minimum evidence: current open/closed status, verified step-free approach, access permission and any required staff/intercom response for each claimed entrance. Method: classify entrances as independently usable, staff-dependent, qualified or unavailable; do not collapse these states into open/closed. Quantified uncertainty: report critical-evidence completeness as n/N, plus required checks passed/total, state age and unresolved dependency count; any unverified critical dependency prevents an independently usable claim. Safe failure: publish only the verified state and owner contact, or direct the team to a staffed verified alternative.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not treat an open door as authorisation, disclose a person's arrival, or promise that staff or an intercom will respond. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with Security, Estates, the entrance owner and the person.
WHY THIS IS USEFUL	Enables the team to publish accurate entrance instructions, staff a dependency or remove an entrance from guidance until it is checked.

AI-012

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Are the powered doors, push pads and accessible gates on the planned route dependable for the required interval?

SENSORS AND TELEMETRY	Proposed evidence: operator power, command, open/close cycle, obstruction, fault and manual-override telemetry. Coverage: every powered door, push pad and gate on the primary and fallback route. Timing/alignment: on each activation with a one-minute heartbeat and five-minute fault summaries; use a common clock. Aggregation: by asset, retaining fault codes but no user-trigger history beyond short operational aggregation. Quality gate: require commissioning and current maintenance mapping, permission, clock skew <=2 seconds, >=98% event capture and last heartbeat <=2 minutes. Privacy guard: No linkage of activations to cards, phones, faces or individuals; discard raw activation timing after operational aggregation. Known limits: telemetry may not reveal excessive force, poor button reach, intermittent mechanical drag or a blocked approach; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: asset register, maintenance status, fault log, manual-override status and current route closure decisions (Estates Maintenance, Security and the building owner). Corroborating sources: competent functional test and user-reported barrier tickets. Precedence: a competent failed test or owner isolation outranks successful telemetry; maintenance release is required after remedial work. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: heartbeat older than 2 minutes, test older than its owner-defined validity or any unresolved fault affecting the route. Conflict handling: keep disagreement visible and refer it to the Estates maintenance duty owner.
ANALYSIS REQUIRED	Operation: critical-device reliability check. Decision interval: the planned journey interval and the preceding owner-defined observation window. Minimum evidence: current heartbeat, no unresolved critical fault and a competent functional test for each route-critical operator. Method: evaluate required test states separately and inspect recent failure/timeout frequency without predicting a person's experience. Quantified uncertainty: report critical-evidence completeness as n/N, plus tests passed/required, activation failure rate with a 95% Wilson interval when >=20 cycles exist, and oldest test age; no rate claim for sparse data. Safe failure: remove the device from the verified route, arrange a physical test or publish a checked manual/staffed alternative.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer who activated a device, state that a door is accessible for every person, or remotely cycle equipment as a test while someone may be using it. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with Estates Maintenance, Security and the person.
WHY THIS IS USEFUL	Supports targeted remedial work, route substitution and honest communication about a device that is working, staff-dependent or not verified.

Entrances, routes, lifts and accessible circulation

AI-013

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Do current clearances at thresholds, door approaches and corridors support the stated passage envelope after furniture, deliveries and queues are considered?

SENSORS AND TELEMETRY	Proposed evidence: door-position, fixed clearance, non-imaging obstruction, pressure-mat or anonymous zone-density telemetry where proportionate. Coverage: critical thresholds, turning points and corridor pinch points on the intended route. Timing/alignment: on change or every minute during busy periods; fixed dimensions on controlled version; use a common clock. Aggregation: by zone and obstruction state, with no body shape, identity or trajectory. Quality gate: require competent dimensional mapping, commissioned privacy assessment, permission, >=90% live coverage and last observation <=5 minutes. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: low objects, protrusions, moveable furniture and brief blockages may be missed; sensors cannot prove manoeuvrability; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current route-clearance standard, room/corridor setup plan, delivery schedule and live obstruction reports (Estates Operations, Security, Cleaning, Logistics and the local space owner). Corroborating sources: competent on-site clearance inspection. Precedence: a current physical inspection or closure decision outranks occupancy or obstruction telemetry and planned layouts. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: live state older than 5 minutes or dimensional/layout records after an unverified change. Conflict handling: keep disagreement visible and refer it to the local Estates or Security duty owner.
ANALYSIS REQUIRED	Operation: pinch-point clearance validation. Decision interval: the intended passage window. Minimum evidence: current evidence for every known pinch point and a competent check wherever the sensor cannot establish usable clear width or turning space. Method: compare verified dimensions and current obstruction state with the person-stated equipment envelope; distinguish clear, partly observed and unchecked. Quantified uncertainty: report critical-evidence completeness as n/N, plus measured clearance with survey tolerance, checked pinch points/total and oldest live observation; do not claim pass when margin is within tolerance. Safe failure: request removal or human measurement, close the link in the route model, and offer a verified alternative.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not estimate a person's body or equipment dimensions from images or behaviour, identify people in a queue, or authorise moving safety-critical items. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Estates, Security and local space owner.
WHY THIS IS USEFUL	Enables the team to remove a specific obstruction, adjust deliveries or route guidance, and avoid publishing a path that is only clear on paper.

AI-014

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which lift is verified to serve the required floors and accommodate the person-stated space or equipment envelope throughout the visit?

SENSORS AND TELEMETRY	Proposed evidence: lift service, floor availability, car position, door, fault, load-band and call/wait telemetry. Coverage: every lift bank serving the origin, destination and viable fallback route. Timing/alignment: on state change with one-minute heartbeat; wait data aggregated in five-minute bands; use a common clock. Aggregation: by lift car/bank and floor, with no access-card or passenger trace. Quality gate: require asset-to-floor mapping, commissioning, permission, clock skew <=2 seconds, >=98% service-state uptime and state age <=2 minutes. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: load bands cannot prove available manoeuvring space, and telemetry cannot guarantee the next journey; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: lift asset register, current service/isolation status, served floors, car dimensions, load limits and maintenance release (Estates Maintenance and the lift service contractor). Corroborating sources: Security restrictions, evacuation rules and the person-stated equipment envelope. Precedence: maintenance isolation, competent inspection and current emergency instruction outrank BMS status or schedule. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: service state older than 2 minutes, dimensions after an unverified refurbishment, or unresolved fault code. Conflict handling: keep disagreement visible and refer it to the Estates lift duty owner or competent contractor.
ANALYSIS REQUIRED	Operation: lift compatibility and availability validation. Decision interval: the outward and return journey windows. Minimum evidence: verified served floors, current service state, current dimensions/capacity and one fallback route if the lift is critical. Method: filter lifts by route and stated envelope, then separate physical fit, operational status, wait estimate and emergency restrictions. Quantified uncertainty: report critical-evidence completeness as n/N, plus dimension clearance margin with survey tolerance, state age and number of independent lift options; no fit claim when margin <= measurement tolerance. Safe failure: withhold the lift option, arrange a competent measurement or route trial, and consider another entrance, floor or delivery format.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer equipment type or disability, promise lift availability, treat load telemetry as permission, or remotely call/hold a lift for an identified person. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Estates Maintenance, lift contractor and Security.
WHY THIS IS USEFUL	Enables the team to choose a lift-backed route, expose single points of failure and relocate an activity before the journey becomes impossible.

Entrances, routes, lifts and accessible circulation

AI-015

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

When demand peaks, will lift waiting create an avoidable participation delay, and which operational mitigation should be prepared?

SENSORS AND TELEMETRY	Proposed evidence: lift call, arrival, door-cycle, service and anonymous load-band telemetry plus nearby zone-density counts. Coverage: the relevant lift bank, waiting areas and any alternative lift/route. Timing/alignment: event-level capture with 30-second aggregation; clocks aligned within 2 seconds; use a common clock. Aggregation: as wait and queue distributions by time band, never as passenger journeys. Quality gate: require commissioned sources, permission, >=95% event capture, <10% missingness and >=8 comparable busy windows for a forecast. Privacy guard: No face, card, phone or person tracking; do not retain individual call sequences. Known limits: individual priority, group behaviour, queue etiquette and sudden faults remain unknown; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current timetable/event schedule, lift service status and approved crowd-management plan (Timetabling, Events, Estates Operations and Security). Corroborating sources: privacy-safe historical wait distributions and steward observations. Precedence: a live incident, owner restriction or changed event plan outranks historical patterns and forecasts. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: live service state older than 2 minutes or comparison data collected before a material timetable, lift or route change. Conflict handling: keep disagreement visible and refer it to the event lead with Estates and Security.
ANALYSIS REQUIRED	Operation: busy-period lift-wait forecast and contingency comparison. Decision interval: the planned arrival/departure bands around the class change or event. Minimum evidence: current lift status, current demand schedule and >=8 comparable windows with <=10% missing data. Method: estimate bank-level wait distributions, compare an alternative route and include transfer time without assigning priority to an inferred user group. Quantified uncertainty: report critical-evidence completeness as n/N, plus median and 90th-percentile wait with an 80% prediction interval; if the interval width exceeds the median, label the forecast weak. Safe failure: do not give a wait estimate; advise an earlier window chosen by the person, a staffed plan or a verified alternative lift/route.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not identify who is waiting, infer mobility or distress from queue behaviour, reserve priority, or promise a waiting time. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, event lead, Estates and Security.
WHY THIS IS USEFUL	Enables the team to re-time arrivals, manage lift priority under owner policy, provide a staffed fallback or relocate the activity before unequal delay excludes participation.

AI-016

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Is the step-free route continuous through every controlled door, gate, turnstile and card-access boundary for this authorised visit?

SENSORS AND TELEMETRY	Proposed evidence: door/gate state, controller heartbeat, reader fault and intercom telemetry. Coverage: every controlled link on the primary and fallback route, including boundary transitions between services. Timing/alignment: on state change with one-minute heartbeat; access-rule snapshots on every approved change; use a common clock. Aggregation: by asset and rule set, without logging individual credentials or access attempts. Quality gate: require verified asset/rule mapping, permission, clock skew <=2 seconds, >=98% controller heartbeat and state age <=2 minutes. Privacy guard: No cardholder identity, credential history, phone identifier or person-level access pattern. Known limits: a healthy controller does not prove that a specific credential is authorised or that staff will grant an exception; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current access-control policy, zone permissions, visitor process, staffed-entry arrangements and closure notices (Security, the destination service owner and Estates Operations). Corroborating sources: the person's confirmed authorised visit or role, used only for this decision. Precedence: authoritative access rules and Security instructions outrank controller telemetry and route topology; no route output can grant permission. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: rule snapshot after a superseding change, controller state older than 2 minutes or unresolved owner conflict. Conflict handling: keep disagreement visible and refer it to Security or the access-zone owner.
ANALYSIS REQUIRED	Operation: permission-aware route continuity check. Decision interval: the authorised visit and travel window. Minimum evidence: an approved purpose/visitor route, current rule for every controlled link and a verified process for any staffed dependency. Method: separate physical step-free continuity from access permission; exclude unauthorised links even if physically open. Quantified uncertainty: report critical-evidence completeness as n/N, plus controlled links verified/total, rule version and unresolved owner count; any unknown or unauthorised critical link breaks continuity. Safe failure: return no authorised continuous route, name the blocking zone and refer to Security or the destination owner for an alternative process.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not reveal access rights, test a person's credential, infer role or status, grant access, or suggest tailgating or bypassing a control. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with Security, the destination service owner, Estates and the person.
WHY THIS IS USEFUL	Prevents a technically step-free route from failing at an access boundary and gives the team a lawful escalation point before travel.

Entrances, routes, lifts and accessible circulation

AI-017

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which measured gradient, crossfall, turning, threshold or door-force constraints materially affect the proposed route?

SENSORS AND TELEMETRY	Proposed evidence: competent dimensional survey data, door-force test results and live door/obstruction state. Coverage: every known geometric pinch point on the primary and fallback route. Timing/alignment: survey on controlled version; door/obstruction state on change or every 5 minutes; use a common clock. Aggregation: by route segment and constraint type. Quality gate: require current survey provenance, instrument calibration, mapped asset IDs, permission and re-survey after any relevant works or layout change. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: geometry cannot represent every technique, surface friction, temporary load or person-specific experience; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current competent access survey, asset dimensions, door-force inspection and approved route records (Estates Compliance, Estates Maintenance and the relevant route owner). Corroborating sources: live obstruction reports and the person-stated equipment envelope when voluntarily supplied. Precedence: competent current measurement outranks model geometry, design drawings and the May 2021 plan; live closure outranks all dimensional analysis. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a measurement after an unverified physical change or outside the survey owner's validity period. Conflict handling: keep disagreement visible and refer it to the competent survey owner or Estates Compliance lead.
ANALYSIS REQUIRED	Operation: constraint inventory and route-envelope comparison. Decision interval: the current route configuration and intended journey. Minimum evidence: current measured geometry/force for each known pinch point plus confirmation that no relevant change has occurred. Method: list constraints individually, compare only with person-stated dimensions or preferences, and avoid a single accessibility score. Quantified uncertainty: report critical-evidence completeness as n/N, plus measurement value, instrument tolerance and clearance/force margin; flag any margin within twice the measurement tolerance as requiring physical trial. Safe failure: label the constraint unverified, request competent measurement or route trial, and remove it from an assured route.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer body size, strength, reach or mobility from the route choice, and do not declare a constraint acceptable for every person. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, competent surveyor and Estates route owner.
WHY THIS IS USEFUL	Provides the team with an exact feature to modify, inspect or route around instead of relying on generic labels such as accessible corridor.

AI-018

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Are weather, drainage, leaves, works or surface defects creating a current barrier on external paths, ramps or entrance approaches?

SENSORS AND TELEMETRY	Proposed evidence: surface temperature, precipitation, drainage level, illuminance, works-barrier and route-obstruction telemetry. Coverage: all external step-free links, ramps, crossings and entrance approaches used by published routes. Timing/alignment: every 1-5 minutes and on works/closure changes; timestamps aligned within 30 seconds; use a common clock. Aggregation: by segment and hazard type. Quality gate: require mapped segments, calibrated devices, permission, >=90% usable coverage and no critical live source older than 10 minutes. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: black ice, local pooling, loose materials, potholes and barrier placement may require direct inspection; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current grounds inspections, works permits, gritting/treatment logs, defect reports and closure notices (Estates Grounds, Estates Projects, Security and Health and Safety). Corroborating sources: local weather observations and competent site inspection. Precedence: a competent site inspection, works exclusion or closure decision outranks telemetry and general weather data. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: weather/route state older than 10 minutes or inspection/treatment evidence beyond its declared validity. Conflict handling: keep disagreement visible and refer it to the Grounds or incident duty owner.
ANALYSIS REQUIRED	Operation: external-segment hazard status check. Decision interval: now and the next stated journey interval. Minimum evidence: current evidence for every exposed critical segment and a competent inspection for hazards that cannot be sensed reliably. Method: apply owner-defined hazard triggers, link treatments and defects to segments, and keep observed, forecast and inspected states separate. Quantified uncertainty: report critical-evidence completeness as n/N, plus covered segments/total, oldest observation, sensor tolerance and unresolved hazard count; no clear claim with any uncovered critical segment. Safe failure: close the segment in guidance, request inspection/treatment and offer only a verified alternative.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not declare a route safe from remote data alone, infer a person's risk tolerance, or overrule a works or weather closure. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with Grounds, Projects, Security, Health and Safety and the person.
WHY THIS IS USEFUL	Enables the team to remove a compromised route from guidance, request treatment or remedial work, and communicate a checked alternative.

Entrances, routes, lifts and accessible circulation

AI-019

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Can the person move between all required locations without crossing a restricted zone or depending on an unverified route link?

SENSORS AND TELEMETRY	Proposed evidence: door, lift, gate, cordon and route-obstruction state telemetry. Coverage: all inter-floor and inter-wing links, including crossover points and fallback routes. Timing/alignment: on state change with one-minute heartbeat; temporary-zone maps on every authorised update; use a common clock. Aggregation: by segment and restriction zone, with no traveller tracking. Quality gate: require current zone mapping, commissioned sources, permission, clock skew <=2 seconds, >=95% uptime and state age <=5 minutes. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: informal cordons, moving work fronts and staff instructions may not appear immediately in telemetry; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current closure/cordon decisions, works boundaries, access-control rules and lift/door status (Security, Estates Projects, Estates Operations and the affected service owner). Corroborating sources: incident instructions and competent on-site confirmation. Precedence: incident command or the owner of a restricted area outranks route engines, schedules, sensor states and historical floor plans. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a restriction map without a current effective period or live state older than 5 minutes. Conflict handling: keep disagreement visible and refer it to the incident lead or restricted-area owner.
ANALYSIS REQUIRED	Operation: restriction-aware connectivity test. Decision interval: the travel window and any overlapping works/incident period. Minimum evidence: current restriction geometry and authority plus verified status for every link in one end-to-end route. Method: remove restricted zones and unverified links from the graph, then test connectivity and expose any single point of failure. Quantified uncertainty: report critical-evidence completeness as n/N, plus viable route count, unresolved link count and maximum evidence age; zero independently verified routes means no continuity claim. Safe failure: state that inter-area travel is not verified, contact the restriction owner and consider relocation or remote participation.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not reveal security-sensitive restricted-area detail beyond what is needed for safe routing, infer who intends to enter, or suggest bypassing a cordon. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with incident command, Security, Estates Projects and the person.
WHY THIS IS USEFUL	Enables the team to avoid routing through an active restriction and decide early whether to change the room, timing or delivery mode.

AI-020

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which circulation bottlenecks cause materially unequal delay or discomfort, when do they occur, and what proportionate operating change should be tested?

SENSORS AND TELEMETRY	Proposed evidence: anonymous zone-entry/exit counts, lift/door cycle times and density bands from non-identifying counters. Coverage: predefined public pinch points, waiting areas and alternative routes; no continuous person path. Timing/alignment: 30-second counts aggregated into five-minute bands and retained only as privacy-safe summaries; use a common clock. Aggregation: by zone, direction and time band with small-cell suppression. Quality gate: require privacy assessment, mapped zones, commissioning, permission, clock skew <=5 seconds, >=90% count coverage and suppression below 10 observations. Privacy guard: No faces, Wi-Fi/Bluetooth identifiers, re-identification, gait, demographic classification or person-level dwell. Known limits: density does not reveal why people wait, individual impact, queue fairness or conditions outside instrumented zones; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current timetable, event plan, route capacity/management plan and live restrictions (Timetabling, Events, Security, Estates Operations and the local service owner). Corroborating sources: privacy-safe aggregate counts and structured steward observations. Precedence: a current incident or steward instruction outranks historical patterns; counts inform but do not authorise crowd-control measures. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a five-minute band with <90% source coverage or data collected before a material layout/timetable change. Conflict handling: keep disagreement visible and refer it to the event or building duty owner with Security.
ANALYSIS REQUIRED	Operation: aggregate bottleneck detection and intervention comparison. Decision interval: selected class-change, arrival or event windows. Minimum evidence: >=8 comparable windows, >=90% count coverage, current route configuration and a verified alternative or management option. Method: compare zone flow, dwell and door/lift throughput by time band; evaluate re-timing, one-way flow, stewarding or route alternatives without identifying people. Quantified uncertainty: report critical-evidence completeness as n/N, plus median and 90th-percentile density/delay with 95% bootstrap intervals and suppress cells <10; distinguish recurring from one-off conditions. Safe failure: publish no quantitative pattern; use direct steward observation and trial a reversible operational change under owner control.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer disability, anxiety, distress, behaviour or protected characteristics from movement; rank individuals; or use counts to deny access. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the event/building owner, Security, Estates and affected people.
WHY THIS IS USEFUL	Enables the team to alter stewarding, release timing, furniture or route direction at the specific bottleneck, then test whether unequal delay falls.

Rooms, seating, participation and adjustments

AI-021

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Before confirming the booking, which room features are currently verified against the requirements the person has chosen to state?

SENSORS AND TELEMETRY	Proposed evidence: room-door, lift/route, environmental, AV-heartbeat and movable-equipment status telemetry, supplemented by a structured pre-use inspection. Coverage: the booked room, its step-free route, entrance, seating zones, teaching position and any required equipment. Timing/alignment: live asset state every 1-5 minutes; room inspection within the owner-defined pre-use window; inventory on controlled version; use a common clock. Aggregation: by room feature and dependency, never by attendee. Quality gate: require current room/asset mapping, commissioning, permission, live-source age <=10 minutes and a signed inspection for any critical feature not directly observable. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: sensors cannot prove sightlines, manoeuvring, participation quality, furniture setup or suitability for a particular person; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current room inventory, booking, approved layout, access-route status and service-owner feature records (Space Management, Timetabling, Estates Operations, IT/AV and the room owner). Corroborating sources: the person-selected requirements and a current pre-use inspection. Precedence: the latest competent room inspection and live closure/status outrank booking descriptions, equipment catalogues and historical plans. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a booking or inventory superseded by a room change, a live state older than 10 minutes or an inspection outside its declared validity. Conflict handling: keep disagreement visible and refer it to the room owner, with Estates or IT/AV for their assets.
ANALYSIS REQUIRED	Operation: requirement-to-feature verification matrix. Decision interval: booking confirmation through the planned session. Minimum evidence: evidence for every non-negotiable stated requirement, the step-free route and each critical equipment dependency. Method: map each stated requirement to an observed feature, authority and time; classify verified, qualified, human-check or unsupported without producing a generic room accessibility score. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified non-negotiable requirements/total, oldest evidence age and unresolved conflicts; all non-negotiable requirements must be verified for a positive match. Safe failure: withhold the match, commission the missing room check, offer a verified alternative or ask the person whether a trade-off is acceptable.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer why a feature is required, disclose the requirement to unrelated staff, or describe the room as universally accessible or suitable. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, room owner, Space Management, Estates and IT/AV.
WHY THIS IS USEFUL	Enables the team to confirm, inspect or change a room before the person arrives and to communicate precisely which feature is still uncertain.

AI-022

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Does the seating plan offer genuine integrated choice for a wheelchair user and chosen companion, rather than a single isolated position?

SENSORS AND TELEMETRY	Proposed evidence: no person-identifying sensing is justified; proposed room-door, movable-seat inventory, setup-completion and anonymous zone-occupancy telemetry may support a physical inspection. Coverage: all designated and flexible wheelchair/companion seating positions, adjacent circulation and sightline zones in the room. Timing/alignment: setup status on every room reset; anonymous occupancy in five-minute bands only when privacy-approved; use a common clock. Aggregation: by seating zone with small-cell suppression and no individual seat history. Quality gate: require current layout version, mapped furniture, permission, a competent pre-use inspection and suppression of any zone count below 10. Privacy guard: No seat-level identity, camera, pressure pattern, reservation history linked to a person or inference about wheelchair use. Known limits: telemetry cannot establish social inclusion, actual preference, sightline quality or whether furniture has been positioned well; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current room layout, seat inventory, booking/setup instruction and companion-seat policy (Space Management, the room owner, Events/Timetabling and Estates). Corroborating sources: the person's chosen seating preferences and a current physical setup check. Precedence: the person's choice and observed setup outrank nominal designated positions, room photographs and default layouts. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a layout after any unverified reset or an inspection outside the session setup window. Conflict handling: keep disagreement visible and refer it to the room or event owner.
ANALYSIS REQUIRED	Operation: integrated-seating option validation. Decision interval: the room setup and session interval. Minimum evidence: at least two verified positions where feasible, or an explicit explanation of the physical constraint, with adjacent companion seating and route/sightline checks. Method: compare positions by person-selected criteria and test group integration, circulation and companion adjacency separately. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified positions/available positions, unresolved setup checks and clearance/sightline measurement tolerance; do not claim choice when only one unchecked position exists. Safe failure: arrange a room reset or alternative room and let the person choose from the verified options.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not label or reserve a person-visible special seat without agreement, infer wheelchair use, expose the reason for the setup or force separation as the default. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, room/event owner, Space Management and Estates.
WHY THIS IS USEFUL	Enables the team to protect choice and group participation, not merely provide a nominal space at the edge of the room.

Rooms, seating, participation and adjustments

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

AI-023

Are tables, seats, lectern and controls set up and adjustable for the stated reach, height, transfer-space and equipment requirements?

SENSORS AND TELEMETRY

Proposed evidence: equipment power, actuator position/fault, lock state and asset-presence telemetry, plus competent setup measurements. Coverage: each required adjustable table, seat, lectern, control panel and transfer zone in the booked room. Timing/alignment: on activation with a five-minute heartbeat; setup measurement within the pre-use window; use a common clock. Aggregation: by asset and adjustment range, with no record of who changed it. Quality gate: require asset mapping, commissioning, permission, current maintenance release, state age <=5 minutes and calibrated setup measurements for critical dimensions. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: motor telemetry cannot prove reach, operating force, stability, clear approach or suitability for a particular technique; missing, stale or unhealthy evidence is unknown.

AUTHORITATIVE SUPPORTING DATA

Owners and primary records: current equipment specification, maintenance status, room layout and booking/setup task (Estates Maintenance, Space Management, IT/AV where applicable and the room owner). Corroborating sources: the person-stated dimensional/operational requirements and a competent pre-use check. Precedence: observed setup and maintenance release outrank catalogue specification and nominal room inventory. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: equipment state older than 5 minutes, specification after a modification or setup evidence outside the session window. Conflict handling: keep disagreement visible and refer it to the equipment owner or Estates maintenance duty owner.

ANALYSIS REQUIRED

Operation: equipment-range and setup validation. Decision interval: the setup period and planned activity. Minimum evidence: verified adjustment range, clear approach/transfer space, operating condition and completion of any agreed setup task for every critical asset. Method: compare person-stated requirements with measured range and clearance, test function, and keep physical capability separate from room booking and training needs. Quantified uncertainty: report critical-evidence completeness as n/N, plus range/clearance margin with measurement tolerance, tests passed/required and oldest test age; a margin within tolerance requires direct trial. Safe failure: mark the asset unverified, provide a checked portable alternative, change the position/room or arrange a competent trial.

ANSWER BOUNDARY

Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer reach, strength, stature or diagnosis, disclose the reason for an adjustment, or remotely move equipment while it may be occupied. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, equipment owner, Estates, Space Management and IT/AV.

WHY THIS IS USEFUL

Enables the team to complete a concrete setup task, source an alternative or change the room before participation is compromised.

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

AI-024

Is the room's hearing-enhancement system present, powered, recently function-tested and connected to the planned audio path?

SENSORS AND TELEMETRY

Proposed evidence: hearing-loop or infrared/radio system power, amplifier fault, field-monitor and AV-source heartbeat telemetry. Coverage: the audience and speaking areas specified for the room, including any overflow or remote feed. Timing/alignment: continuous heartbeat during the session with a competent field/function test before use; use a common clock. Aggregation: by system zone and test point; no recording of speech or listener devices. Quality gate: require commissioned equipment mapping, current maintenance release, permission, clock skew <=2 seconds, heartbeat age <=2 minutes and a dated competent test. Privacy guard: No audio content, listener identity, hearing-device detection or connection history. Known limits: power and field telemetry cannot prove intelligibility, individual compatibility, microphone practice or absence of interference; missing, stale or unhealthy evidence is unknown.

AUTHORITATIVE SUPPORTING DATA

Owners and primary records: current assistive-listening inventory, coverage design, maintenance/test record and planned AV configuration (IT/AV, Estates where fixed infrastructure is involved and the room/event owner). Corroborating sources: competent field-strength/function test and current fault tickets. Precedence: a competent failed test or maintenance isolation outranks a healthy heartbeat; the planned audio configuration must match the tested configuration. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: heartbeat older than 2 minutes, test outside the owner-defined validity or configuration changed after testing. Conflict handling: keep disagreement visible and refer it to the IT/AV duty owner or competent maintainer.

ANALYSIS REQUIRED

Operation: assistive-listening readiness assessment. Decision interval: setup through the end of the planned session. Minimum evidence: power/heartbeat, current fault status, a competent test across required zones and confirmation that microphones/source routing match the test. Method: evaluate each required test point and dependency separately; do not convert equipment presence into a usable-system claim. Quantified uncertainty: report critical-evidence completeness as n/N, plus test points passed/required, measured range with instrument tolerance and test age; any failed required zone makes the system not verified for that area. Safe failure: arrange a retest or portable alternative, change seating/room, and communicate the limitation before the session.

ANSWER BOUNDARY

Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer hearing status, detect personal devices, record audio, promise intelligibility or describe the system as suitable for every listener. A device heartbeat or inventory entry is not a successful listening test and is not evidence of individual benefit. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, IT/AV, competent maintainer and event/room owner.

WHY THIS IS USEFUL

Enables the team to distinguish installed from ready, fix the actual signal chain and provide a verified alternative before the session starts.

Rooms, seating, participation and adjustments

AI-025

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Are microphones, captions, recording and remote-participation tools ready for the actual speaking, question and group-work pattern?

SENSORS AND TELEMETRY	Proposed evidence: microphone, DSP, caption-service, camera-control, network-path and platform heartbeat/fault telemetry. Coverage: all planned speaking positions, audience microphones, caption displays and remote endpoints under institutional control. Timing/alignment: continuous heartbeat from setup to session end; synthetic test before use; use a common clock. Aggregation: by service component and room zone, without retaining meeting content. Quality gate: require current configuration, permissions, clock skew <=2 seconds, >=98% service heartbeat, network test in the setup window and an end-to-end rehearsal for critical sessions. Privacy guard: No speech transcription for monitoring, content inspection, speaker identification or participant analytics beyond the authorised service. Known limits: heartbeats cannot prove readable captions, speaker practice, remote user conditions, consent or interaction quality; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current event/teaching plan, AV configuration, caption booking, platform status and recording/consent settings (the session owner, IT/AV, Learning Technology and any contracted caption provider). Corroborating sources: an end-to-end test and the person-selected participation/format requirements. Precedence: the session owner's approved plan, current provider confirmation and live service status outrank generic room capability. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: service status older than 5 minutes, booking without provider confirmation or configuration changed after test. Conflict handling: keep disagreement visible and refer it to the session owner with IT/AV or Learning Technology.
ANALYSIS REQUIRED	Operation: multi-service participation-readiness check. Decision interval: setup, session and any scheduled breakouts. Minimum evidence: verified signal path for every planned interaction mode, confirmed caption/remote service and a tested fallback for each critical dependency. Method: run scripted end-to-end tests for presenter, audience and remote interaction; map failures to the exact component and planned activity. Quantified uncertainty: report critical-evidence completeness as n/N, plus test cases passed/required, network latency/loss range and service-state age; any failed critical interaction prevents a ready claim. Safe failure: simplify the interaction plan, provide a tested alternative channel, delay the session start or relocate with owner approval.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not inspect speech or work content, infer communication needs, enable recording without authority/consent, or promise caption accuracy or uninterrupted remote access. Do not transcribe, inspect or retain speech content merely to prove that a caption or microphone service was available. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, session owner, IT/AV, Learning Technology and provider.
WHY THIS IS USEFUL	Enables the team to test the actual participation pattern, not just equipment presence, and to deploy a known fallback before attendees are excluded.

AI-026

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which verified seats should we offer for the person's stated sightline, aisle, door-distance, lighting and sound preferences?

SENSORS AND TELEMETRY	Proposed evidence: room layout, luminaire state, illuminance, sound-level, display/speaker state and anonymous zone-occupancy telemetry. Coverage: all selectable seating zones and their routes, sightlines and nearby exits/doors. Timing/alignment: environmental data every 1-5 minutes; setup and sightline checks before the session; occupancy in five-minute privacy-safe bands; use a common clock. Aggregation: by seating zone with small-cell suppression. Quality gate: require current layout and AV configuration, calibrated sensors, permission, >=90% coverage, no environmental reading older than 10 minutes and physical verification of critical sightlines. Privacy guard: No seat-level identity, person tracking, inferred sensory profile or history of preferred locations. Known limits: individual perception, seat comfort, late arrivals and movable obstructions cannot be fully sensed; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current room layout, seat availability/booking rules, display and speaker configuration and route status (the room/session owner, Space Management, IT/AV and Estates). Corroborating sources: the person-selected preferences and a current setup inspection. Precedence: the person controls the criteria; observed setup and live restrictions outrank default plans and historical room descriptions. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: layout after an unverified reset, live readings older than 10 minutes or availability not confirmed for the session. Conflict handling: keep disagreement visible and refer it to the room or session owner.
ANALYSIS REQUIRED	Operation: person-owned seating option comparison. Decision interval: the room setup and session interval. Minimum evidence: at least two verified options when physically possible, with evidence for each non-negotiable criterion and the route to the seat. Method: filter by non-negotiable criteria, present trade-offs by zone and let the person choose; never infer or persist a sensory profile. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified criteria/required criteria for each option and rank stability under +/-20% weight changes for preferences; unstable ranks are shown as equal choices. Safe failure: offer only the verified facts, request a targeted seat check or change the room/setup.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer impairment, distress or social preference, disclose the selected seat unnecessarily, or designate a conspicuous special area without agreement. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person and the room/session owner.
WHY THIS IS USEFUL	Supports meaningful choice and lets the team adjust layout, lighting, audio or room selection rather than assigning a generic accessible seat.

Rooms, seating, participation and adjustments

AI-027

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Has any room reset, furniture movement or temporary equipment reduced critical circulation, turning or transfer space?

SENSORS AND TELEMETRY	Proposed evidence: asset-tag presence, door state, non-imaging obstruction telemetry and setup-completion signals, supported by a physical clearance inspection. Coverage: entrance approaches, aisles, turning zones, wheelchair spaces, transfer zones and presenter positions in the room. Timing/alignment: on every setup/reset and within the pre-use inspection window; use a common clock. Aggregation: by room zone and layout version. Quality gate: require a controlled layout baseline, mapped movable assets, permission and a competent signed clearance check after any material reset. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: tags and obstruction sensors may miss untagged furniture, cable hazards, low protrusions or actual manoeuvring quality; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: approved room layout, setup request, furniture inventory and current booking configuration (Space Management, Events/Timetabling, Estates and the room owner). Corroborating sources: pre-use clearance inspection and current barrier reports. Precedence: observed room setup outranks the planned layout, asset-tag list and the May 2021 historical plan. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: any layout record after an unverified move or inspection outside the setup validity window. Conflict handling: keep disagreement visible and refer it to the room/event owner with Estates or Space Management.
ANALYSIS REQUIRED	Operation: layout-change detection and clearance verification. Decision interval: from room setup through the session. Minimum evidence: the current layout version, evidence of every material asset move and a competent check of all critical circulation/transfer zones. Method: compare observed setup with the approved baseline, list changed zones and validate clearances rather than treating tag agreement as proof. Quantified uncertainty: report critical-evidence completeness as n/N, plus matched movable assets/expected, critical zones checked/total and clearance margin with survey tolerance; any uninspected changed critical zone remains unknown. Safe failure: stop publication of the layout claim, reset or inspect the room, and provide another verified space if needed.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not use images to identify occupants, infer who needs transfer space, or move equipment that is safety-critical or in active use without owner authority. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the room/event owner, Space Management and Estates.
WHY THIS IS USEFUL	Enables the team to catch a real setup regression before arrival and assign the exact reset or clearance task to the responsible owner.

AI-028

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

If the booked room fails a stated requirement, which available alternative provides the best verified match with the fewest new dependencies?

SENSORS AND TELEMETRY	Proposed evidence: room, route, lift, environmental and AV/equipment status telemetry. Coverage: all candidate rooms in the permitted search area plus their complete arrival routes. Timing/alignment: live status every 1-10 minutes according to source; inventory and bookings on controlled change; use a common clock. Aggregation: by room-feature and route dependency, never by attendee. Quality gate: require current room/route mapping, permission, verified booking status, all critical live sources within their age limits and a pre-use check for the selected room. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: availability can change, subjective fit remains person-owned and uninstrumented features need inspection; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current room bookings, room/feature inventory, route status, access rules and service-owner equipment records (Space Management, Timetabling, Estates, IT/AV and candidate room owners). Corroborating sources: the person-selected requirements and any approved adjustment task. Precedence: current booking/closure and competent inspection outrank inventory descriptions, model scores and historical plans. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: booking after any change, live status beyond its source-specific limit or unverified feature inventory. Conflict handling: keep disagreement visible and refer it to Space Management or Timetabling, with the relevant feature owner.
ANALYSIS REQUIRED	Operation: constraint-based alternative-room selection. Decision interval: the booking decision through the planned session. Minimum evidence: at least one available candidate with every non-negotiable room and route requirement verified, plus current booking authority. Method: filter non-compliant/unknown candidates, compare remaining options by person-selected preferences and count new dependencies such as lifts, staff or portable equipment. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified requirements/total, dependency count and rank stability under +/-20% preference weights; do not declare a winner if the top option changes. Safe failure: state that no verified match exists, identify the blocking requirement and escalate for relocation, re-timing, remote participation or a targeted inspection.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer why a requirement exists, reveal it to all room owners, auto-book a room, or describe a model-selected room as accessible for every person. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Timetabling/Space Management and affected service owners.
WHY THIS IS USEFUL	Provides a defensible relocation choice and shows whether the team should inspect, move equipment, change timing or offer another participation mode.

Rooms, seating, participation and adjustments

AI-029

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Are the accessible workstation, laboratory bench, makerspace station or shared device needed for the task operational, configured and bookable?

SENSORS AND TELEMETRY	Proposed evidence: asset power, fault, height-adjustment, safety-interlock and booking heartbeat telemetry, plus a competent task-specific setup inspection. Coverage: each candidate workstation/station, its clear approach, controls, local route and required shared devices. Timing/alignment: on state change with a five-minute heartbeat; inspection before the booked task; use a common clock. Aggregation: by asset and capability, without user identity or work-content monitoring. Quality gate: require asset mapping, commissioning, maintenance release, permission, heartbeat age <=5 minutes and competent inspection of all task-critical physical/safety features. Privacy guard: No monitoring of work content, productivity, technique, device files, identity or individual usage history. Known limits: telemetry cannot establish task suitability, reach, force, training, contamination, consumables or every safety condition; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current equipment inventory, booking, maintenance/safety status, local operating procedure and room access rules (the laboratory/makerspace owner, Estates where relevant, Technical Services and IT for digital devices). Corroborating sources: the person-stated practical setup requirement and competent technician confirmation. Precedence: safety isolation, competent technician decision and current booking status outrank equipment heartbeat or catalogue specification. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: heartbeat older than 5 minutes, maintenance status not released or procedure/configuration changed after inspection. Conflict handling: keep disagreement visible and refer it to the competent laboratory, makerspace or equipment owner.
ANALYSIS REQUIRED	Operation: task-specific station readiness and booking check. Decision interval: setup, booked use and required clean-down/handback interval. Minimum evidence: an authorised booking, current maintenance/safety release and verification of every task-critical feature and route dependency. Method: map the stated task requirements to station features, check safety prerequisites separately and compare verified alternatives without observing the person's work. Quantified uncertainty: report critical-evidence completeness as n/N, plus critical checks passed/required, asset state age and any dimensional margin with tolerance; any missing safety check prevents a ready claim. Safe failure: withhold the station, refer to the competent technical owner and offer a checked alternative or revised task arrangement.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer capability, monitor work or speech, access files, lower safety controls, waive training or authorise equipment use. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person and the competent laboratory, makerspace, technical or IT owner.
WHY THIS IS USEFUL	Enables the team to secure the right station and support before the task while keeping safety authority and the person's work outside the analytics.

AI-030

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Have agreed room adjustments been assigned, acknowledged and evidenced complete by the correct owners without disclosing the reason for them?

SENSORS AND TELEMETRY	Proposed evidence: privacy-minimised task-state, asset-status and setup-completion telemetry. Coverage: only the adjustment tasks and assets required for the named session; no health, casework or personal emergency-plan systems. Timing/alignment: on authorised task-state change with completion evidence captured in the setup window; use a common clock. Aggregation: by task and accountable owner, using a pseudonymous event reference only when needed. Quality gate: require explicit permission, minimal fields, current owner mapping, immutable timestamps and competent evidence for each critical completed task. Privacy guard: No diagnosis, health information, case notes, free-text reasons, broad attendee lists or reuse outside the stated purpose. Known limits: a completed workflow status cannot prove physical completion or participant satisfaction; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the approved adjustment task list, booking/event record and asset-owner completion evidence (the accessibility/inclusion team, room/session owner and each responsible service owner). Corroborating sources: the person's chosen requirements translated into minimum practical tasks, with the reason withheld from delivery teams unless explicitly necessary and permitted. Precedence: the person-approved task specification and competent completion evidence outrank ticket status or informal assurance. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: an unacknowledged task after its response deadline or completion evidence outside the setup interval. Conflict handling: keep disagreement visible and refer it to the task owner, coordinated by the accessibility/inclusion team.
ANALYSIS REQUIRED	Operation: confidential task dependency and completion check. Decision interval: request approval through the session start. Minimum evidence: an accountable owner, due time, acknowledgement and acceptable completion evidence for every critical task. Method: build a dependency graph, distinguish acknowledged from physically verified complete and expose only the minimum task information to each owner. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified critical tasks/total, overdue count and oldest evidence age; all critical tasks must be verified for a ready status. Safe failure: escalate the exact task, communicate the practical limitation to the person, and change room/time/format if completion cannot be verified.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not use health, casework or personal emergency-plan records, reveal the reason for a task, infer a condition, or treat task completion as consent to future reuse. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, accessibility/inclusion team, session owner and task owners.
WHY THIS IS USEFUL	Enables the team to chase the named owner, complete the adjustment before use, switch rooms or tell the person early without exposing why the adjustment exists.

Lighting, noise, air, temperature and sensory comfort

AI-031

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Are light levels and glare at the relevant route, seat and work positions verified for the planned activity and time?

SENSORS AND TELEMETRY	Proposed evidence: calibrated illuminance sensors, luminaire state and targeted luminance/glare measurements. Coverage: entrances, route decisions, representative seating/work positions, displays and presenter locations rather than one room-average point. Timing/alignment: illuminance every minute; targeted measurements after layout, blind, luminaire or display changes and before critical use; use a common clock. Aggregation: as position-level minimum, median and maximum with no person sensing. Quality gate: require calibrated instruments, mapped measurement positions, permission, clock alignment <=5 seconds, >=90% interval coverage and no reading older than 10 minutes. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: fixed sensors may miss reflections, screen glare, daylight changes, shadows and the exact viewing direction; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current lighting design/controls, maintenance status, room layout and owner-agreed activity lighting requirements (Estates Lighting, the room owner and Health and Safety where applicable). Corroborating sources: competent spot measurements and the person-selected lighting preferences. Precedence: a competent on-site measurement and current luminaire fault/override status outrank BMS values, design intent and historical room description. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: live readings older than 10 minutes or measurements made before a material layout/daylight/control change. Conflict handling: keep disagreement visible and refer it to the Estates lighting owner or competent assessor.
ANALYSIS REQUIRED	Operation: spatial lighting and glare assessment. Decision interval: the planned activity and expected daylight/control condition. Minimum evidence: measurements at every critical position and route decision point, current luminaire/control state and the activity owner's operating requirement. Method: compare position-level values with owner-agreed ranges, inspect glare directionally and keep measured light separate from person-stated preference. Quantified uncertainty: report critical-evidence completeness as n/N, plus min/median/max, spatial coverage, instrument tolerance and age; any unmeasured critical position or glare concern requires qualification. Safe failure: do not claim suitability; adjust blinds/luminaires where authorised, relocate the position or request a competent check.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer visual impairment, migraine, distress or productivity, and do not remotely override lighting without room-owner authority or create a personal lighting profile. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, room owner, Estates Lighting and competent safety owner.
WHY THIS IS USEFUL	Enables the team to change lighting, blinds, position or room using evidence tied to the actual activity rather than a misleading room average.

AI-032

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which route edges, entrances or room zones have persistent low light or failed fittings requiring immediate mitigation or owner action?

SENSORS AND TELEMETRY	Proposed evidence: luminaire power/fault, emergency-light self-test where authorised and illuminance telemetry. Coverage: every critical entrance, route decision point, stair/edge interface and representative room perimeter zone. Timing/alignment: faults on change; illuminance every 1-5 minutes; self-tests on the competent owner's schedule; use a common clock. Aggregation: by fitting/zone and time band. Quality gate: require fixture-zone mapping, calibrated sensors, commissioning, permission, >=95% fault-feed uptime and position measurements with known tolerance. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: sensors can be shaded, misplaced or healthy while the visual task remains poorly lit; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current luminaire asset register, fault tickets, maintenance release, emergency-light test records and route status (Estates Lighting, Estates Maintenance and the building owner). Corroborating sources: competent night/low-light inspection and user-reported barrier locations. Precedence: a competent failed inspection or active fault ticket outranks normal power telemetry; emergency-light decisions remain with the competent owner. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: fault state older than 10 minutes, illuminance data outside the relevant lighting condition or test evidence beyond its validity. Conflict handling: keep disagreement visible and refer it to the Estates lighting or emergency-light owner.
ANALYSIS REQUIRED	Operation: low-light anomaly detection and maintenance prioritisation. Decision interval: current use plus recurring relevant lighting periods. Minimum evidence: current fault status and repeated position-level low-light evidence, or one competent failed inspection at a critical location. Method: compare zones against their owner-defined operating range, distinguish isolated failure from recurring control/daylight pattern and link each finding to an asset. Quantified uncertainty: report critical-evidence completeness as n/N, plus affected samples/valid samples, duration, instrument tolerance and repeated-day count; require >=3 relevant periods for a recurrence claim unless a critical inspection fails. Safe failure: open a remedial work/inspection task, mark the location unverified and provide temporary lighting or a checked alternative route under owner control.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer who is affected, classify a person's vision, certify emergency-lighting compliance or remotely test/override systems outside competent procedures. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with Estates Lighting, the building owner and competent safety personnel.
WHY THIS IS USEFUL	Enables the team to separate a transient low reading from a persistent asset problem and assign remedial work or temporary mitigation to the right owner.

Lighting, noise, air, temperature and sensory comfort

AI-033

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

What current sound conditions should we communicate, and which quieter periods are supported by enough evidence to offer as options?

SENSORS AND TELEMETRY	Proposed evidence: class-appropriate sound-pressure-level meters and anonymous activity/occupancy counts. Coverage: the destination room, nearby circulation and key approach segments, using representative measurement positions. Timing/alignment: acoustic metrics every minute and occupancy in five-minute privacy-safe bands; clocks aligned within 5 seconds; use a common clock. Aggregation: as LAeq and agreed event metrics by zone/time band; no audio waveform or speech. Quality gate: require calibrated meters, mapped positions, acoustic privacy assessment, permission, >=90% coverage and no reading older than 10 minutes. Privacy guard: No raw audio, speech content, voice detection, speaker identification or person-level dwell. Known limits: sound level does not reveal source, meaning, speech intelligibility, subjective impact or future one-off noise; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current room/event schedule, works and plant notices, room-use owner instructions and noise complaints/barrier reports (the room owner, Events/Timetabling, Estates Operations and Estates Maintenance). Corroborating sources: competent acoustic investigation where a source or suitability claim is needed. Precedence: a live works/event notice or competent inspection outranks historical acoustic patterns; measured level cannot establish personal comfort. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: live readings older than 10 minutes or historical periods before a material room, plant or schedule change. Conflict handling: keep disagreement visible and refer it to the room owner or Estates acoustic/plant owner.
ANALYSIS REQUIRED	Operation: current acoustic description and quieter-period estimation. Decision interval: now and the person-selected candidate time bands. Minimum evidence: current calibrated measurements plus >=8 comparable periods with >=90% coverage for a quieter-period claim. Method: compare time-band distributions at relevant positions, control for known events/works and present alternatives without inferring tolerance. Quantified uncertainty: report critical-evidence completeness as n/N, plus median, 90th percentile and 80% prediction interval; label periods indistinguishable when intervals overlap materially or coverage is <90%. Do not label a period "quiet" from an average alone; retain peak and variability evidence for the stated locations. Safe failure: give only the current measured range, request a spot check or offer a verified quiet-space/remote option.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not record speech, infer distress, concentration, neurotype or productivity, promise quiet, or create a persistent personal sound preference without consent. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, room owner, Estates and event/timetable owners.
WHY THIS IS USEFUL	Enables the team to recommend an evidence-supported time or space, warn about known noise and avoid overstating what a sound-level meter can tell.

AI-034

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Are intermittent sounds from plant, works, alarm tests or equipment likely during the activity, and can the responsible owner reduce or pre-announce them?

SENSORS AND TELEMETRY	Proposed evidence: sound-level event metrics, plant/equipment operating state and works activity telemetry. Coverage: the room, adjacent plant zones and route segments where the source could materially affect the activity. Timing/alignment: event detection at one-second metrics with minute summaries; plant/works state on change; use a common clock. Aggregation: by source class and zone without recording audio content. Quality gate: require calibrated meters, mapped source dependencies, permission, clock skew <=2 seconds, >=90% coverage and source-state evidence for attribution. Privacy guard: No raw audio, speech classification, speaker identity or behavioural interpretation. Known limits: a level event may be misattributed, and unscheduled knocks, voices or alarms cannot be forecast reliably; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current works permits, plant schedules, alarm-test programme, equipment bookings and live incident notices (Estates Projects, Estates Maintenance, Fire Safety, the room owner and equipment owners). Corroborating sources: competent source investigation and verified event logs. Precedence: an alarm/incident instruction or authorised works plan outranks acoustic analytics; only the competent owner may confirm or change an operating schedule. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: source-state data older than 10 minutes or historical event patterns after a material equipment/works change. Conflict handling: keep disagreement visible and refer it to the owner of the suspected source or current incident.
ANALYSIS REQUIRED	Operation: intermittent-event association and schedule overlap check. Decision interval: the planned activity plus a relevant look-back window. Minimum evidence: timestamp-aligned acoustic events and authoritative source states for attribution, or a competent observation. Method: match events to known source changes within a declared tolerance, compare recurrence by time/activity and keep unexplained events separate. Quantified uncertainty: report critical-evidence completeness as n/N, plus event count, attribution rate and timing offset; require >=5 matched events for a recurring source association and never label unexplained events as that source. Safe failure: state that the source or likelihood is unverified, request owner investigation and communicate only confirmed tests/works.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer a person's reaction or condition, record speech, suppress or alter alarms, or direct plant/work changes without competent owner authority. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, source owner, room owner and competent safety owner.
WHY THIS IS USEFUL	Supports practical re-timing, source investigation or advance communication while keeping alarm and plant decisions with competent owners.

Lighting, noise, air, temperature and sensory comfort

AI-035

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Do the available ventilation indicators justify an operational investigation, room change or timing change without making a health claim?

SENSORS AND TELEMETRY	Proposed evidence: CO2, temperature, relative-humidity, airflow/pressure where installed, window/damper state and ventilation-plant telemetry. Coverage: representative occupied zones and the serving ventilation system, with sensor positions documented. Timing/alignment: environmental values every 1-5 minutes and plant state on change; clocks aligned within 5 seconds; use a common clock. Aggregation: by room/zone and time band, never by person. Quality gate: require calibrated and correctly sited sensors, mapped plant dependencies, permission, >=90% valid samples and no critical reading older than 10 minutes. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: CO2 is a context indicator, not a diagnosis or complete measure of air quality, ventilation rate or infection risk; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current room use/booking, ventilation design and operating set-points, plant status, maintenance faults and owner procedures (Estates Building Services, the room owner and Health and Safety where escalation criteria apply). Corroborating sources: competent inspection, commissioning/airflow test and current occupancy context at zone level. Precedence: a competent plant/airflow finding and current owner instruction outrank a single environmental reading or model estimate. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: live readings older than 10 minutes, calibration overdue or room use/configuration inconsistent with the evidence. Conflict handling: keep disagreement visible and refer it to the Estates building-services duty owner.
ANALYSIS REQUIRED	Operation: ventilation indicator triage. Decision interval: the current and planned occupied period. Minimum evidence: valid calibrated readings from representative positions, current plant state and enough occupancy/use context to interpret the period. Method: compare trends with owner-defined operating triggers, check sensor agreement and plant response, and separate observed condition from cause. Quantified uncertainty: report critical-evidence completeness as n/N, plus range, duration, sensor tolerance, inter-sensor spread and missingness; require at least two consistent readings or competent confirmation for an operational issue claim. Safe failure: label the cause unverified, contact the building-services owner, consider owner-approved ventilation/room changes and avoid health advice.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer illness, infection, distress, attendance or productivity; diagnose occupants; certify air quality; or control dampers, windows or plant. CO2, airflow and plant data may indicate an operating issue but cannot diagnose exposure, illness or individual risk. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with Estates Building Services, the room owner and competent Health and Safety personnel.
WHY THIS IS USEFUL	Enables the team to escalate a well-evidenced operating concern, change room or timing, and avoid turning CO2 or other indicators into health claims.

AI-036

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Where and for how long are temperature or humidity outside the responsible owner's operating range in access, waiting or participation spaces?

SENSORS AND TELEMETRY	Proposed evidence: calibrated air-temperature and relative-humidity sensors plus HVAC zone and plant-state telemetry. Coverage: representative positions in entrances, waiting areas, seating/work zones and the serving HVAC zones. Timing/alignment: every 1-5 minutes with plant state on change; clocks aligned within 5 seconds; use a common clock. Aggregation: by zone with min/median/max rather than a single building value. Quality gate: require documented sensor siting, calibration, plant mapping, permission, >=90% coverage and no critical reading older than 10 minutes. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: local radiant effects, draughts, sunlight, clothing, activity and personal comfort are not fully represented; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current owner-defined operating ranges, room use, HVAC schedule/set-points, plant faults and approved overrides (Estates Building Services and the room/service owner). Corroborating sources: competent spot measurement and current weather context. Precedence: a competent measurement, active fault or owner override outranks BMS summaries; the range is operational, not a universal comfort or health threshold. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: reading older than 10 minutes, calibration overdue or evidence collected under a materially different room/HVAC configuration. Conflict handling: keep disagreement visible and refer it to the Estates building-services owner.
ANALYSIS REQUIRED	Operation: zone-level range exceedance and duration analysis. Decision interval: the current/planned use and the preceding stabilisation period. Minimum evidence: valid readings from all critical zones, current HVAC state and the owner-approved operating range for that use. Method: calculate duration outside range, spatial spread and response to plant changes; present person-stated preference separately from operating status. Quantified uncertainty: report critical-evidence completeness as n/N, plus min/median/max, duration, instrument tolerance, spatial coverage and missingness; one uncovered critical zone prevents a whole-room claim. Safe failure: state the condition is not verified, request a competent check and consider room, timing or owner-approved local mitigation.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer health, distress, sensitivity or capability, issue medical advice, promise comfort, or change HVAC set-points without owner authority. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, room owner and Estates Building Services.
WHY THIS IS USEFUL	Supports a precise facilities escalation and an evidence-based decision to adjust, relocate or re-time the activity without medicalising comfort.

Lighting, noise, air, temperature and sensory comfort

AI-037

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Is lighting flicker or unstable dimming present at the person's selected position or route, and what technical isolation or check is needed?

SENSORS AND TELEMETRY	Proposed evidence: dedicated flicker-meter measurements, luminaire driver state and lighting-control event telemetry. Coverage: representative route, seating, workstation and display-adjacent positions for the affected lighting circuit. Timing/alignment: high-rate measurement during a reported/observed event and repeat tests across relevant dimming levels; control state on change; use a common clock. Aggregation: as flicker metrics by position and control state, not continuous personal exposure. Quality gate: require a calibrated flicker instrument, known sampling specification, mapped circuits, permission and a competent test under the actual operating configuration. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: ordinary illuminance sensors cannot establish flicker; intermittent faults and camera/display interactions may be missed; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current luminaire/driver inventory, control configuration, fault history and maintenance status (Estates Lighting, IT/AV for displays and the room owner). Corroborating sources: competent electrical/lighting investigation and person-reported practical barrier without health details. Precedence: competent instrumented testing and maintenance findings outrank user-device video, generic specifications or an illuminance trend. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: test evidence after a driver/control/display change or outside the reported operating state. Conflict handling: keep disagreement visible and refer it to the competent Estates lighting or IT/AV owner.
ANALYSIS REQUIRED	Operation: flicker verification and source isolation. Decision interval: the reported operating state and planned use. Minimum evidence: a calibrated high-rate measurement at each relevant position, current control/driver state and a reproducible test condition. Method: compare metrics across control states and circuits, isolate lighting versus display sources and avoid interpreting health impact. Quantified uncertainty: report critical-evidence completeness as n/N, plus measured metric, instrument uncertainty, positions tested/required and reproducibility across >=3 runs; a non-reproduced event remains intermittent/unverified. Safe failure: avoid a no-flicker claim, move the activity or isolate the suspected asset under competent owner control and arrange retest.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer epilepsy, migraine, diagnosis or sensitivity, use consumer video as certification, or alter electrical systems or displays without competent authority. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Estates Lighting, IT/AV and the room owner.
WHY THIS IS USEFUL	Provides the team with a technically defensible route to isolate the source, change the space or control state and commission competent electrical remedial work.

AI-038

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Can instrumentation meaningfully address the reported odour, particulate or air concern, or must the team rely on competent inspection?

SENSORS AND TELEMETRY	Proposed evidence: PM2.5/PM10, total-VOC where appropriate, CO2, temperature, humidity and ventilation-plant telemetry. Coverage: representative locations in the affected room and adjacent source/route zones, with sensor siting documented. Timing/alignment: every 1-5 minutes and on plant/source changes; clocks aligned within 5 seconds; use a common clock. Aggregation: by zone and pollutant indicator, never by individual exposure. Quality gate: require calibrated/maintained instruments appropriate to the indicator, permission, >=90% coverage and readings no older than 10 minutes. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: generic VOC sensors do not identify odours or chemicals; many hazards, cleaning products, damp sources and local plumes require inspection; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current incident/maintenance reports, cleaning/works activity, ventilation status and hazardous-substance controls (Estates Building Services, Cleaning, Estates Projects, Health and Safety and the room owner). Corroborating sources: competent environmental or occupational-hygiene inspection where source or risk is at issue. Precedence: an incident instruction, competent inspection or hazardous-substance control outranks low-cost sensor output and model attribution. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: readings older than 10 minutes, calibration/maintenance overdue or source conditions changed after observation. Conflict handling: keep disagreement visible and refer it to the competent Health and Safety or Estates owner.
ANALYSIS REQUIRED	Operation: instrumentation sufficiency and anomaly triage. Decision interval: the current concern and any planned use before resolution. Minimum evidence: appropriate healthy sensors at representative points plus source/plant context; source identification requires competent evidence. Method: compare zones and baseline under similar conditions, test sensor agreement and classify only observed indicator anomaly, not chemical identity or health effect. Quantified uncertainty: report critical-evidence completeness as n/N, plus indicator range, sensor tolerance, inter-sensor spread and coverage; require >=2 consistent instruments or competent confirmation for a spatial anomaly claim. Safe failure: state that instrumentation cannot answer, restrict guidance to owner instructions, request competent inspection and consider relocation.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not diagnose symptoms, infer sensitivity or exposure, identify a substance from generic sensors, certify air safety or override hazardous-material procedures. Instrument non-detection must not be presented as proof that an odour or air concern is absent. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Health and Safety, Estates and the room owner.
WHY THIS IS USEFUL	Enables the team to avoid false reassurance, direct the issue to the right competent owner and decide whether to relocate or pause use.

Lighting, noise, air, temperature and sensory comfort

AI-039

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which available space best matches the person-stated light, noise, temperature, air and crowding preferences, with evidence gaps and trade-offs explicit?

SENSORS AND TELEMETRY	Proposed evidence: illuminance, sound-level, temperature, humidity, CO2 and anonymous density telemetry plus room/route/AV status. Coverage: candidate spaces, their routes and representative seating zones within the permitted search area. Timing/alignment: environmental data every 1-5 minutes; availability and route state on change; use a common clock. Aggregation: by room/zone and time band with small-cell suppression. Quality gate: require calibrated/mapped sensors, current booking and route evidence, permission, >=90% interval coverage and source age <=10 minutes. Privacy guard: No person tracking, inferred sensory profile, health interpretation or reuse of preferences beyond the chosen purpose. Known limits: metrics do not equal personal comfort, future conditions can change and some spaces may lack comparable sensor coverage; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current room availability, route/access status, owner-approved operating ranges and service restrictions (Space Management/Timetabling, Estates, Security and room owners). Corroborating sources: the person-selected preferences and current competent checks for unsensed features. Precedence: the person controls the criteria; current booking/closure and inspection outrank environmental ranking and historical room descriptions. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: availability after a change, live readings older than 10 minutes or incomparable sensor configurations. Conflict handling: keep disagreement visible and refer it to the room/space owner and Space Management.
ANALYSIS REQUIRED	Operation: person-owned environmental option comparison. Decision interval: the requested use window. Minimum evidence: at least one available room with verified route and current evidence for every non-negotiable preference; comparisons require comparable measurement coverage. Method: filter non-negotiable conditions, normalise only comparable metrics and present trade-offs without a wellness/accessibility score. Quantified uncertainty: report critical-evidence completeness as n/N, plus metric ranges and sensor tolerances, evidence coverage per room and rank stability under +/-20% preference weights; unstable or incomparable options remain unranked. Safe failure: present verified facts only, request a spot check, offer remote participation or state that no evidence-supported match exists.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer diagnosis, neurotype, distress or future needs, persist a personal profile without explicit permission, or promise comfort. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Space Management, room owners and Estates.
WHY THIS IS USEFUL	Enables the team to offer real choices, target a room check and avoid presenting a sensor-derived score as a personal recommendation.

AI-040

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which sensory-comfort barriers recur under identifiable operating conditions, and which owner should run a controlled change test?

SENSORS AND TELEMETRY	Proposed evidence: privacy-safe environmental telemetry, plant/lighting/equipment state and structured barrier reports. Coverage: predefined rooms, routes and service zones with sufficient sensor and report coverage; no individual movement linkage. Timing/alignment: environmental data every 1-5 minutes and reports at submission; analyse in weekly or monthly decision windows; use a common clock. Aggregation: by location, time band, condition and asset state with small-cell suppression. Quality gate: require calibrated mapped sources, permissions, provenance, >=80% comparable-period coverage and suppression of cells with fewer than 5 reports or 10 occupancy observations. Privacy guard: No health or casework data, free-text profiling, person-level histories or linkage of reports to attendance. Known limits: reports are selective, sensor coverage is uneven and association does not establish cause or personal impact; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current room/asset ownership, maintenance/change history, event/timetable context and barrier-report workflow (Estates, Space Management, local service owners and the accessibility/inclusion team). Corroborating sources: competent investigation outcomes and confirmed completed actions. Precedence: competent investigation and current operational changes outrank statistical association; unresolved owner conflicts remain visible. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: data collected before a material asset/layout/use change or outside the selected comparison window. Conflict handling: keep disagreement visible and refer it to the owner of the suspected asset/service, coordinated by the accessibility/inclusion team.
ANALYSIS REQUIRED	Operation: recurrence and condition-association analysis. Decision interval: a defined monthly/termly improvement window with pre/post operational periods. Minimum evidence: >=5 independent barrier reports or repeated instrumented anomalies across >=3 comparable periods, current ownership and adequate denominator/context. Method: group by location/time/asset state, compare rates or distributions, control for known schedule changes and treat associations as hypotheses for a trial. Quantified uncertainty: report critical-evidence completeness as n/N, plus counts, exposure denominator, 95% Wilson intervals or bootstrap intervals and missingness; suppress small cells and avoid causal language without a controlled change. Safe failure: record insufficient evidence, commission a targeted measurement/invisible owner-approved trial.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer health, neurotype, distress or productivity from reports or conditions, identify reporters in aggregate outputs, or use patterns to label a group or room universally unsuitable. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with reporters, the accessibility/inclusion team and competent service owners.
WHY THIS IS USEFUL	Enables the team to assign the recurring condition to the correct owner, test one proportionate change and accept it only against pre-declared evidence.

Wayfinding, communication formats and assistive information

AI-041

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Can we publish one current route with equivalent meaning in clear text, map and spoken formats from the chosen entrance to the destination?

SENSORS AND TELEMETRY	Proposed evidence: door/lift/route-state telemetry and digital content-service health checks. Coverage: every instruction step, decision point and asset used by the route, plus each delivery format under institutional control. Timing/alignment: route states on change or every 5 minutes; content health on publication and at least every 15 minutes; use a common clock. Aggregation: as claim-to-segment and claim-to-format coverage, never as user navigation traces. Quality gate: require verified route mapping, commissioned feeds, content version control, permissions, all critical route states <=5 minutes old and a human accessibility check of each published format. Privacy guard: No tracking of who opens directions, device fingerprinting, destination history or inferred assistive-technology use. Known limits: automated checks cannot prove that wording is understandable, speech output is intelligible or a map is cognitively usable; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current destination name/location, route and closure records, entrance status and approved communication templates (Space Management, Estates Operations, Security and the destination/content owner). Corroborating sources: competent plain-language, map and text-to-speech/recorded-audio checks. Precedence: current operational route authority outranks generated directions; the destination/content owner controls wording and version; live restrictions override all formats. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: any route state older than 5 minutes or a format not regenerated/rechecked after a route or destination change. Conflict handling: keep disagreement visible and refer it to the route owner for path facts and the content owner for publication.
ANALYSIS REQUIRED	Operation: cross-format route generation and semantic equivalence check. Decision interval: publication through the stated journey window. Minimum evidence: one verified route, a step-to-segment trace and a current human-checked version in every promised format. Method: generate all formats from one structured route source, compare essential decisions and distances step by step, and run human checks for clarity and spoken/map usability. Quantified uncertainty: report critical-evidence completeness as n/N, plus matched essential instructions/total, route-state age and unresolved wording conflicts; 100% essential-step equivalence is required before claiming equivalent formats. Safe failure: publish only the verified formats, name the missing format/check and provide an owner contact or staffed directions.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer a person's impairment or preferred assistive technology, store route use, promise independent navigation or describe machine-generated speech/map output as accessible without assessment. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, route owners and content/destination owner.
WHY THIS IS USEFUL	Enables the team to issue one consistent route in several usable forms and prevent format drift after a closure or room move.

AI-042

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which room names or destination identifiers conflict across signs, booking systems, directories and digital maps, and which source should be corrected?

SENSORS AND TELEMETRY	Proposed evidence: content-version, directory, booking and digital-map integration telemetry plus structured sign inventory checks. Coverage: every public identifier for the target destination and all decision points on its published routes. Timing/alignment: on every source change with a daily reconciliation; physical signs inspected on a controlled schedule and after moves; use a common clock. Aggregation: by destination identifier and channel. Quality gate: require source-owner mapping, versioned identifiers, permission, clock alignment within 1 minute and a current physical-sign inspection for every route-critical label. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: digital consistency cannot prove physical sign presence, visibility or that temporary paper signs have been removed; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the current authoritative space/destination register and approved room naming/numbering decision (Space Management and the destination service owner). Corroborating sources: booking/timetabling, directory, digital-map and signage inventories owned by their respective service owners. Precedence: the authoritative destination register and current owner-approved change notice outrank booking copies, cached maps, local spreadsheets and historical floor plans. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: any copy not refreshed after the effective time of the authoritative change or a sign inspection outside its validity. Conflict handling: keep disagreement visible and refer it to Space Management or the destination owner.
ANALYSIS REQUIRED	Operation: identifier reconciliation and route-impact analysis. Decision interval: now and any announced future effective change. Minimum evidence: an authoritative current identifier plus observed values in every public channel and route-critical physical sign. Method: compare normalised identifiers and effective times, flag exact mismatches and identify which route instructions or services are affected. Quantified uncertainty: report critical-evidence completeness as n/N, plus consistent channels/total, unresolved aliases and lag from effective time; any route-critical mismatch prevents a fully consistent claim. Safe failure: publish the authoritative name with a warning, suppress conflicting generated directions and open correction tasks for each owner.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not expose restricted room details, infer who is attending, auto-edit owner systems or treat a historical label as current. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with Space Management, destination owner and each channel owner.
WHY THIS IS USEFUL	Provides the team with a precise correction list and reduces avoidable confusion caused by one destination appearing under several names.

Wayfinding, communication formats and assistive information

AI-043

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

At each real decision point, is the next sign visible, unobstructed, sufficiently lit and positioned to support the correct route choice?

SENSORS AND TELEMETRY	Proposed evidence: sign asset/location records, non-imaging obstruction telemetry and local illuminance measurements, supported by structured human inspection. Coverage: every route decision point, entrance, lift lobby, corridor junction and destination approach on published routes. Timing/alignment: obstruction/light every 1-5 minutes where instrumented; physical sign inspection after changes and on a defined schedule; use a common clock. Aggregation: by decision point and sign, without capturing viewers. Quality gate: require mapped sign assets, calibrated light readings, permission and a competent inspection with distance, angle, contrast and obstruction fields complete. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: sensors cannot establish viewing angle, legibility, contrast, clutter, comprehension or temporary sign quality; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current signage standard, approved route/destination register and sign asset inventory (Estates, Space Management, Communications/Brand where applicable and the destination owner). Corroborating sources: competent on-site sign inspection and current route/closure notices. Precedence: observed physical condition and current route decision outrank design files, sign inventory and historical photographs. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: an inspection after a layout/route/sign change is absent or outside its owner-defined validity. Conflict handling: keep disagreement visible and refer it to the signage/route owner.
ANALYSIS REQUIRED	Operation: decision-point sign adequacy inspection analysis. Decision interval: the current route configuration and publication interval. Minimum evidence: a current inspection for every essential decision point and confirmation that the sign leads to a currently usable next link. Method: score no person; instead record pass/fail/unknown for visibility, obstruction, contrast, position and route consistency at each point. Quantified uncertainty: report critical-evidence completeness as n/N, plus essential decision points passed/total, fields unknown and inspection age; all essential points must be passed for a complete signed-route claim. Safe failure: mark the signed route incomplete, provide multi-format directions or staffed help, and issue the exact sign/obstruction task.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not identify viewers, infer visual ability, certify legal compliance from a checklist or automatically reposition signs or furniture. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, signage owner, route owner and destination owner.
WHY THIS IS USEFUL	Enables the team to fix the decision point where navigation fails rather than merely confirming that a sign exists somewhere nearby.

AI-044

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which tactile, Braille or raised-character signs have current competent inspection evidence, and where do we have inventory evidence only?

SENSORS AND TELEMETRY	Proposed evidence: no continuous people sensing is appropriate; proposed sign-asset tags or inventory heartbeats may confirm asset identity, but physical features require inspection. Coverage: entrances, lifts, toilets, room identifiers and other locations where the current signage owner records tactile information. Timing/alignment: inventory on controlled change; competent inspection after installation, damage, relocation or on the owner's assessment schedule; use a common clock. Aggregation: by sign asset and feature, with no scan/user history. Quality gate: require a current sign ID/location, competent inspector, inspection method, observed timestamp, versioned result and permission; do not treat tag presence as feature verification. Privacy guard: No logging of who touches or scans a sign and no inference about visual impairment. Known limits: an asset tag cannot prove Braille accuracy, tactile quality, height, reach, contrast, damage or route consistency; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the current signage asset register, specification and approved destination/room identifier (Estates/Signage, Space Management and the destination owner). Corroborating sources: competent tactile/Braille inspection and remedial work history. Precedence: the latest competent physical inspection and current destination identifier outrank procurement records, asset tags and historic drawings. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: inspection after any sign/destination change is absent or beyond the owner-defined validity. Conflict handling: keep disagreement visible and refer it to the competent signage owner.
ANALYSIS REQUIRED	Operation: tactile-sign inventory and inspection sufficiency check. Decision interval: current publication and planned route use. Minimum evidence: a current inspection for each claimed tactile/Braille feature, correct destination text and current location. Method: join asset, identifier and inspection records; separate present, inspected and verified-correct states and list uninspected claims. Quantified uncertainty: report critical-evidence completeness as n/N, plus inspected claimed signs/total, failed features and oldest inspection age; only inspected-and-current signs may be described as available. Safe failure: publish no feature claim for the uninspected sign, provide another format and open an inspection/remedial work task.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer who needs tactile information, claim that presence guarantees usability, disclose restricted destinations or certify compliance. Do not equate an ordered, tagged or photographed sign with a correctly installed and usable tactile feature. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, competent signage owner and destination/space owner.
WHY THIS IS USEFUL	Enables the team to distinguish a procurement or inventory record from a current usable feature and direct checks to the exact sign.

Wayfinding, communication formats and assistive information

AI-045

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Do QR codes, NFC tags, kiosks and digital wayfinding links reach current content and work with common assistive-technology pathways?

SENSORS AND TELEMETRY	Proposed evidence: endpoint uptime, link-resolution, content-version and kiosk hardware/accessibility self-test telemetry. Coverage: every public QR/NFC target, kiosk and fallback link on the relevant route. Timing/alignment: synthetic checks at least every 15 minutes and after every content/deployment change; use a common clock. Aggregation: by endpoint/device and test case, without logging real users. Quality gate: require mapped physical tag/device, controlled URL/version, permission, >=98% synthetic-test availability and manual assistive-technology testing after material changes. Privacy guard: No scan/user identifiers, device fingerprinting, session replay, location history or inferred assistive-technology use. Known limits: synthetic checks cannot cover every device, browser, screen reader, physical reach or network condition; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current content, destination and route records plus the approved digital accessibility standard and service configuration (the content owner, IT/Digital Service, Space Management and route/destination owners). Corroborating sources: manual tests with defined browsers, keyboards and assistive technologies, plus current incident status. Precedence: current route/destination authority and manual accessibility test outrank endpoint uptime; a live incident/withdrawal outranks cached content. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: synthetic result older than 15 minutes or manual accessibility test before a material template/content change. Conflict handling: keep disagreement visible and refer it to the content owner with IT/Digital Service.
ANALYSIS REQUIRED	Operation: end-to-end digital wayfinding accessibility test. Decision interval: publication through the journey window. Minimum evidence: successful physical tag-to-current-content resolution, essential content equivalence and passed manual tests for the supported interaction set. Method: run scripted endpoint checks and manual keyboard/screen-reader/content tests; trace failures to physical tag, network, page, content or kiosk hardware. Quantified uncertainty: report critical-evidence completeness as n/N, plus test cases passed/required, uptime interval and last manual-test age; all essential tasks must pass before claiming supported access. Safe failure: remove or qualify the digital channel, display a current non-digital fallback and open the exact remediation task.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not track scans, infer assistive-technology use, promise compatibility with every device or auto-publish content that has not passed owner assessment. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, content owner, IT/Digital Service and route/destination owners.
WHY THIS IS USEFUL	Enables the team to fix broken links or inaccessible interactions before people encounter them and to keep an equivalent fallback available.

AI-046

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Are essential announcements delivered in equivalent audible and visual forms across every affected location and effective period?

SENSORS AND TELEMETRY	Proposed evidence: public-address, display, messaging-platform and network delivery/heartbeat telemetry. Coverage: every affected zone and each authorised visual, audible and digital channel promised for the message. Timing/alignment: on publication and delivery event with one-minute heartbeat during urgent use; use a common clock. Aggregation: by message version, channel and zone; no recipient tracking beyond system-level delivery where authorised. Quality gate: require one authoritative message ID/version, mapped channel coverage, permission, clock skew <=2 seconds and current health for every critical channel. Privacy guard: No individual attention, hearing/vision inference, device tracking or disclosure of recipient lists beyond authorised operations. Known limits: delivery telemetry cannot prove that a person saw, heard or understood the message; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the approved announcement text, affected area, effective period, urgency and publishing authority (Security/Incident Communications, the service/event owner and Communications where applicable). Corroborating sources: channel coverage maps, current channel status and manual observation. Precedence: incident command or the authorised message owner controls content and timing; their current instruction outranks automated translation, summarisation or schedule. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a channel state older than 2 minutes during urgent use or any version mismatch after the latest approved message. Conflict handling: keep disagreement visible and refer it to the authorised message owner or incident communications lead.
ANALYSIS REQUIRED	Operation: cross-channel message equivalence and coverage check. Decision interval: the message effective period. Minimum evidence: one approved essential-message structure, the current version on every required channel and verified zone coverage. Method: compare action, location, time, severity and contact elements across channels; test delivery separately from comprehension. Quantified uncertainty: report critical-evidence completeness as n/N, plus matched essential elements/total, channels/zones delivered and timing skew; 100% essential-element match is required for equivalent-content status. Safe failure: publish a correction through the verified channels, name the unavailable channel and deploy authorised staff/manual communication.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer who heard or understood a message, alter emergency content, promise receipt, or use a personal channel without authority and permission. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the message owner, incident command, channel owners and recipients.
WHY THIS IS USEFUL	Enables the team to detect a version or channel gap and deliver one actionable message rather than parallel announcements that contradict each other.

Wayfinding, communication formats and assistive information

AI-047

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Do digital displays give essential information enough contrast, size and dwell time, with an equivalent non-display channel?

SENSORS AND TELEMETRY	Proposed evidence: display power, content-version, playback, brightness and schedule telemetry plus structured visual/interaction inspection. Coverage: every display carrying essential route, closure, room or event information and its declared alternative channel. Timing/alignment: playback heartbeat every minute; content/version checks on change; physical inspection after relocation/template changes; use a common clock. Aggregation: by display, message and alternative channel. Quality gate: require display/content mapping, controlled templates, permission, >=98% playback heartbeat and a current competent inspection of size, contrast, timing and physical position. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: telemetry cannot prove real-world contrast, reflections, viewing distance, reading speed, language clarity or comprehension; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the approved message, digital content standard, display schedule and destination/route authority (the content owner, IT/Digital Signage, Communications and destination/route owners). Corroborating sources: competent on-site readability check and current alternative-format content. Precedence: the approved current message and observed display condition outrank playback logs; current closure/route authority outranks scheduled content. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: heartbeat older than 2 minutes, content version superseded or inspection before a material template/position change. Conflict handling: keep disagreement visible and refer it to the content owner with Digital Signage/IT.
ANALYSIS REQUIRED	Operation: display readability, timing and alternative-channel readiness check. Decision interval: the message display/effective period. Minimum evidence: correct current message, verified presentation at representative viewing positions, sufficient owner-set dwell time and a working equivalent alternative. Method: test essential task completion at specified viewing distances, compare message elements across channels and separate hardware state from content quality. Quantified uncertainty: report critical-evidence completeness as n/N, plus checks passed/required, measured text/contrast/timing values with tolerance and alternative-channel age; any failed essential check prevents a ready claim. Safe failure: remove or correct the display message, extend dwell time under owner control and direct users to the verified alternative channel.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer reading ability or impairment, track who looks at a display, promise readability for every person or change emergency messaging without authority. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, content owner, Digital Signage/IT and message authority.
WHY THIS IS USEFUL	Enables the team to correct the actual content, timing or physical presentation and prevents a display-only message from becoming a single point of exclusion.

AI-048

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Have closures, room moves and route changes reached each affected attendee and accompanying person through their selected authorised channels before travel?

SENSORS AND TELEMETRY	Proposed evidence: authorised notification, message-version and channel delivery-status telemetry. Coverage: only the event/contact list and channels required for the specific change; no health, casework or broad behavioural data. Timing/alignment: on approved publication and delivery attempt, with retry state according to channel policy; use a common clock. Aggregation: by event, message version and channel; use aggregate delivery status where person-level confirmation is not authorised. Quality gate: require explicit event/contact authority, current permission, one approved message version, clock skew <=1 minute and traceable delivery outcome with minimal retention. Privacy guard: No disclosure of requirements, diagnosis or support reason; no cross-event contact profile or channel inference. Known limits: delivery does not prove attention, comprehension or that contact details remain current; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the authorised event/booking contact list, selected communication channels, approved change message and effective time (the event/session owner and institutional communications/contact-data owners). Corroborating sources: current closure/room/route authority and any person-supplied accompanying-person contact permission. Precedence: the operational owner confirms the change; the event owner authorises recipients and content; selected channels and consent outrank convenience. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a contact list or preference not valid for the event, a message superseded by a newer version or delivery after the decision deadline. Conflict handling: keep disagreement visible and refer it to the event/session owner and contact-data owner.
ANALYSIS REQUIRED	Operation: authorised notification coverage and deadline check. Decision interval: from change approval to the last useful decision time before travel/session. Minimum evidence: an approved current message, authorised recipient/channel set and at least one valid delivery route for each contact where person-level delivery is permitted. Method: send one version, deduplicate authorised contacts, compare delivery time with the decision deadline and keep accompanying-person communication separately permissioned. Quantified uncertainty: report critical-evidence completeness as n/N, plus authorised contacts with a successful channel/total, version conflicts and late deliveries; do not equate delivery with understanding. Safe failure: escalate undelivered cases to the event owner for an authorised alternative, publish public updates and prepare on-site assistance.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not reveal the reason a person needs a channel or companion contact, contact an accompanying person without permission, promise receipt or reuse contact preferences for another purpose. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, event/session owner and contact-data/channel owners.
WHY THIS IS USEFUL	Supports timely, privacy-respecting change communication and highlights exactly which contacts need another authorised route before travel.

Wayfinding, communication formats and assistive information

AI-049

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which proposed assistive-navigation beacons are mapped, commissioned, healthy and suitable to mention, and where must the service stay silent?

SENSORS AND TELEMETRY	Proposed evidence: beacon power, battery, configuration, broadcast and gateway health telemetry plus calibrated location survey. Coverage: every beacon and decision point in the advertised navigation area, including boundaries and known radio-shadow zones. Timing/alignment: health every 1-5 minutes; configuration on change; location/coverage survey after installation or environmental change; use a common clock. Aggregation: by beacon and zone, without collecting user-device identifiers or movement. Quality gate: require independent deployment, mapping, RF commissioning, permission/security assessment, configuration provenance, clock alignment and a current route-level field test. Privacy guard: No handset identifiers, probe requests, app analytics, person tracking, route history or inferred impairment. Known limits: healthy broadcasting does not prove phone compatibility, indoor positioning accuracy, understandable instructions or continuous coverage; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the approved beacon inventory, RF/site survey, route content, security/privacy assessment and supported-app specification (IT/Networks, Estates, Information Security, the navigation service owner and route owners). Corroborating sources: current field-test results and live route/closure authority. Precedence: route closures and competent field tests outrank beacon heartbeat; Information Security and service owners decide whether the service may operate. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: health older than 5 minutes, field test before a material layout/RF/configuration change or unsupported app/version. Conflict handling: keep disagreement visible and refer it to the navigation service owner with IT/Networks and Information Security.
ANALYSIS REQUIRED	Operation: assistive-navigation service readiness and coverage validation. Decision interval: the intended journey and supported service version. Minimum evidence: current health and configuration for every required beacon, a route-level field test, current content and verified non-beacon fallback. Method: test end-to-end positioning/instruction at each decision point using supported devices, record error and coverage gaps and keep it explicitly optional. Quantified uncertainty: report critical-evidence completeness as n/N, plus tested decision points/total, horizontal error distribution and longest outage; require 100% critical-point coverage within the owner-defined error bound for a supported-route claim. Safe failure: do not advertise or rely on the beacon route; provide text/map/spoken or staffed directions and open a service fault.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not track devices or people, infer assistive-navigation need, make beacon use mandatory, promise positioning accuracy or bypass security/privacy approval. Do not imply that a beacon service works with a person's device or preferred navigation method unless that exact end-to-end pathway was verified. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, navigation service owner, IT/Networks, Information Security and route owners.
WHY THIS IS USEFUL	Prevents an experimental or partially deployed beacon system from being presented as dependable and keeps a verified non-beacon route available.

AI-050

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

When signs, maps, bookings and live route states disagree, what can we safely publish now and which owner must resolve each conflict?

SENSORS AND TELEMETRY	Proposed evidence: source health, version, timestamp and mapping telemetry for every wayfinding input. Coverage: all claims in the route or destination answer and every physical/digital channel that carries them. Timing/alignment: at retrieval and on each source change; use a common clock. Aggregation: as claim-to-source provenance and conflict sets. Quality gate: require known owner, permission, source version, effective/observed/retrieved times, mapping and health for every decision-critical claim. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: technical freshness cannot determine which owner has authority, and a consistent set of stale sources can still be wrong; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the current source-owner/precedence register and authoritative route, destination, closure and communication decisions (Space Management, Estates, Security, content owners and the Talking Abacws data steward). Corroborating sources: competent on-site inspection and channel-specific published versions. Precedence: current live restriction and competent owner decision outrank schedules, inventories, telemetry, generated text and the May 2021 plan; conflicts are not majority-voted. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: any source beyond its claim-specific age limit, unknown authority, missing permission or superseded version. Conflict handling: keep disagreement visible and refer it to the authoritative owner for that claim, coordinated by the data steward.
ANALYSIS REQUIRED	Operation: claim-level conflict resolution and safe-publication classification. Decision interval: the publication decision and affected journey/event window. Minimum evidence: a named authoritative owner and current evidence for every critical route/destination claim, or an explicit unresolved-conflict state. Method: construct a provenance graph, apply declared precedence, separate factual conflict from timing lag and classify each claim as publish, qualify, check or withhold. Quantified uncertainty: report critical-evidence completeness as n/N, plus conflict count, affected critical claims, source ages and authority gaps; any unresolved critical conflict prevents a complete route claim. Safe failure: publish only non-conflicting qualified facts, name the exact conflict and smallest owner check, and withhold generated directions that depend on it.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not hide or average conflicts, choose an owner by model confidence, expose security-sensitive details or ask the person for extra personal information to resolve source failure. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the data steward, authoritative source owners and the person.
WHY THIS IS USEFUL	Provides the team with a transparent stop rule, a publishable subset of facts and a named owner for the smallest verification step.

Toilets, rest, quiet spaces and amenities

AI-051

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which accessible toilets can we currently describe as open, reachable and not known to be out of service for the required interval?

SENSORS AND TELEMETRY	Proposed evidence: door/service state, out-of-service indicator, alarm-system heartbeat and route/lift status telemetry. Coverage: each designated accessible toilet and every critical link from relevant public areas. Timing/alignment: on state change with a five-minute heartbeat; cleaning/service status on authorised update; use a common clock. Aggregation: by facility and route, with no occupant identity or visit history. Quality gate: require mapped facilities and routes, commissioning, permission, clock skew <=5 seconds, >=95% service-state uptime and last critical update <=5 minutes. Privacy guard: No cameras, audio, identity, duration histories, repeated-use linkage or inference about who uses a toilet. Known limits: a door or vacant indicator cannot prove cleanliness, supplies, transfer space, hardware condition or suitability; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current toilet designation, opening hours, cleaning/service status, fault/closure notices and route status (Estates/Facilities Operations, Cleaning, Security and the local building owner). Corroborating sources: competent facility inspection and current incident instructions. Precedence: a live closure, cleaning restriction or competent failed inspection outranks door/occupancy telemetry and published directories. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: service state older than 5 minutes or inspection outside its stated validity. Conflict handling: keep disagreement visible and refer it to the Facilities or building duty owner.
ANALYSIS REQUIRED	Operation: facility-and-route availability validation. Decision interval: now or the person-selected visit window. Minimum evidence: current open/service state, a verified route and a current inspection for essential features not observable remotely. Method: separate open, reachable, inspected and qualified states; list dependencies such as lifts or access control. Quantified uncertainty: report critical-evidence completeness as n/N, plus critical checks passed/required, route gap count and oldest evidence age; all critical checks are required for a verified available claim. Safe failure: withhold the facility claim, identify the smallest inspection or route check and offer only a verified alternative.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not identify users, reveal occupancy to unrelated parties, infer health/support need, promise immediate access or remotely unlock/lock the facility. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Facilities, Cleaning, Security and the building owner.
WHY THIS IS USEFUL	Enables the team to publish a current option, dispatch a targeted check or direct people to a verified alternative rather than relying on a directory label.

AI-052

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Are the alarm, rails, transfer space, door hardware and other essential features of the intended accessible toilet supported by current competent evidence?

SENSORS AND TELEMETRY	Proposed evidence: alarm power/self-test, door-hardware and asset-presence telemetry where technically appropriate, supplemented by a structured physical inspection. Coverage: each essential feature in the facility, its clear approach and the alarm call path to the responding service. Timing/alignment: alarm heartbeat continuously; full feature inspection after maintenance/change and within the owner-defined service window; use a common clock. Aggregation: by feature and test result, without user activity records. Quality gate: require mapped assets, commissioning, permission, current maintenance release, a competent inspection and an end-to-end alarm response test under authorised procedure. Privacy guard: No recording of who uses, triggers or tests the facility beyond the authorised test role. Known limits: asset presence and self-test cannot prove reach, force, transfer clearance, cleanliness, alarm audibility/response or real-world usability; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current feature specification, maintenance/fault status, cleaning/service record and alarm-response procedure (Facilities/Estates Maintenance, Cleaning, Security or the designated alarm responder and the building owner). Corroborating sources: competent physical inspection and end-to-end alarm test evidence. Precedence: a competent failed inspection or alarm-response test outranks asset inventory, heartbeat and prior pass records. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: test/inspection after a relevant change is absent or beyond its owner-defined validity. Conflict handling: keep disagreement visible and refer it to the competent Facilities/Estates or alarm-response owner.
ANALYSIS REQUIRED	Operation: essential-feature and alarm-path verification. Decision interval: the intended open/service period. Minimum evidence: current pass evidence for every critical physical feature and the complete alarm path, including responder acknowledgement. Method: evaluate each feature separately, require dimensional/force checks where relevant and distinguish self-test from end-to-end response. Quantified uncertainty: report critical-evidence completeness as n/N, plus critical features passed/required, measurement margins with tolerance and alarm test completion time; one failed/missing critical feature prevents a verified claim. Safe failure: mark the facility unavailable or qualified under owner instruction, raise the exact remedial work/test task and direct users to a verified alternative.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer who needs a feature, certify the facility, simulate an alarm outside authorised procedure, or disclose alarm activations beyond operational need. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, competent Facilities/Estates owner, responder and building owner.
WHY THIS IS USEFUL	Enables the team to distinguish a toilet that merely exists from one whose critical features and response path have current evidence.

Toilets, rest, quiet spaces and amenities

AI-053

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Is a Changing Places toilet or other named higher-support facility open, reachable and operational at the required time?

SENSORS AND TELEMETRY	Proposed evidence: facility service/door state, equipment power/fault, alarm heartbeat and route/lift status telemetry. Coverage: each named facility, its specialist equipment and every route dependency from relevant arrival points. Timing/alignment: on state change with five-minute heartbeat; equipment inspection before each declared availability period; use a common clock. Aggregation: by facility, equipment and route, never by user. Quality gate: require current facility designation, mapped/commissioned equipment, permission, maintenance release, all live states <=5 minutes and competent pre-use inspection. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: telemetry cannot prove cleanliness, consumables, sling compatibility, transfer space, staff practice or suitability for every person; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current facility designation, opening arrangements, equipment inventory/maintenance, cleaning status, access rules and route status (Facilities/Estates, Cleaning, Security and the building/service owner). Corroborating sources: the person-stated practical equipment requirement and competent facility inspection. Precedence: current owner closure/inspection and equipment release outrank directory listings, telemetry and historical plans. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: live state older than 5 minutes, inspection outside the declared availability period or equipment specification after change. Conflict handling: keep disagreement visible and refer it to the facility owner with competent equipment maintainer.
ANALYSIS REQUIRED	Operation: specialist-facility readiness and route validation. Decision interval: the requested visit interval. Minimum evidence: verified open/service state, current route, pass evidence for every required equipment feature and any access/staff dependency. Method: map only person-stated requirements to current inspected features; separate facility availability, equipment readiness and route continuity. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified required features/total, route dependency count and oldest evidence age; all non-negotiable requirements must be verified for a positive match. Safe failure: state that the facility is not verified for the requirement, provide owner contact and identify another checked facility or visit arrangement.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer personal care needs, diagnosis or equipment use, store the requirement beyond the task, promise compatibility or authorise use of specialist equipment. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, facility owner, competent maintainer and Security.
WHY THIS IS USEFUL	Enables the team to confirm the actual facility and equipment combination or arrange a verified alternative before the journey.

AI-054

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Can we communicate likely waiting for an accessible toilet using privacy-safe aggregate evidence, without identifying users or constructing visit histories?

SENSORS AND TELEMETRY	Proposed evidence: privacy-preserving vacant/engaged state or external queue-zone counts only where a formal privacy assessment supports them. Coverage: the facility status indicator and a limited external waiting zone, never the interior. Timing/alignment: state on change; queue count in one-minute samples aggregated to five-minute bands and deleted after approved summary retention; use a common clock. Aggregation: by facility/time band with small-cell suppression. Quality gate: require privacy-by-design approval, commissioning, permission, >=95% state capture, no status older than 2 minutes and suppression of counts below 5. Privacy guard: No cameras, audio, identity, access-card data, repeated-use linkage, individual duration or occupancy history. Known limits: engaged duration does not equal wait, queue order or availability of features, and a closed door may not indicate use; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current facility open/service state and the approved privacy/retention design (Facilities, the institutional privacy/data-protection owner and the building owner). Corroborating sources: privacy-safe historical engaged intervals and direct staff observation during exceptional demand. Precedence: facility closure or cleaning status outranks occupancy indicators; privacy constraints outrank analytical convenience. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: status older than 2 minutes, <90% interval coverage or data collected under a different facility/queue configuration. Conflict handling: keep disagreement visible and refer it to the Facilities owner with the privacy/data-protection owner.
ANALYSIS REQUIRED	Operation: privacy-safe wait-range estimation. Decision interval: now and the next short planning interval. Minimum evidence: current open/service status plus >=20 privacy-safe engaged intervals or >=8 comparable time bands with <=10% missingness. Method: estimate facility-level occupied-duration and external queue bands without identifying users; present current state separately from forecast. Quantified uncertainty: report critical-evidence completeness as n/N, plus median and 90th-percentile wait proxy with an 80% interval, coverage and small-cell suppression; no forecast when evidence is sparse. Safe failure: say only occupied/vacant/unknown where authorised, avoid a wait prediction and offer another verified facility.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not identify or track users, infer health or support need, disclose individual occupancy duration, promise availability or use the data for behaviour monitoring. Do not expose live cubicle use, infer who is waiting or retain sequences that could reconstruct an individual visit. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with users, Facilities, the privacy/data-protection owner and building owner.
WHY THIS IS USEFUL	Provides a limited planning aid while protecting dignity and gives the team a clear stop point when privacy-safe evidence is insufficient.

Toilets, rest, quiet spaces and amenities

AI-055

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Where are verified rest seats available along the planned route, and will they remain reachable, stable and unobstructed during the journey?

SENSORS AND TELEMETRY	Proposed evidence: seat asset-presence, non-imaging obstruction, route and local lighting/weather telemetry, supplemented by physical inspection. Coverage: all mapped rest points on the primary and fallback routes, including approach and transfer/circulation space. Timing/alignment: asset/layout on controlled change; obstruction and environmental state every 1-5 minutes; inspection after moves or damage reports; use a common clock. Aggregation: by rest point and route segment, without recording who sits or for how long. Quality gate: require mapped seat assets, permission, current route evidence and a competent inspection of stability and clearance within the owner-defined validity. Privacy guard: No pressure sensing, seat occupancy history, identity or inference about fatigue/stamina. Known limits: asset tags cannot prove stability, comfort, arm support, usable approach or temporary blockage; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current furniture/rest-point inventory, route status, cleaning/maintenance record and local setup/works plan (Estates/Facilities, Cleaning, Space Management and the local area owner). Corroborating sources: competent physical inspection and person-selected preference for spacing or seat features. Precedence: observed condition and current route restriction outrank furniture inventory and historical plan positions. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: inspection after a move/damage report is absent or outside its validity, or route state exceeds its age limit. Conflict handling: keep disagreement visible and refer it to the local Facilities/Estates owner.
ANALYSIS REQUIRED	Operation: rest-point availability and spacing check. Decision interval: the planned route and journey interval. Minimum evidence: current route continuity and a passed inspection for each rest point offered, including clear approach and stability. Method: order verified rest points along the route, calculate spacing and show features without inferring a need to rest. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified rest points/total, maximum spacing with map/survey tolerance and oldest inspection age; unverified points are excluded. Safe failure: provide no rest-supported route claim, request a check or offer a shorter/different verified route chosen by the person.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer fatigue, mobility, diagnosis or likely use, monitor sitting time, reserve seats without authority or promise that a seat will remain free. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Facilities/Estates and local area owner.
WHY THIS IS USEFUL	Enables the team to publish concrete rest opportunities, place or restore seating and expose where a long route has no verified pause point.

AI-056

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which quiet or low-stimulation spaces are open for voluntary short use, and what can we honestly say about their likely condition?

SENSORS AND TELEMETRY	Proposed evidence: sound-level, lighting, temperature, CO2, door/open-state and anonymous density telemetry. Coverage: each designated or owner-approved quiet/rest space and its access route, using representative sensor positions. Timing/alignment: environmental values every 1-5 minutes; availability on change; density in five-minute privacy-safe bands; use a common clock. Aggregation: by space/zone and time band with small-cell suppression. Quality gate: require current designation, room/route mapping, calibrated sensors, permission, >=90% coverage, no critical state older than 10 minutes and a current physical check. Privacy guard: No identity, visit tracking, reason-for-use, distress inference, audio or person-level dwell. Known limits: sensors do not establish subjective calm, privacy, conflict-free use, individual suitability or future availability; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current space designation, opening/booking rules, supervision/safeguarding arrangements where relevant and route status (the space owner, Space Management, Security and Estates). Corroborating sources: the person-selected environmental preferences and current owner inspection. Precedence: the space owner decides availability and purpose; current booking/incident/inspection outranks environmental analytics and labels. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: availability after any booking/status change or environmental readings older than 10 minutes. Conflict handling: keep disagreement visible and refer it to the quiet-space owner or building duty owner.
ANALYSIS REQUIRED	Operation: quiet-space option validation and condition description. Decision interval: now or the requested short-use interval. Minimum evidence: verified open/use status, route and current measurements for each stated non-negotiable preference, with a current owner check. Method: present measured ranges and known activities, filter only by person-selected requirements and avoid a universal calmness score. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified criteria/required criteria, range/tolerance and state age; do not recommend when any non-negotiable criterion is unknown. Safe failure: state no verified match, offer another space/time or refer to the space owner for a direct check.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer distress, mental health, neurotype or reason for use, track visits, promise privacy/quiet or treat voluntary use as an incident signal. Do not label a space therapeutic, calming or suitable for a particular condition; describe only verified features and current operating limits. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, quiet-space owner, Security and Estates.
WHY THIS IS USEFUL	Provides the team with an honest option to offer and identifies whether the right action is a room check, booking change or additional low-stimulation provision.

Toilets, rest, quiet spaces and amenities

AI-057

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Are drinking-water points, catering counters and vending areas reachable and usable for the approach, reach and height requirements a person has stated?

SENSORS AND TELEMETRY	Proposed evidence: water-point service/fault, vending/counter equipment heartbeat, queue-density and route-state telemetry plus competent dimensional inspection. Coverage: each candidate amenity, its approach/clearance, operating controls and complete route. Timing/alignment: service state on change or every 5 minutes; anonymous queues in five-minute bands; dimensions on controlled version; use a common clock. Aggregation: by amenity and zone, with no purchase or person history. Quality gate: require mapped assets, permission, current maintenance/service state, route evidence and competent measurements after any counter/equipment change. Privacy guard: No payment data, purchase history, identity, face/device tracking or inference about diet/health. Known limits: telemetry cannot prove reach, force, cup/container handling, product suitability, staff response or stock; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current amenity location, opening hours, asset status, route and service-owner operating arrangements (Catering, Facilities/Estates, vending/water service owners and Security where access-controlled). Corroborating sources: competent access/height/reach inspection and current fault/service reports. Precedence: live service closure and observed physical setup outrank asset inventory, published hours and historical plans. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: service state older than 5 minutes or dimensional evidence after an unverified equipment/counter change. Conflict handling: keep disagreement visible and refer it to the relevant Catering, Facilities or vending/water owner.
ANALYSIS REQUIRED	Operation: amenity usability-feature and route validation. Decision interval: the intended visit window. Minimum evidence: current open/service state, verified route and evidence for each person-stated non-negotiable approach/control requirement. Method: compare measured features with stated requirements, distinguish independent use from staff-assisted service and show alternatives. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified required features/total, measurement margins with tolerance, queue-state age and unknown stock/service factors. Safe failure: do not claim usability; provide a verified alternative, arrange staff support through the service owner or request inspection.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer health, diet, dexterity or stature, inspect purchases, promise stock or queue time, or operate vending/catering equipment on a person's behalf without agreement. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person and the relevant amenity/service owners.
WHY THIS IS USEFUL	Enables the team to identify an amenity that works for the stated task, fix a specific reach/route barrier or arrange an equivalent service.

AI-058

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Are accessible showers, changing rooms, lockers or related well-being amenities open, operational and ready for the stated use?

SENSORS AND TELEMETRY	Proposed evidence: door/service state, alarm heartbeat, water/temperature fault, equipment/locker status and route telemetry. Coverage: each provided amenity, its critical equipment, privacy boundary and full access route. Timing/alignment: on change with five-minute heartbeat; physical inspection and hygiene/service check within the declared open period; use a common clock. Aggregation: by facility and asset, without user identity or use history. Quality gate: require current facility designation, mapped/commissioned assets, permission, maintenance release, all live states <=5 minutes and competent pre-use inspection. Privacy guard: No cameras/audio, locker identity, duration histories, access-card profiling or inference about personal care/health. Known limits: telemetry cannot prove cleanliness, privacy, reach, transfer space, water comfort, consumables or equipment compatibility; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current facility designation, opening/access rules, cleaning status, equipment maintenance, alarm response and route status (Facilities/Estates, Cleaning, Security and the local service owner). Corroborating sources: the person-stated practical requirement and competent facility inspection. Precedence: current closure, competent inspection and maintenance release outrank directories, telemetry and prior checks. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: live state older than 5 minutes or inspection outside the declared service period. Conflict handling: keep disagreement visible and refer it to the facility owner with competent maintenance/cleaning owners.
ANALYSIS REQUIRED	Operation: amenity readiness and requirement-match check. Decision interval: the intended use interval. Minimum evidence: current open/service state, verified route and current pass evidence for every critical feature the person has stated. Method: map stated requirements to inspected features, separate availability from compatibility and expose any staff/key dependency. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified critical features/total, state age and measurement tolerance; all non-negotiable features must be verified for a positive match. Safe failure: state that the facility is not verified, provide owner contact and offer another checked facility or arrangement.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer personal care, health, gender identity or equipment use, record facility-use history, promise privacy or authorise restricted access. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, facility owner, Cleaning, Estates and Security.
WHY THIS IS USEFUL	Enables the team to confirm the real amenity and route combination or make an alternative arrangement before it becomes a barrier.

Toilets, rest, quiet spaces and amenities

AI-059

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which current location can support an assistance dog's pause, water and toileting needs without blocking a route or breaching a restriction?

SENSORS AND TELEMETRY	Proposed evidence: route, gate, lighting, water-point, weather and grounds-condition telemetry, supplemented by physical inspection. Coverage: each owner-approved relief/rest area and the complete route from public entrances and destinations. Timing/alignment: route/weather every 1-10 minutes; grounds/cleaning inspection on the owner's schedule and after reported issues; use a common clock. Aggregation: by area and route segment, with no dog/person tracking. Quality gate: require current approved area, mapped route, permission, current grounds/cleaning inspection and no critical live source beyond its age limit. Privacy guard: No recognition or tracking of dogs/handlers, visit history or inference about assistance-dog use. Known limits: sensors cannot establish cleanliness, suitability for a particular dog, conflict with wildlife/operations or temporary contamination; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current assistance-dog access policy, owner-approved relief/rest areas, water-point status, route and local restrictions (Estates Grounds, Facilities, Security and the relevant land/building owner). Corroborating sources: competent grounds/cleaning inspection and the person's chosen practical requirements. Precedence: current land/incident restriction and observed grounds condition outrank mapped areas, telemetry and historical practice. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: route/weather status beyond its limit or inspection after any contamination/works report is absent. Conflict handling: keep disagreement visible and refer it to the Grounds or relevant land/building owner.
ANALYSIS REQUIRED	Operation: approved-area and route readiness check. Decision interval: the planned visit interval. Minimum evidence: an owner-approved area, verified route, current grounds condition and any water/cleaning dependency. Method: present distance, surface, lighting, shelter and restrictions separately and let the person decide; do not infer use from dog presence. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified checks/required, route gap count and oldest inspection age; an unverified route or area prevents a usable claim. Safe failure: provide no recommendation, refer to the land/building owner and identify another verified area or practical arrangement.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer disability, identify or track the handler/dog, restrict lawful access based on analytics, promise cleanliness or control gates/water points. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Grounds/Facilities, Security and land/building owner.
WHY THIS IS USEFUL	Enables the team to give a respectful practical option and direct maintenance or route work to the exact area rather than improvising on arrival.

AI-060

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which amenity barrier needs action first, who owns it, and what verified interim arrangement can be offered while it remains unresolved?

SENSORS AND TELEMETRY	Proposed evidence: asset fault/heartbeat, door state, alarm test, non-imaging obstruction and service-status telemetry plus structured reports and inspections. Coverage: all designated accessible toilets, specialist facilities, rest/quiet spaces and key amenities. Timing/alignment: faults on change; service summaries every 5 minutes; reports at submission and inspection at triage; use a common clock. Aggregation: by facility, feature and accountable owner. Quality gate: require mapped assets, current owner, permission, claim-specific age limits and competent confirmation for high-impact or unsensed barriers. Privacy guard: No user identity or health or casework data in operational summaries; protect reporter details and facility-use privacy. Known limits: telemetry may miss hygiene, supplies, manual locks, layout problems and the lived impact of a barrier; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current facility/asset ownership, fault tickets, service standards, closure authority and response procedures (Facilities/Estates, Cleaning, Security, Health and Safety and local service owners). Corroborating sources: structured barrier reports, competent inspection and incident instructions. Precedence: a competent safety/closure decision and current inspection outrank automated severity, telemetry and ticket status. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: live status beyond its limit, report without current location/asset mapping or ticket after a superseding owner update. Conflict handling: keep disagreement visible and refer it to the competent asset/service owner or incident duty lead.
ANALYSIS REQUIRED	Operation: amenity-barrier triage and dependency analysis. Decision interval: immediate operational response plus the agreed restoration target. Minimum evidence: current location/asset, verified impact on an essential feature, accountable owner and a safe interim state. Method: classify by loss of essential function, route alternatives, urgency and affected service rather than inferred user characteristics; link duplicate signals to one case. Quantified uncertainty: report critical-evidence completeness as n/N, plus evidence confidence, affected critical features, alternative count and elapsed time; any possible life-safety/alarm failure goes directly to competent triage. Safe failure: restrict or qualify the facility under owner instruction, provide a verified alternative and escalate without waiting for statistical confirmation.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer who is affected, disclose reporter identity unnecessarily, certify safety, set emergency priority by model score or control/close assets without authority. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the competent service/incident owner and accessibility/inclusion team.
WHY THIS IS USEFUL	Enables the team to protect the essential amenity function now, publish a verified interim option and direct remedial work to the accountable owner.

Services, support routes, events and accompanying people

AI-061

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

When a person states an access requirement before arrival, which current support route applies and who owns the next acknowledged action?

SENSORS AND TELEMETRY	Proposed evidence: privacy-minimised service-directory, queue-state and task-routing telemetry. Coverage: the authorised support channels, service hours and hand-off points needed for the stated practical request; no health or casework systems. Timing/alignment: service status on change; queue summaries every 5-15 minutes; task state only for the active request; use a common clock. Aggregation: by service and task type with small-cell suppression. Quality gate: require current service owner, scope, hours, permissions, retention rule and verified hand-off path; suppress aggregate cells below 10. Privacy guard: Collect only the practical requirement and contact details needed for the task; no diagnosis, health, casework, personal emergency-plan records records or cross-service profile. Known limits: availability telemetry cannot prove expertise, response quality, eligibility or that the person will accept a referral; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the current institutional support directory, service scope, hours, referral rules and named duty/queue owner (the accessibility/inclusion service, student/staff service owners, Security and local operational teams as relevant). Corroborating sources: the person's chosen practical request and consent for any hand-off. Precedence: the person controls what is shared; the receiving service owner decides scope and action; current service instructions outrank cached directories and model routing. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a directory entry after an owner/role change, service status outside its update interval or consent absent for the proposed hand-off. Conflict handling: keep disagreement visible and refer it to the receiving service owner, coordinated by the accessibility/inclusion team.
ANALYSIS REQUIRED	Operation: consent-aware service routing and hand-off validation. Decision interval: from request receipt to the last useful pre-arrival action time. Minimum evidence: a current in-scope service, named owner, open contact route, person permission and only the minimum task information. Method: match the practical task to service scope, show expected response window and verify acknowledgement; do not route by inferred disability or diagnosis. Quantified uncertainty: report critical-evidence completeness as n/N, plus matched scope elements/required, hand-off acknowledgement state and deadline slack; any scope or consent uncertainty blocks automatic hand-off. Safe failure: give the person verified contact options, retain the request with the current team or escalate to a human coordinator without additional disclosure.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer condition or eligibility, use health or casework/personal emergency-plan records data, share the request without permission, promise support or make a professional/service decision. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, accessibility/inclusion team and receiving service owner.
WHY THIS IS USEFUL	Enables the team to route the practical task once, preserve consent and avoid sending the person between services that cannot act.

AI-062

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Has the event or teaching activity completed the access-planning checks required for its actual venue, format, timings and participation pattern?

SENSORS AND TELEMETRY	Proposed evidence: privacy-safe planning-task, room/route, AV/service and equipment-status telemetry. Coverage: the event/session, venue, arrival routes, participation channels and all declared audience-facing services. Timing/alignment: task state on change; operational asset health within the pre-event verification window; use a common clock. Aggregation: by checklist item and accountable owner, not by attendee. Quality gate: require approved checklist version, current owners, explicit permissions, venue/route mapping and competent evidence for every critical item. Privacy guard: No attendee diagnosis, health, casework or personal emergency-plan records records; use only requirements people choose to state and aggregate planning assumptions. Known limits: a completed checklist cannot prove quality, attendee experience or that last-minute changes are accessible; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the current event/teaching plan, venue booking, route/room authority, communication plan and institutional accessibility planning requirements (the event/session owner, Timetabling/Events, Estates, IT/AV, Security and relevant service owners). Corroborating sources: completed task evidence, provider confirmations and current venue inspection. Precedence: current venue/incident status and competent owner evidence outrank a ticked checklist; the event owner remains accountable for the plan. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: any evidence after a venue/time/format change is absent or outside its task validity. Conflict handling: keep disagreement visible and refer it to the event/session owner, with each competent service owner for its item.
ANALYSIS REQUIRED	Operation: critical-planning dependency and readiness assessment. Decision interval: publication deadline through event/session completion. Minimum evidence: an accountable owner and acceptable current evidence for every critical route, room, communication, participation and support item. Method: build a dependency graph, distinguish documented, acknowledged, tested and verified-complete states, and rerun affected checks after change. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified critical items/total, overdue count, change-affected items and oldest evidence age; all critical items are required for ready status. Safe failure: delay or qualify publication, name the blocking item and owner, and change venue/format or provide a tested fallback.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not turn the checklist into an accessibility certificate, infer attendee needs, disclose individual requests broadly, promise inclusion or overrule event/safety owners. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the event/session owner, competent service owners and people attending.
WHY THIS IS USEFUL	Enables the team to stop a preventable planning failure, chase the exact owner and make a venue, format or communication change while there is still time.

Services, support routes, events and accompanying people

AI-063

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Can the person's chosen companion, personal assistant, interpreter or support worker enter, sit and move with them throughout the activity?

SENSORS AND TELEMETRY	Proposed evidence: entrance/access, route, lift, room-layout, seating and ticket/booking status telemetry without identity tracking. Coverage: the complete arrival, check-in, route, seating, breakout and departure sequence for the attendee and accompanying role. Timing/alignment: operational state on change or every 5 minutes; booking/access rule on each authorised update; use a common clock. Aggregation: by dependency and party-size envelope, not by named person. Quality gate: require current access/booking rules, mapped route and seating, permission, all critical live states within age limits and a pre-event human check of any role-dependent process. Privacy guard: No inference about relationship or support reason and no tracking of either person beyond authorised booking/access processing. Known limits: telemetry cannot prove role recognition, confidentiality arrangements, seating quality or staff discretion; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current visitor/ticket/access rules, companion/assistant arrangements, room capacity/layout and route status (the event/session owner, Security, Space Management/Timetabling and venue owners). Corroborating sources: the attendee's chosen request and permission to share the minimum role/logistics information. Precedence: the attendee controls disclosure; current event/access authority and observed layout outrank default ticket rules and generic capacity data. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: rules after a change are not confirmed, live route state exceeds its limit or seating/layout was reset after inspection. Conflict handling: keep disagreement visible and refer it to the event/session owner with Security and venue/space owner.
ANALYSIS REQUIRED	Operation: whole-journey accompaniment continuity check. Decision interval: arrival through departure, including breakouts and room changes. Minimum evidence: authorised entry process, same-route or agreed alternative, adjacent/appropriate seating and access to every planned activity. Method: validate each stage, identify any separation point and distinguish physical, permission, capacity and confidentiality dependencies. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified stages/total, separation-risk count and oldest evidence age; any unresolved critical stage prevents a continuous-accompaniment claim. Safe failure: arrange an authorised process or different room/layout and let the attendee approve any unavoidable alternative before the event.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer the relationship or diagnosis, expose the attendee's requirement, separate the pair without agreement, grant entry or promise seating. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the attendee, accompanying person, event owner, Security and venue/space owners.
WHY THIS IS USEFUL	Enables the team to remove a hidden access or seating break that would otherwise appear only at check-in or during a room change.

AI-064

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Are booked interpreters, captioners, note-taking support and portable assistive equipment confirmed, function-tested and aligned with the session plan?

SENSORS AND TELEMETRY	Proposed evidence: privacy-minimised booking-confirmation, provider check-in, equipment heartbeat, battery/fault and AV/network test telemetry. Coverage: each booked service or portable asset and every technical dependency needed for the planned interaction. Timing/alignment: confirmation on change; equipment health every 5 minutes; end-to-end test in the setup window; use a common clock. Aggregation: by service/equipment task and session reference only. Quality gate: require authorised booking, named owner/provider, minimal data permission, current configuration and successful end-to-end test for every critical dependency. Privacy guard: No diagnosis, case notes, speech or work content, provider performance profiling or reuse of service need beyond the session. Known limits: confirmed status cannot prove provider arrival, service quality, language/domain match, consent or suitability for every interaction; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current authorised booking, service specification, provider confirmation, equipment inventory/maintenance and session interaction plan (the event/session owner, accessibility/inclusion team, provider, IT/AV and equipment owner). Corroborating sources: the person-selected service requirement and current end-to-end test evidence. Precedence: the person-approved requirement and provider/service-owner confirmation outrank generic booking status; a failed test or cancellation outranks prior confirmation. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: confirmation after a schedule/room/format change is absent, provider acknowledgement exceeds its validity or test configuration has changed. Conflict handling: keep disagreement visible and refer it to the session owner and contracted/internal service owner.
ANALYSIS REQUIRED	Operation: service-and-equipment readiness dependency check. Decision interval: booking confirmation through session completion. Minimum evidence: confirmed provider/equipment, correct time/location/format, tested technical path and a fallback for each critical service. Method: map the session interaction plan to provider/equipment tasks, verify hand-offs and distinguish booked, acknowledged, arrived/connected, tested and ready. Quantified uncertainty: report critical-evidence completeness as n/N, plus verified critical tasks/total, acknowledgement age, test cases passed and fallback coverage; all critical tasks are required for ready status. Safe failure: escalate the exact dependency, deploy a tested authorised fallback, adjust interaction format or postpone/relocate under session-owner control.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not disclose why support is booked, inspect speech or work content, rate providers from participant behaviour, promise service quality or authorise substitutions without agreement. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, session owner, provider and technical/equipment owners.
WHY THIS IS USEFUL	Enables the team to distinguish booked from actually ready and protect participation when a provider, device or signal path fails.

Services, support routes, events and accompanying people

AI-065

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Can registration, screening and check-in be completed without an avoidable queue, inaccessible counter or unnecessary personal disclosure?

SENSORS AND TELEMETRY	Proposed evidence: anonymous queue counts, service-desk/counter state, self-service kiosk health, door/gate state and ticketing-system heartbeat. Coverage: all authorised check-in routes, counter positions, waiting zones and alternative/manual processes. Timing/alignment: queue counts every minute aggregated to five-minute bands; system/asset state on change; use a common clock. Aggregation: by process and zone with small-cell suppression. Quality gate: require privacy assessment, mapped processes/assets, permission, >=90% queue coverage, system health within 2 minutes and a current physical/process inspection. Privacy guard: No face recognition, device/card tracking, demographic inference, identity linkage to queue behaviour or collection beyond the authorised check-in need. Known limits: telemetry cannot prove staff practice, communication clarity, counter reach, privacy, paperwork burden or how a person experiences screening; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current registration data requirements, visitor/security process, ticket/identity policy, counter/kiosk inventory and event access rules (the event owner, Security, Registration/Reception, Information Governance and venue owner). Corroborating sources: the person-selected practical requirements and a current observed process check. Precedence: lawful security/identity requirements and current Security instruction outrank convenience analytics; no extra data may be requested by the model. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: process or form after a change has not been checked, queue state older than 5 minutes or kiosk/counter inspection outside its validity. Conflict handling: keep disagreement visible and refer it to Security or the registration/reception owner.
ANALYSIS REQUIRED	Operation: check-in process accessibility and queue alternative assessment. Decision interval: the arrival windows for the event/service. Minimum evidence: at least one authorised route with verified physical access, communication option and minimum lawful data demand, plus current queue/process state. Method: map each process step, identify physical/information dependencies and compare staffed, mobile or pre-check alternatives without profiling users. Quantified uncertainty: report critical-evidence completeness as n/N, plus steps verified/total, current and 90th-percentile wait with interval when >=8 comparable windows exist, and unresolved data-demand issues. Safe failure: avoid a wait claim, open an authorised alternative/manual route, deploy staff or re-time arrivals under owner control.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer disability or identity risk, collect extra health or casework data, waive lawful screening, deny entry, promise queue time or control security systems. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, Security, registration/reception and event/venue owner.
WHY THIS IS USEFUL	Enables the team to remove a process barrier, staff an alternative counter or adjust arrival guidance without weakening lawful security requirements.

AI-066

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Have stewards and service desks received the practical access instructions they need, while medical, diagnostic and casework information remains excluded?

SENSORS AND TELEMETRY	Proposed evidence: privacy-minimised briefing publication, acknowledgement and shift-coverage telemetry. Coverage: only the roles, locations, times and practical actions needed for the event/service; no personal health or casework systems. Timing/alignment: on approved briefing issue/update and at shift handover; use a common clock. Aggregation: by role/shift and task, not by attendee or diagnosis. Quality gate: require approved minimum-information briefing, current role roster, permission, version control and human scenario/knowledge check for critical actions. Privacy guard: No diagnosis, health, neurotype, distress, casework, personal emergency-plan records detail or personal narrative; identify a person only when operationally necessary and authorised. Known limits: acknowledgement does not prove understanding, competence, recall or correct action in context; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the approved event/service plan, role roster, practical task instructions and escalation contacts (the event/service owner, Security, accessibility/inclusion team and relevant operational owners). Corroborating sources: the person's consented minimum practical instruction where an individual arrangement is necessary. Precedence: the event/service owner approves the role briefing; the person controls individual disclosure; current incident command overrides routine briefing. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: an acknowledgement to a superseded version, roster after shift change or instruction outside its effective period. Conflict handling: keep disagreement visible and refer it to the event/service duty owner.
ANALYSIS REQUIRED	Operation: minimum-information briefing coverage and competency check. Decision interval: briefing issue through the operational shift. Minimum evidence: current approved briefing, every critical role covered, acknowledgement and a checked escalation path. Method: map critical tasks to roles/shifts, test a small set of scenario questions and expose uncovered periods without adding personal explanations. Quantified uncertainty: report critical-evidence completeness as n/N, plus critical roles briefed/required, scenario checks passed and uncovered minutes; 100% critical-role coverage is required for ready status. Safe failure: brief the missing role, add an authorised supervisor or remove/alter the dependent activity until coverage is verified.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not disclose diagnosis, health, casework or personal emergency-plan records information, infer a person's needs, promise staff behaviour or replace professional training and supervision. Briefings must contain task-level instructions only and must not expose a diagnosis, case history or reason for the chosen requirement. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, event/service owner, Security and operational line managers.
WHY THIS IS USEFUL	Enables the team to give staff enough to act correctly while preventing unnecessary disclosure and revealing exactly where shift coverage is missing.

Services, support routes, events and accompanying people

AI-067

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Are general emergency and disruption instructions available in accessible formats with the current competent owner and contact route clearly shown?

SENSORS AND TELEMETRY	Proposed evidence: emergency-content version, public-address/display/platform health and route/lift/fire-system status telemetry only as authorised. Coverage: general public arrangements, affected zones and each promised communication channel; exclude personal emergency-plan records. Timing/alignment: content on controlled change; channel/system health continuously or at least every minute during an incident/test; use a common clock. Aggregation: by message/version, zone and channel, never by individual. Quality gate: require emergency-owner approval, current version/effective time, channel mapping, permission and tested alternative formats under competent procedures. Privacy guard: No health, casework or personal emergency-plan records, person tracking or inference about who needs assistance. Known limits: telemetry cannot establish personal evacuation suitability, comprehension, responder availability or incident conditions outside coverage; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current general emergency plan, incident procedures, public instructions, competent owner contacts and authorised message templates (Emergency Planning, Fire Safety, Security and building/service owners). Corroborating sources: current incident command instructions and competent exercises/tests. Precedence: incident command and competent emergency owners always outrank generated guidance, telemetry, routine plans, room bookings and historical maps. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: any plan/contact after a superseding approval, channel status beyond its incident age limit or test before a material system/process change. Conflict handling: keep disagreement visible and refer it to incident command or the competent emergency plan owner.
ANALYSIS REQUIRED	Operation: general-arrangement publication and cross-format readiness check. Decision interval: normal operation, planned event and any active incident period. Minimum evidence: current owner-approved general instructions, current contact route and equivalent essential content in every promised format/channel. Method: compare action/location/time/contact elements, verify channel delivery and label all person-specific decisions as requiring direct competent planning. Quantified uncertainty: report critical-evidence completeness as n/N, plus essential elements matched/total, channels/zones tested and plan/contact version age; any critical mismatch blocks a complete publication claim. Safe failure: publish only current owner-approved facts and contacts, identify the unavailable format/channel and defer all incident action to command.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not use health, casework or personal emergency-plan records, infer who needs assistance, give person-specific emergency advice, certify safety or direct/control an incident response. General information must not be presented as a personal emergency plan or as confirmation that assistance will be available. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with incident command, competent emergency owners and the person.
WHY THIS IS USEFUL	Provides the team with a current, multi-format general information baseline while making clear when a person must speak with the competent emergency owner.

AI-068

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Can the service desk arrange route assistance, portable seating or equipment through one authorised hand-off without making the person repeat sensitive information?

SENSORS AND TELEMETRY	Proposed evidence: privacy-minimised task, asset availability and staff/shift acknowledgement telemetry. Coverage: only the practical task, time, location, contact route and responsible services needed for the arrangement; no health, casework or personal emergency-plan records systems. Timing/alignment: on authorised task-state change with owner acknowledgement and completion evidence; use a common clock. Aggregation: by task and event reference, using minimal pseudonymous identifiers where necessary. Quality gate: require explicit permission, data minimisation, current task owner, retention deadline, asset/service readiness and competent completion evidence. Privacy guard: No diagnosis, narrative case notes, repeated disclosure, cross-event profile or sharing beyond the minimum authorised delivery chain. Known limits: workflow completion cannot prove quality, staff arrival, equipment fit or that the person accepts the arrangement; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the person-approved practical request, current service/asset directory, staff/equipment availability and task ownership (the service desk, accessibility/inclusion team, Estates/Facilities, Security and equipment/service owners). Corroborating sources: authorised hand-off and completion acknowledgement. Precedence: the person controls what is shared; each owner receives only the task detail needed; current safety/security instruction outranks the arrangement. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: task after a time/location change is not revalidated, owner acknowledgement exceeds its validity or permission/retention rule is absent. Conflict handling: keep disagreement visible and refer it to the service desk coordinator with each delivery owner.
ANALYSIS REQUIRED	Operation: consent-preserving task orchestration and completion validation. Decision interval: request receipt through the agreed delivery/use window. Minimum evidence: one approved task description, accountable owners, service/asset readiness and acceptable completion evidence for every dependency. Method: tokenise the request reference, share least information, track dependencies and separate acknowledged, dispatched, physically verified and person-confirmed states. Quantified uncertainty: report critical-evidence completeness as n/N, plus critical tasks verified/total, overdue dependencies and oldest evidence age; all critical tasks must be verified before stating ready. Safe failure: escalate the exact task, communicate the practical limitation once, and offer a verified alternative without seeking additional sensitive detail.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer condition, use health or casework/personal emergency-plan records data, ask the person to repeat the reason, disclose beyond need-to-know, promise staff/equipment or control assets. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, service desk, accessibility/inclusion team and delivery owners.
WHY THIS IS USEFUL	Enables the team to deliver the practical arrangement once, protect the person from repeated disclosure and expose the owner blocking completion.

Services, support routes, events and accompanying people

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

AI-069

Will a room move, cancellation or delay reach attendees and accompanying people through selected channels before they decide to travel?

SENSORS AND TELEMETRY

Proposed evidence: authorised contact-channel, message-version and delivery-status telemetry. Coverage: the affected event/session contacts and public channels only; accompanying-person contacts included only with explicit permission. Timing/alignment: on approved change publication, delivery attempt and retry until the decision deadline; use a common clock. Aggregation: by message version, channel and event; minimise person-level retention. Quality gate: require current authorised contact set, selected channels, approved message, clock alignment within 1 minute, privacy permission and traceable minimal retention. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: delivery does not prove attention, comprehension, current contact details or successful rerouting; missing, stale or unhealthy evidence is unknown.

AUTHORITATIVE SUPPORTING DATA

Owners and primary records: the approved booking/event change, authoritative room/route status, contact list and communication preferences valid for the event (the event/session owner, Timetabling/Space Management and institutional contact/channel owners). Corroborating sources: the person's permission for accompanying-person communication and public status channels. Precedence: the event/operational owner confirms the change; the event owner controls recipients and message; current version outranks earlier delivery attempts. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: contact/preferences outside the event purpose, message superseded, or delivery after the last useful decision time. Conflict handling: keep disagreement visible and refer it to the event/session owner and contact-data owner.

ANALYSIS REQUIRED

Operation: deadline-aware authorised notification coverage. Decision interval: change approval to the last useful travel/reroute decision time. Minimum evidence: one current approved message, authorised recipient/channel set and at least one viable delivery route for each contact where person-level status is permitted. Method: deduplicate, send the current version, compare delivery timestamps with the decision deadline and separate attendee/companion permissions. Quantified uncertainty: report critical-evidence completeness as n/N, plus successful authorised channel/contacts, version conflicts and late/unknown cases; never equate delivery with understanding or attendance. Safe failure: escalate unknown cases to the event owner for an authorised alternative and prepare verified on-site route/help arrangements.

ANSWER BOUNDARY

Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not disclose why a person needs a channel or companion contact, infer attendance, contact anyone without authority, promise receipt or reuse preferences across events. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, event/session owner and contact/channel owners.

WHY THIS IS USEFUL

Enables the team to act before travel, avoid inconsistent versions and focus manual contact on the cases that still lack an authorised delivery route.

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

AI-070

Which aggregate demand patterns justify changes to staffing, equipment, service hours or event support without profiling any individual?

SENSORS AND TELEMETRY

Proposed evidence: privacy-safe task counts, equipment bookings, service contacts, queue bands and anonymous attendance/zone counts. Coverage: defined services, assets, events and time bands with no person linkage across visits or datasets. Timing/alignment: operational events at source; analysis in weekly, termly or annual planning windows; use a common clock. Aggregation: by service type, location and time band with small-cell suppression. Quality gate: require consistent definitions, current permissions, provenance, deduplication rules, >=80% period coverage and suppression of cells below 10. Privacy guard: No diagnosis, health or casework/personal emergency-plan records data, person-level histories, demographic inference or cross-service linkage. Known limits: recorded demand excludes unmet or unreported need, service design affects contact volume and counts do not reveal why support was requested; missing, stale or unhealthy evidence is unknown.

AUTHORITATIVE SUPPORTING DATA

Owners and primary records: current service definitions, staffing rotas, equipment inventory, event/timetabling plans and approved operational demand records (the accessibility/inclusion team, service owners, Events/Timetabling, HR/workforce owners and equipment owners). Corroborating sources: structured barrier feedback and known periods of service interruption or changed eligibility. Precedence: owners define service scope and denominators; current operational changes must be reflected before comparing periods; aggregate analytics do not set staffing automatically. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: data before a definition/service/process change without harmonisation or periods with <80% coverage. Conflict handling: keep disagreement visible and refer it to the relevant service owner with institutional workforce/resource governance.

ANALYSIS REQUIRED

Operation: privacy-preserving demand, capacity and scenario analysis. Decision interval: agreed weekly/termly planning periods and named future event scenarios. Minimum evidence: consistent demand definitions, usable denominator/context, current staffing/equipment capacity and at least 8 comparable periods for trend/forecast claims. Method: calculate rates and peak distributions, distinguish contacts from completed support and test reversible staffing/equipment scenarios without predicting individuals. Quantified uncertainty: report critical-evidence completeness as n/N, plus counts, suppressed cells, 95% intervals, missingness and scenario ranges; no forecast when definitions changed or comparable periods <8. Safe failure: use qualitative owner judgement, commission better aggregate capture and trial a limited reversible resource change.

ANSWER BOUNDARY

Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer disability prevalence, diagnosis, individual future demand, distress or productivity; identify small groups; or automate staffing, eligibility or funding decisions. Do not turn aggregate service demand into a prediction about any named person, group identity or future attendance. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with service owners, workforce/resource governance and affected communities.

WHY THIS IS USEFUL

Supports transparent staffing and equipment planning while exposing hidden demand, coverage gaps and the uncertainty around any scenario.

Barriers, feedback, incidents, governance and improvement

AI-071

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which new barriers were reported or detected today, what essential function do they affect, and which competent owner must respond first?

SENSORS AND TELEMETRY	Proposed evidence: asset fault/heartbeat, route/room/service state and privacy-minimised structured barrier-report telemetry. Coverage: all public access routes, rooms, amenities and services represented in the catalogue, linked to current asset/location ownership. Timing/alignment: faults on change; reports at submission; triage view refreshed at least every 5 minutes during service hours; use a common clock. Aggregation: by barrier, asset/location, service and owner, with duplicate linking rather than person linking. Quality gate: require current mapping, owner, permission, source health, observed/retrieved times and competent confirmation for any high-impact or unsensed condition. Privacy guard: Minimise reporter details, protect contact data, exclude diagnosis/health or casework/personal emergency-plan records data and do not link reports to attendance. Known limits: sensor faults can be false or incomplete, reports are selective, and severity cannot be inferred from reporter characteristics; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current asset/location/service ownership, live closure/fault decisions, helpdesk/barrier workflow and response standards (Estates, Security, Space Management, IT/AV, Facilities and local service owners). Corroborating sources: structured reports, competent inspection and incident instructions. Precedence: a competent safety/closure decision and observed condition outrank automated severity, historical patterns and ticket labels. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: live state beyond its source-specific limit, location/owner mapping unresolved or report superseded by a current inspection. Conflict handling: keep disagreement visible and refer it to the competent asset/service owner or incident lead.
ANALYSIS REQUIRED	Operation: real-time barrier deduplication, triage and ownership assignment. Decision interval: today's operational window and any active incident. Minimum evidence: current location/asset, evidence of the affected function, accountable owner and a safe interim status for each high-impact item. Method: merge only evidence about the same asset/event, classify loss of essential function and route/service alternatives, and keep reporter impact as stated rather than inferred. Quantified uncertainty: report critical-evidence completeness as n/N, plus evidence confidence, duplicate-source count, alternative count and elapsed time; possible life-safety or total-route loss bypasses automated ranking. Safe failure: escalate immediately to competent triage, qualify/withdraw affected answers and publish a verified alternative or unknown state.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer disability, health or severity from reporter identity, expose reporter details, close/control an asset, or replace emergency/safety triage. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the competent service/incident owner and accessibility/inclusion team.
WHY THIS IS USEFUL	Provides the team with one actionable live queue with the right owner and interim communication instead of fragmented sensor alarms and reports.

AI-072

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which barriers recur after earlier tickets were closed at the same asset, place or service, and when should a root-cause investigation be triggered?

SENSORS AND TELEMETRY	Proposed evidence: versioned barrier tickets, asset fault/state, maintenance completion and privacy-safe structured feedback telemetry. Coverage: the same mapped asset/location/service across incidents, remedial works and verified post-work observations. Timing/alignment: on each report, fault, completion and verification event; analyse in agreed monthly/termly windows; use a common clock. Aggregation: by asset/location and failure mode, never by reporter or affected person. Quality gate: require stable asset/location IDs, current owner mapping, provenance, permissions, comparable definitions and acceptable closure evidence for each resolved episode. Privacy guard: No reporter identity in trend outputs, no health or casework data and no linkage to personal schedules or attendance. Known limits: duplicate reporting, changed definitions, incomplete closure evidence and differing exposure can create false recurrence patterns; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current work orders, closure reasons, remedial work evidence, post-work verification and asset/service change history (the relevant service owner, Estates/Facilities/IT/AV as applicable and the accessibility/inclusion team). Corroborating sources: competent inspection findings and structured barrier reports. Precedence: competent root-cause findings and current asset condition outrank ticket labels; a closed ticket without acceptable verification is not a resolved barrier. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: episodes before an asset redesign/definition change unless explicitly harmonised, or closure evidence outside the approved verification method. Conflict handling: keep disagreement visible and refer it to the competent asset/service owner.
ANALYSIS REQUIRED	Operation: recurrence detection and root-cause assessment trigger. Decision interval: a defined rolling 6- or 12-month improvement window. Minimum evidence: at least two independently verified post-closure recurrences of the same functional failure, with comparable exposure/context and current ownership. Method: link episodes by stable asset and failure mode, measure time-to-recurrence, distinguish unresolved from genuinely restored, and assess maintenance and change context. Quantified uncertainty: report critical-evidence completeness as n/N, plus recurrence count, time-to-recurrence range and 95% interval for rate when a denominator exists; do not call recurrence from unverified duplicates. Safe failure: retain a suspected-recurrence flag, commission competent inspection/root-cause assessment and stop repeating the same unverified fix.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not attribute recurrence to users or staff without investigation, identify reporters, infer personal impact, or auto-direct disciplinary or procurement action. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the competent asset/service owner and governance body.
WHY THIS IS USEFUL	Enables the team to escalate chronic failures, challenge premature closure and invest in root-cause work rather than repeatedly treating symptoms.

Barriers, feedback, incidents, governance and improvement

AI-073

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Are high-impact barriers receiving timely triage, a verified interim arrangement and acceptable closure evidence against the current service target?

SENSORS AND TELEMETRY	Proposed evidence: barrier/ticket state, owner acknowledgement, interim-control status, asset/service recovery and verification telemetry. Coverage: all barriers classified by loss of essential function across routes, rooms, communication, amenities and services. Timing/alignment: on every workflow or asset-state change; dashboard refreshed at least every 15 minutes for active high-impact cases; use a common clock. Aggregation: by barrier class, owner and elapsed-time band with protected case details. Quality gate: require current case/asset mapping, owner, service target version, permission, immutable timestamps and competent verification of interim and final states. Privacy guard: Exclude diagnosis/health or casework/personal emergency-plan records data from operational analytics; minimise reporter/person details and suppress small group reporting. Known limits: workflow timestamps do not prove impact, safe interim control, remedial work quality or that a person can use the alternative; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current barrier severity/triage procedure, service targets, owner assignments, closure authority and acceptable evidence definitions (the accessibility/inclusion team, Estates/Facilities/IT/AV/Security and relevant service governance owners). Corroborating sources: competent triage, interim arrangement evidence and post-resolution verification. Precedence: competent safety/incident triage overrides target timers and model priority; a ticket status does not outrank observed unresolved condition. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: a case without current owner/target version or resolution evidence that does not meet the approved acceptance method. Conflict handling: keep disagreement visible and refer it to the competent service owner and governance escalation route.
ANALYSIS REQUIRED	Operation: service-target compliance and interim-control sufficiency analysis. Decision interval: from verified barrier onset/report to accepted resolution. Minimum evidence: verified impact class, owner acknowledgement, target clock rule, interim arrangement where needed and competent closure evidence. Method: calculate acknowledgement, interim-control and resolution times separately; pause clocks only under explicit policy and independently check all overrides. Quantified uncertainty: report critical-evidence completeness as n/N, plus median/90th-percentile times, on-target proportion with 95% Wilson interval, overdue high-impact count and unverified closures; do not combine incomparable classes. Pause or reset service clocks only under an explicit rule, and expose every override in the case evidence. Safe failure: escalate overdue or unprotected cases, withdraw affected service claims and retain the case open until competent verification.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer impact from diagnosis or identity, expose case details, let a model downgrade a safety issue, certify resolution or close/authorise assets. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the competent service owner, governance lead and affected people.
WHY THIS IS USEFUL	Shows whether the organisation is protecting people now as well as fixing assets later, and identifies the owner and clock behind each overdue case.

AI-074

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which access-related incidents or near misses need immediate protective action and competent investigation, and what evidence may lawfully be preserved?

SENSORS AND TELEMETRY	Proposed evidence: authorised asset/alarm/route state, incident timestamps and privacy-minimised report telemetry. Coverage: the affected assets, locations, services and decision period only; no broad person tracking or content surveillance. Timing/alignment: preserve relevant state at incident time under an approved evidence-hold process; live protective status on change; use a common clock. Aggregation: as event-specific evidence with strict access control and retention. Quality gate: require legal/incident authority, chain of custody, source mapping, clock-offset record, permissions and immutable provenance; independently verify critical evidence health. Privacy guard: No health or casework/personal emergency-plan records records, unnecessary identity, raw speech or work content or speculative linkage across datasets. Known limits: telemetry may be incomplete, clock-misaligned or unable to capture human context; absence of a signal does not disprove an incident; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the current incident-reporting procedure, emergency/safety authority, asset logs, closure decisions and evidence-retention rules (Incident Command, Health and Safety, Security, the affected service/asset owner and Information Governance). Corroborating sources: first-hand accounts volunteered under the proper process and competent inspection/investigation evidence. Precedence: incident command and competent investigators control protective action and evidence use; telemetry and generated narratives are supporting evidence only. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: data outside the incident window, unknown chain of custody, unverified clock offset or retention/permission absent. Conflict handling: keep disagreement visible and refer it to the competent incident investigator or command lead.
ANALYSIS REQUIRED	Operation: incident-evidence preservation and protective-action triage. Decision interval: immediate safety response followed by the authorised investigation period. Minimum evidence: a competent incident owner, protected current state, verified evidence provenance/clock and a lawful minimal evidence set. Method: separate facts, accounts, system states and hypotheses; build a timeline with explicit source/clock uncertainty and never assign personal fault automatically. Quantified uncertainty: report critical-evidence completeness as n/N, plus source coverage, maximum clock uncertainty, unresolved conflicts and evidence gaps; any plausible immediate danger triggers competent action without waiting for analytical confidence. Safe failure: defer to command, restrict the affected area/service under owner authority, preserve only lawful evidence and state what remains unknown.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not identify or blame people by analytics, use health or casework/personal emergency-plan records records, inspect speech or work content, make legal findings, direct emergency response or disclose incident data improperly. Do not identify or blame people through analytical linkage, and do not preserve data beyond the authorised incident purpose and retention period. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with incident command, competent investigators, Information Governance and affected people.
WHY THIS IS USEFUL	Enables the team to protect people immediately, preserve a trustworthy evidence trail and avoid speculative automated conclusions during investigation.

Barriers, feedback, incidents, governance and improvement

AI-075

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Before works, moves or service changes start, have access impacts and viable alternatives been verified for every affected period?

SENSORS AND TELEMETRY	Proposed evidence: works/closure boundary, route/asset state, temporary sign, lighting and alternative-route telemetry. Coverage: all affected entrances, routes, rooms, amenities, communications and services across each project phase. Timing/alignment: project plan on controlled change; live boundary/asset state on change or every 5 minutes; inspection before each phase opens; use a common clock. Aggregation: by phase, location, affected function and alternative. Quality gate: require approved phase mapping, commissioning/permission for temporary sensing, current owner contacts and competent pre-opening inspection of every critical alternative. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: plans cannot prove barrier placement, contractor practice, temporary surface condition or that an alternative works in reality; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current works/move/change plan, risk/access assessment, closures, phasing, temporary routes/services and communication plan (Estates Projects, Space Management, Security, Health and Safety, contractors and affected service owners). Corroborating sources: competent site inspection, contractor briefing/acknowledgement and affected-community input. Precedence: current incident/safety instruction and observed site condition outrank project drawings, schedules and historical plans; project owner approves phase changes. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: plan after a phase/change is not reapproved or inspection before the current phase is absent/outside validity. Conflict handling: keep disagreement visible and refer it to the project/change owner with competent safety and operational owners.
ANALYSIS REQUIRED	Operation: phase-based accessibility impact and alternative-path validation. Decision interval: each works/change phase, including setup and recovery. Minimum evidence: all affected essential functions identified, one verified alternative or explicit managed arrangement for each, current inspection and owner-approved communication. Method: trace dependencies by phase, test alternatives end to end, identify single points of failure and revalidate after every material change. Quantified uncertainty: report critical-evidence completeness as n/N, plus affected functions covered/total, critical alternatives verified/required and change-affected checks; 100% critical-function coverage is required before a phase opens. Safe failure: delay or modify the phase under owner authority, close the unverified route/service and communicate a verified alternative or non-availability.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not certify project compliance, infer who will be affected, authorise construction/closure, weaken safety controls or promise that temporary arrangements will suit every person. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the project/change owner, competent safety owners, service owners and affected people.
WHY THIS IS USEFUL	Provides the team with a phase-opening decision and prevents temporary access from becoming an afterthought once barriers are already in place.

AI-076

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which inspections, maintenance tasks and access actions are due, overdue or awaiting acceptable completion evidence?

SENSORS AND TELEMETRY	Proposed evidence: asset maintenance, inspection schedule, task-state, fault and post-work verification telemetry. Coverage: all route, room, communication, amenity and support assets/actions represented in published answers. Timing/alignment: on every schedule/task/fault change; due-status recalculated daily and after critical incidents; use a common clock. Aggregation: by asset/action, competent owner and evidence state. Quality gate: require stable asset/action IDs, current owner, approved interval/trigger, permission, immutable timestamps and versioned acceptance evidence. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: a closed task can lack acceptable evidence, and schedule compliance does not prove current condition; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current asset registers, competent inspection regimes, maintenance plans, action owners, due rules and acceptance criteria (Estates/Facilities/IT/AV/Security, Space Management and accessibility governance owners). Corroborating sources: fault history, change records, competent completion certificates or observed verification. Precedence: competent statutory/safety regimes and owner-defined triggers outrank generated due dates; observed failure can make a task due immediately. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: schedule/owner after a change is not updated or completion evidence fails the current acceptance method. Conflict handling: keep disagreement visible and refer it to the competent asset/action owner and governance escalation route.
ANALYSIS REQUIRED	Operation: due-state reconciliation and evidence-quality check. Decision interval: current operational planning and the next agreed maintenance window. Minimum evidence: authoritative due rule, last acceptable completion, current asset/action owner and any event-triggered need for every critical item. Method: calculate due/overdue state from approved rules, separate completed from accepted and prioritise unresolved critical function loss over calendar age alone. Quantified uncertainty: report critical-evidence completeness as n/N, plus due, overdue and unverified-complete counts, days overdue and critical-function coverage; no accepted-complete status without current evidence. Safe failure: leave the item open, qualify affected published answers and escalate the exact missing inspection/evidence to the competent owner.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not certify compliance, invent maintenance intervals, close tasks from telemetry alone, authorise work or expose sensitive asset/security information unnecessarily. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with competent maintenance/inspection owners and governance leads.
WHY THIS IS USEFUL	Enables the team to challenge evidence-free closure, protect published information and focus maintenance on overdue critical access functions.

Barriers, feedback, incidents, governance and improvement

AI-077

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which improvement option should be prioritised when impact, recurrence, inclusion benefit, cost, disruption, deliverability and evidence confidence are compared?

SENSORS AND TELEMETRY	Proposed evidence: privacy-safe barrier, recurrence, asset-condition, service-performance and project/cost telemetry. Coverage: candidate improvements with current owners, affected functions and comparable decision evidence; no person-level profiling. Timing/alignment: operational data at source; option appraisal at agreed quarterly/annual windows and after material evidence changes; use a common clock. Aggregation: by option, function, location and scenario with small-cell suppression. Quality gate: require current definitions, provenance, permissions, comparable denominators, owner-assessed cost/deliverability ranges and explicit community/stakeholder input. Privacy guard: No diagnosis/health or casework/personal emergency-plan records data, individual impact scoring, small-group exposure or inferred protected characteristics. Known limits: recorded barriers undercount unmet need, cost estimates change, metrics are not fully comparable and values cannot be derived from sensors; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: current strategic objectives, legal/policy duties, barrier evidence, asset plans, cost ranges, disruption constraints and decision governance (accessibility governance, Estates/Finance/Projects, service owners and authorised decision bodies). Corroborating sources: competent technical appraisal and input from affected people gathered through appropriate inclusive processes. Precedence: legal/safety obligations and competent decisions are constraints, not model weights; decision makers set values and may override ranking with reasons. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: evidence/cost after material change, unresolved option ownership or incomparable definitions without adjustment. Conflict handling: keep disagreement visible and refer it to the authorised governance/portfolio decision body.
ANALYSIS REQUIRED	Operation: multi-criteria option appraisal with sensitivity analysis. Decision interval: the named planning/funding cycle and implementation horizon. Minimum evidence: defined options, mandatory constraints, comparable evidence, cost/disruption ranges, accountable owners and explicit stakeholder-agreed criteria. Method: filter mandatory obligations, score remaining options using published criteria, show distributional effects and test rank sensitivity rather than output one opaque priority score. Quantified uncertainty: report critical-evidence completeness as n/N, plus input ranges, evidence grades and rank under +/-20% weights and cost uncertainty; unstable options are presented as a decision set, not a winner. Safe failure: state that ranking is not robust, commission missing appraisal/community input and defer the authorised decision rather than inventing precision.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer whose life matters more, use diagnosis or individual data, automate legal/financial decisions, certify compliance or authorise projects/funding. A ranking is decision support only; it must not override statutory duties, urgent protective action, competent judgement or commitments already made to affected people. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the authorised governance body, competent professionals and affected communities.
WHY THIS IS USEFUL	Provides a traceable investment discussion, exposes value judgements and shows which evidence would genuinely change the priority decision.

AI-078

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

After an intervention, did the targeted barrier actually reduce for the intended function and period, with evidence sufficient for the owner to accept the outcome?

SENSORS AND TELEMETRY	Proposed evidence: pre/post asset state, environmental/flow/service telemetry and privacy-safe structured barrier reports. Coverage: the changed asset/service, affected route/room/function and a comparable control or baseline where feasible. Timing/alignment: continuous or event-level capture across defined pre and post windows; post-work inspection at handover and after settling; use a common clock. Aggregation: by function/location/time band, never by individual outcome. Quality gate: require current mapping, comparable definitions/sensors, permissions, calibration, >=80% period coverage, documented change time and competent handover/inspection evidence. Privacy guard: No health, productivity, distress or person-level before/after outcome; protect reporter details and suppress small cells. Known limits: other changes, season, timetable, reporting behaviour and regression to the mean can mimic improvement; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the approved improvement objective, baseline evidence, completion/handover record, acceptance criteria and current operating context (the project/service owner, accessibility governance, Estates/IT/AV/Facilities as applicable and affected service owners). Corroborating sources: competent inspection and inclusive feedback gathered through authorised methods. Precedence: competent acceptance and current observed condition outrank project completion status; analytics cannot certify success or compliance. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: pre/post periods with material incomparable changes, evidence before commissioning or post data below coverage threshold. Conflict handling: keep disagreement visible and refer it to the authorised project/service acceptance owner.
ANALYSIS REQUIRED	Operation: pre/post outcome and durability evaluation. Decision interval: defined baseline, post-commissioning and follow-up periods. Minimum evidence: a pre-specified target metric/function, comparable pre/post evidence, competent handover and enough exposure/context to interpret change. Method: compare distributions/rates, use an interrupted time series or matched comparison where feasible, test for unintended route/service effects and keep feedback qualitative where samples are small. Quantified uncertainty: report critical-evidence completeness as n/N, plus effect size with 95% interval, coverage, confounders and sensitivity to window choice; no success claim when the interval includes no meaningful change or evidence is incomparable. Use the same outcome definition and observation window declared before the intervention; do not select a favourable metric afterwards. Safe failure: retain provisional acceptance, commission longer/targeted observation or reopen the action if the barrier remains or evidence is weak.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not infer health, wellbeing or productivity benefit, identify respondents, claim causality from simple before/after counts, certify compliance or close governance concerns automatically. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the project/service acceptance owner, competent professionals and affected communities.
WHY THIS IS USEFUL	Enables the team to verify real functional improvement, detect displacement or regression and decide whether to accept, adapt or reopen the work.

Barriers, feedback, incidents, governance and improvement

AI-079

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Is ownership, permission, lineage, precedence and human decision authority explicit for every data source, generated claim, published answer and escalation?

SENSORS AND TELEMETRY	Proposed evidence: source registry, permission, schema/version, lineage, health, access-log and publication-state telemetry. Coverage: every dataset/integration and claim used by the catalogue, including manual evidence and generated outputs. Timing/alignment: on every source, permission, owner, schema, model or publication change; governance reconciliation at least daily; use a common clock. Aggregation: by source, claim and decision role, not by individual data subject. Quality gate: require independently verified owner, purpose, lawful/authorised permission, retention, schema/version, provenance, staleness rule, health test and named human decision role. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: a complete registry can still contain incorrect owners, excessive permissions or weak professional accountability; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the current data/service owner register, information-governance decisions, professional responsibilities, publication approvals and escalation procedures (Information Governance, Information Security, service/data owners, accessibility governance and competent operational owners). Corroborating sources: data-protection/security assessments, contracts and current professional/incident authority. Precedence: law, policy, incident command and competent professional authority outrank system configuration and model confidence; missing ownership stops use. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: owner/permission/version unknown, assessment expired or any unresolved conflict about purpose, precedence or accountability. Conflict handling: keep disagreement visible and refer it to the relevant governance authority and competent operational owner.
ANALYSIS REQUIRED	Operation: claim-to-owner governance completeness and separation-of-duties assurance check. Decision interval: before deployment/publication and continuously during operation. Minimum evidence: a verified owner, purpose, permission, retention, precedence, staleness rule, human approver and escalation route for every critical source and claim. Method: build a source-claim-decision lineage graph, test least privilege and incompatible roles, and block orphaned or over-permissioned claims. Quantified uncertainty: report critical-evidence completeness as n/N, plus governed critical sources/total, orphaned claims, excessive permissions and expired assessments; 100% critical governance coverage is required for publication. Every decision-critical claim requires 100% coverage of owner, purpose, permission, precedence, staleness rule, human approver and escalation route. Safe failure: disable the affected integration/claim, retain a transparent unavailable state and refer ownership/permission to governance before reuse.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not treat logging as consent, use health or casework/personal emergency-plan records data, let a model appoint owners or approve itself, expose security-sensitive details or bypass professional accountability. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with governance authorities, data/service owners and competent decision makers.
WHY THIS IS USEFUL	Enables the team to block orphaned or over-permissioned claims and trace every published answer to a permitted source and accountable human decision.

AI-080

ACCESSIBILITY, INCLUSION, AND WELL-BEING TEAMS QUESTION

Which requested answers must stop at "not enough evidence", and what is the smallest safe verification step that could change each decision?

SENSORS AND TELEMETRY	Proposed evidence: claim-level source health, mapping, timestamp, permission, coverage and conflict telemetry. Coverage: every decision-critical claim used by all AI-001 to AI-080 answers, including manual and authoritative sources. Timing/alignment: at retrieval and whenever a critical source, rule, owner or permission changes; use a common clock. Aggregation: as claim-to-evidence sufficiency states, never as a global confidence score. Quality gate: require independently verified deployment/mapping/commissioning/permission/health, claim-specific age limits, current owner and explicit precedence for every critical source. Privacy guard: no identity, tracking, raw audio/images or person-level history. Known limits: healthy technical feeds can still be wrong, stale in meaning, blind to temporary barriers or subordinate to a current owner decision; missing, stale or unhealthy evidence is unknown.
AUTHORITATIVE SUPPORTING DATA	Owners and primary records: the current source-owner/precedence register, minimum-evidence rules for each question and competent operational decisions (all source/service owners, the Talking Abacws data steward and accessibility governance). Corroborating sources: current inspections, incident instructions and claim-source provenance. Precedence: current authoritative owners, competent professionals and incident command always outrank sensors, integrations, analytics and the May 2021 historical plan. Evidence record: retain source owner and version, access permission, provenance, and effective, observed and retrieved times for every claim. Stale when: any critical source beyond its age limit, missing permission/owner and version, unresolved conflict or incomplete required coverage. Conflict handling: keep disagreement visible and refer it to the accountable owner named for the missing claim.
ANALYSIS REQUIRED	Operation: catalogue-wide minimum-evidence and safe-failure evaluation. Decision interval: the exact decision and time window for each requested answer. Minimum evidence: all question-specific critical evidence, current authority and permissions; critical gaps cannot be averaged away by other sources. Method: apply each record's declared minimum, classify claims as verified, qualified, human-check or unsupported, and select the smallest check that can change the decision. Quantified uncertainty: report critical-evidence completeness as n/N, plus critical claims verified/total, gap type, oldest evidence, clock skew and unresolved conflicts; only complete critical coverage supports a verified answer. Safe failure: say what is known and unknown, why the gap matters, name the checker/owner and offer a verified alternative without inferring anything about the person.
ANSWER BOUNDARY	Use only requirements the person chooses to state for this purpose and interval. Do not infer disability, diagnosis, health, neurotype, distress, capability or support need; identify or track people; use health, casework or personal emergency-plan records; or disclose beyond authorised need-to-know. Do not hide uncertainty, generate certainty from missing data, ask for more personal disclosure to compensate, certify accessibility, promise outcomes or make owner/professional decisions. Do not certify accessibility or safety, promise an outcome, grant access, authorise an exception or control an asset. Decision authority remains with the person, data steward, authoritative owners and competent professionals.
WHY THIS IS USEFUL	Enables the team to stop unsupported answers consistently, explain the blocking gap and commission the smallest safe check that could unlock a defensible action.

Eighty questions organised around eight operational decisions

1	AI-001 to AI-010	Journeys, arrival and person-owned planning	Publish person-owned journey options, compare lawful arrivals, expose dependencies and prepare verified fallbacks.
2	AI-011 to AI-020	Entrances, routes, lifts and accessible circulation	Verify entrances, powered doors, route clearances, lifts, controlled access and unequal circulation delay.
3	AI-021 to AI-030	Rooms, seating, participation and adjustments	Confirm room features, integrated seating, participation tools and confidential completion of agreed adjustments.
4	AI-031 to AI-040	Lighting, noise, air, temperature and sensory comfort	Describe environmental conditions and recurring barriers without inferring health, distress, neurotype or productivity.
5	AI-041 to AI-050	Wayfinding, communication formats and assistive information	Keep names, signs, directions, announcements and optional assistive information current, equivalent and verifiable.
6	AI-051 to AI-060	Toilets, rest, quiet spaces and amenities	Check toilets, rest points, quiet spaces and amenities while protecting dignity and use privacy.
7	AI-061 to AI-070	Services, support routes, events and accompanying people	Route support, prepare activities, include accompanying people and plan capacity from privacy-safe evidence.
8	AI-071 to AI-080	Barriers, feedback, incidents, governance and improvement	Triage barriers, preserve lawful evidence, verify outcomes and keep data and decisions under accountable human control.

ACTION STANDARD

Every usable answer must lead to an authorised action: publish qualified information, obtain a targeted human check, fix an asset or process, relocate or re-time an activity, arrange practical support, communicate a change, escalate to a competent owner, prioritise an evidence-backed intervention or withhold a claim that the evidence cannot support.

Rules that apply to every question and every answer

1

PROPOSED UNTIL VERIFIED

No sensor, integration, map, model or feed is assumed operational. Deployment, mapping, commissioning, permission and current health must be independently established before use.

2

CURRENT AUTHORITY FIRST

Current service owners, competent professionals, safety leads and incident command outrank telemetry, schedules, inventories, generated answers and the May 2021 historical floor plan.

3

CLAIM-LEVEL TIME AND PROVENANCE

Keep effective, observed and retrieved times, owner and version provenance, coverage, clock alignment, staleness limit and conflicts for every decision-critical claim.

4

PERSON OWNS THE REQUIREMENT

Use only practical requirements a person chooses to state. Do not infer disability, diagnosis, health, neurotype, distress, capability, support need, productivity or wellness.

5

MINIMUM DATA AND PERMISSION

Do not use health, casework or personal emergency-plan records. Do not identify or track people, inspect speech or work content, or disclose chosen requirements beyond authorised need-to-know roles.

6

SAFE FAILURE AND HUMAN CONTROL

When minimum evidence is absent, say not enough evidence, identify the smallest safe check and name the accountable verifier. Never promise, certify, authorise or control what belongs to a person, professional or service owner.