

STAKEHOLDER QUESTION CATALOGUE 10

People with Mobility, Sensory, or Other Accessibility Requirements

80 practical questions for person-owned travel, route, entrance, space, seating, communication, comfort and contingency choices

STAKEHOLDER	People who choose to state mobility, visual, hearing, sensory-processing, cognitive, neurodivergent, fatigue-related, dexterity, communication or other functional requirements for the current interaction.
QUESTION RANGE	AR-001 to AR-080 across eight categories covering arrival, circulation, participation, sensory comfort, wayfinding, amenities, disruptions and independent contingency choices.
EVIDENCE MODEL	Proposed privacy-preserving sensing plus current authoritative route, access, lift, door, room, seating, assistive-provision, amenity, closure, transport and emergency sources. Proposed capability is never presented as verified deployment.

CORE PRINCIPLE
Help each person make their own travel, route, entrance, space, seating, communication, comfort and contingency choices from verified current information. Use only functional requirements they choose to state; never demand a diagnosis, infer sensitive traits, identify or track people, certify accessibility or safety, grant access, operate systems or overstate evidence.

1. Catalogue scope and design principles

Stakeholder-facing questions support personal choices; they do not transfer authority from current service owners or competent professionals.

This catalogue describes what a Talking Abacws service could answer for a person who chooses to state functional requirements. All sensing and integrations are proposed design requirements unless independently verified. The May 2021 floor plan is historical spatial reference only and cannot establish current access, room use, services or closures.

PERSON-OWNED AND DIAGNOSIS-FREE

Use only functional requirements the person chooses to state for the current decision. Never demand a diagnosis, rank needs or infer disability, health, neurotype, fatigue or distress.

PROPOSED CAPABILITY, NOT CURRENT FACT

Treat sensors, status feeds and integrations as proposed until deployment, mapping, commissioning, permissions and current health are verified.

WHOLE-ROUTE VALIDATION

Validate the complete journey: entrance, doors, audited gradients or ramps where current records exist, lift or stairs, circulation, destination and time restrictions.

CURRENT AUTHORITATIVE VERIFICATION

Current access, lift, door, room, seating, amenity, closure, maintenance and emergency owners override telemetry and historical drawings.

PRIVACY, DIGNITY AND MINIMAL DATA

Use anonymous aggregate counts and numerical environmental indicators only when proportionate. Do not use cameras, microphones, biometrics, device tracking or movement histories.

CORRECTLY LOCATED EVIDENCE

Never use corridor or adjacent-room measurements as room evidence. Preserve coverage, timestamps, calibration, gaps, drift, provenance, maintenance state and conflicts.

COMFORT IS PERSONAL, NOT CERTIFIED

Environmental and sensory evidence may compare conditions but cannot guarantee individual suitability, certify accessibility or replace professional assessment.

HONEST OPERATION AND INCLUSIVE FALLBACK

Label lookup, observation, calculation, estimate, forecast, comparison, diagnosis and recommendation correctly. Clarify, qualify, defer or return not assessable.

2. How to read each question record

Every record states the personal decision, minimum evidence, operation, uncertainty, authority boundary and value.

ACCESSIBILITY QUESTION	A natural, person-owned question about the person's own travel, route, entrance, space, seating, communication, comfort, support, departure or contingency choice.
SENSORS AND TELEMETRY	Only physically plausible, privacy-preserving proposed evidence. Each record states asset or area, spatial coverage, interval or aggregation, and quality or maintenance limits.
AUTHORITATIVE SUPPORTING DATA	Current owner-controlled sources for routes, entrances, lifts, doors, rooms, seating, assistive provision, amenities, opening, closures, transport, security and emergencies.
ANALYSIS REQUIRED	The named operation, decision interval, minimum evidence, method, controls or baseline, uncertainty and safe failure. Estimates and forecasts are never presented as observations.
ANSWER BOUNDARY	What the service must not infer, disclose, promise, certify, authorise or control, and when it must clarify, qualify, defer or return not assessable.
WHY THIS IS USEFUL	The concrete choice supported: entrance, route, space, seat, break, communication format, departure plan or fallback.

IMPLEMENTATION READINESS

R1 - PRACTICAL Primarily authoritative lookup, verified static information or current owner-issued status. Useful before a full sensing programme exists.	R2 - INTEGRATION-DEPENDENT Requires current cross-system integration and/or proposed privacy-preserving sensing with verified coverage, timing and quality.	R3 - RESEARCH OR RESTRICTED Requires validated modelling, higher-consequence interpretation, specialist governance, simulation or restricted evidence.
---	---	--

GLOBAL RULE Distinguish proposed capability from verified fact, use only the person's stated requirements, preserve authoritative-source precedence and return a qualified or not-assessable answer whenever a critical route, permission, evidence or safety condition is unverified.

3. Worked question-to-evidence example

A person-owned request is translated into explicit evidence obligations before a route recommendation is made.

EXAMPLE QUESTION I use a wheelchair, need seated rests and prefer a quieter route. Which verified route should I take from my arrival point, where can I rest, and what is the fallback if the lift fails?

1. RESOLVE STATED REQUIREMENTS

Use only the current interaction: step-free travel, lower effort, quieter conditions, rest points and a lift-failure fallback. Ask no diagnosis.

2. VERIFY AUTHORITY AND ACCESS

Check current opening, designated entrance, access rules, destination, accessible-route audit, door/lift status, rest-point inventory and closures from their owners.

3. VERIFY EVIDENCE QUALITY

Confirm complete route coverage, asset mapping, clock alignment, commissioning/calibration, uptime, gaps, drift or relocation, maintenance state and source conflicts.

4. PERFORM THE RIGHT OPERATIONS

Use authorised lookup plus whole-route calculation, then compare eligible alternatives. Treat anonymous crowd bands as preference context, not proof of accessibility.

5. PRESERVE DIGNITY AND ALTERNATIVES

Do not identify or track people, infer impairment, expose other occupants, operate assets or certify accessibility. Retain a staffed or organiser-approved fallback.

6. COMMUNICATE ANSWERABILITY

Separate confirmed facts, calculations, estimates and unresolved segments. If any critical segment is unverified, restrict the answer or return not assessable.

ANSWER SHAPE Lead with the verified route or state that no whole route is assessable. Then show authoritative status, estimated effort or crowding, rest points, fallback, recheck time, uncertainty and the responsible contact in the person's chosen accessible format.

1. Pre-visit planning, arrival and route choice

AR-001 to AR-002 | 10 questions in this section | Plan an authorised arrival from stated functional requirements, complete route evidence and current status.

AR-001

STEP-FREE

L3 - recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

I use a wheelchair. Which verified step-free route from my arrival point to the authorised entrance should I use at my arrival time?

SENSORS AND TELEMETRY
Proposed evidence: automatic-door operator state and door contact at the designated entrance; lift-controller availability only if the route needs a lift; an anonymous entrance count only when crowding is requested. Coverage: every segment from the stated arrival point to the authorised entrance, including doors, audited ramp/gradient records and any lift. Timing/aggregation: event-driven door/lift state with a heartbeat no slower than 30 seconds; optional crowd counts as 1-minute aggregates. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current accessible-route audit, designated entrance, public opening/access rules, transport or drop-off information, closure notices and official visit instructions. Precedence: organiser, accessibility, facilities and security owners determine route eligibility and entry. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + whole-route calculation + bounded recommendation. Decision interval: planned arrival until entry. Minimum evidence: a current route graph with every critical segment, route restriction and required asset verified. Method: reject any route with an unverified entrance, door, gradient/ramp, lift or time restriction; compare only fully eligible alternatives. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: give the last verified point and official contact, or return not assessable.

ANSWER BOUNDARY
A step-free route is not a legal certification and a healthy status feed is not proof that the route will remain usable. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Supports a defensible choice of arrival point and entrance before travelling.

AR-002

LOW-EFFORT

L3 - recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

I need regular seated rests. Which verified route from my stop or drop-off point is shortest, and where are the confirmed rest points?

SENSORS AND TELEMETRY
Proposed evidence: owner-issued lift and door status, current audited route geometry and confirmed rest-point locations; optional anonymous crowd bands on eligible route segments. No gait, fatigue or biometric sensing. Coverage: the complete route from the selected stop/drop-off point to the destination, including every proposed rest point. Timing/aggregation: asset events with a 30-second heartbeat; crowd bands, if used, as 1-minute aggregates; static geometry only from a current audited record. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current accessible routes and gradients where recorded, entrance/access rules, verified seating/rest-point inventory, opening hours and transport-stop or drop-off information. Precedence: the person defines distance/rest preferences; route, amenity and access owners define what is available. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + distance/rest calculation + recommendation. Decision interval: arrival through destination entry. Minimum evidence: a fully verified route, current door/lift status and rest points with valid access hours. Method: calculate route length and spacing between rest points against the limits the person states; disclose missing gradient or surface information. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: offer a verified partial plan and staffed alternative, or return not assessable.

ANSWER BOUNDARY
Do not infer stamina or promise that a seat will be free; apparent vacancy does not create permission or availability. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person pace the journey and choose a route with suitable rest opportunities.

1. Pre-visit planning, arrival and route choice

AR-003 to AR-004 | 10 questions in this section | Plan an authorised arrival from stated functional requirements, complete route evidence and current status.

AR-003

ORIENTATION

L2 - comparison

R2 - integration-dependent

ACCESSIBILITY QUESTION

I have low vision. Which public entrance offers the simplest verified route to reception, with the fewest decision points?

SENSORS AND TELEMETRY
Proposed evidence: door and public digital-signage status plus calibrated illuminance at named orientation points; optional anonymous entrance crowd bands. No camera or image analysis. Coverage: each eligible public entrance, vestibule and route to the current reception/check-in point. Timing/aggregation: door/signage status event-driven; illuminance sampled every 5-15 seconds and aggregated to 1 minute; crowding as 1-minute bands. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current public entrances, accessible wayfinding audit, tactile/high-contrast sign inventory, reception/check-in location, opening/access rules and closures. Precedence: wayfinding/accessibility content owners and organiser instructions determine the valid route and cues. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + route comparison + recommendation. Decision interval: planned arrival to reception/check-in. Minimum evidence: eligible entrances, current door status, complete routes and verified orientation cues at decision points. Method: compare decision-point count, cue availability, route length and disruptions; use light and crowding only as qualified context. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: recommend a staffed arrival option if no complete route has adequate verified cues.

ANSWER BOUNDARY
Brightness does not prove legibility, and missing signage must not be invented or inferred from the floor plan. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person choose an entrance that reduces avoidable orientation uncertainty.

AR-004

TEXT CHECK-IN

L1 - authorised lookup

R1 - practical

ACCESSIBILITY QUESTION

I cannot use a phone call. What official text-based check-in or arrival contact can I use?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: owner-issued availability for approved SMS, web-chat or text-relay channels serving the relevant reception or organiser, including current service window and fallback. Quality gate: preserve source identity, retrieved time, uptime/gaps, version state and provenance; capability remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: official check-in instructions, approved text/contact channels, service hours, accessibility communication options and fallback contact. Precedence: the organiser or reception owner determines which channel can be used and when. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup. Decision interval: before arrival and during the published check-in period. Minimum evidence: a current official text channel, operating window and fallback contact. Return only verified details and their retrieval time. Safe failure: if no accessible text channel is confirmed, state that clearly and provide the responsible staffed contact without inventing a service.

ANSWER BOUNDARY
Do not request a diagnosis or expose messages, phone numbers or personal details beyond the authorised contact information. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Allows the person to arrange arrival without relying on a phone call.

1. Pre-visit planning, arrival and route choice

AR-005 to AR-006 | 10 questions in this section | Plan an authorised arrival from stated functional requirements, complete route evidence and current status.

AR-005

QUIETER ARRIVAL

L3 - forecast/recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Crowded entrances are difficult for me. When within my authorised arrival window is the designated entrance likely to be quieter?

SENSORS AND TELEMETRY

Proposed evidence: anonymous bidirectional counters covering every branch of the organiser-designated entrance or queue boundary; no identity, device or movement-history data. Coverage: the named entrance and its immediate waiting boundary only. Timing/aggregation: crossing events reconciled to 1-minute aggregate counts; validate counter error for the event layout and preserve configuration changes. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: current public opening, authorised arrival/check-in window, event timetable, expected arrival waves, entrance assignment and late-arrival policy. Precedence: organiser and access rules override any crowd forecast. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED

Operation: forecast + bounded recommendation. Decision interval: the person-selected interval within the authorised arrival window. Minimum evidence: current entrance eligibility, complete anonymous counts and comparable event/time evidence. Method: forecast broad crowd bands using comparable programme, entrance configuration and weather; report a range rather than a precise headcount. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: report current conditions only, or not assessable, when coverage or comparability is weak.

ANSWER BOUNDARY

Do not identify attendees, guarantee a quiet arrival or recommend arrival outside the authorised window. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Supports a calmer arrival choice while preserving official check-in requirements.

AR-006

ARRIVAL BUFFER

L2 - calculation/estimate

R2 - integration-dependent

ACCESSIBILITY QUESTION

I need more time at doors and lifts. How much arrival time should I allow before my appointment or event?

SENSORS AND TELEMETRY

Proposed evidence: automatic-door cycle times, lift-call/door-cycle telemetry and anonymous queue counts at the exact assets on the route; no personal pace or gait sensing. Coverage: the selected entrance-to-destination route and only the doors/lifts that serve it. Timing/aggregation: event timestamps with sub-minute clock alignment; queue counts as 1-minute aggregates over comparable operating periods. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: current appointment/event time, authorised entrance, route, lift/door status, opening rules and known works or closures. Precedence: organiser, access and asset owners determine the valid route and timing constraints. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED

Operation: calculation + bounded time estimate. Decision interval: planned arrival to the required check-in/session time. Minimum evidence: route length, verified assets, recent cycle/queue evidence and the extra time preference the person states. Method: sum walking/rolling distance, user-stated buffer, recent asset delays and a conservative uncertainty margin; do not model an individual from past movement. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: give a conservative range and official contact, or return not assessable.

ANSWER BOUNDARY

Do not infer walking speed, fatigue or punctuality, and do not promise that a lift or door will remain available. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person choose a realistic departure and arrival time.

1. Pre-visit planning, arrival and route choice

AR-007 to AR-008 | 10 questions in this section | Plan an authorised arrival from stated functional requirements, complete route evidence and current status.

AR-007

COMPANION

L1 - authorised lookup

R1 - practical

ACCESSIBILITY QUESTION

I am arriving with a personal assistant, carer or support person. Can we use the same authorised entrance and route?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current access-rule and organiser-status feeds; no occupancy or identity sensing is needed. Coverage: the designated entrance, route, destination and relevant visitor policy. Timing: use the current policy effective time and event/visit window. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current companion/personal-assistant or support-person policy, visitor registration process, access rules, room/event instructions and support contact. Precedence: organiser, room/access owner and security determine entry; telemetry cannot create permission. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup. Decision interval: before arrival and at check-in. Minimum evidence: a current policy, destination-specific instruction and official contact for exceptions. Method: state what is confirmed, what must be arranged in advance and any route implications. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to the organiser/access owner if the policy is missing or event-specific.

ANSWER BOUNDARY
Do not ask why support is needed, identify the companion, grant entry or expose visitor records. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL Lets the person confirm whether they and their chosen support person can arrive together.

AR-008

MOBILITY AID

L2 - constraint check

R2 - integration-dependent

ACCESSIBILITY QUESTION

I use a mobility scooter. Do the verified route widths, door clearances and lift dimensions fit the measurements I provide?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current audited route geometry, door clear widths, turning envelopes, lift-car dimensions and owner-issued door/lift status; no inference from the person or mobility aid. Coverage: every segment of the selected route, including thresholds, doors, turns, lift and destination entrance. Timing: use the audit/version date for geometry and current event status for doors/lifts. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current measured route geometry, lift dimensions/load rules, access restrictions, closures and the dimensions the person elects to provide. Precedence: accessibility/facilities records determine geometry; the person controls the supplied dimensions. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised constraint calculation. Decision interval: the planned journey. Minimum evidence: current measurements for every critical segment, measurement tolerance and live status for required assets. Method: compare each clearance with the supplied dimensions plus an explicit tolerance; identify the first unknown or incompatible segment. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: provide a staffed alternative or return not assessable when any critical measurement is absent.

ANSWER BOUNDARY
Do not remotely measure the person/device, infer device type or certify manoeuvrability, weight capacity or safe use. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL Lets the person decide whether the route can accommodate the dimensions they provide.

1. Pre-visit planning, arrival and route choice

AR-009 to AR-010 | 10 questions in this section | Plan an authorised arrival from stated functional requirements, complete route evidence and current status.

AR-009

WEATHER ROUTE

L3 - recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Wet, icy or windy conditions make travel harder for me. Which verified entrance route minimises exposed distance and difficult gradients?

SENSORS AND TELEMETRY
Proposed evidence: a correctly sited outdoor weather station for wind, rain and temperature; owner-issued surface, gritting, closure, door and lift status. No automated claim of ice from temperature alone. Coverage: eligible outdoor approaches plus the complete indoor route to the entrance/destination. Timing/aggregation: weather sampled every 10-30 seconds and aggregated to 1 minute; route/closure events source-native and time-aligned. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current weather warnings, transport or drop-off status, route surface/gradient records, gritting or closure notices, designated entrances and access rules. Precedence: weather/transport, facilities and access owners override modelled conditions. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + route comparison + recommendation. Decision interval: the planned travel and arrival window. Minimum evidence: a verified whole route, current weather/closure information and comparable alternatives. Method: compare exposed distance, recorded gradients, weather exposure and verified asset status; treat surface condition as unknown unless officially confirmed. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: prioritise a verified sheltered/staffed option or defer when a safe route cannot be established.

ANSWER BOUNDARY
Do not certify a surface as safe, infer mobility risk or recommend a route through a closed/restricted area. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person choose a less exposed arrival option under current conditions.

AR-010

LOW-STIMULATION

L3 - recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

I prefer a lower-stimulation arrival. Which authorised entrance and waiting option is likely to have less crowding, noise and visual intensity?

SENSORS AND TELEMETRY
Proposed evidence: anonymous entrance/waiting-area counts, calibrated numerical sound-level metrics and illuminance/glare indicators at each eligible area; no raw audio, images or identities. Coverage: the authorised entrance, check-in path and waiting areas being compared; room/corridor evidence is not interchangeable. Timing/aggregation: counts and environmental values as clock-aligned 1-minute aggregates; preserve calibration, event-layout and operating-state changes. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current authorised entrances, waiting areas, opening/check-in windows, room purpose, access rules, closures and staffed alternatives. Precedence: organiser, accessibility and space owners determine eligibility; telemetry describes context only. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: multi-criteria comparison + bounded recommendation. Decision interval: the selected arrival and waiting interval. Minimum evidence: two or more eligible options with comparable current evidence and the preferences the person states. Method: compare crowd band, LAeq/peak variability and lighting variability separately; show trade-offs and forecast uncertainty. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: offer a verified staffed option or return not assessable when no comparable evidence exists.

ANSWER BOUNDARY
Do not infer sensory needs from behaviour, guarantee calmness, promise a free waiting place or rank other people's needs. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person choose a lower-stimulation arrival and waiting plan.

2. Entrances, doors, lifts, stairs and circulation

AR-011 to AR-012 | 10 questions in this section | Move through the building using verified assets, whole-route checks and realistic time or crowding estimates.

AR-011

AUTOMATIC DOOR

L1 - lookup/observation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Is the designated accessible entrance open now, and is its automatic door officially reported as working?

SENSORS AND TELEMETRY
Proposed evidence: automatic-door operator fault/enable state, leaf contact and obstruction/fault status at the designated accessible entrance. Coverage: the exact entrance door; a nearby door or general building status is insufficient. Timing/aggregation: event-driven state with a heartbeat no slower than 30 seconds; require controller/contact agreement and a current maintenance flag. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current public opening/access rules, designated entrance, official door outage/maintenance notice and staffed assistance contact. Precedence: access/security and asset owners determine whether entry is permitted and the door is in service. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + current-status observation. Decision interval: now and the intended arrival interval. Minimum evidence: current opening/permission plus fresh owner and telemetry status for the named door. Method: cross-check controller, contact and official notice; report last update and any disagreement. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: state the verified status and staffed fallback, or return not assessable.

ANSWER BOUNDARY
An open leaf does not prove public access, and a healthy feed does not certify safe or reliable operation. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person decide whether to use the planned entrance or seek the official fallback.

AR-012

DOOR EFFORT

L2 - comparison

R2 - integration-dependent

ACCESSIBILITY QUESTION

Are there heavy manual doors on my verified route, and what authorised assisted alternative is available?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current audited door clear width, opening-force or powered-assistance record, and owner-issued operator status for the exact route. Coverage: every door on the selected route. Timing: use audit/commissioning dates for geometry and force, with live status only for powered operators. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current accessible-route audit, manual-door opening-force test/maintenance records, powered-door inventory, access restrictions and official assisted route. Precedence: facilities/access and security owners determine usable doors and assistance. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + route comparison. Decision interval: the planned journey. Minimum evidence: verified door characteristics/status for every route and an authorised alternative. Method: identify manual doors and compare force/assistance and route length; do not estimate opening force from door type. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: provide a verified assisted route/contact or mark the route not assessable.

ANSWER BOUNDARY
Do not infer dexterity or strength, promise that another person will help, or treat a held-open door as a permanent solution. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person avoid an unexpectedly difficult door and plan authorised assistance.

2. Entrances, doors, lifts, stairs and circulation

AR-013 to AR-014 | 10 questions in this section | Move through the building using verified assets, whole-route checks and realistic time or crowding estimates.

AR-013

LIFT ROUTE

L2 - route calculation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Which lift serves my destination, is it officially in service, and is the route to it currently open?

SENSORS AND TELEMETRY

Proposed evidence: lift-controller service/fault state, landing-door state and only the route doors needed to reach the lift and destination. Coverage: the named lift, its approach from the authorised entrance and the complete route from the destination landing. Timing/aggregation: event-driven lift/door state with a 30-second heartbeat and aligned maintenance/outage timestamps. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: current lift service map, accessible-route graph, destination allocation, access restrictions, closures and official lift outage notice. Precedence: facilities/lift and access owners determine which lift serves the destination and whether the route is authorised. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED

Operation: authorised lookup + whole-route calculation. Decision interval: the planned movement interval. Minimum evidence: verified serving relationships, route segments, access windows and fresh lift/door status. Method: select only a lift that serves the destination and has a fully verified approach/exit route; report last update. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: give the official alternative/contact or return not assessable.

ANSWER BOUNDARY

Do not operate/call the lift, grant access or treat a lift shown as running as proof that the whole route is usable. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL Helps the person identify the correct lift and verify the complete route to it.

AR-014

LIFT QUEUE

L3 - recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

The lift lobby is busy. Is another verified step-free route available, or is waiting the more reliable choice?

SENSORS AND TELEMETRY

Proposed evidence: anonymous counts at the named lift-lobby boundary, lift car arrival/door-cycle events and status for any authorised alternative route; no identities or movement histories. Coverage: the selected lobby and complete alternative route, not the whole building. Timing/aggregation: counts as 1-minute aggregates; lift events source-native; validate coverage for all lobby approaches. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: current lift service, authorised alternative routes, access restrictions, expected event transitions and official outage/assistance instructions. Precedence: lift/access owners and organisers determine the valid alternatives. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED

Operation: current observation + short-horizon estimate + recommendation. Decision interval: the next 5-15 minutes. Minimum evidence: complete lobby count coverage, fresh lift cycles and a fully verified alternative route. Method: estimate a broad wait band from recent arrivals/departures and compare with alternative route time/effort; disclose count error. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: recommend waiting or the verified alternative; otherwise defer/not assessable.

ANSWER BOUNDARY

Do not identify lobby users, guarantee a wait time, infer assistance need or direct someone onto an unverified route. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL Helps the person choose between waiting and a confirmed alternative without unnecessary movement.

2. Entrances, doors, lifts, stairs and circulation

AR-015 to AR-016 | 10 questions in this section | Move through the building using verified assets, whole-route checks and realistic time or crowding estimates.

AR-015

STAIR OPTION

L2 - comparison

R2 - integration-dependent

ACCESSIBILITY QUESTION

I can manage a few stairs if necessary. Which authorised route has the fewest steps, confirmed handrails and nearby rest points?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current audited stair count, handrail/landing record, door/lift status and verified rest-point inventory. Coverage: each candidate route from origin to destination. Timing: use the current audit/version date and source-native asset status. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current route graph, step counts, handrail/landing details, rest points, access restrictions, lift status and closures. Precedence: accessibility/facilities owners define the route; the person states the acceptable number of stairs. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: constraint calculation + route comparison. Decision interval: the planned movement interval. Minimum evidence: complete geometry/status for each route and the limit the person states. Method: exclude routes exceeding the stated limit or with unverified handrails/landings; compare distance and rest opportunities. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: offer a fully step-free/staffed option or return not assessable.

ANSWER BOUNDARY
Do not infer physical capacity, judge whether stairs are safe for the person or treat handrail presence as personal suitability. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person choose a route matching the stair limit they state.

AR-016

TURNING SPACE

L2 - constraint check

R2 - integration-dependent

ACCESSIBILITY QUESTION

Do the verified corridor widths and turning spaces on my route fit the mobility-aid dimensions I provide?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current audited corridor clear widths, turning envelopes, door clearances and lift dimensions; no image, gait or device tracking. Coverage: every constrained point on the chosen route. Timing: use the audit/version date and live closure/obstruction notices where available. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current measured geometry, temporary-obstruction/works notices, access restrictions and the mobility-aid dimensions the person chooses to provide. Precedence: facilities/accessibility records govern geometry; the person controls the supplied dimensions. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised constraint calculation. Decision interval: the planned route interval. Minimum evidence: current measurements and tolerances for each critical point. Method: compare dimensions plus tolerance, identify the narrowest/unknown point and test only authorised alternatives. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: provide a verified alternative or return not assessable.

ANSWER BOUNDARY
Do not infer the person/device from movement, certify manoeuvrability or treat nominal corridor width as clear width during works. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person determine whether the route geometry matches the dimensions they provide.

2. Entrances, doors, lifts, stairs and circulation

AR-017 to AR-018 | 10 questions in this section | Move through the building using verified assets, whole-route checks and realistic time or crowding estimates.

AR-017

DOOR STATUS

L1 - observation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Are any doors on my planned route currently locked, restricted, held open or reported out of service?

SENSORS AND TELEMETRY

Proposed evidence: owner-issued access/lock status, door contact and powered-operator fault state for each route door; no credential or personal access-log disclosure. Coverage: the doors on the selected route only. Timing/aggregation: event-driven state with current access-rule effective time, 30-second heartbeat where available and maintenance flags. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: current opening/access rules, staff permissions, door/route ownership, restriction/closure notices and official assistance contact. Precedence: security/access and facilities owners determine permission and service status. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED

Operation: authorised lookup + status observation. Decision interval: now and the intended movement interval. Minimum evidence: current permission, door mapping and fresh status from owner sources. Method: cross-check lock/restriction, contact/operator status and official notices; separate permission from mechanical state. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: report the blocked segment and official alternative/contact, or not assessable.

ANSWER BOUNDARY

Do not expose access events or identities, infer who opened a door, grant entry or suggest bypassing a restriction. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL Lets the person avoid a route blocked by a locked, restricted or failed door.

AR-018

REALISTIC TIME

L2 - calculation/estimate

R2 - integration-dependent

ACCESSIBILITY QUESTION

How long should I allow for this route if I need extra time at doors, turns and lifts?

SENSORS AND TELEMETRY

Proposed evidence: route geometry, door/lift cycle times and anonymous queue counts at the exact route assets; no personal pace history. Coverage: the full origin-to-destination route. Timing/aggregation: events time-aligned to seconds; queue counts as 1-minute aggregates over a recent comparable window. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: current route/access, lift/door status, destination availability, known class/event transitions and closures. Precedence: route/access and asset owners define valid segments; the person supplies any extra-time preference. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED

Operation: calculation + bounded travel-time estimate. Decision interval: the intended movement interval. Minimum evidence: route length, verified assets, recent delay evidence and stated time allowance. Method: calculate a range from route distance, user-selected pace/buffer and asset/queue delays; use comparable periods only. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: give a conservative range and fallback or return not assessable.

ANSWER BOUNDARY

Do not infer mobility, productivity or punctuality from past movement and do not promise a precise arrival time. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL Helps the person schedule transitions with a realistic, uncertainty-labelled buffer.

2. Entrances, doors, lifts, stairs and circulation

AR-019 to AR-020 | 10 questions in this section | Move through the building using verified assets, whole-route checks and realistic time or crowding estimates.

AR-019

LOW-CROWD ROUTE

L3 - forecast/recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Which authorised route between my two destinations is expected to be least crowded when I need to move?

SENSORS AND TELEMETRY
Proposed evidence: anonymous segment-level people counts at all candidate route branches, plus current door/lift status; no identity, device tracking or route histories. Coverage: only the candidate authorised routes between the two stated destinations. Timing/aggregation: crossing events aggregated to 1-minute bands; require complete branch coverage and event-layout validation. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current route/access graph, destination times, door/lift status, closures and scheduled transition periods. Precedence: access/route owners and current destination instructions determine eligible routes. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: short-horizon forecast + route recommendation. Decision interval: the requested movement window. Minimum evidence: fully verified alternatives with complete anonymous count coverage and comparable recent periods. Method: forecast broad crowd bands for each route, then compare with distance and asset risk; show confidence and uncovered segments. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: use current observation only or return not assessable when coverage is incomplete.

ANSWER BOUNDARY
Do not identify or track route users, guarantee low crowding or choose a route that is not authorised and fully verified. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person select a less crowded route at the time they need to move.

AR-020

REORIENTATION

L2 - recommendation

R1 - practical

ACCESSIBILITY QUESTION

If I become disoriented, where is the nearest verified place to pause, reorient and ask for help?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current wayfinding/help-point status, verified seating/rest-point inventory and door/lift status for the route to the nearest eligible point. Coverage: the person's stated current area and the route to each candidate help/reorientation point. Timing: use current source times and no personal location history. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current help/reception points, staffed hours, accessible route, seating/rest locations, public access rules and closures. Precedence: reception/organiser/accessibility and route owners determine which points are open and authorised. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + nearest-point calculation + recommendation. Decision interval: the current journey. Minimum evidence: a stated coarse location, eligible help/rest points and a verified route. Method: rank by route completeness, distance, decision-point count and staffed status; present one step at a time if requested. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: offer the official contact or return not assessable when location/route evidence is insufficient.

ANSWER BOUNDARY
Ask only the minimum location needed; do not track the person, infer disorientation or promise that staff will be immediately available. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Provides a dignified pause and reorientation option without requiring a diagnosis.

3. Teaching, work, meeting and event spaces, seating and participation

AR-021 to AR-022 | 10 questions in this section | Choose an authorised room, seat or participation option without inferring availability, permission or individual suitability.

AR-021

ROOM ACCESS

L2 - constraint check

R2 - integration-dependent

ACCESSIBILITY QUESTION

Does my assigned room have a currently verified step-free route and an entrance I am authorised to use?

SENSORS AND TELEMETRY

Proposed evidence: door/lift status only for the verified route to the assigned room; no room-condition sensing is needed for basic access. Coverage: the entire authorised route and the named room entrance. Timing/aggregation: event-driven asset status with a 30-second heartbeat and current closure flags. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: current room allocation/purpose, access and booking owner, accessible route, entrance details, door/lift status and closures. Precedence: the room/event/access owners determine whether the person may use the space. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED

Operation: authorised lookup + whole-route constraint check. Decision interval: before the planned room use. Minimum evidence: current room assignment and every critical route segment/status. Method: verify step-free continuity, time-dependent access and the room entrance; do not infer eligibility from occupancy. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: give the official alternative/contact or return not assessable.

ANSWER BOUNDARY

Do not grant room access, certify accessibility or substitute corridor evidence for room/entrance evidence. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person verify the assigned room and route before committing to the journey.

AR-022

WHEELCHAIR SEATING

L1 - authorised lookup

R2 - integration-dependent

ACCESSIBILITY QUESTION

Is wheelchair-accessible seating confirmed for this room, and how do I verify or request it through the official service?

SENSORS AND TELEMETRY

No personal sensing. Proposed system evidence: current authorised seating inventory and booking/adjustment status; no seat camera or occupancy inference. Coverage: the named room and designated wheelchair-accessible seating positions. Timing: use current room allocation, seating-plan version and owner status. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: current room/event allocation, seating plan, circulation/egress constraints, adjustment request process and organiser/accessibility contact. Precedence: organiser, room and accessibility owners determine provision and allocation. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED

Operation: authorised lookup. Decision interval: before the named activity. Minimum evidence: correct room, current seating inventory and official request/confirmation status. Method: state what is confirmed, how to request/verify it and the relevant deadline. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to the organiser/accessibility owner; do not infer a seat from apparent vacancy.

ANSWER BOUNDARY

Do not reserve or promise a seat, expose another attendee's adjustment, or treat occupancy as proof of availability. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person confirm or request wheelchair-accessible seating through the right service.

3. Teaching, work, meeting and event spaces, seating and participation

AR-023 to AR-024 | 10 questions in this section | Choose an authorised room, seat or participation option without inferring availability, permission or individual suitability.

AR-023

EXIT-NEAR SEAT

L2 - recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

I need a seat near an exit. Which authorised seating options meet that preference without obstructing circulation?

SENSORS AND TELEMETRY

No personal sensing. Proposed system evidence: current seating plan, door/exit geometry and circulation/egress clearances; no occupant identification. Coverage: the named room and only seating positions authorised for the activity. Timing: use the current layout/room allocation and official change time. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: current room/event allocation, seating plan, exit/egress constraints, accessibility provision and organiser approval process. Precedence: organiser, room and safety owners determine which seats may be used. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED

Operation: authorised constraint check + recommendation. Decision interval: the activity window. Minimum evidence: eligible seats, exit locations, circulation clearances and any required approval. Method: filter seats by authorised use and proximity preference while preserving egress; show trade-offs. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: offer an official request/contact or return not assessable.

ANSWER BOUNDARY

Do not move furniture, reserve a seat, obstruct circulation or certify emergency suitability. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL Lets the person request a suitable seat without compromising authorised room arrangements.

AR-024

VISUAL ACCESS

L2 - comparison

R2 - integration-dependent

ACCESSIBILITY QUESTION

I need a clear view of captions, an interpreter or the main display. Which verified seating zone is most suitable?

SENSORS AND TELEMETRY

Proposed evidence: calibrated illuminance and glare indicators at named seating zones; status of caption display or interpreter position from owner systems. No camera, screen or teaching-content inspection. Coverage: the exact room and eligible seating zones. Timing/aggregation: light sampled every 5-15 seconds and aggregated to 1 minute; display/assistive status source-native and time-aligned. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: current room allocation, seating plan, display/caption/interpreter provision, event format, lighting/shading state and accessibility contact. Precedence: organiser, AV/assistive-technology and room owners determine provision and eligible seating. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED

Operation: authorised lookup + seating-zone comparison + recommendation. Decision interval: the activity window. Minimum evidence: eligible seats, confirmed provision and correctly located current light/glare evidence. Method: compare viewing geometry, provision and light variability; do not analyse displayed content. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: recommend an authorised option or defer/not assessable.

ANSWER BOUNDARY

Do not inspect screens or content, infer vision/hearing status, promise caption/interpreter quality or allocate seats. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL Helps the person request a seating zone that better supports the provision they use.

3. Teaching, work, meeting and event spaces, seating and participation

AR-025 to AR-026 | 10 questions in this section | Choose an authorised room, seat or participation option without inferring availability, permission or individual suitability.

AR-025		HEARING SUPPORT	L1 - lookup/status	R2 - integration-dependent
ACCESSIBILITY QUESTION	Is a hearing loop or another assistive-listening system confirmed, recently tested and available in this room?			
SENSORS AND TELEMETRY Proposed evidence: owner-issued status from the room-specific assistive-listening system, including installed zone, last functional test, battery/receiver availability where applicable and maintenance state. No speech or audio recording. Quality gate: verified room/asset mapping, test provenance, effective date, current fault status and source agreement; capability remains proposed until verified.		ANALYSIS REQUIRED Operation: authorised lookup + service-status check. Decision interval: before and during the named activity. Minimum evidence: correct room, installed system, current test record and owner status. Method: report what is confirmed, test date, known limitation and official request/help route. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to the responsible owner when status is stale or conflicting.		
AUTHORITATIVE SUPPORTING DATA Authoritative sources: current room allocation, hearing-loop/assistive-listening inventory, latest test/commissioning record, AV/assistive owner status and organiser instructions. Precedence: the AV/assistive-technology owner and organiser determine availability and use. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.		ANSWER BOUNDARY Do not listen to speech, inspect content, pair or operate devices, infer hearing status or guarantee individual benefit. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.		
WHY THIS IS USEFUL Lets the person confirm or request the listening support needed to participate.				

AR-026		ADJUSTABLE WORKSPACE	L1 - authorised lookup	R2 - integration-dependent
ACCESSIBILITY QUESTION	Is a height-adjustable desk or sufficient clear space for my mobility aid confirmed in the room I will use?			
SENSORS AND TELEMETRY No personal sensing. Proposed system evidence: current inventory and owner-issued service status for a height-adjustable desk or defined clear workspace; powered-desk fault status only if integrated. No person or desk-user sensing. Coverage: the named room and authorised workstation(s). Timing: use current inventory/inspection and source-native fault time. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.		ANALYSIS REQUIRED Operation: authorised lookup + dimensional constraint check. Decision interval: before the planned use. Minimum evidence: correct room, current workstation dimensions/status and any person-supplied clearance requirement. Method: verify provision and compare dimensions with stated needs; report maintenance status. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: provide the official request/alternative or return not assessable.		
AUTHORITATIVE SUPPORTING DATA Authoritative sources: current room allocation, workspace inventory, dimensions, access/booking rules, maintenance status and adjustment request process. Precedence: room/workspace and accessibility owners determine provision and allocation. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.		ANSWER BOUNDARY Do not reserve or operate the desk, infer body dimensions or certify ergonomic suitability. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.		
WHY THIS IS USEFUL Helps the person confirm a usable workspace or request an authorised alternative.				

3. Teaching, work, meeting and event spaces, seating and participation

AR-027 to AR-028 | 10 questions in this section | Choose an authorised room, seat or participation option without inferring availability, permission or individual suitability.

AR-027

MOVEMENT BREAKS

L2 - recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

I may need to stand, move or take short breaks. Which authorised seating area lets me do that without blocking circulation?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current seating/circulation layout, room rules and authorised break/re-entry process; anonymous occupancy only if crowd context is requested. Coverage: the named room and approved break/movement areas. Timing: use the current layout/event version; optional counts as 1-minute aggregates. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current room/event allocation, seating plan, circulation constraints, break/re-entry rules and organiser/accessibility contact. Precedence: organiser, room and safety owners determine permitted movement and seating. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + seating-area recommendation. Decision interval: the activity and break windows. Minimum evidence: eligible seating/movement areas and current organiser rules. Method: identify options near an authorised exit or movement area while preserving circulation and participation. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to the organiser or return not assessable.

ANSWER BOUNDARY
Do not infer why breaks are needed, reserve seats, alter the room or promise unrestricted re-entry. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person plan movement breaks without unnecessary disclosure or disruption.

AR-028

LOW-DISTRACTION

L3 - recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

I need a lower-distraction way to participate. Is an authorised quieter zone, smaller room or remote option available?

SENSORS AND TELEMETRY
Proposed evidence: room-level numerical LAeq/peak metrics, illuminance variability and anonymous occupancy for eligible spaces; no raw audio, images or content capture. Coverage: each named authorised room/zone and its complete route; corridor evidence cannot represent a closed room. Timing/aggregation: sound computed locally at 1 second and stored as 1-minute metrics; light/occupancy as aligned 1-minute aggregates. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current room/event purpose, access/booking, quiet/remote participation options, assistive provision, scheduled activity and closures. Precedence: organiser and room/access owners determine which alternatives are available. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: comparison + bounded recommendation. Decision interval: the activity window. Minimum evidence: eligible options with comparable room-level evidence and current remote/quiet-space status. Method: compare noise, light and occupancy variability separately, plus route and participation constraints. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: offer the official remote/quiet option or return not assessable.

ANSWER BOUNDARY
Do not record speech, infer engagement or sensory condition, guarantee low distraction, grant room use or inspect meeting content. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person select an authorised way to participate with fewer distractions.

3. Teaching, work, meeting and event spaces, seating and participation

AR-029 to AR-030 | 10 questions in this section | Choose an authorised room, seat or participation option without inferring availability, permission or individual suitability.

AR-029

SUPPORTER SEATING

L1 - authorised lookup

R1 - practical

ACCESSIBILITY QUESTION

Can my support person sit with me in the assigned space under the current organiser or room rules?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current seating/visitor policy and organiser confirmation; no occupancy or identity sensing is needed. Coverage: the assigned room and seating arrangement. Timing: use the current event/room version and owner confirmation time. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current organiser policy, room capacity/seating plan, support-person arrangements, registration/access rules and contact. Precedence: organiser, room and access owners determine whether adjacent seating is available. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup. Decision interval: before the activity. Minimum evidence: current policy and room-specific confirmation. Method: state what is confirmed and how to request/verify adjacent seating. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to the organiser; do not infer availability from low occupancy.

ANSWER BOUNDARY
Do not ask why support is needed, expose other attendees, reserve seats or grant access. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person confirm whether their chosen support person can sit with them.

AR-030

SPACE FALLBACK

L3 - forecast/recommendation

R3 - research or restricted

ACCESSIBILITY QUESTION

If my assigned space becomes unsuitable, which authorised alternative could I use without losing access to the activity?

SENSORS AND TELEMETRY
Proposed evidence: correctly located room-level environmental, acoustic and anonymous occupancy evidence for approved fallback spaces, plus route door/lift status. No content or identity sensing. Coverage: the assigned space, each organiser-approved alternative and every connecting route. Timing/aggregation: environmental/count data as aligned 1-minute aggregates; route assets event-driven; preserve room-use changes. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current room/event allocation, approved fallback spaces, access/booking, participation/assistive provision, capacity, routes and closures. Precedence: organiser, room/access and accessibility owners determine eligibility and transfer. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: forecast + comparison + bounded recommendation. Decision interval: the activity and likely changeover window. Minimum evidence: approved alternatives, complete routes and comparable current/forecast evidence. Method: forecast broad suitability indicators and compare participation/route constraints; never create an alternative not authorised. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: give organiser contact and mark the fallback not assessable if any critical element is unverified.

ANSWER BOUNDARY
Do not switch rooms, grant access, promise continuity or infer that an empty room is available or confidential. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person prepare an authorised fallback before conditions become unsuitable.

4. Lighting, glare, acoustics, temperature, air, crowding and sensory comfort

AR-031 to AR-032 | 10 questions in this section | Compare environmental and sensory evidence honestly, with room-level coverage and no guarantee of personal suitability.

AR-031

QUIET SPACE

L2 - comparison

R2 - integration-dependent

ACCESSIBILITY QUESTION

Which authorised space has the lowest verified background-noise level during the time I plan to use it?

SENSORS AND TELEMETRY
Proposed evidence: calibrated sound-level meters that calculate LAeq, LAFmax and selected percentiles locally; no raw audio or speech retention. Coverage: each eligible room/zone being compared; a corridor meter cannot stand in for a closed room. Timing/aggregation: 1-second local calculation with 1-minute aggregates; require acoustic calibration, room mapping and comparable operating state. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current room purpose, access/booking, quiet-space designation, scheduled activity, works/noise notices and closures. Precedence: space owners determine eligibility and availability; acoustic telemetry describes conditions only. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: observation + matched comparison + recommendation. Decision interval: the requested use window. Minimum evidence: two or more eligible spaces with fresh room-level data and comparable known activity. Method: compare distributions and variability over a recent matched window, not a single reading. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: qualify the result or return not assessable when spaces/coverage are not comparable.

ANSWER BOUNDARY
Do not record or infer speech/conversation, identify occupants, guarantee quietness, reserve space or imply confidentiality. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person choose a lower-noise authorised space using transparent evidence.

AR-032

SUDDEN NOISE

L2 - lookup/comparison

R2 - integration-dependent

ACCESSIBILITY QUESTION

Sudden loud sounds are difficult for me. Are any authorised activities or building works expected to create noise near my destination?

SENSORS AND TELEMETRY
Proposed evidence: room/route sound-level metrics for numerical peaks only; no audio recording. Planned works and event activity come from authoritative schedules, not acoustic inference. Coverage: the destination, immediate authorised route and named source area where relevant. Timing/aggregation: 1-second local sound calculation with 1-minute summaries; event/works status source-native and time-aligned. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current works/maintenance schedule, event/activity programme, room allocation, public notices and closures. Precedence: maintenance, organiser and room owners determine planned activity and disruption. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + recent-condition comparison. Decision interval: the planned use window. Minimum evidence: current planned-activity sources and correctly located sound evidence where available. Method: list verified expected sources, compare recent peak frequency with a matched baseline and avoid source attribution from sound alone. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: state the planned information only or return not assessable.

ANSWER BOUNDARY
Do not identify a sound source/person, inspect speech, diagnose a condition or promise that no sudden noise will occur. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person avoid known noisy periods or prepare an alternative.

4. Lighting, glare, acoustics, temperature, air, crowding and sensory comfort

AR-033 to AR-034 | 10 questions in this section | Compare environmental and sensory evidence honestly, with room-level coverage and no guarantee of personal suitability.

AR-033

GLARE

L2 - comparison

R2 - integration-dependent

ACCESSIBILITY QUESTION

I am sensitive to glare. Which verified seating zone is likely to have less glare at my planned time?

SENSORS AND TELEMETRY
Proposed evidence: calibrated horizontal/vertical illuminance and a validated glare proxy at named seating zones, plus blind state and outdoor solar irradiance where integrated. Coverage: eligible seating zones in the exact room; do not generalise from a wall or corridor sensor. Timing/aggregation: light sampled every 5-15 seconds and aggregated to 1 minute; outdoor solar at 1 minute; preserve sensor orientation and shading changes. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

ANALYSIS REQUIRED
Operation: observation + time-matched comparison + recommendation. Decision interval: the planned activity interval. Minimum evidence: correctly oriented seat-zone evidence, current layout and comparable sun/time conditions. Method: compare glare indicators and variability across eligible zones, including forecast solar context. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: qualify the answer or return not assessable when seat-zone coverage is absent.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current room/seating layout, orientation, window/blind configuration, event time, access and scheduled lighting changes. Precedence: room/organiser owners determine eligible seating; lighting evidence does not allocate seats. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANSWER BOUNDARY
Do not infer visual impairment, guarantee comfort, inspect screens/content, operate blinds/lights or reserve seating. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person request a seating zone with lower measured glare risk.

AR-034

FLICKER

L1 - lookup/observation

R3 - research or restricted

ACCESSIBILITY QUESTION

Is there a current room-specific flicker assessment, or an authorised alternative with verified lower-flicker lighting?

SENSORS AND TELEMETRY
Proposed evidence: a dedicated calibrated flicker meter or a current owner-held commissioning/test record for the exact room and lighting circuit. A standard lux sensor cannot establish flicker. Coverage must match the intended seating zone; test method, luminaire/driver configuration, date and maintenance changes must be recorded. Capability remains proposed until verified.

ANALYSIS REQUIRED
Operation: authorised lookup + measurement-validity check + comparison. Decision interval: before the planned use. Minimum evidence: a current room-specific assessment using a recognised flicker metric, or an eligible alternative assessed by the same method. Report the method, date, coverage and limits. Safe failure: state that no comparable assessment exists and return not assessable rather than infer flicker from illuminance.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current room allocation, luminaire/driver inventory, latest commissioning or specialist flicker assessment, maintenance state and verified alternative space. Precedence: lighting/facilities and room owners determine the authoritative assessment and alternative. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANSWER BOUNDARY
Do not infer health effects, claim low flicker from illuminance, certify medical suitability or operate lighting. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person verify whether credible low-flicker evidence exists or seek an alternative.

4. Lighting, glare, acoustics, temperature, air, crowding and sensory comfort

AR-035 to AR-036 | 10 questions in this section | Compare environmental and sensory evidence honestly, with room-level coverage and no guarantee of personal suitability.

AR-035

HEAT SENSITIVITY

L2 - observation/trend

R2 - integration-dependent

ACCESSIBILITY QUESTION

I am sensitive to heat. What are the current room-level temperature conditions, and how stable have they been recently?

SENSORS AND TELEMETRY
Proposed evidence: room-level air temperature and relative humidity; mean-radiant temperature and air speed only where a commissioned comfort reference node exists. Coverage: the occupied zone of the exact room; corridor/adjacent-room readings are not room evidence. Timing/aggregation: temperature/RH every 15-30 seconds aggregated to 1 minute; reference-node variables at validated rates; preserve sensor placement and HVAC/solar context. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current room purpose/access, HVAC zone/operating state, planned occupancy/activity, maintenance/closure notices and any authorised alternative. Precedence: room and facilities owners determine eligibility and HVAC status. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: current observation + recent stability trend + bounded recommendation. Decision interval: now through the planned use window. Minimum evidence: fresh correctly located data, recent completeness and relevant HVAC/solar/occupancy context. Method: report current values and variability over a stated recent window; do not convert them into a universal comfort claim. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: give a qualified comparison/alternative or return not assessable.

ANSWER BOUNDARY
Do not infer medical risk or heat tolerance, guarantee comfort, diagnose HVAC faults or operate temperature controls. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person decide whether to use the room, shorten the visit or request an alternative.

AR-036

AIR CONTEXT

L2 - observation/trend

R2 - integration-dependent

ACCESSIBILITY QUESTION

I have respiratory sensitivities. What verified room-level information is available about ventilation and particulate conditions?

SENSORS AND TELEMETRY
Proposed evidence: correctly located room-level NDIR CO2, calibrated PM2.5, temperature and relative humidity; mapped HVAC airflow/status only from the equipment serving that room. TVOC may provide broad context but not compound-specific safety evidence. Sample environmental sensors at 10-60 seconds and retain aligned 1-minute values. Quality gate: in-situ checks, calibration/drift records, completeness, clock alignment, maintenance state and provenance; never substitute corridor data.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current room purpose/access, HVAC service mapping, filter/maintenance state, scheduled activity, outdoor PM/weather and authorised alternative. Precedence: facilities/HVAC and room owners determine operating context; official health/safety advice overrides telemetry. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: room-level observation + trend comparison. Decision interval: now and the planned use window. Minimum evidence: fresh room data, adequate occupied-zone coverage, outdoor/context data and mapped HVAC state where used. Report measurements, trends and missingness; CO2 is a ventilation indicator, not complete air quality. Safe failure: qualify the answer or return not assessable when placement, calibration or coverage is inadequate.

ANSWER BOUNDARY
Do not make medical, exposure, infection-risk or safety claims, identify occupants, diagnose a fault or treat CO2 as complete air quality. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Gives the person transparent room-level air context for their own participation choice.

4. Lighting, glare, acoustics, temperature, air, crowding and sensory comfort

AR-037 to AR-038 | 10 questions in this section | Compare environmental and sensory evidence honestly, with room-level coverage and no guarantee of personal suitability.

AR-037

LOWER CROWDING

L3 - forecast/recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Crowding is difficult for me. Which eligible space or time is forecast to be less crowded?

SENSORS AND TELEMETRY

Proposed evidence: anonymous bidirectional counts or privacy-preserving room counts at every entrance to each eligible space; no identity, device or movement-history data. Coverage: the exact eligible spaces and queue/entry boundaries being compared. Timing/aggregation: events reconciled to 1-minute counts; validate count error, multi-door coverage and room-capacity mapping. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: current room purpose, access/booking, capacity, scheduled activity, opening hours and closures. Precedence: room/organiser owners determine eligibility and availability; counts do not create permission. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED

Operation: short-horizon forecast + recommendation. Decision interval: the requested time window. Minimum evidence: complete anonymous count coverage, current schedule and comparable space/time evidence. Method: forecast broad occupancy bands with uncertainty and compare only eligible spaces/times. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: report current observation only or return not assessable when coverage/comparability is weak.

ANSWER BOUNDARY

Do not identify attendees, infer disability, promise low crowding, disclose exact sensitive occupancy or reserve a space. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person select a less crowded authorised space or time.

AR-038

SENSORY ROUTE

L3 - multi-criteria recommendation

R3 - research or restricted

ACCESSIBILITY QUESTION

Which authorised route best matches the noise, crowding and lighting preferences I state for this journey?

SENSORS AND TELEMETRY

Proposed evidence: segment-level numerical LAeq/peak metrics, illuminance variability and anonymous people counts; no raw audio, cameras, device tracking or continuous personal location. Coverage: every segment of each candidate authorised route; any uncovered segment must remain explicit. Timing/aggregation: sound locally computed at 1 second and stored per minute; light/counts as aligned 1-minute aggregates; preserve route-layout changes. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: current route/access graph, door/lift status, works/events, opening restrictions and destination status. Precedence: route/access owners determine eligibility; the person chooses the sensory priorities/weights. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED

Operation: multi-criteria route comparison + recommendation. Decision interval: the requested movement window. Minimum evidence: fully verified routes with comparable segment-level evidence and stated preferences. Method: score noise, crowding and lighting separately, disclose weights/trade-offs and include distance/asset status. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: offer a qualified route with unknown segments flagged or return not assessable.

ANSWER BOUNDARY

Do not infer sensory condition from behaviour, hide weighting, track movement, guarantee low stimulation or recommend an unauthorised route. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person choose a route using their own stated sensory priorities.

4. Lighting, glare, acoustics, temperature, air, crowding and sensory comfort

AR-039 to AR-040 | 10 questions in this section | Compare environmental and sensory evidence honestly, with room-level coverage and no guarantee of personal suitability.

AR-039

STABLE CONDITIONS

L2 - comparison

R2 - integration-dependent

ACCESSIBILITY QUESTION

I need stable conditions rather than one good reading. Which authorised space has been most stable recently?

SENSORS AND TELEMETRY
Proposed evidence: correctly located room-level temperature/RH, CO2, illuminance and numerical acoustic metrics; anonymous occupancy only as context. Coverage: each eligible room/zone being compared. Timing/aggregation: aligned 1-minute records over a stated recent period; require comparable sampling, calibration, completeness, room use and HVAC state. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current room purpose/access, scheduled activity, HVAC/lighting state, maintenance, closures and authorised alternatives. Precedence: space owners determine eligibility; operations context is required to compare variability. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: time-series stability calculation + matched comparison. Decision interval: the planned use window informed by a stated recent baseline. Minimum evidence: eligible rooms with sufficient complete, comparable data and known operating context. Method: compare median, variability and excursion frequency rather than single readings; disclose baseline and missingness. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: restrict to supported variables or return not assessable.

ANSWER BOUNDARY
Do not create a universal comfort score, infer health/needs, guarantee future stability or treat an empty room as available. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person choose a space with more stable measured conditions.

AR-040

CONDITION ALERT

L3 - change detection/recommendation

R3 - research or restricted

ACCESSIBILITY QUESTION

If conditions in my chosen space pass a limit I set, can I receive a private alert and a verified alternative?

SENSORS AND TELEMETRY
Proposed evidence: a user-selected threshold evaluated against correctly located room-level numerical data; private session-scoped notifications and owner-approved alternative-space status. No diagnosis or permanent profile. Coverage: the chosen authorised room and any pre-approved alternative. Timing/aggregation: 1-minute quality-controlled values; require freshness, consecutive-sample logic and suppression during sensor faults/maintenance. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current room/access/booking, alternative-space eligibility, notification channel/privacy notice, maintenance and closure status. Precedence: space owners determine alternatives; the person controls thresholds and session-scoped contact choice. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: change detection + bounded recommendation. Decision interval: the stated use interval. Minimum evidence: a user-set limit, fresh valid data, persistence rule and authorised fallback. Method: trigger only after the stated persistence/quality gate; label the event as an observation, not a health/safety determination. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: suppress the alert and state not assessable during bad/stale data.

ANSWER BOUNDARY
Do not infer a health condition, send alerts without explicit opt-in, retain a permanent profile, guarantee suitability, or move/reserve a space. Use only requirements the person states for this session. No identity, tracking, content inspection, building control or accessibility/safety certification; authorised space owners remain responsible.

WHY THIS IS USEFUL

Lets the person receive a private prompt to reconsider their plan when chosen conditions change.

5. Public wayfinding, signage, communication and assistive information

AR-041 to AR-042 | 10 questions in this section | Receive verified directions and updates in a usable format without identity, content inspection or invented cues.

AR-041

PLAIN DIRECTIONS

L1 - route calculation

R1 - practical

ACCESSIBILITY QUESTION

Can you give step-by-step directions in plain language without relying only on colour, small signs or visual landmarks?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current route, door/lift status and official wayfinding content; no colour recognition, camera or personal-location tracking is required. Coverage: the complete authorised route from the stated origin to destination. Timing: use current route/status retrieval times and a session-only coarse origin. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current public route graph, entrance/destination, door/lift status, closures, verified landmarks/help points and accessible communication guidance. Precedence: wayfinding/access owners determine the route and wording. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: whole-route calculation + accessible-language transformation. Decision interval: the current/planned journey. Minimum evidence: a complete authorised route and current status at every critical segment. Method: produce stepwise directions using distances, turns and non-colour-dependent cues; preserve fallback/help points. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: state the last verified step and official contact, or return not assessable.

ANSWER BOUNDARY
Do not track the person, infer visual ability, invent landmarks or promise the route will remain open. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Provides directions that can be followed without relying only on colour or small visual signs.

AR-042

ACCESSIBLE FORMAT

L1 - authorised lookup

R1 - practical

ACCESSIBILITY QUESTION

Can you provide my route and essential instructions in large text, high contrast or a screen-reader-friendly format?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current authoritative route/instruction content and an accessible rendering service supporting large text, high contrast and screen-reader-compatible structure. Coverage: the requested public information only. Timing: use the current source version and session-selected format. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current wayfinding, event/visit instructions, accessibility communication standards and official contact information. Precedence: content owners determine meaning; the rendering service may transform presentation, not substance. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + format transformation. Decision interval: the current interaction. Minimum evidence: current source content and the format preference the person states. Method: preserve headings, sequence, links, warnings and source metadata; validate output structure where possible. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: offer plain text/official document or defer if a reliable transformation is unavailable.

ANSWER BOUNDARY
Do not infer impairment, demand proof, alter official meaning or claim conformance without a verified accessibility test. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person receive essential information in a format they can use.

5. Public wayfinding, signage, communication and assistive information

AR-043 to AR-044 | 10 questions in this section | Receive verified directions and updates in a usable format without identity, content inspection or invented cues.

AR-043

TACTILE SIGNS

L1 - authorised lookup

R1 - practical

ACCESSIBILITY QUESTION

Where are tactile or Braille signs currently confirmed on my route, and which decision points do not have them?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: a current audited tactile/Braille/high-contrast signage inventory; no camera-based sign detection. Coverage: the selected route and every decision point on it. Timing: use the audit/version date and current route/closure status. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current signage audit, route graph, entrance/destination, replacement/maintenance notices and staffed help points. Precedence: wayfinding/accessibility and facilities owners determine signage status. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + route coverage calculation. Decision interval: the planned journey. Minimum evidence: a complete route and sign inventory at each decision point. Method: list confirmed cues and explicitly identify gaps; compare alternative routes only if fully verified. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: recommend a staffed orientation option or return not assessable.

ANSWER BOUNDARY
Do not infer visual impairment, invent missing signs, use images to identify the person or certify that signage is sufficient for every user. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person know where tactile/Braille cues exist and where assistance may be needed.

AR-044

CONTROL DESCRIPTION

L1 - authorised lookup

R2 - integration-dependent

ACCESSIBILITY QUESTION

Can you describe the lift controls, floor announcements and door controls I will encounter in a format I can use?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current owner-issued descriptions and status for lift controls, floor announcements, automatic/manual door controls and help-call points; no recording of user interaction. Coverage: the exact assets on the planned route. Timing: use the latest commissioning/instruction version and current service status. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current asset operating instructions, tactile/audio/visual features, floor numbering, route/access rules, maintenance status and official assistance contact. Precedence: lift/door/accessibility owners determine the authoritative description and service status. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + accessible-format transformation. Decision interval: before and during the journey. Minimum evidence: asset-specific instructions/features and current status. Method: describe controls in the person-selected format and route order; distinguish installed feature from currently working status. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to staff or return not assessable if asset details/status are unverified.

ANSWER BOUNDARY
Do not operate controls, infer dexterity/hearing/vision, record interactions or guarantee that a feature meets an individual need. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person anticipate the controls and announcements they will encounter.

5. Public wayfinding, signage, communication and assistive information

AR-045 to AR-046 | 10 questions in this section | Receive verified directions and updates in a usable format without identity, content inspection or invented cues.

AR-045

DIGITAL SIGNAGE

L1 - status observation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Which public digital signs on my route are officially reported as working and showing current information?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: digital-signage content-management health, player/display heartbeat and last successful content update; no camera inspection of screens or viewers. Coverage: the named public signs on the authorised route. Timing: heartbeat/status source-native with displayed-content version and update time. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current public information source, signage inventory, route, maintenance notice and alternative communication channel. Precedence: content/signage owners determine current information; device telemetry only reports delivery status. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + service-status observation. Decision interval: the current journey. Minimum evidence: sign identity, content version, device heartbeat and an authoritative fallback. Method: cross-check content publication and player/display status; report last update and any conflict. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: direct to the official alternative channel or return not assessable.

ANSWER BOUNDARY
Do not inspect screens with cameras, infer who viewed information or treat a powered display as proof the content is current/correct. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person know whether to rely on a sign or use another official information source.

AR-046

ONE STEP AT A TIME

L1 - dialogue transformation

R1 - practical

ACCESSIBILITY QUESTION

I process directions better one step at a time. Can you give one instruction, wait for my confirmation, and then continue?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: session-scoped dialogue state that stores only the current route step and confirmation; no location tracking or persistent profile. Coverage: the current interaction and selected route only. Timing: advance only after explicit confirmation; expire state when the session ends. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current route/instruction source, closure/status updates and official help contact. Precedence: route/content owners determine the directions; the person controls pacing. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: dialogue transformation + stepwise route presentation. Decision interval: the current journey. Minimum evidence: a complete verified route and explicit confirmation after each step. Method: present one instruction at a time, allow repeat/backtrack and revalidate status after delays. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: pause and provide help/contact when location/status is uncertain.

ANSWER BOUNDARY
Do not infer cognitive/neurodivergent status, track precise location, pressure the person to continue or continue on an invalidated route. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person control the pace and reduce information overload.

5. Public wayfinding, signage, communication and assistive information

AR-047 to AR-048 | 10 questions in this section | Receive verified directions and updates in a usable format without identity, content inspection or invented cues.

AR-047

TEXT CONTACT

L1 - authorised lookup

R1 - practical

ACCESSIBILITY QUESTION

I communicate mainly by text. Which official text channel can I use to contact reception, the organiser or security?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current status for approved SMS, web-chat or text-relay channels; no reading or retention of message content beyond the authorised service. Coverage: the relevant reception, organiser or security contact channel. Timing: use owner-published service hours and current channel status. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: official text contact details, service hours, purpose/permission scope, privacy notice and fallback channel. Precedence: the channel owner determines availability and appropriate use. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup. Decision interval: before/during the visit. Minimum evidence: a current official channel and fallback. Method: return the channel, hours, expected response and scope; do not test it using personal information. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to the official alternative when no text channel is confirmed.

ANSWER BOUNDARY
Do not inspect messages, expose private contact details, infer communication needs or promise response time beyond the owner's statement. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person contact an official service without relying on speech.

AR-048

CAPTIONED UPDATES

L1 - lookup/status

R2 - integration-dependent

ACCESSIBILITY QUESTION

If there is a public announcement, which verified text, caption or visual alternative will be available?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current certified/public-announcement distribution status and owner-issued availability of text, caption, visual or other authorised alternative channels; no speech capture. Coverage: the building/event zones relevant to the person. Timing: use source-native event time, channel heartbeat and last-test/commissioning record. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current event communication plan, public/certified alert channels, caption/text provision, responsible contact and official emergency communication. Precedence: organiser and competent safety/communications owners determine what is provided. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + channel-status check. Decision interval: the event/visit window. Minimum evidence: current provision and owner status for the relevant zone/channel. Method: state which alternative is confirmed, last checked/tested and how to access it. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to the organiser/competent authority if status is unknown.

ANSWER BOUNDARY
Do not record announcements, infer hearing status, replace certified alarms/official messages or guarantee receipt by an individual. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person identify the verified non-audio route for important updates.

5. Public wayfinding, signage, communication and assistive information

AR-049 to AR-050 | 10 questions in this section | Receive verified directions and updates in a usable format without identity, content inspection or invented cues.

AR-049

ROOM CHANGE

L2 - notification/route

R2 - integration-dependent

ACCESSIBILITY QUESTION

If my room or route changes, can the official update reach me in my chosen format and include a newly verified route?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: authorised room/route-change feed, door/lift status and a session-consented accessible notification channel; no personal location tracking. Coverage: the changed origin/destination and complete revised route. Timing: use effective/change time, retrieval time and revalidate route assets immediately before use. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current organiser/room-allocation update, access policy, wayfinding route, lift/door status, closure notices and official contact. Precedence: organiser/room/access owners determine the change and valid route. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + whole-route recalculation + notification. Decision interval: from official change until the activity starts. Minimum evidence: a current authoritative change, fully verified revised route and consented format/channel. Method: separate the official change from route calculation; highlight any new unverified segment. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: send/offer only the confirmed information or defer/not assessable.

ANSWER BOUNDARY
Do not infer the person's location, expose other attendees, grant access or treat telemetry as proof the changed room is authorised/accessible. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person receive a usable update and re-plan before moving.

AR-050

SIMPLE ROUTE

L2 - route recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Can you give me an authorised route with fewer decision points and clear places to reorient, even if it is slightly longer?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current route graph, verified orientation/help points and owner-issued door/lift status; optional anonymous crowd band only as secondary context. Coverage: every segment of each eligible route. Timing: status source-native; optional counts as 1-minute aggregates. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current authorised routes, access restrictions, decision-point/landmark inventory, staffed help points and closures. Precedence: wayfinding/access owners determine route validity; the person states preference for fewer decisions. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: route-complexity calculation + recommendation. Decision interval: the planned movement interval. Minimum evidence: fully verified routes, decision points, cues and asset status. Method: minimise decision points first, then compare distance and status; retain clear reorientation points. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: provide a staffed option or return not assessable.

ANSWER BOUNDARY
Do not infer cognitive/neurodivergent status, track movement, hide a longer distance or recommend an unauthorised route. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person choose a simpler route even when it is slightly longer.

6. Toilets, amenities, rest, quiet spaces and accompanying people

AR-051 to AR-052 | 10 questions in this section | Plan breaks, amenities and support-person arrangements using current owner records and proportionate status evidence.

AR-051

ACCESSIBLE TOILET

L1 - lookup/status

R2 - integration-dependent

ACCESSIBILITY QUESTION

Where is the nearest verified accessible toilet on my route, and is it officially reported open or out of service?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: owner-issued accessible-toilet service/outage status and optional privacy-preserving occupied/free indicator approved for the facility; no identity or use history. Coverage: the exact facility and complete route from the stated location. Timing: status source-native; any occupancy indicator event-based with no retained history. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current accessible-toilet register, features, opening/access rules, route, out-of-service/cleaning notices and fallback facility. Precedence: facilities/accessibility owners determine provision and status. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + nearest-facility calculation + status observation. Decision interval: the current journey. Minimum evidence: current facility record, complete verified route and fresh service status. Method: rank eligible facilities by whole-route distance and status; label occupancy only when an approved indicator exists. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: provide the verified location/fallback and defer current availability when status is stale.

ANSWER BOUNDARY
Do not identify users, infer health, record use history, operate locks, certify cleanliness/suitability or infer availability from nearby occupancy. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person plan a necessary stop and avoid an out-of-service facility.

AR-052

CHANGING PLACES

L1 - authorised lookup

R1 - practical

ACCESSIBILITY QUESTION

Is a Changing Places toilet available in or near Abacws, and what are the current verified access arrangements?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current owner-published facility inventory and service/access status; no personal or occupancy sensing is required. Coverage: the confirmed facility in or near Abacws and the complete route to it. Timing: use current facility/access publication and outage time. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current Changing Places register, verified features/equipment, opening/access arrangements, route, outage notice and responsible contact. Precedence: facility/accessibility owners determine whether the facility exists, is open and can be used. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + whole-route calculation. Decision interval: the planned/current visit. Minimum evidence: a current facility record and verified route/access arrangement. Method: state location, verified features, opening/access and route; distinguish in-building from nearby provision. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to the facility owner or return not assessable.

ANSWER BOUNDARY
Do not infer need, guarantee equipment availability/cleanliness, grant access or substitute a standard accessible toilet. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person decide whether the visit can meet the facility requirement they state.

6. Toilets, amenities, rest, quiet spaces and accompanying people

AR-053 to AR-054 | 10 questions in this section | Plan breaks, amenities and support-person arrangements using current owner records and proportionate status evidence.

AR-053

REST POINTS

L2 - route calculation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Where are the confirmed rest points on my route, and how far apart are they?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current audited seating/rest-point inventory, route geometry and owner-issued access/closure status; optional anonymous crowd bands only for likely availability context. Coverage: the entire selected route and each listed rest point. Timing: use inventory version/current status; optional counts as 1-minute aggregates. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current route, seating/rest-point locations and features, opening/access rules, temporary removal/closure notices and destination. Precedence: space/route owners determine which rest points are authorised and available. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + spacing calculation. Decision interval: the planned journey. Minimum evidence: a complete route and verified rest-point positions/status. Method: calculate distances between successive rest points and compare with the interval the person states. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: identify gaps and offer a verified alternative/staff contact, or return not assessable.

ANSWER BOUNDARY
Do not infer stamina, promise a free seat, reserve seating or treat apparent vacancy as availability. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person plan where to pause and whether the route matches their stated rest interval.

AR-054

QUIET REST

L2 - comparison

R2 - integration-dependent

ACCESSIBILITY QUESTION

Is there an authorised quiet or lower-stimulation space I can use, and when is it officially available?

SENSORS AND TELEMETRY
Proposed evidence: room-level numerical LAeq/peak metrics, illuminance variability and anonymous occupancy for eligible quiet/lower-stimulation spaces; no raw audio, images or identities. Coverage: each named authorised space and complete route; corridor evidence cannot represent a closed space. Timing/aggregation: aligned 1-minute aggregates with acoustic/light calibration, room mapping and operating-state flags. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current quiet/lower-stimulation space designation, access/booking/opening, room purpose, scheduled use, capacity and closures. Precedence: space/accessibility owners determine whether and when the space may be used. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + current comparison + recommendation. Decision interval: the requested break interval. Minimum evidence: eligible spaces, complete routes and comparable fresh room-level evidence. Method: compare noise/light/crowding separately and show uncertainty; do not infer availability from sensor values. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: give the official option/contact or return not assessable.

ANSWER BOUNDARY
Do not record speech, infer distress, guarantee low stimulation, grant use, reserve space or expose other users. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person choose a verified lower-stimulation break option.

6. Toilets, amenities, rest, quiet spaces and accompanying people

AR-055 to AR-056 | 10 questions in this section | Plan breaks, amenities and support-person arrangements using current owner records and proportionate status evidence.

AR-055

WAIT WITH SUPPORTER

L2 - recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Where can I wait with my support person without blocking circulation or entering a restricted area?

SENSORS AND TELEMETRY
Proposed evidence: optional anonymous count at the authorised waiting-area boundary and current route door/lift status; no identity, companion relationship or movement tracking. Coverage: the eligible waiting areas and complete route from the stated origin. Timing/aggregation: counts as 1-minute aggregates with full entrance coverage; asset status event-driven. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current public waiting areas, access rules, seating/capacity, circulation constraints, companion policy, opening and closures. Precedence: organiser/space/access owners determine where waiting is permitted. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + route/capacity comparison + recommendation. Decision interval: the requested waiting interval. Minimum evidence: eligible waiting areas, route, capacity/seating record and current status. Method: filter restricted areas, compare route and aggregate crowd context, and preserve circulation. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: provide the official staffed alternative or return not assessable.

ANSWER BOUNDARY
Do not infer relationships, identify people, promise seats, grant access or recommend an apparently empty restricted area. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person and supporter wait together in an authorised, practical location.

AR-056

DRINKING WATER

L1 - lookup/status

R2 - integration-dependent

ACCESSIBILITY QUESTION

Where is the nearest verified drinking-water point on my accessible route, and is it officially in service?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: owner-issued drinking-water point service status; flow/pressure telemetry only if already approved for maintenance and mapped to the exact outlet, not to infer use. Coverage: the named water point and complete accessible route. Timing: use current service/outage status and source-native telemetry time if present. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current drinking-water inventory, access/opening, route, maintenance/out-of-service notice and alternative point. Precedence: facilities/amenity owners determine service status and availability. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + nearest-point calculation + status check. Decision interval: the current/planned visit. Minimum evidence: a current amenity record, complete route and owner status. Method: return nearest eligible point, verified route and fallback; do not infer potability or cleanliness from flow. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to owner or return not assessable.

ANSWER BOUNDARY
Do not identify users, monitor consumption, operate the outlet or certify water quality without authoritative testing. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person plan hydration without an unnecessary detour to an unavailable point.

6. Toilets, amenities, rest, quiet spaces and accompanying people

AR-057 to AR-058 | 10 questions in this section | Plan breaks, amenities and support-person arrangements using current owner records and proportionate status evidence.

AR-057

BREAK SEATING

L2 - constraint check

R2 - integration-dependent

ACCESSIBILITY QUESTION

Does the authorised break area have verified seating and turning space that fit the measurements I provide?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current audited seating/turning geometry and optional anonymous aggregate occupancy at the break-area boundary; no person/device measurement. Coverage: the authorised break area, seating positions and route. Timing: use audit/layout version and current access/status; optional counts per minute. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current break-area purpose/access, seating plan/dimensions, turning/circulation clearances, capacity and closures; dimensions the person chooses to provide. Precedence: space/accessibility owners determine eligibility and geometry. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised constraint calculation. Decision interval: the planned break interval. Minimum evidence: current geometry/status and any person-supplied dimensions. Method: compare clearances plus tolerance and identify unknown/blocked segments; occupancy is context only. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: offer a verified alternative or return not assessable.

ANSWER BOUNDARY
Do not infer mobility aid or body size, promise a seat, reserve/alter furniture or certify manoeuvrability. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person judge whether the break area can accommodate the dimensions they state.

AR-058

PRIVATE SUPPORT

L1 - authorised lookup

R3 - research or restricted

ACCESSIBILITY QUESTION

I may need privacy to manage medication or another personal need. Which official private-space or support option can staff confirm?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: an owner-issued inventory/status for an authorised private space or staffed support route; no environmental, occupancy or content sensing is required. Coverage: the responsible official service and, only if authorised, the confirmed space/route. Timing: use current service hours, purpose, access and owner confirmation time. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current accessibility/well-being/first-aid process, designated private-space rules, access/booking, responsible contact and emergency guidance. Precedence: competent staff determine what is appropriate, available and private. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup. Decision interval: the current/planned visit. Minimum evidence: a current official support process and contact; a location only when explicitly confirmed. Method: return the verified process and minimal location/route information needed. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer; never propose an apparently empty room.

ANSWER BOUNDARY
Do not ask why privacy is needed, record medication/health information, monitor the space or promise confidentiality from telemetry. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person arrange a private option without unnecessary disclosure.

6. Toilets, amenities, rest, quiet spaces and accompanying people

AR-059 to AR-060 | 10 questions in this section | Plan breaks, amenities and support-person arrangements using current owner records and proportionate status evidence.

AR-059

ASSISTANCE DOG

L1 - authorised lookup

R1 - practical

ACCESSIBILITY QUESTION

Can I bring an assistance dog, and which current routes and areas are authorised?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current policy and route/access status only; no animal, person or device sensing. Coverage: the authorised entrance, route, destination and relevant amenities. Timing: use the current policy effective time and live route/closure status. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current assistance-dog policy, registration/visitor instructions, accessible routes, relief/water information if officially provided, room/event rules and contact. Precedence: organiser, access and space owners determine entry and area use. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + route check. Decision interval: before and during the visit. Minimum evidence: current policy, destination-specific rules and complete route. Method: state confirmed arrangements and any advance-contact step; avoid assumptions about the person or dog. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to the responsible service when the policy is event-specific or unclear.

ANSWER BOUNDARY
Do not demand proof beyond official policy, infer disability, identify/track the person or animal, or grant access. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person confirm practical access arrangements for an assistance dog.

AR-060

HELP DURING BREAK

L1 - authorised lookup

R1 - practical

ACCESSIBILITY QUESTION

If I need help during a break, what is the official contact method and nearest verified help point?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current owner-issued help-point/contact status and route to a staffed location; no personal-location tracking beyond a user-stated coarse area. Coverage: the person's stated area and route to the relevant help point. Timing: use service hours, last status update and current route/closure information. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current reception/organiser/security/accessibility contact methods, staffed help points, opening hours, route and escalation guidance. Precedence: the responsible service determines availability and response. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + nearest/help-route calculation. Decision interval: the current break/visit interval. Minimum evidence: coarse location, current contacts/help points and a verified route. Method: return the most appropriate official contact and route, plus fallback. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to official emergency communications when relevant; otherwise not assessable.

ANSWER BOUNDARY
Do not infer why help is needed, identify/track the person, promise immediate response or replace emergency services. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person know whom to contact and where to seek help during a break.

7. Disruptions, lift or route outages, closures, evacuation and emergency information

AR-061 to AR-062 | 10 questions in this section | Use current official status and emergency communications; the service never improvises safety instructions.

AR-061

OUTAGE CHECK

L1 - lookup/status

R2 - integration-dependent

ACCESSIBILITY QUESTION

Is any lift, automatic door or accessible route segment on my planned route currently reported out of service?

SENSORS AND TELEMETRY
Proposed evidence: lift-controller service/fault state, automatic-door operator/contact state and owner-issued route closure status for the exact planned route. Coverage: every required lift, door and route segment; nearby assets are not substitutes. Timing/aggregation: event-driven status with a 30-second heartbeat, maintenance state and last owner confirmation. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current lift/door outage notices, route closures, access/opening, maintenance information and official alternatives/contact. Precedence: facilities/lift, access/security and organiser owners determine service and route validity. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + status observation + route answerability check. Decision interval: now and the planned journey. Minimum evidence: fresh owner status for every critical asset/segment. Method: cross-check telemetry with official notices and flag disagreement; do not infer failure from missing data. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: provide the last verified point and official alternative/contact, or not assessable.

ANSWER BOUNDARY
A healthy feed is not certification, a missing feed is not proof of outage, and telemetry cannot create an alternative route or permission. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person re-plan before encountering an inaccessible route segment.

AR-062

LIFT FAILURE

L2 - contingency

R3 - research or restricted

ACCESSIBILITY QUESTION

If the main lift becomes unavailable while I am inside, what official alternative or staff-assistance procedure is in force?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current owner-issued lift outage status and approved accessible contingency/assistance procedure; no automatic route invention. Coverage: the current floor, destination and every officially designated alternative. Timing: use the outage effective time, owner confirmation and current route status. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current lift outage, approved accessible-route contingency, staffed assistance procedure, access/opening and official contact. Precedence: facilities/lift, security, organiser and emergency authorities determine the response. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authoritative contingency lookup. Decision interval: the current outage and visit. Minimum evidence: confirmed lift status plus an owner-approved alternative or staff-assistance procedure. Method: relay the official options and their verified route limits; do not optimise beyond the approved plan. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: show the official contact/instruction and mark further travel not assessable.

ANSWER BOUNDARY
Do not operate the lift, infer the person's location, invent assistance/evacuation instructions or grant restricted access. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person decide whether to wait, seek staff help or change plans using an official contingency.

7. Disruptions, lift or route outages, closures, evacuation and emergency information

AR-063 to AR-064 | 10 questions in this section | Use current official status and emergency communications; the service never improvises safety instructions.

AR-063

ACCESSIBLE CHANGE NOTICE

L1 - notification

R2 - integration-dependent

ACCESSIBILITY QUESTION

How will I receive a room, entrance or route-closure notice in a format I can use?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: official room/entrance/route change feed and status of the person-selected accessible communication channel; no personal tracking. Coverage: the affected event/visit and revised route. Timing: use change effective time, retrieval time and channel delivery status. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current organiser/facilities closure notice, room/entrance allocation, route/lift/door status, accessibility communication route and official contact. Precedence: the source owner/competent authority determines the change and effective time. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + accessible-format notification. Decision interval: from the official change until the relevant movement/visit. Minimum evidence: a current authoritative change, affected scope and verified alternative route/instruction. Method: present the change, impact, effective time and recheck point in the chosen format. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: do not send unverified advice; defer/not assessable.

ANSWER BOUNDARY
Do not infer disability, location or attendance, expose other people, create a route from telemetry or promise message delivery. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person receive and act on a closure in a usable format.

AR-064

ALARM INFORMATION

L1 - official relay

R3 - research or restricted

ACCESSIBILITY QUESTION

If an alarm activates, which official information should I follow for my current location?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: certified alarm-zone status and official emergency communication feeds only. Experimental environmental or occupancy telemetry must not generate or alter instructions. Coverage is limited to the person's stated current area and the official channels serving it; preserve source-native event times, message times, source identity and availability.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: certified alarm system, official emergency instructions, organiser/building safety communications and competent authority contacts. Precedence: certified alarms and competent authorities always prevail. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: official information relay. Decision interval: during an active alarm or incident. Minimum evidence: a current certified event and an authoritative instruction for the relevant area. Relay the official wording, source and time; do not calculate a personalised emergency route. Safe failure: if no authoritative message is available, instruct the person to follow alarms, staff and emergency services.

ANSWER BOUNDARY
Do not suppress/replace alarms, improvise emergency instructions, certify personal safety or reveal restricted operational details. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Gives the person a clear source of official information during an alarm.

7. Disruptions, lift or route outages, closures, evacuation and emergency information

AR-065 to AR-066 | 10 questions in this section | Use current official status and emergency communications; the service never improvises safety instructions.

AR-065

EVACUATION SUPPORT

L1 - authorised lookup

R3 - research or restricted

ACCESSIBILITY QUESTION

I cannot use stairs. Which general evacuation-assistance arrangements apply, and who should I contact before arrival?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: current general evacuation-assistance procedure and official contact only; no personal tracking, health/support records or PEEP access. Coverage: the building/event context stated by the person. Timing: use current policy effective time and official contact availability. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current general evacuation-assistance policy, named safety/accessibility contact, venue/event instructions and certified alarm information. Precedence: competent safety authorities and any separately managed personal plan prevail. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup. Decision interval: pre-visit planning or before an incident. Minimum evidence: current general procedure, official contact and relevant venue/event instruction. Method: explain how to request individual planning without requesting a diagnosis. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to the responsible accessibility/safety service; do not create a personal plan.

ANSWER BOUNDARY
Provide only general, current arrangements and official contacts; do not request or disclose a PEEP, create a personal evacuation plan, promise assistance or certify egress. Use only requirements the person chooses to state. Do not identify or track people, operate alarms/lifts/doors, or override fire-safety and emergency authorities.

WHY THIS IS USEFUL Lets the person contact the right service before the visit instead of relying on an improvised plan.

AR-066

VISUAL ALERTS

L1 - lookup/status

R3 - research or restricted

ACCESSIBILITY QUESTION

I may not hear an audible alarm. Which verified visual, vibrating or staff-assisted notification provision is available?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: certified visual-alert device inventory, commissioning/test record and current owner-issued service status; optional official vibrating/personal alert process where offered. No cameras or personal-device tracking. Coverage: the relevant room/zone and authorised notification channel. Timing: use latest test time, current fault/service status and official message time. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current certified alarm/visual-alert provision, latest test/maintenance status, event/venue communication plan and responsible safety contact. Precedence: fire/safety and venue owners determine provision and instructions. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + service-status check. Decision interval: before the visit and during any official alert. Minimum evidence: zone-specific provision, current test/status and official contact. Method: state what is installed/confirmed, last checked and how official information will be provided. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to the safety owner when status is unknown.

ANSWER BOUNDARY
Do not infer hearing ability, guarantee a notification will be perceived, create a personal emergency plan or substitute for certified alarms and staff procedures. Use only the person's stated communication requirement. No identity, tracking, system control or safety certification; competent authorities remain decisive.

WHY THIS IS USEFUL Lets the person verify the official non-audio alert provision and contact route.

7. Disruptions, lift or route outages, closures, evacuation and emergency information

AR-067 to AR-068 | 10 questions in this section | Use current official status and emergency communications; the service never improvises safety instructions.

AR-067

AUDIBLE ALERTS

L1 - lookup/status

R3 - research or restricted

ACCESSIBILITY QUESTION

I may not see visual alerts. Which verified audible or staff-assisted notification provision is available?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: certified audible/voice-alarm provision, commissioning/test record and current owner-issued status; no recording or analysis of announcements. Coverage: the relevant room/zone. Timing: use latest test time, current fault/service status and official message time. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current certified audible/voice alarm provision, latest testing/maintenance, event/venue communication plan and responsible safety contact. Precedence: fire/safety and venue owners determine provision and instructions. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + service-status check. Decision interval: before the visit and during any official alert. Minimum evidence: zone-specific provision and current authoritative status. Method: state what is confirmed and the official fallback/staff-assistance process. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: defer to the safety owner when evidence is stale or conflicting.

ANSWER BOUNDARY
Do not infer vision, guarantee a notification will be perceived, create a personal emergency plan or substitute for certified alarms and staff procedures. Use only the person's stated communication requirement. No identity, tracking, system control or safety certification; competent authorities remain decisive.

WHY THIS IS USEFUL

Lets the person verify the official audible notification provision and fallback.

AR-068

EVACUATION CROWDING

L1 - official relay

R3 - research or restricted

ACCESSIBILITY QUESTION

Crowded evacuation is difficult for me. Which official instructions apply, and what will the talking-building service not improvise?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: official emergency instructions and certified alarm information only; anonymous crowd telemetry must not drive personal evacuation advice. Coverage: the current venue/zone. Timing: use authoritative incident time and message version. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current general evacuation instructions, organiser/venue safety information, staff assistance process, certified alarms and competent authority communications. Precedence: competent safety authorities prevail over all other sources. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: official information relay + boundary explanation. Decision interval: during an alarm or drill. Minimum evidence: current certified event status and official instructions for the stated area. Relay those instructions and identify the responsible contact; do not estimate evacuation flow or improvise a route for the individual. Safe failure: follow alarms, staff and emergency services.

ANSWER BOUNDARY
Do not create a personal evacuation route, analyse people flow for the person, suppress alarms, certify safety or reveal restricted response information. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Clarifies the official action source and prevents unsafe improvised advice.

7. Disruptions, lift or route outages, closures, evacuation and emergency information

AR-069 to AR-070 | 10 questions in this section | Use current official status and emergency communications; the service never improvises safety instructions.

AR-069

SEVERE WEATHER

L3 - recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

If severe weather or transport disruption affects my accessible route, which verified arrival or departure alternatives are available?

SENSORS AND TELEMETRY
Proposed evidence: correctly sited weather data plus owner-issued transport, entrance, route, door and lift status; no claim of surface safety from weather alone. Coverage: the full accessible journey from transport/drop-off to destination and back. Timing/aggregation: weather sampled every 10-30 seconds and aggregated to 1 minute; operator/route status source-native and aligned. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current severe-weather warnings, transport accessibility/service notices, opening/closure, designated entrances, verified routes and official alternatives/contact. Precedence: weather/transport operators, facilities/access and organiser owners determine current options. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + whole-journey comparison + bounded recommendation. Decision interval: the stated travel/visit interval. Minimum evidence: current operator/service evidence and a fully verified accessible route for each option. Method: compare only usable alternatives by exposure, transfers, route status and timing; state weather/transport uncertainty. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: prioritise official accessible options or return not assessable.

ANSWER BOUNDARY
Do not certify surfaces/travel as safe, infer health risk, guarantee operator assistance or recommend travel through a closed route. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person select an official arrival/departure fallback during disruption.

AR-070

DATA OUTAGE

L1 - safe failure

R2 - integration-dependent

ACCESSIBILITY QUESTION

If live data fails during a disruption, what can the service still tell me safely from authoritative sources?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: cached authoritative data with explicit source/version/expiry, plus current system-health status; no stale telemetry presented as live. Coverage: only the route/assets/services already verified before the outage. Timing: show last successful retrieval, expected refresh and expiry for each item. Quality gate: preserve source identity, aligned clocks, uptime and gaps, maintenance/version state, permission scope and provenance. The integration remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current or last-known official opening/access, route, closure, contact and emergency information, with owner-defined validity periods. Precedence: competent authorities and source owners determine what remains valid. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: safe-failure and answerability assessment. Decision interval: the outage interval. Minimum evidence: source timestamps, validity/expiry and an official contact/fallback. Method: separate still-valid static facts from stale status; do not extrapolate live conditions. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: provide official contact/instructions or return not assessable.

ANSWER BOUNDARY
Do not conceal the outage, label cached data as live, infer asset state, create permission or provide improvised emergency advice. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Shows what can still be relied on safely when live integrations fail.

8. Independence, dignity, privacy, reliability, contingencies and lower-impact choices

AR-071 to AR-072 | 10 questions in this section | Preserve person-controlled preferences, transparent evidence, dependable fallbacks and honest abstention.

AR-071

MINIMAL PREFERENCES

L1 - privacy control

R3 - research or restricted

ACCESSIBILITY QUESTION

Can the service use the route and sensory preferences I state for this visit without storing a diagnosis or permanent profile?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: session-scoped preference controls, purpose and retention settings, consent state and an audit record of deletion or expiry. Store only the functional requirements needed for the current plan; no diagnosis or permanent accessibility profile. Quality gate: verified privacy configuration, access control, timestamps and deletion status.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current privacy notice, consent options, data-minimisation/retention policy, deletion control and service permission scope. Precedence: the person's choice and data-protection controls govern use. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: privacy-control lookup + consent choice. Decision interval: the current interaction. Minimum evidence: a clear privacy notice, session scope and working deletion/expiry control. Method: store only selected functional preferences needed for the current decision and show what depends on them. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: continue in generic/no-storage mode or decline personalisation.

ANSWER BOUNDARY
Do not require proof, store a diagnosis, create/reuse a permanent profile, combine with other records or disclose preferences to unrelated services. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person use helpful personalisation while controlling sensitive information.

AR-072

ANONYMOUS SESSION

L1 - privacy control

R2 - integration-dependent

ACCESSIBILITY QUESTION

Can I plan without identifying myself and have my stated accessibility preferences deleted when the interaction ends?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: anonymous or pseudonymous session controls, session expiry and deletion confirmation for stated preferences. No device fingerprinting, location tracking or cross-session linkage. Quality gate: verified privacy settings, access control, retention timer, deletion outcome and provenance.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current privacy notice, anonymous-use capability, retention/deletion policy and any function that genuinely requires authentication. Precedence: the person decides whether to authenticate; service owners define functions that cannot operate anonymously. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: privacy-mode lookup + capability comparison. Decision interval: the current session. Minimum evidence: documented anonymous and authenticated modes with data/feature differences. Method: explain what works anonymously, what needs identity and why, before asking for consent. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: offer the anonymous subset or stop the function.

ANSWER BOUNDARY
Do not fingerprint devices, infer identity, retain preferences after expiry or pressure the person to authenticate. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person plan with the minimum personal information needed.

8. Independence, dignity, privacy, reliability, contingencies and lower-impact choices

AR-073 to AR-074 | 10 questions in this section | Preserve person-controlled preferences, transparent evidence, dependable fallbacks and honest abstention.

AR-073

EVIDENCE TRANSPARENCY

L1 - evidence explanation

R1 - practical

ACCESSIBILITY QUESTION

Which parts of your answer are confirmed facts, observations, calculations, estimates or recommendations, and how fresh is each source?

SENSORS AND TELEMETRY
No new sensing. Proposed system evidence: the provenance and quality record for every source already used, including owner, source type, observed/effective/retrieved time, coverage, calibration or version, gaps, conflicts and permission scope. Unverifiable claims remain unknown.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: the authoritative sources and owners behind access, routes, assets, spaces, services and official communications. Precedence: source owners determine official facts; calculations/estimates must remain labelled. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: evidence explanation. Decision interval: the current answer and decision interval. Minimum evidence: a claim-to-source map with operation type, coverage, quality and uncertainty. Method: classify each statement as authoritative fact, observation, calculation, estimate, forecast or recommendation and expose gaps/conflicts. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: remove unsupported claims or mark them not assessable.

ANSWER BOUNDARY
Do not disclose restricted security/operational details or personal data, and do not hide uncertainty behind fluent prose. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL Lets the person judge which parts of the answer are dependable enough for their decision.

AR-074

PRIMARY AND BACKUP

L3 - contingency recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Can you give me a verified primary route and a verified fallback if a lift, door or entrance becomes unavailable?

SENSORS AND TELEMETRY
Proposed evidence: current door/lift status and only the anonymous route-context telemetry needed for both candidate routes; no personal tracking. Coverage: the complete primary and fallback routes, including entrance, every door/lift and destination. Timing/aggregation: asset state event-driven with 30-second heartbeat; optional crowd context as 1-minute aggregates. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current accessible routes, opening/access, asset status, closures, official help contacts and organiser instructions. Precedence: route/access and asset owners determine which plans are valid. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: whole-route calculation + contingency recommendation. Decision interval: the planned journey and recheck time. Minimum evidence: two fully verified authorised routes or one route plus an approved staff-assistance fallback. Method: validate each independently, show trigger for switching and recheck status before movement. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: provide only the verified plan/contact or return not assessable.

ANSWER BOUNDARY
Do not call a route a fallback if any critical segment is unknown, grant access, operate assets or certify personal safety. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL Gives the person a primary plan and a credible fallback before setting out.

8. Independence, dignity, privacy, reliability, contingencies and lower-impact choices

AR-075 to AR-076 | 10 questions in this section | Preserve person-controlled preferences, transparent evidence, dependable fallbacks and honest abstention.

AR-075

STATUS RELIABILITY

L2 - evidence-quality calculation

R2 - integration-dependent

ACCESSIBILITY QUESTION

How trustworthy is today's lift or automatic-door status feed, and should I confirm the asset with staff before relying on it?

SENSORS AND TELEMETRY
Proposed evidence: asset heartbeat, last update, controller/contact agreement, connector health, maintenance/override state and official owner status for the named lift or door. Coverage: the specific asset and relevant time window. Timing/aggregation: use source-native event/heartbeat expectations with clock synchronisation and explicit gap/latency calculations. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current asset-owner status, maintenance/outage notice, service-level metadata and official confirmation contact. Precedence: the asset owner and official notice override calculated data-feed quality. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: data-feed quality calculation + bounded recommendation. Decision interval: today and the planned use time. Minimum evidence: expected heartbeat, last update, latency, gaps, controller/contact agreement, maintenance/override state and owner status. Calculate feed completeness and freshness only - not physical asset reliability. Safe failure: require staff confirmation when evidence is stale, incomplete or conflicting.

ANSWER BOUNDARY
Do not equate a healthy feed with a functioning asset, a missing feed with asset failure, or certify reliability. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person decide whether live status is dependable enough or needs staff confirmation.

AR-076

LOW-EFFORT CHOICE

L3 - recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Can you recommend the lowest-effort authorised route using only the limits I state, without inferring fatigue from my movement?

SENSORS AND TELEMETRY
Proposed evidence: current audited route geometry, door/lift status and optional anonymous crowd bands; no gait, speed, fatigue or device tracking. Coverage: every segment of each eligible authorised route. Timing/aggregation: asset events source-native; counts as 1-minute aggregates; static geometry versioned and current. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current routes/gradients/rest points, access restrictions, asset status, closures and the effort limits/preferences the person states. Precedence: the person sets the preference; route/access owners determine eligibility. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: multi-criteria route calculation + recommendation. Decision interval: the planned journey. Minimum evidence: complete routes, current status and stated criteria such as distance, gradients, doors/lifts and rest points. Method: compare criteria transparently and disclose weights/trade-offs; do not learn effort from movement history. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: offer a verified partial/staffed plan or return not assessable.

ANSWER BOUNDARY
Do not infer fatigue or capability, track movement, guarantee low effort or recommend an unauthorised route. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person choose the route that best matches the effort limits they state.

8. Independence, dignity, privacy, reliability, contingencies and lower-impact choices

AR-077 to AR-078 | 10 questions in this section | Preserve person-controlled preferences, transparent evidence, dependable fallbacks and honest abstention.

AR-077

ACCESSIBLE LOW-CARBON

L3 - recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Which lower-carbon travel option is also realistically accessible for the requirements and visit time I state?

SENSORS AND TELEMETRY
No personal tracking. Proposed evidence is limited to correctly sited weather observations where available and owner-issued transport, entrance, lift and route status. Coverage must include the complete journey from each eligible stop or drop-off point to the destination. Preserve source-native times, service disruptions, route gaps and provenance; capability remains proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current transport-operator accessibility/service information, stop/drop-off records, carbon-factor/source assumptions, weather/disruption, public opening, entrance and whole-route access. Precedence: transport and access owners determine usable options; carbon estimates are secondary. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: authorised lookup + whole-journey comparison + bounded recommendation. Decision interval: the stated travel and visit time. Minimum evidence: current accessible service status and a fully verified entrance route for each option. Compare carbon only among usable options and show carbon-factor assumptions, transfers and accessibility uncertainties. Safe failure: prioritise the verified usable option or return not assessable.

ANSWER BOUNDARY
Do not infer disability, income or travel history, guarantee operator assistance or choose lower carbon over verified accessibility. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Lets the person compare lower-impact choices without compromising usability.

AR-078

COMPARE SPACES

L2 - comparison

R2 - integration-dependent

ACCESSIBILITY QUESTION

Can you compare two authorised spaces against my stated accessibility and sensory preferences without ranking anyone else's needs?

SENSORS AND TELEMETRY
Proposed evidence: correctly located room-level temperature/RH, CO2/PM where available, numerical acoustic/light evidence and anonymous occupancy for the two eligible spaces; no content or identity sensing. Coverage: only the two authorised spaces and both complete routes. Timing/aggregation: aligned 1-minute data with compatible calibration, completeness and operating context. Quality gate: verified asset/location mapping, aligned clocks, applicable commissioning or calibration, current maintenance state, uptime and gaps, drift or relocation flags, and provenance. Uncovered, stale or adjacent-area evidence stays unknown; all sensing and integrations remain proposed until verified.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current room purpose/access/booking, seating, assistive provision, route status, services, closures and preferences stated for the current comparison. Precedence: space/accessibility/organiser owners determine eligibility and provision. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: matched comparison + user-weighted recommendation. Decision interval: the planned use window. Minimum evidence: two eligible spaces with comparable evidence and selected criteria. Method: compare each criterion separately, explain weights/trade-offs and exclude non-comparable variables. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: restrict the answer or return not assessable when evidence/permission differs materially.

ANSWER BOUNDARY
Do not infer disability, rank people/needs, guarantee suitability, reserve spaces or collapse criteria into an unexplained accessibility score. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Helps the person choose between two real options using their own priorities.

8. Independence, dignity, privacy, reliability, contingencies and lower-impact choices

AR-079 to AR-080 | 10 questions in this section | Preserve person-controlled preferences, transparent evidence, dependable fallbacks and honest abstention.

AR-079

EVIDENCE GAPS

L1 - answerability check

R1 - practical

ACCESSIBILITY QUESTION

What evidence is missing from my plan, and which parts can the service not assess reliably?

SENSORS AND TELEMETRY
No personal sensing. Proposed system evidence: an observability and provenance inventory linking every planned claim to the required route, asset, room, service, permission and quality evidence. Use current freshness, coverage, calibration/version, source conflict and access flags; never fill a gap with inferred personal information.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current route, space, access, assistive/service records, source owners, permission scope and official contacts for unresolved items. Precedence: source owners determine authority; the service must expose staleness/conflicts. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: evidence-sufficiency and answerability assessment. Decision interval: the planned decision interval. Minimum evidence: an explicit requirement-to-evidence map for every requested claim. Method: classify claims as supported, qualified, conflicting or not assessable and identify the smallest clarification/contact needed. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: never fill a gap with generic assumptions.

ANSWER BOUNDARY
Do not infer missing personal information, request diagnoses, hide uncertainty or treat absence of evidence as evidence of access/safety. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Shows what is known, unknown and worth verifying before relying on the plan.

AR-080

FINAL PLAN

L2 - synthesis/recommendation

R2 - integration-dependent

ACCESSIBILITY QUESTION

Before I set out, can you summarise my verified route, support contacts, recheck points and contingencies?

SENSORS AND TELEMETRY
No new sensing. Synthesize only the verified sources, quality flags and session-scoped preferences already used. Coverage must include the chosen primary route, fallback, destination, contacts and recheck points. Preserve each source's owner, freshness/expiry, permission scope and unresolved conflicts; do not retain preferences beyond the agreed session.

AUTHORITATIVE SUPPORTING DATA
Authoritative sources: current opening/access, route, door/lift, destination, support contacts, closures, organiser instructions and official emergency information. Precedence: current source owners and competent authorities remain decisive; the summary creates no permission. Show source owner, effective/observed/retrieved time, permission scope, staleness and unresolved conflicts. Current owner records outrank telemetry and the May 2021 historical plan.

ANALYSIS REQUIRED
Operation: evidence synthesis + bounded recommendation. Decision interval: the planned visit/journey. Minimum evidence: a verified primary plan, fallback, official contacts, recheck times and clearly labelled unresolved items. Method: separate confirmed facts, observations, calculations, estimates and recommendations in a concise accessible format. Label confirmed facts, calculations, estimates and forecasts separately; report coverage, assumptions, uncertainty and conflicts. Safe failure: omit unverified steps and state exactly what must be checked with staff.

ANSWER BOUNDARY
Do not add unverified details, retain preferences beyond the agreed session, grant access or certify accessibility/safety. Use only requirements the person chooses to state for this interaction. Do not infer disability, diagnosis, health, neurotype, distress, fatigue or assistance need; do not identify or track people, inspect content, use biometrics or retain movement history. Do not grant access, operate systems, certify accessibility or safety, or override competent authorities.

WHY THIS IS USEFUL

Gives the person one clear, evidence-labelled plan to check before departure.

4. Catalogue summary and implementation requirements

The 80 questions define the evidence, authority, privacy and safe-failure capabilities required for responsible person-owned answers.

QUESTIONS	80	AR-001 to AR-080 across eight accessibility-centred categories.
R1 - PRACTICAL	14	Authoritative lookup, verified static information or current owner-issued status.
R2 - INTEGRATION-DEPENDENT	54	Cross-system integration and proposed privacy-preserving sensing.
R3 - RESEARCH OR RESTRICTED	12	Validated modelling, higher-consequence interpretation or restricted governance.

RECURRING CAPABILITY REQUIREMENTS

WHOLE-ROUTE ACCESSIBILITY RESOLUTION Model entrances, doors, audited ramps or gradients where current records exist, lifts or stairs, circulation, destination, access windows and verified alternatives.	DOOR, LIFT AND ROUTE STATUS INTEGRATION Use current owner-issued status, maintenance and closure information with aligned timestamps and verified mapping; never infer availability from occupancy.	SPACE, SEATING AND ASSISTIVE PROVISION Use current room, seating, assistive-technology, amenity and support records. Apparent vacancy or low noise never creates access, permission or availability.
SENSOR CONTEXT EVIDENCE Use correctly located, calibrated numerical light, acoustic, environmental and anonymous aggregate occupancy evidence only as qualified context.	ACCESSIBLE COMMUNICATION AND PREFERENCE Present concise, screen-reader friendly, high-contrast or text-based answers as requested, with source-labelled facts and uncertainty.	PRIVACY, DIGNITY, SAFETY AND ABSTENTION Use only stated requirements, demand no diagnosis, identify nobody, certify no accessibility or safety, operate no system, and return not assessable when evidence is inadequate.

QUESTION RECORD CONTRACT Every implementation question maps the person's stated requirement and decision interval to minimum authoritative evidence, justified proposed telemetry, spatial and temporal coverage, quality checks, a named operation, uncertainty, prohibited inference and safe failure.

5. Evidence, permissions and answerability rules

These catalogue-wide rules apply to every answer, regardless of readiness class or question category.

1. CURRENT ACCESS AND BUILDING STATUS

Use current owner-issued opening, access, route, lift, door, room, seating, amenity, maintenance and closure records. The May 2021 plan is historical reference only.

3. USER-STATED REQUIREMENTS ONLY

Use only functional requirements and preferences the person chooses to state for this interaction. Do not demand diagnosis, infer sensitive traits, rank needs or retain them without consent.

5. NO IDENTITY, TRACKING OR CONTENT INSPECTION

Do not use cameras, microphones, biometrics, gait analysis or device tracking; inspect no speech, content or network data; build no precise movement or behaviour history.

7. ASSISTIVE PROVISION AND PERMISSIONS

Current room, seating, communication-format and assistive-technology owners determine provision and use. The service may report verified status but cannot grant, reserve or certify it.

9. ENVIRONMENTAL INTERPRETATION

Separate observation, calculation, estimate, forecast, comparison, diagnosis and recommendation. State coverage, comparable cases, uncertainty and conflicts; no medical, causal or universal comfort claims.

2. WHOLE-ROUTE SPATIAL COVERAGE

A route is assessable only when every critical segment is verified. Never bridge a missing entrance, door, gradient, lift, corridor, destination or time restriction.

4. CALIBRATION AND DATA QUALITY

For proposed telemetry preserve sensor or status-source mapping, commissioning/calibration, clock alignment, maintenance state, uptime, gaps, drift, relocation, provenance and source conflicts.

6. OCCUPANCY, SOUND, LIGHT AND COMFORT

Anonymous counts and numerical acoustic, light and environmental measures are qualified context only. They cannot prove access, availability, confidentiality, personal suitability or safety.

8. EMERGENCY AND HIGH-CONSEQUENCE ANSWERS

Certified alarms, official emergency communications and competent authorities prevail. Do not generate personal evacuation instructions, suppress or replace alarms, or predict personal safety.

10. OPERATIONS AND AUTHORITY

The service does not grant bookings or access, operate doors, lifts, lighting, HVAC or alarms, decide eligibility, certify accessibility or safety, or override service owners and competent authorities.

ANSWERABILITY RULE When official evidence, permission or authority is missing, stale, conflicting, unauthorised or spatially insufficient, ask only the minimal necessary clarification, provide a qualified inclusive alternative where possible, defer to the responsible source, or return not assessable. Never conceal an evidence gap with a generic assumption or confident prose.