

Stakeholder Question Catalogue 07

Professional-services Staff

80 professional-services questions mapped to correctly scoped proposed sensing, current authoritative sources, explicit operations, calibrated evidence, uncertainty, permissions and safe answer boundaries.

STAKEHOLDER	School and department administrators, student-facing support, HR, finance and research-support colleagues, programme and records teams, reception staff and other professional service providers using Abacws offices, service points, meeting spaces and routes.
QUESTION RANGE	Service-day planning; concentrated administration and office comfort; front desks and appointments; meetings and shared resources; hybrid services; movement and demand peaks; visitors, accessibility and well-being; disruptions, irregular work, resilience, safety and sustainability.
EVIDENCE MODEL	Proposed privacy-preserving sensing is combined with current authoritative service, room, access, accessibility, equipment, IT, maintenance, visitor, lone-working and safety sources. Every record states spatial coverage, timing, quality, precedence, operation, uncertainty and safe failure.

Core principle: Help professional-services staff coordinate their own work and service interactions using verified, correctly scoped evidence - without inspecting service content, exposing personal data, identifying or tracking people, inferring workload or performance, taking over another team's authority, or sounding more certain than the evidence.

1. Catalogue scope and design principles

This catalogue covers decisions professional-services staff may ask a conversational university building to support while planning service work, delivering appointments, using offices and shared resources, moving around Abacws and responding to disruption. It assists the staff member; it does not replace service owners or operational teams.

Proposed capability, not current fact

Every sensor, integration and service is a design requirement unless deployment, room coverage, permission and operational status are independently verified. The catalogue does not claim that all capabilities currently exist.

Current building information

The May 2021 floor plan is a historical spatial reference. Current room purpose, ownership, allocation, capacity, bookability, access, accessibility, equipment, services and closures require authoritative verification.

Staff-owned decisions

Questions help a staff member plan their service day, concentration block, appointment, meeting, route, break, fallback or sustainability choice. They do not set staffing, service policy, bookings, maintenance, IT, security or safety operations.

Correctly located evidence

A room-level claim requires sensing inside the named room or a validated served zone. Corridor and adjacent-room readings may be labelled context but cannot be silently substituted. Time, coverage and quality remain visible.

Privacy by design

Use anonymous aggregate occupancy, queue counts and numerical acoustic indicators only where proportionate. Do not inspect casework, records, emails, calls, speech, screens, network traffic or device content; identify people; or infer workload or performance.

Authoritative-source precedence

Service calendars, appointments, room/desk allocation, privacy classification, booking, access, accessibility, equipment, IT, closures, lone-working and emergencies come from authorised sources. Telemetry cannot grant permission or certify safety.

Honest operation and failure

Each record labels observation, lookup, calculation, estimate, forecast, comparison, diagnosis or recommendation. Missing, stale, conflicting or unauthorised evidence produces clarification, a limited answer, deferral or not assessable.

Concrete staff value

The output should support a practical work, service, appointment, meeting, route, break or contingency decision, not create a performance dashboard or transfer another team's responsibility to the conversational service.

2. How to read each question record

Every record turns a natural professional-services question into a bounded evidence requirement. The fields identify proposed sensing, current authoritative sources, the permitted operation, uncertainty and the point at which the service must clarify, restrict, defer or abstain.

PROFESSIONAL-SERVICES STAFF QUESTION	A natural question owned by the staff member and framed around their work, service, appointment, meeting, route, break or contingency decision rather than an operator task.
SENSORS AND TELEMETRY	Physically plausible proposed room, service-point, route, network, power, environmental or BMS evidence with relevant location, timing, aggregation, privacy and quality limits.
AUTHORITATIVE SUPPORTING DATA	Current service, appointment, room, booking, access, accessibility, privacy, equipment, IT, maintenance, visitor, lone-working or safety records that take precedence over inference.
ANALYSIS REQUIRED	The exact operation: observation, authorised lookup, calculation, estimate, forecast, comparison, diagnosis or recommendation. It states the decision window, comparator and safe failure.
ANSWER BOUNDARY	What the building must not infer, disclose, control or certify; when it must ask for clarification, provide a limited answer, defer to the responsible service or return not assessable.
WHY THIS IS USEFUL	The concrete professional-services decision supported by the answer.

Readiness

R1 - practical Core proposed sensing plus basic current spatial, service or provenance data.	R2 - integration-dependent Service calendar, appointment, room, booking, access, accessibility, IT, BMS, maintenance, visitor, lone-working or forecasting integration.	R3 - research-grade or restricted Dense sensing, validated comparison/diagnosis, controlled operational data, or stronger privacy, governance and safety controls.
Global rule: use only verified eligible spaces and authorised data; preserve timestamps, service-point or room coverage and quality; inspect no casework or communication content; never identify people or infer individual workload or performance; and return a limited or not-assessable answer when critical evidence is missing.		

3. Worked example: a mixed service day

A responsible answer combines user-authorised commitments and service requirements with verified room, privacy, access, accessibility, equipment, IT and environmental evidence. It never treats an empty room as available, low noise as confidentiality, or telemetry as permission, staffing adequacy or safety certification.

Professional-services staff member: "I need an hour for records work, a confidential appointment, front-desk cover, an accessible visitor route and a fallback if the network fails. What can the building verify, recommend and not assess?"

1. Resolve the service day

Use only the user-authorised times, locations and stated requirements for records work, the appointment, front-desk activity, visitor access and continuity.

2. Verify authoritative status

Check the current service calendar, privacy classification, room/desk allocation, booking, access, accessibility, visitor procedure, equipment, IT incidents, closures and continuity rules before using sensors.

3. Verify evidence quality

Require target-room or waiting-area coverage, verified asset and route mapping, timestamps, commissioning/calibration, uptime, gaps, drift and source agreement. Mark unverified criteria unknown.

4. Perform the right operation

Use lookup for permission/status, observation for current conditions, calculation for route and capacity, forecast for demand, and diagnosis only when permitted time-aligned evidence supports it.

5. Recommend staff-owned actions

Recommend work windows, pre-checks, eligible rooms, route buffers and verified fallbacks. Do not set staffing, make bookings, grant access, operate systems or override service owners.

6. Communicate answerability

State confirmed facts, estimates, forecasts, source times, confidence and omitted criteria. Return a conditional or not-assessable result when evidence or authority is inadequate.

ILLUSTRATIVE ANSWER STRUCTURE

"The 9:30-10:30 records-work block is compatible with the approved service schedule, but demand confidence is moderate because the queue counter has a gap. The appointment room is booked and privacy-classified; current environmental and network checks are fresh, but accessibility must be confirmed from the authoritative record. The visitor route is currently open and step-free. For network failure, the approved continuity procedure identifies an alternative service point; I cannot book it or approve relocation. Recheck official status at [time]."

1. Service-day and administrative workflow planning

Questions PS-001-PS-002

PS-001

CORE

L2 - forecast + recommendation

R2 - integration-dependent

Professional-services staff question: I have a service-desk shift, three confirmed appointments and routine admin today. When is the safest one-hour block for focused work without affecting those duties?

Sensors and telemetry

Proposed sensing (minimum): Anonymous aggregate queue count at the assigned service point; room-level occupancy, numerical acoustic indicators, temperature, CO2 and light in eligible workspaces. Coverage: The assigned service point, its waiting boundary and each eligible workspace. Quality: native event/status cadence plus one-minute aggregates; align clocks, verify room/service/asset mapping and report calibration or count error, uptime, gaps, drift, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts and non-content numerical/status evidence only; no identities, speech or movement histories.

Authoritative supporting data

Authoritative data: The staff member's user-authorised appointments and assigned service period; current approved opening hours, workspace allocation, service calendar, room access, closures and known events. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, short-horizon demand forecast and recommendation. Decision window: the rest of the working day. Minimum evidence: current authorised status and healthy telemetry from the correct target space or asset. Method or baseline: matched weekdays, current queue trend and known deadline/event context. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The service may suggest a personal work sequence but cannot decide staffing, reassign colleagues, infer case complexity or treat a quiet period as permission to close a service point. No content inspection, personal-data exposure, individual workload/performance inference, staffing policy, access grant or service-owner override. If decisive authority, target-space evidence or time alignment is missing, omit that criterion and restrict or abstain.

Why this is useful: Helps choose focused-work time while protecting confirmed appointments and service duties.

PS-002

CORE

L2 - demand forecast

R2 - integration-dependent

Professional-services staff question: How busy is the front desk likely to be from 10:00 to 12:00 next Monday, and when should I prepare the standard information and escalation contacts?

Sensors and telemetry

Proposed sensing (minimum): Anonymous doorway and waiting-zone counts for the service point, with current queue length where an authorised queue system exists. Coverage: The named front desk entrance and clearly defined waiting area. Quality: event-level or one-minute anonymous aggregates from commissioned counters; align clocks and report count error, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregates only; no identities, case types or movement histories.

Authoritative supporting data

Authoritative data: Approved service hours, aggregate appointment totals, institutional deadline calendar, scheduled events and known closures; no applicant or student identity is required. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: forecast. Decision window: 10 a.m.-noon next Monday. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Method or baseline: same service point, equivalent academic-cycle week and comparable opening pattern. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The result is an aggregate planning estimate, not a staffing instruction or guarantee. No content inspection, personal-data exposure, individual workload/performance inference, staffing policy, access grant or service-owner override. Weak count coverage permits confirmed status or a broad range only, never a precise wait or staffing conclusion.

Why this is useful: Helps the staff member prepare standard information and escalation contacts before an expected demand peak.

1. Service-day and administrative workflow planning

Questions PS-003-PS-004

PS-003

CORE

L2 - temporal recommendation

R2 - integration-dependent

Professional-services staff question: I need one uninterrupted hour for routine records work today. Which remaining authorised period is least likely to be interrupted by walk-ins?

Sensors and telemetry

Proposed sensing (minimum): Anonymous service-point arrivals, waiting-zone count and numerical acoustic indicators in the staff member's authorised work area. Coverage: The assigned service point and the proposed records-work room or desk zone. Quality: event-level or one-minute anonymous aggregates from commissioned counters; align clocks and report count error, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregates only; no identities, case types or movement histories.

Authoritative supporting data

Authoritative data: Current service rota visible to the user, approved opening hours, aggregate appointment schedule, workspace allocation, access and closure status. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: current observation, short-horizon forecast and recommendation. Decision window: the remaining authorised workday. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Method or baseline: same weekday and comparable point in the service cycle. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Low demand does not authorise suspension of service, and low sound does not certify confidentiality. The building cannot evaluate the records or the staff member's output. No content inspection, personal-data exposure, individual workload/performance inference, staffing policy, access grant or service-owner override. Weak count coverage permits confirmed status or a broad range only, never a precise wait or staffing conclusion.

Why this is useful: Helps select a realistic records-processing block without assuming the service point can close.

PS-004

USEFUL

L2 - break-window recommendation

R2 - integration-dependent

Professional-services staff question: Which authorised break window today fits around my appointments and desk duty with the lowest likely effect on service?

Sensors and telemetry

Proposed sensing (minimum): Anonymous aggregate queue and arrival counts at the assigned service point; optional current occupancy and environmental conditions in approved break spaces. Coverage: The service point and approved staff break spaces. Quality: event-level or one-minute anonymous aggregates from commissioned counters; align clocks and report count error, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregates only; no identities, case types or movement histories.

Authoritative supporting data

Authoritative data: The user-authorised appointment and duty schedule, approved break policy, service opening hours, local rota information the user is permitted to see, access and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, estimate and recommendation. Decision window: the current service day. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Method or baseline: current queue trend and comparable service days. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not infer workload, stress or staffing adequacy, and do not rearrange another person's duties. A recommendation must remain subordinate to local management and break arrangements. No content inspection, personal-data exposure, individual workload/performance inference, staffing policy, access grant or service-owner override. Weak count coverage permits confirmed status or a broad range only, never a precise wait or staffing conclusion.

Why this is useful: Helps choose a legitimate break window while preserving confirmed service commitments.

1. Service-day and administrative workflow planning

Questions PS-005-PS-006

PS-005

CORE

L2 - peak-risk forecast

R2 - integration-dependent

Professional-services staff question: A major student deadline falls this week. Which approved service periods are most likely to be unusually busy, so I can prepare my own work and standard information?

Sensors and telemetry

Proposed sensing (minimum): Historical anonymous arrivals, queue counts and service-zone occupancy for the relevant point; current counts for trend confirmation. Coverage: Each authorised service point included in the comparison. Quality: event-level or one-minute anonymous aggregates from commissioned counters; align clocks and report count error, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregates only; no identities, case types or movement histories.

Authoritative supporting data

Authoritative data: Official deadline calendar, approved service hours, aggregate appointment totals, planned events, closures and any published service changes. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: historical comparison and forecast. Decision window: the specified week. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Method or baseline: same academic process, comparable opening pattern and documented service changes. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not assume demand equals workload or case difficulty, and do not produce individual staff-performance comparisons. If historical service definitions changed, label the comparison limited. No content inspection, personal-data exposure, individual workload/performance inference, staffing policy, access grant or service-owner override. Weak count coverage permits confirmed status or a broad range only, never a precise wait or staffing conclusion.

Why this is useful: Helps prepare personal work and standard responses for likely deadline-related surges.

PS-006

CORE

L2 - on-site day recommendation

R2 - integration-dependent

Professional-services staff question: Do tomorrow's confirmed duties require me on site, and are my authorised workspace, access and essential services expected to be available?

Sensors and telemetry

Proposed sensing (minimum): Current environmental conditions in authorised workspaces and status telemetry for room power, network endpoints and shared resources where approved. Coverage: Only workspaces and assets the staff member is authorised to use. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: The user-authorised appointment and duty schedule, approved hybrid-work arrangements, workspace allocation, opening/access, room and resource status, maintenance and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup and recommendation. Decision window: tomorrow's authorised working period. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: current authoritative schedule and latest service-health forecasts. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The building cannot approve remote work, interpret employment policy or inspect calendar content beyond the constraints the user authorises. It cannot assess the user's home environment. No content inspection, personal-data exposure, individual workload/performance inference, staffing policy, access grant or service-owner override. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Supports an evidence-based choice between on-site and remote work without changing assigned duties.

1. Service-day and administrative workflow planning

Questions PS-007-PS-008

PS-007

USEFUL

L2 - resource-window recommendation

R2 - integration-dependent

Professional-services staff question: I need to scan and print confidential paperwork on an approved device. Which authorised device and time window are likely to have the shortest wait?

Sensors and telemetry

Proposed sensing (minimum): Authorised printer/scanner health, paper/consumable status if exposed by the device, and anonymous aggregate occupancy near the resource; no document or job metadata. Coverage: The specific shared-resource area and device. Quality: owner-managed device state and fault/consumable status, with anonymous queue counts where available; report exact mapping, source times, staleness and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no document, username, file, print or scan content inspection.

Authoritative supporting data

Authoritative data: Current authorised resource inventory, permitted use, staff access, privacy classification, maintenance incidents, opening hours and any booking or reservation rule. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, short-horizon estimate and recommendation. Decision window: the user-specified working window. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: same resource and comparable office periods. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not inspect document names, print jobs, scanned content or user identities. A quiet area does not certify confidentiality; privacy classification and local handling rules are mandatory. No content inspection, personal-data exposure, individual workload/performance inference, staffing policy, access grant or service-owner override. Missing/conflicting device-owner status requires an owner check; do not promise availability, wait time or completion.

Why this is useful: Helps choose an approved device and lower-wait period without exposing document content.

PS-008

USEFUL

L2 - handover planning

R2 - integration-dependent

Professional-services staff question: When should I start today's service-desk handover so it is complete before the final likely demand peak?

Sensors and telemetry

Proposed sensing (minimum): Anonymous arrivals, queue count and waiting-zone occupancy for the assigned service point. Coverage: The service desk entrance and waiting boundary. Quality: event-level or one-minute anonymous aggregates from commissioned counters; align clocks and report count error, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregates only; no identities, case types or movement histories.

Authoritative supporting data

Authoritative data: Approved closing time, the user's assigned duty period, aggregate appointments, official handover procedure, known events and service-change notices. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: short-horizon forecast and recommendation. Decision window: the final two hours of the service day. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Method or baseline: comparable closing periods and current arrival trend. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The service cannot close the desk, determine staffing or evaluate handover quality. It must defer to the official handover and service-owner procedure. No content inspection, personal-data exposure, individual workload/performance inference, staffing policy, access grant or service-owner override. Weak count coverage permits confirmed status or a broad range only, never a precise wait or staffing conclusion.

Why this is useful: Supports a timely handover that is complete before the final likely rush.

1. Service-day and administrative workflow planning

Questions PS-009-PS-010

PS-009

CORE

L2 - service-risk recommendation

R2 - integration-dependent

Professional-services staff question: I need an uninterrupted hour on an approved administrative system. Which remaining on-site period has the lowest verified disruption risk?

Sensors and telemetry

Proposed sensing (minimum): Authorised network endpoint health, power status and room environmental conditions for eligible workspaces; no packet, application, account or device-content inspection. Coverage: The relevant network zone, power circuit and authorised workspace. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: Official IT service status and planned maintenance, local power incidents, workspace allocation/access, building opening and the user-specified interval. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, recent-stability calculation and recommendation. Decision window: one hour within the remaining workday. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: authoritative incident history and current service health. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The building cannot guarantee application availability or inspect the user's session. Network and power authorities remain responsible for status and restoration. No content inspection, personal-data exposure, individual workload/performance inference, staffing policy, access grant or service-owner override. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Helps protect a time-sensitive administration block with a verified fallback.

PS-010

USEFUL

L3 - scenario comparison

R3 - research-grade or restricted

Professional-services staff question: Given next week's appointments, service periods and likely demand peaks, what personal work sequence best protects service coverage and focused admin time?

Sensors and telemetry

Proposed sensing (minimum): Historical anonymous queue, arrival and service-zone occupancy; eligible workspace environment and service-health data for planning only. Coverage: The relevant service point and authorised staff workspaces. Quality: native event/status cadence plus one-minute aggregates; align clocks, verify room/service/asset mapping and report calibration or count error, uptime, gaps, drift, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts and non-content numerical/status evidence only; no identities, speech or movement histories.

Authoritative supporting data

Authoritative data: User-authorised appointments and assigned duties, approved service calendar, official deadlines/events, workspace/access rules and planned maintenance or closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: scenario comparison and recommendation. Decision window: the specified service week. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Method or baseline: equivalent peak weeks, current policy and known schedule changes. Use eligible matched options with aligned windows; disclose residual non-comparability and uncertainty. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

This is personal planning support, not workforce optimisation. Do not rank staff, infer case complexity or recommend reductions in service coverage. No content inspection, personal-data exposure, individual workload/performance inference, staffing policy, access grant or service-owner override. If decisive authority, target-space evidence or time alignment is missing, omit that criterion and restrict or abstain.

Why this is useful: Helps plan a compressed, high-demand week without becoming a staffing plan.

2. Professional-services workspaces, concentration and comfort

Questions PS-011-PS-012

PS-011

CORE

L2 - forecast + recommendation

R2 - integration-dependent

Professional-services staff question: I need two quiet hours for detailed admin work. Which workspace I am authorised to use is most likely to remain suitable for the full period?

Sensors and telemetry

Proposed sensing (minimum): Room-level temperature, RH, direct NDIR CO2, illuminance, numerical acoustic indicators and anonymous occupancy in every eligible workspace. Coverage: Each candidate room or desk zone. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: Current workspace allocation, permitted use, bookability, opening/access, privacy classification, accessibility, closures and the user-specified work period. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, forecast and multi-criteria recommendation. Decision window: the requested two-hour block. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: comparable weekdays and known events. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

An empty or quiet-looking space is not automatically available, confidential or accessible. If target-room coverage is absent, the environmental part is not assessable. No work-content inspection, individual tracking, presence/productivity inference, desk allocation, privacy/accessibility certification or system control. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Helps choose an authorised workspace likely to support two hours of concentrated administration.

PS-012

CORE

L2 - short-horizon forecast

R2 - integration-dependent

Professional-services staff question: My shared office is usually busier after lunch. Which remaining period today is most likely to support concentrated work?

Sensors and telemetry

Proposed sensing (minimum): Anonymous room occupancy, doorway counts and numerical sound metrics inside the shared office, with temperature and CO2 for context. Coverage: The shared office itself, not the corridor. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: Current staff access and workspace-allocation rules, the user-authorised work window, building opening, known events and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: current observation, short-horizon forecast and comparison. Decision window: the remaining authorised workday. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: same office, same weekday and comparable service cycle. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not identify who is present, infer individual routines or promise silence. Occupancy estimates need stated count uncertainty and cannot prove desk availability. No work-content inspection, individual tracking, presence/productivity inference, desk allocation, privacy/accessibility certification or system control. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Supports a same-day choice of a lower-interruption period in the shared office.

2. Professional-services workspaces, concentration and comfort

Questions PS-013-PS-014

PS-013

CORE

L2 - current condition + recommendation

R2 - integration-dependent

Professional-services staff question: This office feels stuffy. Is the room-level evidence good enough for me to stay, move to an authorised alternative or report the condition?

Sensors and telemetry

Proposed sensing (minimum): In-room direct NDIR CO2, temperature, RH and anonymous occupancy; mapped supply-airflow or fan status where authorised. Coverage: The occupied room or validated served zone. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: Current room access/allocation, authorised alternative workspaces, HVAC served-zone mapping, maintenance incidents and official reporting route. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: current room observation, short comparison and recommendation. Decision window: now through the next hour. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Use eligible matched options with aligned windows; disclose residual non-comparability and uncertainty. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

CO2 is only a ventilation indicator, not a complete air-quality or health assessment. The service cannot certify safety, diagnose a fault or move the user; it may only describe valid room evidence and approved alternatives. No work-content inspection, individual tracking, presence/productivity inference, desk allocation, privacy/accessibility certification or system control. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Helps decide whether to stay, move or report a condition using valid room-level evidence.

PS-014

USEFUL

L2 - glare forecast

R2 - integration-dependent

Professional-services staff question: Afternoon glare makes screen work difficult at my desk. When, or in which authorised workspace, is glare likely to be lower?

Sensors and telemetry

Proposed sensing (minimum): Desk-zone illuminance, directional light or blind state where available, indoor temperature and outdoor solar radiation; no screen or document inspection. Coverage: The affected desk zone and eligible alternatives with comparable coverage. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: Current workspace allocation, window/facade orientation, authorised alternatives, blind-control policy, accessibility needs and weather/solar forecast. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: historical comparison, forecast and recommendation. Decision window: the requested afternoon or coming days. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: same season, facade and comparable weather. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Illuminance alone does not certify visual comfort. The service cannot operate blinds unless an authorised control policy separately permits it. No work-content inspection, individual tracking, presence/productivity inference, desk allocation, privacy/accessibility certification or system control. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Supports a practical time or workspace choice that reduces likely screen glare.

2. Professional-services workspaces, concentration and comfort

Questions PS-015-PS-016

PS-015

USEFUL

L3 - comparative diagnosis

R3 - research-grade or restricted

Professional-services staff question: My office often feels colder than comparable offices. Is the difference persistent and well evidenced enough to report?

Sensors and telemetry

Proposed sensing (minimum): In-room temperature, RH and optional radiant temperature; mapped supply-air temperature/flow and valve or damper state where authorised; outdoor weather. Coverage: The affected room and eligible comparable rooms or served zones. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: Current room purpose, HVAC zone and asset mapping, occupancy context, maintenance history, setpoint policy and official reporting route. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: matched room comparison and bounded diagnosis. Decision window: the user-specified period. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Use time-aligned independent sources, rank plausible contributors and preserve alternatives; do not assert cause. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

A persistent difference supports a well-scoped report but does not prove a fault or identify a responsible asset. Do not compare identifiable occupants or treat comfort telemetry as a health judgement. No work-content inspection, individual tracking, presence/productivity inference, desk allocation, privacy/accessibility certification or system control. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Provides comparable evidence for deciding whether to submit a facilities report.

PS-016

USEFUL

L2 - quiet-period recommendation

R2 - integration-dependent

Professional-services staff question: Activity in the corridor near my office interrupts concentration. Which authorised work periods are usually quieter?

Sensors and telemetry

Proposed sensing (minimum): Numerical LAeq/percentile sound metrics in the office and adjacent circulation zone, plus anonymous footfall; no speech or raw audio. Coverage: Both the office and the relevant corridor segment. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: Opening hours, timetable or event periods that may lawfully be used as aggregate context, current office access and known works/closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: historical comparison and forecast. Decision window: the requested day or week. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: same corridor and comparable teaching/event periods. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not infer conversation, identity or reason for movement. A forecast of lower noise is not a guarantee of quiet. No work-content inspection, individual tracking, presence/productivity inference, desk allocation, privacy/accessibility certification or system control. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Helps schedule concentration-heavy work outside recurring circulation-noise peaks.

2. Professional-services workspaces, concentration and comfort

Questions PS-017-PS-018

PS-017

CORE

L2 - workspace suitability lookup

R2 - integration-dependent

Professional-services staff question: Which shared desk I am authorised to use is officially available now, with working power, network service and suitable room conditions?

Sensors and telemetry

Proposed sensing (minimum): Authorised desk-zone power/service status, network endpoint health, room temperature, CO2, light and anonymous aggregate occupancy. Coverage: The eligible shared-desk zone and mapped supporting assets. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: Current workspace allocation or hot-desk entitlement, booking/claim rule, accessibility, desk features, opening/access, maintenance and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, observation and recommendation. Decision window: now and the user's intended work period. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: current owner-controlled desk and service status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

An apparently vacant desk is not necessarily available. The building cannot assign a desk, inspect a connected device or guarantee application performance. No work-content inspection, individual tracking, presence/productivity inference, desk allocation, privacy/accessibility certification or system control. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Prevents a move to a desk that is quiet but unavailable, unauthorised or without dependable services.

PS-018

CORE

L2 - privacy-aware recommendation

R2 - integration-dependent

Professional-services staff question: I need to handle confidential administration. Which authorised workspace is formally approved and available for the period I need?

Sensors and telemetry

Proposed sensing (minimum): Anonymous room occupancy and door state may describe broad use; numerical acoustic background may provide context but cannot prove speech privacy. Coverage: Only rooms with current authoritative privacy and access classifications. Quality: owner-controlled classification/status is primary; any telemetry is corroborative and must map to the exact room/resource with source times, staleness and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no identities, content or individual activity; disclose only role-authorised status.

Authoritative supporting data

Authoritative data: Current room purpose, staff access, booking, privacy classification, capacity, permitted activity, accessibility and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup and recommendation. Decision window: the user-specified interval. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: current room-owner records. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Low occupancy, a closed door or low sound does not certify confidentiality. The service cannot judge case sensitivity or expose another booking. No work-content inspection, individual tracking, presence/productivity inference, desk allocation, privacy/accessibility certification or system control. Missing/conflicting owner classification, permission or status requires deferral or not assessable.

Why this is useful: Supports a formally appropriate confidential-workspace choice rather than an inference from emptiness or quietness.

2. Professional-services workspaces, concentration and comfort

Questions PS-019-PS-020

PS-019

USEFUL

L2 - condition comparison

R2 - integration-dependent

Professional-services staff question: The air feels dry in my office. What do the room measurements show, and is this unusual for the room and season?

Sensors and telemetry

Proposed sensing (minimum): In-room RH and temperature, with sensor health and optional outdoor RH; direct CO2 may provide ventilation context. Coverage: The occupied room or validated served zone. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: Current sensor-room mapping, maintenance/calibration records, room use, HVAC served-zone mapping and weather data. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: observation and historical comparison. Decision window: now and a user-specified historical period. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: same season and occupied operating hours. Use eligible matched options with aligned windows; disclose residual non-comparability and uncertainty. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not make medical claims or recommend treatment. If calibration or room coverage is uncertain, state only the available reading and its limitation. No work-content inspection, individual tracking, presence/productivity inference, desk allocation, privacy/accessibility certification or system control. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Helps decide whether a dry-air concern is transient, recurrent or worth reporting.

PS-020

USEFUL

L2 - voluntary evidence comparison

R3 - research-grade or restricted

Professional-services staff question: Can you compare a comfort report I choose to submit with the room conditions at that time, without creating a personal profile or tracking me?

Sensors and telemetry

Proposed sensing (minimum): In-room temperature, RH, CO2, light and numerical acoustics as relevant; voluntary timestamped feedback linked only to the requested session. Coverage: The room used during the submitted feedback interval. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: Explicit user consent, feedback-retention and deletion rules, current room mapping and approved service purpose; no work output or health record. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: voluntary, one-session comparison. Decision window: the interval stated in the question. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Use eligible matched options with aligned windows; disclose residual non-comparability and uncertainty. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Feedback is optional and non-evaluative. Do not infer health, mood, performance or productivity; do not retain identity-linked comfort history; and do not generalise one person's report to other occupants. No work-content inspection, individual tracking, presence/productivity inference, desk allocation, privacy/accessibility certification or system control. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Allows a voluntary comfort report to be interpreted without creating an individual monitoring profile.

3. Front desks, appointments and in-person service interactions

Questions PS-021-PS-022

PS-021

CORE

L2 - queue forecast

R2 - integration-dependent

Professional-services staff question: My next appointment block starts in 30 minutes. Is the authorised waiting area likely to become crowded, and is an approved overflow option available?

Sensors and telemetry

Proposed sensing (minimum): Anonymous waiting-zone count, arrival rate and doorway count; room temperature, CO2 and numerical sound for context. Coverage: The named waiting area and any approved overflow area. Quality: event-level or one-minute anonymous aggregates from commissioned counters; align clocks and report count error, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregates only; no identities, case types or movement histories.

Authoritative supporting data

Authoritative data: Aggregate appointment totals and arrival windows, approved waiting/overflow locations, capacity, accessibility, visitor rules, closures and current service-point status. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: short-horizon forecast and recommendation. Decision window: the next 60-90 minutes. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Method or baseline: comparable appointment blocks and current arrival trend. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not expose appointment identities or decide staffing. Occupancy telemetry cannot authorise use of an overflow space or certify safe capacity. No appointment/visitor-detail exposure, identification, needs/case inference, staffing/queue policy, access grant or replacement of visitor/privacy rules. Weak count coverage permits confirmed status or a broad range only, never a precise wait or staffing conclusion.

Why this is useful: Gives time to prepare an approved overflow arrangement before the appointment block starts.

PS-022

CORE

L2 - waiting-area recommendation

R2 - integration-dependent

Professional-services staff question: Which approved waiting area is accessible, easy to find and suitable for today's booked visitors?

Sensors and telemetry

Proposed sensing (minimum): Anonymous occupancy, temperature, CO2, light and numerical acoustic indicators in approved waiting areas; current lift/door state. Coverage: Each approved waiting area and its public route. Quality: owner-controlled classification/status is primary; any telemetry is corroborative and must map to the exact room/resource with source times, staleness and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no identities, content or individual activity; disclose only role-authorised status.

Authoritative supporting data

Authoritative data: Current visitor process, approved waiting locations, aggregate appointment demand, accessibility features, entrance/lift status, opening, access and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, route calculation and recommendation. Decision window: the appointment period. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: current authoritative visitor and route status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not reveal who is visiting, direct visitors into staff-only areas or claim accessibility from telemetry. Official accessibility information and visitor rules are mandatory. No appointment/visitor-detail exposure, identification, needs/case inference, staffing/queue policy, access grant or replacement of visitor/privacy rules. Missing/conflicting owner classification, permission or status requires deferral or not assessable.

Why this is useful: Supports clear visitor directions to a currently approved and accessible waiting option.

3. Front desks, appointments and in-person service interactions

Questions PS-023-PS-024

PS-023

CORE

L2 - wait-time estimate

R2 - integration-dependent

Professional-services staff question: What is the current estimated wait at this service point, what evidence supports it, and how uncertain is the estimate?

Sensors and telemetry

Proposed sensing (minimum): Anonymous queue count, arrival rate and service-completion events from an authorised aggregate queue system; no case or person identifiers. Coverage: The service-point queue boundary and approved queue platform. Quality: event-level or one-minute anonymous aggregates from commissioned counters; align clocks and report count error, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregates only; no identities, case types or movement histories.

Authoritative supporting data

Authoritative data: Current opening/service status, queue operating rules, known interruptions and any official published wait-time method. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: current observation and estimate. Decision window: now and the next 15-30 minutes. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Method or baseline: recent same-point service rate under current mode. Expose inputs, assumptions and an error range or conservative buffer. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not expose queue membership, case type or service speed by employee. If the queue system is partial or service modes differ, return count only or not assessable. No appointment/visitor-detail exposure, identification, needs/case inference, staffing/queue policy, access grant or replacement of visitor/privacy rules. Weak count coverage permits confirmed status or a broad range only, never a precise wait or staffing conclusion.

Why this is useful: Lets the staff member communicate a bounded wait estimate rather than an unsupported precise time.

PS-024

USEFUL

L2 - aggregate attendance estimate

R3 - research-grade or restricted

Professional-services staff question: For this afternoon, what range of in-person arrivals should I prepare for using booked appointments and anonymous aggregate patterns?

Sensors and telemetry

Proposed sensing (minimum): anonymous aggregate entrance and waiting-zone counts for the named service point, used only to contextualise arrivals. Coverage: the defined entrance and waiting boundary. Quality: event-level or one-minute anonymous aggregates from commissioned counters; align clocks and report count error, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregates only; no identities, case types or movement histories.

Authoritative supporting data

Authoritative data: aggregate counts of appointments designated in-person for the requested afternoon, approved opening hours, cancellations or service changes and permitted aggregate attendance statistics. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: aggregate estimate and forecast. Decision window: the specified afternoon. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The service may report aggregate booked volume and a clearly labelled attendance range. It must not expose identities, appointment subjects or infer who will attend, why they may not attend, case complexity, staffing adequacy or individual workload. Missing permissions or weak comparability require confirmed totals only or not assessable. No appointment/visitor-detail exposure, identification, needs/case inference, staffing/queue policy, access grant or replacement of visitor/privacy rules. Weak count coverage permits confirmed status or a broad range only, never a precise wait or staffing conclusion.

Why this is useful: Supports preparation for an aggregate arrival range without exposing appointment identities or inferring no-shows as facts.

3. Front desks, appointments and in-person service interactions

Questions PS-025-PS-026

PS-025

CORE

L2 - privacy suitability lookup

R2 - integration-dependent

Professional-services staff question: I need to discuss a sensitive matter with a visitor. Which available authorised service space has the required privacy classification?

Sensors and telemetry

Proposed sensing (minimum): room-level numerical acoustic, occupancy and environmental measures may describe conditions after formal eligibility is established. Coverage: only candidate rooms the user is authorised to consider. Quality: owner-controlled classification/status is primary; any telemetry is corroborative and must map to the exact room/resource with source times, staleness and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no identities, content or individual activity; disclose only role-authorised status.

Authoritative supporting data

Authoritative data: current room privacy classification, permitted use, booking, capacity, staff/visitor access, accessibility, closure and room-owner rules for the requested period. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup and recommendation. Decision window: the appointment interval. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: current room-owner records. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Low occupancy or low measured sound does not prove confidentiality, availability or permission. The service cannot inspect the matter, identify participants, book a room, grant access or certify privacy; missing or conflicting authoritative classification requires deferral or not assessable. No appointment/visitor-detail exposure, identification, needs/case inference, staffing/queue policy, access grant or replacement of visitor/privacy rules. Missing/conflicting owner classification, permission or status requires deferral or not assessable.

Why this is useful: Helps select a formally privacy-classified service space for a sensitive conversation.

PS-026

USEFUL

L2 - environmental forecast

R2 - integration-dependent

Professional-services staff question: Are the front desk and waiting area likely to remain environmentally suitable through the expected lunchtime rush?

Sensors and telemetry

Proposed sensing (minimum): Room-level temperature, RH, direct NDIR CO2, anonymous occupancy and mapped supply-airflow where authorised. Coverage: The service point and waiting zone, with separate coverage if they are distinct spaces. Quality: native event/status cadence plus one-minute aggregates; align clocks, verify room/service/asset mapping and report calibration or count error, uptime, gaps, drift, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts and non-content numerical/status evidence only; no identities, speech or movement histories.

Authoritative supporting data

Authoritative data: Approved service hours, aggregate appointment/arrival forecast, room capacity, HVAC served-zone mapping, maintenance status and weather forecast. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: forecast. Decision window: the specified lunchtime service period. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: similar demand, weather and HVAC operating state. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

CO2 is not complete air quality and telemetry does not certify safety or capacity. If coverage or airflow mapping is missing, provide current observation only. No appointment/visitor-detail exposure, identification, needs/case inference, staffing/queue policy, access grant or replacement of visitor/privacy rules. If decisive authority, target-space evidence or time alignment is missing, omit that criterion and restrict or abstain.

Why this is useful: Supports a decision to prepare mitigation, use an approved alternative or report a persistent waiting-area condition.

3. Front desks, appointments and in-person service interactions

Questions PS-027-PS-028

PS-027

CORE

L2 - disruption routing

R2 - integration-dependent

Professional-services staff question: Our usual service point is officially closed. Which approved alternative should I direct visitors to, and which route is currently verified?

Sensors and telemetry

Proposed sensing (minimum): Current door, lift and broad route-flow status; environmental conditions only for approved alternatives. Coverage: The closed point, approved alternative and public route. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: Official closure notice, approved alternative service point, current opening/access, visitor rules, accessibility, capacity and responsible contact. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, route calculation and recommendation. Decision window: the closure interval. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Method or baseline: current official status only. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not invent an alternative, reroute visitors into staff-only areas or treat low occupancy as service availability. Official communications take precedence. No appointment/visitor-detail exposure, identification, needs/case inference, staffing/queue policy, access grant or replacement of visitor/privacy rules. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Prevents staff from directing visitors to a closed, restricted or inaccessible route.

PS-028

USEFUL

L2 - transition planning

R2 - integration-dependent

Professional-services staff question: I have appointments at service points on different floors. How much travel and setup time should I allow between them?

Sensors and telemetry

Proposed sensing (minimum): Aggregate corridor/stair flow, lift status and door state; no individual movement tracking. Coverage: The authorised routes between the confirmed destinations. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: The user-authorised appointment times and locations, current accessible route graph, staff access, lift/door status, closures and any setup requirement. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, route calculation and estimate. Decision window: between the specified appointments. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Method or baseline: same route and comparable class-change periods. Expose inputs, assumptions and an error range or conservative buffer. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not inspect appointment content or infer who is attending. Route estimates cannot guarantee lift availability or grant access. No appointment/visitor-detail exposure, identification, needs/case inference, staffing/queue policy, access grant or replacement of visitor/privacy rules. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Reduces lateness by providing a conservative inter-appointment travel and setup buffer.

3. Front desks, appointments and in-person service interactions

Questions PS-029-PS-030

PS-029

USEFUL

L3 - peak-cause comparison

R3 - research-grade or restricted

Professional-services staff question: The queue peaked after classes yesterday. Which time-aligned factors were associated with the peak, and is a similar aggregate pattern likely today?

Sensors and telemetry

Proposed sensing (minimum): Anonymous arrival, queue and nearby corridor counts with synchronised clocks; numerical sound and environmental data only as context. Coverage: The service point and relevant circulation zone. Quality: event-level or one-minute anonymous aggregates from commissioned counters; align clocks and report count error, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregates only; no identities, case types or movement histories.

Authoritative supporting data

Authoritative data: Published timetable release periods at aggregate level, service hours, appointment totals, event schedule, closures and current service mode. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: time-aligned historical comparison and recurrence forecast. Decision window: the observed event and next comparable period. Do not claim causality; missing clock alignment or changed service definitions make the explanation limited. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not identify students or link an individual class or attendee to service use. A temporal association may support preparation but cannot prove why a person joined the queue. No appointment/visitor-detail exposure, identification, needs/case inference, staffing/queue policy, access grant or replacement of visitor/privacy rules. Weak count coverage permits confirmed status or a broad range only, never a precise wait or staffing conclusion.

Why this is useful: Helps prepare for a recurring aggregate queue pattern without claiming a proven cause.

PS-030

USEFUL

L3 - temporary service-point comparison

R3 - research-grade or restricted

Professional-services staff question: We may use either of two service points temporarily. Which is better suited to expected demand and the visitors' stated requirements?

Sensors and telemetry

Proposed sensing (minimum): Anonymous occupancy/queue history, room temperature, CO2, numerical sound, route flow and service-health telemetry for both approved points. Coverage: Each candidate service point and its waiting/route boundary. Quality: native event/status cadence plus one-minute aggregates; align clocks, verify room/service/asset mapping and report calibration or count error, uptime, gaps, drift, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts and non-content numerical/status evidence only; no identities, speech or movement histories.

Authoritative supporting data

Authoritative data: Owner approval for the temporary activity, current room purpose, capacity, access, accessibility, privacy classification, opening, equipment and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: comparison and recommendation. Decision window: the approved temporary-service interval. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Method or baseline: same expected demand and operating mode. Use eligible matched options with aligned windows; disclose residual non-comparability and uncertainty. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The building cannot authorise relocation, set staffing or advertise a change. If approval or comparable coverage is absent, the comparison is not assessable. No appointment/visitor-detail exposure, identification, needs/case inference, staffing/queue policy, access grant or replacement of visitor/privacy rules. If decisive authority, target-space evidence or time alignment is missing, omit that criterion and restrict or abstain.

Why this is useful: Supports a temporary service-point choice that respects demand, access, privacy and visitor requirements.

4. Meetings, collaboration and shared rooms/resources

Questions PS-031-PS-032

PS-031

CORE

L2 - privacy-aware recommendation

R2 - integration-dependent

Professional-services staff question: Which authorised room meets the privacy, access and availability requirements for this confidential HR, finance, programme or research-support meeting?

Sensors and telemetry

Proposed sensing (minimum): Anonymous occupancy and numerical acoustic background may support context; no speech capture. Coverage: Only candidate rooms with current privacy, access and booking records. Quality: owner-controlled classification/status is primary; any telemetry is corroborative and must map to the exact room/resource with source times, staleness and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no identities, content or individual activity; disclose only role-authorised status.

Authoritative supporting data

Authoritative data: Room purpose, privacy classification, capacity, booking, staff/visitor access, accessibility, equipment, opening and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup and recommendation. Decision window: the requested meeting interval. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: current room-owner records. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The building cannot determine information sensitivity, reveal another meeting or certify confidentiality from quietness. No meeting/document inspection, participant identification, confidentiality inference from quietness, booking/access grant or equipment control. Missing/conflicting owner classification, permission or status requires deferral or not assessable.

Why this is useful: Helps select a legitimate room for a confidential professional-services meeting.

PS-032

CORE

L2 - hybrid readiness recommendation

R2 - integration-dependent

Professional-services staff question: Which authorised room is best for a hybrid team meeting with verified network, power, approved AV and any required assistive technology?

Sensors and telemetry

Proposed sensing (minimum): Authorised network endpoint and power status, AV/capture equipment health, room temperature, CO2 and numerical acoustic indicators; no content inspection. Coverage: The candidate room and mapped digital/building assets. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: Current room features, bookability, capacity, access, accessibility and assistive-technology inventory; official AV/IT incidents, maintenance and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, service comparison and recommendation. Decision window: the meeting and setup interval. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: latest official service-health data. Use eligible matched options with aligned windows; disclose residual non-comparability and uncertainty. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not inspect meeting content, grant access or guarantee personal-device compatibility. Unknown assistive or service status requires an approved pre-check. No meeting/document inspection, participant identification, confidentiality inference from quietness, booking/access grant or equipment control. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Supports a hybrid-room choice that is authorised, accessible and service-ready.

4. Meetings, collaboration and shared rooms/resources

Questions PS-033-PS-034

PS-033

CORE

L2 - meeting-condition forecast

R2 - integration-dependent

Professional-services staff question: Is the assigned room likely to remain suitable for a two-hour working meeting with ten people?

Sensors and telemetry

Proposed sensing (minimum): In-room temperature, RH, direct NDIR CO2, anonymous occupancy and mapped supply-airflow; numerical acoustics if discussion suitability matters. Coverage: The candidate room or validated served zone. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: Current booking, room capacity/purpose, expected group size supplied by the user, HVAC mapping, accessibility, maintenance and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: forecast. Decision window: the two-hour meeting period. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: similar group size, duration, weather and HVAC state. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The result cannot certify safety or guarantee comfort. If expected occupancy or airflow coverage is missing, provide current conditions only. No meeting/document inspection, participant identification, confidentiality inference from quietness, booking/access grant or equipment control. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Helps decide whether to proceed in the assigned room or seek an authorised alternative before the meeting.

PS-034

CORE

L2 - availability-aware recommendation

R2 - integration-dependent

Professional-services staff question: This shared meeting room looks empty. Is it actually available, bookable and authorised for my team to use now?

Sensors and telemetry

Proposed sensing (minimum): Anonymous occupancy and door state may describe current use but cannot establish booking or permission. Coverage: The room itself. Quality: owner-controlled classification/status is primary; any telemetry is corroborative and must map to the exact room/resource with source times, staleness and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no identities, content or individual activity; disclose only role-authorised status.

Authoritative supporting data

Authoritative data: Current authoritative booking, room purpose, ownership, permitted use, staff access, capacity, setup buffer, accessibility and closure status. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative availability lookup. Decision window: now through the proposed meeting. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Show source owner/effective/retrieval time and do not extrapolate beyond the record. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Empty or quiet does not mean available, bookable, private or authorised. The service cannot make or override a booking, grant access or displace another user. No meeting/document inspection, participant identification, confidentiality inference from quietness, booking/access grant or equipment control. Missing/conflicting owner classification, permission or status requires deferral or not assessable.

Why this is useful: Prevents an apparently empty room from being treated as available or permitted.

4. Meetings, collaboration and shared rooms/resources

Questions PS-035-PS-036

PS-035

USEFUL

L2 - shared-resource recommendation

R2 - integration-dependent

Professional-services staff question: Which approved printer, scanner or shared device is operational now and likely to have the shortest queue?

Sensors and telemetry

Proposed sensing (minimum): owner-managed operational state, error/consumable status and anonymous aggregate queue or device-use state for approved printers, scanners or shared devices. Coverage: the exact device and its authorised service location. Quality: owner-managed device state and fault/consumable status, with anonymous queue counts where available; report exact mapping, source times, staleness and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no document, username, file, print or scan content inspection.

Authoritative supporting data

Authoritative data: current approved-device inventory, staff entitlement, operational/maintenance status, location, opening/access and any reservation or secure-print rules. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, estimate and recommendation. Decision window: the user-specified period. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: current device status and recent aggregate demand. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not inspect documents, print jobs, usernames or device/network content; do not bypass secure-print rules, reserve a device, grant access or guarantee completion. Stale or conflicting device status requires a limited answer or referral to the owner. No meeting/document inspection, participant identification, confidentiality inference from quietness, booking/access grant or equipment control. Missing/conflicting device-owner status requires an owner check; do not promise availability, wait time or completion.

Why this is useful: Helps choose an approved operational device with a bounded wait estimate.

PS-036

CORE

L2 - visitor-meeting recommendation

R2 - integration-dependent

Professional-services staff question: I am hosting an interview or external meeting. Which authorised room is private, accessible and straightforward for visitors to reach?

Sensors and telemetry

Proposed sensing (minimum): Public-route footfall, lift/door state, room environment and numerical acoustic background for approved options; no speech. Coverage: Candidate visitor-approved rooms and their public routes. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: Current visitor process, room purpose/privacy, booking, capacity, visitor access, accessibility, entrance/lift status, equipment and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, route calculation and recommendation. Decision window: the meeting and arrival window. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Method or baseline: current official visitor and route status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not expose interview details, grant access or direct visitors into staff-only areas. Quietness does not certify privacy. No meeting/document inspection, participant identification, confidentiality inference from quietness, booking/access grant or equipment control. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Supports an inclusive, private and navigable meeting-room choice for an external visitor.

4. Meetings, collaboration and shared rooms/resources

Questions PS-037-PS-038

PS-037

USEFUL

L2 - recurrence forecast

R2 - integration-dependent

Professional-services staff question: The meeting room became stuffy yesterday. Is the same pattern likely during tomorrow's meeting under comparable use and conditions?

Sensors and telemetry

Proposed sensing (minimum): In-room CO2, temperature, RH, anonymous occupancy and mapped supply-airflow with one-minute history. Coverage: The same room or validated served zone. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: Tomorrow's confirmed booking, expected group size/duration, HVAC schedule, maintenance state, weather forecast and comparable prior meetings. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: event reconstruction and forecast. Decision window: tomorrow's meeting period. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: same room, similar group size, duration and HVAC state. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not assume identical attendance or claim a mechanical cause. If yesterday's or tomorrow's coverage is incomplete, return a conditional forecast or not assessable. No meeting/document inspection, participant identification, confidentiality inference from quietness, booking/access grant or equipment control. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Helps decide whether to keep the assigned room, change time or request an authorised alternative.

PS-038

USEFUL

L2 - lower-disruption recommendation

R2 - integration-dependent

Professional-services staff question: Can I choose an authorised room or time for this internal meeting with lower expected background noise and foot traffic?

Sensors and telemetry

Proposed sensing (minimum): Numerical acoustic indicators and anonymous occupancy/footfall in eligible rooms and routes; no speech or identities. Coverage: Each candidate room and nearby circulation boundary. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: Current booking options the user is authorised to consider, room purpose/capacity, access, accessibility, participant constraints supplied by the user and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, comparison and recommendation. Decision window: the allowed alternative windows. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: same room type and comparable schedule context. Use eligible matched options with aligned windows; disclose residual non-comparability and uncertainty. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The service cannot reschedule the meeting or infer participant availability beyond constraints explicitly supplied by the user. No meeting/document inspection, participant identification, confidentiality inference from quietness, booking/access grant or equipment control. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Supports a lower-disruption meeting choice without claiming confidentiality from low noise.

4. Meetings, collaboration and shared rooms/resources

Questions PS-039-PS-040

PS-039

USEFUL

L2 - secure-resource lookup

R2 - integration-dependent

Professional-services staff question: Is the secure storage or records-drop facility assigned to my team currently accessible and reported operational?

Sensors and telemetry

Proposed sensing (minimum): Authorised asset health, door/lock state and environmental or leak alert only where exposed by the owner; no content or access-log identities. Coverage: The named secure resource and its authorised access point. Quality: owner-managed device state and fault/consumable status, with anonymous queue counts where available; report exact mapping, source times, staleness and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no document, username, file, print or scan content inspection.

Authoritative supporting data

Authoritative data: Current staff entitlement, resource owner, permitted use, opening/access, maintenance, closure and official incident status. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup with status observation. Decision window: now or the requested visit time. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: current owner-controlled status. Show source owner/effective/retrieval time and do not extrapolate beyond the record. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not disclose contents, user identities or detailed access events, and do not unlock or grant access. Security system authority takes precedence. No meeting/document inspection, participant identification, confidentiality inference from quietness, booking/access grant or equipment control. Missing/conflicting device-owner status requires an owner check; do not promise availability, wait time or completion.

Why this is useful: Confirms whether an assigned secure resource is authorised and reported usable before the staff member travels to it.

PS-040

USEFUL

L2 - workshop-space readiness

R2 - integration-dependent

Professional-services staff question: We have an approved cross-team workshop. Is the assigned room ready for the agreed layout, equipment, expected occupancy and duration?

Sensors and telemetry

Proposed sensing (minimum): Room temperature, CO2, anonymous occupancy, power status and authorised AV/service health; no material or screen inspection. Coverage: The confirmed room and mapped services. Quality: native event/status cadence plus one-minute aggregates; align clocks, verify room/service/asset mapping and report calibration or count error, uptime, gaps, drift, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts and non-content numerical/status evidence only; no identities, speech or movement histories.

Authoritative supporting data

Authoritative data: Current booking, approved room layout/capacity, permitted activity, equipment inventory, accessibility, setup window, AV/IT status, maintenance and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, readiness calculation and recommendation. Decision window: setup through workshop end. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: current owner records and comparable group load. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The building cannot rearrange furniture, approve the activity or guarantee equipment compatibility. Current room-owner and AV/IT guidance remains authoritative. No meeting/document inspection, participant identification, confidentiality inference from quietness, booking/access grant or equipment control. If decisive authority, target-space evidence or time alignment is missing, omit that criterion and restrict or abstain.

Why this is useful: Helps confirm workshop readiness and identify gaps for the responsible owner before participants arrive.

5. Hybrid work, communications infrastructure and dependable services

Questions PS-041-PS-042

PS-041

CORE

L2 - on-site suitability recommendation

R2 - integration-dependent

Professional-services staff question: I have remote meetings and in-person appointments tomorrow. Which part of the day is the best-supported option for working in Abacws?

Sensors and telemetry

Proposed sensing (minimum): Authorised room network/power status, environmental conditions and anonymous occupancy for eligible workspaces. Coverage: Only workspaces the staff member may use. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: User-authorized meeting/appointment constraints, approved hybrid-work arrangements, workspace allocation, access, booking, opening, maintenance and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup and recommendation. Decision window: tomorrow's working day. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: current schedule and latest official service forecasts. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The service cannot approve hybrid work, inspect meeting content or assess the user's home environment. No call/traffic/account/device/content inspection, user identification, performance promise, IT-control bypass, access grant or system control. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Supports a practical on-site work period around fixed remote and in-person commitments.

PS-042

CORE

L2 - confidential-call recommendation

R2 - integration-dependent

Professional-services staff question: Which authorised space is approved and currently suitable for a confidential video or telephone call?

Sensors and telemetry

Proposed sensing (minimum): Numerical acoustic background, anonymous occupancy and room environment; network and power status from authorised service feeds. No speech or call capture. Coverage: Candidate rooms with authoritative privacy classification. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: Current room purpose/privacy, booking, capacity, staff access, accessibility, network/power/AV status and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative privacy/permission lookup plus current service observation and recommendation. Decision window: the call interval. Unknown privacy classification makes the room ineligible. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Low measured sound does not certify confidentiality, and the building must not record or analyse the call. The service cannot book the room, grant access or guarantee acoustic privacy. No call/traffic/account/device/content inspection, user identification, performance promise, IT-control bypass, access grant or system control. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Helps choose a formally suitable call space rather than assuming privacy from quietness.

5. Hybrid work, communications infrastructure and dependable services

Questions PS-043-PS-044

PS-043

CORE

L2 - service-readiness forecast

R2 - integration-dependent

Professional-services staff question: Are the assigned room's network, power and approved meeting equipment likely to support the webinar, and what verified fallback is available?

Sensors and telemetry

Proposed sensing (minimum): Authorised network endpoint health, access-point/controller status, room circuit/UPS state and optional AV equipment health; no traffic or device-content inspection. Coverage: The assigned room and mapped digital/power assets. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: Official IT/power incidents and planned maintenance, current room booking/access, webinar time, required AV features and approved support guidance. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, recent-stability calculation and forecast. Decision window: setup and webinar interval. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: official incident history and current asset status. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not inspect webinar content or guarantee end-to-end internet, platform or personal-device performance. IT service status is authoritative. No call/traffic/account/device/content inspection, user identification, performance promise, IT-control bypass, access grant or system control. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Allows the organiser to verify webinar readiness and retain an authorised fallback.

PS-044

CORE

L1 - service lookup

R2 - integration-dependent

Professional-services staff question: Where can I work for the next hour with confirmed access, power, an authorised network connection and suitable room conditions?

Sensors and telemetry

Proposed sensing (minimum): Authorised desk/room power status, network service health and room occupancy/environment for eligible spaces. Coverage: The candidate workspace and mapped power/network assets. Quality: native event/status cadence plus one-minute aggregates; align clocks, verify room/service/asset mapping and report calibration or count error, uptime, gaps, drift, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts and non-content numerical/status evidence only; no identities, speech or movement histories.

Authoritative supporting data

Authoritative data: Current workspace entitlement, booking/claim rule, staff access, accessibility, opening, service incidents and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup with observation. Decision window: the next hour. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: current owner-controlled status. Show source owner/effective/retrieval time and do not extrapolate beyond the record. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

An empty desk is not automatically available. The building cannot connect a device, inspect traffic or guarantee application performance. No call/traffic/account/device/content inspection, user identification, performance promise, IT-control bypass, access grant or system control. If decisive authority, target-space evidence or time alignment is missing, omit that criterion and restrict or abstain.

Why this is useful: Helps locate a workspace that is both permitted and service-ready for the next hour.

5. Hybrid work, communications infrastructure and dependable services

Questions PS-045-PS-046

PS-045

CORE

L2 - outage fallback recommendation

R2 - integration-dependent

Professional-services staff question: The network in my usual area is degraded. Which authorised fallback workspace is officially unaffected and suitable for my task?

Sensors and telemetry

Proposed sensing (minimum): Authorised network-zone and endpoint health, power status and room environmental conditions in eligible alternatives. Coverage: The affected network zone and each candidate fallback workspace. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: Official IT incident scope, workspace allocation/access, booking, accessibility, opening, room/service status and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, spatial impact mapping and recommendation. Decision window: the incident period. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: official incident boundary and current endpoint status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not infer outage scope from user traffic, reroute networks, inspect content or grant workspace access. If official incident mapping is absent, defer to IT. No call/traffic/account/device/content inspection, user identification, performance promise, IT-control bypass, access grant or system control. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Supports an authorised move away from a known network incident without guessing from signal strength.

PS-046

USEFUL

L2 - transfer-window recommendation

R2 - integration-dependent

Professional-services staff question: I need a reliable window for a large authorised data transfer. When is the verified network-service risk lowest?

Sensors and telemetry

Proposed sensing (minimum): Authorised network service-health and capacity indicators at aggregate infrastructure level; no file, destination, packet, account or device inspection. Coverage: The relevant authorised network zone or wired endpoint. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: Official maintenance/incidents, applicable usage policy, approved network endpoint and the user-specified duration/technical requirement. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authorised service-health lookup, historical reliability comparison and bounded forecast. Decision window: user-specified. Do not inspect traffic or estimate file content; stale or unavailable network telemetry means no forecast. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The service cannot inspect the transfer, promise throughput, prioritise traffic or bypass information-security controls. The recommendation remains subordinate to IT policy and authorised service status. No call/traffic/account/device/content inspection, user identification, performance promise, IT-control bypass, access grant or system control. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Helps schedule a large transfer during a lower-risk service window with a valid fallback.

5. Hybrid work, communications infrastructure and dependable services

Questions PS-047-PS-048

PS-047

CORE

L2 - hybrid equipment readiness

R2 - integration-dependent

Professional-services staff question: A remote participant is joining our meeting. Are the approved hybrid facilities reported ready, and what verified fallback can I use?

Sensors and telemetry

Proposed sensing (minimum): Authorised AV/capture, display, microphone/speaker health, network and power status; room environment for comfort only. No audio/video content capture by the building service. Coverage: The confirmed meeting room and mapped equipment. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: Current booking, equipment inventory, official AV/IT status, assistive-technology needs supplied by the user, support contact, setup window and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup and readiness recommendation. Decision window: setup through meeting start. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: latest official equipment status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not activate recording, inspect content or guarantee platform/device compatibility. AV/IT and accessibility services remain authoritative. No call/traffic/account/device/content inspection, user identification, performance promise, IT-control bypass, access grant or system control. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Allows the organiser to verify the hybrid setup before the remote participant joins.

PS-048

USEFUL

L2 - low-noise call-space recommendation

R2 - integration-dependent

Professional-services staff question: I have a routine phone call. Which authorised nearby space has a lower measured noise background, without implying confidentiality?

Sensors and telemetry

Proposed sensing (minimum): Numerical LAeq/percentile sound metrics and anonymous occupancy in eligible call spaces; no raw audio or speech. Coverage: Each candidate room or approved call area. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: Current permitted use, booking/availability, staff access, accessibility, privacy classification and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, observation and recommendation. Decision window: the requested call period. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: current room and sensor status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Low sound is not privacy. Do not record, transcribe or infer conversation content, and do not recommend a space whose permitted use is unknown. No call/traffic/account/device/content inspection, user identification, performance promise, IT-control bypass, access grant or system control. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Helps choose a less noisy location for a routine call while keeping confidentiality separate.

5. Hybrid work, communications infrastructure and dependable services

Questions PS-049-PS-050

PS-049

USEFUL

L3 - recovery assessment

R3 - research-grade or restricted

Professional-services staff question: After today's outage, is there enough authoritative status and local evidence for me to resume time-sensitive work?

Sensors and telemetry

Proposed sensing (minimum): Authorised network endpoint/controller status, room circuit/UPS state and recent interruption events; no user traffic or content. Coverage: The affected service zone and the user's eligible workspace. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: Official incident and restoration messages, maintenance state, current workspace access/booking and the service owner's recovery criteria. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative recovery lookup and stability calculation. Decision window: now and the next hour. One successful connection is insufficient; conflicting or stale status requires continued fallback or deferral. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Expose inputs, assumptions and an error range or conservative buffer. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The service cannot declare the incident closed, inspect devices or network content, or guarantee uninterrupted operation. It may support the staff member's resume-or-wait decision using authorised recovery evidence only. No call/traffic/account/device/content inspection, user identification, performance promise, IT-control bypass, access grant or system control. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Supports a cautious decision to resume, delay or relocate time-sensitive work after an outage.

PS-050

USEFUL

L1 - bounded comparison

R1 - practical

Professional-services staff question: Using only the on-site requirements I specify, can you assess whether an authorised Abacws option meets them without evaluating my home setup?

Sensors and telemetry

Proposed sensing (minimum): only on-site room, power, network and environmental status for authorised Abacws options. Coverage: the named candidate workspace and its validated served assets. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: User-specified on-site requirements, current workspace entitlement, access, booking, accessibility, opening, maintenance and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: requirements matching and recommendation. Decision window: the requested work period. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not inspect, infer or request details about the user's home, devices, household, connection or working pattern. The service recommends only among authorised on-site options and cannot set hybrid-work policy. No call/traffic/account/device/content inspection, user identification, performance promise, IT-control bypass, access grant or system control. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Helps assess an on-site option against stated needs without monitoring or comparing the home environment.

6. Movement, service/event support and demand peaks

Questions PS-051-PS-052

PS-051

CORE

L2 - dynamic route recommendation

R2 - integration-dependent

Professional-services staff question: What is the least crowded currently verified step-free route from my office to the service desk during the next class change?

Sensors and telemetry

Proposed sensing (minimum): Anonymous corridor/stair footfall, lift/door state and broad congestion indicators. Coverage: Eligible routes between the confirmed origin and destination. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: Current route graph, staff access, accessibility features, lift/door status, closures and the user-supplied departure time. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, short-horizon flow forecast and route recommendation. Decision window: the next transition period. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Method or baseline: matched class-change flow and current route status. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not track the user or others, expose access events or guarantee a route remains clear. Official closure and accessibility information takes precedence. No individual tracking or movement history, permission inference from low crowding, duty change, access grant or closure/accessibility override. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Helps the staff member arrive on time using a currently verified step-free route with lower expected congestion.

PS-052

USEFUL

L2 - materials route planning

R2 - integration-dependent

Professional-services staff question: I need to carry approved service or event materials to another floor. Which authorised route is currently suitable?

Sensors and telemetry

Proposed sensing (minimum): Lift, door and route-state telemetry, anonymous congestion and optional environmental conditions; no inspection of materials. Coverage: The authorised origin, destination and handling route. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: Current staff access, route and lift status, closures, handling/trolley restrictions, event destination and any load or induction rule. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, route calculation and recommendation. Decision window: the planned movement window. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Method or baseline: current official route and lift status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not inspect, classify or authorise the materials, exceed lift/load rules or grant access. Safety and handling procedures remain authoritative. No individual tracking or movement history, permission inference from low crowding, duty change, access grant or closure/accessibility override. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Supports safe, authorised movement of approved service or event materials between floors.

6. Movement, service/event support and demand peaks

Questions PS-053-PS-054

PS-053

CORE

L2 - transition-time estimate

R2 - integration-dependent

Professional-services staff question: I have appointments on different floors with a short gap. What conservative travel and setup buffer should I allow?

Sensors and telemetry

Proposed sensing (minimum): Anonymous route flow, lift state and door status; no individual movement tracking. Coverage: The eligible routes between user-authorised appointment locations. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: The user-authorised appointment times/locations, current staff access, accessible route graph, closures, lift status and required setup time. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, route calculation and estimate. Decision window: between the confirmed appointments. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Method or baseline: same route and comparable time-of-day. Expose inputs, assumptions and an error range or conservative buffer. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not inspect appointment content or infer attendees. Travel time is an estimate and cannot grant access or guarantee lift availability. No individual tracking or movement history, permission inference from low crowding, duty change, access grant or closure/accessibility override. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Reduces missed appointments by allowing for route, lift and setup uncertainty.

PS-054

CORE

L3 - event-demand forecast

R3 - research-grade or restricted

Professional-services staff question: An open day or recruitment event is scheduled. When, and at which authorised service points, are aggregate enquiries likely to peak?

Sensors and telemetry

Proposed sensing (minimum): Anonymous entrance, corridor, waiting-zone and service-point counts with synchronised clocks; numerical environmental data for service-area context. Coverage: Approved event routes, entrances and service points. Quality: event-level or one-minute anonymous aggregates from commissioned counters; align clocks and report count error, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregates only; no identities, case types or movement histories.

Authoritative supporting data

Authoritative data: Official event programme, registrations at aggregate level, approved service locations/hours, visitor routes, accessibility, closures and staffing instructions supplied by event owners. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: spatial-temporal forecast. Decision window: the event day. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Method or baseline: comparable events and current programme. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not identify visitors, set staffing or change event operations. Event owner and security/safety instructions take precedence. No individual tracking or movement history, permission inference from low crowding, duty change, access grant or closure/accessibility override. Weak count coverage permits confirmed status or a broad range only, never a precise wait or staffing conclusion.

Why this is useful: Lets service staff prepare information and visitor-flow arrangements for event-driven demand peaks.

6. Movement, service/event support and demand peaks

Questions PS-055-PS-056

PS-055

USEFUL

L2 - event-support transition recommendation

R2 - integration-dependent

Professional-services staff question: I need to move from my office to a confirmed teaching or event-support point. When should I leave to avoid the busiest route?

Sensors and telemetry

Proposed sensing (minimum): Anonymous route footfall, lift and door state; no tracking. Coverage: The authorised route between the confirmed locations. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: User-authorised event time/location and support duty, current access, accessible routes, closures, lift status and setup requirement. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: route forecast and recommendation. Decision window: the pre-event transition window. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Method or baseline: comparable event or class-change periods. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The building cannot assign the support duty, inspect event content or override event-owner instructions. No individual tracking or movement history, permission inference from low crowding, duty change, access grant or closure/accessibility override. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Supports timely departure for a confirmed support duty without changing the timetable.

PS-056

CORE

L2 - accessible handling route

R2 - integration-dependent

Professional-services staff question: I am moving boxes or a trolley between service areas. Which approved step-free route is usable now, and are the lift and door dimensions sufficient?

Sensors and telemetry

Proposed sensing (minimum): Lift/door operational state and anonymous route congestion; no material inspection. Coverage: The authorised handling route and relevant lift/doors. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: Current accessible route graph, staff access, lift/load rules, trolley/handling policy, closures and destination status. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup and route recommendation. Decision window: the movement interval. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Method or baseline: current official route status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not certify load safety, authorise the item or exceed manual-handling guidance. If no verified route exists, defer rather than improvising. No individual tracking or movement history, permission inference from low crowding, duty change, access grant or closure/accessibility override. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Helps choose a route that is authorised and physically suitable for the trolley or load.

6. Movement, service/event support and demand peaks

Questions PS-057-PS-058

PS-057

USEFUL

L2 - low-congestion timing

R2 - integration-dependent

Professional-services staff question: During the next two hours, when is movement between my confirmed service points likely to be least crowded?

Sensors and telemetry

Proposed sensing (minimum): Anonymous corridor/stair/lift-lobby footfall and current lift/door state. Coverage: The eligible route network between confirmed service points. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: Current access and route graph, closures, timetable/event periods as aggregate context and the user's allowed movement window. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: current observation, short-horizon forecast and recommendation. Decision window: the next two hours. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Method or baseline: same route and comparable timetable context. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not identify people or infer where individuals are going. The result cannot guarantee a route remains uncrowded. No individual tracking or movement history, permission inference from low crowding, duty change, access grant or closure/accessibility override. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Lets the staff member avoid a predictable circulation peak when the trip is flexible.

PS-058

USEFUL

L3 - visitor-arrival forecast

R3 - research-grade or restricted

Professional-services staff question: A group of visitors is expected. When is reception likely to face the highest aggregate arrival load, and how much preparation time do I have?

Sensors and telemetry

Proposed sensing (minimum): Anonymous entrance, reception and waiting-zone counts; no identity or face recognition. Coverage: The approved visitor entrance and reception boundary. Quality: event-level or one-minute anonymous aggregates from commissioned counters; align clocks and report count error, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregates only; no identities, case types or movement histories.

Authoritative supporting data

Authoritative data: Official visit schedule and aggregate group size, approved arrival window, visitor process, entrance status, accessibility and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: arrival-wave forecast. Decision window: the visitor arrival period. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Method or baseline: same entrance and comparable group-arrival pattern. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not expose visitor names or infer attendance. The estimate cannot set staffing or change security procedures. No individual tracking or movement history, permission inference from low crowding, duty change, access grant or closure/accessibility override. Weak count coverage permits confirmed status or a broad range only, never a precise wait or staffing conclusion.

Why this is useful: Creates a preparation window for signage, information and an approved visitor-flow arrangement.

6. Movement, service/event support and demand peaks

Questions PS-059-PS-060

PS-059

CORE

L2 - closure-aware route

R2 - integration-dependent

Professional-services staff question: A corridor or entrance is officially closed. Which currently verified route should I use to reach my service point?

Sensors and telemetry

Proposed sensing (minimum): Door/lift state and anonymous congestion on eligible alternatives. Coverage: The affected segment and authorised alternative routes. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: Official closure notice, current route graph, staff access, accessibility, lift status and responsible contact. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup and route recommendation. Decision window: the closure period. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Method or baseline: current official status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not infer a closure solely from low movement or a door sensor, and do not route staff through restricted areas. No individual tracking or movement history, permission inference from low crowding, duty change, access grant or closure/accessibility override. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Prevents use of an outdated or inaccessible route during an official closure.

PS-060

USEFUL

L3 - assigned-task route optimisation

R3 - research-grade or restricted

Professional-services staff question: I have several confirmed service points to visit. In what order should I make the trips to reduce walking and avoid known demand peaks?

Sensors and telemetry

Proposed sensing (minimum): Anonymous route flow, lift/door status and broad service-point demand indicators; no personal tracking. Coverage: Only routes and service points in the user's authorised task list. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: The user-authorised destinations, required time windows and task sequence constraints; current access, routes, lift/closure status and service-point opening. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: constrained route calculation and recommendation. Decision window: the specified work period. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Method or baseline: current route status and forecast demand peaks. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The building cannot assign duties, reallocate staff or decide service priorities. It may optimise only the confirmed task list supplied by the user. No individual tracking or movement history, permission inference from low crowding, duty change, access grant or closure/accessibility override. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Reduces unnecessary walking while respecting fixed duties, access and current closures.

7. Visitors, accessibility, inclusion and staff well-being

Questions PS-061-PS-062

PS-061

CORE

L2 - accessible visitor route

R2 - integration-dependent

Professional-services staff question: A visitor needs a step-free route to our approved meeting point. Which route is currently verified as usable?

Sensors and telemetry

Proposed sensing (minimum): Lift and door state plus anonymous route congestion; no identity tracking. Coverage: The public/visitor-approved route between the confirmed entrance and meeting point. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: Current visitor process, approved entrance/meeting point, authoritative accessible route, lift/door status, temporary closures and assistance contact. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup and route recommendation. Decision window: the visitor arrival period. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Method or baseline: current official accessibility and asset status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Telemetry cannot certify accessibility or grant visitor access. If no verified route exists, defer to the accessibility/visitor service. No disability/health inference, identification, visitor-data disclosure, accessibility/safety certification from telemetry or support-service override. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Helps give a visitor a current step-free route rather than relying on the historical plan.

PS-062

CORE

L2 - inclusive-room suitability

R2 - integration-dependent

Professional-services staff question: Which authorised meeting room meets the access and assistive-technology requirements the visitor has stated?

Sensors and telemetry

Proposed sensing (minimum): Authorised room service status, numerical acoustics, light and environment only as secondary context. Coverage: Candidate rooms with current authoritative accessibility records. Quality: owner-controlled classification/status is primary; any telemetry is corroborative and must map to the exact room/resource with source times, staleness and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no identities, content or individual activity; disclose only role-authorised status.

Authoritative supporting data

Authoritative data: User-supplied functional requirements, current room accessibility features, assistive-technology inventory/status, booking, access, capacity, visitor rules and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup and recommendation. Decision window: the meeting interval. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: current accessibility and room-owner records. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

. No disability/health inference, identification, visitor-data disclosure, accessibility/safety certification from telemetry or support-service override. Missing/conflicting owner classification, permission or status requires deferral or not assessable.

Why this is useful: Supports an inclusive room choice based on stated requirements and current authorised records.

7. Visitors, accessibility, inclusion and staff well-being

Questions PS-063-PS-064

PS-063

USEFUL

L2 - quieter waiting recommendation

R2 - integration-dependent

Professional-services staff question: A visitor has asked for a quieter waiting place. Which approved accessible option nearby currently has lower measured noise and crowding?

Sensors and telemetry

Proposed sensing (minimum): Numerical acoustic indicators and anonymous occupancy in visitor-approved waiting areas; no speech or identity. Coverage: Each approved waiting area and public route. Quality: native event/status cadence plus one-minute aggregates; align clocks, verify room/service/asset mapping and report calibration or count error, uptime, gaps, drift, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts and non-content numerical/status evidence only; no identities, speech or movement histories.

Authoritative supporting data

Authoritative data: Current visitor-approved locations, access, accessibility, capacity, opening, route status and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, observation and recommendation. Decision window: the waiting period. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: current room and route status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not infer distress, disability or health. Low sound does not imply privacy, and the building cannot create a new waiting area. No disability/health inference, identification, visitor-data disclosure, accessibility/safety certification from telemetry or support-service override. If decisive authority, target-space evidence or time alignment is missing, omit that criterion and restrict or abstain.

Why this is useful: Helps offer a calmer approved waiting option without profiling or identifying visitors.

PS-064

CORE

L1 - amenity lookup

R2 - integration-dependent

Professional-services staff question: Where is the nearest accessible toilet reported open, and is the step-free route to it currently verified?

Sensors and telemetry

Proposed sensing (minimum): event-driven lift and relevant door state may confirm route operation after the facility is verified. Coverage: the current accessible toilet and the complete step-free route from the stated origin. Quality: verify route/asset mapping, observed/retrieved times, staleness, maintenance and conflict flags. Telemetry is proposed and cannot certify accessibility. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: current accessible-facility designation, opening/closure status, accessible route graph, staff/visitor access rules, lift/door status and official wayfinding information. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative amenity/accessibility lookup and route calculation. Decision window: now. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Expose inputs, assumptions and an error range or conservative buffer. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The service cannot infer personal needs, certify accessibility from sensors, unlock doors or promise the facility will remain available. Missing or conflicting authoritative status requires a qualified answer, official contact or not assessable. No disability/health inference, identification, visitor-data disclosure, accessibility/safety certification from telemetry or support-service override. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Allows accurate directions to an officially open accessible facility and route.

7. Visitors, accessibility, inclusion and staff well-being

Questions PS-065-PS-066

PS-065

CORE

L2 - stated-needs workspace recommendation

R2 - integration-dependent

Professional-services staff question: I need a lower-noise, lower-crowding workspace today. Which authorised option best meets the requirements I have stated?

Sensors and telemetry

Proposed sensing (minimum): Numerical sound, anonymous occupancy, temperature, CO2 and light in eligible workspaces. Coverage: Each candidate room or desk zone. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: User-stated functional requirements, current workspace entitlement, booking, access, accessibility, opening, services and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, observation/forecast and recommendation. Decision window: the user-specified work interval. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: same space and comparable periods where forecasting is used. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

. No disability/health inference, identification, visitor-data disclosure, accessibility/safety certification from telemetry or support-service override. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Supports a personal workspace choice based on stated needs and authorised availability.

PS-066

USEFUL

L2 - lower-congestion appointment time

R2 - integration-dependent

Professional-services staff question: I can offer a visitor several approved appointment times. Which is expected to have the least route and waiting-area congestion?

Sensors and telemetry

Proposed sensing (minimum): Anonymous entrance, route and waiting-area counts; no identities. Coverage: The approved visitor route and waiting area. Quality: event-level or one-minute anonymous aggregates from commissioned counters; align clocks and report count error, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregates only; no identities, case types or movement histories.

Authoritative supporting data

Authoritative data: The appointment times the user is authorised to offer, current visitor process, accessible routes, service opening, planned events and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: forecast and comparison. Decision window: the offered appointment windows. Minimum evidence: valid aggregate coverage for comparable service periods, a stable service definition and current calendar/process context. Method or baseline: same route, service mode and academic-cycle context. Use eligible comparable history and known events; report a range, confidence and recheck time. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not infer the visitor's needs or change appointments without the user. The result cannot guarantee low congestion. No disability/health inference, identification, visitor-data disclosure, accessibility/safety certification from telemetry or support-service override. Weak count coverage permits confirmed status or a broad range only, never a precise wait or staffing conclusion.

Why this is useful: Helps offer a visitor an appointment time with lower expected circulation and waiting pressure.

7. Visitors, accessibility, inclusion and staff well-being

Questions PS-067-PS-068

PS-067

USEFUL

L2 - personal break planning

R2 - integration-dependent

Professional-services staff question: Where can I take a short authorised break nearby with reasonable environmental conditions and low crowding?

Sensors and telemetry

Proposed sensing (minimum): Anonymous occupancy, numerical sound, temperature, CO2 and light in approved staff break or shared spaces. Coverage: Only spaces authorised for staff breaks. Quality: native event/status cadence plus one-minute aggregates; align clocks, verify room/service/asset mapping and report calibration or count error, uptime, gaps, drift, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts and non-content numerical/status evidence only; no identities, speech or movement histories.

Authoritative supporting data

Authoritative data: Current permitted-use and access rules, opening, accessibility, route, closures and the user's available break interval. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, observation and recommendation. Decision window: the intended break interval. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: current room and route status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not infer stress, workload or health, and do not treat a quiet work area as a break space unless permitted use confirms it. No disability/health inference, identification, visitor-data disclosure, accessibility/safety certification from telemetry or support-service override. If decisive authority, target-space evidence or time alignment is missing, omit that criterion and restrict or abstain.

Why this is useful: Supports a practical restorative break without inferring health, stress or workload.

PS-068

CORE

L2 - discomfort response

R2 - integration-dependent

Professional-services staff question: I am uncomfortable in my current workspace. What do the room measurements show, and which authorised alternative is suitable now?

Sensors and telemetry

Proposed sensing (minimum): In-room temperature, RH, CO2, light and numerical sound; equivalent coverage in eligible alternatives. Coverage: The occupied room and each candidate alternative. Quality: 10-30-second local samples aggregated to one minute; verify occupied-zone placement and exact room/served-zone mapping; report calibration, clock alignment, uptime, gaps, drift/relocation and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate occupancy and numerical environmental/acoustic indicators only; no speech, images or individual histories.

Authoritative supporting data

Authoritative data: Current workspace entitlement, access, booking, accessibility, opening, maintenance incidents and closures; user may state which condition matters most. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: observation, comparison and recommendation. Decision window: now and the intended remaining work period. Minimum evidence: valid target-room coverage for the full interval; diagnosis also needs aligned BMS/asset data and relevant occupancy, weather or event context. Method or baseline: same timestamp and comparable sensing coverage. Use eligible matched options with aligned windows; disclose residual non-comparability and uncertainty. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not make health claims or infer why the user is uncomfortable. If room-level evidence is missing, provide authorised options without environmental ranking. No disability/health inference, identification, visitor-data disclosure, accessibility/safety certification from telemetry or support-service override. Weak target-space coverage or sensor quality makes the environmental/diagnostic part not assessable; adjacent-room data cannot substitute.

Why this is useful: Helps decide whether to stay, relocate or report a room condition using valid evidence.

7. Visitors, accessibility, inclusion and staff well-being

Questions PS-069-PS-070

PS-069

USEFUL

L1 - inclusive service information lookup

R2 - integration-dependent

Professional-services staff question: A visitor needs interpretation or another approved support service. Which current official service or contact should I direct them to?

Sensors and telemetry

Proposed sensing (minimum): Only the minimum non-content telemetry explicitly required by the record. Coverage: the named room, service point, waiting boundary, route segment or mapped asset referenced in the question. Quality: owner-controlled classification/status is primary; any telemetry is corroborative and must map to the exact room/resource with source times, staleness and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no identities, content or individual activity; disclose only role-authorised status.

Authoritative supporting data

Authoritative data: current official support-service directory, approved referral route, opening/contact information, accessibility and language/communication-support information, visitor access and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative service-directory and availability lookup. Decision window: now or the requested appointment. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Show source owner/effective/retrieval time and do not extrapolate beyond the record. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not infer language, disability, immigration status or other personal characteristics; inspect the visitor's matter; expose personal data; determine eligibility; or promise an outcome. Missing current information requires referral to the official central service. No disability/health inference, identification, visitor-data disclosure, accessibility/safety certification from telemetry or support-service override. Missing/conflicting owner classification, permission or status requires deferral or not assessable.

Why this is useful: Ensures the visitor is directed to a current official support route rather than an improvised answer.

PS-070

USEFUL

L2 - well-being space recommendation

R2 - integration-dependent

Professional-services staff question: Which approved nearby space is suitable for a brief quiet pause before my next appointment?

Sensors and telemetry

Proposed sensing (minimum): Numerical sound, anonymous occupancy, temperature, CO2 and light in approved spaces. Coverage: Each candidate space and route. Quality: a cadence proportionate to the decision; verify exact room/service-point/asset mapping and report commissioning/calibration, clock alignment, uptime, gaps, drift, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no identities, content or individual activity.

Authoritative supporting data

Authoritative data: Current permitted use, staff access, accessibility, opening, route, appointment time supplied by the user and closures. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, observation and recommendation. Decision window: the available pause window. Minimum evidence: current authorised status and healthy telemetry from the correct target space or asset. Method or baseline: current room and route status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not infer health, stress or performance. The service cannot reclassify rooms or displace other users. No disability/health inference, identification, visitor-data disclosure, accessibility/safety certification from telemetry or support-service override. Missing, stale or conflicting authority/evidence requires clarification, a limited answer, referral or not assessable.

Why this is useful: Helps choose a short authorised pause option before the next service commitment.

8. Disruptions, irregular work, resilience and sustainability

Questions PS-071-PS-072

PS-071

CORE

L2 - late-work eligibility lookup

R2 - integration-dependent

Professional-services staff question: I may need to work in Abacws this evening. Are my access, workspace and lone-working requirements officially confirmed for that period?

Sensors and telemetry

Proposed sensing (minimum): Authorised room environment, power/network status and broad route state may provide context after eligibility is confirmed. Coverage: The approved workspace and access route. Quality: owner-controlled classification/status is primary; any telemetry is corroborative and must map to the exact room/resource with source times, staleness and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no identities, content or individual activity; disclose only role-authorised status.

Authoritative supporting data

Authoritative data: Current staff access entitlement, building opening, workspace allocation, lone-working procedure, check-in/escalation requirements, closures and emergency contacts. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: restricted authoritative eligibility and status lookup. Decision window: the interval stated in the question. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Show source owner/effective/retrieval time and do not extrapolate beyond the record. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

The service cannot approve lone working, infer that another person is present, monitor compliance or replace check-in and emergency procedures. Missing or conflicting policy/status requires deferral to the competent authority. No incident diagnosis, irregular-work approval, access grant, system control, contradiction of official instructions, restricted-data exposure or authority substitution. Missing/conflicting owner classification, permission or status requires deferral or not assessable.

Why this is useful: Prevents an evening-work plan from proceeding without current access and lone-working confirmation.

PS-072

CORE

L2 - weekend service readiness

R2 - integration-dependent

Professional-services staff question: I am supporting an approved weekend service or event. Which entrances, rooms and digital services are officially available for my role and time window?

Sensors and telemetry

Proposed sensing (minimum): Authorised entrance/door, lift, room power/network and environmental status; no access-log identities or content. Coverage: Only assets in the approved weekend plan. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: Official event/service approval, opening and access, assigned rooms, visitor rules, lone-working or staffing procedure, IT/power status, closures and emergency information. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup and readiness recommendation. Decision window: the weekend setup and service period. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: current owner-controlled status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not create access, approve the event or replace security, IT, facilities or safety procedures. No incident diagnosis, irregular-work approval, access grant, system control, contradiction of official instructions, restricted-data exposure or authority substitution. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Supports a weekend-service checklist based on official availability rather than weekday assumptions.

8. Disruptions, irregular work, resilience and sustainability

Questions PS-073-PS-074

PS-073

CORE

L2 - power disruption fallback

R2 - integration-dependent

Professional-services staff question: A power problem is affecting my work area. Which authorised service point is officially available for essential continuity work?

Sensors and telemetry

Proposed sensing (minimum): Authorised circuit/room power state, UPS status where relevant, network health and environmental conditions in eligible fallbacks. Coverage: The affected area and candidate authorised alternatives. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: Official power incident scope, workspace/service-point access, booking, opening, maintenance/closure notices and responsible contact. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, impact mapping and recommendation. Decision window: the incident period. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: official incident and current asset status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not operate electrical systems, declare an area safe or override closure instructions. Official incident communications take precedence. No incident diagnosis, irregular-work approval, access grant, system control, contradiction of official instructions, restricted-data exposure or authority substitution. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Helps maintain essential work at an authorised fallback while the responsible team manages the power incident.

PS-074

CORE

L2 - network disruption continuity

R2 - integration-dependent

Professional-services staff question: The administrative network service is unavailable. Which approved continuity option can I use now?

Sensors and telemetry

Proposed sensing (minimum): Authorised network service/endpoint health and room power status; no traffic, account, application or device inspection. Coverage: The affected network zone and approved alternative endpoints/workspaces. Quality: owner-managed status, heartbeat or synthetic probes for the exact mapped endpoint, circuit, room, network zone or AV asset; report source times, staleness, incidents, maintenance and provenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no traffic, payload, account, file, device-content or individual-activity inspection.

Authoritative supporting data

Authoritative data: Official IT incident and workaround guidance, workspace access, approved alternative systems or processes, maintenance and closure status. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup and recommendation. Decision window: the current incident period. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: official IT guidance. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not invent workarounds, inspect data, bypass security controls or declare restoration. IT and information-governance rules take precedence. No incident diagnosis, irregular-work approval, access grant, system control, contradiction of official instructions, restricted-data exposure or authority substitution. Missing/conflicting owner status permits confirmed facts, a manual check or authorised fallback only, never a performance promise.

Why this is useful: Directs the staff member to an approved continuity process without bypassing IT controls.

8. Disruptions, irregular work, resilience and sustainability

Questions PS-075-PS-076

PS-075

CORE

L2 - accessibility contingency

R2 - integration-dependent

Professional-services staff question: The lift on my usual route is unavailable. Is there a currently verified accessible alternative for me or my visitor?

Sensors and telemetry

Proposed sensing (minimum): Authorised lift, door and route state; anonymous congestion only. Coverage: The affected route and approved accessible alternatives. Quality: authoritative event status plus one-minute anonymous counts where congestion matters; verify current route mapping and report clock alignment, count uncertainty, uptime, gaps and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: anonymous aggregate counts only; no identities or individual movement histories.

Authoritative supporting data

Authoritative data: Official lift incident, accessible route graph, staff/visitor access, closures, assistance procedure and responsible contact. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup and route recommendation. Decision window: the disruption period. Minimum evidence: a current route/accessibility graph, access and closure state, lift/door status, and the user's stated route requirements. Method or baseline: current official accessibility and asset status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not infer an accessible route from geometry or telemetry alone. If no authoritative alternative exists, defer to the accessibility/service owner. No incident diagnosis, irregular-work approval, access grant, system control, contradiction of official instructions, restricted-data exposure or authority substitution. Missing route, accessibility, lift/door, closure or segment evidence permits confirmed route facts only or not assessable.

Why this is useful: Supports an accessible contingency decision during a verified lift outage.

PS-076

CORE

L1 - emergency deferral

R1 - practical

Professional-services staff question: An alarm or emergency message has occurred. What is the latest authoritative instruction for my location and role?

Sensors and telemetry

Authoritative telemetry (minimum): certified alarm outputs and current official emergency communications, with source owner, affected area, effective time and retrieval time. Experimental sensors, occupancy estimates and conversational inference cannot issue instructions, clearance or re-entry approval.

Authoritative supporting data

Authoritative data: certified alarm system, official University/security/emergency communications, current incident procedure and competent-authority instruction. These sources take absolute precedence; report owner, affected area, effective/retrieved times, permission and conflicts.

Analysis required

Operation: authoritative-source verification and faithful display. Decision window: immediate. Minimum evidence: a current certified alarm or official instruction for the affected area and role. Return only the latest verified instruction and source time; if authority or freshness is unverified, direct the user to official channels and abstain. Safe failure: if the source, affected area, role or freshness is unverified, provide no inferred instruction and direct the user to official channels.

Answer boundary

Do not delay compliance, reinterpret or downgrade an alarm, invent a cause, issue independent emergency instructions or declare re-entry safe. If source, affected area, role or freshness cannot be verified, give no inferred advice and direct the user to the official channel.

Why this is useful: Delivers the latest authoritative instruction without unsafe AI interpretation.

8. Disruptions, irregular work, resilience and sustainability

Questions PS-077-PS-078

PS-077

CORE

L2 - closure continuity recommendation

R2 - integration-dependent

Professional-services staff question: A leak or maintenance closure has affected our service area. Which approved alternative can support the minimum service we are authorised to provide?

Sensors and telemetry

Proposed sensing (minimum): Authorised leak/closure status, door/lift state, power/network and environment in approved alternatives. Coverage: The affected area and candidate continuity locations. Quality: owner-controlled classification/status is primary; any telemetry is corroborative and must map to the exact room/resource with source times, staleness and maintenance. Capability status: proposed until exact deployment, mapping, commissioning and permission are verified for the decision window; corridor or adjacent-room readings cannot replace target-space evidence. Privacy limit: no identities, content or individual activity; disclose only role-authorised status.

Authoritative supporting data

Authoritative data: Official closure and maintenance notice, owner-approved alternative service point, access, accessibility, capacity, privacy, IT/power and visitor rules. Source precedence: current source-owner records for the requested interval override telemetry, inference and historic floor-plan labels. Expose source owner, scope, effective/observed/retrieved times, permission, staleness and conflicts.

Analysis required

Operation: authoritative lookup, impact mapping and recommendation. Decision window: the closure interval. Minimum evidence: current owner status for the exact room, device, service or asset; telemetry may corroborate but cannot grant permission. Method or baseline: current official incident and room status. Apply permission, privacy, accessibility, safety and service constraints first; disclose ranking criteria, unknowns and fallback. Safe failure: separate confirmed facts from analysis and report source times, coverage and uncertainty; if minimum evidence is missing, stale, conflicting or unauthorised, clarify, limit, defer or return not assessable.

Answer boundary

Do not infer that a leak is resolved from sensor silence, enter closed areas or relocate services without owner approval. No incident diagnosis, irregular-work approval, access grant, system control, contradiction of official instructions, restricted-data exposure or authority substitution. Missing/conflicting owner classification, permission or status requires deferral or not assessable.

Why this is useful: Helps maintain only the authorised minimum service from a verified alternative location.

PS-078

USEFUL

L3 - sustainability recommendation

R3 - research-grade or restricted

Professional-services staff question: Several authorised workspaces meet my service, privacy and accessibility needs. Which is likely to have the lower energy impact for this work period?

Sensors and telemetry

Proposed sensing (minimum): commissioned room/zone electricity or HVAC and lighting power/energy, anonymous aggregate occupancy and room environmental conditions for each eligible workspace. Coverage: each candidate room with verified served-zone and meter/end-use mapping; whole-building totals are insufficient. Quality: one-minute power and 15-minute energy aligned with occupancy, weather and operating state; expose mapping, commissioning, clock alignment, gaps, drift and maintenance. Capability status: proposed until exact deployment, mapping and permission are verified for the decision window. Privacy limit: aggregate room/zone data only.

Authoritative supporting data

Authoritative data: current workspace entitlement or booking, privacy, accessibility and service requirements; verified room-to-meter/BMS mapping, operating schedule, weather and the approved sustainability method. Source precedence: current eligibility and owner-controlled records valid for the decision window override telemetry, inference and historic floor-plan labels. Expose source owner, scope, times, permission, staleness and conflicts.

Analysis required

Operation: constrained comparison and recommendation. Decision window: the requested work period. Minimum evidence: at least two already-authorised options, valid room-to-meter/BMS mapping and comparable occupancy, weather and operating conditions. Compare aligned windows, disclose residual non-comparability and report a bounded difference rather than claimed savings. Safe failure: if mapping or comparability is weak, provide no energy ranking.

Answer boundary

Energy cannot override accessibility, confidentiality, service quality, ownership or safety. Do not identify occupants, operate controls or present an estimated marginal difference as measured savings. Missing room-to-meter/BMS mapping or non-comparable operating context makes the energy part not assessable.

Why this is useful: Supports a lower-impact choice only after service, privacy, accessibility and suitability constraints are satisfied.

8. Disruptions, irregular work, resilience and sustainability

Questions PS-079-PS-080

PS-079

USEFUL

L2 - low-occupancy sustainability choice

R2 - integration-dependent

Professional-services staff question: I am working outside normal hours. Which already-authorised workspace meets my needs without conditioning a larger area than necessary?

Sensors and telemetry

Proposed sensing (minimum): verified active-zone HVAC and lighting state, room/zone power or energy, and room environmental conditions for already-authorised candidate workspaces. Coverage: each room and its mapped served zone; whole-building totals and adjacent-room readings are insufficient. Quality: one-minute power and 15-minute energy aligned with operating state; expose mapping, commissioning, gaps, drift and maintenance. Capability status: proposed until exact deployment, mapping and permission are verified for the decision window. Privacy limit: aggregate data only.

Authoritative supporting data

Authoritative data: current after-hours access, workspace allocation and opening, lone-working rules, privacy and accessibility needs, room/zone mapping and BMS schedule. Source precedence: these owner-controlled records determine eligibility and override telemetry, inference and historic floor-plan labels. Expose source owner, scope, times, permission, staleness and conflicts.

Analysis required

Operation: authoritative eligibility lookup and bounded sustainability recommendation. Decision window: the stated after-hours period. Minimum evidence: at least two already-authorised options, valid room-to-meter/BMS mapping and comparable operating conditions. Apply permission, accessibility, privacy and safety constraints before energy criteria; report assumptions and uncertainty. Safe failure: without authority or adequate mapping, provide no energy recommendation.

Answer boundary

The service cannot approve after-hours work, alter HVAC or lighting, infer that a smaller room will be conditioned, or trade away privacy, accessibility or safety. Missing authority or metering requires deferral or an energy result of not assessable.

Why this is useful: Helps choose a smaller authorised operational footprint without operating building controls.

PS-080

CORE

L3 - evidence transparency

R2 - integration-dependent

Professional-services staff question: For this answer, what evidence was used, what is missing, and which parts are observation, authorised lookup, calculation, estimate, forecast, diagnosis or recommendation?

Sensors and telemetry

No new sensing. Expose permitted provenance for every source used: mapping, units, cadence/aggregation, observed/retrieved times, commissioning/calibration, uptime, gaps, drift/relocation, maintenance, permissions, method version and conflicts.

Authoritative supporting data

Authoritative data: the permitted source register for the answer, including owner-controlled room/access/service records, sensor/asset mappings, permissions, method/configuration version and conflict resolution. Report owner, scope, times, staleness and conflicts; summarise restricted details.

Analysis required

Operation: evidence-package summary. Decision window: the answer being explained. Minimum evidence: permitted sources, mappings, timestamps, quality flags, permissions, method version and conflicts. Label each statement as observation, authorised lookup, calculation, estimate, forecast, comparison, diagnosis or recommendation; show coverage, assumptions, uncertainty and missing evidence. Unsupported parts are not assessable. Safe failure: if provenance, permission or quality evidence is missing, mark the affected statement not assessable.

Answer boundary

Do not hide weak evidence behind fluent language or expose restricted source details. No incident diagnosis, irregular-work approval, access grant, system control, contradiction of official instructions, restricted-data exposure or authority substitution. Protect restricted source details; show weak or missing provenance and mark unsupported parts not assessable.

Why this is useful: Lets the staff member judge whether the answer is strong enough for the practical decision.

4. Catalogue summary and implementation requirements

The catalogue combines everyday professional-services questions with current service, room, privacy, access, accessibility, equipment, IT and route integrations, plus bounded comparison, forecast, diagnosis and safety-sensitive cases. Readiness identifies the spatial coverage, timing, commissioning, quality, authority, permission and failure conditions required for a responsible answer.

Questions	80	Eight professional-services-staff-centred sections containing ten distinct questions each.
R1 practical	2	Can be supported with proposed core sensing and basic current spatial, service or provenance feeds.
R2 integration-dependent	67	Require service calendar, appointment, room, booking, access, accessibility, IT, BMS, maintenance, visitor, lone-working or forecasting integration.
R3 research or restricted	11	Require dense coverage, validated comparison/diagnosis, controlled operational data, or stronger privacy and safety controls.

Recurring system capabilities

1	Service-day and demand planning Resolve fixed duties, appointments, focused work, breaks, handovers, demand peaks and personal work sequencing without setting staffing or service policy.	2	Room, privacy and permission reasoning Use current room purpose, allocation, bookability, staff access, privacy classification, accessibility, routes, lifts, opening and closures.
3	Environmental and service evidence Combine correctly located room or waiting-zone sensing with anonymous queues, BMS, power, network, shared-resource and authorised service status.	4	Forecast, comparison and diagnosis Forecast aggregate demand and conditions, build matched baselines, compare eligible options, reconstruct service events and avoid unsupported causal claims.
5	Evidence quality and provenance Check room/asset mapping, aggregation, clocks, commissioning/calibration, uptime, gaps, drift, source agreement, maintenance state and permissions.	6	Privacy, accessibility, safety and abstention Minimise personal and work-content data, refuse unauthorised permission or safety claims, preserve inclusive alternatives and return not assessable when evidence is inadequate.

QUESTION RECORD STRUCTURE

Each entry can become a system test containing the natural utterance and paraphrases, required entities, minimum room, service-point and route evidence, source-precedence rule, quality threshold, expected operation, permission rule, answerability class, acceptable clarification, uncertainty statement, safe failure, expected answer characteristics and prohibited overclaims.

5. Evidence, permissions and answerability rules

These rules apply across all 80 records and define when the building may answer, qualify, ask for clarification, defer to an authorised service or return not assessable.

Building and room status

The May 2021 plan is a historical spatial reference. Current room purpose, ownership, allocation, capacity, bookability, staff access, privacy classification, equipment, accessible features, entrances, lifts, services and closures require an authoritative current source.

Spatial coverage

A room- or service-point-level answer requires correctly located sensing in the named space or a validated served zone. Corridor and adjacent-room data may be labelled context but cannot be silently substituted.

Time window and operation type

Every answer resolves the requested interval and labels its operation as observation, authorised lookup, calculation, estimate, forecast, comparison, diagnosis or recommendation. Preserve observed-at and retrieved-at times.

Calibration and data quality

Use stated sampling/aggregation, synchronised clocks, commissioning/calibration, uptime, gap and drift flags, maintenance state and source agreement. Failed, stale, relocated or unverified points cannot support a precise claim.

Content and personal-data minimisation

Do not inspect casework, records, tickets, forms, emails, documents, meetings, calls, speech, screens, network traffic or device content. Do not expose student, applicant, visitor or staff personal data.

Occupancy, queues and sound

Use anonymous aggregate counts and numerical LAeq or percentile statistics only where proportionate. Do not identify people, retain speech, infer conversation or individual movement history, or estimate staff workload, performance or productivity.

Environmental interpretation

Direct-reading NDIR CO2 is a ventilation indicator, not complete air quality. Temperature, RH, PM, indicative TVOC, airflow, radiant conditions, light, outdoor weather and activity may be relevant subject to coverage and quality.

Service and room authority

Environmental or occupancy telemetry cannot authorise room use, certify confidentiality/accessibility, prove a service point is staffed or available, set service policy, or grant bookings/access. Current owner-controlled systems take precedence.

Operational services and permissions

Bookings, access, visitors, lifts, network, power, shared equipment, maintenance and closures come from authorised feeds. The service cannot operate systems or override timetabling, IT, facilities, security, accessibility or safety authorities.

Emergency and high-consequence answers

Certified alarms and official communications take precedence. Safety, health, lone-working, accessibility and compliance questions require competent authority; missing or conflicting critical evidence requires a limited or not-assessable answer.

FINAL ANSWERABILITY RULE

Answer only when the required variables, current room or service-point coverage, requested interval, source authority, quality threshold, permissions, privacy, accessibility and safety constraints are adequate. Otherwise ask for clarification, omit unsupported criteria, return confirmed facts with explicit uncertainty, restrict disclosure, defer to the responsible service, or mark the analytical part not assessable.