

Security officers

80 practical questions for evidence-bounded staffing, access, incident, event, key, out-of-hours, emergency and service decisions.

80

QUESTIONS

complete, traceable and bounded

8

CATEGORIES

complete, traceable and bounded

6

FIELDS PER RECORD

complete, traceable and bounded

OPERATING PRINCIPLE

Current authenticated owner records and competent professionals lead. Verified telemetry may support a bounded answer; it never creates authority. When mapping, time, permission, health or minimum evidence is insufficient, the result is **not assessable** - not a guess.

HISTORICAL REFERENCE

The May 2021 floor plan is historical spatial reference only. It cannot establish current room use, access, services, hazards, occupancy, emergency arrangements, routes or closures.

Purpose and operating boundary

This catalogue frames decisions Security officers may ask of a proposed Talking Abacws service. It states what evidence can support each answer, who owns the truth and when the service must stop.

DECISION SUPPORT

Each question ends in a concrete check, escalation, coordination, handover or record action. The service presents evidence and uncertainty; authorised officers and owners decide.

PROPOSED CAPABILITY

All sensors, telemetry, integrations and derived outputs remain proposals until deployment, exact mapping, commissioning, purpose permission and current health are independently confirmed.

AUTHORITATIVE PRECEDENCE

Security, Access Control, Facilities, IT, Events, Safety, Emergency and information owners determine current status. Their effective instructions override telemetry and historical material.

HISTORICAL PLAN BOUNDARY

The May 2021 floor plan supports historical orientation only. It cannot establish present room use, access class, services, hazards, occupancy, emergency arrangements, routes or closures.

PRIVACY BY DESIGN

Use anonymous counts and equipment or door states only where necessary. No facial recognition, biometrics, device tracking, person-path reconstruction, or camera and microphone content analysis.

OPERATIONAL NON-AUTHORITY

The service does not identify suspects, assess intent, grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue commands, promise outcomes or certify safety or security.

DEFAULT SAFE RESULT

Not assessable from currently verified evidence. Show the missing or conflicting item, its owner, latest valid time, permission or health limitation, and the current procedure or competent authority to follow.

How to read each question record

Read the authoritative owner and precedence first. Use verified telemetry only as bounded context. Every answer must carry scope, time, permission, provenance, uncertainty and a safe-failure state.

1

STAKEHOLDER QUESTION

A natural operational question tied to a real decision, check, escalation or handover task.

2

SENSORS AND TELEMETRY

Proposed modality and location, spatial and temporal coverage, sampling or aggregation, calibration or functional test, clocks, uptime, gaps, drift, provenance and limits.

3

AUTHORITATIVE SUPPORTING DATA

Current owners, precedence, effective, observed and retrieved times, permissions, provenance, staleness and explicit conflict routing.

4

ANALYSIS REQUIRED

Operation type, decision interval, minimum evidence, method, uncertainty and the safe result when evidence fails.

5

ANSWER BOUNDARY

What the service must not infer, disclose, promise, certify, authorise, control or turn into an operational instruction.

6

WHY THIS IS USEFUL

The concrete choice, check, escalation, coordination step or record action that the officer can take.

ANSWER STATUS

Confirmed = current owner record. Observed = verified source state. Calculated = transparent operation on adequate evidence. Estimated or forecast = bounded uncertainty. Restricted = permission-limited. Conflicting = sources disagree. Not assessable = evidence, mapping, time, permission or health is insufficient.

1

staffing, patrols and operational briefings

SO-001 to SO-010 | ten operational questions

SO-001 STAFFING, PATROLS AND OPERATIONAL BRIEFINGS

POST + ROSTER

COMPARISON

STAKEHOLDER QUESTION

Which posts required by the current operating plan still lack an authorised, role-qualified assignment?

SENSORS AND TELEMETRY

Proposed evidence: read-only ready-state check-ins at fixed named posts, radio-dock availability by equipment pool and anonymous beam counts at designated public entrances; no officer location history. Coverage: the posts and entrance points explicitly mapped for the current shift. Sampling and aggregation: event timestamps plus five-minute post and entrance summaries; retain no person path. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (post-console functional test, radio-dock self-test and manual count check for each entrance sensor), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a missing check-in does not prove an unattended post, and entrance counts do not determine staffing need. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: comparison. Decision interval: shift start and every material staffing change. Minimum evidence: a current post requirement list, effective roster, role prerequisites, authorised changes and one current readiness indicator for each named post. Method: reconcile required role-level cover with owner-confirmed assignments; label covered, gap, restricted and unverified states without ranking people. Uncertainty: late recording, sickness notification and temporary relief can make the picture incomplete. Safe failure: show only confirmed requirements and known gaps, mark the rest unverified and route allocation to the Duty Manager.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security Duty Manager owns the duty roster and post plan; HR or training owners hold competence and absence records; Event and Facilities owners hold approved demand or closure notices. Precedence: the latest authenticated Duty Manager instruction effective for this shift overrides roster snapshots, console states and demand estimates. Time discipline: display effective, observed and retrieved times; expire assignments at shift end and treat verbal redeployments as unconfirmed until recorded. Permissions and provenance: Limit roster and competence fields to authorised Security supervisors; expose role-level status to other users and retain the source record ID and retrieval path; retain owner role, record or case ID, version and extraction path. Conflict handling: show roster and telemetry differences separately and refer them to the Duty Manager and the owner of the disputed record; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not name absent staff to unauthorised users, infer attendance from counts or console silence, rank individuals, or allocate or redeploy personnel. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets the Duty Manager seek relief, rebalance authorised cover or formally record an accepted gap before public activity begins.

SO-002 STAFFING, PATROLS AND OPERATIONAL BRIEFINGS

HANDOVER + STATES

COMPARISON

STAKEHOLDER QUESTION

What owner-confirmed changes since the last signed handover alter this shift's posts, patrols or public interface?

SENSORS AND TELEMETRY

Proposed evidence: read-only exception states from mapped doors, access controllers, alarms, lifts and fixed communication points, with anonymous zone counts only where commissioned. Coverage: the patrol zones, entrances and service points named in the previous handover and current operating plan. Sampling and aggregation: event-driven changes and five-minute summaries from the signed handover time to the present. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (asset-state functional test, source heartbeat check and clock comparison across the contributing systems), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: sensor silence may indicate communications failure rather than normal conditions, and manual instructions may appear late. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: comparison and change detection. Decision interval: from the last signed handover to the current briefing. Minimum evidence: both handover versions, effective times for instructions, active incident or closure states and healthy evidence for every cited exception. Method: compare owner records first, then attach telemetry as bounded context; group confirmed changes by location, dependency and stated operational consequence. Uncertainty: not every verbal or paper instruction is captured immediately, and asynchronous feeds may not describe one simultaneous state. Safe failure: list confirmed changes and unresolved conflicts only; do not propose a patrol order where current instructions are absent.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security handover owner, active incident owner, Access Control owner, Facilities service owner and Event Manager. Precedence: current Duty Manager or incident-command instructions override earlier handover text, owner-issued closures and service states override telemetry. Time discipline: display effective, observed and retrieved times; use the last signed handover as the baseline and reject items whose effective period has ended. Permissions and provenance: Limit roster and competence fields to authorised Security supervisors; expose role-level status to other users and retain the source record ID and retrieval path; retain owner role, record or case ID, version and extraction path. Conflict handling: present each conflicting instruction or state with its owner and route it to the Duty Manager plus the relevant source owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not infer threat, suspicious behaviour or officer effectiveness from a changed state, and do not convert a difference into an operational direction. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Focuses the briefing on new closures, faults, incidents and event demands that the incoming shift must understand.

1

staffing, patrols and operational briefings

SO-001 to SO-010 | ten operational questions

SO-003

STAFFING, PATROLS AND OPERATIONAL BRIEFINGS

ROUTE STATES

CALCULATION

STAKEHOLDER QUESTION

For the next patrol window, which approved circuit is evidenced as feasible, and which segments still need a physical check?

SENSORS AND TELEMETRY

Proposed evidence: mapped door contacts, lift service states and fixed anonymous count sensors on eligible public-route segments; no continuous officer or public trajectory. Coverage: only route segments in the current Security-approved circuit set and current authoritative route map. Sampling and aggregation: door and lift events with a latest-state age of five minutes; one-minute counts aggregated to five-minute route bands. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (door open-close sequence test, lift feed end-to-end test and manual count comparison at each covered segment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a door-open state does not prove authorised passage, and unmonitored obstructions or temporary controls remain invisible. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: calculation. Decision interval: the next planned patrol circuit. Minimum evidence: a current eligible route graph, effective access restrictions, confirmed closures, lift state where relevant and sufficiently fresh evidence for every proposed segment. Method: remove officially unavailable or unauthorised segments, calculate owner-approved feasible options, and mark every uncovered segment for manual confirmation. Uncertainty: unmapped doors, short-lived crowd changes and delayed lift states can invalidate an option. Safe failure: return no route option when any mandatory segment lacks current authority or evidence; show the exact check and owner needed.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security patrol-route owner, Access Control Manager, Facilities closure and lift owners, Event Manager and accessibility-route owner. Precedence: approved route eligibility and current official closures lead; telemetry can describe a segment but cannot create permission. Time discipline: display effective, observed and retrieved times; use only route versions and closures effective for the patrol window; the May 2021 floor plan is historical reference and cannot establish a current route. Permissions and provenance: Limit roster and competence fields to authorised Security supervisors; expose role-level status to other users and retain the source record ID and retrieval path; retain owner role, record or case ID, version and extraction path. Conflict handling: show the conflicting segment states and refer them to the route owner and the owner of the closure, access or lift record; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not track an officer, expose patrol patterns to unauthorised users, unlock a door or route anyone through a restricted or officially closed zone. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Allows the shift lead to select an approved circuit or arrange a targeted physical check before the patrol starts.

SO-004

STAFFING, PATROLS AND OPERATIONAL BRIEFINGS

SHIFT CHECKPOINTS

LOOKUP

STAKEHOLDER QUESTION

Which scheduled patrol checkpoints are current, due, overdue or unverified for this shift?

SENSORS AND TELEMETRY

Proposed evidence: fixed checkpoint terminals or sealed buttons that record a shift-level confirmation, plus the signed patrol log; no device identifier, continuous location or individual path. Coverage: only checkpoints named in the current patrol schedule and exactly mapped to their fixed location. Sampling and aggregation: one event per required checkpoint with minute-level timestamps; show gaps rather than interpolating between checkpoints. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (terminal/button functional test, seal state, clock comparison and expected event-delivery test), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a recorded event does not prove the whole circuit was completed, while a missing event may reflect a failed terminal or delayed entry. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup and rule comparison. Decision interval: each checkpoint due window and the current handover point. Minimum evidence: the effective patrol schedule, accepted confirmation method, current shift identifier and health evidence for every cited terminal. Method: compare each required checkpoint with an accepted shift-level confirmation; label current, due, overdue, terminal-unhealthy or unverified. Uncertainty: late manual entries and clock offsets can change status near a deadline. Safe failure: do not mark overdue from an unhealthy checkpoint alone; show the missing confirmation route and require the Duty Manager to decide follow-up.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Duty Manager owns the patrol schedule; the signed shift log owner holds accepted confirmations; Facilities or IT own checkpoint faults. Precedence: the current schedule and Duty Manager exceptions determine what is due; a terminal event is supporting evidence only. Time discipline: display effective, observed and retrieved times; evaluate against the checkpoint time window effective for this shift and expire status when the shift closes. Permissions and provenance: Limit roster and competence fields to authorised Security supervisors; expose role-level status to other users and retain the source record ID and retrieval path; retain owner role, record or case ID, version and extraction path. Conflict handling: separate schedule, manual log and terminal differences and refer them to the Duty Manager and checkpoint service owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not reconstruct an individual officer's movement, infer diligence or misconduct, or treat a checkpoint event as proof of conditions between checkpoints. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Supports a targeted checkpoint follow-up and an accurate shift handover without creating staff tracking.

1

staffing, patrols and operational briefings

SO-001 to SO-010 | ten operational questions

SO-005

STAFFING, PATROLS AND OPERATIONAL BRIEFINGS

EXCEPTIONS

RECOMMENDATION

STAKEHOLDER QUESTION

Which unresolved access, damage or service exceptions require an explicit call-out in this shift briefing?

SENSORS AND TELEMETRY

Proposed evidence: read-only door, lock, controller, alarm, lift, lighting and fixed communication-point exception states for assets already named in owner records. Coverage: the building assets and public or restricted zones within this shift's authorised operational scope. Sampling and aggregation: event-driven exceptions with five-minute status summaries and no personal event detail. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (modality-specific functional test, controller heartbeat, state-transition check and cross-system clock comparison), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: telemetry can show an exception but cannot establish severity, cause, ownership or the adequacy of a temporary control. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: recommendation limited to briefing inclusion. Decision interval: the current pre-shift briefing. Minimum evidence: a current owner-classified exception, affected asset or zone, owner, effective time, stated consequence, temporary control and next update time. Method: apply the approved briefing criteria, separate confirmed facts from observations, and recommend inclusion or omission with the rule used. Uncertainty: open cases may be reclassified and telemetry may recover before the owner record is updated. Safe failure: include the item as unresolved with its owner and recheck time, but do not invent severity or response advice.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security incident and handover owners, Access Control Manager, Facilities service owner, IT service owner and Event Manager. Precedence: owner-classified incidents, closures, temporary controls and service-impact statements lead; raw faults and counts cannot set briefing priority. Time discipline: display effective, observed and retrieved times; include only open or recently changed items effective for the shift and mark any source not refreshed within its owner-defined interval. Permissions and provenance: Limit roster and competence fields to authorised Security supervisors; expose role-level status to other users and retain the source record ID and retrieval path; retain owner role, record or case ID, version and extraction path. Conflict handling: show competing classifications and route them to the Duty Manager and responsible service owner before assigning a priority; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not diagnose cause, set operational priority outside the approved criteria, disclose restricted incident detail or direct a response. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Ensures the briefing carries the few unresolved conditions that genuinely affect posts, patrols, access or public contact.

SO-006

STAFFING, PATROLS AND OPERATIONAL BRIEFINGS

ANONYMOUS COUNTS

FORECAST

STAKEHOLDER QUESTION

When is public-facing demand most likely to peak during this shift, and how wide is the forecast range?

SENSORS AND TELEMETRY

Proposed evidence: privacy-preserving dual-beam or non-imaging time-of-flight counters at designated public entrances and foyer thresholds, linked only to zone totals. Coverage: the commissioned public entrances and waiting areas relevant to the current opening and event plan. Sampling and aggregation: one-second sensor samples converted to one-minute counts and fifteen-minute demand bands; retain aggregates, not raw detections. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (manual count comparison by direction, occlusion check, counter reset record and cross-sensor clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: groups, tailgating, counter occlusion and changed entrance use can bias totals, and demand does not equal risk. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: forecast. Decision interval: rolling fifteen-minute windows across the current shift. Minimum evidence: current schedules, at least several comparable complete periods, healthy counters covering the relevant entrances and an owner-approved forecast horizon. Method: fit a transparent time-band forecast using comparable events or opening patterns; report median, lower and upper ranges and the coverage basis. Uncertainty: weather, late programme changes, counter bias and small samples can widen the range. Safe failure: return no peak forecast when comparability or coverage is inadequate; show scheduled demand times and the missing evidence instead.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security service owner, Event Manager, public-service owner, timetabling owner and opening-hours owner. Precedence: current approved schedules and service plans define expected activity; anonymous counts provide context but cannot alter opening or staffing authority. Time discipline: display effective, observed and retrieved times; use schedule versions effective for the shift and historical count periods with documented completeness and comparable operating conditions. Permissions and provenance: Limit roster and competence fields to authorised Security supervisors; expose role-level status to other users and retain the source record ID and retrieval path; retain owner role, record or case ID, version and extraction path. Conflict handling: show schedule-count conflicts and refer them to the Duty Manager plus the event or service owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not infer who is present, assess behaviour or intent, or treat a demand forecast as an instruction to change staffing or access. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Helps the Duty Manager time public-facing availability, supervisor attention and liaison with event or service owners.

1

staffing, patrols and operational briefings

SO-001 to SO-010 | ten operational questions

SO-007 STAFFING, PATROLS AND OPERATIONAL BRIEFINGS

ROLE RECORDS

RULE COMPARISON

STAKEHOLDER QUESTION

Do current post assignments satisfy the authorised role, induction and briefing prerequisites for this shift?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required; optional fixed-post console readiness may confirm equipment availability but cannot establish competence or attendance. Coverage: the role requirements and assigned posts in the current authorised shift plan. Sampling and aggregation: record lookups at shift preparation and after an assignment change; no continuous personnel monitoring. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (source availability test, identity-to-role mapping check inside the owner system and timestamp alignment between roster and competence records), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: training records can lag completed activity, and a console state cannot prove a person is present or briefed. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: rule comparison. Decision interval: before shift release and after any reassignment. Minimum evidence: the current post requirement, authorised assignment, each required prerequisite, its effective dates and any valid exception. Method: compare role-level requirements with owner-confirmed status and label satisfied, expired, missing, restricted or conflicting without exposing unnecessary personal detail. Uncertainty: recent training, temporary authorisation or suspension may not yet be synchronised. Safe failure: mark the assignment unverified and require owner confirmation; never infer competence from prior shifts or equipment use.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Duty Manager owns assignments; HR, training and Security authorisation owners hold current role, induction and briefing prerequisites. Precedence: owner-confirmed competence and authorisation records lead; the Duty Manager alone decides a lawful assignment or substitution. Time discipline: display effective, observed and retrieved times; use records effective for the full shift or the stated post interval and display expiry or suspension times. Permissions and provenance: Limit roster and competence fields to authorised Security supervisors; expose role-level status to other users and retain the source record ID and retrieval path; retain owner role, record or case ID, version and extraction path. Conflict handling: do not resolve mismatches automatically; route them to the Duty Manager and the owner of the prerequisite record; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not make an employment decision, disclose health or personnel details, rank staff, or automatically authorise, reject or substitute an assignment. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives the Duty Manager a precise prerequisite gap to resolve before a post is released.

SO-008 STAFFING, PATROLS AND OPERATIONAL BRIEFINGS

EQUIPMENT HEALTH

DIAGNOSIS

STAKEHOLDER QUESTION

Which radios, duress devices and fixed communication points have enough current evidence to be issued or relied on for this shift?

SENSORS AND TELEMETRY

Proposed evidence: radio-dock self-tests, battery-charge bands, network registration status, duress-device functional-test records and fixed call-point heartbeats; no live audio, GPS or user location. Coverage: the numbered equipment pools and fixed communication points assigned to Abacws. Sampling and aggregation: device events at docking or test time, one-minute health summaries during the shift and owner-defined test intervals. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (known-signal test, battery measurement tolerance, call-point activation test without message content and clock alignment to the asset register), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a passed self-test does not prove coverage in every location or performance under emergency load. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: diagnosis. Decision interval: equipment issue before and during the current shift. Minimum evidence: asset identity, current custody state, required test, latest valid test result, battery or power state, network status and any open fault. Method: apply owner thresholds to classify ready, degraded, unavailable or unverified; distinguish device, dock, network and mapping evidence. Uncertainty: battery telemetry, intermittent coverage and delayed fault closure can misstate readiness. Safe failure: do not label equipment ready without all required tests; show the failed or missing check and route issue or substitution to the custodian.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security equipment custodian, radio or communications service owner, IT network owner and Duty Manager. Precedence: the custodian's issue status and approved test criteria lead; telemetry can indicate a fault but cannot authorise issue or guarantee service. Time discipline: display effective, observed and retrieved times; show the latest completed functional test, observed health time and retrieval time; expire readiness at the owner-defined test age or after a reported fault. Permissions and provenance: Limit roster and competence fields to authorised Security supervisors; expose role-level status to other users and retain the source record ID and retrieval path; retain owner role, record or case ID, version and extraction path. Conflict handling: present device and network disagreements separately and refer them to the equipment custodian and responsible service owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not listen to or analyse communications, track users, guarantee coverage or emergency performance, issue equipment, or direct a response. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets the shift lead issue tested equipment, reserve a spare or log a specific fault before deployment.

1

staffing, patrols and operational briefings

SO-001 to SO-010 | ten operational questions

SO-009

STAFFING, PATROLS AND OPERATIONAL BRIEFINGS

DATA READINESS

DIAGNOSIS

STAKEHOLDER QUESTION

Which required briefing inputs are missing, stale, conflicting, restricted or supported by unhealthy integrations?

SENSORS AND TELEMETRY

Proposed evidence: integration heartbeats, source-version metadata, mapping status, permission decisions and freshness indicators; no additional operational result. Coverage: every source named by the current Security briefing template. Sampling and aggregation: check at briefing assembly and when any source changes; aggregate only source-level health and coverage status. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (connector retrieval test, schema and mapping validation, clock-offset check and source-record lineage test), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a healthy connector does not prove its source record is complete, current or correct. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: diagnosis. Decision interval: the current briefing assembly window. Minimum evidence: the briefing source checklist, source owner, operation result, effective time, latest retrieval, mapping state, connector health and field completeness. Method: test each input against currency, permission, mapping and health gates; list the decisions blocked by every failed gate. Uncertainty: some manual sources cannot expose machine-readable completeness and permission can vary by recipient. Safe failure: publish no unsupported status; return a concise missing-input list with owner, latest valid time and required check.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security briefing owner and the owners of roster, incident, access, facilities, event, safety and communications sources. Precedence: each source owner controls meaning and currency; the briefing owner controls required inputs, while telemetry health cannot replace a missing owner record. Time discipline: display effective, observed and retrieved times; apply each source's effective period and owner-defined freshness limit at the briefing time. Permissions and provenance: Limit roster and competence fields to authorised Security supervisors; expose role-level status to other users and retain the source record ID and retrieval path; retain owner role, record or case ID, version and extraction path. Conflict handling: show each disagreement or denied field with its owner and refer it to the briefing owner plus the relevant source owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not fill gaps from historical plans, adjacent zones or prior shifts, and do not widen permissions to complete the briefing. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets the briefing lead qualify, delay or escalate only the portions that lack dependable evidence.

SO-010

STAFFING, PATROLS AND OPERATIONAL BRIEFINGS

VERIFIED SOURCES

SYNTHESIS

STAKEHOLDER QUESTION

What concise shift brief can be assembled now, with an evidence label, owner and recheck time for every material item?

SENSORS AND TELEMETRY

Proposed evidence: only owner records and proposed telemetry that have passed the applicable permission, mapping, time, health and sufficiency gates; no new sensing is introduced. Coverage: the posts, routes, incidents, events and equipment within the incoming shift's authorised scope. Sampling and aggregation: compile at briefing time and refresh on a material owner update; retain source facts and bounded aggregates, not person histories. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (end-to-end source retrieval test, mapping verification, clock alignment and lineage check for each included statement), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a concise brief can omit nuance unless conflicts, assumptions and blind areas are kept visible. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: structured synthesis. Decision interval: the current shift briefing and any material in-shift refresh. Minimum evidence: all mandatory briefing inputs, a valid authority chain, permission, exact scope, current health and the minimum evidence required by each included question. Method: assemble short statements grouped by decision, label confirmed, observed, calculated, estimated, restricted, conflicting or not assessable, and include owner plus recheck time. Uncertainty: late changes and unequal source update rates can make the brief age unevenly. Safe failure: release only the verified subset and attach a visible unresolved-items block; never generate an instruction for a missing or conflicting item.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Duty Manager owns the released brief; each cited Security, Access Control, Facilities, IT, Event, Safety or Emergency owner retains authority for its source fact. Precedence: current authenticated instructions and competent emergency authority override schedules, telemetry and derived summaries. Time discipline: display effective, observed and retrieved times; show every source effective time, observation time where applicable, retrieval time and the brief validity or recheck time. Permissions and provenance: Limit roster and competence fields to authorised Security supervisors; expose role-level status to other users and retain the source record ID and retrieval path; retain owner role, record or case ID, version and extraction path. Conflict handling: do not collapse conflicts; name both positions, their owners and the resolution route before release; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not alter owner classifications, conceal uncertainty, disclose restricted details, set priorities outside current procedures or turn the brief into automated tasking. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Provides a usable, traceable briefing that officers can act on while knowing exactly what remains uncertain or owner-dependent.

2

public opening, doors, zones and access status

SO-011 to SO-020 | ten operational questions

SO-011 PUBLIC OPENING, DOORS, ZONES AND ACCESS STATUS

DOOR + SCHEDULE

RECONCILIATION

STAKEHOLDER QUESTION

Which public entrances are authorised to be open now, and which observed door states still require a physical check?

SENSORS AND TELEMETRY

Proposed evidence: reed or Hall-effect door contacts, monitored latch or lock state and read-only access-controller mode at each designated public entrance; no passage identity. Coverage: only entrances in the current authoritative public-opening plan and exact commissioned door assets. Sampling and aggregation: event timestamps plus one-minute latest-state summaries; retain aggregate opening duration, not credential detail. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (door open-close and latch sequence test, controller-to-door mapping test and clock alignment across sources), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: an open door does not prove authorised opening or passage, and a closed contact does not prove the latch is secure. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup and observation reconciliation. Decision interval: now and the next authorised opening transition. Minimum evidence: the current opening instruction, exact entrance mapping, latest healthy door and lock states, controller mode and any active closure or exception. Method: label each entrance authorised-open, authorised-closed, observed-open, observed-closed, conflicting or unverified; never infer permission from telemetry. Uncertainty: contact misalignment, manual locking and delayed controller updates can create false disagreement. Safe failure: show the authoritative instruction and request a physical check for any inconsistent or unhealthy entrance; do not state an open/closed conclusion from one sensor alone.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security Duty Manager, building opening-hours owner, Access Control Manager, Event Manager and Facilities closure owner. Precedence: the latest authenticated opening instruction or incident closure effective now overrides schedule and controller configuration; telemetry only describes observed state. Time discipline: display effective, observed and retrieved times; reject expired event windows and display the age of each door observation and schedule retrieval. Permissions and provenance: Limit detailed zone, controller and schedule data to authorised Security, Access Control and Facilities roles; expose only the minimum public-facing status; retain owner role, record or case ID, version and extraction path. Conflict handling: show official and observed states separately and refer disagreement to the Duty Manager and the opening or access owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not unlock or lock a door, grant admission, infer who passed, or announce that an entrance is safe or secure solely from telemetry. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets officers confirm the public-opening position and target manual checks at doors whose evidence does not match the current instruction.

SO-012 PUBLIC OPENING, DOORS, ZONES AND ACCESS STATUS

DOOR DURATION

CALCULATION

STAKEHOLDER QUESTION

Which monitored doors have remained open or ajar beyond their authorised operating or exemption window?

SENSORS AND TELEMETRY

Proposed evidence: door-position contacts and, where separately commissioned, latch monitors at exact mapped doors; no camera, microphone or credential-content analysis. Coverage: doors with an owner-defined open-duration rule or current temporary exemption. Sampling and aggregation: state-change events at source resolution with duration calculated to the second and reported in one-minute bands. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (full open-close sequence test, contact debounce validation, latch-state test and source clock comparison), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: wedging, maintenance, loading and contact faults can produce the same observed state, so duration does not establish cause. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: calculation. Decision interval: each current open interval and the next operational check point. Minimum evidence: exact door mapping, continuous healthy state events from opening to now, current duration rule and any valid exemption. Method: calculate elapsed open time, subtract only authorised exemption periods, and classify within-window, exceeded, gap-crossed or unverified. Uncertainty: event loss, contact bounce and unsynchronised clocks can distort short intervals. Safe failure: do not calculate across a gap or failed test; show the last verified state and require a physical check under current procedure.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Access Control Manager owns door rules; the Duty Manager, Event Manager and Facilities owner hold current exemptions and maintenance states. Precedence: an effective owner-approved exemption or operational instruction overrides the standard duration rule; the door event cannot classify intent or incident status. Time discipline: display effective, observed and retrieved times; use the rule and exemption version active throughout the observed interval and stop calculation across data gaps or clock discontinuity. Permissions and provenance: Limit detailed zone, controller and schedule data to authorised Security, Access Control and Facilities roles; expose only the minimum public-facing status; retain owner role, record or case ID, version and extraction path. Conflict handling: show rule, exemption and sensor conflicts separately and refer them to the Duty Manager plus Access Control or Facilities owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not label the event forced, malicious or negligent, identify a user, acknowledge an alarm, or command closure. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Helps officers distinguish a measurable duration exception from a sensor gap or authorised operational use.

2

public opening, doors, zones and access status

SO-011 to SO-020 | ten operational questions

SO-013 PUBLIC OPENING, DOORS, ZONES AND ACCESS STATUS

ROUTE DEPENDENCIES

CALCULATION

STAKEHOLDER QUESTION

Which authorised public routes are interrupted by an official closure, unavailable door, lift fault or unverified segment?

SENSORS AND TELEMETRY

Proposed evidence: mapped door contacts, lift service-state feeds and owner-recorded barrier or route inspections; optional anonymous counters describe demand but not route authority. Coverage: segments in the current authoritative public-route graph, including every door and lift dependency. Sampling and aggregation: event-driven asset states with five-minute snapshots; inspection records at their signed time and anonymous counts in five-minute bands. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (door and lift functional tests, route-to-asset mapping verification and clock alignment between asset feeds), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: temporary obstructions and uninstrumented segments may be invisible, and an available lift state does not certify accessibility. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: calculation. Decision interval: now through the next scheduled route change. Minimum evidence: a current route graph, exact asset mapping, official closures, healthy door and lift states and a signed check for uninstrumented mandatory segments. Method: evaluate each route end to end, mark the first blocking or unverified dependency, and list only owner-approved alternatives. Uncertainty: state changes can occur after calculation and manually placed barriers may not be sensed. Safe failure: return no route as usable unless every mandatory segment has current authority and evidence; name the physical check required.

AUTHORITATIVE SUPPORTING DATA

Current owners: the public-route owner, Facilities closure and lift owners, Access Control Manager, Event Manager and accessibility owner. Precedence: official closures and owner-approved route versions lead; telemetry cannot reopen a segment or make a historical plan current. Time discipline: display effective, observed and retrieved times; use only route and closure records effective for the decision interval; the May 2021 floor plan remains historical reference only. Permissions and provenance: Limit detailed zone, controller and schedule data to authorised Security, Access Control and Facilities roles; expose only the minimum public-facing status; retain owner role, record or case ID, version and extraction path. Conflict handling: show every segment conflict and refer it to the route owner plus the owner of the door, lift or closure record; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not direct the public, certify accessibility or safety, remove a closure, operate a lift or door, or infer the reason for a blockage. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Enables officers to identify the exact route dependency needing confirmation and coordinate with the responsible owner.

SO-014 PUBLIC OPENING, DOORS, ZONES AND ACCESS STATUS

ZONE REGISTER

LOOKUP

STAKEHOLDER QUESTION

What is the current owner-approved access classification of each requested zone, and where is the record too stale or conflicted to rely on?

SENSORS AND TELEMETRY

Proposed evidence: no environmental sensing is required; a read-only snapshot of controller group configuration may be used only to detect a mismatch with the owner register. Coverage: the exact zones and door groups in the current authoritative access register. Sampling and aggregation: retrieve at decision time and after an approved access change; no person or credential history is needed. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (zone-to-door mapping validation, controller configuration checksum and source-clock comparison), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: controller configuration can lag an approved decision or contain local exceptions and therefore is not the authority. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup and comparison. Decision interval: the access-status enquiry and any pending operational use. Minimum evidence: zone identity, current owner, classification, effective dates, approved exceptions and controller snapshot where comparison is permitted. Method: return the owner-approved class, then compare configuration only as a separate observed state; flag missing owner, expiry and mismatch. Uncertainty: unsynchronised changes and ambiguous zone boundaries can create apparent conflicts. Safe failure: return not assessable and name the owner or mapping needed; never infer class from neighbouring zones or the May 2021 plan.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Access Control Manager and designated zone owners hold classifications; the Security Duty Manager owns current operational restrictions. Precedence: the latest authenticated zone-owner decision and current Security restriction override controller configuration, schedules and historical spatial material. Time discipline: display effective, observed and retrieved times; show the decision effective period, observation time for configuration and retrieval time; treat expired, ownerless or superseded classifications as unusable. Permissions and provenance: Limit detailed zone, controller and schedule data to authorised Security, Access Control and Facilities roles; expose only the minimum public-facing status; retain owner role, record or case ID, version and extraction path. Conflict handling: do not choose between conflicting owner records; refer them to the Access Control Manager and relevant zone owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not disclose the full restricted-zone matrix to unauthorised users, create access rights, decide a person's entitlement or treat controller state as permission. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets officers check the correct source before applying current procedures at a zone boundary.

2

public opening, doors, zones and access status

SO-011 to SO-020 | ten operational questions

SO-015 PUBLIC OPENING, DOORS, ZONES AND ACCESS STATUS

ACCESS HEALTHDIAGNOSIS

STAKEHOLDER QUESTION

Which readers, controllers or monitored locks are degraded, and what operational scope is actually evidenced as affected?

SENSORS AND TELEMETRY

Proposed evidence: reader and controller heartbeats, power and network status, lock-monitor state, controller fault codes and last successful command acknowledgement; no credential or user identity. Coverage: each commissioned access-control asset and its verified door and dependency mapping within Abacws. Sampling and aggregation: event-driven faults, one-minute heartbeats and five-minute health summaries with explicit gaps. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (reader test card in a controlled test window without retaining credential identity, controller input-output test, lock-state test and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a heartbeat can remain present while a reader or lock function is impaired, and shared dependencies can widen or narrow the true scope. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: diagnosis. Decision interval: now and the next opening, closing or access-control decision. Minimum evidence: exact asset mapping, current heartbeat and fault sequence, recent functional test, dependency health and owner service status. Method: trace each failed symptom through the verified controller, network, power and lock dependency graph; report affected, possibly affected and unverified scope separately. Uncertainty: topology errors, intermittent faults and stale closure records can misstate impact. Safe failure: do not generalise beyond verified dependencies; show the last healthy evidence and require owner diagnosis or physical check.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Access Control service owner, IT network owner, Facilities power or lock owner and Security Duty Manager. Precedence: owner-confirmed service status and dependency records lead; telemetry supports fault localisation but cannot declare a door secure or insecure. Time discipline: display effective, observed and retrieved times; show fault effective time, latest observed state and retrieval time; expire a healthy label after the owner-defined heartbeat or test age. Permissions and provenance: Limit detailed zone, controller and schedule data to authorised Security, Access Control and Facilities roles; expose only the minimum public-facing status; retain owner role, record or case ID, version and extraction path. Conflict handling: show asset and dependency disagreements and refer them to the Access Control service owner plus the affected infrastructure owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not remotely reset or control equipment, infer compromise or unauthorised entry, expose sensitive topology, or certify a door's security state. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Supports a precise fault escalation and proportionate manual coverage without overstating the affected area.

SO-016 PUBLIC OPENING, DOORS, ZONES AND ACCESS STATUS

ALARM HISTORYCOMPARISON

STAKEHOLDER QUESTION

Where are door-held, forced-door or controller alarms recurring, and which occurrences are owner-classified incidents, confirmed faults or still unresolved?

SENSORS AND TELEMETRY

Proposed evidence: de-identified access-controller event codes, door contacts, lock-monitor states and source-health events grouped by exact asset; no credential identity or image/audio content. Coverage: commissioned monitored doors and controllers with stable asset identifiers. Sampling and aggregation: retain event timestamps; report counts and intervals in owner-approved daily or shift bands, suppressing small personalisable groups. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (event-code injection test, door-state sequence check, duplicate-event test and cross-controller clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: the same code can arise from maintenance, delay, misuse or fault, so recurrence is not evidence of intent or cause. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: comparison. Decision interval: the current shift and a defined comparable period. Minimum evidence: healthy event coverage, exact asset mapping, stable alarm-code definitions, owner classifications and sufficient occurrences for the chosen aggregation. Method: group by asset and event class, separate incidents, faults, tests and unresolved cases, and show frequency plus exposure without a single risk score. Uncertainty: changes in door use, maintenance and classification practice can shift apparent recurrence. Safe failure: report only robust counts and unresolved classifications; do not label a hotspot or cause when evidence is sparse or inconsistent.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security incident owner, Access Control service owner and Facilities maintenance owner classify each occurrence. Precedence: owner-confirmed incident or fault classifications lead; raw event-code labels and frequency cannot determine wrongdoing or root cause. Time discipline: display effective, observed and retrieved times; use stable classification rules and asset mappings for the comparison period; show classification effective, event observed and data retrieved times. Permissions and provenance: Limit detailed zone, controller and schedule data to authorised Security, Access Control and Facilities roles; expose only the minimum public-facing status; retain owner role, record or case ID, version and extraction path. Conflict handling: keep unclassified and conflicting cases separate and refer them to the incident owner and Access Control service owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not identify an entrant, infer forced entry or suspicious intent, rank doors as dangerous, or initiate alarm acknowledgement or response. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Helps Security and Access Control target a specific asset or classification gap for human investigation.

2

public opening, doors, zones and access status

SO-011 to SO-020 | ten operational questions

SO-017

PUBLIC OPENING, DOORS, ZONES AND ACCESS STATUS

ACCESSIBLE ROUTE

CALCULATION

STAKEHOLDER QUESTION

Is one officially designated step-free public route evidenced as available end to end, and where does the evidence stop?

SENSORS AND TELEMETRY

Proposed evidence: lift service states, accessible-door contacts and signed physical checks at uninstrumented route segments; optional non-imaging clearance sensors only at commissioned choke points. Coverage: the current accessibility-owner-approved route and every required door, lift and segment. Sampling and aggregation: event-driven asset states with five-minute snapshots; manual checks at their signed observed time. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (lift end-to-end test, door force or opening functional test where owned, clearance-sensor reference check and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: telemetry cannot detect every obstacle, door-force issue or user-specific requirement and cannot certify accessibility. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: calculation. Decision interval: now through the requested public-use window. Minimum evidence: one current approved route, exact segment mapping, healthy lift and door evidence, official closures and recent physical checks for blind segments. Method: test every segment against owner-defined availability; return available-evidenced, interrupted or unverified with the limiting segment and evidence age. Uncertainty: short-lived faults, manual barriers and individual access needs may not be represented. Safe failure: do not state route availability when a mandatory segment is unverified; provide the official contact or physical-check requirement.

AUTHORITATIVE SUPPORTING DATA

Current owners: the accessibility route owner, Facilities lift and door owners, Event Manager, Security Duty Manager and emergency authority where applicable. Precedence: the current accessibility instruction and official closure lead; sensor availability never creates an approved route. Time discipline: display effective, observed and retrieved times; use the route version and checks effective for the intended period; the May 2021 floor plan cannot establish current accessibility or services. Permissions and provenance: Limit detailed zone, controller and schedule data to authorised Security, Access Control and Facilities roles; expose only the minimum public-facing status; retain owner role, record or case ID, version and extraction path. Conflict handling: show the first conflicting segment and refer it to the accessibility owner plus the relevant asset or closure owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not certify accessibility, infer a person's disability or needs, direct a person onto an unconfirmed route, or operate doors or lifts. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets officers give the accessibility owner a precise segment to confirm before communicating an official route.

SO-018

PUBLIC OPENING, DOORS, ZONES AND ACCESS STATUS

EVENT ENTRANCE

LOOKUP

STAKEHOLDER QUESTION

Which entrance is currently designated for this event, appointment or public service, and is its observed state consistent with that designation?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required for designation; mapped door and lock states at the named entrance may provide a current observation. Coverage: the event or service entry named in the current approved plan and its exact door asset. Sampling and aggregation: retrieve designation at enquiry time; door events at source resolution with one-minute state summaries. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (door functional test, lock-state test, event-to-entrance mapping check and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: an observed open entrance does not prove it is designated, staffed or admitting people. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup and observation. Decision interval: the current arrival window. Minimum evidence: an approved event or service record, current entrance designation, any closure or change, exact door mapping and latest healthy door state. Method: return the designated entrance and separately label its observed state, evidence age and any conflict. Uncertainty: late event changes and manual door operation can make the observed state temporary. Safe failure: provide no entrance answer when the owner record is absent; show the named owner and do not substitute another open door.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Event Manager or public-service owner, Security Duty Manager, building opening owner and Access Control Manager. Precedence: the latest authorised event or service instruction and any current closure override schedule and telemetry. Time discipline: display effective, observed and retrieved times; show the designation effective window, door observation time and retrieval time; reject superseded plan versions. Permissions and provenance: Limit detailed zone, controller and schedule data to authorised Security, Access Control and Facilities roles; expose only the minimum public-facing status; retain owner role, record or case ID, version and extraction path. Conflict handling: present designation and observed state separately and route a mismatch to the Duty Manager plus event or service owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not grant admission, promise entry, infer who is expected, disclose a restricted event route or direct the public contrary to the current owner instruction. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets officers verify the correct public-facing entrance and escalate a state mismatch before arrivals.

2

public opening, doors, zones and access status

SO-011 to SO-020 | ten operational questions

SO-019 PUBLIC OPENING, DOORS, ZONES AND ACCESS STATUS

SCHEDULED TRANSITIONS

COMPARISON

STAKEHOLDER QUESTION

Which authorised lock or unlock transitions are due, late or unconfirmed, and which doors now require a manual status check?

SENSORS AND TELEMETRY

Proposed evidence: read-only controller schedule, command acknowledgement, lock monitor and door contact for each mapped scheduled door; no credential events. Coverage: doors with a current owner-approved transition in the decision window. Sampling and aggregation: command and state events at source resolution; report status in one-minute bands around each scheduled time. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (test schedule-to-door mapping, command acknowledgement path, lock-state transition and clock alignment within the owner tolerance), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a command acknowledgement may not prove the physical lock changed, and manual operation may not appear in the controller log. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: comparison. Decision interval: from ten minutes before to the owner-defined confirmation time after each transition. Minimum evidence: approved schedule, exact door mapping, current overrides, command acknowledgement, healthy lock and door state and aligned clocks. Method: compare due time, issued command and observed state; label upcoming, confirmed, late, failed, manually overridden or unverified. Uncertainty: network delay, manual operation and sensor misalignment can affect short timing windows. Safe failure: do not claim failure from a missing acknowledgement alone; identify the evidence gap and require the authorised manual check.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Access Control Manager owns schedules; the Duty Manager, opening owner, Event Manager and incident authority hold current overrides. Precedence: an authenticated override effective now leads; the approved schedule leads over controller configuration, while physical observations remain supporting evidence. Time discipline: display effective, observed and retrieved times; use the schedule version and override active at the transition time and stop comparisons across clock or event gaps. Permissions and provenance: Limit detailed zone, controller and schedule data to authorised Security, Access Control and Facilities roles; expose only the minimum public-facing status; retain owner role, record or case ID, version and extraction path. Conflict handling: show schedule, command and physical-state conflicts separately and refer them to the Duty Manager and Access Control Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not execute a transition, override a schedule, unlock or lock a door, infer passage or certify secure closure. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Supports timely manual verification and a precise access-control fault or exception escalation.

SO-020 PUBLIC OPENING, DOORS, ZONES AND ACCESS STATUS

CLOSE CHECKLIST

SYNTHESIS

STAKEHOLDER QUESTION

What evidence supports the current secure-close record, and which doors, keys or checks remain unconfirmed?

SENSORS AND TELEMETRY

Proposed evidence: door and latch states at designated perimeter or restricted doors, access-controller close status, key-cabinet slot state and signed manual checklist confirmations; no occupancy inference. Coverage: only assets listed in the current owner-approved secure-close checklist. Sampling and aggregation: event states through the close window, one final timestamped snapshot and manual checks at their signed time. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (door-latch sequence test, controller-close test, cabinet slot test, checklist source validation and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: closed contacts, an armed controller or returned keys do not prove the building is vacant, secure or free of defects. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: structured synthesis. Decision interval: the current close operation and immediate handover. Minimum evidence: the complete current checklist, exact asset mapping, healthy supporting state for each monitored item, signed manual checks for blind items and all active exceptions. Method: assemble item-level confirmed, conflicting, restricted and unverified states; never collapse them into an opaque secure score. Uncertainty: later entry, sensor faults and unsynchronised manual checks can invalidate the snapshot. Safe failure: state that secure close is not assessable when any mandatory item is missing or conflicting; show the exact check and owner required.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Duty Manager owns the close record; Access Control, Facilities and key-custody owners hold asset and key states; incident authority owns exceptions. Precedence: the signed current close checklist and explicit owner exceptions lead; telemetry supports individual checks but cannot certify the overall outcome. Time discipline: display effective, observed and retrieved times; use checks observed within the authorised close window and display their observation and retrieval times; expire status after any later access or fault. Permissions and provenance: Limit detailed zone, controller and schedule data to authorised Security, Access Control and Facilities roles; expose only the minimum public-facing status; retain owner role, record or case ID, version and extraction path. Conflict handling: show each checklist-state conflict and refer it to the Duty Manager plus the relevant asset or key owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not infer vacancy, certify that Abacws is secure, close an incident, control doors or alarms, or conceal an unresolved checklist item. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives the closing officer a traceable record of completed checks and a focused list for manual confirmation or handover.

3

alarms, incidents and service-desk coordination

SO-021 to SO-030 | ten operational questions

SO-021

ALARMS, INCIDENTS AND SERVICE-DESK COORDINATION

ALERT + PROCEDURE

RULE COMPARISON

STAKEHOLDER QUESTION

Which active alerts meet the current procedure's conditions for human verification, and which remain unclassified or not assessable?

SENSORS AND TELEMETRY

Proposed evidence: read-only alarm events, exact source and zone mapping, current source heartbeat, maintenance or test mode and any commissioned independent state such as door contact or plant fault; no image or audio content. Coverage: active alerts from commissioned systems within the officer's authorised Abacws scope. Sampling and aggregation: event timestamps at source resolution with a one-minute active-alert summary; preserve gaps and test-mode intervals. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (alarm input test, event-delivery test, mapping validation and cross-source clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: an alert can be genuine, spurious, test-generated or technically degraded, and telemetry cannot determine intent or procedural attendance. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: rule comparison. Decision interval: each alert's current procedural decision window. Minimum evidence: the active alert, exact mapping, current procedure, source health, test or maintenance status, any required independent evidence and current owner classification. Method: evaluate only the published procedural conditions; label eligible-for-human-check, held by procedure, test, source-unhealthy, unclassified or not assessable. Uncertainty: delayed source health and incomplete independent coverage can change the label. Safe failure: return unclassified or not assessable with the missing condition and owner; do not recommend attendance, priority or acknowledgement.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security Duty Manager owns operational handling; the alarm-system owner holds source status; Safety, Facilities or IT owners classify system-specific conditions; incident command leads during an emergency. Precedence: the current authorised alarm procedure and any competent emergency instruction override default thresholds, telemetry labels and earlier case notes. Time discipline: display effective, observed and retrieved times; apply the procedure version effective when the alert occurred and display event, observation and retrieval times; expire a classification when the source state materially changes. Permissions and provenance: Apply incident-case, need-to-know and recipient restrictions; minimise narrative and personal fields and preserve case/source lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: show procedural, source-health and owner-classification conflicts separately and refer them to the Duty Manager plus the alarm owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not acknowledge, silence or reset an alarm; do not decide that an incident has occurred, set response priority or direct attendance. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets officers see which alerts have a complete procedural evidence package and which require owner clarification before any human decision.

SO-022

ALARMS, INCIDENTS AND SERVICE-DESK COORDINATION

DEPENDENCY HEALTH

DIAGNOSIS

STAKEHOLDER QUESTION

Do several current alerts share a verified technical dependency, or is the apparent pattern only a time correlation?

SENSORS AND TELEMETRY

Proposed evidence: alert timestamps, controller and gateway heartbeats, network-link state, power-monitor status and verified asset-dependency mappings; no credential, camera or microphone content. Coverage: only the alert sources and infrastructure dependencies exactly mapped in the current asset model. Sampling and aggregation: source events at native resolution, one-minute infrastructure health and five-minute grouped summaries. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (dependency-map validation, controlled heartbeat or failover test where authorised, power-monitor calibration and clock-offset comparison), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: simultaneous alerts can be coincidental, and an incomplete dependency map can create a false common-cause impression. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: diagnosis. Decision interval: the active alert cluster and immediate technical escalation window. Minimum evidence: aligned alert times, exact source mapping, current dependency graph, healthy status feeds and at least one evidenced shared component or independent path. Method: trace each alert through verified dependencies, compare shared failure states and label confirmed shared dependency, possible dependency, independent sources or not assessable. Uncertainty: clock drift, cascading retries and hidden local power paths can mimic common failure. Safe failure: state only possible association unless the shared component and time alignment are independently verified; defer root-cause confirmation to the technical owner.

AUTHORITATIVE SUPPORTING DATA

Current owners: the alarm-system owner, Access Control service owner, IT network owner, Facilities power owner and Security incident owner. Precedence: owner-confirmed topology and technical diagnosis lead; temporal coincidence and derived grouping cannot establish root cause. Time discipline: display effective, observed and retrieved times; use dependency records effective for the alert interval and health observations covering that interval; mark old topology or missing telemetry as stale. Permissions and provenance: Apply incident-case, need-to-know and recipient restrictions; minimise narrative and personal fields and preserve case/source lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: retain competing dependency explanations and route them to the relevant technical owners and the Security incident owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not declare a cyberattack, sabotage, intrusion or root cause, expose sensitive topology beyond authorised roles, or initiate technical control actions. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Supports a focused multi-team escalation without turning coincident alerts into an unsupported incident narrative.

3

alarms, incidents and service-desk coordination

SO-021 to SO-030 | ten operational questions

SO-023

ALARMS, INCIDENTS AND SERVICE-DESK COORDINATION

LOCATION CONTEXT

OBSERVATION

STAKEHOLDER QUESTION

Before attendance is considered under procedure, what verified non-personal context is available for the reported location?

SENSORS AND TELEMETRY

Proposed evidence: mapped door and lock state, fixed environmental alarm state, lift or utility service state, anonymous zone count where commissioned and fixed call-point health; no camera, microphone, identity or device-location data. Coverage: the exact reported room, entrance or zone plus only dependencies explicitly relevant to the current procedure. Sampling and aggregation: latest state no older than the owner threshold, with one-minute anonymous aggregates and event timestamps for discrete alarms. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (functional test for each cited modality, exact room or zone mapping, counter accuracy check and cross-system clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: anonymous counts can miss or double-count people, environmental states may be local, and absence of a signal does not prove normal conditions. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: observation and lookup. Decision interval: the immediate procedural decision window for the report. Minimum evidence: a valid incident location, current procedure, exact sensor mapping, healthy source state and permission to disclose each contextual field. Method: present a compact fact table separating owner-confirmed status, observed equipment or environmental state, anonymous count range and unknowns. Uncertainty: coverage gaps and asynchronous observations may prevent a coherent snapshot. Safe failure: return only the current owner facts and verified observations; mark missing locations or stale evidence not assessable and leave attendance to authorised staff.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security incident owner, Facilities service owner, Safety owner, Access Control Manager and source-system owners. Precedence: the current incident report and competent owner instructions lead; telemetry supplies bounded context but cannot decide whether attendance is required. Time discipline: display effective, observed and retrieved times; show report effective time, sensor observation times and retrieval time; exclude states older than the procedure permits. Permissions and provenance: Apply incident-case, need-to-know and recipient restrictions; minimise narrative and personal fields and preserve case/source lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: show contradictory owner and sensor states without resolving them and route the conflict to the Duty Manager plus the relevant source owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not infer who is present, identify a suspect, reconstruct movement, assess intent or danger, or treat absence of telemetry as reassurance. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives the Duty Manager a bounded evidence picture for applying the current incident procedure and briefing any authorised responder.

SO-024

ALARMS, INCIDENTS AND SERVICE-DESK COORDINATION

CASE METADATA

LOOKUP

STAKEHOLDER QUESTION

Has this reported issue already been logged, and which owner currently holds the next update?

SENSORS AND TELEMETRY

Proposed evidence: no new sensing is required; use read-only case identifiers, asset or zone references, category, status, owner and update time from authorised Security and service-desk systems. Coverage: records within the reported asset, zone and time window that the user is permitted to search. Sampling and aggregation: retrieve at report time and show source-level update timestamps; do not ingest personal narrative for matching unless explicitly authorised. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (connector retrieval test, category and asset mapping validation, case-ID integrity check and source-clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: records can use different categories or locations, and a similar case does not prove the same issue. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup and similarity comparison. Decision interval: the moment a new report is being triaged. Minimum evidence: a report time, exact or bounded location, asset or service reference, authorised category fields and current case ownership. Method: search exact identifiers first, then bounded location-time-category candidates; show confidence factors without merging or suppressing the new report. Uncertainty: free-text variation, incomplete mapping and concurrent faults can create false matches or misses. Safe failure: state no confirmed existing case when exact evidence is absent; show candidates for human confirmation and preserve the new report route.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security incident owner, central service-desk owner and responsible Facilities, IT or Access Control service owner. Precedence: the authoritative case status and assigned owner in the source system lead; a derived match cannot transfer ownership or close a new report. Time discipline: display effective, observed and retrieved times; show case creation, latest owner update, effective status and retrieval times; treat closed or superseded records according to the owner's recurrence rule. Permissions and provenance: Apply incident-case, need-to-know and recipient restrictions; minimise narrative and personal fields and preserve case/source lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: present candidate cases separately and refer uncertain ownership to the Security incident owner and service-desk coordinator; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not merge, close, reassign or suppress a case, expose personal narratives, or infer that two reports share a cause or actor. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Reduces avoidable duplicate handling while preserving a clear route when the match or current owner is uncertain.



alarms, incidents and service-desk coordination

SO-021 to SO-030 | ten operational questions

SO-025

ALARMS, INCIDENTS AND SERVICE-DESK COORDINATION

CASE TIMES

CALCULATION

STAKEHOLDER QUESTION

Which active incidents are approaching or exceeding their authorised response or update targets?

SENSORS AND TELEMETRY

Proposed evidence: no additional sensing is required; use owner-recorded incident creation, acceptance, attendance, update and status timestamps with case-class metadata. Coverage: active Security cases in the authorised service scope and only the timing milestones defined for their class. Sampling and aggregation: calculate from source timestamps at enquiry time and refresh on each case event; report time bands rather than person-level work traces. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (timestamp completeness test, source-clock comparison, milestone-definition validation and duplicate-event check), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: missing timestamps, paused cases and class changes can make elapsed-time calculations incomplete or non-comparable. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: calculation. Decision interval: the current case-management interval and next required update. Minimum evidence: current case class, valid target, complete required timestamps, authorised pauses and owner-confirmed status. Method: compute elapsed and remaining time under the published rule; label within target, approaching, exceeded, paused, incomplete or not assessable. Uncertainty: late entry and retrospective status changes can alter the result. Safe failure: do not classify a breach when required timestamps or target rules are missing; show the missing milestone and current owner.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security service owner owns targets and case classes; the incident owner holds case status; service-desk owners hold accepted milestone semantics. Precedence: the target and pause rules effective for the case class lead; telemetry or a generic elapsed time cannot create a breach. Time discipline: display effective, observed and retrieved times; show target effective date, each case event time and retrieval time; recalculate if the case class or authorised pause changes. Permissions and provenance: Apply incident-case, need-to-know and recipient restrictions; minimise narrative and personal fields and preserve case/source lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: show target, class and milestone conflicts and refer them to the Security service owner and case owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not rank officers, infer negligence, create disciplinary conclusions, promise response times, change case priority or direct attendance. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets supervisors prompt a case-owner update or record a timing exception before the handover point.

SO-026

ALARMS, INCIDENTS AND SERVICE-DESK COORDINATION

INDEPENDENT EVIDENCE

DIAGNOSIS

STAKEHOLDER QUESTION

Is this alarm supported by an independent source, or could source, mapping, power, network or controller failure explain the signal?

SENSORS AND TELEMETRY

Proposed evidence: the primary alarm event plus a genuinely independent commissioned modality such as a separate door contact, lock monitor, environmental detector or local power state, together with network and controller health. Coverage: the exact alarm asset and only the verified independent sources mapped to the same physical condition. Sampling and aggregation: event timestamps at native resolution with one-minute dependency health; retain source independence metadata. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (controlled source test, independent-path validation, power and network test, duplicate-event check and sub-second or owner-tolerated clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: two feeds may share hidden power, controller or network dependencies and therefore may not be independent. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: diagnosis. Decision interval: the alarm's current verification window. Minimum evidence: the primary event, exact source mapping, at least one verified independent source or explicit absence, aligned clocks and current dependency health. Method: test independence first, then compare state and timing; label corroborated observation, single-source alert, shared-dependency risk, source-unhealthy or not assessable. Uncertainty: intermittent faults, delayed events and hidden dependencies can weaken corroboration. Safe failure: do not call the alarm confirmed when independence is missing; show the strongest verified state and require current procedure to govern the next step.

AUTHORITATIVE SUPPORTING DATA

Current owners: the alarm-system owner, Access Control or Facilities asset owner, IT network owner and Security incident owner. Precedence: owner-confirmed source mapping and technical diagnosis lead; a second signal is corroboration only when its independence is verified. Time discipline: display effective, observed and retrieved times; use mappings and health states effective at the alarm time and display alarm, corroboration and retrieval times. Permissions and provenance: Apply incident-case, need-to-know and recipient restrictions; minimise narrative and personal fields and preserve case/source lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: show each competing technical explanation and route unresolved dependency questions to the source owners and Security incident owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not decide that intrusion or another incident occurred, infer cause or actor, acknowledge or reset the alarm, or dispatch a response. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Helps officers distinguish corroborated equipment evidence from a single-source or technically compromised alert.

3

alarms, incidents and service-desk coordination

SO-021 to SO-030 | ten operational questions

SO-027

ALARMS, INCIDENTS AND SERVICE-DESK COORDINATION

OFFICIAL SCOPE

LOOKUP

STAKEHOLDER QUESTION

Which routes, services or secured assets are officially inside the current incident or closure scope?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required to define scope; read-only door, barrier, lift and service states may show implementation at assets named by the official scope. Coverage: the exact zones, routes, services and assets listed in the current incident or closure record. Sampling and aggregation: retrieve at each command update; observed asset states at source resolution with five-minute summaries. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (scope-to-asset mapping validation, asset-state functional test and clock alignment to the incident timeline), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: telemetry can be inconsistent with a newly issued scope and cannot determine the legal or operational boundary. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup and spatial mapping. Decision interval: the current incident-command interval. Minimum evidence: the current signed scope statement, authoritative current spatial mapping, exact asset links and any approved exceptions. Method: map only explicitly named zones and dependencies, then show observed implementation as a separate layer with time and health labels. Uncertainty: ambiguous boundaries, stale maps and unmapped assets can leave gaps. Safe failure: return only the textual official scope when current mapping is incomplete; never expand or contract it by inference.

AUTHORITATIVE SUPPORTING DATA

Current owners: the competent incident commander or closure owner, Security Duty Manager, Facilities and Access Control owners. Precedence: the latest authenticated incident-command or closure instruction effective now overrides schedules, prior maps, telemetry and historical plans. Time discipline: display effective, observed and retrieved times; display scope effective time, asset observation times and retrieval time; retire superseded scope versions immediately. Permissions and provenance: Apply incident-case, need-to-know and recipient restrictions; minimise narrative and personal fields and preserve case/source lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: show conflicting owner instructions without choosing between them and refer them to incident command and the named source owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not create, widen, narrow or lift an incident boundary, direct movement, disclose restricted tactical detail or treat the May 2021 plan as current. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives officers a traceable official boundary for signage, liaison and owner escalation without taking command.

SO-028

ALARMS, INCIDENTS AND SERVICE-DESK COORDINATION

PERMISSION METADATA

RULE COMPARISON

STAKEHOLDER QUESTION

What incident information may be shared with each intended recipient for the stated purpose and no further?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required; use field classification, incident restriction, recipient role, stated purpose, approved channel, aggregation level and prior disclosure metadata. Coverage: the exact fields proposed for the specific recipient and communication. Sampling and aggregation: evaluate immediately before disclosure and again if the incident state, recipient, purpose or channel changes. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (classification lookup test, recipient-role resolution, source-permission validation and disclosure-lineage check), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: metadata can be incomplete, and a recipient's general role does not prove need for every field. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: rule comparison. Decision interval: immediately before the proposed disclosure. Minimum evidence: field-level source permission, recipient authorisation, stated purpose, approved channel, current incident restrictions and retention requirement. Method: evaluate each field separately; output share, aggregate, redact, withhold or owner-confirmation-needed with the governing rule. Uncertainty: recipient context and legal restrictions can change faster than cached permissions. Safe failure: withhold any field lacking a current permission chain and show the authorised owner or channel needed; do not create a shareable report automatically.

AUTHORITATIVE SUPPORTING DATA

Current owners: the incident information owner, Security information owner, competent incident command, Data Protection or information-governance owner and recipient organisation owner. Precedence: incident-command and legal restrictions lead; the field owner's minimum-necessary rule overrides operational convenience and prior sharing. Time discipline: display effective, observed and retrieved times; show each rule's effective time, the proposed disclosure time and permission retrieval time; recheck after a material incident update. Permissions and provenance: Apply incident-case, need-to-know and recipient restrictions; minimise narrative and personal fields and preserve case/source lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: deny unresolved fields and refer conflicts to the incident information owner and information-governance owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not send, publish or redact records, expose personal or tactical detail, infer consent, or treat prior disclosure as continuing authority. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets an authorised officer prepare the minimum permissible message and route uncertain fields before sharing.



alarms, incidents and service-desk coordination

SO-021 to SO-030 | ten operational questions

SO-029

ALARMS, INCIDENTS AND SERVICE-DESK COORDINATION

DE-IDENTIFIED CASES

COMPARISON

STAKEHOLDER QUESTION

Are repeated reports sufficiently similar to be candidate duplicates, or must they remain separate unresolved cases?

SENSORS AND TELEMETRY

Proposed evidence: de-identified case metadata limited to asset or bounded location, event class, time band, source system and current owner; no personal narrative, identity or content analysis. Coverage: authorised Security and service-desk cases within a defined time and spatial window. Sampling and aggregation: compare on demand and in owner-approved short intervals; suppress sparse group outputs that could expose individuals. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (category mapping test, asset and location mapping validation, timestamp alignment and case-ID integrity check), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: similar time and place can reflect separate events, while inconsistent categorisation can hide duplicates. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: comparison. Decision interval: new-report triage and periodic unresolved-case coordination. Minimum evidence: stable de-identified fields, exact or bounded location, aligned time bands, current case status and enough discriminating attributes. Method: apply transparent exact and fuzzy matching on authorised fields; show match factors and a bounded similarity level, not a single opaque decision. Uncertainty: shared assets, recurring faults and missing fields can inflate or reduce similarity. Safe failure: keep cases separate unless an authorised owner confirms duplication; return insufficient-evidence where decisive fields are missing.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security incident owner and service-desk owner retain case identity, status and merge authority; technical service owners hold asset classifications. Precedence: human-confirmed case relationships lead; a similarity result cannot merge, close or suppress a report. Time discipline: display effective, observed and retrieved times; use case versions and classifications current at comparison time and display event, update and retrieval times. Permissions and provenance: Apply incident-case, need-to-know and recipient restrictions; minimise narrative and personal fields and preserve case/source lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: show candidate relationships with the conflicting fields and refer them to the case owners; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not identify reporters or subjects, infer a common actor or cause, merge or close cases, or suppress a new report. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives case owners a focused candidate list for human consolidation while preserving separate accountability until confirmed.

SO-030

ALARMS, INCIDENTS AND SERVICE-DESK COORDINATION

OPEN CASES + ALERTS

SYNTHESIS

STAKEHOLDER QUESTION

For every unresolved alert or incident, which owner, evidence gap and next update time must be carried into handover?

SENSORS AND TELEMETRY

Proposed evidence: read-only active alert state, case status, latest owner update, source health and mapped asset status; no personal narrative beyond authorised need. Coverage: all unresolved Security alerts and incidents assigned to or affecting the current Abacws shift. Sampling and aggregation: compile at handover and refresh on each owner update; retain item-level timestamps and source links. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (case-source retrieval test, alert-to-case mapping validation, heartbeat check and cross-system clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: an alert may clear before case closure, and a case may remain open after the underlying equipment state changes. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: structured synthesis. Decision interval: the current shift handover. Minimum evidence: every unresolved item, exact owner, current authoritative status, latest verified evidence, known gap, restriction, next update time and current procedure reference. Method: assemble one concise row per item; separate owner facts, observations and unknowns and order only by an approved handover scheme. Uncertainty: late updates and source outages can leave an item temporarily inconsistent. Safe failure: carry the item as unresolved with the last valid evidence and named owner; never mark resolved or assign a response automatically.

AUTHORITATIVE SUPPORTING DATA

Current owners: the outgoing Duty Manager owns the handover; case owners and alarm-system owners retain status authority; the incoming Duty Manager accepts the operational record. Precedence: current case-owner status and incident-command direction override raw alert state and earlier notes. Time discipline: display effective, observed and retrieved times; show case effective status, latest observation, latest owner update, retrieval time and the required next-update deadline. Permissions and provenance: Apply incident-case, need-to-know and recipient restrictions; minimise narrative and personal fields and preserve case/source lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: retain conflicting states with both owners and route unresolved acceptance questions to the outgoing and incoming Duty Managers; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not close, reassign or reprioritise cases, identify suspects, direct the incoming shift or conceal conflicts and missing evidence. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Creates an accountable handover in which each unresolved item has a clear owner, evidence gap and timed next contact.

4

events, queues, crowds and public routes

SO-031 to SO-040 | ten operational questions

SO-031EVENTS, QUEUES, CROWDS AND PUBLIC ROUTES

EVENT PLAN + READINESSCOMPARISON

STAKEHOLDER QUESTION

Which events are due today, and which approved Security arrangements are current, missing or no longer valid for each one?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required to approve an arrangement; read-only entrance door state, barrier contact state, radio-pool readiness and anonymous entrance counts may provide bounded readiness context. Coverage: only event entrances, public routes, assembly points and equipment named in each current approved event plan. Sampling and aggregation: retrieve plans at briefing and before each event window; event-driven asset states with five-minute summaries and fifteen-minute anonymous demand bands. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (event-to-location mapping check, door or barrier functional test, equipment self-test and count-sensor manual comparison), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: asset readiness does not prove staff deployment, stewarding, permission or overall event safety. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: comparison. Decision interval: the daily briefing and each event's final preparation window. Minimum evidence: the current event schedule, approved plan version, required Security arrangements, named owners, valid time windows and current evidence for cited assets. Method: compare every required arrangement with its owner-confirmed status; label approved-current, pending, expired, conflicted, restricted or not assessable. Uncertainty: late programme changes and informal local arrangements may not yet be recorded. Safe failure: show only confirmed arrangements and a named gap list; do not assume an event is ready or recommend that it proceed.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Event Manager owns the approved event plan; the Security Duty Manager owns operational Security arrangements; Facilities, Access Control and Safety owners hold asset, route and control conditions. Precedence: the latest approved event and Security instruction effective for the event leads; incident or closure instructions override it, and telemetry cannot approve an arrangement. Time discipline: display effective, observed and retrieved times; show plan effective window, each observation time and retrieval time; treat draft, expired or superseded plans as unusable. Permissions and provenance: Use anonymous aggregates and approved event records only; restrict operational route detail and retain no person-level movement data; retain owner role, record or case ID, version and extraction path. Conflict handling: list each missing or conflicting arrangement with its owner and refer it to the Event Manager and Duty Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not approve or cancel an event, allocate staff, infer attendance, control access or certify that the arrangements are adequate. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets the Duty Manager target owner confirmations before arrivals and carry explicit exceptions into the event briefing.

SO-032EVENTS, QUEUES, CROWDS AND PUBLIC ROUTES

QUEUE COUNTSESTIMATE

STAKEHOLDER QUESTION

Where are anonymous queues forming at designated public points, and what lower and upper count bounds can the evidence support?

SENSORS AND TELEMETRY

Proposed evidence: dual-beam directional counters at queue entry and exit, or non-imaging time-of-flight occupancy sensors over a bounded queue zone; no video, identity, device or path data. Coverage: only the physically marked queue areas and thresholds with commissioned sensor geometry. Sampling and aggregation: one-second detections converted to one-minute inflow, outflow and occupancy estimates; publish five-minute bands and retain aggregates only. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (manual count comparison across low and high density, direction test, occlusion check, sensor reset record and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: groups, side entry, children, mobility aids, occlusion and queue spill beyond the mapped zone can widen error. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: estimate. Decision interval: rolling one- and five-minute queue conditions. Minimum evidence: commissioned coverage of all intended queue boundaries, healthy counters, current geometry, directional flows and a recent calibration error range. Method: estimate occupancy from bounded inflow and outflow or direct non-imaging counts; report central, lower and upper values and mark spill outside coverage. Uncertainty: unobserved side entry and dense occlusion can make the range asymmetric or too wide to use. Safe failure: return only flow observations or not assessable when coverage is incomplete; require a physical count under current procedure.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Event Manager or public-service owner defines queue zones; the Security Duty Manager and Safety owner hold operational thresholds; the sensor service owner holds count quality. Precedence: owner-approved zone and threshold definitions lead; the estimate cannot create a crowd-control instruction or redefine the queue footprint. Time discipline: display effective, observed and retrieved times; use only sensor calibration and geometry current for the event layout and display observation and retrieval times. Permissions and provenance: Use anonymous aggregates and approved event records only; restrict operational route detail and retain no person-level movement data; retain owner role, record or case ID, version and extraction path. Conflict handling: show plan, zone and sensor conflicts separately and refer them to the Event Manager plus sensor or Safety owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not identify or track people, infer behaviour or intent, label a crowd dangerous, or direct queue movement or officer action. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Helps officers decide whether to request an authorised physical check or alert the event or service owner to a measurable queue condition.



events, queues, crowds and public routes

SO-031 to SO-040 | ten operational questions

SO-033

EVENTS, QUEUES, CROWDS AND PUBLIC ROUTES

ROUTE DENSITY

ESTIMATE + COMPARISON

STAKEHOLDER QUESTION

Is anonymous crowding on a designated public route rising beyond the owner-approved threshold, or is the trend too uncertain to use?

SENSORS AND TELEMETRY

Proposed evidence: non-imaging time-of-flight zone occupancy, directional beam counts and door-flow totals at defined public-route segments; no video content, device identifiers or person trajectories. Coverage: only commissioned route zones with current geometry and an owner-approved counting purpose. Sampling and aggregation: one-second detections aggregated to thirty-second occupancy and two-minute trend estimates; retain only bounded aggregates. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (manual density comparison, entry-exit balance test, occlusion and spill check, sensor drift test and cross-zone clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: people outside the sensor footprint, group occlusion and changing route geometry can invalidate the trend. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: estimate and comparison. Decision interval: rolling two-minute windows during the approved event period. Minimum evidence: healthy complete zone coverage, current geometry, recent calibration error, aligned clocks, enough observations for a trend and an effective owner threshold. Method: estimate occupancy with uncertainty, fit a short transparent trend and compare its full interval with the threshold; label below, possibly crossing, clearly crossing or not assessable. Uncertainty: short bursts, counter lag and edge spill can reverse a weak trend. Safe failure: do not report a threshold crossing when the uncertainty interval overlaps materially or coverage is incomplete; show the physical check needed.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Event Manager and Safety owner define route zones and thresholds; the Security Duty Manager owns operational use; the sensor owner holds measurement quality. Precedence: the current approved threshold and route definition lead; a derived trend cannot establish danger, intent or an operational response. Time discipline: display effective, observed and retrieved times; show threshold effective time, observation interval and retrieval time; invalidate comparison after a layout change or expired calibration. Permissions and provenance: Use anonymous aggregates and approved event records only; restrict operational route detail and retain no person-level movement data; retain owner role, record or case ID, version and extraction path. Conflict handling: show threshold, geometry and sensor-quality conflicts and refer them to the Event Manager, Safety owner and Duty Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not assess crowd mood, intent, disorder or individual movement, declare an emergency, or issue crowd-control or dispatch instructions. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Provides a bounded trigger for human observation and event-owner coordination rather than an unsupported crowd-risk claim.

SO-034

EVENTS, QUEUES, CROWDS AND PUBLIC ROUTES

EVENT ROUTES

CALCULATION

STAKEHOLDER QUESTION

Which owner-approved public-route options remain feasible for the next event movement, and what evidence gap limits each option?

SENSORS AND TELEMETRY

Proposed evidence: mapped door and barrier states, lift service status, route-asset fault states and anonymous route-zone counts where commissioned; no person paths. Coverage: only route alternatives explicitly approved in the current event plan and exact mapped dependencies. Sampling and aggregation: event-driven asset states with five-minute freshness and one-minute counts aggregated to five-minute demand bands. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (door, barrier and lift functional tests, route mapping validation, count accuracy check and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: temporary obstructions, stewarding controls and blind segments may not be represented by telemetry. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: calculation. Decision interval: the next planned event movement window. Minimum evidence: the current approved route set, exact segment mapping, official closures, healthy asset states and recent checks for uninstrumented segments. Method: evaluate each approved option end to end, attach demand context separately, and list feasible-evidenced, interrupted and unverified routes with the limiting dependency. Uncertainty: rapid state changes and manual controls can make an option obsolete. Safe failure: return no option as feasible unless every mandatory segment is current; require event control to choose or authorise any alternative.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Event Manager owns approved route options; Facilities, Access Control and accessibility owners hold route dependencies; the Duty Manager owns Security use. Precedence: current event and closure instructions lead; telemetry can remove confidence in an option but cannot authorise a new route. Time discipline: display effective, observed and retrieved times; use the route version and asset states effective for the movement window and reject historical or superseded mappings. Permissions and provenance: Use anonymous aggregates and approved event records only; restrict operational route detail and retain no person-level movement data; retain owner role, record or case ID, version and extraction path. Conflict handling: show each conflicting segment and refer it to the Event Manager plus the relevant asset or closure owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not reroute the public, create an unapproved route, operate barriers, doors or lifts, disclose restricted route detail or certify accessibility or safety. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets event control choose among approved routes while seeing the exact segment that requires confirmation.

4

events, queues, crowds and public routes

SO-031 to SO-040 | ten operational questions

SO-035

EVENTS, QUEUES, CROWDS AND PUBLIC ROUTES

EVENT DEMANDFORECAST

STAKEHOLDER QUESTION

What arrival and departure peak windows are forecast for the next event, and what prediction range should officers plan around?

SENSORS AND TELEMETRY

Proposed evidence: anonymous directional counters at designated event entrances and exits, combined with approved event timing and registration totals; no ticket identity, device tracking or image analysis. Coverage: the event's commissioned public entrances and exits under the current layout. Sampling and aggregation: one-minute flows aggregated to five- and fifteen-minute bands; historical data retained only at approved aggregate level. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (directional count calibration, manual comparison, missing-flow balance check, event-to-entrance mapping and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: late arrivals, walk-ins, programme changes and entrance switching can make past event shapes non-comparable. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: forecast. Decision interval: fifteen-minute windows from pre-opening through final departure. Minimum evidence: current event schedule, expected attendance range, healthy entrance coverage and enough genuinely comparable complete events or an explicit low-data model. Method: forecast arrival and departure flows separately using transparent time-band baselines adjusted for the current programme; report central and prediction ranges. Uncertainty: small samples, changed layout and unplanned attendance can widen error materially. Safe failure: return schedule-based windows only when data are insufficient and state that no evidence-based flow forecast is available.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Event Manager owns programme and registration data; the Security service owner owns planning use; the sensor owner holds count quality. Precedence: the current approved programme and entrance plan lead; registration is a planning input, not proof of attendance. Time discipline: display effective, observed and retrieved times; use comparable event periods with documented coverage and display programme effective time, observation windows and retrieval time. Permissions and provenance: Use anonymous aggregates and approved event records only; restrict operational route detail and retain no person-level movement data; retain owner role, record or case ID, version and extraction path. Conflict handling: show programme, registration and count conflicts and refer them to the Event Manager and Security planning owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not identify attendees, promise turnout, infer individual arrival patterns, change staffing automatically or issue access or crowd instructions. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Helps the Duty Manager time briefings, public-interface cover and liaison with the Event Manager while preserving uncertainty.

SO-036

EVENTS, QUEUES, CROWDS AND PUBLIC ROUTES

DOOR FLOWSCOMPARISON

STAKEHOLDER QUESTION

Are anonymous door-flow observations consistent with the approved event footprint, or is the comparison not assessable?

SENSORS AND TELEMETRY

Proposed evidence: directional beam counts at event-designated doors, reported only as aggregate inflow and outflow; no credential identity, camera content or cross-door person matching. Coverage: the doors explicitly assigned to the event and any comparison doors authorised for aggregate use. Sampling and aggregation: one-minute counts aggregated to five-minute shares over the event window; retain no raw detections. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (manual directional count comparison, door-to-event mapping check, counter reset record and clock alignment across entrances), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: people may use doors for unrelated activity, and uninstrumented doors or changed stewarding can distort the footprint comparison. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: comparison. Decision interval: the current event window and agreed monitoring intervals. Minimum evidence: current footprint, complete authorised door coverage or a known coverage fraction, healthy counters, aligned clocks and enough flow for a stable comparison. Method: compare observed door-flow shares with the approved footprint expectation; show differences, coverage and uncertainty without a compliance score. Uncertainty: background building traffic and small counts can make percentage differences misleading. Safe failure: return not assessable when door coverage or event attribution is inadequate; show raw aggregate flows and the missing plan or sensor evidence.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Event Manager owns the approved footprint; the opening and Access Control owners hold door designation; the sensor owner holds count quality. Precedence: the current event plan determines expected doors; observed flow cannot prove unauthorised entry or redefine the event boundary. Time discipline: display effective, observed and retrieved times; use the footprint effective for the observed period and exclude intervals with closures, sensor gaps or layout changes. Permissions and provenance: Use anonymous aggregates and approved event records only; restrict operational route detail and retain no person-level movement data; retain owner role, record or case ID, version and extraction path. Conflict handling: show plan and flow mismatches and refer them to the Event Manager and Duty Manager without assigning cause; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not infer unauthorised access, identify attendees, reconstruct paths, attribute cause or direct door control or staff deployment. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives event and Security owners an evidence-bounded indication that the planned entrance pattern may need a human check.

4

events, queues, crowds and public routes

SO-031 to SO-040 | ten operational questions

SO-037EVENTS, QUEUES, CROWDS AND PUBLIC ROUTESASSET READINESSRULE COMPARISON

STAKEHOLDER QUESTION

Which route assets have enough current evidence to be treated as ready for their intended public use?

SENSORS AND TELEMETRY

Proposed evidence: door and barrier contacts, lift service state, emergency-lighting or public-lighting health where owned, fixed call-point status and signed signage or route inspections. Coverage: the exact assets and route segments named in the current event or public-service plan. Sampling and aggregation: event-driven telemetry with five-minute health snapshots; manual inspection at signed observed time and owner-defined recheck intervals. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (functional test for each asset type, exact route mapping, inspection-record validation and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a healthy electronic state does not prove signage position, clear passage, adequate lighting level or safe public use. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: rule comparison. Decision interval: the final preparation window and event operating period. Minimum evidence: the current asset checklist, exact mapping, valid functional tests, recent inspections, active faults and official closures. Method: test each item against owner criteria and label ready-evidenced, degraded, unverified, restricted or officially unavailable; avoid one overall score. Uncertainty: manual changes and conditions outside sensor scope can invalidate readiness. Safe failure: mark the route item unverified when any mandatory check is missing and name the physical inspection or owner confirmation required.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Event Manager or service owner, Facilities asset owners, accessibility owner, Access Control Manager and Security Duty Manager. Precedence: the owner-approved readiness checklist and official closure status lead; telemetry supports individual items but cannot certify the route. Time discipline: display effective, observed and retrieved times; show checklist version, observation or inspection time and retrieval time; expire readiness at the owner-defined interval or after any fault or layout change. Permissions and provenance: Use anonymous aggregates and approved event records only; restrict operational route detail and retain no person-level movement data; retain owner role, record or case ID, version and extraction path. Conflict handling: show asset and inspection conflicts and refer them to the route owner plus the responsible asset owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not certify a route safe, accessible or compliant, operate assets, remove closures or assume a healthy device means the surrounding route is clear. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets officers target final checks and escalate a specific asset gap before public use begins.

SO-038EVENTS, QUEUES, CROWDS AND PUBLIC ROUTESPLAN DIFFERENCECHANGE DETECTION

STAKEHOLDER QUESTION

After an approved route change, which barriers, signs, doors and stewarding points require a new physical confirmation?

SENSORS AND TELEMETRY

Proposed evidence: no new sensing is required; use versioned approved route plans, exact asset mappings, barrier or door state where commissioned and signed physical-check records. Coverage: only elements added, removed, moved or given a different function by the current approved route plan. Sampling and aggregation: calculate at plan approval and refresh after any further authorised change; asset states at source resolution and checks at signed time. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (plan-version integrity check, old-to-new mapping validation, asset functional test and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: digital plans may not show temporary furniture, tape, portable signs or stewarding practice unless these are explicitly recorded. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: change detection. Decision interval: from approval of the new route to the final pre-opening check. Minimum evidence: two authenticated plan versions, exact element identifiers, current asset mapping and the owner's recheck rule. Method: compare versions element by element and produce a bounded confirmation list for changed dependencies only; attach current state where verified. Uncertainty: poorly versioned drawings and informal changes can omit affected elements. Safe failure: do not state that an item is in place without a signed check; list unresolved elements and route them to the event control owner.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Event Manager owns the approved route plan; Facilities, Access Control and Security owners hold asset and stewarding checks. Precedence: the latest approved plan effective for the event leads; draft mark-ups, telemetry and the May 2021 floor plan cannot define the current arrangement. Time discipline: display effective, observed and retrieved times; show both plan effective times, physical-check times and retrieval time; reject superseded or unsigned versions. Permissions and provenance: Use anonymous aggregates and approved event records only; restrict operational route detail and retain no person-level movement data; retain owner role, record or case ID, version and extraction path. Conflict handling: display unresolved mapping differences and refer them to the Event Manager and relevant asset or Security owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not place or move barriers or signs, assign stewards, approve the changed route or treat plan geometry as proof of physical deployment. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Concentrates the pre-opening walk-through on elements actually affected by the authorised route change.



events, queues, crowds and public routes

SO-031 to SO-040 | ten operational questions

SO-039

EVENTS, QUEUES, CROWDS AND PUBLIC ROUTES

QUEUE DURATION

CALCULATION + COMPARISON

STAKEHOLDER QUESTION

Has a designated queue persisted longer than the authorised service plan or genuinely comparable events, without claiming why?

SENSORS AND TELEMETRY

Proposed evidence: anonymous queue-zone occupancy estimates and directional entry-exit counts from commissioned non-imaging sensors; no person identity or path history. Coverage: the designated queue zone and entrances under the current layout. Sampling and aggregation: one-minute occupancy estimates, five-minute duration bands and event-level aggregates after approved minimisation. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (manual count comparison, zone-geometry validation, threshold test, gap detection and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: queue spill, short sensor gaps and service pauses can break apparent continuity, and duration does not establish cause. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: calculation and comparison. Decision interval: the active queue episode and the agreed post-event reporting period. Minimum evidence: a valid queue threshold, continuous enough healthy coverage, a defined start and end rule and comparable periods with the same exposure. Method: calculate bounded persistence after excluding confirmed gaps, then compare with the service-plan limit and distribution of comparable events. Uncertainty: uncertain start time, spill and changing service capacity can widen the duration range. Safe failure: report only a lower and upper persistence bound when continuity is uncertain; do not claim exceedance or causation without adequate evidence.

AUTHORITATIVE SUPPORTING DATA

Current owners: the public-service or Event Manager owns the service plan; the Security service owner and Safety owner hold agreed operational use; the sensor owner holds quality. Precedence: the current service-plan threshold and defined comparable-event criteria lead; aggregate observations cannot assign responsibility. Time discipline: display effective, observed and retrieved times; use the plan effective for the queue interval and comparison periods with documented layout, opening and coverage equivalence. Permissions and provenance: Use anonymous aggregates and approved event records only; restrict operational route detail and retain no person-level movement data; retain owner role, record or case ID, version and extraction path. Conflict handling: show plan or comparability conflicts and refer them to the service owner and Security Duty Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not blame staff or attendees, infer dissatisfaction or disorder, identify people, or direct queue operations or staffing changes. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Supports a factual service-owner conversation about a prolonged queue while keeping causation and response with authorised people.

SO-040

EVENTS, QUEUES, CROWDS AND PUBLIC ROUTES

DATA MINIMISATION

RECOMMENDATION

STAKEHOLDER QUESTION

What is the minimum authorised evidence that may be retained after a crowd or queue issue without creating identity or movement history?

SENSORS AND TELEMETRY

Proposed evidence: only privacy-preserving aggregates already collected for the approved purpose: time bands, bounded zone counts, sensor health, threshold version, owner instructions and incident or event reference; no raw detections or personal data. Coverage: the specific crowd or queue issue, source zones and time window authorised by the information owner. Sampling and aggregation: retain the coarsest approved interval and shortest approved period; delete or avoid collecting raw events where not required. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (aggregate reproducibility check, source-lineage validation, clock alignment and deletion or expiry-control test), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: aggregate data can still become sensitive in very small groups or when combined with detailed event information. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: recommendation limited to data minimisation. Decision interval: before evidence is stored, exported or handed over. Minimum evidence: the stated purpose, field-level necessity, source permission, approved aggregation, retention rule, incident hold status and recipient need. Method: map each proposed field to a purpose and owner rule; recommend retain, coarsen, redact, withhold or expire, with lineage and the governing basis. Uncertainty: future investigative need may be uncertain and legal holds can change. Safe failure: retain nothing beyond an explicit current permission; route any preservation question to the information and incident owners.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security information owner, Event or service owner, incident owner and Data Protection or information-governance owner. Precedence: lawful purpose, incident hold and minimum-necessary retention rules lead; operational interest cannot extend retention or increase granularity. Time discipline: display effective, observed and retrieved times; show rule effective time, evidence observation interval, retrieval time and authorised expiry or hold date. Permissions and provenance: Use anonymous aggregates and approved event records only; restrict operational route detail and retain no person-level movement data; retain owner role, record or case ID, version and extraction path. Conflict handling: withhold or minimise any disputed field and refer conflicts to the information owner and Data Protection or information-governance owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not retain raw person-level detections, reconstruct movement, infer identity, extend a hold, delete protected evidence or disclose data beyond the approved purpose. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Allows officers to preserve a useful, proportionate event record without creating an unnecessary surveillance dataset.



keys, locks, assets and restricted areas

SO-041 to SO-050 | ten operational questions

SO-041

KEYS, LOCKS, ASSETS AND RESTRICTED AREAS

KEY CUSTODY

RECONCILIATION

STAKEHOLDER QUESTION

Which physical keys are signed out, overdue, returned but not reconciled, or unsupported by a current custody record?

SENSORS AND TELEMETRY

Proposed evidence: key-cabinet slot switches, cabinet-door state and authorised transaction records keyed to asset and custody event; no biometrics, device tracking or inference from nearby presence. Coverage: the numbered keys and cabinet slots in the current Security-owned key register for Abacws. Sampling and aggregation: transaction and slot-change events at source resolution with a current snapshot at shift handover; retain only authorised custody history. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (slot-by-slot presence test, cabinet-controller event test, key-to-slot mapping check and clock alignment between cabinet and register), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: an empty slot does not identify a holder, and a returned key can be placed in the wrong slot or recorded late. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup and reconciliation. Decision interval: key issue, return, shift handover and owner-defined overdue checkpoints. Minimum evidence: current key register, exact key-slot mapping, signed issue or return record, due time, valid exception and healthy cabinet evidence where available. Method: classify each key as in cabinet and reconciled, signed out within time, overdue, returned but mismatched, restricted or unverified; never infer a holder from a slot alone. Uncertainty: late paperwork, slot swaps and cabinet outages can create temporary mismatch. Safe failure: retain the authoritative custody status, mark the physical state unverified and require the custodian's physical reconciliation.

AUTHORITATIVE SUPPORTING DATA

Current owners: the key custodian owns the signed custody register; the Security Duty Manager owns shift exceptions; Access Control or Facilities owners hold key identity and authorised use. Precedence: the current signed transaction and custodian instruction lead; cabinet slot state is supporting evidence and cannot create or transfer custody. Time discipline: display effective, observed and retrieved times; show issue, due, observed return and retrieval times; expire temporary exceptions at their stated end and flag unsigned or superseded entries. Permissions and provenance: Restrict key-holder, lock, asset and restricted-zone details to authorised custodians and Security roles; preserve transaction and work-order lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: show register and cabinet differences separately and refer them to the key custodian and Duty Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not expose key-holder identity beyond authorised need, infer theft or misconduct, assign custody from telemetry, unlock cabinets or issue or recall keys automatically. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets the custodian resolve specific key-record mismatches and carry genuine overdue items into supervisor action.

SO-042

KEYS, LOCKS, ASSETS AND RESTRICTED AREAS

PRIORITY KEYS

RULE COMPARISON

STAKEHOLDER QUESTION

Which master, plant or other high-consequence keys have passed their authorised return time and now require supervisor attention?

SENSORS AND TELEMETRY

Proposed evidence: authorised key-custody transactions and key-cabinet slot state for keys already classified as high consequence by the owner; no biometric confirmation or person tracking. Coverage: only keys in the current high-consequence key list and their mapped cabinet slots. Sampling and aggregation: evaluate at the due time and owner-defined escalation intervals; slot events remain item-level and access is restricted. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (slot presence test, transaction completeness check, high-consequence classification mapping and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: cabinet absence does not prove loss, misuse or who holds a key, and a valid extension may be recorded late. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: rule comparison. Decision interval: each high-consequence key's return deadline and defined follow-up interval. Minimum evidence: current classification, signed issue record, due time, authorised extension, current custody status and healthy cabinet evidence if cited. Method: apply the owner rule and label within time, overdue-confirmed, possible return mismatch, restricted or not assessable; show elapsed time without ranking people. Uncertainty: late transaction entry and unsynchronised clocks can alter a near-deadline label. Safe failure: do not escalate from slot state alone; show the overdue record or missing confirmation and leave supervisor action to the Duty Manager.

AUTHORITATIVE SUPPORTING DATA

Current owners: the key custodian and relevant asset or plant owner define consequence and return rules; the Duty Manager owns supervisor attention during the shift. Precedence: the current key classification, signed custody record and authorised extension lead; sensor state cannot set consequence or escalation. Time discipline: display effective, observed and retrieved times; show classification effective time, issue and due times, observed slot state and retrieval time; reject expired extensions. Permissions and provenance: Restrict key-holder, lock, asset and restricted-zone details to authorised custodians and Security roles; preserve transaction and work-order lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: hold conflicting due times or classifications for the key custodian and asset owner; do not choose the stricter or looser rule automatically; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not infer loss, theft, intent or negligence, contact or accuse a holder automatically, disclose high-consequence key details widely or command a search. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Surfaces the small set of time-critical custody exceptions that require an authorised supervisor decision.



keys, locks, assets and restricted areas

SO-041 to SO-050 | ten operational questions

SO-043

KEYS, LOCKS, ASSETS AND RESTRICTED AREAS

CABINET HEALTH

DIAGNOSIS

STAKEHOLDER QUESTION

Are key-cabinet state and transaction evidence healthy and complete enough to support current custody decisions?

SENSORS AND TELEMETRY

Proposed evidence: cabinet-controller heartbeat, door contact, slot-switch states, transaction sequence, local power and network health and signed manual reconciliation records. Coverage: each commissioned key cabinet, controller, slot bank and synchronised custody source used for Abacws. Sampling and aggregation: one-minute heartbeats, event-driven door and slot changes, and a complete transaction sequence since the last signed reconciliation. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (slot-bank test, cabinet-door test, controller restart continuity check, event-sequence completeness test and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a live heartbeat does not prove every slot or transaction channel works, and offline transactions may arrive later. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: diagnosis. Decision interval: before issuing a custody answer and at shift handover. Minimum evidence: current asset mapping, full slot test result, continuous enough transaction sequence, heartbeat, power and network state, clock alignment and last signed reconciliation. Method: test completeness and function by component; classify reliable for bounded use, degraded, sequence-gap, mapping-conflict or not assessable. Uncertainty: intermittent network loss and delayed offline uploads can make a temporary gap appear permanent. Safe failure: suspend telemetry-supported custody conclusions and use the signed manual process until the custodian confirms reconciliation.

AUTHORITATIVE SUPPORTING DATA

Current owners: the key custodian owns accepted custody evidence; the cabinet service owner, IT network owner and Facilities power owner hold technical states. Precedence: the custodian's signed reconciliation leads; technical telemetry can restrict reliance but cannot correct custody records. Time discipline: display effective, observed and retrieved times; show last successful full test, latest event, observed health and retrieval times; mark evidence stale after the owner's test interval or an unexplained sequence gap. Permissions and provenance: Restrict key-holder, lock, asset and restricted-zone details to authorised custodians and Security roles; preserve transaction and work-order lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: keep custody and technical conflicts separate and refer them to the key custodian and cabinet service owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not infer missing keys, theft or holder identity from cabinet health, alter transactions, unlock the cabinet or certify custody completeness. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Tells officers when the cabinet can support reconciliation and when the manual key-control procedure must take over.

SO-044

KEYS, LOCKS, ASSETS AND RESTRICTED AREAS

LOCK DEFECTS

LOOKUP + COMPARISON

STAKEHOLDER QUESTION

Which locks or secure doors have an owner-confirmed defect, temporary control or overdue remedial action?

SENSORS AND TELEMETRY

Proposed evidence: lock-monitor and door-contact states, controller fault codes and authorised manual check records linked to current work orders; no passage identity. Coverage: the exact secure doors and locks in current Security and Facilities asset registers. Sampling and aggregation: event-driven states with five-minute summaries; physical checks and work-order updates at their recorded time. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (lock and latch functional test, door alignment check, controller-to-lock mapping and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: telemetry cannot establish the adequacy of a temporary control or whether a defect creates a security breach. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup and comparison. Decision interval: the current shift and next opening or closing decision. Minimum evidence: exact asset identity, current work order, owner-confirmed defect class, temporary control, latest physical check and healthy supporting state if cited. Method: return item-level defect, control, owner and target status, then compare current observation separately; label overdue only under the owner rule. Uncertainty: manual interventions and delayed case closure can make state and record differ. Safe failure: retain the owner-confirmed defect and control when evidence conflicts; request an authorised physical check rather than declaring restoration.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Facilities lock or door owner, Access Control Manager, Security Duty Manager and work-order service owner. Precedence: owner-confirmed defect, temporary control and completion status lead; sensor recovery cannot close a work order or remove a control. Time discipline: display effective, observed and retrieved times; show defect effective time, observed state, latest owner update, target date and retrieval time; treat closed cases as current only after owner confirmation. Permissions and provenance: Restrict key-holder, lock, asset and restricted-zone details to authorised custodians and Security roles; preserve transaction and work-order lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: show sensor and work-order conflicts and refer them to the Facilities owner and Duty Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not certify a door secure, remove or approve a temporary control, close work orders, infer intrusion or operate locks or doors. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets officers apply the current temporary arrangement and escalate a specific overdue owner action.



keys, locks, assets and restricted areas

SO-041 to SO-050 | ten operational questions

SO-045

KEYS, LOCKS, ASSETS AND RESTRICTED AREAS

TIME-WINDOW EVENT

OBSERVATION + COMPARISON

STAKEHOLDER QUESTION

Is there a de-identified access or door event outside the restricted area's authorised operating window that requires owner verification?

SENSORS AND TELEMETRY

Proposed evidence: de-identified controller event type, door contact and lock state at the exact restricted-area boundary; exclude credential identity and retain no person path. Coverage: only doors in the current restricted-area register and their authorised operating windows. Sampling and aggregation: event timestamps at native resolution with one-minute grouping of repeated technical events; no cross-door linking. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (event-code test, door-state sequence test, zone mapping validation and clock alignment to the approved schedule), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: maintenance, tests, delayed closing and authorised exceptions can produce the same time-window mismatch. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: observation and comparison. Decision interval: each event and the owner-defined verification interval. Minimum evidence: exact door mapping, healthy event sequence, current operating window, valid exceptions, test or maintenance status and aligned clocks. Method: compare the event time and state with the owner window; label within-window, authorised exception, outside-window observation, source-unhealthy or not assessable. Uncertainty: clock error and late exception entry can change the classification. Safe failure: do not call the event unauthorised; show the bounded mismatch and require owner verification under current procedure.

AUTHORITATIVE SUPPORTING DATA

Current owners: the zone owner and Access Control Manager own operating windows and exceptions; the Security incident owner classifies any report. Precedence: the current owner-approved window and explicit exception lead; a de-identified event cannot establish unauthorised access or wrongdoing. Time discipline: display effective, observed and retrieved times; show schedule effective time, event observed time and retrieval time; stop comparison across clock gaps or superseded windows. Permissions and provenance: Restrict key-holder, lock, asset and restricted-zone details to authorised custodians and Security roles; preserve transaction and work-order lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: show schedule, exception and event conflicts and refer them to the Access Control Manager and zone owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not reveal credential identity, infer who entered or why, identify a suspect, label trespass or automatically create access or response action. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Provides a precise, privacy-preserving exception for the zone owner and Security to verify.

SO-046

KEYS, LOCKS, ASSETS AND RESTRICTED AREAS

ZONE GOVERNANCE

GAP ANALYSIS

STAKEHOLDER QUESTION

Which restricted areas lack a current accountable owner, stated purpose or effective access-classification record?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required; use the restricted-area register, zone-to-door mapping and read-only controller group summary only to expose governance mismatch. Coverage: all zones currently marked restricted in the authoritative building and access registers. Sampling and aggregation: check at owner-defined governance intervals and after a zone, use or access change; no credential history. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (register completeness test, zone-door mapping validation, controller-group checksum and source-clock comparison), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a configured restricted group does not prove the classification is current, lawful or complete. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: gap analysis. Decision interval: the current access-governance checkpoint and before any operational reliance. Minimum evidence: a complete restricted-zone inventory, current owner, purpose, classification, effective period, door mapping and approved exceptions. Method: test mandatory governance fields and mapping; label complete, owner-missing, purpose-missing, expired, conflicting or unmapped. Uncertainty: long-lived local practices may exist outside the connected register. Safe failure: return not assessable for operational status and name the missing owner record; never assume the zone is open, closed or unrestricted.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Access Control Manager, designated zone owner, building information owner and Security service owner. Precedence: the current authenticated zone-owner record and institutional access policy lead; controller configuration and the May 2021 plan cannot create ownership or purpose. Time discipline: display effective, observed and retrieved times; show owner and classification effective dates, configuration observation time and retrieval time; mark ownerless, expired or superseded records unusable. Permissions and provenance: Restrict key-holder, lock, asset and restricted-zone details to authorised custodians and Security roles; preserve transaction and work-order lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: do not infer a resolution from adjacent zones; refer gaps to the Access Control Manager and building information owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not assign a zone owner, create or relax a classification, disclose sensitive zone detail broadly or grant any person access. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives governance owners a concrete list of restricted areas that cannot safely support access decisions until records are corrected.



keys, locks, assets and restricted areas

SO-041 to SO-050 | ten operational questions

SO-047

KEYS, LOCKS, ASSETS AND RESTRICTED AREAS

ASSET ENCLOSURE

OBSERVATION

STAKEHOLDER QUESTION

Which monitored cabinets, cages or fixed anchor points are in an unexpected state that still needs human verification?

SENSORS AND TELEMETRY

Proposed evidence: reed contacts, continuity loops or fixed anchor-state switches on owner-selected cabinets, cages and tether points, linked to a signed expected-state record; no camera or item identification by image. Coverage: only commissioned enclosures and anchors with exact asset and location mapping. Sampling and aggregation: state-change events at source resolution with one-minute latest-state summaries; no person association. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (open-close or continuity functional test, tamper-state test, asset mapping check and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: maintenance, authorised use, loose contacts and cable movement can produce an unexpected state without loss or intrusion. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: observation and comparison. Decision interval: the current shift and any owner-defined secure-state checkpoint. Minimum evidence: exact asset mapping, current expected state, valid exception, healthy sensor, recent functional test and aligned clock. Method: compare observed with expected state and label expected, unexpected-observed, exception, sensor-unhealthy or not assessable; keep cause unknown. Uncertainty: contact drift and unrecorded authorised use can create false exceptions. Safe failure: show the observed state and require a custodian physical check; do not state loss, tampering or intrusion.

AUTHORITATIVE SUPPORTING DATA

Current owners: the asset custodian owns expected state; Facilities or laboratory owners hold maintenance and use exceptions; Security owns any incident record. Precedence: the current custodian record and authorised exception lead; telemetry can request verification but cannot classify loss, theft or breach. Time discipline: display effective, observed and retrieved times; show expected-state effective time, observed event time and retrieval time; expire an expected state after authorised access or an owner update. Permissions and provenance: Restrict key-holder, lock, asset and restricted-zone details to authorised custodians and Security roles; preserve transaction and work-order lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: present state and owner-record differences and refer them to the custodian and Duty Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not identify a user, infer theft, tampering or intent, inspect research contents, control an enclosure or trigger dispatch. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets officers and custodians target a physical check at a specific fixed asset without surveillance of people or contents.

SO-048

KEYS, LOCKS, ASSETS AND RESTRICTED AREAS

TAMPER STATE

CHANGE DETECTION

STAKEHOLDER QUESTION

Which monitored seals, tamper loops or secure enclosures changed state since the last signed physical check?

SENSORS AND TELEMETRY

Proposed evidence: electrical continuity loops, seal-state switches or enclosure contacts on approved fixed assets, plus the last signed physical-check record; no video or content inspection. Coverage: the exact sealed or monitored assets listed in the current asset-control plan. Sampling and aggregation: event timestamps at source resolution from the last signed check to now; one final current-state snapshot. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (continuity or contact functional test, seal-to-asset mapping check, event-sequence completeness and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: sensor faults, maintenance and authorised opening can produce the same change; an electronic loop does not validate a physical seal number. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: change detection. Decision interval: from the last signed physical check to the current enquiry. Minimum evidence: valid baseline check, exact asset mapping, continuous enough event sequence, current functional test and authorised opening or maintenance records. Method: compare baseline and current state, list change times and match authorised intervals; label explained, unexplained-observed, gap-crossed or not assessable. Uncertainty: event loss and clock drift can hide or misplace a short state change. Safe failure: do not assert tampering; require a new signed physical check and preserve only authorised evidence.

AUTHORITATIVE SUPPORTING DATA

Current owners: the asset custodian owns the signed check and authorised opening; Facilities or technical owners hold maintenance; Security owns incident classification. Precedence: the signed physical check and owner-approved opening record lead; telemetry shows a state change only and cannot establish tampering. Time discipline: display effective, observed and retrieved times; show check time, change observed time, authorised-use effective time and retrieval time; stop analysis across event gaps. Permissions and provenance: Restrict key-holder, lock, asset and restricted-zone details to authorised custodians and Security roles; preserve transaction and work-order lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: show unexplained differences and refer them to the custodian and Security Duty Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not infer who changed the state, inspect protected contents, declare tampering or wrongdoing, or command an investigation or response. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Provides a bounded timeline for the custodian to reconcile authorised use and arrange a physical inspection.



keys, locks, assets and restricted areas

SO-041 to SO-050 | ten operational questions

SO-049

KEYS, LOCKS, ASSETS AND RESTRICTED AREAS

CONTROL REQUESTS

DIAGNOSIS

STAKEHOLDER QUESTION

Which lock changes, key cancellations or access-profile requests remain outstanding, and what verified dependency blocks each one?

SENSORS AND TELEMETRY

Proposed evidence: read-only work-order and access-request states, approval dependencies, controller synchronisation status, lock or key record status and technical service health; no credential content beyond authorised metadata. Coverage: requests affecting Abacws doors, keys or access profiles in the authorised Security scope. Sampling and aggregation: retrieve on demand and at handover; event-driven workflow updates with five-minute technical health summaries. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (request-to-asset mapping check, workflow-state validation, controller synchronisation test and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a workflow status may lag physical work, while technical success does not prove approval or complete implementation. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: diagnosis. Decision interval: the current request-management and handover interval. Minimum evidence: current request, required approvals, exact asset or profile mapping, dependency states, completion evidence and any valid exception. Method: trace each request through approval, physical, configuration and verification stages; label the first evidenced blocker and all unverified dependencies. Uncertainty: parallel work and delayed synchronisation can make the apparent blocker temporary. Safe failure: do not infer completion or failure; show the last confirmed stage, owner and missing evidence and leave action to the responsible owner.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Access Control Manager owns profile and cancellation decisions; the key custodian and Facilities lock owner hold physical changes; service-desk owners hold workflow status. Precedence: current authorised approval and owner completion evidence lead; telemetry cannot approve, cancel or close a request. Time discipline: display effective, observed and retrieved times; show request effective and due times, latest owner update, technical observation and retrieval time; mark superseded or withdrawn requests accordingly. Permissions and provenance: Restrict key-holder, lock, asset and restricted-zone details to authorised custodians and Security roles; preserve transaction and work-order lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: keep approval, physical work and system-synchronisation conflicts separate and refer them to the relevant owners; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not approve, cancel, implement or close a request, create access rights, operate locks or disclose sensitive profile or key detail. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives officers a precise owner and dependency to chase when a protective change remains incomplete.

SO-050

KEYS, LOCKS, ASSETS AND RESTRICTED AREAS

RESTRICTED CLOSE

SYNTHESIS

STAKEHOLDER QUESTION

Can the restricted-room secure-close checklist be evidenced without inferring that the room is vacant?

SENSORS AND TELEMETRY

Proposed evidence: door and latch state, approved lock status, key or cabinet reconciliation, fixed enclosure states and signed manual checklist items; deliberately exclude occupancy sensing for the close conclusion. Coverage: only assets and checks listed in the current restricted-room close procedure. Sampling and aggregation: event states through the close window, a final snapshot, and manual confirmations at their signed observed times. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (door-latch functional test, lock-state test, key mapping check, enclosure test, checklist integrity and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: closed and reconciled states do not prove vacancy, absence of people, absence of hazards or overall security. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: structured synthesis. Decision interval: the close window and immediate handover. Minimum evidence: the complete current checklist, exact asset mapping, healthy supporting evidence for monitored items, signed manual checks and all active exceptions. Method: return item-level confirmed, observed, conflicting, restricted and unverified states and explicitly state that vacancy is not assessed. Uncertainty: later access, delayed logs and blind checks can invalidate a snapshot. Safe failure: state close not assessable when any mandatory item is missing; require the named owner or physical check without inferring occupancy.

AUTHORITATIVE SUPPORTING DATA

Current owners: the restricted-room owner owns the close procedure; Security owns the shift record; Access Control, Facilities and key custodians own supporting asset states. Precedence: the current owner-approved checklist and any competent incident instruction lead; telemetry supports individual items only. Time discipline: display effective, observed and retrieved times; use the checklist version effective for the close, show observation and retrieval times and invalidate status after later access or fault. Permissions and provenance: Restrict key-holder, lock, asset and restricted-zone details to authorised custodians and Security roles; preserve transaction and work-order lineage; retain owner role, record or case ID, version and extraction path. Conflict handling: show each item conflict and refer it to the room owner and Security Duty Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not infer vacancy, inspect research activity or contents, certify the room secure, control locks or alarms, or conceal an unresolved item. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Supports a defensible close record while avoiding a false claim about whether anyone remains inside.

6

out-of-hours work, lone working and escorts

SO-051 to SO-060 | ten operational questions

SO-051 OUT-OF-HOURS WORK, LONE WORKING AND ESCORTS

WORK AUTHORISATIONS

LOOKUP

STAKEHOLDER QUESTION

Which out-of-hours activities are currently authorised for Abacws, and which entries remain incomplete, expired or unconfirmed?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required to establish authorisation; mapped entrance door state, fixed check-in terminal status and anonymous zone-presence totals may provide bounded operational context. Coverage: only activities, entrances and zones named in current out-of-hours permits, bookings or work orders. Sampling and aggregation: retrieve at shift briefing and before each activity window; door events at source resolution and anonymous presence in five-minute bands. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (permit-to-location mapping check, check-in terminal functional test, door-state test and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: telemetry cannot identify a worker, prove attendance or create authorisation, and scheduled activity may be cancelled informally. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup and reconciliation. Decision interval: the current shift and each proposed activity window. Minimum evidence: a current owner-approved activity record, purpose, exact location, permitted time, responsible contact, access and escort conditions and any incident restriction. Method: return authorised-current, future, expired, incomplete, conflicting, restricted or not found; attach telemetry only as separate context. Uncertainty: late cancellations and manual changes may not reach connected systems immediately. Safe failure: state no confirmed authorisation when the owner record is absent or conflicted and direct the enquiry to the named sponsor or Duty Manager.

AUTHORITATIVE SUPPORTING DATA

Current owners: the activity sponsor, Facilities work-order owner, visitor or contractor owner, Security Duty Manager and Access Control Manager. Precedence: the latest authenticated permit, booking or owner instruction effective now leads; incident restrictions override it, and telemetry cannot grant access. Time discipline: display effective, observed and retrieved times; show authorisation effective and expiry times, observation times and retrieval time; treat unsigned, draft, expired or superseded records as invalid. Permissions and provenance: Restrict visitor, contractor, lone-working and escort details to authorised operational roles; show only the minimum identity fields from owner records when necessary; retain owner role, record or case ID, version and extraction path. Conflict handling: show owner, time and location conflicts and refer them to the activity sponsor and Duty Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not grant admission, infer presence or identity from sensor activity, approve work, waive conditions or disclose unnecessary visitor or contractor details. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets officers distinguish a current authorised activity from a record that needs sponsor confirmation before procedure is applied.

SO-052 OUT-OF-HOURS WORK, LONE WORKING AND ESCORTS

CHECK-IN EVENTS

RULE COMPARISON

STAKEHOLDER QUESTION

Which required lone-worker check-ins are current, due, overdue or not assessable under the authorised procedure?

SENSORS AND TELEMETRY

Proposed evidence: manual call, secure web form or fixed check-in point recording an activity-level confirmation and time; no continuous tracking, device identifier, audio analysis or inferred location. Coverage: only authorised lone-working activities and check-in channels named in the current procedure. Sampling and aggregation: one confirmation per required interval, reported to the nearest minute; retain no movement sequence beyond the authorised check-in record. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (channel end-to-end functional test, activity-to-check-in mapping, duplicate-event test and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a check-in does not prove safety or exact location, and a missing event may reflect communications failure or delayed entry. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: rule comparison. Decision interval: each required check-in window and current handover point. Minimum evidence: current activity authorisation, check-in schedule, accepted channel, complete event sequence, channel health and any valid exception. Method: compare accepted check-in events with due windows and label current, due, overdue-confirmed, channel-unhealthy, restricted or not assessable. Uncertainty: clock error, duplicate events and delayed submission can affect status near a deadline. Safe failure: do not mark overdue solely from an unhealthy channel; show the missing confirmation and follow the current human escalation procedure.

AUTHORITATIVE SUPPORTING DATA

Current owners: the lone-working procedure owner and activity sponsor define required intervals; the Security Duty Manager owns operational handling; communication owners hold channel health. Precedence: the current authorised procedure and any competent emergency instruction lead; sensor or system silence cannot determine a person's condition. Time discipline: display effective, observed and retrieved times; show procedure effective time, each check-in observed time and retrieval time; apply authorised pauses or amended intervals only when recorded. Permissions and provenance: Restrict visitor, contractor, lone-working and escort details to authorised operational roles; show only the minimum identity fields from owner records when necessary; retain owner role, record or case ID, version and extraction path. Conflict handling: show procedure, activity and channel conflicts and refer them to the Duty Manager and lone-working owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not infer safety, distress, exact location, identity or intent from a check-in or its absence, and do not dispatch or contact emergency services automatically. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets the Duty Manager apply the authorised lone-working procedure with a clear distinction between overdue confirmation and channel failure.

6

out-of-hours work, lone working and escorts

SO-051 to SO-060 | ten operational questions

SO-053 OUT-OF-HOURS WORK, LONE WORKING AND ESCORTS

ESCORT CONDITIONSLOOKUP

STAKEHOLDER QUESTION

Which visitor or contractor records carry a confirmed escort condition, and what authorised time and zone limits apply?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required; use owner-approved visitor, contractor, permit and access-condition records, with optional entrance state only as operational context. Coverage: the specific visit or work activity and zones covered by its current authorisation. Sampling and aggregation: retrieve before arrival, at handover and after an owner change; no person movement data. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (record-to-visit mapping check, condition-field completeness test, entrance-state functional test and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a booking may be current while an escort condition is missing, changed or recorded in a separate owner system. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup. Decision interval: before admission and throughout the authorised visit window. Minimum evidence: current visit or work record, sponsor, purpose, zone scope, start and end time, escort condition, authorised exception and responsible contact. Method: return the owner-confirmed escort requirement and limits with evidence status; do not derive a condition from role, organisation or past visits. Uncertainty: late sponsor changes and separate permit systems can leave temporary gaps. Safe failure: state the condition not confirmed and route to the sponsor or Access Control owner; do not admit or waive the requirement.

AUTHORITATIVE SUPPORTING DATA

Current owners: the visit sponsor or contractor manager owns the visit purpose; Access Control owns zone conditions; Security owns operational escort handling. Precedence: the latest authenticated sponsor and access-condition records effective for the visit lead; an open door or prior visit cannot waive an escort. Time discipline: display effective, observed and retrieved times; show condition effective and expiry times, any observation time and retrieval time; reject superseded or unsigned exceptions. Permissions and provenance: Restrict visitor, contractor, lone-working and escort details to authorised operational roles; show only the minimum identity fields from owner records when necessary; retain owner role, record or case ID, version and extraction path. Conflict handling: show conflicting sponsor, permit and access conditions and refer them to the sponsor, Access Control Manager and Duty Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not grant access, approve or waive an escort, expose unnecessary personal details, infer trustworthiness or track the visitor or contractor. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives officers the exact escort, time and zone condition to apply under the current access procedure.

SO-054 OUT-OF-HOURS WORK, LONE WORKING AND ESCORTS

ESCORT ROUTECALCULATION

STAKEHOLDER QUESTION

Is an approved escort route usable for the authorised activity, and which segments still require a physical check?

SENSORS AND TELEMETRY

Proposed evidence: mapped door and lock states, lift availability, official closures and signed checks for uninstrumented segments; optional anonymous route counts provide demand context only. Coverage: the owner-approved escort route and alternative routes within the activity's authorised zones. Sampling and aggregation: asset events with five-minute latest-state age, manual checks at signed time and anonymous counts in five-minute bands. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (door and lift functional tests, route-to-asset mapping, count-sensor check and cross-system clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: temporary obstruction, individual access need and stewarding condition may not be visible, and telemetry cannot authorise a different zone. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: calculation. Decision interval: immediately before the escorted movement and during any authorised change. Minimum evidence: a current approved route, exact zone and asset mapping, valid access scope, official closures, healthy door or lift evidence and checks for blind segments. Method: evaluate each authorised route end to end and list usable-evidenced, interrupted and unverified options with the first limiting segment. Uncertainty: rapid door, lift or closure changes can invalidate the result. Safe failure: return no route option when any mandatory segment lacks current evidence or permission; require authorised owner confirmation or a physical check.

AUTHORITATIVE SUPPORTING DATA

Current owners: the activity sponsor, Access Control Manager, Facilities route and lift owners, accessibility owner and Security Duty Manager. Precedence: the current approved escort route, access limits and official closures lead; telemetry can only qualify a permitted option. Time discipline: display effective, observed and retrieved times; use route and access records effective for the whole activity window; the May 2021 floor plan cannot establish the current route. Permissions and provenance: Restrict visitor, contractor, lone-working and escort details to authorised operational roles; show only the minimum identity fields from owner records when necessary; retain owner role, record or case ID, version and extraction path. Conflict handling: show each segment conflict and refer it to the route owner, activity sponsor and Duty Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not grant access, direct or track the escorted party, choose an unapproved route, operate doors or lifts or certify accessibility or safety. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets the escorting officer identify the exact route check or owner decision needed before movement.

6

out-of-hours work, lone working and escorts

SO-051 to SO-060 | ten operational questions

SO-055

OUT-OF-HOURS WORK, LONE WORKING AND ESCORTS

CONTROL DEPENDENCIES

DIAGNOSIS

STAKEHOLDER QUESTION

Which current service outages materially affect the controls required for approved out-of-hours work?

SENSORS AND TELEMETRY

Proposed evidence: read-only health from access control, alarm, fixed communications, relevant lighting, lift and power systems, linked to the approved work-control checklist; no user activity content. Coverage: only systems and assets explicitly required by the current out-of-hours activity control plan. Sampling and aggregation: event-driven faults and one-minute heartbeats with five-minute summaries across the activity window. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (end-to-end service test, asset dependency mapping, power and network health test and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a healthy headline service can hide local impairment, while a degraded system may have an owner-approved temporary control. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: diagnosis. Decision interval: before and during the approved out-of-hours activity. Minimum evidence: current control checklist, exact service dependencies, owner-confirmed outage or recovery, recent functional tests and any approved temporary control. Method: trace each required control to its service and local asset; label available-evidenced, degraded-with-owner-control, unavailable, restricted or not assessable. Uncertainty: incomplete dependency mapping and intermittent faults can misstate materiality. Safe failure: show the failed control and owner; do not recommend that work start, continue or stop when the authorised decision maker is absent.

AUTHORITATIVE SUPPORTING DATA

Current owners: the activity sponsor and control-plan owner, Facilities and IT service owners, Access Control Manager, Safety owner and Security Duty Manager. Precedence: the current owner-approved work controls and service status lead; telemetry cannot authorise work to start or continue. Time discipline: display effective, observed and retrieved times; show control-plan effective time, outage start, latest observation and retrieval time; expire a recovered state only after owner confirmation where required. Permissions and provenance: Restrict visitor, contractor, lone-working and escort details to authorised operational roles; show only the minimum identity fields from owner records when necessary; retain owner role, record or case ID, version and extraction path. Conflict handling: show dependency and temporary-control conflicts and refer them to the activity sponsor and responsible service owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not authorise or prohibit work, create a substitute control, operate systems, promise availability or certify that remaining controls are sufficient. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives the sponsor and Duty Manager a precise control dependency to resolve before applying the current work procedure.

SO-056

OUT-OF-HOURS WORK, LONE WORKING AND ESCORTS

ANONYMOUS PRESENCE

OBSERVATION

STAKEHOLDER QUESTION

Where is there unexpected anonymous presence evidence outside scheduled use, and how incomplete or ambiguous is that evidence?

SENSORS AND TELEMETRY

Proposed evidence: non-imaging passive infrared or time-of-flight zone presence, anonymous doorway counts and door contact events; no camera, microphone, device identifiers or cross-zone path reconstruction. Coverage: only commissioned public or service zones with an owner-approved out-of-hours monitoring purpose. Sampling and aggregation: binary presence or counts sampled at one second and aggregated to one- and five-minute zone bands; retain no individual sequence. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (empty-zone and occupied-zone functional test, doorway count comparison, clock alignment and false-trigger check for HVAC or environmental effects), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: cleaning, authorised work, animals, heat sources, sensor spill and blind areas can create false or missed presence. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: observation and comparison. Decision interval: rolling five-minute intervals outside scheduled use. Minimum evidence: current schedules and authorised activities, exact sensor-zone mapping, healthy coverage, calibrated error limits and aligned clocks. Method: compare anonymous zone evidence with expected-use intervals; label expected, unexpected-observed, possible spill, source-unhealthy or not assessable and show evidence bounds. Uncertainty: a single sensor event is weak evidence and cannot distinguish authorised from unauthorised presence. Safe failure: do not issue a presence conclusion from one unhealthy or uncovered source; show the zone, time, uncertainty and current manual verification route.

AUTHORITATIVE SUPPORTING DATA

Current owners: the building opening and scheduling owners define expected use; the activity sponsor and Security Duty Manager own authorised exceptions; the sensor owner holds measurement quality. Precedence: current authorised activity and opening records lead; anonymous presence cannot establish trespass, identity, intent or exact location. Time discipline: display effective, observed and retrieved times; show schedule effective time, observation interval and retrieval time; exclude periods with sensor faults or changed zone geometry. Permissions and provenance: Restrict visitor, contractor, lone-working and escort details to authorised operational roles; show only the minimum identity fields from owner records when necessary; retain owner role, record or case ID, version and extraction path. Conflict handling: show schedule, activity and sensor conflicts and refer them to the Duty Manager and relevant owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not identify or track people, infer trespass, threat or intent, inspect activity content, or dispatch officers or trigger access action. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Provides a privacy-preserving prompt for an authorised physical check without converting anonymous sensing into a suspicion claim.



out-of-hours work, lone working and escorts

SO-051 to SO-060 | ten operational questions

SO-057

OUT-OF-HOURS WORK, LONE WORKING AND ESCORTS

ACTIVITY CONFIRMATIONS

RECONCILIATION

STAKEHOLDER QUESTION

Are the required arrival and departure confirmations complete for each authorised out-of-hours activity?

SENSORS AND TELEMETRY

Proposed evidence: owner-approved sign-in and sign-out records or fixed check-in terminal events linked to an activity reference; anonymous door counts may show only aggregate context. Coverage: the activities and confirmation points specified in the current out-of-hours procedure. Sampling and aggregation: one event per required arrival or departure, at minute resolution; no continuous movement history. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (terminal functional test, activity-reference validation, duplicate-event check, door-count calibration and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: an aggregate door event cannot confirm an individual arrival or departure, and manual records can be entered late. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: reconciliation. Decision interval: activity start, planned finish and shift handover. Minimum evidence: current activity authorisation, required confirmation method, accepted arrival and departure records, valid exceptions and channel health. Method: compare each authorised activity with its required confirmations at activity level; label complete, arrival-only, departure-missing, exception, channel-unhealthy or not assessable. Uncertainty: late entries and early or extended work can change status. Safe failure: do not infer departure from door counts or silence; carry the missing confirmation with the sponsor and current procedure.

AUTHORITATIVE SUPPORTING DATA

Current owners: the activity sponsor owns expected participants and completion; Security owns the operational record; visitor, contractor or Facilities owners hold the sign-in source. Precedence: the authorised sign-in or sign-out record leads; sensor counts cannot create a person-level confirmation. Time discipline: display effective, observed and retrieved times; show activity window, recorded event time and retrieval time; treat confirmations outside the owner tolerance or after record expiry as exceptional. Permissions and provenance: Restrict visitor, contractor, lone-working and escort details to authorised operational roles; show only the minimum identity fields from owner records when necessary; retain owner role, record or case ID, version and extraction path. Conflict handling: show missing or conflicting records and refer them to the activity sponsor and Duty Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not infer a person's location or safety, disclose identity beyond authorised need, close the activity record or dispatch a response automatically. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets the Duty Manager identify the exact missing confirmation before closing the activity or transferring it to the next shift.

SO-058

OUT-OF-HOURS WORK, LONE WORKING AND ESCORTS

AUTHORISATION TIMES

CALCULATION

STAKEHOLDER QUESTION

Which permits, access approvals or escort authorisations expire before the planned work is due to finish?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required; use current permit, work-order, access and escort records with their effective and expiry times, plus owner-approved planned finish. Coverage: each authorised out-of-hours activity and the permissions explicitly attached to it. Sampling and aggregation: calculate at approval check, arrival and after any time change; no person movement data. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (record-link validation, time-zone and daylight-saving check, source-clock comparison and duplicate-authorisation test), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: planned finish can change, and separate authorisations may use different time conventions or conditions. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: calculation. Decision interval: before the activity begins and after any approved time change. Minimum evidence: current activity finish, every mandatory permission and condition, aligned time basis and any authorised extension. Method: calculate remaining authorised time for each dependency and identify those ending before planned finish; label confirmed gap, possible gap, complete or not assessable. Uncertainty: late plan changes and mismatched time zones can create false gaps. Safe failure: do not assume extension or truncate the activity automatically; show the first expiry and owner who must decide.

AUTHORITATIVE SUPPORTING DATA

Current owners: the permit owner, activity sponsor, Access Control Manager, escort owner and Security Duty Manager. Precedence: each permission owner controls its effective period; the earliest mandatory expiry limits the evidenced authorisation, and telemetry cannot extend it. Time discipline: display effective, observed and retrieved times; display all effective, expiry, planned-finish and retrieval times in one time basis; reject unsigned or superseded extensions. Permissions and provenance: Restrict visitor, contractor, lone-working and escort details to authorised operational roles; show only the minimum identity fields from owner records when necessary; retain owner role, record or case ID, version and extraction path. Conflict handling: show conflicting finish or expiry times and refer them to the activity sponsor and relevant permission owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not extend, approve or cancel a permit or access right, grant continued admission, change an escort condition or direct work to stop. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives the sponsor time to resolve a permission gap before it becomes an out-of-hours exception.

6

out-of-hours work, lone working and escorts

SO-051 to SO-060 | ten operational questions

SO-059 OUT-OF-HOURS WORK, LONE WORKING AND ESCORTS

PRE-START GATERULE COMPARISON

STAKEHOLDER QUESTION

Which controls, contacts and evidence must be confirmed before an escort or lone-working period begins?

SENSORS AND TELEMETRY

Proposed evidence: fixed communication-point and issued-device test status, authorised check-in channel health, route-asset states and signed manual control confirmations; no tracking or content analysis. Coverage: only controls named in the current escort or lone-working procedure for the specific activity and zone. Sampling and aggregation: check during the pre-start window; device and service health in one-minute summaries and manual confirmations at signed time. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (communication end-to-end test, route asset functional test, checklist integrity, contact validation and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a passed equipment test does not prove future communication, personal safety or that every physical condition is acceptable. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: rule comparison. Decision interval: the defined pre-start window. Minimum evidence: current activity authorisation, responsible contact, check-in method, escalation route, escort condition, approved route, required communication tests and permission validity. Method: test each required control separately and label confirmed, degraded with owner-approved alternative, missing, conflicting, restricted or not assessable. Uncertainty: conditions can change immediately after the check and some controls depend on human readiness not represented in data. Safe failure: state pre-start evidence incomplete and name the missing owner or check; do not recommend that the period begin.

AUTHORITATIVE SUPPORTING DATA

Current owners: the lone-working or escort procedure owner, activity sponsor, Security Duty Manager, Safety owner and relevant service owners. Precedence: the current owner-approved control checklist and any competent emergency instruction lead; telemetry cannot approve the start. Time discipline: display effective, observed and retrieved times; show checklist effective time, each test or confirmation time and retrieval time; expire evidence at the owner-defined age or after a fault or route change. Permissions and provenance: Restrict visitor, contractor, lone-working and escort details to authorised operational roles; show only the minimum identity fields from owner records when necessary; retain owner role, record or case ID, version and extraction path. Conflict handling: show unresolved control conflicts and refer them to the procedure owner and Duty Manager; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not certify the activity safe to start, approve a substitute control, grant access, assign an escort, track a lone worker or issue an operational direction. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Provides a clear pre-start evidence checklist for the authorised sponsor and Duty Manager to apply.

SO-060 OUT-OF-HOURS WORK, LONE WORKING AND ESCORTS

ACTIVITY HANDOVERSYNTHESIS

STAKEHOLDER QUESTION

Which unresolved out-of-hours, lone-working or escort matters must the incoming shift inherit?

SENSORS AND TELEMETRY

Proposed evidence: read-only activity authorisations, check-in status, escort conditions, arrival or departure confirmations, control outages and current route or door states; no person path or communications content. Coverage: all active or unresolved out-of-hours activities affecting the current and incoming shifts. Sampling and aggregation: compile at handover and refresh on an owner update; preserve item timestamps and source links, not continuous movement data. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (cross-system activity mapping, connector retrieval test, channel heartbeat check and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: separate systems may update at different times, and a cleared sensor state does not resolve an owner record. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: structured synthesis. Decision interval: the current shift handover. Minimum evidence: every active or unresolved activity, sponsor, authorised time and zone, escort or lone-working condition, latest confirmation, current control gap and next update time. Method: assemble one evidence-labelled item per activity and separate owner facts, observations, restrictions and unknowns. Uncertainty: late departure, delayed confirmation and service recovery can change an item during handover. Safe failure: carry unresolved items with last valid evidence and owner; do not assume completion, safety or permission continuity.

AUTHORITATIVE SUPPORTING DATA

Current owners: the outgoing Duty Manager owns handover assembly; activity sponsors, permit owners, lone-working owners and escort owners retain source authority; the incoming Duty Manager accepts the record. Precedence: current owner status and competent emergency instruction override telemetry and earlier shift notes. Time discipline: display effective, observed and retrieved times; show authorisation effective and expiry times, latest check-in or confirmation, owner update, observation and retrieval times. Permissions and provenance: Restrict visitor, contractor, lone-working and escort details to authorised operational roles; show only the minimum identity fields from owner records when necessary; retain owner role, record or case ID, version and extraction path. Conflict handling: retain each conflict with its owners and route acceptance questions to the outgoing and incoming Duty Managers; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not close an activity, infer a person's location or welfare, extend permissions, allocate an escort or direct the incoming shift. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Ensures the incoming shift receives each live activity with a named owner, expiry point and exact unresolved control.

7

emergency coordination, closures and communications

SO-061 to SO-070 | ten operational questions

SO-061 EMERGENCY COORDINATION, CLOSURES AND COMMUNICATIONS

COMMAND SOURCE LOOKUP

STAKEHOLDER QUESTION

What official emergency state and authorised instructions are active for Abacws now?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required to establish authority; read-only fire-panel, building-alarm, utility and access-system states may be displayed as separately labelled observations. Coverage: the whole building or exact incident zones named by the competent authority. Sampling and aggregation: retrieve command updates immediately; sensor events at source resolution with one-minute current-state summaries. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (authoritative-feed retrieval test, instruction-version check, alarm-source functional test and clock alignment to the incident timeline), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a panel state does not declare an emergency, define its scope or prove that an instruction was received or followed. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup. Decision interval: the current emergency-command interval. Minimum evidence: an authenticated source, current state or instruction, effective time, scope, intended audience, version and permission to display it. Method: return only the current owner-issued state and instruction; attach equipment observations in a separate evidence block with time and health. Uncertainty: communications delay and rapidly changing command can make cached information obsolete. Safe failure: show no operational instruction when the authority chain or version is uncertain; identify the official channel and last valid message.

AUTHORITATIVE SUPPORTING DATA

Current owners: the competent emergency or incident commander, Fire Safety Manager, Security Duty Manager and institutional emergency communications owner. Precedence: the latest authenticated competent-authority instruction effective now overrides normal schedules, local summaries, telemetry and earlier messages. Time discipline: display effective, observed and retrieved times; display instruction effective time, each observation time and retrieval time; withdraw superseded instructions from the current view while preserving authorised lineage. Permissions and provenance: Apply incident-command, emergency-plan, safety and communications permissions; share audience-specific instructions only through approved channels; retain owner role, record or case ID, version and extraction path. Conflict handling: show any competing instructions verbatim at the minimum permitted detail and refer them immediately to the competent authority; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not declare or end an emergency, reinterpret or issue instructions, infer conditions from alarms, dispatch resources or present telemetry as command authority. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives officers one traceable source for the current official position while keeping command with the competent authority.

SO-062 EMERGENCY COORDINATION, CLOSURES AND COMMUNICATIONS

CLOSURE REGISTER LOOKUP + OBSERVATION

STAKEHOLDER QUESTION

Which entrances, routes or zones are officially closed, and when was each closure last confirmed by its owner?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required to define a closure; door, barrier, lift and access-controller states at named closure points may show physical implementation. Coverage: only entrances, routes and zones explicitly listed in the current closure record and exact current spatial mapping. Sampling and aggregation: retrieve after every command update; asset events at source resolution with five-minute snapshots. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (closure-to-asset mapping validation, door or barrier functional test and clock alignment to the command timeline), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: an apparently open asset does not cancel a closure, and physical barriers or local conditions may not be instrumented. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup and observation. Decision interval: the current closure interval and every scheduled recheck. Minimum evidence: current closure instruction, scope, owner, effective and expected end or recheck time, authoritative mapping and any permitted implementation observations. Method: list each officially closed element with latest owner confirmation; show physical implementation separately as confirmed, inconsistent or unverified. Uncertainty: rapid command changes and incomplete asset mapping can create temporary inconsistency. Safe failure: retain the official closure when evidence conflicts and request owner confirmation; never infer reopening from an open door or recovered system.

AUTHORITATIVE SUPPORTING DATA

Current owners: the competent incident or closure owner, Security Duty Manager, Facilities route owner, Access Control Manager and accessibility owner. Precedence: the latest authenticated closure instruction effective now leads; telemetry, schedules and the May 2021 floor plan cannot create or remove a closure. Time discipline: display effective, observed and retrieved times; show closure effective time, owner confirmation time, observed asset time and retrieval time; mark closures without a current confirmation according to the owner rule. Permissions and provenance: Apply incident-command, emergency-plan, safety and communications permissions; share audience-specific instructions only through approved channels; retain owner role, record or case ID, version and extraction path. Conflict handling: show competing closure states and refer them to the competent authority and named route or asset owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not open, close or control an asset, remove or widen a closure, direct public movement or certify that a closed area is safe or empty. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets officers maintain consistent closure information and focus checks where physical state does not match the official instruction.

7

emergency coordination, closures and communications

SO-061 to SO-070 | ten operational questions

SO-063 EMERGENCY COORDINATION, CLOSURES AND COMMUNICATIONS

COMMS HEALTH DIAGNOSIS

STAKEHOLDER QUESTION

Which approved emergency communication channels and fixed points have current end-to-end health evidence?

SENSORS AND TELEMETRY

Proposed evidence: radio-network test results, fixed call-point heartbeats, public-address controller self-tests without audio capture, emergency-message gateway receipts and backup power state; no live content or user location. Coverage: the channels, zones and fixed communication points named in the current emergency communications plan. Sampling and aggregation: one-minute heartbeats, event-driven test results and owner-defined end-to-end test intervals. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (known-signal radio test, call-point activation test, message gateway loop test, backup power test and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a self-test does not prove intelligibility, user receipt, coverage under load or operation at every location. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: diagnosis. Decision interval: the current emergency state and each planned communications check. Minimum evidence: current approved channel list, exact zone mapping, recent end-to-end test, heartbeat, power and network dependencies and any active fault. Method: classify each channel or fixed point as tested-current, partially tested, degraded, unavailable or not assessable and state the untested layer. Uncertainty: intermittent coverage, acoustic conditions and emergency load are not fully represented. Safe failure: do not label a channel ready without the required end-to-end test; show the official fallback route from the current plan.

AUTHORITATIVE SUPPORTING DATA

Current owners: the emergency communications owner, IT and radio service owners, Facilities power owner, Fire Safety Manager and Security Duty Manager. Precedence: the current communications plan and owner-confirmed service status lead; telemetry cannot guarantee emergency performance or authorise channel use beyond the plan. Time discipline: display effective, observed and retrieved times; show latest full test, current observed health and retrieval times; expire readiness after the owner-defined age, fault or configuration change. Permissions and provenance: Apply incident-command, emergency-plan, safety and communications permissions; share audience-specific instructions only through approved channels; retain owner role, record or case ID, version and extraction path. Conflict handling: show channel and dependency conflicts and refer them to the emergency communications owner and technical service owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not listen to or analyse message content, track users, send or alter messages, guarantee receipt or coverage, or direct emergency communications. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets officers identify the authorised fallback channel and the exact technical owner when a primary route lacks evidence.

SO-064 EMERGENCY COORDINATION, CLOSURES AND COMMUNICATIONS

MUSTER SOURCES LOOKUP + ESTIMATE

STAKEHOLDER QUESTION

What assembly-point and muster information is current and authorised for this incident or exercise?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required for the official assembly instruction; optional anonymous directional counters at designated exits or assembly-zone boundaries may provide bounded totals without identity or path linking. Coverage: only assembly points, exits and zones specified by the current competent-authority instruction. Sampling and aggregation: retrieve instructions immediately; one-minute anonymous flow and occupancy estimates with explicit lower and upper bounds. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (assembly-point mapping check, exit counter direction test, manual count comparison and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: anonymous counts cannot establish who is accounted for, may double-count movement and may miss people using uninstrumented routes. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup and estimate. Decision interval: the current assembly or muster interval. Minimum evidence: current authorised assembly instruction, exact point mapping, permitted team-level muster records, healthy anonymous coverage if cited and known blind routes. Method: present official locations and instructions first; show team-level recorded status and anonymous count ranges separately, without matching people across sources. Uncertainty: movement, repeated crossings and incomplete routes can make counts unreliable. Safe failure: do not state that everyone is accounted for; show owner-confirmed team status, count limits and the official muster process.

AUTHORITATIVE SUPPORTING DATA

Current owners: the competent incident commander or exercise director owns the assembly instruction; Fire Safety and building emergency owners hold plans; team owners hold authorised muster records. Precedence: the current incident or exercise instruction leads; normal plan locations, telemetry and historical drawings cannot override it. Time discipline: display effective, observed and retrieved times; show instruction effective time, team-record update time, sensor observation interval and retrieval time; reject superseded assembly points. Permissions and provenance: Apply incident-command, emergency-plan, safety and communications permissions; share audience-specific instructions only through approved channels; retain owner role, record or case ID, version and extraction path. Conflict handling: show plan, command and count conflicts and refer them to the competent authority and muster owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not identify or track evacuees, infer an individual's location, declare a person missing or accounted for, or change an assembly instruction. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives officers the current official muster source and a bounded aggregate context without creating person tracking.

7

emergency coordination, closures and communications

SO-061 to SO-070 | ten operational questions

SO-065

EMERGENCY COORDINATION, CLOSURES AND COMMUNICATIONS

LIFE-SAFETY STATES

DIAGNOSIS

STAKEHOLDER QUESTION

Which building systems are owner-confirmed as degraded in a way relevant to current emergency coordination?

SENSORS AND TELEMETRY

Proposed evidence: read-only fire detection, alarm, smoke-control, emergency-lighting, lift, access-control, power, water and fixed communication states only where the system owner permits and mapping is verified. Coverage: the systems and zones named in the current emergency plan or incident scope. Sampling and aggregation: event-driven states and one-minute heartbeats with five-minute summaries; preserve every gap and test or maintenance interval. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (owner-approved functional test, input-output sequence test, dependency mapping and clock alignment to the incident timeline), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: system telemetry may be partial, delayed or designed for maintenance rather than operational safety decisions. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: diagnosis. Decision interval: the current emergency-command interval and each material system update. Minimum evidence: exact system and zone mapping, current owner status, recent valid test, dependency health, active maintenance state and authorised disclosure. Method: trace confirmed degradation through verified dependencies and report only the evidenced operationally relevant scope, confidence and blind areas. Uncertainty: complex system modes and hidden local overrides can limit interpretation. Safe failure: show the owner-confirmed state and unknown scope; do not infer safety impact or recommend emergency action beyond current instructions.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Fire Safety Manager, Facilities system owners, Access Control Manager, IT service owner and competent incident commander. Precedence: the competent authority and system owner's confirmed status lead; raw panel or device telemetry cannot certify system function or determine emergency strategy. Time discipline: display effective, observed and retrieved times; show status effective time, observation time, latest owner confirmation and retrieval time; mark any source stale after the owner-defined test or heartbeat age. Permissions and provenance: Apply incident-command, emergency-plan, safety and communications permissions; share audience-specific instructions only through approved channels; retain owner role, record or case ID, version and extraction path. Conflict handling: show system-owner and telemetry conflicts and route them to the competent authority and relevant system owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not certify life-safety performance, declare a building safe or unsafe, operate systems, reinterpret alarms or issue evacuation or closure directions. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Provides incident command and officers with a precise owner-confirmed system limitation and its evidenced scope.

SO-066

EMERGENCY COORDINATION, CLOSURES AND COMMUNICATIONS

ACCESSIBILITY ARRANGEMENTS

LOOKUP

STAKEHOLDER QUESTION

Which officially provided accessibility arrangements and assistance points are current for this closure or evacuation?

SENSORS AND TELEMETRY

Proposed evidence: no personal sensing is required; use approved assistance-point status, accessible-route and lift states, fixed communication-point health and authorised team-level availability; no disability inference or individual tracking. Coverage: only arrangements, routes and points named by the current accessibility or incident instruction. Sampling and aggregation: retrieve on every command update; asset states in one-minute summaries and team-level availability at owner-recorded time. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (route and assistance-point mapping, lift and call-point functional tests and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: telemetry cannot represent individual needs, personal emergency plans, human assistance quality or every physical obstacle. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup. Decision interval: the current closure or evacuation interval. Minimum evidence: current authorised arrangement, exact assistance-point and route mapping, owner contact, relevant asset state, valid time and permission for the intended audience. Method: return official arrangements and separately label asset or team evidence as current, degraded, unverified or restricted. Uncertainty: individual needs and short-lived route conditions may not be represented. Safe failure: provide no personal or inferred assistance advice; show the official contact and mark any route or point without current evidence not assessable.

AUTHORITATIVE SUPPORTING DATA

Current owners: the competent incident commander, accessibility and inclusion owner, Fire Safety Manager, Facilities lift owner and Security Duty Manager. Precedence: the current incident and accessibility instruction leads; personal emergency arrangements remain controlled by their owner and are not inferred or broadly disclosed. Time discipline: display effective, observed and retrieved times; show instruction effective time, asset observation time, team availability update and retrieval time; remove superseded points from the current display. Permissions and provenance: Apply incident-command, emergency-plan, safety and communications permissions; share audience-specific instructions only through approved channels; retain owner role, record or case ID, version and extraction path. Conflict handling: show arrangement and asset conflicts and refer them to the accessibility owner and competent authority; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not disclose disability or personal emergency-plan details, infer who needs help, promise assistance, direct evacuation or certify route accessibility. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets officers communicate the current authorised assistance arrangements and flag a specific unavailable point to the responsible owner.

Talking Abacws | Security Officers | Category 7

36 / 46

7

emergency coordination, closures and communications

SO-061 to SO-070 | ten operational questions

SO-067 EMERGENCY COORDINATION, CLOSURES AND COMMUNICATIONS

TEAM RECEIPTS

COMPARISON

STAKEHOLDER QUESTION

Which required internal teams have provided a current team-level receipt acknowledgement for the authorised emergency message?

SENSORS AND TELEMETRY

Proposed evidence: approved messaging-system delivery and team-level receipt records, fixed terminal health and channel gateway status; no individual location, read-content analysis or personal device tracking. Coverage: only teams and channels named in the current emergency communications plan. Sampling and aggregation: event-driven delivery and receipt timestamps with one-minute status summaries; retain team-level evidence only. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (message-version integrity check, gateway loop test, team-recipient mapping and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: delivery or receipt does not prove comprehension, action or that every team member received the message. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: comparison. Decision interval: the current message acknowledgement window. Minimum evidence: authorised message version, required team list, approved channels, valid delivery records, team-level acknowledgements and current channel health. Method: compare required teams with acknowledgements for the exact message; label acknowledged, delivered-not-acknowledged, delivery-failed, restricted or not assessable. Uncertainty: manual acknowledgements and gateway delays can appear after the first check. Safe failure: show the missing team-level acknowledgement and official fallback contact; do not infer receipt, understanding or action.

AUTHORITATIVE SUPPORTING DATA

Current owners: the competent emergency communications owner defines the recipient list and message; team leads own team-level acknowledgement; IT owns delivery infrastructure. Precedence: the current authorised message version and recipient list lead; system receipts cannot create an instruction or prove compliance. Time discipline: display effective, observed and retrieved times; show message effective time, send, delivery, team acknowledgement and retrieval times; invalidate receipts tied to a superseded message. Permissions and provenance: Apply incident-command, emergency-plan, safety and communications permissions; share audience-specific instructions only through approved channels; retain owner role, record or case ID, version and extraction path. Conflict handling: show recipient-list and receipt conflicts and refer them to the communications owner and relevant team lead; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not identify or track individuals, infer comprehension or compliance, send reminders automatically, alter the recipient list or issue operational directions. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets the communications owner focus authorised follow-up on teams lacking a verified receipt for the current message.

SO-068 EMERGENCY COORDINATION, CLOSURES AND COMMUNICATIONS

MESSAGE CONTROL

LOOKUP

STAKEHOLDER QUESTION

What exact public-facing message version is currently authorised, for which audience and approved channels?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required; use authorised message text, version, audience, channel, approval and publication-receipt metadata; no microphone, social-media content or public reaction analysis. Coverage: the specific emergency, closure or service message and its approved audiences and channels. Sampling and aggregation: retrieve immediately before use and after every owner update; publication receipts at event time. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (version-hash check, approver validation, audience-channel mapping and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a publication receipt does not prove that the audience saw, heard or understood the message. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: lookup and version comparison. Decision interval: immediately before each publication or verbal use. Minimum evidence: current approved wording, version, audience, channel, effective time, approver and any expiry or replacement instruction. Method: return the exact authorised version and permitted channel list; compare any proposed text and mark differences without rewriting it. Uncertainty: rapid updates and local copies can leave stale text in circulation. Safe failure: show no message when the current version or approval is uncertain; identify the official source and last valid version.

AUTHORITATIVE SUPPORTING DATA

Current owners: the competent incident or communications owner, institutional communications owner, Security Duty Manager and legal or information owner where required. Precedence: the latest authenticated approved message effective now leads; earlier drafts, local paraphrases and telemetry cannot replace it. Time discipline: display effective, observed and retrieved times; show approval effective time, publication time and retrieval time; remove superseded wording from the current operational view. Permissions and provenance: Apply incident-command, emergency-plan, safety and communications permissions; share audience-specific instructions only through approved channels; retain owner role, record or case ID, version and extraction path. Conflict handling: withhold unresolved versions and refer conflicts to the competent communications owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not publish, edit, paraphrase or translate the message, infer public reaction, broaden the audience or promise an outcome. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Helps officers use the correct authorised wording and avoid circulating a superseded or mis-scoped message.

7

emergency coordination, closures and communications

SO-061 to SO-070 | ten operational questions

SO-069 EMERGENCY COORDINATION, CLOSURES AND COMMUNICATIONS

RELEASE CHECKLIST

RULE COMPARISON

STAKEHOLDER QUESTION

Which owner-defined evidence items are still missing before the competent authority can consider lifting a closure?

SENSORS AND TELEMETRY

Proposed evidence: read-only system states, work-order completion, signed physical checks, communication status and owner confirmations named in the current closure-release checklist. Coverage: only closure zones, dependencies and evidence items specified by the competent authority. Sampling and aggregation: event-driven status with five-minute summaries and manual checks at signed time; no inference beyond named items. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (functional test for each cited system, checklist-to-asset mapping, completion-record validation and clock alignment), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: satisfied telemetry conditions do not prove hazards are absent or that competent owners have accepted the evidence. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: rule comparison. Decision interval: the current closure-release consideration window. Minimum evidence: the current checklist, exact scope, mandatory evidence, owner acceptance, valid tests, active exceptions and any recheck interval. Method: evaluate each item separately as accepted, observed-not-accepted, failed, missing, restricted or not assessable; do not calculate an overall safety score. Uncertainty: conditions can change after a check and some criteria require professional judgement outside the service. Safe failure: show the missing or unaccepted item and its owner; do not recommend or imply that the closure should be lifted.

AUTHORITATIVE SUPPORTING DATA

Current owners: the competent authority owns the release decision and checklist; Fire Safety, Facilities, Access Control, Safety and Security owners hold individual evidence items. Precedence: the current competent-authority checklist and explicit owner acceptance lead; telemetry cannot satisfy a sign-off requirement by itself. Time discipline: display effective, observed and retrieved times; show checklist effective time, each evidence observation or owner-confirmation time and retrieval time; invalidate items after a new fault or command change. Permissions and provenance: Apply incident-command, emergency-plan, safety and communications permissions; share audience-specific instructions only through approved channels; retain owner role, record or case ID, version and extraction path. Conflict handling: show conflicting evidence and refer it to the competent authority and responsible item owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not lift or relax a closure, certify safety, substitute telemetry for professional judgement, operate systems or issue reopening instructions. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives the competent authority and officers a precise evidence-gap list while preserving the human release decision.

SO-070 EMERGENCY COORDINATION, CLOSURES AND COMMUNICATIONS

INCIDENT EVIDENCE

RECOMMENDATION

STAKEHOLDER QUESTION

What minimum authorised evidence should be preserved for incident learning and accountability?

SENSORS AND TELEMETRY

Proposed evidence: owner instructions, message versions, case and alarm timestamps, mapped asset-state snapshots, source health, anonymous aggregates and signed operational records already collected for the authorised purpose; no new surveillance. Coverage: the incident scope and time window defined by the incident and information owners. Sampling and aggregation: preserve original source timestamps and the coarsest adequate authorised aggregates; avoid continuous person or movement records. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (lineage and checksum validation, clock-offset record, completeness test and retention-control test), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: source gaps, asynchronous clocks and later owner classification can limit reconstruction, while aggregate data can still be sensitive in small groups. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: recommendation limited to evidence preservation. Decision interval: before handover, export, expiry or source-system overwrite. Minimum evidence: defined incident purpose and scope, field-level necessity, source permission, lineage, clock information, retention or hold rule and authorised recipient. Method: map each evidence item to the decision or accountability need; recommend preserve, aggregate, redact, withhold or expire with the governing rule. Uncertainty: future legal or technical needs may be uncertain and holds can change. Safe failure: make no preservation recommendation without a current owner rule; identify the source at risk and route the decision to the information owner.

AUTHORITATIVE SUPPORTING DATA

Current owners: the incident information owner, competent authority, Security information owner, system owners and Data Protection or information-governance owner. Precedence: legal holds, incident purpose and minimum-necessary rules lead; operational convenience cannot expand fields, retention or recipients. Time discipline: display effective, observed and retrieved times; show incident effective window, evidence observation times, retrieval time, hold status and authorised expiry or transfer time. Permissions and provenance: Apply incident-command, emergency-plan, safety and communications permissions; share audience-specific instructions only through approved channels; retain owner role, record or case ID, version and extraction path. Conflict handling: preserve disputed items without interpretation only when authorised and refer conflicts to the incident information and information-governance owners; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not create new surveillance, identify suspects, alter original records, delete held evidence, extend retention or disclose incident material without authority. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Supports proportionate learning and accountability while keeping preservation, disclosure and retention decisions with authorised owners.



records, handover, privacy and service performance

SO-071 to SO-080 | ten operational questions

SO-071 RECORDS, HANDOVER, PRIVACY AND SERVICE PERFORMANCE

SOURCE LINEAGE

PROVENANCE CHECK

STAKEHOLDER QUESTION

What traceable evidence supports each handover statement, and which statements still require owner confirmation?

SENSORS AND TELEMETRY

Proposed evidence: no new sensing is required; use source record IDs, owner roles, versions, effective and observation times, connector paths, mapping references and current health for every handover statement. Coverage: all statements included in the current Security handover. Sampling and aggregation: validate at assembly and release; retain item-level lineage and source status without duplicating restricted source content. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (source retrieval test, identifier integrity check, mapping validation, clock-offset record and end-to-end lineage test), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: complete lineage proves traceability, not that the source owner's statement is correct or current. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: provenance verification. Decision interval: the current handover preparation and acceptance window. Minimum evidence: one source chain per material statement, current owner, exact scope, valid time, permission, mapping and health where telemetry is cited. Method: trace each statement to source, classify owner-confirmed, observed, calculated, estimated, restricted, conflicting or unsupported, and expose the missing link. Uncertainty: manual statements and late updates may lack machine-readable lineage. Safe failure: remove unsupported assertions from the confirmed section and carry them as owner-confirmation-needed with the last valid source.

AUTHORITATIVE SUPPORTING DATA

Current owners: the outgoing Duty Manager owns handover assembly; each Security, Access Control, Facilities, IT, Event, Safety or Emergency owner retains authority for its source statement. Precedence: the current authenticated owner record leads; derived summaries and telemetry cannot replace missing owner confirmation. Time discipline: display effective, observed and retrieved times; show source effective time, observation time where applicable, retrieval time and handover validity or recheck time. Permissions and provenance: Apply purpose, field-level, recipient, retention and disclosure controls from the information owner; preserve lineage for every source and derivative; retain owner role, record or case ID, version and extraction path. Conflict handling: retain conflicting statements with separate lineage and refer them to the outgoing and incoming Duty Managers plus the source owners; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not certify that a statement is true merely because lineage exists, alter source records, conceal conflicts or disclose restricted source detail in the handover. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives the incoming shift a defensible handover and a precise list of statements that still depend on owner confirmation.

SO-072 RECORDS, HANDOVER, PRIVACY AND SERVICE PERFORMANCE

RECORD QUALITY

DIAGNOSIS

STAKEHOLDER QUESTION

Which current Security records are incomplete, stale, duplicated or conflicting, and which operational decisions do those defects block?

SENSORS AND TELEMETRY

Proposed evidence: source metadata for required fields, versions, owners, status, timestamps, duplicate identifiers, mappings and connector health; no additional operational sensing. Coverage: the Security records and linked owner sources used for current Abacws decisions. Sampling and aggregation: check at source retrieval, handover and owner-defined governance intervals; aggregate defects by record type and blocked question. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (schema and completeness test, identifier and mapping validation, clock comparison, duplicate check and source-lineage test), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a technically complete record can still be wrong, and a similar record can represent a separate valid case. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: diagnosis. Decision interval: the current decision and the next handover or governance checkpoint. Minimum evidence: the required field set, owner, current version, effective period, duplicate rule, exact mapping, permission and connector health. Method: test completeness, currency, uniqueness, consistency and lineage; map each defect to the specific questions and decisions it blocks. Uncertainty: manual sources and legitimate repeated cases can make automated quality flags uncertain. Safe failure: return the affected answer as restricted, conflicting or not assessable and name the record owner and missing correction.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security information owner and each source-system owner control record meaning and correction; the Duty Manager owns operational reliance. Precedence: the current authenticated source and owner correction lead; derived quality flags cannot alter, merge or delete records. Time discipline: display effective, observed and retrieved times; show record effective, last-updated and retrieved times and apply the owner-defined freshness rule for each decision. Permissions and provenance: Apply purpose, field-level, recipient, retention and disclosure controls from the information owner; preserve lineage for every source and derivative; retain owner role, record or case ID, version and extraction path. Conflict handling: show every conflicting source and refer it to the Security information owner and source owner rather than selecting one automatically; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not alter, merge or delete records, infer that a missing field means normal conditions, rank source owners or fill gaps from historical material. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets Security target record correction where it has a direct operational consequence rather than pursuing generic data tidiness.



records, handover, privacy and service performance

SO-071 to SO-080 | ten operational questions

SO-073

RECORDS, HANDOVER, PRIVACY AND SERVICE PERFORMANCE

PERMISSION CHAIN

RULE COMPARISON

STAKEHOLDER QUESTION

Are source, field, purpose, recipient and time permissions valid for every item used in this Security answer?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required; use source-purpose metadata, field classifications, user role, intended action, recipient, time limit, aggregation, retention and disclosure controls. Coverage: every source field and derived value proposed for the specific answer. Sampling and aggregation: evaluate before retrieval, derivation and release and again after a role, purpose, recipient or incident-state change. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (permission-source retrieval test, user-role resolution, field-lineage validation and clock alignment for time-limited grants), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: permissions can be conditional, recipient-specific and unavailable to the service even when a user can view a source elsewhere. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: rule comparison. Decision interval: before each source access and answer release. Minimum evidence: authenticated user role, explicit purpose, intended action, source and field permissions, recipient, time window, aggregation and retention rule. Method: evaluate each field and derivative through the full permission chain; label permitted, aggregate-only, restricted, expired, conflicting or not assessable. Uncertainty: role changes and emergency restrictions can invalidate cached permission quickly. Safe failure: omit any item without a complete current chain and show the owner or permission needed; never widen access to complete an answer.

AUTHORITATIVE SUPPORTING DATA

Current owners: the source information owner, Security information owner, Data Protection or information-governance owner and incident owner where applicable. Precedence: the narrowest current lawful and owner-approved condition leads; operational need and prior access cannot widen purpose, fields, recipient or time. Time discipline: display effective, observed and retrieved times; show permission effective and expiry times, proposed use time and retrieval time; reject cached or superseded grants. Permissions and provenance: Apply purpose, field-level, recipient, retention and disclosure controls from the information owner; preserve lineage for every source and derivative; retain owner role, record or case ID, version and extraction path. Conflict handling: withhold unresolved fields and refer conflicts to the Security information owner and relevant source owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not disclose restricted data, infer consent, reuse data for a new purpose, extend access or retention, or release an answer because most fields are permitted. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Prevents a useful operational answer from becoming an unauthorised disclosure or purpose change.

SO-074

RECORDS, HANDOVER, PRIVACY AND SERVICE PERFORMANCE

DEPENDENCY COVERAGE

DIAGNOSIS

STAKEHOLDER QUESTION

Which proposed sensors or integrations are unhealthy, unmapped, stale or unverified, and which catalogue questions does each failure block?

SENSORS AND TELEMETRY

Proposed evidence: commissioning records, exact asset and location mappings, modality tests or calibration, heartbeats, uptime, gaps, clock offsets, maintenance or tamper state, drift indicators and connector lineage. Coverage: every proposed source dependency linked to SO-001 through SO-080. Sampling and aggregation: continuous health where available, owner-defined test intervals and daily or shift-level coverage summaries. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (end-to-end source test, mapping check, calibration or functional-test validation, heartbeat and gap test, clock comparison and lineage verification), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a healthy integration can still carry stale or incorrect owner data, while an unhealthy optional source may not block a decision. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: diagnosis and dependency mapping. Decision interval: before answer release and at each shift health check. Minimum evidence: the complete question-to-source dependency map, current mapping, permission, health, test, clock, coverage and lineage for each mandatory source. Method: evaluate mandatory and optional dependencies separately; list the exact questions, fields and locations blocked or weakened by each failed gate. Uncertainty: dependency documentation can lag catalogue or system changes. Safe failure: return affected questions not assessable or reduced-evidence and name the missing source or manual check; never substitute an adjacent feed.

AUTHORITATIVE SUPPORTING DATA

Current owners: each sensor or integration service owner holds technical health; asset and building information owners hold mapping; Security information and service owners define dependency and permitted use. Precedence: owner-confirmed source and mapping status lead; no proposed feed is usable until deployment, commissioning, permission and current health are independently confirmed. Time discipline: display effective, observed and retrieved times; show commissioning and test dates, latest observation, retrieval time and owner-defined expiry for each health claim. Permissions and provenance: Apply purpose, field-level, recipient, retention and disclosure controls from the information owner; preserve lineage for every source and derivative; retain owner role, record or case ID, version and extraction path. Conflict handling: show mapping, owner and technical conflicts and refer them to the source owner, building information owner and Security service owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not claim a source is deployed or trustworthy without independent evidence, infer coverage from neighbouring assets, enable a feed or bypass a failed permission gate. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets service owners see the operational consequence of each technical or mapping gap and prioritise verification accordingly.



records, handover, privacy and service performance

SO-071 to SO-080 | ten operational questions

SO-075

RECORDS, HANDOVER, PRIVACY AND SERVICE PERFORMANCE

DE-IDENTIFIED TIMES

STATISTICAL COMPARISON

STAKEHOLDER QUESTION

Are response and update times changing for genuinely comparable incident classes, and how uncertain is the difference?

SENSORS AND TELEMETRY

Proposed evidence: de-identified case class, priority rule, creation, acceptance, update and closure timestamps, authorised pause flags and service-exposure measures; no staff identity or person-level work trace. Coverage: owner-approved Security incident classes over defined comparable service periods. Sampling and aggregation: case-level timestamps transformed to approved aggregates such as median, interquartile range and completion proportion; suppress small groups. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (timestamp completeness test, class-definition consistency, duplicate-case check, clock alignment and missingness profile), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: changed classification, workload, opening, event mix and recording practice can create apparent time changes unrelated to service performance. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: statistical comparison. Decision interval: the defined service reporting period against a pre-specified comparable baseline. Minimum evidence: stable classes, sufficient case counts, complete required timestamps, authorised pauses, comparable operating exposure and documented missingness. Method: compare robust distributions and proportions with confidence intervals or bootstrap ranges; stratify material case-mix changes and avoid one combined score. Uncertainty: small samples, censoring and changed recording practice can dominate the result. Safe failure: report no trend when comparability or sample size is inadequate; show descriptive ranges and the exact evidence limitation.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security service owner defines incident classes and targets; case owners hold status; information-governance owners control aggregate use. Precedence: stable owner-approved definitions and complete milestone semantics lead; raw averages cannot support comparison across changed classes or exposure. Time discipline: display effective, observed and retrieved times; show class-definition effective periods, case event times, extraction time and comparison window; exclude incompatible periods explicitly. Permissions and provenance: Apply purpose, field-level, recipient, retention and disclosure controls from the information owner; preserve lineage for every source and derivative; retain owner role, record or case ID, version and extraction path. Conflict handling: show classification and milestone conflicts and refer them to the Security service owner and case-system owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not rank or appraise individual officers, infer blame or causation, promise future response times, alter targets or expose small-group case detail. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives Security leadership a fair basis for discussing service timing without turning administrative timestamps into staff surveillance.

SO-076

RECORDS, HANDOVER, PRIVACY AND SERVICE PERFORMANCE

AGGREGATE DEMAND

COMPARISON + OPTION FRAMING

STAKEHOLDER QUESTION

Which recurring building issues consume the most Security handling time, and what cross-team prevention options merit consideration?

SENSORS AND TELEMETRY

Proposed evidence: de-identified incident and service-desk categories, exact asset or zone identifiers, repeat event counts and owner-approved handling-time bands; no personal narrative or staff-level timing. Coverage: authorised Security, Facilities, IT and Access Control cases affecting Abacws over a defined service period. Sampling and aggregation: aggregate by stable issue class, asset and comparable operating exposure; suppress small or personalisable groups. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (case-category mapping, duplicate check, timestamp completeness, asset mapping, clock alignment and lineage validation), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: frequent low-impact faults can dominate totals, under-reporting can hide burden and recorded time may not represent full effort. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: comparison and option framing. Decision interval: the service planning period. Minimum evidence: stable issue classes, sufficient classified cases, comparable exposure, documented handling-time method, owner-confirmed dependencies and permission for aggregate cross-team use. Method: rank issue groups by transparent frequency and handling ranges, separate incidents from technical faults, and frame owner-supplied prevention options with evidence and dependencies. Uncertainty: classification drift, missing time and unrecorded work can change apparent burden. Safe failure: show only robust recurring groups and evidence gaps; do not select an investment or claim that an option will prevent incidents.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security service owner, service-desk owner, Facilities, IT and Access Control owners hold classification and owner-confirmed contributing factors. Precedence: owner-confirmed case classes and causes lead; frequency and handling burden cannot establish root cause or the best prevention investment. Time discipline: display effective, observed and retrieved times; use stable definitions and comparable exposure for the chosen period and show case, observation and retrieval times. Permissions and provenance: Apply purpose, field-level, recipient, retention and disclosure controls from the information owner; preserve lineage for every source and derivative; retain owner role, record or case ID, version and extraction path. Conflict handling: retain unresolved classifications and refer prevention questions to the responsible cross-team owners; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not infer blame, staff productivity, criminal risk or causal responsibility, expose individual cases, approve investment or prescribe a technical solution. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Supports a focused prevention conversation with Facilities, IT, Events or Access Control using transparent demand evidence.



records, handover, privacy and service performance

SO-071 to SO-080 | ten operational questions

SO-077

RECORDS, HANDOVER, PRIVACY AND SERVICE PERFORMANCE

DATA LIFECYCLE

CONFORMANCE CHECK

STAKEHOLDER QUESTION

Are retention, minimisation and access restrictions applied to every Security data product used by this service?

SENSORS AND TELEMETRY

Proposed evidence: data-product metadata for purpose, fields, aggregation, source lineage, access group, disclosure, retention or expiry, deletion evidence, incident hold and derived copies; no additional sensing. Coverage: every source extract, cache, aggregate, report and derivative used for Security answers. Sampling and aggregation: check at onboarding, before use, at owner-defined governance intervals and before exceptional retention or disclosure. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (inventory completeness test, field-lineage validation, access-control test, expiry-control test, clock alignment and deletion-evidence check), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: metadata may be incomplete and a compliant configured rule does not prove that every downstream copy is controlled. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: conformance check. Decision interval: before answer release and at each governance checkpoint. Minimum evidence: a complete product inventory, current purpose, field necessity, source lineage, access roles, recipients, retention or hold rule and expiry or deletion evidence. Method: compare actual metadata and controls with owner rules; identify excess fields, broad access, expired retention, missing lineage and untracked derivatives. Uncertainty: copies outside connected systems may not be visible and deletion evidence may lag. Safe failure: block the affected product from new answers when purpose, access, lineage or lifecycle control cannot be confirmed and name the owner action needed.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security information owner, each source information owner, Data Protection or information-governance owner and incident hold owner. Precedence: current purpose, legal hold, minimum-necessary, access and retention rules lead; operational convenience cannot extend them. Time discipline: display effective, observed and retrieved times; show rule effective time, data observation interval, retrieval time, authorised expiry and hold status; treat ownerless derivatives as restricted. Permissions and provenance: Apply purpose, field-level, recipient, retention and disclosure controls from the information owner; preserve lineage for every source and derivative; retain owner role, record or case ID, version and extraction path. Conflict handling: restrict disputed products and refer conflicts to the Security information owner and source owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not make a legal-compliance determination, widen access, delete or release held data, infer that absence of evidence proves control or expose personal data. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives information owners a concrete list of products needing tighter minimisation, access, expiry or lineage before operational use.

SO-078

RECORDS, HANDOVER, PRIVACY AND SERVICE PERFORMANCE

REPORT DISCLOSURE

RULE COMPARISON

STAKEHOLDER QUESTION

May this operational Security report be shared with the intended recipient, and at what authorised level of detail?

SENSORS AND TELEMETRY

Proposed evidence: no sensing is required; use report-field classification, source permission, recipient role, stated purpose, incident restriction, aggregation level, approved channel and disclosure history. Coverage: the exact report version and proposed recipient or audience. Sampling and aggregation: evaluate immediately before each disclosure and after any report, recipient, purpose or incident change. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (report-version integrity check, recipient-role resolution, field-lineage validation, channel approval test and clock alignment for expiring permissions), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: a recipient may be authorised for the report purpose but not for every field or level of spatial and operational detail. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: rule comparison. Decision interval: immediately before proposed sharing. Minimum evidence: authenticated recipient, stated purpose, exact report version, field-level lineage and permissions, current incident restrictions, channel and retention rule. Method: evaluate each field and output full detail, aggregate, redact, withhold or owner-confirmation-needed; show the rule and permitted channel. Uncertainty: recipient role and incident restrictions can change after a report is generated. Safe failure: release nothing automatically; produce a permission result and route all unresolved fields to the report owner.

AUTHORITATIVE SUPPORTING DATA

Current owners: the report owner, Security information owner, source information owners, incident owner and Data Protection or information-governance owner. Precedence: the narrowest current field, recipient, channel and purpose rule leads; a previous disclosure cannot authorise a new recipient or updated report. Time discipline: display effective, observed and retrieved times; show permission effective and expiry times, report generation time, proposed disclosure time and retrieval time. Permissions and provenance: Apply purpose, field-level, recipient, retention and disclosure controls from the information owner; preserve lineage for every source and derivative; retain owner role, record or case ID, version and extraction path. Conflict handling: withhold conflicted fields and refer them to the report owner and relevant source or information-governance owner; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not send, publish or redact the report, infer recipient need, expose personal or tactical detail, broaden purpose or treat a general Security role as blanket access. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Lets an authorised officer prepare the minimum permissible report and avoid an avoidable disclosure breach.



records, handover, privacy and service performance

SO-071 to SO-080 | ten operational questions

SO-079

RECORDS, HANDOVER, PRIVACY AND SERVICE PERFORMANCE

REPORTING COVERAGE

BIAS ASSESSMENT

STAKEHOLDER QUESTION

Which coverage, health or provenance gaps prevent fair Security service-performance reporting?

SENSORS AND TELEMETRY

Proposed evidence: case-source coverage metadata, source uptime and gaps, location mapping, classification completeness, clock quality, permission exclusions and lineage for each reported measure; no new operational sensing. Coverage: all locations, periods, case classes and sources included or intended in the service report. Sampling and aggregation: compute coverage by location, time and class for the reporting period; retain aggregate quality measures and explicit exclusions. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (source completeness test, mapping validation, heartbeat and gap analysis, clock comparison, classification consistency and lineage verification), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: missingness may be systematic, and healthy telemetry does not correct unreported cases or inconsistent administrative practice. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: bias and coverage assessment. Decision interval: before any service-performance result is released. Minimum evidence: the full intended population of locations, periods and classes, actual source coverage, missingness, health, permissions, stable definitions and lineage. Method: calculate coverage and missingness by relevant strata, test whether exclusions are uneven, and state which comparisons or claims are unsupported. Uncertainty: unobserved cases and changing recording behaviour can create bias that cannot be quantified. Safe failure: suppress or qualify any measure lacking adequate comparable coverage; show the blocked claim and the evidence needed.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security service owner owns measure definitions; source owners hold data meaning; information-governance owners control permitted reporting. Precedence: the published measure specification and current source definitions lead; incomplete or non-comparable evidence cannot be normalised away without owner approval. Time discipline: display effective, observed and retrieved times; show definition effective periods, data observation windows, extraction time and every excluded interval or location. Permissions and provenance: Apply purpose, field-level, recipient, retention and disclosure controls from the information owner; preserve lineage for every source and derivative; retain owner role, record or case ID, version and extraction path. Conflict handling: present source-definition and coverage conflicts and refer them to the Security service owner and source owners; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not rank teams or individuals, impute hidden cases as fact, conceal exclusions, certify fairness or publish a measure whose denominator or coverage is unknown. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Prevents incomplete evidence from producing misleading claims about Security demand, timeliness or service quality.

SO-080

RECORDS, HANDOVER, PRIVACY AND SERVICE PERFORMANCE

PLANNING EVIDENCE

OPTION FRAMING

STAKEHOLDER QUESTION

Which evidence-backed Security service-development options can be framed for the next planning cycle without turning them into automatic recommendations?

SENSORS AND TELEMETRY

Proposed evidence: de-identified demand and incident aggregates, source-health and coverage gaps, owner-confirmed recurring faults, authorised event and opening context, service measures and structured stakeholder feedback; no surveillance expansion by default. Coverage: the Security service decisions, locations and periods defined for the next planning cycle. Sampling and aggregation: use owner-approved monthly, term or annual aggregates with suppression of small groups and explicit source coverage. Quality and provenance gate: verify deployment, exact asset and location mapping, commissioning, purpose permission and current health; retain the modality-specific calibration or functional test (measure-definition validation, case and asset mapping, duplicate check, clock alignment, missingness analysis and source-lineage verification), clock offset and alignment, expected heartbeat, uptime, gaps, maintenance or tamper state, drift and source-to-answer lineage. Limits: historical demand may not predict future conditions, stakeholder feedback is selective and technical feasibility or cost may be uncertain. Uninstrumented, unmapped or unhealthy scope is unknown.

ANALYSIS REQUIRED

Operation type: option framing. Decision interval: the next authorised service-planning cycle. Minimum evidence: a defined decision, baseline demand and coverage, owner-confirmed problem statement, feasible option descriptions, dependencies, cost and resource ranges, privacy and safety constraints and uncertainty. Method: frame a small set of options with evidence for benefits, limits, prerequisites, affected owners and measures; separate observed need, estimate and forecast and avoid an opaque score. Uncertainty: future demand, implementation quality, displaced workload and privacy impact may be uncertain. Safe failure: present no preferred option when evidence or owner agreement is insufficient; show the missing evidence and decisions that require human consultation.

AUTHORITATIVE SUPPORTING DATA

Current owners: the Security service owner owns planning questions; Finance, Estates, Access Control, IT, Events, Safety, procurement and information-governance owners hold constraints and evidence. Precedence: current institutional priorities, legal duties, owner-confirmed constraints and competent professional advice lead; derived metrics cannot choose an option. Time discipline: display effective, observed and retrieved times; show source observation periods, policy effective times, retrieval time and the planning horizon; reject outdated costs, assumptions or mappings. Permissions and provenance: Apply purpose, field-level, recipient, retention and disclosure controls from the information owner; preserve lineage for every source and derivative; retain owner role, record or case ID, version and extraction path. Conflict handling: retain conflicting owner objectives and evidence and present them as explicit trade-offs for authorised decision makers; do not merge incompatible states or let telemetry create authority.

ANSWER BOUNDARY

Do not approve procurement or policy, recommend surveillance expansion without necessity and authority, promise benefits, allocate resources or convert an option into operational direction. Do not identify suspects or infer identity, intent or wrongdoing; do not grant access, allocate or dispatch officers, acknowledge alarms, control systems, issue operational commands, promise outcomes or certify safety or security. Current Security and emergency procedures and competent authority prevail.

WHY THIS IS USEFUL

Gives Security leadership a transparent set of choices and trade-offs for consultation, governance and budget decisions.

Catalogue map

Eighty questions are organised around the decisions Security officers make before, during and after a shift. Current owner records lead in every category.

1	staffing, patrols and operational briefings SO-001 to SO-010	Confirm cover, briefing changes, patrol feasibility, checkpoint evidence and communication readiness.
2	public opening, doors, zones and access status SO-011 to SO-020	Reconcile authorised public access with door, route, controller and secure-close evidence.
3	alarms, incidents and service-desk coordination SO-021 to SO-030	Verify alerts, assemble non-personal context, test dependencies, track ownership and hand over unresolved items.
4	events, queues, crowds and public routes SO-031 to SO-040	Reconcile event plans with anonymous demand, route readiness, queue evidence and proportionate retention.
5	keys, locks, assets and restricted areas SO-041 to SO-050	Maintain key custody, lock-defect evidence, restricted-area governance and secure-close assurance.
6	out-of-hours work, lone working and escorts SO-051 to SO-060	Confirm authorised activity, check-ins, escort conditions, route availability, expiry times and handover needs.
7	emergency coordination, closures and communications SO-061 to SO-070	Display official states, closures, communication health, accessibility arrangements and evidence gaps without taking command.
8	records, handover, privacy and service performance SO-071 to SO-080	Test provenance, permissions, answerability, service measures, privacy controls and planning evidence.

Evidence and permissions rules

Apply these ten rules before any record contributes to an operational answer.

1

START WITH OWNER DATA

Identify the current source owner, effective instruction and competent authority before reading telemetry.

2

VERIFY PERMISSION

Confirm purpose, field-level access, recipient, disclosure level and retention before retrieval.

3

VERIFY SCOPE

Confirm exact asset, door, zone and route mapping. Adjacent evidence cannot stand in for the requested place.

4

VERIFY HEALTH

Check commissioning, modality test or calibration, heartbeat, clocks, uptime, gaps, maintenance, tamper and drift.

5

APPLY PRECEDENCE

Current authenticated instructions and competent emergency authority override schedules, telemetry, derived values and historical material.

6

ALIGN TIME

Show effective, observed and retrieved times. Do not present asynchronous states as one simultaneous picture.

7

SEPARATE CLAIM TYPES

Label owner facts, observations, calculations, estimates, forecasts, comparisons, diagnoses, options, conflicts and unknowns.

8

TEST SUFFICIENCY

Require the stated minimum evidence. When absent, return not assessable and name the owner or check required.

9

MINIMISE RETENTION

Retain only authorised evidence for a defined purpose and period. Do not create identity or movement histories.

10

KEEP HUMAN AUTHORITY

The service informs decisions; it does not grant access, direct officers, control alarms or systems, or certify safety or security.

Answer release gate

Release an operational answer only when every applicable gate is satisfied. A failed gate changes the result to restricted, conflicting or not assessable; it never invites a guess.

1

DECISION

The question, authorised user role, decision interval and intended action are explicit.

2

AUTHORITY

The current owner source and precedence are known; emergency authority is clear where applicable.

3

TIME

Effective, observed and retrieved times are visible and valid for the decision interval.

4

PERMISSION

Purpose, field-level access, recipient, disclosure level and retention are authorised.

5

MAPPING

Every cited asset, door, zone and route segment is exactly mapped and in scope.

6

HEALTH

Commissioning, test or calibration, clocks, uptime, gaps, maintenance, tamper and drift are acceptable.

7

SUFFICIENCY

The minimum evidence is present and any required independent corroboration is adequate.

8

UNCERTAINTY

Conflicts, missing evidence, blind areas, assumptions and estimate or forecast ranges are explicit.

9

BOUNDARY

No prohibited identity, intent, surveillance, access, dispatch, control or certification is implied.

10

HANDOVER

The answer names its owner, validity or recheck time, and safe route when evidence is insufficient.

DEFAULT SAFE RESULT

Not assessable from currently verified evidence. Show the missing or conflicting item, its owner, latest valid time, permission or health limitation, and the current procedure or competent authority to follow.