

STAKEHOLDER QUESTION CATALOGUE 13

Teaching and Audiovisual Support Team

80 actionable, evidence-aware questions for room readiness, compatibility, fault triage, live continuity, hybrid teaching, assistive technology, maintenance, privacy and service resilience.

STAKEHOLDER

Teaching-room and audiovisual support professionals who prepare rooms, diagnose content-free technical faults, support live teaching, maintain managed AV assets and route restricted incidents.

QUESTION RANGE

AV-001 to AV-080 across eight decision areas, from near-term room checks through lifecycle planning and recovery testing.

EVIDENCE MODEL

Current authorised room, timetable, AV, network, platform, accessibility, maintenance, privacy, security and safety sources, supported only by minimum proposed content-free telemetry with verified mapping, timing, quality and permission.

CORE PRINCIPLE

Use current evidence to identify the next authorised support action. Never capture teaching content, access accounts or credentials, operate equipment, change configuration, identify people, or treat telemetry as permission, accessibility, privacy or safety approval.

1. Scope and design principles

The catalogue supports technical decisions by the teaching and AV support team. It does not transfer authority from lecturers, room owners, AV/IT services, accessibility services, security, safety authorities or competent professionals.

SUPPORT DECISIONS, NOT REMOTE CONTROL

The service may perform authorised lookup, observation, calculation, comparison, diagnosis and recommendation. It never operates devices, changes configuration, accesses accounts or grants permission.

PROPOSED UNTIL INDEPENDENTLY VERIFIED

Sensors, endpoint feeds, mappings, analytics and integrations remain design requirements until deployed, commissioned, permitted and confirmed healthy for the decision window.

CURRENT AUTHORITATIVE SOURCES FIRST

Timetable, room, AV, network, platform, accessibility, maintenance, privacy, security and safety owners govern their domains. Telemetry cannot override owner-issued status.

CONTENT AND IDENTITY MINIMISATION

Use device state, technical counters and numerical environmental measures only. Never analyse speech, video, screens, recordings, teaching material, credentials, payloads or identities.

EXACT ROOM, ASSET AND SERVICE SCOPE

A room claim requires room-level evidence and verified room-to-rack, port, endpoint and service-path mapping. Corridor or adjacent-room data cannot stand in.

HONEST ANSWERABILITY

Name the operation and uncertainty. Missing, stale, contradictory, unauthorised or spatially invalid mandatory evidence requires clarification, a physical check, owner deferral or not assessable.

2. Record fields and readiness labels

Every record is a decision specification, not a claim that the capability is already deployed.

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION	The natural support decision: what to check, where to attend, which authorised fallback to explain, which owner to involve, or which maintenance action to propose.
SENSORS AND TELEMETRY	Minimum proposed content-free technical evidence, including exact room, rack, endpoint or service path; timing and aggregation; mapping, commissioning or calibration; health, gaps and provenance.
AUTHORITATIVE SUPPORTING DATA	Current owner-managed timetable, room, AV, network, platform, accessibility, maintenance, privacy, security and safety records, with owner, effective/observed and retrieval times, permissions and conflicts.
ANALYSIS REQUIRED	The named operation, decision interval, minimum evidence, method, comparator or baseline, uncertainty and safe failure. Diagnosis ranks plausible domains; it does not prove causality.
ANSWER BOUNDARY	What the service must not inspect, infer, disclose, promise, certify, authorise or control, and when it must clarify, qualify, defer or return not assessable.
WHY THIS IS USEFUL	The concrete action enabled: prioritise a visit, stage an approved spare, select a diagnostic check, explain a fallback, route an incident or request owner verification.

READINESS

R1 PRACTICAL Mostly current authorised lookup or verified static information.	R2 VERIFIED INTEGRATION Requires current cross-system mapping and/or commissioned content-free endpoint telemetry.	R3 RESTRICTED Requires privacy, security, accessibility, capture or higher-consequence governance and permission.
--	---	--

1. Pre-session readiness and room checks

AV-001 to AV-010. Decide which rooms are evidenced ready, which are degraded, and which still need a physical check.

3. Fault detection, triage and service-desk routing

AV-021 to AV-030. Narrow the first technical check and route the incident without inspecting teaching or personal content.

5. Hybrid teaching, lecture capture and streaming infrastructure

AV-041 to AV-050. Verify the authorised service chain without examining captured or transmitted content.

7. Maintenance, spares, upgrades and handover

AV-061 to AV-070. Plan proportionate lifecycle actions using current asset, teaching and service evidence.

2. Room AV inventory, configuration and compatibility

AV-011 to AV-020. Match approved room profiles to current, content-free equipment evidence before advising compatibility.

4. Live teaching support and fallback choices

AV-031 to AV-040. Present authorised, time-bounded continuity options while lecturers and service owners retain control.

6. Accessibility and assistive-technology provision

AV-051 to AV-060. Check technical provision against stated functional requirements without inferring needs or certifying accessibility.

8. Incidents, cybersecurity, privacy and service performance

AV-071 to AV-080. Support restricted escalation, recovery and service learning with minimum necessary technical evidence.

1. Pre-session readiness and room checks

AV-001 to AV-010 | Decide which rooms are evidenced ready, which are degraded, and which still need a physical check.

AV-001

NEXT-90-MINUTE READINESS

L2 calculation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

For teaching due to start in the next 90 minutes, which rooms have complete current AV evidence and which require an on-site check?

SENSORS AND TELEMETRY

Proposed evidence: each scheduled room and its mapped AV rack and managed endpoints: controller, display or projector, DSP, amplifier, lectern computer, capture endpoint, managed network link, rack power and rack temperature status. Coverage and timing: Use event-driven state plus a 60-second heartbeat from the start of the setup window to session start; summarise by room Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Current timetable and room assignment; room-owner opening or closure state; AV asset register and approved room baseline; maintenance/change records; central network and platform status Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus readiness calculation. Decision interval: the next 90 minutes and each room setup window. Minimum evidence: a current schedule, eligible room, complete endpoint mapping and current mandatory service status. Method: apply hard readiness rules and classify ready, degraded, technician visit or not assessable; list the missing dependency. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

This supports readiness triage only. Do not start equipment or declare a room open, ready, accessible or safe; conflicting schedule, closure or endpoint evidence requires owner confirmation and an on-site check.

WHY THIS IS USEFUL

Sets the technician visit order before the earliest affected teaching starts.

AV-002

FIRST-ROOM START-UP

L2 comparison | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Has the first teaching room of the day completed its approved start-up sequence, or should we visit it before staff arrive?

SENSORS AND TELEMETRY

Proposed evidence: the named room controller, display path, audio rack and managed lectern computer: boot state, display light-source state, input lock, DSP and amplifier heartbeat, computer health, network link and rack temperature. Coverage and timing: Capture state transitions from the authorised start-up time until 20 minutes before teaching Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Current first-session timetable; approved start-up sequence and self-test criteria; room configuration baseline; overnight maintenance, shutdown and closure notices Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus sequence comparison. Decision interval: the approved morning start-up period. Minimum evidence: the current session, approved sequence and status for every mandatory endpoint. Method: compare observed transitions with the approved order and flag incomplete, late or contradictory steps. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

This supports readiness triage only. Do not start equipment or declare a room open, ready, accessible or safe; conflicting schedule, closure or endpoint evidence requires owner confirmation and an on-site check.

WHY THIS IS USEFUL

Decides whether an early walk-round is needed before the first session.

1. Pre-session readiness and room checks

AV-001 to AV-010 | Decide which rooms are evidenced ready, which are degraded, and which still need a physical check.

AV-003

POST-MAINTENANCE RELEASE

L2 comparison | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Following maintenance, is there enough post-work evidence to keep this room in service, or should it remain on hold?

SENSORS AND TELEMETRY

Proposed evidence: the exact room and every AV asset covered by the work order: post-work power, controller, display, audio, managed computer, capture and network self-test results. Coverage and timing: Use only tests recorded after the signed work-completion time and before the next scheduled setup window Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Signed maintenance completion; approved acceptance checklist; room-owner closure state; asset and configuration updates; unresolved defect register; next timetable booking Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus acceptance comparison. Decision interval: after work completion and before the next booking. Minimum evidence: signed completion, current acceptance criteria, mapped post-work tests and no unresolved blocking defect. Method: separate passed, failed, untested and conflicting checks and identify the responsible sign-off owner. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

This supports readiness triage only. Do not start equipment or declare a room open, ready, accessible or safe; conflicting schedule, closure or endpoint evidence requires owner confirmation and an on-site check.

WHY THIS IS USEFUL

Supports a return-to-service decision or continued hold for owner verification.

AV-004

DISPLAY INPUT READINESS

L2 comparison | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is the approved display and input path ready for the presenter's declared connection in the next session?

SENSORS AND TELEMETRY

Proposed evidence: the scheduled room input, switcher, extender and display path: connector presence, EDID and HDCP negotiation, selected input, signal lock, extender health and display fault state; no image or screen content. Observe from 30 minutes before setup until session start, using event logs and a 60-second health summary. Coverage and timing: Use event-driven state and a current health snapshot within the decision window; aggregate only to the level needed for the question Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Current room booking; approved AV signal-path diagram; room input profile; declared source type supplied by the session owner; open incidents and maintenance records Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus path comparison. Decision interval: the next session setup window. Minimum evidence: current room and source requirement, verified path mapping and state for every mandatory link. Method: compare the required source path with supported interfaces and current link state; identify the first unsupported or failed segment. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

This supports readiness triage only. Do not start equipment or declare a room open, ready, accessible or safe; conflicting schedule, closure or endpoint evidence requires owner confirmation and an on-site check.

WHY THIS IS USEFUL

Determines whether to stage the declared source or an approved alternative.

1. Pre-session readiness and room checks

AV-001 to AV-010 | Decide which rooms are evidenced ready, which are degraded, and which still need a physical check.

AV-005

AUDIO PATH READINESS

L2 diagnosis | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is the complete audio path ready for the scheduled teaching format, including the required microphone type?

SENSORS AND TELEMETRY

Proposed evidence: the scheduled room microphone receiver, DSP, amplifier and supervised loudspeaker path: power and heartbeat, receiver presence, mute and route state, amplifier protection state and line-supervision or authorised test-tone result; no ambient audio. Coverage and timing: Use event state and an approved content-free self-test within the 30-minute setup window Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Current timetable; declared teaching format and microphone requirement; approved audio topology and baseline; room maintenance and current incident status Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus diagnostic readiness check. Decision interval: the setup period before the scheduled session. Minimum evidence: approved audio requirement, complete mapped chain and current status for all mandatory components. Method: verify the ordered chain from source to loudspeaker and distinguish unavailable, muted, degraded and untested states. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

This supports readiness triage only. Do not start equipment or declare a room open, ready, accessible or safe; conflicting schedule, closure or endpoint evidence requires owner confirmation and an on-site check.

WHY THIS IS USEFUL

Identifies whether the audio chain needs a pre-session physical test.

AV-006

LECTERN COMPUTER READINESS

L2 comparison | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Are the managed lectern computer and authorised USB peripherals ready for the next class?

SENSORS AND TELEMETRY

Proposed evidence: the named lectern computer, managed USB hub and approved room peripherals: device health, approved peripheral enumeration, storage and update state, USB hub power and fault status; no files, screen, keystrokes or device content. Coverage and timing: Use the latest managed health report, no older than 15 minutes, plus event changes during the setup window Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Current room profile; approved peripheral list; session requirement supplied by the lecturer or organiser; endpoint-management status; maintenance and change records Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus compatibility comparison. Decision interval: the next setup window. Minimum evidence: current room allocation, required approved peripherals and current endpoint health. Method: compare required devices with the room baseline and observed enumeration; separate absent, faulty, blocked and unverified items. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

This supports readiness triage only. Do not start equipment or declare a room open, ready, accessible or safe; conflicting schedule, closure or endpoint evidence requires owner confirmation and an on-site check.

WHY THIS IS USEFUL

Decides whether the lectern computer or approved peripheral needs attention.

1. Pre-session readiness and room checks

AV-001 to AV-010 | Decide which rooms are evidenced ready, which are degraded, and which still need a physical check.

AV-007

MICROPHONE BATTERY PLAN

L3 forecast | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which rooms starting soon need a charged wireless-microphone battery or an approved spare staged in advance?

SENSORS AND TELEMETRY

Proposed evidence: the mapped wireless microphone docks, transmitters and receivers for scheduled rooms: dock occupancy, battery state of charge, charge fault, cycle-health flag, receiver pairing identity and spare-stock count; no audio. Coverage and timing: Use 5-minute charge summaries from 90 minutes before teaching and forecast state at the setup deadline Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Current timetable and microphone requirement; authoritative room inventory; approved battery thresholds; loan and spare-stock register; open maintenance incidents Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: calculation plus short-horizon forecast. Decision interval: each room setup deadline within the next 90 minutes. Minimum evidence: mapped microphone set, current battery data, charge model and available approved spare stock. Method: estimate state at the deadline, flag uncertain batteries and rank rooms by intervention urgency without assigning staff automatically. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

This supports readiness triage only. Do not start equipment or declare a room open, ready, accessible or safe; conflicting schedule, closure or endpoint evidence requires owner confirmation and an on-site check.

WHY THIS IS USEFUL

Targets battery changes and spare staging before microphone demand begins.

AV-008

CAPTURE PRECHECK

L2 calculation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is the authorised lecture-capture endpoint technically ready for the next scheduled recording window?

SENSORS AND TELEMETRY

Proposed evidence: the named room capture appliance and its approved service path: endpoint heartbeat, local storage headroom, schedule-trigger receipt, ingest reachability and platform service state; no captured audio, video or screen content. Coverage and timing: Use event-driven status from 30 minutes before the authorised capture window through the planned start time Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Current timetable and room booking; owner-approved capture schedule and mode; capture platform status; room AV baseline; maintenance and privacy notices Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus readiness calculation. Decision interval: the next authorised capture window. Minimum evidence: valid capture authorisation and schedule, mapped endpoint, storage and ingest status, and current platform owner state. Method: check each mandatory dependency and return ready, degraded, technician check or not assessable with the missing item. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

This supports readiness triage only. Do not start equipment or declare a room open, ready, accessible or safe; conflicting schedule, closure or endpoint evidence requires owner confirmation and an on-site check. Recording authority and retention rules must be confirmed independently of technical status.

WHY THIS IS USEFUL

Determines whether capture needs an on-site check before the recording window.

1. Pre-session readiness and room checks

AV-001 to AV-010 | Decide which rooms are evidenced ready, which are degraded, and which still need a physical check.

AV-009

ASSISTIVE LISTENING PRECHECK

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Has the room's approved assistive-listening system passed the required technical pre-session check?

SENSORS AND TELEMETRY

Proposed evidence: the installed hearing loop or approved assistive-audio transmitter, field-test instrument and charging dock: amplifier fault and current status, latest calibrated field-strength test summary, receiver battery/charge state and endpoint heartbeat; no audio content. Coverage and timing: Use the latest in-date commissioning result and a content-free pre-session status check within 30 minutes of use. Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds. Any numerical test instrument must have an in-date calibration.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Current room accessibility profile; approved provision for the session; accessibility-service instructions; maintenance/loan records; room closure and safety status. Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus acceptance comparison. Decision interval: the pre-session accessibility setup window. Minimum evidence: current approved provision, in-date test criteria, mapped equipment and current service status. Method: compare technical evidence with the approved checklist and identify passed, failed, untested and owner-confirmation items. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

This supports readiness triage only. Do not start equipment or declare a room open, ready, accessible or safe; conflicting schedule, closure or endpoint evidence requires owner confirmation and an on-site check. Do not disclose who requested support or infer any disability or diagnosis.

WHY THIS IS USEFUL

Triggers a timely assistive-listening check or authorised fallback discussion.

AV-010

WALK-ROUND PRIORITY

L3 recommendation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which scheduled rooms should be included in the walk-round because remote readiness evidence is missing, stale or contradictory?

SENSORS AND TELEMETRY

Proposed evidence: the monitoring service for scheduled rooms and all mapped mandatory AV endpoints: heartbeat age, missing intervals, mapping confidence, clock offset, configuration version and monitor self-health; no teaching or user content. Coverage and timing: Evaluate monitoring completeness throughout each room setup window and at the current decision time. Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Current schedule and room eligibility; authoritative AV asset map; monitoring inventory; maintenance, change and outage records; support staffing window. Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: evidence-quality calculation plus recommendation. Decision interval: the next two hours of scheduled teaching. Minimum evidence: current schedule, mandatory endpoint list and monitoring-quality state for each room. Method: score answerability rather than device readiness; recommend a visit only where remote evidence cannot support the requested decision. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

This supports readiness triage only. Do not start equipment or declare a room open, ready, accessible or safe; conflicting schedule, closure or endpoint evidence requires owner confirmation and an on-site check.

WHY THIS IS USEFUL

Uses limited walk-round capacity where remote evidence cannot answer responsibly.

2. Room AV inventory, configuration and compatibility

AV-011 to AV-020 | Match approved room profiles to current, content-free equipment evidence before advising compatibility.

AV-011

APPROVED ROOM INVENTORY

L2 comparison | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

What AV equipment is currently approved for this room, and which items have current evidence that they are in service?

SENSORS AND TELEMETRY

Proposed evidence: the room controller and each owner-managed AV endpoint mapped to the room: asset identifier, model, firmware/configuration identifier, heartbeat and maintenance state; no device content. Coverage and timing: Use event updates and a current 60-second health snapshot at the requested time Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative AV asset register and room profile; current room purpose/ownership; installation and change records; maintenance and decommission notices Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus inventory reconciliation. Decision interval: the current support request. Minimum evidence: current room identity, owner-approved inventory and endpoint-to-room mapping. Method: compare registered inventory with observed managed endpoints; label registered, observed, in service, out of service, moved and unverified separately. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not change configuration, promise compatibility or treat observed hardware as authorised inventory. The approved room profile and responsible owner govern; incomplete mapping makes the result limited or not assessable.

WHY THIS IS USEFUL

Provides a defensible equipment list before support staff attend the room.

AV-012

ROOM-TO-ASSET MAPPING

L3 recommendation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Do the observed AV endpoints still match the approved room, rack, port and signal-path mapping?

SENSORS AND TELEMETRY

Proposed evidence: the named controllers, switches, managed endpoints and network ports: serial or asset ID, controller membership, switch/port relationship, LLDP or equivalent content-free adjacency and signal-path status. Coverage and timing: Use the latest topology snapshot plus change events from the selected verification period Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative asset register; as-built signal-path diagram; rack and patching records; approved network topology; completed change and relocation records Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: mapping comparison plus diagnosis. Decision interval: the current incident or audit window. Minimum evidence: stable asset identifiers, authoritative room/rack/port map and current content-free topology evidence. Method: identify exact matches, stale records, ambiguous duplicates and conflicts; recommend physical verification when location cannot be resolved. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not change configuration, promise compatibility or treat observed hardware as authorised inventory. The approved room profile and responsible owner govern; incomplete mapping makes the result limited or not assessable.

WHY THIS IS USEFUL

Prevents support and diagnosis from using an obsolete asset or signal-path map.

2. Room AV inventory, configuration and compatibility

AV-011 to AV-020 | Match approved room profiles to current, content-free equipment evidence before advising compatibility.

AV-013

PRESENTER DEVICE COMPATIBILITY

L2 calculation | R1 practical

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Can the presenter's declared device use a supported room input without an unapproved workaround?

SENSORS AND TELEMETRY

Proposed evidence: the room input panel, switcher/extender and display endpoint: available connector types, approved wireless-presentation status, EDID capability and current input-path health; no source content. Coverage and timing: Use a current capability snapshot and setup-window status; no environmental sensing is needed Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Current room AV profile; approved input standards; presenter-declared connector and output specification; supported adapter list; current maintenance state Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus constraint calculation. Decision interval: before the presenter travels or enters the setup window. Minimum evidence: verified room capability, declared source specification and approved connection policy. Method: apply hard interface, resolution, HDCP and policy constraints; return supported, supported with approved adapter, unsupported or not assessable. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not change configuration, promise compatibility or treat observed hardware as authorised inventory. The approved room profile and responsible owner govern; incomplete mapping makes the result limited or not assessable.

WHY THIS IS USEFUL

Determines whether the declared source is directly supported or needs approved adaptation.

AV-014

ADAPTER AND CABLE STAGING

L3 recommendation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which approved adapters and cables should we stage for the declared presenter devices?

SENSORS AND TELEMETRY

Proposed evidence: the owner-managed adapter store and the scheduled room input path: stock count, check-in state, functional-test date, cable/adapter type and optional charge state; no borrower identity. Flag stale counts, holds and unreturned items without borrower identities. Coverage and timing: Use owner-issued inventory updated at issue/return and a current room-path health check before the setup deadline. Use owner-issued stock time, test/charge state and provenance Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Presenter-declared source requirements; current room input profile; approved adapter catalogue; loan rules; stock, cleaning/test and maintenance records Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus recommendation. Decision interval: the presenter setup deadline. Minimum evidence: declared source, verified room interface, approved compatibility matrix and available tested stock. Method: select the smallest approved kit that satisfies the path and show any unverified compatibility or stock conflict. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not change configuration, promise compatibility or treat observed hardware as authorised inventory. The approved room profile and responsible owner govern; incomplete mapping makes the result limited or not assessable.

WHY THIS IS USEFUL

Stages only the approved connection kit needed for the session.

2. Room AV inventory, configuration and compatibility

AV-011 to AV-020 | Match approved room profiles to current, content-free equipment evidence before advising compatibility.

AV-015

DISPLAY FORMAT SUPPORT

L2 comparison | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Can the full display path support the requested resolution, aspect ratio and protected-content requirement?

SENSORS AND TELEMETRY

Proposed evidence: the mapped source input, switcher/extender and display: EDID capability, negotiated resolution, refresh rate, aspect setting, signal lock and current path faults; no image content. Coverage and timing: Use the current room profile and a content-free handshake test during the setup window Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Approved room AV specification; display and extender limits; source requirement supplied by the organiser; configuration baseline and current maintenance state Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: capability comparison. Decision interval: the planned setup and session. Minimum evidence: declared source format, verified end-to-end path and current endpoint capability. Method: compare supported formats across every link; identify the limiting component and approved fallback modes. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not change configuration, promise compatibility or treat observed hardware as authorised inventory. The approved room profile and responsible owner govern; incomplete mapping makes the result limited or not assessable.

WHY THIS IS USEFUL

Determines whether the requested presentation format is supported end to end.

AV-016

DUAL-DISPLAY ELIGIBILITY

L2 comparison | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is this room currently approved and configured for separate presenter and audience displays?

SENSORS AND TELEMETRY

Proposed evidence: the room matrix/switcher, both display endpoints and controller profile: output count, route state, display heartbeat, configuration profile ID and fault state; no screen content. Coverage and timing: Use a current status snapshot plus changes during the setup window Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Current room AV profile; approved dual-display configuration; session requirement; room-owner restrictions; configuration and maintenance records Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus configuration comparison. Decision interval: the next setup window. Minimum evidence: verified room capability, approved profile and current status of both output paths. Method: compare the requested use with the approved configuration; identify missing output, mirrored-only mode, degraded path or unauthorised profile. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not change configuration, promise compatibility or treat observed hardware as authorised inventory. The approved room profile and responsible owner govern; incomplete mapping makes the result limited or not assessable.

WHY THIS IS USEFUL

Confirms whether the planned dual-display workflow is technically eligible.

2. Room AV inventory, configuration and compatibility

AV-011 to AV-020 | Match approved room profiles to current, content-free equipment evidence before advising compatibility.

AV-017

VISUALISER STATUS

L1 lookup/observation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is a working visualiser or document camera currently assigned to this room and available for the session?

SENSORS AND TELEMETRY

Proposed evidence: the named visualiser/document-camera endpoint and managed USB or network connection: asset heartbeat, power, approved peripheral enumeration and maintenance state; no image or document capture. Coverage and timing: Use the latest managed status, no older than 15 minutes, and the current room inventory mapping Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative room AV inventory; current booking and room profile; portable-equipment stock; maintenance and loan records Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup. Decision interval: the presenter setup window. Minimum evidence: current room assignment, authoritative asset record and current content-free device health. Method: return installed and in service, installed but degraded, portable option, absent or not assessable. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not change configuration, promise compatibility or treat observed hardware as authorised inventory. The approved room profile and responsible owner govern; incomplete mapping makes the result limited or not assessable.

WHY THIS IS USEFUL

Avoids promising a visualiser that is absent, moved or out of service.

AV-018

HYBRID ROOM ELIGIBILITY

L3 recommendation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which authorised rooms meet the declared technical requirements for this hybrid-teaching activity?

SENSORS AND TELEMETRY

Proposed evidence: candidate rooms and their mapped camera, microphone/DSP, display, capture/encoder and managed network endpoints: content-free health, route state, platform reachability and room rack power/temperature. Coverage and timing: Use current endpoint status and 5-minute network-quality aggregates for the proposed session window Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative room eligibility and booking data; current AV capability profiles; session requirements; accessibility provision; network/platform status; closures and maintenance Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: hard-constraint calculation plus recommendation. Decision interval: the requested session and setup interval. Minimum evidence: eligible candidate rooms, declared hybrid requirements and current mandatory service state. Method: filter by non-negotiable capability and owner constraints, then rank remaining rooms by evidence completeness and operational risk. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not change configuration, promise compatibility or treat observed hardware as authorised inventory. The approved room profile and responsible owner govern; incomplete mapping makes the result limited or not assessable.

WHY THIS IS USEFUL

Produces a technically eligible shortlist for the organiser or room owner.

2. Room AV inventory, configuration and compatibility

AV-011 to AV-020 | Match approved room profiles to current, content-free equipment evidence before advising compatibility.

AV-019

CONTROL PROFILE DRIFT

L2 diagnosis | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Has the room-control configuration moved away from the current approved baseline?

SENSORS AND TELEMETRY

Proposed evidence: the room controller, managed AV endpoints and configuration repository; configuration hash/version, endpoint inventory, route table identifiers and timestamped change events; no media or credentials. Compare the current snapshot with the approved baseline and changes since the last verified deployment. Coverage and timing: Use event-driven state and a current health snapshot within the decision window; aggregate only to the level needed for the question Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative configuration baseline; approved change records; asset inventory; maintenance and incident history; configuration-owner status Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: configuration comparison plus diagnosis. Decision interval: the selected audit or incident window. Minimum evidence: approved baseline, current signed/hashed configuration and complete change history. Method: separate authorised change, stale baseline, partial deployment, endpoint replacement and unexplained drift; report confidence. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not change configuration, promise compatibility or treat observed hardware as authorised inventory. The approved room profile and responsible owner govern; incomplete mapping makes the result limited or not assessable.

WHY THIS IS USEFUL

Supports verification, restoration or acceptance of an authorised configuration change.

AV-020

FIXED POWER CAPACITY

L3 recommendation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Does the fixed, approved power arrangement have verified capacity for the planned AV load?

SENSORS AND TELEMETRY

Proposed evidence: the mapped AV rack PDU, UPS-backed loads and relevant fixed circuits: current, power, breaker/PDU alarm, UPS load and temperature; no personal-device data. Coverage and timing: Use 1-10 second electrical sampling aggregated to one minute during comparable operation and the planned setup window Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds. Any numerical test instrument must have an in-date calibration or commissioning record.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative electrical single-line and circuit ratings; approved AV equipment list and load data; room asset map; maintenance, isolation and safety status Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: load calculation plus recommendation. Decision interval: the planned setup and session peak. Minimum evidence: verified circuit/UPS mapping, rated capacity, planned equipment load and current safety-owner status. Method: calculate diversified load and headroom using approved limits; flag missing ratings, transient uncertainty and any requirement for competent electrical review. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not change configuration, promise compatibility or treat observed hardware as authorised inventory. The approved room profile and responsible owner govern; incomplete mapping makes the result limited or not assessable. Telemetry is not electrical safety approval; competent electrical authority remains responsible.

WHY THIS IS USEFUL

Shows whether competent electrical confirmation or a reduced load is required.

3. Fault detection, triage and service-desk routing

AV-021 to AV-030 | Narrow the first technical check and route the incident without inspecting teaching or personal content.

AV-021

BLANK DISPLAY TRIAGE

L3 recommendation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

The display is blank. Which part of the approved signal path should we check first?

SENSORS AND TELEMETRY

Proposed evidence: the affected room source input, switcher, extender and display: selected input, source detect, EDID/HDCP events, signal lock, link errors, display power and fault state; no image content. Coverage and timing: Use synchronized event data from five minutes before the report through the active incident Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative signal-path map; approved room baseline; current room/session status; open incidents, maintenance and central outage notices Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: diagnosis. Decision interval: the active incident and next technician action. Minimum evidence: verified path mapping, current status from at least the failing endpoint and its upstream link, and no known shared outage. Method: walk the path in order, rank plausible failure points and recommend the least disruptive physical check; state gaps and alternatives. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

A diagnosis ranks the next technical check; it does not prove root cause. Do not inspect teaching content, credentials or payloads, restart systems or disclose restricted topology; route the case to the responsible owner.

WHY THIS IS USEFUL

Directs the first physical check instead of random component replacement.

AV-022

NO-AUDIO TRIAGE

L2 diagnosis | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

There is no amplified sound. Which stage of the audio chain has the strongest evidence for the first check?

SENSORS AND TELEMETRY

Proposed evidence: the mapped microphone receiver, DSP, amplifier and supervised loudspeaker path: power/heartbeat, route and mute state, receiver link, amplifier protection and line-supervision result; no ambient audio. Coverage and timing: Use content-free events from five minutes before the report and the current state Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative audio topology and baseline; current teaching-format requirement; room/session status; maintenance and shared-service incidents Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: diagnosis. Decision interval: the active incident and next technician action. Minimum evidence: complete audio path map and current status from source, processing and output stages. Method: rank microphone/source, DSP route, amplifier and speaker-path explanations; distinguish unavailable evidence from normal state. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

A diagnosis ranks the next technical check; it does not prove root cause. Do not inspect teaching content, credentials or payloads, restart systems or disclose restricted topology; route the case to the responsible owner.

WHY THIS IS USEFUL

Focuses the first audio check on the strongest evidenced failure stage.

3. Fault detection, triage and service-desk routing

AV-021 to AV-030 | Narrow the first technical check and route the incident without inspecting teaching or personal content.

AV-023

WIRELESS MICROPHONE TRIAGE

L2 diagnosis | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

The wireless microphone is unavailable. Should we check battery, pairing, RF path, receiver or inventory first?

SENSORS AND TELEMETRY

Proposed evidence: the named transmitter, charging dock and receiver: battery/charge state, transmitter and receiver heartbeat, RF link quality, approved pairing identifier and fault code; no audio. Coverage and timing: Use event data from 30 minutes before setup through the incident, aggregated at one minute for RF quality Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative room microphone inventory; approved frequency/pairing plan; loan/stock state; maintenance and interference notices Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: diagnosis. Decision interval: the active setup or teaching incident. Minimum evidence: verified transmitter-receiver mapping, current battery and link state, and approved pairing plan. Method: separate discharged battery, missing transmitter, pairing mismatch, RF degradation, receiver fault and incomplete evidence. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

A diagnosis ranks the next technical check; it does not prove root cause. Do not inspect teaching content, credentials or payloads, restart systems or disclose restricted topology; route the case to the responsible owner.

WHY THIS IS USEFUL

Guides the technician to the most plausible microphone failure domain.

AV-024

TOUCH-PANEL TRIAGE

L2 diagnosis | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

The touch panel is unresponsive. Does the evidence point first to panel power, network, controller service or panel hardware?

SENSORS AND TELEMETRY

Proposed evidence: the named touch panel, PoE switch port and room controller: panel power/PoE state, link and error counters, controller heartbeat, application process state and last successful check-in. Coverage and timing: Use event-level data for ten minutes before the failure and a current 30-second heartbeat Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative room control topology; approved software/configuration baseline; network status; maintenance/change history; current shared-service incident state Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: diagnosis. Decision interval: the active incident and first escalation decision. Minimum evidence: verified panel-controller-port mapping and current evidence from at least two independent layers. Method: rank power, network, controller, application and hardware domains; show where the chain becomes unobservable. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

A diagnosis ranks the next technical check; it does not prove root cause. Do not inspect teaching content, credentials or payloads, restart systems or disclose restricted topology; route the case to the responsible owner. Telemetry is not electrical safety approval; competent electrical authority remains responsible.

WHY THIS IS USEFUL

Separates a local panel issue from controller or network-service failure.

3. Fault detection, triage and service-desk routing

AV-021 to AV-030 | Narrow the first technical check and route the incident without inspecting teaching or personal content.

AV-025

INTERMITTENT HDMI

L2 diagnosis | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

The HDMI signal keeps dropping. Which supported path element is the best next check?

SENSORS AND TELEMETRY

Proposed evidence: the affected input cable test point, extender pair, switcher and display: signal-lock transitions, EDID/HDCP renegotiations, link error counters, temperature and power state; no screen content. Align events at sub-minute resolution from ten minutes before the first dropout through the incident. Coverage and timing: Use event-driven state and a current health snapshot within the decision window; aggregate only to the level needed for the question Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative path and cable specification; approved source/display capability; maintenance and replacement history; known firmware or shared-service issues Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: time-aligned diagnosis. Decision interval: the active incident and immediate swap/test decision. Minimum evidence: verified end-to-end path, synchronized event logs and at least two dropout events or an approved reproduction test. Method: compare event ordering across path segments, identify the earliest abnormal transition and report competing explanations. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

A diagnosis ranks the next technical check; it does not prove root cause. Do not inspect teaching content, credentials or payloads, restart systems or disclose restricted topology; route the case to the responsible owner.

WHY THIS IS USEFUL

Prioritises the next supported cable, input or signal-path check.

AV-026

CAPTURE INCIDENT ROUTING

L2 diagnosis | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

A scheduled capture failed. Which owner should receive the first incident route: room endpoint, schedule integration, network, storage or platform?

SENSORS AND TELEMETRY

Proposed evidence: the room capture endpoint and approved ingest/storage service path: trigger receipt, endpoint heartbeat, local storage headroom, network reachability, ingest acknowledgement and platform/storage status; no media. Coverage and timing: Use synchronized events from 15 minutes before scheduled start through the declared failure and stop window Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative capture authorisation and schedule; room/endpoint mapping; platform and storage incidents; network status; maintenance/change records Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: multi-source diagnosis. Decision interval: the failed capture window and initial routing decision. Minimum evidence: valid authorised schedule, complete endpoint/service mapping and current status for each domain. Method: reconstruct the technical sequence, identify the first missing acknowledgement and rank local, integration, network, storage and platform domains. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

A diagnosis ranks the next technical check; it does not prove root cause. Do not inspect teaching content, credentials or payloads, restart systems or disclose restricted topology; route the case to the responsible owner. Recording authority and retention rules must be confirmed independently of technical status.

WHY THIS IS USEFUL

Routes the capture incident to the owner with the strongest initial evidence.

3. Fault detection, triage and service-desk routing

AV-021 to AV-030 | Narrow the first technical check and route the incident without inspecting teaching or personal content.

AV-027

STREAM QUALITY TRIAGE

L2 diagnosis | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Streaming quality is poor. Is the strongest technical evidence in the room encoder, room network, upstream service or platform?

SENSORS AND TELEMETRY

Proposed evidence: the room encoder and managed network path to the approved platform: encoder health, bitrate target, dropped-frame count, packet loss, latency, jitter and platform ingest status; no payloads or media. Coverage and timing: Use 5-second technical counters aggregated to one minute from ten minutes before degradation through recovery Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative approved streaming profile; room/port/service mapping; network and platform incident status; endpoint configuration and change records Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: path-segment comparison plus diagnosis. Decision interval: the active degradation and routing decision. Minimum evidence: verified service path, synchronized room/network/platform metrics and the approved profile thresholds. Method: compare observed quality at each segment, identify the earliest degraded domain and report uncertainty and shared-outage evidence. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

A diagnosis ranks the next technical check; it does not prove root cause. Do not inspect teaching content, credentials or payloads, restart systems or disclose restricted topology; route the case to the responsible owner.

WHY THIS IS USEFUL

Separates local room degradation from an upstream streaming-service issue.

AV-028

RACK THERMAL CONTRIBUTION

L2 diagnosis | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

The AV rack is running hot. Is the temperature evidence strong enough to include thermal conditions in the fault investigation?

SENSORS AND TELEMETRY

Proposed evidence: the exact rack inlet/outlet positions, rack fans, PDU and affected endpoints: calibrated temperature, fan state, rack load, thermal alarms and timestamped endpoint fault/restart events. Coverage and timing: Sample temperature and load every 10-30 seconds, retain one-minute summaries and align with incident events Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds. Any numerical test instrument must have an in-date calibration or commissioning record.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative rack layout and equipment thermal limits; BMS/room cooling status; maintenance, filter and ventilation records; endpoint incident history Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: comparison plus diagnostic assessment. Decision interval: the incident window and a matched normal period. Minimum evidence: verified rack/endpoint mapping, calibrated temperature data, equipment limits and synchronized fault history. Method: compare thermal conditions with matched operating periods and fault timing; report association, lag and alternative explanations. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

A diagnosis ranks the next technical check; it does not prove root cause. Do not inspect teaching content, credentials or payloads, restart systems or disclose restricted topology; route the case to the responsible owner.

WHY THIS IS USEFUL

Decides whether cooling or rack inspection should accompany AV diagnosis.

3. Fault detection, triage and service-desk routing

AV-021 to AV-030 | Narrow the first technical check and route the incident without inspecting teaching or personal content.

AV-029

LOCAL OR SHARED INCIDENT

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is the current fault confined to one room, or does it affect a shared service or asset group?

SENSORS AND TELEMETRY

Proposed evidence: the affected room endpoints and comparable endpoints that share the same network, platform, controller or power dependency: content-free fault, heartbeat and reachability events with synchronized timestamps. Coverage and timing: Use event-level status across the suspected dependency group from ten minutes before the first report to the current time Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative service-dependency topology; current timetable/room use; central network/platform/power incidents; maintenance and change records Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: scope calculation plus comparison. Decision interval: the active incident and dispatch decision. Minimum evidence: verified shared-dependency mapping, current status from the reported room and at least one comparable endpoint. Method: group simultaneous failures by dependency, distinguish common-mode and room-specific evidence and show unobserved areas. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

A diagnosis ranks the next technical check; it does not prove root cause. Do not inspect teaching content, credentials or payloads, restart systems or disclose restricted topology; route the case to the responsible owner.

WHY THIS IS USEFUL

Determines whether to dispatch locally or escalate a shared-service incident.

AV-030

MINIMUM ESCALATION PACK

L3 recommendation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

What is the minimum content-free evidence pack needed to route this incident to the correct owner?

SENSORS AND TELEMETRY

Proposed evidence: the affected endpoint and its mapped service path: content-free health, fault codes, configuration identifier, timestamps, completed diagnostic checks and monitoring quality; no media, credentials or payloads. Coverage and timing: Collect only the active incident window and the smallest pre-incident context required by the owner-approved schema Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative service-desk routing rules; asset ownership and topology; incident severity criteria; current known outages; privacy/security retention policy Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: evidence-completeness calculation plus recommendation. Decision interval: the current escalation decision. Minimum evidence: asset identity, room/service mapping, incident time, reproducible symptom, completed safe checks and current owner status. Method: compare available evidence with the target queue requirements, remove unnecessary data and identify the next safe missing check. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

A diagnosis ranks the next technical check; it does not prove root cause. Do not inspect teaching content, credentials or payloads, restart systems or disclose restricted topology; route the case to the responsible owner.

WHY THIS IS USEFUL

Creates a minimal, privacy-preserving incident handoff for the correct owner.

4. Live teaching support and fallback choices

AV-031 to AV-040 | Present authorised, time-bounded continuity options while lecturers and service owners retain control.

AV-031

FALLBACK INPUT

L3 recommendation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

The primary input has failed. Which approved fallback input is currently evidenced as usable?

SENSORS AND TELEMETRY

Proposed evidence: the room alternate input panel, switcher/extender routes and display: connector presence, selected route, signal lock, endpoint health and approved profile identifier; no screen content. Coverage and timing: Use current state and events during the active incident; recheck immediately before advising the fallback Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative room fallback map and AV baseline; declared presenter source; room/session status; open incidents and maintenance restrictions Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus recommendation. Decision interval: the next five minutes of the live session. Minimum evidence: verified alternate path, current endpoint state and an approved connection for the declared source. Method: filter to approved paths, rank by fewest dependencies and state the physical action for an authorised technician. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not switch inputs, move sessions, start or stop capture, or choose on behalf of the lecturer. Present only authorised options and current limitations; the lecturer, organiser and service owner decide and act.

WHY THIS IS USEFUL

Chooses a currently evidenced fallback input without changing configuration.

AV-032

MICROPHONE FALLBACK

L3 recommendation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

The wireless microphone failed during teaching. Which authorised audio fallback is currently available?

SENSORS AND TELEMETRY

Proposed evidence: the room wired microphone input, spare wireless set, DSP/amp path and charging dock: endpoint health, input availability, battery/charge state, receiver status and supervised output path; no audio content. Coverage and timing: Use event state and current health within the active incident, with a recheck before use Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative room audio fallback procedure; approved spare/loan stock; room profile; current incident and safety/access restrictions Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: recommendation. Decision interval: the next five minutes of the live session. Minimum evidence: at least one approved alternative source, healthy output chain and current stock/room status. Method: compare wired, spare wireless and non-amplified approved options by readiness, setup time and constraints. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not switch inputs, move sessions, start or stop capture, or choose on behalf of the lecturer. Present only authorised options and current limitations; the lecturer, organiser and service owner decide and act.

WHY THIS IS USEFUL

Supports an immediate authorised audio-fallback discussion with the lecturer.

4. Live teaching support and fallback choices

AV-031 to AV-040 | Present authorised, time-bounded continuity options while lecturers and service owners retain control.

AV-033

DISPLAY-FAILURE ALTERNATIVE

L3 recommendation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

The main display cannot be restored quickly. Which authorised teaching alternative is technically feasible now?

SENSORS AND TELEMETRY

Proposed evidence: the room secondary display, local confidence monitor and other approved presentation endpoints: power, input availability, signal lock and current fault state; no image content. Coverage and timing: Use current status during the incident and any owner-issued estimated restoration time Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative room fallback profile; current timetable/booking; session format supplied by the lecturer; alternative-room status; AV/network incidents Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: recommendation. Decision interval: the next ten minutes and remaining session duration. Minimum evidence: confirmed main-display fault, at least one approved alternative and the lecturer’s essential presentation need. Method: compare secondary display, audio-led continuation, approved remote sharing and owner-authorised relocation consideration; show trade-offs. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not switch inputs, move sessions, start or stop capture, or choose on behalf of the lecturer. Present only authorised options and current limitations; the lecturer, organiser and service owner decide and act.

WHY THIS IS USEFUL

Identifies a feasible teaching alternative while the main display remains unavailable.

AV-034

LOCAL CONTROL FALLBACK

L3 recommendation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

The touch panel has failed. Is there an approved technician-only local-control fallback?

SENSORS AND TELEMETRY

Proposed evidence: the room controller and documented alternate control interface: controller heartbeat, alternate interface availability, permission state and endpoint health; no user interactions or content. Coverage and timing: Use current status and the approved technician procedure for the active incident Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative room control design; technician role/permission; approved fallback procedure; current network/controller incident and change state Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus recommendation. Decision interval: the live incident and immediate technician action. Minimum evidence: verified controller/interface mapping, current role permission and an in-date fallback procedure. Method: confirm whether the alternate control is available and permitted; otherwise return physical escalation or not assessable. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not switch inputs, move sessions, start or stop capture, or choose on behalf of the lecturer. Present only authorised options and current limitations; the lecturer, organiser and service owner decide and act.

WHY THIS IS USEFUL

Shows whether an authorised technician has a local-control option.

4. Live teaching support and fallback choices

AV-031 to AV-040 | Present authorised, time-bounded continuity options while lecturers and service owners retain control.

AV-035

NETWORK-DEGRADED FUNCTIONS

L2 calculation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

During managed-network degradation, which room AV functions still have current evidence that they can operate?

SENSORS AND TELEMETRY

Proposed evidence: the named room local controller, display/audio paths, capture/hybrid endpoints and managed network port: local endpoint state, dependency flags, reachability and content-free network quality; no payloads. Coverage and timing: Use current network-owner status plus room state during the active degradation; aggregate network metrics at one minute Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative network incident and affected scope; room AV dependency profile; current session requirements; platform status and local fallback procedure Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: dependency calculation. Decision interval: the active outage and next ten minutes. Minimum evidence: verified room/service dependency map, current network owner status and local endpoint health. Method: separate proven local functions, network-dependent functions, degraded functions and untested assumptions. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not switch inputs, move sessions, start or stop capture, or choose on behalf of the lecturer. Present only authorised options and current limitations; the lecturer, organiser and service owner decide and act.

WHY THIS IS USEFUL

Explains which room functions can continue during network degradation.

AV-036

CAPTURE FALLBACK

L3 recommendation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Lecture capture is unavailable. Which authorised alternative can support staff explain for this session?

SENSORS AND TELEMETRY

Proposed evidence: the approved capture endpoint and any owner-approved alternate service: endpoint/platform status, storage availability and fallback service health; no recording content. Coverage and timing: Use current owner-issued service state and endpoint health for the active session window Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative capture policy and session authorisation; approved fallback methods; accessibility requirements; lecturer/academic owner decision; platform incident notice Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus recommendation. Decision interval: the active session and immediate communication window. Minimum evidence: confirmed capture unavailability, current policy and at least one owner-approved alternative or deferral route. Method: list approved alternatives with prerequisites and limitations; return deferral when no authorised substitute exists. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not switch inputs, move sessions, start or stop capture, or choose on behalf of the lecturer. Present only authorised options and current limitations; the lecturer, organiser and service owner decide and act. Recording authority and retention rules must be confirmed independently of technical status.

WHY THIS IS USEFUL

Gives staff an authorised continuity option when capture cannot be restored.

4. Live teaching support and fallback choices

AV-031 to AV-040 | Present authorised, time-bounded continuity options while lecturers and service owners retain control.

AV-037

PLATFORM-OUTAGE CONTINUITY

L2 calculation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

A central teaching platform is unavailable. Which local room functions remain independently usable?

SENSORS AND TELEMETRY

Proposed evidence: the room display, audio, local controller and any platform-independent endpoints: local power, heartbeat, route state and dependency flags; no content. Coverage and timing: Use current room status and central platform owner notice throughout the active outage
Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative platform incident; room AV dependency profile; current session requirement; network status and approved continuity guidance
Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus dependency calculation. Decision interval: the active platform outage. Minimum evidence: current owner-confirmed outage scope, verified room dependency map and local endpoint state. Method: identify functions independent of the failed platform and label assumed or untested functions separately. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not switch inputs, move sessions, start or stop capture, or choose on behalf of the lecturer. Present only authorised options and current limitations; the lecturer, organiser and service owner decide and act.

WHY THIS IS USEFUL

Separates usable local room functions from failed central services.

AV-038

DIAGNOSE OR RELOCATE

L3 recommendation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

With limited session time remaining, should we continue local diagnosis or advise the organiser to request an authorised room change?

SENSORS AND TELEMETRY

Proposed evidence: the affected room fault state and candidate rooms' mandatory AV endpoint health: current fault persistence, completed safe checks, estimated owner restoration time and content-free readiness evidence for eligible alternatives. Coverage and timing: Use the active incident plus the remaining setup/session window; candidate-room status must be current
Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative room booking and eligibility; event/session owner; current timetable; AV support capacity; alternative-room capability; accessibility and closure status
Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: recommendation. Decision interval: the time remaining before or during the session. Minimum evidence: current fault evidence, completed checks, owner ETA, decision deadline and at least one eligible candidate room. Method: compare expected local recovery with authorised relocation lead time and constraints; expose uncertainty and the owner who must decide. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not switch inputs, move sessions, start or stop capture, or choose on behalf of the lecturer. Present only authorised options and current limitations; the lecturer, organiser and service owner decide and act.

WHY THIS IS USEFUL

Supports a time-bounded choice between diagnosis and an authorised relocation request.

4. Live teaching support and fallback choices

AV-031 to AV-040 | Present authorised, time-bounded continuity options while lecturers and service owners retain control.

AV-039

RECOVERY STABILITY

L2 comparison | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

The fault appears to have cleared. Has the service remained stable long enough to return to normal use?

SENSORS AND TELEMETRY

Proposed evidence: the affected endpoint and complete service path: heartbeat, error counters, signal/route state and repeated approved self-test results after recovery; no content. Coverage and timing: Use a defined soak period appropriate to the fault, normally 10-30 minutes, and include the next setup check Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative incident record; approved recovery/acceptance criteria; room baseline; maintenance/change history; next scheduled session Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: recovery comparison. Decision interval: the post-recovery soak period and next use. Minimum evidence: known symptom, current baseline, stable mapped telemetry and successful mandatory tests. Method: compare the recovered state with baseline and pre-fault behaviour; identify residual errors, untested dependencies and recheck time. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not switch inputs, move sessions, start or stop capture, or choose on behalf of the lecturer. Present only authorised options and current limitations; the lecturer, organiser and service owner decide and act.

WHY THIS IS USEFUL

Prevents premature return to service after a short-lived recovery.

AV-040

LECTURER STATUS UPDATE

L1 lookup/observation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

What concise technical status, limitation and next update should we give the lecturer now?

SENSORS AND TELEMETRY

Proposed evidence: Proposed content-free telemetry: No room or content sensing is required. Proposed integrations may expose owner-confirmed service state, affected function, completed safe checks and next update time; no media, user activity or restricted topology. Coverage and timing: Use the current incident snapshot and update only when the responsible owner changes status. Use only owner-issued status or content-free technical metadata with retrieved time, permission, provenance and conflict flags Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative incident owner message; current room/session status; approved communication template; support ETA and fallback policy Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus constrained summarisation. Decision interval: the current communication and next update interval. Minimum evidence: owner-confirmed facts, affected function, available fallback and next review time. Method: produce a short status separating confirmed, probable and unknown information and naming the responsible decision owner. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not switch inputs, move sessions, start or stop capture, or choose on behalf of the lecturer. Present only authorised options and current limitations; the lecturer, organiser and service owner decide and act.

WHY THIS IS USEFUL

Gives the lecturer a clear status, limitation and next update time.

5. Hybrid teaching, lecture capture and streaming infrastructure

AV-041 to AV-050 | Verify the authorised service chain without examining captured or transmitted content.

AV-041

CAPTURE SCHEDULE MATCH

L2 comparison | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Does the authorised capture schedule still match the current room, session and timetable?

SENSORS AND TELEMETRY

Proposed evidence: the named room capture endpoint and schedule-integration service: schedule trigger identifier, room/endpoint ID, planned start/stop times and acknowledgement state; no content. Compare owner-issued schedules when created or changed and recheck within 30 minutes of session start. Coverage and timing: Use event-driven state and a current health snapshot within the decision window; aggregate only to the level needed for the question Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Current timetable and room allocation; authoritative capture schedule; session identifier; capture policy/authorisation; change and cancellation notices Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus schedule comparison. Decision interval: the session setup window. Minimum evidence: matching current session, room, endpoint, authorised mode and start/stop times from both owners. Method: identify exact match, late change, duplicate, missing trigger or unresolved conflict; use owner precedence for corrections. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not view, capture or analyse media, screens, speech, recordings, credentials or network payloads, and do not authorise recording or streaming. Policy, consent, platform and service owners retain authority. Recording authority and retention rules must be confirmed independently of technical status.

WHY THIS IS USEFUL

Prevents capture from being associated with the wrong room or session.

AV-042

AUTHORISED CAPTURE MODE

L1 lookup/observation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which capture mode, if any, is currently authorised for this room and session?

SENSORS AND TELEMETRY

Proposed evidence: Proposed content-free telemetry: No room or content sensing is required. Proposed integrations may expose approved capability flags and endpoint service state; no audio, video, screen or recording access. Coverage and timing: Use current owner-issued mode status at the setup time. Use only owner-issued status or content-free technical metadata with retrieved time, permission, provenance and conflict flags Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative capture policy; session-specific authorisation and notice state; timetable/room allocation; approved room capability profile; privacy/accessibility instructions Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup. Decision interval: the current session setup. Minimum evidence: current session identifier, owner-approved capture mode and room capability. Method: return the authorised mode, technical prerequisites and any unresolved owner conflict; do not infer from prior sessions. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not view, capture or analyse media, screens, speech, recordings, credentials or network payloads, and do not authorise recording or streaming. Policy, consent, platform and service owners retain authority. Recording authority and retention rules must be confirmed independently of technical status.

WHY THIS IS USEFUL

Separates technical capability from the capture mode actually authorised.

5. Hybrid teaching, lecture capture and streaming infrastructure

AV-041 to AV-050 | Verify the authorised service chain without examining captured or transmitted content.

AV-043

HYBRID SERVICE CHAIN

L2 calculation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is every required component in the approved hybrid-teaching service chain currently ready?

SENSORS AND TELEMETRY

Proposed evidence: the room microphone/DSP, camera endpoint, display, encoder/capture appliance, managed uplink and approved platform interface: content-free heartbeat, route state, privacy state, encoding health, network quality and platform reachability. Coverage and timing: Use event-driven status from 30 minutes before setup and one-minute network aggregates through session start Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Current timetable/room; approved hybrid mode; room AV profile; platform and network owner status; accessibility provision; maintenance and closure notices Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: multi-source readiness calculation. Decision interval: the setup window before the hybrid session. Minimum evidence: valid hybrid authorisation, complete service-path mapping and current status for every mandatory dependency. Method: apply hard checks in service order and return ready, degraded, on-site check or not assessable with the first missing dependency. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not view, capture or analyse media, screens, speech, recordings, credentials or network payloads, and do not authorise recording or streaming. Policy, consent, platform and service owners retain authority.

WHY THIS IS USEFUL

Targets the missing dependency before hybrid teaching begins.

AV-044

ROOM UPLINK HEADROOM

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Does the managed room uplink have current headroom for the approved streaming profile?

SENSORS AND TELEMETRY

Proposed evidence: the exact room network port/VLAN path and encoder interface: available throughput headroom, packet loss, latency, jitter, link errors and encoder bitrate; no payloads. Coverage and timing: Sample technical counters every 5-10 seconds and report one-minute aggregates during a 10-minute pre-session test Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative approved streaming profile; room/port mapping; network owner status and maintenance; platform ingest status; current incident notices Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: comparison. Decision interval: the pre-session test and expected stream window. Minimum evidence: verified room path, approved profile thresholds, synchronized metrics and no owner-declared blocking incident. Method: compare headroom and quality distributions with the profile, report worst intervals and uncertainty; avoid single-snapshot conclusions. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not view, capture or analyse media, screens, speech, recordings, credentials or network payloads, and do not authorise recording or streaming. Policy, consent, platform and service owners retain authority.

WHY THIS IS USEFUL

Determines whether a lower-bandwidth approved profile should be considered.

5. Hybrid teaching, lecture capture and streaming infrastructure

AV-041 to AV-050 | Verify the authorised service chain without examining captured or transmitted content.

AV-045

REMOTE AUDIO RETURN

L2 diagnosis | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is the approved remote-audio return and echo-control path technically healthy?

SENSORS AND TELEMETRY

Proposed evidence: the room DSP, echo-canceller, remote return channel and amplifier path: route/mute state, reference signal presence, echo-canceller convergence/status and authorised loopback-test result; no speech or audio recording. Coverage and timing: Use content-free self-test events during the setup window and current state at session start Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative hybrid audio design and baseline; approved platform test procedure; current session mode; maintenance/change records Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: diagnosis. Decision interval: the hybrid setup test. Minimum evidence: verified audio-return mapping, approved test result and current DSP/platform state. Method: check return path, reference path and echo-control state in order; distinguish absent signal, misroute, degraded convergence and untested state. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not view, capture or analyse media, screens, speech, recordings, credentials or network payloads, and do not authorise recording or streaming. Policy, consent, platform and service owners retain authority.

WHY THIS IS USEFUL

Directs testing of the remote return path before a live session.

AV-046

CAMERA PRIVACY STATE

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is the room camera endpoint healthy and in the authorised privacy state before hybrid use?

SENSORS AND TELEMETRY

Proposed evidence: the mapped camera power/control endpoint, physical shutter or privacy-indicator circuit and managed USB/network interface: power/heartbeat, shutter state, privacy-indicator state, approved configuration ID and endpoint fault; no image or video. Coverage and timing: Use event state throughout the setup window and require a fresh status within two minutes of use Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative room camera/privacy baseline; session capture/hybrid authorisation; current room profile; maintenance and privacy incident notices Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus privacy-state comparison. Decision interval: the immediate pre-use window. Minimum evidence: verified camera-to-room mapping, current physical/privacy state and session authorisation. Method: compare endpoint state with the approved baseline; require a physical check when indicators conflict or are unobservable. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not view, capture or analyse media, screens, speech, recordings, credentials or network payloads, and do not authorise recording or streaming. Policy, consent, platform and service owners retain authority. Show only the minimum detail permitted for the requester.

WHY THIS IS USEFUL

Withholds camera use when health or privacy-state evidence is incomplete.

5. Hybrid teaching, lecture capture and streaming infrastructure

AV-041 to AV-050 | Verify the authorised service chain without examining captured or transmitted content.

AV-047

CAPTURE STATE TIMING

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Did the capture endpoint enter and leave its authorised state at the scheduled times?

SENSORS AND TELEMETRY

Proposed evidence: the capture endpoint and schedule-trigger interface: technical start/stop state, trigger acknowledgement, endpoint heartbeat and ingest session ID; no recording content. Coverage and timing: Use synchronized event timestamps from five minutes before planned start to five minutes after planned stop Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative capture schedule and authorisation; timetable/room allocation; platform state; change/cancellation notices Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: event-sequence comparison. Decision interval: the authorised capture interval. Minimum evidence: matching session/room/endpoint identifiers, schedule times and complete start/stop acknowledgements. Method: compare planned and observed technical states, quantify delay and flag missing or contradictory events. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not view, capture or analyse media, screens, speech, recordings, credentials or network payloads, and do not authorise recording or streaming. Policy, consent, platform and service owners retain authority. Recording authority and retention rules must be confirmed independently of technical status.

WHY THIS IS USEFUL

Supports investigation of missed or over-running states without viewing content.

AV-048

FAILED STREAM DOMAIN

L2 diagnosis | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

A stream never reached the platform. Which technical domain has the strongest first evidence?

SENSORS AND TELEMETRY

Proposed evidence: the room encoder, managed uplink, authentication-status service and platform ingest endpoint: encoder output state, network reachability/quality, non-secret credential validity flag and ingest acknowledgement; no media, payloads or credential values. Coverage and timing: Align events from five minutes before planned start through the failed connection attempt Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative service-path ownership; approved streaming profile; certificate/service-account owner status; network/platform incidents; endpoint change history Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: diagnosis. Decision interval: the failed stream start and first escalation. Minimum evidence: verified service path, synchronized encoder/network/credential-status/platform events and current owner notices. Method: reconstruct the connection sequence, identify the first failed acknowledgement and rank endpoint, network, credential-owner and platform domains. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not view, capture or analyse media, screens, speech, recordings, credentials or network payloads, and do not authorise recording or streaming. Policy, consent, platform and service owners retain authority.

WHY THIS IS USEFUL

Routes the failed stream to the strongest first technical owner.

5. Hybrid teaching, lecture capture and streaming infrastructure

AV-041 to AV-050 | Verify the authorised service chain without examining captured or transmitted content.

AV-049

REMOTE FALLBACK

L3 recommendation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which authorised remote-participation fallback remains available if the primary platform fails?

SENSORS AND TELEMETRY

Proposed evidence: approved alternate endpoint/service health only; local display/audio readiness, alternate platform reachability and room network state; no meeting content or participant data. Coverage and timing: Use current owner-issued outage state and fallback service status during the active incident Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative continuity policy; session owner approval; approved alternate platform/service; accessibility requirements; room capability and network status Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus recommendation. Decision interval: the active outage and next ten minutes. Minimum evidence: confirmed primary outage, current approved fallback and technical readiness of its mandatory dependencies. Method: list only owner-approved options, prerequisites, limitations and the person/service that must authorise the change. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not view, capture or analyse media, screens, speech, recordings, credentials or network payloads, and do not authorise recording or streaming. Policy, consent, platform and service owners retain authority.

WHY THIS IS USEFUL

Provides an authorised continuity option when the main platform is unavailable.

AV-050

NOTICE AND RETENTION CHECK

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Are the current recording notice, retention rule and authorised-access conditions confirmed for this session?

SENSORS AND TELEMETRY

Proposed evidence: Proposed content-free telemetry: No room or content sensing is required. Proposed integrations may expose session/policy identifiers, version and technical notice-display availability; no participant or recording data. Retrieve at setup time and recheck after any schedule or policy change. Coverage and timing: Use only owner-issued status or content-free technical metadata with retrieved time, permission, provenance and conflict flags Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative capture/privacy policy owner; session authorisation; notice and retention configuration; room/session schedule; approved access-control rules Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus policy-version comparison. Decision interval: before any capture function is prepared. Minimum evidence: current session ID, applicable policy version, authorised mode, required notice and owner-confirmed retention/access settings. Method: compare the session configuration with current owner rules and return conflict, missing approval or not assessable for specialist review. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not view, capture or analyse media, screens, speech, recordings, credentials or network payloads, and do not authorise recording or streaming. Policy, consent, platform and service owners retain authority. Recording authority and retention rules must be confirmed independently of technical status.

WHY THIS IS USEFUL

Prevents technical readiness being confused with permission to record or retain.

6. Accessibility and assistive-technology provision

AV-051 to AV-060 | Check technical provision against stated functional requirements without inferring needs or certifying accessibility.

AV-051

HEARING LOOP STATUS

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is the installed hearing loop or other approved assistive-listening system currently in service?

SENSORS AND TELEMETRY

Proposed evidence: the mapped loop amplifier/transmitter and calibrated field-test point: power/fault state, output current, latest in-date field-strength test summary and monitoring self-health; no audio. Coverage and timing: Use current device status and the latest owner-approved test, with a fresh pre-session check Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds. Any numerical test instrument must have an in-date calibration or commissioning record.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative room accessibility profile; equipment owner status; maintenance/commissioning records; current room/session allocation; accessibility-service instructions Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus technical-state comparison. Decision interval: the requested session setup. Minimum evidence: verified equipment-room mapping, current owner state and in-date test evidence. Method: return in service, degraded, physical test required or not assessable; state test age and coverage limits. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not infer a person's needs, identify users, promise provision or certify accessibility. Use only the stated functional requirement and owner-confirmed provision; unresolved evidence requires accessibility-service or organiser confirmation. Do not disclose who requested support or infer any disability or diagnosis.

WHY THIS IS USEFUL

Determines whether an on-site assistive-listening test is required.

AV-052

PORTABLE RECEIVER STOCK

L3 forecast | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Are enough charged portable assistive-listening receivers available through the approved loan process?

SENSORS AND TELEMETRY

Proposed evidence: the owner-managed receiver stock and charging docks: anonymous item count, charge state, charge fault, cleaning/test state and maintenance hold; no borrower identity. Flag stale counts, holds and unreturned items without borrower identities. Coverage and timing: Use issue/return events and 5-minute charging summaries; forecast availability at the setup deadline. Use owner-issued stock time, test/charge state and provenance Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative loan-stock register; requested quantity supplied through the authorised process; issue/cleaning rules; maintenance and reservation status Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: calculation plus short-horizon forecast. Decision interval: the session setup deadline. Minimum evidence: current approved request quantity, reconciled stock count and reliable battery/charging status. Method: calculate available, charging, held, faulty and uncertain receivers and show the shortfall without assigning items. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not infer a person's needs, identify users, promise provision or certify accessibility. Use only the stated functional requirement and owner-confirmed provision; unresolved evidence requires accessibility-service or organiser confirmation. Do not disclose who requested support or infer any disability or diagnosis.

WHY THIS IS USEFUL

Supports a loan-stock decision without exposing who requires a receiver.

6. Accessibility and assistive-technology provision

AV-051 to AV-060 | Check technical provision against stated functional requirements without inferring needs or certifying accessibility.

AV-053

LIVE CAPTION PATH

L2 calculation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is the approved live-caption endpoint and audience display path ready for this room?

SENSORS AND TELEMETRY

Proposed evidence: the caption-service endpoint, room display route and managed network path: service heartbeat, endpoint reachability, display route state and network quality; no speech, captions text or screen content. Coverage and timing: Use current service status and one-minute network summaries during the setup window Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative approved caption provision; session authorisation; room display profile; accessibility-service and platform status; maintenance/closure notices Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: multi-source readiness calculation. Decision interval: the caption setup and session start. Minimum evidence: current approved provision, verified room/service mapping and healthy mandatory technical dependencies. Method: check endpoint, network and display path; classify ready, degraded, physical test, owner confirmation or not assessable. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not infer a person's needs, identify users, promise provision or certify accessibility. Use only the stated functional requirement and owner-confirmed provision; unresolved evidence requires accessibility-service or organiser confirmation. Do not disclose who requested support or infer any disability or diagnosis.

WHY THIS IS USEFUL

Targets a caption endpoint or display-path check before the session.

AV-054

ACCESSIBLE CONTROL METHOD

L2 calculation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is an authorised accessible control method available for the presentation setup?

SENSORS AND TELEMETRY

Proposed evidence: the named accessible control endpoint or physical interface: power/heartbeat, input-device status, approved control-profile ID and fault state; no user interactions or content. Coverage and timing: Use current status within the setup window and the latest commissioning record Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative room accessibility profile; approved control methods; user-stated functional requirement for this interaction; equipment owner and maintenance status Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus constraint calculation. Decision interval: the requested setup interval. Minimum evidence: current room, approved control options, stated functional requirement and current endpoint status. Method: filter to approved methods that satisfy the stated requirement; state physical-verification and assistance dependencies. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not infer a person's needs, identify users, promise provision or certify accessibility. Use only the stated functional requirement and owner-confirmed provision; unresolved evidence requires accessibility-service or organiser confirmation. Do not disclose who requested support or infer any disability or diagnosis.

WHY THIS IS USEFUL

Confirms whether an authorised alternative control method is available.

6. Accessibility and assistive-technology provision

AV-051 to AV-060 | Check technical provision against stated functional requirements without inferring needs or certifying accessibility.

AV-055

LECTERN FUNCTIONAL FIT

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Does the approved lectern and connection arrangement meet the functional requirement stated for this session?

SENSORS AND TELEMETRY

Proposed evidence: the relevant lectern power/data/AV ports and any adjustable lectern actuator: port health, actuator status and content-free endpoint availability; dimensions and reach are not inferred from sensors. Coverage and timing: Use current technical status at setup time; rely on owner-verified physical measurements and layout Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative current room layout and lectern dimensions; accessibility profile; stated functional requirement; room allocation; maintenance and closure state Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus spatial constraint comparison. Decision interval: before room setup or selection. Minimum evidence: current verified layout, approved measurements, required connection type and current port/actuator status. Method: compare reach, clearance and connection constraints; require an on-site check where current layout or setup differs from records. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not infer a person's needs, identify users, promise provision or certify accessibility. Use only the stated functional requirement and owner-confirmed provision; unresolved evidence requires accessibility-service or organiser confirmation.

WHY THIS IS USEFUL

Supports a setup decision against the functional requirement stated for the session.

AV-056

INTERPRETER CONNECTION

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Can the room support the approved interpreter or communication arrangement without monitoring content?

SENSORS AND TELEMETRY

Proposed evidence: the designated audio feed, monitor/display and approved communication endpoint: route availability, endpoint health, display status and network reachability; no speech, video, captions or content. Coverage and timing: Use content-free status during the setup window and an authorised technical self-test Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative session arrangement; interpreter/communication requirements supplied through the approved process; room AV/accessibility profile; platform and maintenance status Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus configuration comparison. Decision interval: the session setup window. Minimum evidence: current approved arrangement, complete room/service mapping and healthy mandatory endpoints. Method: compare required feeds/displays with the approved room profile and identify missing, degraded or untested dependencies. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not infer a person's needs, identify users, promise provision or certify accessibility. Use only the stated functional requirement and owner-confirmed provision; unresolved evidence requires accessibility-service or organiser confirmation. Do not disclose who requested support or infer any disability or diagnosis.

WHY THIS IS USEFUL

Checks the approved communication setup without monitoring speech or teaching.

6. Accessibility and assistive-technology provision

AV-051 to AV-060 | Check technical provision against stated functional requirements without inferring needs or certifying accessibility.

AV-057

VISUAL ACCESS PRESET

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is the approved high-contrast or enlarged-display preset present and technically healthy?

SENSORS AND TELEMETRY

Proposed evidence: the mapped display/controller and calibrated viewing-zone light sensor where commissioned: approved preset ID, display brightness/backlight state, signal path health and numerical illuminance; no screen content. Coverage and timing: Use current preset/endpoint status and one-minute illuminance summaries during setup Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative accessibility display preset; room/display profile; current layout and viewing-zone definition; stated functional requirement; maintenance state Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus comparison. Decision interval: the pre-session setup. Minimum evidence: approved preset, verified display path, current brightness state and eligible viewing-zone light evidence. Method: compare technical state with the approved preset and flag glare/light uncertainty, physical validation need and any unavailable function. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not infer a person's needs, identify users, promise provision or certify accessibility. Use only the stated functional requirement and owner-confirmed provision; unresolved evidence requires accessibility-service or organiser confirmation.

WHY THIS IS USEFUL

Determines whether the approved visual preset needs verification or fallback.

AV-058

ACOUSTIC TEST CONTEXT

L3 recommendation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is background sound low and stable enough for a valid content-free assistive-audio test?

SENSORS AND TELEMETRY

Proposed evidence: the defined room test/seating zone: calibrated A-weighted sound level and percentile statistics only; no raw audio, speech recognition or recording. Compute one-second levels locally and retain one-minute LAeq/percentiles during an empty or controlled test window. Coverage and timing: Use event-driven state and a current health snapshot within the decision window; aggregate only to the level needed for the question Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds. Any numerical.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative room acoustic commissioning baseline; approved test method; current booking/activity schedule; room closure and maintenance status Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: comparison. Decision interval: the proposed technical test window. Minimum evidence: verified acoustic sensor location, calibrated numerical levels, current room activity state and the test acceptance range. Method: compare background statistics with the approved test condition and recommend proceed, wait, relocate test point or not assessable. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not infer a person's needs, identify users, promise provision or certify accessibility. Use only the stated functional requirement and owner-confirmed provision; unresolved evidence requires accessibility-service or organiser confirmation. Do not disclose who requested support or infer any disability or diagnosis.

WHY THIS IS USEFUL

Shows whether the assistive-audio test should be repeated in quieter conditions.

6. Accessibility and assistive-technology provision

AV-051 to AV-060 | Check technical provision against stated functional requirements without inferring needs or certifying accessibility.

AV-059

ASSISTIVE FALLBACK

L3 recommendation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

If the preferred assistive technology is unavailable, which authorised technical alternative can be considered?

SENSORS AND TELEMETRY

Proposed evidence: the approved fallback endpoints or portable equipment: content-free health, stock/charge state and service reachability; no user identity or content. Coverage and timing: Use current owner status and forecast availability at the setup deadline Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative accessibility plan and service owner; stated functional requirement; approved fallback catalogue; room/booking status; loan and maintenance records Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: recommendation. Decision interval: the remaining setup time and session duration. Minimum evidence: confirmed primary unavailability, current owner-approved alternatives and current technical readiness. Method: filter to alternatives authorised for the stated requirement, show dependencies and identify the owner who must confirm suitability. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not infer a person's needs, identify users, promise provision or certify accessibility. Use only the stated functional requirement and owner-confirmed provision; unresolved evidence requires accessibility-service or organiser confirmation. Do not disclose who requested support or infer any disability or diagnosis.

WHY THIS IS USEFUL

Enables an early fallback discussion when preferred provision is unavailable.

AV-060

ACCESSIBILITY HANDOVER

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is the assistive-technology setup, testing responsibility and support handover complete for this session?

SENSORS AND TELEMETRY

Proposed evidence: the approved assistive endpoints and owner-issued checklist status: content-free device health and checklist completion timestamps only; no person, diagnosis, speech or content data. Coverage and timing: Use the final setup window and require a current status before session start Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative accessibility-service handover checklist; session/room allocation; named support responsibilities; equipment status; escalation contacts and maintenance state Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus checklist comparison. Decision interval: the final pre-session handover. Minimum evidence: current approved provision, completed owner checklist, healthy required endpoints and confirmed responsibility contacts. Method: separate completed, outstanding, untested and conflicting items and identify the responsible owner for each gap. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not infer a person's needs, identify users, promise provision or certify accessibility. Use only the stated functional requirement and owner-confirmed provision; unresolved evidence requires accessibility-service or organiser confirmation. Do not disclose who requested support or infer any disability or diagnosis.

WHY THIS IS USEFUL

Prevents gaps in technical ownership at session start.

7. Maintenance, spares, upgrades and handover

AV-061 to AV-070 | Plan proportionate lifecycle actions using current asset, teaching and service evidence.

AV-061

SERVICE-DUE PRIORITY

L3 recommendation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which AV assets should be serviced before the next high-demand teaching period?

SENSORS AND TELEMETRY

Proposed evidence: mapped projectors/displays, microphones, capture endpoints, racks and managed controllers: runtime or light-source hours, battery cycles, fault counts, temperature/power alarms, error rate and monitoring health. Coverage and timing: Use daily aggregates over the selected term plus current state; retain event windows around faults Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative maintenance schedule; asset criticality and warranty; current timetable/demand period; incident history; room eligibility and access windows Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: risk calculation plus recommendation. Decision interval: the planning horizon before the next demand peak. Minimum evidence: stable asset mapping, service thresholds, comparable usage/fault data and current teaching criticality. Method: score service urgency from due state, failure evidence, consequence and available window; show uncertainty and missing data. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not sign off maintenance, approve a change, patch or replacement, or return equipment to service. Asset owners and competent engineers decide; missing acceptance or handover evidence keeps the answer limited.

WHY THIS IS USEFUL

Builds a defensible service-priority list before peak demand.

AV-062

PEAK-DEMAND SPARES

L3 forecast | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which approved spares should be staged for the coming assessment or event peak?

SENSORS AND TELEMETRY

Proposed evidence: the owner-managed spares store and charging locations: stock count, tested/clean state, battery charge/health and maintenance hold; no borrower identity. Flag stale counts, holds and unreturned items without borrower identities. Coverage and timing: Use issue/return events, daily reconciliations and a forecast to the start of the peak period. Use owner-issued stock time, test/charge state and provenance Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative timetable/event demand; asset population and failure history; spare catalogue and minimum stock policy; replenishment lead times Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: forecast plus recommendation. Decision interval: the defined peak period. Minimum evidence: current reconciled stock, eligible historical failure rates, expected room demand and replenishment constraints. Method: forecast demand by spare class, provide ranges and identify items where sparse history makes the estimate unreliable. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not sign off maintenance, approve a change, patch or replacement, or return equipment to service. Asset owners and competent engineers decide; missing acceptance or handover evidence keeps the answer limited.

WHY THIS IS USEFUL

Stages evidence-based spares without overstocking or inferring session content.

7. Maintenance, spares, upgrades and handover

AV-061 to AV-070 | Plan proportionate lifecycle actions using current asset, teaching and service evidence.

AV-063

RECURRING COMPONENT FAULT

L2 diagnosis | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Do recurring faults justify targeted testing of one component class, room path or shared service?

SENSORS AND TELEMETRY

Proposed evidence: the mapped AV assets and shared services: content-free fault codes, restarts, signal errors, battery/temperature/power indicators and monitor quality. Coverage and timing: Use event data and daily aggregates over the selected historical period with configuration-change markers Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative incident taxonomy; asset models/ages; configuration, maintenance and replacement history; room/service dependency map; timetable context Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: trend analysis plus diagnosis. Decision interval: the selected maintenance planning period. Minimum evidence: consistent incident classification, stable asset mapping, known changes and sufficient comparable exposure. Method: compare incident rates by component class and exposure, control shared outages and configuration changes, and report association not cause. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not sign off maintenance, approve a change, patch or replacement, or return equipment to service. Asset owners and competent engineers decide; missing acceptance or handover evidence keeps the answer limited.

WHY THIS IS USEFUL

Targets bench or in-room testing at the most recurrent failure pattern.

AV-064

MAINTENANCE WINDOW

L3 recommendation | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which authorised maintenance window would cause the least teaching disruption while still allowing a complete post-work test?

SENSORS AND TELEMETRY

Proposed evidence: Proposed content-free telemetry: No room or content sensing is required. Proposed integrations may expose owner-issued room/service state and endpoint availability only. Coverage and timing: Use current booking data and, where relevant, a fresh equipment-state check before the proposed window. Use only owner-issued status or content-free technical metadata with retrieved time, permission, provenance and conflict flags Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative timetable and room bookings; room-owner access/closure rules; engineer availability; maintenance duration and dependencies; event and exam restrictions Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus scheduling recommendation. Decision interval: the requested maintenance horizon. Minimum evidence: current bookings/access, realistic work/test duration, required people and approved blackout periods. Method: find feasible windows, include setup/acceptance buffer and rank by teaching disruption and recovery contingency. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not sign off maintenance, approve a change, patch or replacement, or return equipment to service. Asset owners and competent engineers decide; missing acceptance or handover evidence keeps the answer limited.

WHY THIS IS USEFUL

Selects a low-disruption maintenance window with enough time for acceptance testing.

7. Maintenance, spares, upgrades and handover

AV-061 to AV-070 | Plan proportionate lifecycle actions using current asset, teaching and service evidence.

AV-065

REPLACEMENT ACCEPTANCE

L2 comparison | R2 verified integration

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Has the replacement component passed every required acceptance check and asset-record update?

SENSORS AND TELEMETRY

Proposed evidence: the replacement component and complete affected signal/service path: asset ID, firmware/configuration, power/temperature, self-test, signal integrity and endpoint health; no content. Coverage and timing: Use tests recorded after installation and a defined post-installation soak period Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative installation record; approved acceptance checklist; configuration baseline; asset register/warranty; maintenance completion; room-owner status Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: acceptance comparison. Decision interval: after installation and before next teaching use. Minimum evidence: verified replacement identity, completed mandatory tests, updated records and no blocking defect. Method: compare each test and record field with the acceptance criteria; identify passed, failed, missing and conflicting items. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not sign off maintenance, approve a change, patch or replacement, or return equipment to service. Asset owners and competent engineers decide; missing acceptance or handover evidence keeps the answer limited. Recording authority and retention rules must be confirmed independently of technical status.

WHY THIS IS USEFUL

Supports acceptance, further testing or continued quarantine of the replacement.

AV-066

FIRMWARE AND PATCH PLAN

L3 recommendation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which endpoints need an approved firmware or security update, and what low-disruption window is feasible?

SENSORS AND TELEMETRY

Proposed evidence: managed AV endpoints and configuration repository: current firmware/version, health, last reboot, update eligibility and dependency state; no credentials or payloads. Coverage and timing: Use a current inventory snapshot and change events over the selected planning horizon Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative vendor advisory; cybersecurity and AV owner approval; approved baseline; maintenance/change calendar; timetable/booking and fallback requirements Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus recommendation. Decision interval: the patch planning horizon. Minimum evidence: verified endpoint inventory, applicable approved advisory, owner approval state and feasible change window. Method: identify affected endpoints, group compatible changes and propose windows with rollback and acceptance-test time. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not sign off maintenance, approve a change, patch or replacement, or return equipment to service. Asset owners and competent engineers decide; missing acceptance or handover evidence keeps the answer limited.

WHY THIS IS USEFUL

Plans approved updates around teaching and shared-service dependencies.

7. Maintenance, spares, upgrades and handover

AV-061 to AV-070 | Plan proportionate lifecycle actions using current asset, teaching and service evidence.

AV-067

BASELINE DEVIATION

L2 diagnosis | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which rooms show unexplained deviation from the approved AV configuration baseline?

SENSORS AND TELEMETRY

Proposed evidence: room controllers and managed AV endpoints: configuration hashes/versions, endpoint inventory and timestamped change events; no content. Coverage and timing: Use current snapshots compared with the last owner-approved baseline and all intervening change windows Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative configuration baseline; completed/failed change records; asset replacements; maintenance and incident history; room mapping Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: configuration comparison plus diagnosis. Decision interval: the selected audit period. Minimum evidence: stable asset IDs, current signed/hashed state and complete approved change history. Method: classify authorised change, stale baseline, partial deployment, replacement, monitor error and unexplained drift; report evidence gaps. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not sign off maintenance, approve a change, patch or replacement, or return equipment to service. Asset owners and competent engineers decide; missing acceptance or handover evidence keeps the answer limited.

WHY THIS IS USEFUL

Identifies rooms needing configuration reconciliation before faults recur.

AV-068

REPAIR OR REPLACE

L3 recommendation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Does the lifecycle evidence support planned replacement rather than another repair?

SENSORS AND TELEMETRY

Proposed evidence: the named asset and its service dependencies: runtime, fault frequency, error severity, power/temperature stress and monitoring quality over its service life. Coverage and timing: Use comparable monthly exposure-normalised summaries and full-resolution event windows around failures Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative asset age, warranty and replacement cost; repair history/cost; service criticality; approved lifecycle policy; room demand and spare availability Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: lifecycle calculation plus recommendation. Decision interval: the selected budget and maintenance horizon. Minimum evidence: reliable asset exposure/failure data, verified costs, criticality and realistic replacement options. Method: compare expected repair, downtime and replacement scenarios with sensitivity ranges; state non-financial constraints and uncertainty. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not sign off maintenance, approve a change, patch or replacement, or return equipment to service. Asset owners and competent engineers decide; missing acceptance or handover evidence keeps the answer limited.

WHY THIS IS USEFUL

Supports an evidence-based repair-or-replace recommendation to the asset owner.

7. Maintenance, spares, upgrades and handover

AV-061 to AV-070 | Plan proportionate lifecycle actions using current asset, teaching and service evidence.

AV-069

CONTRACTOR HANDOVER

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is the contractor handover complete enough for the support team to assume normal support responsibility?

SENSORS AND TELEMETRY

Proposed evidence: the installed assets and affected service paths: post-work acceptance results, current endpoint health, configuration identifier and monitoring coverage; no content. Coverage and timing: Use owner-approved tests after practical completion and a short operational soak period Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative signed handover; as-built drawings and asset list; configuration/backup records; warranties; training and support contacts; access revocation; outstanding defects Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus handover comparison. Decision interval: before operational responsibility transfers. Minimum evidence: complete handover checklist, verified asset/service map, passed acceptance tests and named ownership/escalation contacts. Method: separate complete, outstanding, inaccessible and conflicting deliverables and show the operational consequence of each gap. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not sign off maintenance, approve a change, patch or replacement, or return equipment to service. Asset owners and competent engineers decide; missing acceptance or handover evidence keeps the answer limited.

WHY THIS IS USEFUL

Determines whether support can accept the service or request missing handover evidence.

AV-070

MAINTENANCE EFFECTIVENESS

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Did the maintenance intervention deliver a sustained improvement under comparable operating conditions?

SENSORS AND TELEMETRY

Proposed evidence: the affected asset and mapped service path: pre/post fault counts, signal errors, restarts, temperature/power state and health uptime; no content. Coverage and timing: Use matched operating windows before and after the work, plus a defined post-work soak period Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative work completion and intervention details; approved baseline; timetable/room exposure; configuration changes; network/platform incidents Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: matched comparison. Decision interval: the defined pre/post evaluation period. Minimum evidence: stable mapping, intervention time, comparable usage windows and controls for other changes/outages. Method: compare exposure-normalised fault and health measures, report effect range and confounders, and distinguish short recovery from sustained change. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not sign off maintenance, approve a change, patch or replacement, or return equipment to service. Asset owners and competent engineers decide; missing acceptance or handover evidence keeps the answer limited.

WHY THIS IS USEFUL

Supports continued monitoring, further diagnosis or owner acceptance.

8. Incidents, cybersecurity, privacy and service performance

AV-071 to AV-080 | Support restricted escalation, recovery and service learning with minimum necessary technical evidence.

AV-071

ABNORMAL ENDPOINT BEHAVIOUR

L2 diagnosis | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Does this managed endpoint show a content-free pattern that warrants restricted cybersecurity or IT investigation?

SENSORS AND TELEMETRY

Proposed evidence: the affected managed endpoint and authorised security-monitoring interface: health, approved configuration drift, connection metadata, restart/error pattern and security indicator flags; no payloads, credentials or media. Coverage and timing: Use synchronized events from an approved baseline period and the active alert window Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative security baseline and escalation criteria; current approved change record; asset owner; maintenance/incident status; restricted response contacts Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: anomaly comparison plus diagnosis. Decision interval: the active alert and escalation decision. Minimum evidence: verified endpoint identity, current baseline, credible multi-source indicators and permission to view them. Method: compare with normal technical behaviour, exclude known change/maintenance explanations and state confidence without attributing intent. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not access credentials, identify people, inspect content, disclose security-sensitive detail or declare a breach. Restricted security, privacy and service owners assess and act; uncertain evidence must be contained and deferred. Show only the minimum detail permitted for the requester.

WHY THIS IS USEFUL

Decides whether to request restricted specialist investigation.

AV-072

UNEXPLAINED CONFIGURATION CHANGE

L2 diagnosis | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is the detected configuration change authorised, a stale record, or a possible incident?

SENSORS AND TELEMETRY

Proposed evidence: the managed endpoint/controller and configuration repository: current hash/version, change timestamp, deployment status and endpoint health; no content. Coverage and timing: Use the current snapshot and the approved change window surrounding the first detected difference Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative approved baseline; change-management record; asset replacement/maintenance history; security owner status; room/service map Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus diagnosis. Decision interval: the detected-change review window. Minimum evidence: stable endpoint identity, current configuration, complete change records and owner permission. Method: match the change to approved work, identify stale baseline or partial deployment, and escalate unexplained differences without attribution. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not access credentials, identify people, inspect content, disclose security-sensitive detail or declare a breach. Restricted security, privacy and service owners assess and act; uncertain evidence must be contained and deferred. Recording authority and retention rules must be confirmed independently of technical status.

WHY THIS IS USEFUL

Separates authorised change from stale records or a potential incident.

8. Incidents, cybersecurity, privacy and service performance

AV-071 to AV-080 | Support restricted escalation, recovery and service learning with minimum necessary technical evidence.

AV-073

EXPIRY RISK

L3 forecast | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which services risk interruption from expiring certificates or owner-managed service credentials?

SENSORS AND TELEMETRY

Proposed evidence: the approved certificate/credential status service and dependent AV endpoints: expiry date, renewal state, health flag and dependency identifier only; no secret, token or credential value. Coverage and timing: Use owner-issued status daily and forecast through the selected teaching horizon Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative certificate/service-account inventory; owner and renewal process; service dependency map; approved change windows; timetable and outage restrictions Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus expiry forecast. Decision interval: the selected teaching/maintenance horizon. Minimum evidence: verified dependency, current expiry/renewal status and owner-confirmed update path. Method: calculate lead time and affected services, group by owner and identify cases where status is missing or permission-restricted. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not access credentials, identify people, inspect content, disclose security-sensitive detail or declare a breach. Restricted security, privacy and service owners assess and act; uncertain evidence must be contained and deferred. Show only the minimum detail permitted for the requester.

WHY THIS IS USEFUL

Prioritises owner action before expiry causes a service interruption.

AV-074

PRIVACY INDICATOR FAILURE

L3 recommendation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Should a faulty privacy indicator keep the affected camera, microphone or capture function unavailable pending a physical check?

SENSORS AND TELEMETRY

Proposed evidence: the mapped privacy-indicator circuit, shutter/control state and associated endpoint: indicator state, device power, shutter state, approved privacy profile and fault code; no audio, video or screen content. Coverage and timing: Use current event state and require a fresh status at the decision time Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative privacy baseline; current session authorisation; equipment owner status; maintenance and privacy incident procedure Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: privacy-state comparison plus recommendation. Decision interval: the immediate pre-use or active-session decision. Minimum evidence: verified endpoint-indicator mapping, current approved state and owner escalation rule. Method: compare expected and observed states; when indicators disagree or are unobservable, recommend withholding the function and physical verification. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not access credentials, identify people, inspect content, disclose security-sensitive detail or declare a breach. Restricted security, privacy and service owners assess and act; uncertain evidence must be contained and deferred. Show only the minimum detail permitted for the requester.

WHY THIS IS USEFUL

Protects privacy by withholding the affected function until physically verified.

8. Incidents, cybersecurity, privacy and service performance

AV-071 to AV-080 | Support restricted escalation, recovery and service learning with minimum necessary technical evidence.

AV-075

MINIMUM INCIDENT DATA

L2 diagnosis | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

What diagnostic data may be retained for this incident while excluding teaching and personal content?

SENSORS AND TELEMETRY

Proposed evidence: the affected managed endpoints and monitoring system: minimal timestamps, asset ID, content-free health/fault codes, configuration identifier, completed safe checks and monitoring-quality flags. Limit collection to the approved incident window and owner-defined retention period. Coverage and timing: Use event-driven state where available and a current health snapshot within the decision window; aggregate only to the level needed for the question Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative incident schema; privacy/security retention policy; asset ownership; access-control list; service-desk routing requirements Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: data-minimisation calculation. Decision interval: the current incident record and retention decision. Minimum evidence: defined diagnostic purpose, target owner requirements, permitted fields and least necessary time window. Method: select the smallest field set that supports reproduction/routing, flag restricted items and remove duplicates or content-bearing data. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not access credentials, identify people, inspect content, disclose security-sensitive detail or declare a breach. Restricted security, privacy and service owners assess and act; uncertain evidence must be contained and deferred.

WHY THIS IS USEFUL

Keeps incident evidence useful while minimising teaching and personal data.

AV-076

OUTAGE SESSION IMPACT

L2 calculation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which scheduled sessions depend on the failed AV service during the current outage?

SENSORS AND TELEMETRY

Proposed evidence: the failed service and mapped room/endpoint dependencies: owner-confirmed service state and dependency health only; no attendance or content. Coverage and timing: Use current outage status and the timetable for the active outage plus the approved planning horizon Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative incident scope; current timetable and room allocation; room AV profiles; platform/network dependency map; official communications Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: impact calculation. Decision interval: the current outage and next owner-defined horizon. Minimum evidence: confirmed failed service, verified dependency map and current scheduled activities. Method: identify technically dependent sessions and uncertainty, separate direct/indirect dependence and provide counts without inferring attendance. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not access credentials, identify people, inspect content, disclose security-sensitive detail or declare a breach. Restricted security, privacy and service owners assess and act; uncertain evidence must be contained and deferred.

WHY THIS IS USEFUL

Shows which sessions need an owner-led continuity response first.

8. Incidents, cybersecurity, privacy and service performance

AV-071 to AV-080 | Support restricted escalation, recovery and service learning with minimum necessary technical evidence.

AV-077

SERVICE RESPONSE TREND

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Are response and restoration times improving for comparable AV incident classes?

SENSORS AND TELEMETRY

Proposed evidence: Proposed content-free telemetry: No room or content sensing is required. Proposed integrations may expose content-free detection/recovery times only, with no ticket narrative, identities or teaching content. Coverage and timing: Aggregate by approved incident class over comparable reporting periods. Use only owner-issued status or content-free technical metadata with retrieved time, permission, provenance and conflict flags Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative service-desk metadata; incident severity/routing rules; service targets; maintenance/change records; outage classifications and exclusions Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: comparison. Decision interval: the selected reporting period against an eligible prior period. Minimum evidence: consistent ticket classes, timestamps, exclusions, comparable severity and known process changes. Method: compare response, assignment and resolution distributions by class and report missingness, censoring and uncertainty. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not access credentials, identify people, inspect content, disclose security-sensitive detail or declare a breach. Restricted security, privacy and service owners assess and act; uncertain evidence must be contained and deferred.

WHY THIS IS USEFUL

Assesses service performance without ranking individual staff.

AV-078

RECURRING INCIDENT PATTERN

L2 diagnosis | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which incident patterns recur by room, asset class, configuration or shared service?

SENSORS AND TELEMETRY

Proposed evidence: mapped rooms, AV assets and shared services: content-free fault/error summaries, restarts, health uptime and monitoring quality; no media or identities. Coverage and timing: Use event data and daily aggregates across the selected historical window, with change/maintenance markers Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative incident taxonomy; asset/room/service mapping; configuration and maintenance history; shared-service topology; timetable exposure context Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: trend analysis plus diagnosis. Decision interval: the selected historical planning period. Minimum evidence: consistent incident classification, stable mapping, known changes and sufficient exposure. Method: group recurrence by asset and dependency, control shared outages/configuration changes and report association with uncertainty. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not access credentials, identify people, inspect content, disclose security-sensitive detail or declare a breach. Restricted security, privacy and service owners assess and act; uncertain evidence must be contained and deferred.

WHY THIS IS USEFUL

Targets systemic improvement at recurring room, asset or service patterns.

8. Incidents, cybersecurity, privacy and service performance

AV-071 to AV-080 | Support restricted escalation, recovery and service learning with minimum necessary technical evidence.

AV-079

RESTRICTED ESCALATION

L3 recommendation | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Is the evidence sufficient to request a restricted security or privacy investigation?

SENSORS AND TELEMETRY

Proposed evidence: the affected managed endpoint and authorised security/privacy monitoring source: approved indicator flags, configuration drift, endpoint health and non-content connection metadata; no payloads, credentials or media. Coverage and timing: Use current multi-source evidence over the active alert and immediate decision window Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative security/privacy escalation criteria; asset ownership; approved baseline; current change/maintenance record; restricted response contacts Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: diagnosis plus recommendation. Decision interval: the active alert and escalation decision. Minimum evidence: credible multi-source indicators, current baseline, permission and consequence-aware escalation criteria. Method: compare evidence with owner-approved thresholds, state confidence and recommend escalation or continued observation without action. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not access credentials, identify people, inspect content, disclose security-sensitive detail or declare a breach. Restricted security, privacy and service owners assess and act; uncertain evidence must be contained and deferred. Show only the minimum detail permitted for the requester.

WHY THIS IS USEFUL

Supports proportionate restricted escalation without declaring a breach.

AV-080

RECOVERY PATH TESTING

L2 comparison | R3 restricted

TEACHING AND AUDIOVISUAL SUPPORT TEAM QUESTION

Which AV services have an owner-approved, recently tested recovery path for power, network or platform loss?

SENSORS AND TELEMETRY

Proposed evidence: owner-managed UPS-backed AV loads, local control, approved alternate endpoints and monitoring service: content-free status and in-date test results for each defined loss scenario; no user or teaching data. Coverage and timing: Use current owner status and the latest approved continuity test within its validity period Quality gate: Evidence is eligible only after commissioned room-to-rack/endpoint/service mapping, clock synchronisation and current health checks. Report data age, cadence or aggregation, uptime, gaps, drift, relocation or maintenance flags and provenance; reject stale, unmapped or unauthorised feeds.

AUTHORITATIVE SUPPORTING DATA

Authoritative sources: Authoritative continuity plan; service-dependency and recovery order; UPS/electrical owner; network/platform fallback; test records; room constraints and emergency rules Precedence: retain the source owner, effective or observed time, retrieval time, permission scope, version/provenance, staleness and conflicts. Current owner-issued status governs its domain and telemetry cannot override it.

ANALYSIS REQUIRED

Operation: authorised lookup plus scenario comparison. Decision interval: the selected outage scenario and recovery horizon. Minimum evidence: current tested continuity plan, mapped dependencies, in-date test evidence and owner-issued status. Method: compare power, network and platform loss scenarios; separate proven from assumed fallback and show restoration dependencies and untested gaps. Uncertainty and safe failure: state eligible coverage, assumptions and conflicts; if a mandatory input is missing, stale, contradictory, unmapped or unauthorised, ask for the smallest clarification or physical check, then defer or return not assessable.

ANSWER BOUNDARY

Do not access credentials, identify people, inspect content, disclose security-sensitive detail or declare a breach. Restricted security, privacy and service owners assess and act; uncertain evidence must be contained and deferred. Telemetry is not electrical safety approval; competent electrical authority remains responsible.

WHY THIS IS USEFUL

Shows which recovery paths are tested and which still need owner-led validation.

4. Implementation summary

The 80 questions define the minimum evidence, integrations, permissions and safe failures needed for responsible teaching and audiovisual support.

QUESTION COVERAGE

Room readiness; approved inventory and compatibility; fault triage; live fallback; hybrid and capture; assistive provision; maintenance and handover; incidents, privacy, cybersecurity and service performance.

SEMANTIC FOUNDATION

Current rooms, racks, endpoints, signal paths, network and platform dependencies, assistive technologies, asset owners, service states, maintenance events and authoritative source links.

PROPOSED TECHNICAL EVIDENCE

Content-free endpoint health, power, thermal, signal-lock, configuration identifier, battery, capture-state, network-quality and monitoring-health evidence with exact asset and service mapping.

AUTHORITATIVE INTEGRATIONS

Timetable and room allocation; AV asset/configuration systems; network/platform status; capture policy/schedule; accessibility provision; maintenance/change; privacy, security, closures, alarms and official communications.

QUALITY AND PROVENANCE

For every source retain owner, version, effective/observed and retrieval times, permission, mapping, cadence, commissioning/calibration, uptime, gaps, drift, maintenance, provenance and conflicts.

ANSWERABILITY STATES

Owner-confirmed or observed; calculated or compared; estimated or forecast; diagnosed; recommended; limited; or not assessable. Missing evidence never becomes a confident readiness or fault claim.

5. Evidence, permissions and answerability rules

These rules apply before any room, endpoint, service, fallback, maintenance or incident answer is returned.

1. OWNER PRECEDENCE

Current room, timetable, AV/IT, network, platform, accessibility, maintenance, privacy, security, alarm and emergency owners override historical records, models and telemetry in their domains.

2. PROPOSED UNTIL VERIFIED

Do not present a sensor, endpoint feed, mapping, model or analysis as current capability until deployment, commissioning, permission, ownership and current health are independently verified.

3. NO CONTENT OR IDENTITY CAPTURE

Never capture or analyse speech, video, screens, recordings, teaching material, credentials, personal-device content, network payloads or identities. Use only minimum content-free technical state.

4. CORRECT ROOM AND SERVICE SCOPE

Room claims require room-level evidence; path claims require mapped racks, ports, endpoints and shared dependencies. Do not substitute corridor, adjacent-room or unrelated evidence.

5. QUALITY BEFORE ANALYSIS

Check clock alignment, sampling/aggregation, commissioning/calibration, uptime, gaps, drift, relocation, maintenance and source agreement. Exclude evidence that cannot support the decision.

6. NAME THE OPERATION HONESTLY

Separate authorised lookup, observation, calculation, estimate, forecast, comparison, diagnosis and recommendation. Association is not root-cause proof and an estimate is not fact.

7. AUTHORITY AND SAFE FAILURE

Never operate equipment, alter configuration, access accounts, grant permission, authorise recording or certify accessibility, privacy or safety. Clarify, qualify, defer or return not assessable when needed.

8. PROPORTIONATE DISCLOSURE

Show only evidence and infrastructure detail the requester is permitted to receive. Withhold credentials, sensitive topology, personal data and teaching information while preserving provenance.