

Specification Hanse 400

 Hull length
 11.99 m | 39'4"

 LWL
 10.80 m | 35'5"

 Beam
 4.04 m | 13'3"

Draft 1.98 m | 6'6" (standard)

1.65 m | 5'5" (option)

Displacement approx. 8.4 t | approx. 18,519 lb

approx. 7.9 t I approx. 17.417 lb (epoxy option)

Ballast approx. 2915 kg l appox. 6,426 lb

Engine 29,5 kW / 40 HP
Fresh water approx. 300 I
Fuel tank approx. 140 I
CE Certificate A (ocean)

Mast length above WL approx. 19.52 m l approx. 64'

Total sail area approx. 105.60 m² l approx. 1,137 sq ft
Main sail approx. 52.20 m² l approx. 562 sq ft
Self-tacking jib approx. 36.20 m² l approx. 390 sq ft

Genoa 140% approx. 53.40 m² | approx. 575 sq ft (option)
Gennaker approx. 120.00 m² | approx. 1,292 sq ft (option)

Rig I 16.50 m I 54′1″

J 4.62 m | 15′2″ P 16.20 m | 53′2″ E 5.57 m | 18′4″

Design judel / vrolijk & co
Interior HanseYachts Design

Germanischer Lloyd by

The production of all HanseYachts is supervised by Germanischer Lloyd according to GL Yacht Plus.

Modellyear 2006/2007 - valid from 01. August 2006



Standard Equipment Hanse 400

1100 Hull

- White hull with blue double waterlines
- Waterline and cove line laid in the gelcoat
- Options for different hull colour according to Hanse colour selection
- GRP sandwich construction hand laid
- Bulkheads laminated to hull and deck
- Waterline and cove line laid in the gelcoat
- GRP strongback
- Option: Hull built with prepreg fibreglass fabrics in epoxy, vacuum bagged with Corecell™ foam, postcured

1200 Deck

- White deck
- Hand laid GRP sandwich construction
- Non-slip deck surface on coach roof

1300 Steering System

- Rod link steering system
- Steering wheel with leather
- Semi-balanced, profiled rudder with alloy shaft and self-aligning needle bearings
- Emergency tiller

1400 Keel

- Performance composite iron / lead keel
- Performance draft: 1.98 m / 6'6"
- Option: Shallow draft 1.65 m / 5'4"
- Stainless steel keel holts

2000 Deck Equipment

- Self-draining anchor-locker with lockable hatch
- Self-draining cockpit with large lockable storage
- 3 opening hatches (forward cabin, aft saloon and saloon)
- 10 opening acrylic glass windows with aluminium frames
- 4 mooring cleats
- 2 self-tailing halyard winches 40 AST
- 2 self-tailing genoa winches 46 AST
- Halvards lead aft to cockpit
- Control lines covered on the coach roof
- 2 winch handles

- Shower on aft deck
- Bow fitting with anchor roller and integrated socket for gennaker pin
- 10 halyard stoppers
- Split pulpit
- Pushpit with ensign staff socket
- Sliding hatch garage
- Sliding hatch
- Drop board
- Double stainless steel safety rail
- Handrails
- Teak on cockpit seats
- Teak on cockpit bottom
- Swimming ladder
- 2 Deck vents

3000 Technical System 3100 Plumbing System / Fresh water

- Fresh water capacity approx. 300 l
- Water infill on deck

Hot water

- Warm water heater, running from engine or immersion heater 110 V / 230 V

Pumps

- Electrical pressurised water system

Faucets

- Faucets in galley and head

3200 Draining pumps

Bilge pumps

- 1 manual bilge pump
- 1 electric bilge pump

Toilet / Head

- Stainless steel holding tank
- Sea and deck discharge
- 1 manual marine toilet

3300 Engine

- Yanmar 3JH4, 29 kW / 40 HP, diesel engine
- Saildrive
- Fresh water cooling
- 2-blade fixed propeller
- Fuel tank stainless steel, approx. 140 l
- Fuel infill on deck
- Seawater strainer

- Fuel filter / Water separator
- Revolution counter
- Engine hour meter
- Engine room sound insulated

3400 Electrics

- 12 V and 110 V / 230 V electrical circuits
- Shore power 230 V incl. differential breaker

Battery charger

- Battery charger 12 V / 20 Amp.

Batteries

- Main battery switch
- 1 Engine battery 12 V / 80 Ah
- 1 Service battery: 12 V / 110 Ah

Electric control panel 12 V

- Onboard electrics
- Outlet 12 V
- Voltmeter
- Water / Fuel gauges

Electric panel 110 V / 230 V

- Differential breaker
- Outlet 110 V / 230 V
- Separate switch for warm water heater

Interior lighting

- in fwd. cabin
- in aft cabin
- in saloon
- in galley
- in head - in storage room
- in engine room

Navigation lights

- Steaming light
- Bow light
- Stern light - Anchor light

Navigation instruments

- Illuminated compass
- Depth sounder
- Log

3500 Galley

- Solid surface stone grey
- Double stainless steel sinks
- 2-burner LPG gas stove with oven, gimbled
- Gas system and self draining LPG bottle

storage in cockpit

- Lockers and drawers
- Extra large 12v fridge of approx. 130 l, top and front loader with light
- Trash can

4000 Interior Accommodation

- High quality marine plywood, mahogany veneer, satin varnish
- Option: light cherry style, satin varnish
- White bulkheads
- Wooden door frames
- Wood / Sandwich doors

Upholstery

- According to Hanse colour selection

Forward cabin

- Separated from saloon by a door
- Large double-berth
- Combined locker
- Shelves above berth
- (Option: diagonal berth)
- (Option: 2nd head)
- Options according to Hanse Individual Cabin Concept

Aft cabin

- Separated from saloon by a door
- Large double berth
- Combined locker - Shelf
- Option: 2nd aft cabin with double berth and locker

Saloon

- Companionway steps
- U-shaped settee area on starboard
- Saloon table
- Bar locker
- Lockers and shelves
- Curtain rails

Navigation area

- 2 single seats on port side
- Option: long bench
- Chart table with storage between single seats
- Electric switch panel

Head / Shower

- Large head with separate shower stall
- Marine toilet
- Holding tank
- Sea and deck discharge
- Sink
- Electrical drain pump
- Mirror
- Locker & shelves
- Opening hatch
- 1 opening portlight

5000 Rig and Sails - 9/10-ria

- 2 spreader anodised aluminium mast and boom
- Furling system for iib
- Hanse single line reefing system (cockpit handling)
- Rod kicker
- Backstav adjuster
- Main and iib halvard lead aft to cockpit
- Main and jib sheets - Main sheet traveller on coach roof
- Main sail fully battened with 2 reefs - Maindrop system with Lazy Jacks:
- colour: light-grey - Self-tacking iib with traveller
- Boom topping lift

All measurements are approximate. Specification and material can be changed without notice. 400/A/GB/010806

HanseYachts AG

Tel: +49 (0)3834/5792-0 | Fax: +49 (0)3834/5792-81

Postfach 31 65 | D-17461 Greifswald | Salinenstr. 22 | D-17489 Greifswald zentrale@hanseyachts.com | www.hanseyachts.com

- Stainless steel standing rigging