

DEFAULT CREDENTIALS CHEAT-SHEET — PORT/SERVICE WISE

FTP • SMTP • DNS • HTTP/HTTPS • POP3/IMAP • MySQL

Pichli PDF mein diye gaye ports (21, 25, 53, 80, 110, 143, 443, 587, 993, 995, 3306) ki har service ke liye common default/weak usernames aur passwords ki list yahan hai — jo real-world misconfigured servers aur CTF/lab boxes mein sabse zyada milte hain. Login/bruteforce karte waqt ye combos sabse pehle try karo.

DISCLAIMER: Ye list sirf authorized labs, CTFs (TryHackMe/HTB) aur written-permission wale pentests ke liye hai. Bina permission real system par try karna illegal hai.

Author: Sujal | Companion sheet to Web & Network Pentest Methodology PDF

Anonymous Login (sabse pehle ye try karo)

```
Username: anonymous
Password: (blank) OR anonymous@ OR any-email@anything.com
Username: ftp
Password: ftp
```

Common Default / Weak Creds (FTP daemons & devices)

Software/Device	Username	Password
vsftpd (misconfig)	anonymous	(blank)
ProFTPD default	admin	admin
Generic FTP server	ftp	ftp
Generic FTP server	test	test
Generic FTP server	root	root
Generic FTP server	admin	password
Router/IoT FTP	admin	1234
Router/IoT FTP	admin	(blank)
Backup/NAS FTP	backup	backup
Legacy Unix FTP	guest	guest

TIP: FTP par sabse pehle 'anonymous' try karo — CTF boxes mein ye bahut common misconfig hai (jaise HTB 'Lame', 'Blue').

SMTP mein zyada tar 'default creds' nahi hote — yahan focus **user enumeration (VRFY/EXPN)** aur phir un valid usernames par common passwords try karne par hota hai.

Common Default Usernames (VRFY/EXPN se confirm karo)

Common Usernames	Common Passwords (try after enum)	Notes
root	root / toor	Almost every Linux box
admin	admin / password	Generic default
postmaster	postmaster	Standard mail alias
mail	mail	Generic mail service acct
test	test / test123	Common test account
user	user / 123456	Generic account
info	info123	Business mail account
support	support123	Business mail account

Default Creds for Mail Server Software

```
hMailServer (Windows) -> Administrator / (set during install, often blank/admin)
Postfix/Sendmail (Linux) -> no default creds; relies on system users (/etc/passwd)
Exim -> no default creds; system users
Zimbra -> admin / zimbra (common lab default)
```

TIP: VRFY se username confirm hote hi wahi username FTP/SSH/web login par bhi try karo — password reuse बहुत common hai.

DNS server (BIND/PowerDNS) khud login-based nahi hota — yahan 'default creds' ka matlab hai DNS management panel ya zone-transfer misconfig.

Software	Username	Password
BIND (rndc key)	N/A	default rndc.key often world-readable
PowerDNS Admin panel	admin	admin
Webmin DNS module	root	(system root password)
Pi-hole Admin	admin	(set at install, default often blank)
Technicolor/ISP router DNS	admin	admin

```
# Zone transfer misconfig check (no creds needed if allowed)
dig axfr @ns1.target.com target.com
```

TIP: DNS par 'creds' se zyada important hai zone-transfer aur DNSSEC misconfig — wahi info leak karte hain.

Web par default creds sabse zyada admin panels, CMS aur management interfaces mein milte hain.

Application/Panel	Username	Password
WordPress (fresh install)	admin	admin / (set at install)
phpMyAdmin	root	(blank) / root
Tomcat Manager	tomcat	tomcat / s3cret
Tomcat Manager (older)	admin	admin
Jenkins	admin	admin / (set at install)
Apache Struts demo	admin	admin123
Router admin panel	admin	admin / password / 1234
Webmin	root	(system root password)
Grafana	admin	admin
Django admin (debug)	admin	admin
JBoss/Wildfly console	admin	admin
ElasticSearch/Kibana (no-auth default)	admin	often no auth at all

Quick Recon Commands

```
whatweb target.com # tech stack identify
gobuster dir -u http://target -w common.txt -x php,txt
# phpMyAdmin / admin panel path guess
curl -s http://target/phpmyadmin/ -o /dev/null -w '%{http_code}\n'
```

TIP: Tech stack pehchan-te hi uska naam 'default credentials' ke sath Google karo — har CMS/panel ki apni known default list hoti hai.

POP3/IMAP mostly system-level mail users use karte hain (jo OS ke /etc/passwd users hote hain), isliye 'default creds' generic weak combos hote hain, khaaskar test/demo mail servers mein.

Mail Server Software	Username	Password
Dovecot (test/demo setup)	test	test / test123
Generic Linux mail user	user	user / password123
Courier-IMAP default	postmaster	postmaster
hMailServer default	administrator	(set at install)
Zimbra webmail	admin@domain	zimbra
cPanel mail account (lab)	info@domain	info123
Generic weak account	mail	mail123

```
# Manual login test (POP3)
nc -nv target.com 110
USER test
PASS test123
# Manual login test (IMAP over SSL)
openssl s_client -connect target.com:993
a LOGIN test test123
```

TIP: Web app se FTP/SMTP enum karke jo bhi username-password mile, wahi POP3/IMAP par bhi try karo — mail box mein aksar aur creds/hints milte hain.

Most Common Defaults

Scenario	Username	Password
Fresh MySQL install (old versions)	root	(blank)
XAMPP default	root	(blank)
WAMP default	root	(blank)
MySQL generic weak	root	root
MySQL generic weak	root	toor
MySQL generic weak	root	password
MySQL generic weak	root	mysql
phpMyAdmin default	admin	admin
MariaDB (Debian pkg, old)	debian-sys-maint	(random, in /etc/mysql/debian.cnf)
Test/demo app DB user	app	app123

Quick Login Test Commands

```
mysql -h target.com -u root # empty password try
mysql -h target.com -u root -p # then try common passwords
hydra -l root -P rockyou.txt mysql://target.com
```

TIP: MySQL par root ka blank password ek bahut classic CTF/lab misconfig hai — sabse pehle wahi try karo.

ALL

Master 'Try-First' List

Sabhi services ke liye universal common combos

Agar kisi bhi service ka exact default pata nahi, ye universal list sabse pehle try karo — ye combos duniya bhar ke misconfigured systems mein sabse zyada milte hain (SecLists/CIRT jaisi public default-password databases ke hisaab se).

Top Universal Username:Password Combos

```
admin:admin
admin:password
admin:(blank)
admin:1234
admin:12345
root:root
root:toor
root:(blank)
root:password
test:test
guest:guest
user:user
administrator:administrator
administrator:password
```

Port	Service	First Combo To Try
21	FTP	anonymous : (blank)
25/587	SMTP	VRFY enum first, then root:root
53	DNS	admin:admin (panel) / try zone-transfer
80/443	HTTP/HTTPS	admin:admin (check tech-specific list)
110/995	POP3/POP3S	test:test
143/993	IMAP/IMAPS	test:test
3306	MySQL	root:(blank)

Bruteforce Karne Ke Liye Tools (jab default kaam na kare)

- **Hydra** — sabse popular multi-protocol brute forcer (ftp, ssh, mysql, smtp, pop3, imap sab support)
- **Medusa** — Hydra jaisa hi, parallel bruteforce ke liye fast
- **SecLists** (GitHub: danielmiessler/SecLists) — Passwords/Default-Credentials/ folder mein full lists hain
- **CIRT.net** — online default password database (device/software se search karo)

```
# Hydra generic syntax
hydra -L users.txt -P passwords.txt <service>://target.com
# Example - FTP
hydra -L users.txt -P rockyou.txt ftp://target.com
# Example - MySQL
hydra -l root -P rockyou.txt mysql://target.com
```

REMINDER: Ye poori list sirf apne authorized labs (TryHackMe/HTB) aur written-permission wale pentests ke liye hai.