

LOCATION+FUEL+SERVICE HISTORY+ALERTS PUSH & PULL API DOCUMENT

Volvo Eicher Commercial Vehicles Ltd.

PUSH AND PULL API

ABSTRACT

API Documentation for Remote Vehicle Management Services for External Parties. The document contains technical details for: Location API (Push and Pull), Fuel API (Push and Pull), Service History API (Pull) and Alerts API (Push and Pull).

VECV IT

Ver 1

Contents

1. PUSH API Technical Details 2

1.1. LOCATION API 2

- Parameter for Location API 2
- JSON REQUEST 3

1.2. Fuel API 3

- Parameter for Fuel API 3
- JSON REQUEST for Fuel API – 4

1.3. Alerts API 5

- Parameter for Alert API 5
- JSON Response For Alert API 6

2. PULL API Technical Details 7

2.1. Overview 7

2.2. Abbreviations 7

2.3. Definitions 7

2.4. General remarks 8

2.5. Communication technology 8

2.6. HTTP headers 8

2.7. Security 8

2.8. API Details 8

- AUTH API for Live Data 8

2.9. Location API 9

2.10. Fuel API 12

2.11. Service History API 15

2.12. Alert API 18

HTTP Response Codes 21

1. PUSH API Technical Details

1.1. LOCATION API

The document contains the API specifications for the Location API (Push API). The API endpoint needs to be set up by the user, and data will be sent from My Eicher to that endpoint. The endpoint must be accessible to our application, if the endpoint has restricted access, please ensure that access is allowed for My Eicher.
Also ensure that the parameters are named the same as mentioned in this document and your endpoint can accept the response below.

- Parameter for Location API

Name	Type	Default	Description
chassisNo	String	MC2CXXXXXXXX34	Chassis Number
deviceId	String	null	Device Id of the Vehicle
vehicleStatus	String	null	This is status of vehicle like STOPPED, MOVING, IDLING
latitude	integer (int64)	0	Latitude of Vehicle
longitude	integer (int64)	0	Longitude of Vehicle
odometer	Float	0	Total distance travelled in kms
regNo	String	null	Vehicle Regn Number
lastUpdated	Long	null	YYYYDDMMHHMMSS Date and time format
epochTime	Long	0	Time in Epoch format
vehicleSpeed	Float	0	Vehicle Moving Speed
vehicleDirection	Double	0	Vehicle Direction

- JSON REQUEST

Note: This response should be accepted by your API endpoint.


```
{
       "locationData": [
     {
        "regNo": "RJ11GC5990",
        "chassisNo": "MC2CAAAC0PX095311",
        "latitude": 22.42,
        "longitude": 75.61,
        "vehicleStatus": "MOVING",
        "lastUpdated": 20250213111843,
        "epochTime": 1739425723,
        "vehicleSpeed": 52.68,
        "odometer": 189944.0,
        "deviceId": "349207067821139"
     }
  ],
  "errorMessage": "None"
}
```


1.2. Fuel API

The document contains the API specifications for the Fuel API (Push API). The API endpoint needs to be set up by the user, and data will be sent from My Eicher to that endpoint. The endpoint must be accessible to our application, if the endpoint has restricted access, please ensure that access is allowed for My Eicher.
Also ensure that the parameters are named the same as mentioned in this document and your endpoint can accept the response below.

- Parameter for Fuel API

Name	Type	Default	Description
chassisNo	String	MC2CXXXXXXXX34	Chassis Number
deviceId	String	null	Device Id of the Vehicle
vehicleStatus	String	null	This is status of vehicle like STOPPED, MOVING, IDLING
fuelType	String	null	Fuel Type Diesel, EV, CNG
latitude	integer (int64)	0	Latitude of Vehicle

longitude	integer (int64)	0	Longitude of Vehicle
odometer	Float	0	Total distance travelled in kms
engineOperatingHours	Float	0	Total engine operating hours
regNo	String	null	Vehicle Regn Number
lastUpdated	Long	null	YYYYDDMMHHMMSS Date and time format
fuelLevelInPer	double	0	Fuel level in Percentage
fuelLevelInLtr	double	0	Fuel level in Liters/For CNG in Kg
epochTime	Long	null	Time in epoch format.
socLevel	double	null	Battery percentage (Applicable for EV)
batteryTemperature	double	null	Temperature of battery. (Applicable for EV)
co2Saving	double	null	Total co2 saving done by vehicle. (Applicable for EV)
vehicleSpeed	Float	0	Vehicle Moving Speed

- JSON REQUEST for Fuel API –

Note: This response should be accepted by your API endpoint

- **JSON Response for Fuel API (Diesel and CNG)**


```
{
  "fuelData": [
    {
      "regNo": "RJ11GC5999",
      "chassisNo": "MC2CAMRC0PG095555",
      "latitude": 22.33,
      "longitude": 75.5,
      "fuelType": "Diesel",
      "vehicleStatus": "MOVING",
      "lastUpdated": 20250213114043,
      "epochTime": 1739427043,
      "vehicleSpeed": 47.55,
```

```
        "odometer": 189964.0,
        "fuelLevelInPer": 24.4,
        "fuelLevelInLtr": 97.07,
        "engineOperatingHours": 4691.0
    }
        ],
 "errorMessage": "None"
}
```


- **JSON RESPONSE FOR FUEL API (EV)**


```
{
  "fuelData": [
    {
      "regNo": "CH01TB4044",
      "chassisNo": "MC2V2HRT0NH212222",
      "latitude": 30.72,
      "longitude": 76.76,
      "fuelType": "EV",
      "vehicleStatus": "MOVING",
      "lastUpdated": 20240927142928,
      "epochTime": 1727427568,
      "vehicleSpeed": 10.02,
      "odometer": 138379.0,
      "socLevel": 74.0,
      "batteryTemperature": 9.0,
      "co2Saving": 9367.2
    }
        ],
 "errorMessage": "None"
}
```


1.3.Alerts API

The document contains the API specifications for the Alerts API (Push API). The API endpoint needs to be set up by the user, and data will be sent from My Eicher to that endpoint. The endpoint must be accessible to our application, if the endpoint has restricted access, please ensure that access is allowed for My Eicher.
Also ensure that the parameters are named the same as mentioned in this document and your endpoint can accept the response below.

- Parameter for Alert API

Name	Type	Default	Description
chassisNo	String	MC2CXXXXXXXX34	Chassis Number
alertTypeId	String	Null	Show the type of alert type

alertSubTypeId	String	Null	The subtype ID of the alert
alertSubType	String	Null	The subtype name of Alert
alertValue	Double	0	The value if any of the alert created.
alertUnit	String	Null	Unit of the alert value.
latitude	integer (int64)	0	Latitude of Vehicle
longitude	integer (int64)	0	Longitude of Vehicle
alertTime	String	Null	"2024-09-20 16:42:40",
faultName	String	Null	Name of the Fault.
caseDescription	String	Null	Description of the fault.
solutionRecommended	String	Null	Solution recommended to resolve the Fault.
regNo	String	Null	Vehicle Regn Number

- JSON Response For Alert API


```
[
  {
    "chassisNo": "MC2BKERC0NJ083162",
    "alertTypeId": "DRIVING_BEHAVIOUR",
    "alertSubTypeId": "OVER_SPEEDING",
    "alertSubType": "Over Speeding",
    "alertValue": 59.0,
    "alertUnit": "Km",
    "lat": "21.82487",
    "lng": "75.18454",
    "alertTime": "2024-09-20 16:42:40",
    "regNo": "RJ14GP3568"
  },
  {
    "chassisNo": "MC2BKERC0NJ083162",
    "alertTypeId": "DRIVING_BEHAVIOUR",
    "alertSubTypeId": "OVER_SPEEDING",
    "alertSubType": "Over Speeding",
    "alertValue": 58.0,
    "alertUnit": "Km",
    "lat": "21.80598",
    "lng": "75.17442",
    "alertTime": "2024-09-20 16:45:40",
    "regNo": "RJ14GP3568"
  }
]
```

2. PULL API Technical Details

2.1. Overview

With VECV Remote Fleet Management Systems (rFMS) external parties such as Partner (Fleet owners, Developers, Research Institutions, System Integrators, Aggregators etc.) will be able to consume Vehicle related information vis Rest APIs. This document intends to describe the technical details of the APIs and how to use them. How is VECV making the Vehicle information via APIs however is out of scope.

The document contains the Pull API technical details on how to generate token using API key and pull the data for the following APIs:

1. **Location API**
2. **Fuel API**
3. **Service History API**
4. **Alerts API**

2.2. Abbreviations

Abbreviation	Description
OEM	Original Equipment Manufacturer
API	Application Programming Interface
REST	Representational State Transfer
HTTPS	Hypertext Transfer Protocol Secure
XSD	XML Schema Definition
XML	Extensible Markup Language
JSON	JavaScript Object Notation
VIN	Vehicle Identification Number
rFMS	Remote Fleet Management System

This external data access API I used to share telematics data to 3rd party. This document describes the details of the API.

2.3. Definitions

Term	Description
Mandatory	The API shall provide the mandatory parameters, provided that the vehicle is configured with the parameter
Optional	It is up to each Partner to decide if they want to implement this information or not in the API.

2.4.General remarks

- This document is valid for all the API services.
- Parameters/attributes not supported by the vehicle will not be part of the response.
- Parameters/attributes currently unavailable or invalid will not be part of the response.
- Updates of data might not be possible during special conditions, e.g. communication not possible with device/backend servers etc.
- Any latency on account of device will also be visible in the timestamp returned as a part of the response.
- The timestamps in the responses are in ***yyyymmddhhmmss*** format in IST time zone and always formatted as a string, regardless of if it is an XML or JSON response.

2.5.Communication technology

- The External Data Access API is a HTTPS based REST API.

2.6. HTTP headers

There are a few mandatory HTTP headers for the External Data Access API.

- Authorization
- Accept

2.7. Security

Security and Authentication is implemented in the header where partner(s) will have to embed the API-KEY in every call.

e.g.

API-KEY: *F6vP3pP3bW0xM3qE1eW0bT6vO3xM4aC4qG3aK1oH 9iB6lF7gR4*

2.8. API Details

The below mentioned section details out the list of APIs currently available to be consumed by third party (s).

- ### AUTH API for Live Data

  Before invoking the API, you must first call this API to obtain the authentication token. This token must then be included in the request to the API in order to successfully retrieve the data. Failure to include the token will result in an Unauthorized Response from the API.

- API –

http://partnerapi.vecv.net/service-gateway/secure/genrateToken

- **HTTP Method: GET**

- **REQUEST HEADERS –**
  API-KEY – API-KEY provided by VECV.

- **Response**

  Response received from this API will be like:


```
    {
        "status": true,
        "clientId": "08a1f851-5ece-42",
        "token":
"7TOwJGy66FQXwI9k6MZu+lj6ecJCLWI/yl/PzUWScIne4YgxroMuUHtVmsgAy81ppojf33uwDYUUFo
4hb9/HqXM+JQY3Fs+EbGNnOuRC4mifJ/hfbL4qUv+dKeURhvfjThG14bimIIpAMddjdzUmIBGSugWKz
bJ0oZEqn7moCKMX+chFzWABlj1iGLF7HopQvl5HjrHlJIIFHXlFILnP23AIjSutBMkDHYwazPsptyGz
uvJZEHk1+vWKItdWn3gE2wwbOv9LBv3TV4VMBykBom1IJvF2asFRuPHnunSLSNmW2n0T9+gVzHOsC5M
aZvALBeKJMGd+wcHIY4N0ckmm7d3GWxF90cI7ecjfmkzW0nc5yb5bLkl++ruc3lKYSHsq0hD7acM5wO
PiHNKYCFxEijwyjMuZXt7p2a6xPt7K99hXNXwVOKFzwMgzlceMLZ5yZ/FNNy6Rvn3FLGusyruhtUdY9
6a7fDYBJrNg6sofJb5v3yoKpPNUl9ZLUpGUKMpM5D5a4ifqi02BmPHwOiXG6hQ5AQxbUhBuMOMhTGoI
pGuY4N5/4WPYH42+kyoLas6wWjiIQLKfYbdzpgZCfxFtvPmz4ggzSl/7vxQR7nR+64UqrF8IKyUq4tL
NxSvCRQwLBOxR7l77ceijyfbIzn/B5qTehgu3V8s7ZU8TmECnJCKJ1MI1z/jod7lWb7yeu4eE7ARnvB
DAJaVoOBxoouy78llgt/ZtOJp4spXZ5iNxF+chnFfo6PNJRpOHExJPFUPHU5oz5RogKoWdUlA6vpef6
r7lqZwLTE68",
        "expTime": "2024-09-28T05:32:57.084+00:00",
        "errorMessage": "None"
    }
```


Token can be used in authorization as Bearer Token for each API call.

2.9. Location API

This API serves to retrieve up-to-date vehicle parameters such as location and odometer reading. Requests can be made in three different ways: by providing your client ID to retrieve details for all chassis associated with that client ID, or by submitting a list of registration numbers and chassis numbers in the request body to fetch the relevant data.

If no data is found for a particular vehicle, the API will return an object containing default and null values.

- API – https://partnerapi.vecv.net/service-gateway/vehicle/v1/getlivedata/location
- HTTP Method: POST
- AUTHORIZATION –

  Bearer Token – Token that will be get from AUTH API Provided By VECV

- REQUEST HEADERS –

  API-KEY – API-KEY provided by VECV.

- Rate Limiter –

  This API is rate limited as per the API-KEY configuration done by VECV.

- **Request Parameters**

Name	Type	Default	Description
clientId	String	Optional	Client Id of the user provided from VECV
regNo	List <String> (list of string)	Optional	Registration Number of Vehicle.
chassisNo	List <String> (list of string)	Optional	Chassis Number of Vehicle

  - If Client Id is passed it will return the data for all the vehicles registered with that client.
  - If Chassis Number or RegNo is passed the response will be for those listed vehicle.

- **Parameter limitations**

  a. It is mandatory to add the header (X-IBM-Client-Id) as you client id provided from VECV.

  b. Only 1 request per minute is made if you try to make more request will return an status code 409.

  c. If none of these parameters are set, a HTTP XXX error will be returned indicating that the parameters supplied are invalid.

- **Response**
  Below is an example of API returning a record for a given chassis - MC2CASRF0PD090409.
  Response will be same if you hit with client Id or Reg No.


```
{
    "locationData": [
        {
            "regNo": "RJ11GC5999",
            "chassisNo": "CC2CCCCC0PG099321",
            "latitude": 22.42,
            "longitude": 75.61,
            "vehicleStatus": "MOVING",
            "lastUpdated": 20250213111843,
            "epochTime": 1739425723,
            "vehicleSpeed": 52.68,
            "odometer": 189944.0,
            "vehicleDirection": 232.1,
            "deviceId": "359207067888239"
        }
    ],
    "errorMessage": "None"
}
```


- Parameter Description

Name	Type	Default	Description
chassisNo	String	MC2CXXXXXXXX34	Chassis Number
deviceId	String	null	Device Id of the Vehicle
vehicleStatus	String	null	This is status of vehicle like STOPPED,MOVING,IDLING
latitude	integer (int64)	0	Latitude of Vehicle
longitude	integer (int64)	0	Longitude of Vehicle
odometer	Float	0	Total distance travelled in kms
regNo	String	null	Vehicle Regn Number
lastUpdated	Long	null	YYYYDDMMHHMMSS Date and time format
epochTime	Long	0	Time in Epoch format
vehicleSpeed	Float	0	Vehicle Moving Speed
vehicleDirection	Double	0	Vehicle Direction

2.10. Fuel API

This API serves to retrieve up-to-date vehicle parameters such as location, odometer reading, and fuel consumption. Requests can be made in three different manners: by providing your client ID to retrieve details for all chassis associated with that client ID, or by submitting a list of registration numbers and chassis numbers in the request body to fetch the relevant data.

If no data is found for a particular vehicle, the API will return an object containing default and null values. For diesel vehicles, the total fuel consumed represents the value of fuel in liters, while for CNG vehicles, it denotes the total CNG consumed.

- **API –**

https://partnerapi.vecv.net/service-gateway/vehicle/v1/getlivedata/fuelData

- **HTTP Method**: POST
- AUTHORIZATION –

  Bearer Token – Token that will be get from AUTH API Provided By VECV

- REQUEST HEADERS –

  API-KEY– API-KEY provided by VECV.

- Rate Limiter –
  This API is rate limited as 1 Request per Minute.

- Request Parameters

Name	Type	Default	Description
clientId	String	Optional	Client Id of the user provided from VECV
regNo	List <String> (list of string)	Optional	Registration Number of Vehicle.
chassisNo	List <String> (list of string)	Optional	Chassis Number of Vehicle

- If Client Id is passed it will return the data for all the vehicles registered with that client.
- If Chassis Number or RegNo will be passed the response will be for those listed vehicle.

❖ Parameter limitations

- It is mandatory to add the header (X-IBM-Client-Id) as you client id provided from VECV.
- Only 1 request per minutes is made if you try to make more request will return an status code 409.
- If none of these parameters are set, a HTTP XXX error will be returned indicating that the parameters supplied are invalid.

❖ Response

Note: This response should be accepted by the customer API.

- **JSON Response for DIESEL and CNG**


```
{
    "fuelData": [
        {
            "regNo": "RJ11GC5999",
            "chassisNo": "MC2CAWWC0PG095331",
            "latitude": 22.33,
            "longitude": 75.5,
            "fuelType": "Diesel",
            "vehicleStatus": "MOVING",
            "lastUpdated": 20250213114043,
            "epochTime": 1739427043,
            "vehicleSpeed": 47.55,
            "odometer": 189964.0,
            "fuelLevelInPer": 24.4,
            "fuelLevelInLtr": 97.07,
            "defLevelInLtr": 17.85,
            "lifeTimeFuelConsumtion": "33807.0",
            "engineOperatingHours": 4691.0
        }
       ],
 "errorMessage": "None"
}
```

- JSON RESPONSE FOR EV –


```
{
    "fuelData": [
        {
            "regNo": "CH01TB6111",
            "chassisNo": "MC2V2HRT0NG211111",
            "latitude": 33.74,
            "longitude": 76.79,
            "fuelType": "EV",
            "vehicleStatus": "STOPPED",
            "lastUpdated": 20250213121119,
            "epochTime": 1739429069,
            "vehicleSpeed": 0.0,
            "odometer": 160982.0,
            "socLevel": 58.0,
            "batteryTemperature": 2.0,
            "co2Saving": 10897.31
        }
       ],
 "errorMessage": "None"
}
```


❖ Parameter Description

Name	Type	Default	Description
chassisNo	String	MC2CXXXXXXXX34	Chassis Number
deviceId	String	null	Device Id of the Vehicle
vehicleStatus	String	null	This is status of vehicle like STOPPED,MOVING,IDLING
fuelType	String	null	Fuel Type Diesel,Ev,CNG
latitude	integer (int64)	0	Latitude of Vehicle
longitude	integer (int64)	0	Longitude of Vehicle
odometer	Float	0	Total distance travelled in kms
engineOperatingHours	Float	0	Total engine operating hours
regNo	String	null	Vehicle Regn Number
lastUpdated	Long	null	YYYYDDMMHHMMSS Date and time format

fuelLevelInPer	double	0	Fuel level in Percentage
lifeTimeFuelConsumtion	String	null	Life Time fuel Consumed by Vehicle.
fuelLevelInLtr	double	0	Fuel level in Liters/For CNG in Kg
defLevelInLtr	double	null	Def Level in Lites
epochTime	Long	null	Time in epoch format.
socLevel	double	null	Battery percentage(Applicable for EV)
batteryTemperature	double	null	Temperature of battery.(Applicable for EV)
co2Saving	double	null	Total co2 saving done by vehicle. (Applicable for EV)
vehicleSpeed	Float	0	Vehicle Moving Speed

2.11. Service History API

This API serves to retrieve the service history of vehicles. Requests can be made as per request format given below in the document.

If no service history is found for a particular vehicle, the API will return an object containing default and null values. The service history includes details such as the date of job card opening, invoice, amount and for other details refer to parameter's description table.

i. API -

https://partnerapi.vecv.net/service-gateway/datalake/serviceHistory/getServiceHistory

ii. HTTP Method: POST

iii. AUTHORIZATION –

Bearer Token – Token will be provided from AUTH API Provided By VECV

iv. REQUEST HEADERS –

API-KEY – API-KEY provided by VECV.

v. Rate Limiter –

As per the API-Key configurations.

vi. Service History API Request Parameters

Name	Type	Default	Description
startDate	String	Optional	Start date from which data to be provided.
endDate	List <String> (list of string)	Optional	End Date till which data to be provided.
chassisNo	List <String> (list of string)	Optional	Chassis Number of Vehicle

vii. Request Format for Service History API –

```
{
  "chassisNo": [
    "MC2FCHRT0MD491374"
  ],
  "startDate": "2024-09-19 00:00:00",
  "endDate": "2024-09-20 23:59:59"
}
```

viii. Parameter limitations

a. It is mandatory to add the header (API-KEY) as you API-KEY provided from VECV.
b. If none of these parameters are set, a **HTTP XXX** error will be returned indicating that the parameters supplied are invalid.

❖ Response: Service History

Below is an example of API returning a record for a given chassis MC2C5HRC0KF444477.


```
{
  "serviceHistory": [
    {
      "jobCardNumber": "4005508588",
      "dealerName": "Asha Motor Sales and Service",
      "lubeTranValue": 2498.0,
      "labourTranValue": 1292.0,
      "partsValueAmount": 153.0,
      "totalCostCust": "0",
      "modelDescription": "Pro1095XP H CBC 20FT BS4NG NGB PRM",
      "odometer": "351166",
      "invoiceNumber": "3004773104",
```

```
    "ordertypedescription": "Running Repair",
    "registrationNo": "KA51AE1806",
    "vehicleChassisNo": "MC2C5HRC0KF444477",
    "jobCardOpenDate": "2023-08-22T00:00:00.000+00:00",
    "jobCardLineItems": [

      {
        "rowId": "a7e2188e-d8db-44eb-ad84-dc17f638a4fa",
        "jobDescription": "PMS -ENGINE OIL & FILTERS CHANGE",
        "jobIdDescription": "",
        "action": "ENGINE OIL & FILTERS CHANGE DONE UNDER SA",
        "matnr": "ID301999",
        "matnrType": "Spare Parts",
        "observation": "ENGINE OIL & FILTERS CHANGE",
        "jobTypeBezei": "AMC",
        "partQty": 1.0,
        "partTotalAmt": 152.54,
        "partTotalAmtInGst": 180.0
      }
    ]
}
```


❖ Service History Parameters and their description

Name	Type	Default	Description
jobCardNumber	String	NULL or “”	Job Card Number
dealerName	String	NULL or “”	Name of dealer
lubeTranValue	Double	0	Transaction value of Lubes used
labourTranValue	Double	0	Transaction value of Labour.
partsValueAmount	Double	0	Transaction value of parts
totalCostCust	String	NULL or “”	Total cost to customer
modelDescription	String	NULL or “”	Description of model
odometer	String	NULL or “”	Distance travelled by vehicle
invoiceNumber	Double	0	Invoice Number
ordertypedescription	String	NULL or “”	Order description
registrationNo	String	NULL or “”	Reg No of Vehicle
vehicleChassisNo	String	NULL or “”	Chassis Number of Vehicle
jobCardOpenDate	String	NULL or “”	Job Card open date
jobCardLineItems	Array of JobCarLineItems	NULL	Number of parts of Jobs in an JobCard
rowId	String	NULL or “”	Unique Id

jobDescription	String	NULL or “”	Job Description
jobIdDescription	String	NULL or “”	Job Id Description
action	String	NULL or “”	Action done
matnr	String	NULL or “”	Part Number
matnrType	String	NULL or “”	Part Type
observation	String	NULL or “”	Observations of Job
jobTypeBezei	String	NULL or “”	
partQty	Double	0	Quantity of Parts
partTotalAmt	Double	0	Part Amount
partTotalAmtInGst	Double	0	Part Amount with GST

2.12. Alert API

This API allows users to retrieve alerts related to their vehicles. Requests can be made as per request format given below in the document.

If no alerts are found for a particular vehicle, the API will return an object containing default and null values. Alerts can include various types of alerts that user sets in the My Alert page in My Eicher.

Note: To receive alerts for a vehicle, users must first configure the alerts on the “My Alerts” page in the My Eicher portal. Users can also set threshold values for the alerts they want to receive; if no thresholds are set, the API will use default values to generate alerts.

❖ API -

https://partnerapi.vecv.net//service-gateway/alertLog/getGetAlertLogs

HTTP Method: POST

AUTHORIZATION –

Bearer Token – Token that will be get from AUTH API Provided By VECV

REQUEST HEADERS –

API-KEY – API-KEY provided by VECV.

Rate Limiter –

As per the API-Key configurations.

❖ Request Parameters

Name	Type	Default	Description
chassisNo	List <String> (list of string)	Optional	Chassis No. of the vehicle.
eventStartDate	String	Optional	Event Start Date
eventEndDate	String	Optional	Event End Date

- Request –

```
{
   "chassisNo": [
      " MC2BFSRC0PA087978"
   ],
   "eventStartDate": "2024-09-30 00:00:00",
   "eventEndDate": "2024-10-01 23:59:59"
}
```

- Parameter limitations
  - It is mandatory to add the header (API-KEY) as you API-KEY provided from VECV.
  - If none of these parameters are set, a HTTP XXX error will be returned indicating that the parameters supplied are invalid.

- Response

Below is an example of API returning a record for a given chassis - **MC2BKERC0PK105111.**


```
{
    "alertLog": [
        {
            "customerId": "12187777",
            "chassisNo": "MC2BKERC0PK105111",
            "regNo": "MH46CL4111",
            "alertType": "Predictive Uptime",
            "alertSubTypeId": "VISIT_SOON",
            "alertSubType": "Visit Soon",
            "alertValue": "0.0",
            "alertUnit": "Na",
            "alertTime": "2025-02-07T14:46:49",
            "lat": "22.42699",
            "lng": "69.91315"
            "caseId": "DPT2412233243111",
            "faultName": "Fuel Pressure Relief Valve  Stuck",
```

```
            "caseDescription": "Fuel Pressure Relief Valve Struck closed or
Over Pressure condition Activated",
            "solutionRecommended": "<span style=\"font-family: 'trebuchet ms',
geneva, sans-serif;\">Please Visit Eicher Authorized workshop.</span>",
            "odometer": "26411.78"
        }
    ],
    "errorMessage": "NONE"
}
```


❖ Parameters and their description

Name	Type	Default	Description
chassisNo	String	MC2CXXXXXXXX34	Chassis Number
alertTypeId	String	Null	Show the type of alert type
alertSubTypeId	String	Null	The subtype ID of the alert
alertSubType	String	Null	The subtype name of Alert
alertValue	Double	0	The value if any of the alert created.
alertUnit	String	Null	Unit of the alert value.
latitude	integer (int64)	0	Latitude of Vehicle
longitude	integer (int64)	0	Longitude of Vehicle
alertTime	String	Null	"2024-09-20 16:42:40",
faultName	String	Null	Name of the Fault.
caseDescription	String	Null	Desrciption of the fault
solutionRecommended	String	Null	Solution recommended to resolve the Fault.
regNo	String	Null	Vehicle Regn Number

HTTP Response Codes

"100 CONTINUE",
"101 SWITCHING_PROTOCOLS",
"102 PROCESSING",
"103 CHECKPOINT",
"200 OK",
"201 CREATED",
"202 ACCEPTED",
"203 NON_AUTHORITATIVE_INFORMATION",
"204 NO_CONTENT",
"205 RESET_CONTENT",
"206 PARTIAL_CONTENT",
"207 MULTI_STATUS",
"208 ALREADY_REPORTED",
"226 IM_USED",
"300 MULTIPLE_CHOICES",
"301 MOVED_PERMANENTLY",
"302 FOUND",
"302 MOVED_TEMPORARILY",
"303 SEE_OTHER",
"304 NOT_MODIFIED",
"305 USE_PROXY",
"307 TEMPORARY_REDIRECT",
"308 PERMANENT_REDIRECT",
"400 BAD_REQUEST",
"401 UNAUTHORIZED",
"402 PAYMENT_REQUIRED",
"403 FORBIDDEN",
"404 NOT_FOUND",
"405 METHOD_NOT_ALLOWED",
"406 NOT_ACCEPTABLE",
"407 PROXY_AUTHENTICATION_REQUIRED",
"408 REQUEST_TIMEOUT",
"409 CONFLICT",
"410 GONE",
"411 LENGTH_REQUIRED",
"412 PRECONDITION_FAILED",
"413 PAYLOAD_TOO_LARGE",
"413 REQUEST_ENTITY_TOO_LARGE",
"414 URI_TOO_LONG",
"414 REQUEST_URI_TOO_LONG",
"415 UNSUPPORTED_MEDIA_TYPE",
"416 REQUESTED_RANGE_NOT_SATISFIABLE",
"417 EXPECTATION_FAILED",
"418 I_AM_A_TEAPOT",
"419 INSUFFICIENT_SPACE_ON_RESOURCE",
"420 METHOD_FAILURE",
"421 DESTINATION_LOCKED",
"422 UNPROCESSABLE_ENTITY",
"423 LOCKED",
"424 FAILED_DEPENDENCY",
"425 TOO_EARLY",

```
"426 UPGRADE_REQUIRED",
"428 PRECONDITION_REQUIRED",
"429 TOO_MANY_REQUESTS",
"431 REQUEST_HEADER_FIELDS_TOO_LARGE",
"451 UNAVAILABLE_FOR_LEGAL_REASONS",
"500 INTERNAL_SERVER_ERROR",
"501 NOT_IMPLEMENTED",
"502 BAD_GATEWAY",
"503 SERVICE_UNAVAILABLE",
"504 GATEWAY_TIMEOUT",
"505 HTTP_VERSION_NOT_SUPPORTED",
"506 VARIANT_ALSO_NEGOTIATES",
"507 INSUFFICIENT_STORAGE",
"508 LOOP_DETECTED",
"509 BANDWIDTH_LIMIT_EXCEEDED",
"510 NOT_EXTENDED",
"511 NETWORK_AUTHENTICATION_REQUIRED"
```