

EXPERIMENT – 6

AIM: To develop a stored procedure `transfer_employee(emp_id, new_dept_id)` with input validation and exception handling, and to create triggers for salary checks and audit logging, testing both with normal and boundary-case inputs.

SOURCE CODE:

USING EXPERIMENT – 3 DATABASE

SQL QUERIES:

STORED PROCEDURE: `transfer_employee`

The procedure will:

1. Check whether the employee exists.
2. Check whether the new department exists.
3. Check whether the employee is already in that department.
4. Transfer the employee.
5. Handle errors using `SQLEXCEPTION`.
6. Roll back the transaction if an error occurs.

`DELIMITER //`

```
CREATE PROCEDURE transfer_employee(  
    IN p_emp_id INT,  
    IN p_new_dept_id INT  
)  
BEGIN  
    DECLARE v_employee_count INT DEFAULT 0;  
    DECLARE v_department_count INT DEFAULT 0;  
    DECLARE v_current_dept INT DEFAULT 0;  
  
    -- Error handler  
    DECLARE EXIT HANDLER FOR SQLEXCEPTION  
    BEGIN  
        ROLLBACK;  
        SELECT 'Error occurred. Transaction rolled back.' AS  
message;  
        END;  
  
    START TRANSACTION;
```

```

-- Check whether employee exists
SELECT COUNT(*)
INTO v_employee_count
FROM Employee
WHERE emp_id = p_emp_id;

IF v_employee_count = 0 THEN
    ROLLBACK;
    SELECT 'Error: Employee does not exist.' AS message;

ELSE

    -- Check whether department exists
    SELECT COUNT(*)
    INTO v_department_count
    FROM Department
    WHERE dept_id = p_new_dept_id;

    IF v_department_count = 0 THEN
        ROLLBACK;
        SELECT 'Error: Department does not exist.' AS
message;

    ELSE

        -- Get current department
        SELECT dept_id
        INTO v_current_dept
        FROM Employee
        WHERE emp_id = p_emp_id;

        -- Check if already in requested department
        IF v_current_dept = p_new_dept_id THEN
            ROLLBACK;
            SELECT 'Error: Employee is already in this
department.'
                AS message;

        ELSE

            -- Transfer employee
            UPDATE Employee
            SET dept_id = p_new_dept_id
            WHERE emp_id = p_emp_id;

            COMMIT;

            SELECT
                'Employee transferred successfully.'
                AS message;

```

```

        END IF;

    END IF;

END IF;

END //

DELIMITER ;

```

TESTING THE STORED PROCEDURE

```

SELECT
    e.emp_id,
    e.emp_name,
    d.dept_name
FROM Employee e
JOIN Department d
    ON e.dept_id = d.dept_id
WHERE e.emp_id = 101;

```

OUTPUT:



The screenshot shows the MySQL IDE interface. The 'EXPLORER' panel on the left lists tables: demo, department, department_salary_summary, employee, employee_basic, and employee_hierarchy. The 'Query 1' tab is active, displaying the SQL query: `SELECT e.emp_id, e.emp_name, d.dept_name FROM Employee e JOIN Department d ON e.dept_id = d.dept_id WHERE e.emp_id = 101;`. The results are shown in a table with three columns: emp_id, emp_name, and dept_name. The data row shows emp_id 101, emp_name Aarav Sharma, and dept_name IT.

emp_id	emp_name	dept_name
101	Aarav Sharma	IT

```
CALL transfer_employee(101, 3);
```

OUTPUT:



The screenshot shows the MySQL IDE interface. The 'Query 1' tab is active, displaying the SQL query: `CALL transfer_employee(101, 3);`. The results are shown in a table with one column: message. The data row shows the message: 'Employee transferred successfully.'

message
Employee transferred successfully.

```

SELECT
    e.emp_id,
    e.emp_name,
    d.dept_name
FROM Employee e
JOIN Department d
    ON e.dept_id = d.dept_id
WHERE e.emp_id = 101;

```

OUTPUT:




The screenshot shows the MySQL IDE interface. The 'EXPLORER' panel on the left lists tables: demo, department, department_salary_summary, and employee. The 'Query 1' tab is active, displaying the SQL query. The results pane shows a single row of data.

emp_id	emp_name	dept_name
101	Aarav Sharma	Finance

EDGE CASE – EMPLOYEE DOES NOT EXIST

```
CALL transfer_employee(999, 3);
```

OUTPUT:



The screenshot shows the MySQL IDE interface. The 'Query 1' tab is active, displaying the SQL query. The results pane shows an error message.

message
Error: Employee does not exist.

EDGE CASE – DEPARTMENT DOES NOT EXIST

```
CALL transfer_employee(101, 99);
```

OUTPUT:



The screenshot shows the MySQL IDE interface. The 'Query 1' tab is active, displaying the SQL query. The results pane shows an error message.

message
Error: Department does not exist.

EDGE CASE – SAME DEPARTMENT

```
CALL transfer_employee(101, 3);
```

OUTPUT:



SALARY VALIDATION TRIGGER

Let, salary must be ≥ 16000

```
DELIMITER //
```

```
CREATE TRIGGER validate_employee_salary
BEFORE INSERT ON Employee
FOR EACH ROW
BEGIN
    IF NEW.salary < 16000 THEN
        SIGNAL SQLSTATE '45000'
        SET MESSAGE_TEXT = 'Salary must be at least 16000'
    ;
END IF;
```

```
END //
```

```
DELIMITER ;
```

TEST SALARY VALIDATION

```
INSERT INTO Employee
(emp_id, emp_name, gender, salary, hire_date, dept_id)
VALUES
VALUES
(131, 'Demo Employee', 'M', 12000, '2026-09-25', 1);
```


OUTPUT:



TEST VALID SALARY

```
INSERT INTO Employee
(emp_id, emp_name, gender, salary, hire_date, dept_id)
VALUES
VALUES
(131, 'Demo Employee', 'M', 32000, '2026-09-25', 1);
SELECT
    emp_id,
    emp_name,
    salary
FROM Employee
WHERE emp_id = 131;
```

OUTPUT:



The screenshot shows a MySQL IDE window titled 'MySQL - db_454577wwy'. On the left is an 'EXPLORER' pane with a search bar and a list of tables: 'demo', 'department', 'department_salary_summary', and 'employee'. The 'demo' table is selected. The main area displays 'Query 1' with the following SQL code:

```
6 SELECT
7     emp_id,
8     emp_name,
9     salary
10 FROM Employee
11 WHERE emp_id = 131;
```

Below the query, a result table is shown with three columns: 'emp_id', 'emp_name', and 'salary'. The first row contains the values 131, Test Employee, and 30000.00.

emp_id	emp_name	salary
131	Test Employee	30000.00

SALARY VALIDATION FOR UPDATE

```
DELIMITER //
```


```
CREATE TRIGGER validate_employee_salary_update
BEFORE UPDATE ON Employee
FOR EACH ROW
BEGIN
    IF NEW.salary < 16000 THEN
        SIGNAL SQLSTATE '45000'
        SET MESSAGE_TEXT = 'Salary must be at least 16000' ;
    END IF;
END //
```

```
DELIMITER ;
```

TEST INVALID SALARY UPDATE

```
UPDATE Employee
SET salary = 5000
WHERE emp_id = 131;
```

OUTPUT:




The screenshot shows the MySQL Workbench interface. The 'EXPLORER' pane on the left lists the database 'demo' and its tables: 'department', 'department_salary_summary', and 'employee'. The 'Query 1' pane contains the following SQL statement:

```
1 UPDATE Employee
2 SET salary = 5000
3 WHERE emp_id = 131;
4
```

The status bar at the bottom displays the error message: "Error: Salary must be at least 15000".

```
SELECT emp_id, emp_name, salary
FROM Employee
WHERE emp_id = 131;
```

OUTPUT:



The screenshot shows the MySQL Workbench interface. The 'Query 1' pane contains the following SQL statement:

```
1 SELECT emp_id, emp_name, salary
2 FROM Employee
3 WHERE emp_id = 131;
4
```

The results pane displays the following data:

emp_id	emp_name	salary
131	Test Employee	30000.00

CREATE AUDIT TABLE

```
CREATE TABLE Salary_Audit (
    audit_id INT AUTO_INCREMENT PRIMARY KEY,
    emp_id INT,
    old_salary DECIMAL(10,2),
    new_salary DECIMAL(10,2),
    changed_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
    action VARCHAR(30)
);
```

AUDIT LOGGING TRIGGER

```
DELIMITER //
```

```
CREATE TRIGGER salary_audit_trigger
AFTER UPDATE ON Employee
FOR EACH ROW
BEGIN
```

```

IF OLD.salary <> NEW.salary THEN

    INSERT INTO Salary_Audit
    (
        emp_id,
        old_salary,
        new_salary,
        action
    )
VALUES
    (
        NEW.emp_id,
        OLD.salary,
        NEW.salary,
        'SALARY UPDATED'
    );

END IF;

END //

DELIMITER ;

```

TEST AUDIT TRIGGER

```

UPDATE Employee
SET salary = 36000
WHERE emp_id = 131;


```

```

SELECT *
FROM Salary_Audit;

```

OUTPUT:



The screenshot shows the MySQL Workbench interface. On the left, the 'EXPLORER' pane displays a database named 'demo' with tables 'department', 'department_salary_summary', and 'employee'. The main query editor shows a query that selects all data from the 'Salary_Audit' table. Below the editor, the 'Query Results' pane displays a single row of data from the 'Salary_Audit' table.

audit_id	emp_id	old_salary	new_salary	changed_at	action
1	131	30000.00	35000.00	2026-09-24T21:46:41.000Z	SALARY UPDATED


TEST MULTIPLE SALARY CHANGES

```
UPDATE Employee
SET salary = 41000
WHERE emp_id = 131;
```

```
UPDATE Employee
SET salary = 46000
WHERE emp_id = 131;
```

```
SELECT
    audit_id,
    emp_id,
    old_salary,
    new_salary,
    action
FROM Salary_Audit
WHERE emp_id = 131;
```

OUTPUT:



audit_id	emp_id	old_salary	new_salary	action
1	131	30000.00	35000.00	SALARY UPDATED
2	131	35000.00	40000.00	SALARY UPDATED
3	131	40000.00	45000.00	SALARY UPDATED

TEST EDGE CASE – SALARY UNCHANGED

```
UPDATE Employee
SET salary = 46000
WHERE emp_id = 131;
```

No new audit record is created

TEST EDGE CASE – NULL SALARY

```
DROP TRIGGER validate_employee_salary;

DELIMITER //

CREATE TRIGGER validate_employee_salary
BEFORE INSERT ON Employee
FOR EACH ROW
BEGIN
```

```

        IF NEW.salary IS NULL OR NEW.salary < 16000          THEN
            SIGNAL SQLSTATE '45000'
            SET MESSAGE_TEXT =
            'Salary cannot be NULL and must be at least 15000';
        END IF;

END //

DELIMITER ;

INSERT INTO Employee
(emp_id, emp_name, gender, salary, hire_date, dept_id)
VALUES
(132, 'Null Salary', 'F', NULL, '2026-09-25', 1);

```

OUTPUT:



CHECK ALL TRIGGERS

```
SHOW TRIGGERS;
```

OUTPUT:

The screenshot shows the MySQL IDE interface. The main query editor shows the command 'SHOW TRIGGERS;'. The output is displayed in a table format with columns: Trigger, Event, Table, and Statement.

Trigger	Event	Table	Statement
validate_employee_salary	INSERT	employee	BEGIN IF NEW.salary IS NULL OR NEW.salary < 15000 THEN SIGNAL SQLSTATE '45000' SET MESSAGE_TEXT = 'Salary cannot be NULL and must be at
validate_employee_salary_update	UPDATE	employee	BEGIN IF NEW.salary < 15000 THEN SIGNAL SQLSTATE '45000' SET MESSAGE_TEXT = 'Salary must be at least 15000'; END IF; END
salary_audit_trigger	UPDATE	employee	BEGIN IF OLD.salary <> NEW.salary THEN INSERT INTO Salary_Audit (emp_id, old_salary, new_salary, action) VALUES (NEW.emp_id, OLD.salary, NEW

CHECK STORED PROCEDURE

```
SHOW PROCEDURE STATUS
WHERE Db = 'db_454577wwy';
```

OUTPUT:

MySQL - db_454577wwy

Query 1Query 2Query 3

1 SHOW PROCEDURE STATUS
2 WHERE Db = 'db_454577wwy';
3

EXPLORER

Search...

TABLES

demo
department
department_salary_summary
employee

Db	Name	Type	Language	Definer	Modified	Created	Security_type	Comment	character_set_client	collati
db_454577wwy	transfer_employee	PROCEDURE	SQL	user_454577wwy@%	2026-09-24T21:39:54.000Z	2026-09-24T21:39:54.000Z	DEFINER		utf8mb4	utf8mi