AIM:-

Consider a disk queue with requests for I/O to blocks on cylinders 98, 183, 41, 122, 14, 124, 65, 67. The SSTF scheduling algorithm is used. The head is initially at cylinder number 53. The cylinders are numbered from 0 to 199. Write a Program to calculate the total head movement (in number of cylinders) incurred while servicing these requests.

CODE:-

```
GNU nano 8.7                                                    SSTFAlgo.c
#include <stdio.h>
#include <stdlib.h>

int main() {
    int requests[] = {98, 183, 41, 122, 14, 124, 65, 67};
    int n = 8;
    int head = 53;
    int total = 0;

    int visited[8] = {0};

    printf("Seek Sequence: %d", head);

    for (int i = 0; i < n; i++) {
        int min = 9999;
        int index = -1;

        for (int j = 0; j < n; j++) {
            if (visited[j] == 0) {
                int diff = abs(head - requests[j]);

                // ☑ Tie-breaking condition added
                if (diff < min || (diff == min && requests[j] > head)) {
                    min = diff;
                    index = j;
                }
            }
        }

        visited[index] = 1;
        total += abs(head - requests[index]);
        head = requests[index];

        printf(" -> %d", head);
    }

    printf("\nTotal Head Movement = %d\n", total);

    return 0;
}
^G Help        ^O Write Out   ^F Where Is    ^K Cut         ^T Execute     ^C L
^X Exit        ^R Read File   ^\ Replace     ^U Paste       ^J Justify     ^/ G
```

OUTPUT:-

```
Admin@DESKTOP-PNDN9B0 MSYS ~
$ nano practical10_sstf.c

Admin@DESKTOP-PNDN9B0 MSYS ~
$ gcc practical10_sstf.c -o sstf
./sstf
Order of servicing:
41 -> 65 -> 67 -> 98 -> 122 -> 124 -> 183 -> 14 ->

Total Head Movement = 323

Admin@DESKTOP-PNDN9B0 MSYS ~
$ |
```